GNNINTERPRETER: A PROBABILISTIC GENERATIVE MODEL-LEVEL EXPLANATION FOR GRAPH NEURAL NETWORKS

ABSTRACT

Recently, Graph Neural Networks (GNNs) have significantly advanced the performance of machine learning tasks on graphs. However, this technological breakthrough makes people wonder: how does a GNN make such decisions, and can we trust its prediction with high confidence? When it comes to some critical fields, such as biomedicine, where making wrong decisions can have severe consequences, it is crucial to interpret the inner working mechanisms of GNNs before applying them. In this paper, we propose a model-agnostic model-level explanation method for different GNNs that follow the message passing scheme, GNNInterpreter, to explain the high-level decision-making process of the GNN model. More specifically, GNNInterpreter learns a probabilistic generative graph distribution that produces the most discriminative graph pattern the GNN tries to detect when making a certain prediction by optimizing a novel objective function specifically designed for the model-level explanation for GNNs. Compared with the existing work, GNNInterpreter is more computationally efficient and more flexible in generating explanation graphs with different types of node features and edge features, without introducing another blackbox to explain the GNN and without requiring manually specified domain-specific knowledge. Additionally, the experimental studies conducted on four different datasets demonstrate that the explanation graph generated by GNNInterpreter can match the desired graph pattern when the model is ideal and reveal potential model pitfalls if there exist any.

1 INTRODUCTION

Graphs are widely used to model data in many applications such as chemistry, social science, transportation, etc. Since a graph is an unique non-Euclidean data structure, modeling graph data remained a challenging task until Graph Neural Networks (GNNs) emerged (Defferrard et al., 2016; Hamilton et al., 2017; Cao et al., 2016; Yu et al., 2018). As a powerful tool for representation learning on graph data, GNN achieved state-of-the-art performance on various different machine learning tasks on graphs. As the popularity of GNNs rapidly increases, people begin to wonder why one should trust this model and how the model makes decisions. However, the complexity of GNNs prevents humans from interpreting the underlying mechanism in the model. The lack of self-explainability becomes a serious obstacle for applying GNNs to real-world problems, especially those when making wrong decisions may incur an unaffordable cost.

Explaining deep learning models on text or image data (Simonyan et al., 2014; Selvaraju et al., 2019; Zhang et al., 2017; Binder et al., 2016) has been well-studied. However, the explainability of deep learning models on graphs is still less explored. Compared with explaining deep learning models on text or image data, explaining deep graph models is a more challenging task for several reasons (Yuan et al., 2020b): (i) the adjacency matrix representing the topological information has only discrete values, which cannot be directly optimized via gradient-based methods (Duval & Malliaros, 2021), (ii) in some application domains, a graph is valid only if it satisfies a set of domain-specific graph rules, so that generating a valid explanation graph to depicts the underlying decision-making process of GNNs is an nontrivial task, and (iii) graph data structure is heterogeneous in nature with different types of node features and edge features, which makes developing a one-size-fits-all explanation method for GNNs to be even more challenging.

In recent years, explaining GNNs has aroused great interest and thus many research works have been conducted. The existing works can be classified into two categories: instance-level explanations (Luo et al., 2020; Ying et al., 2019; Vu & Thai, 2020) and model-level explanations (Yuan et al., 2020a). Instance-level explanation methods attempt to interpret the model prediction for a given graph instance, whereas model-level explanation methods aim at understanding the general behavior of the model not specific to any particular graph instance. However, if the ultimate goal is to examine the model reliability, instance-level methods are very time-consuming because one will need to examine many instances one by one to draw a rigorous conclusion about the model reliability. Conversely, the model-level explanation method can directly explain the high-level decision-making rule inside the blackbox (GNN) for a target prediction, which is much less time-consuming and more informative about the general decision-making process of the model. Besides, it has been shown that any instance-level explanation method would fail to provide faithful explanation for a GNN that suffers from the bias attribution issue (Faber et al., 2021), while model-level explanation method can not only provide faithful explanation for this case but also diagnose the bias attribution issue.

Even though the model-level explanation methods for GNNs have such advantages, they are much less explored than the instance-level explanation methods . In this paper, we propose a probabilistic generative model-level explanation method for GNNs, GNNInterpreter, which learns a generative explanation graph distribution that represents the most discriminative features the GNN tries to detect when making a certain prediction. Precisely, the explanation graph distribution are learned by optimizing a novel objective function specifically designed for model-level explanation of GNNs such that the generated explanation is both faithful and valid regarding the domain-specific knowledge. More importantly, GNNInterpreter is a general approach to generating explanation graphs with different types of node features and edge features for explaining different GNNs which follows the message passing scheme. We quantitatively and qualitatively evaluated the efficiency and effectiveness of GNNInterpreter on four different datasets including synthetic datasets and public real-world dataset. The experimental results show that GNNInterpreter can precisely find the ideal topological structure for the target prediction if the explained model is ideal, and reveal the potential pitfalls in the model decision-making process if there is any. By identifying these potential model pitfalls, people can be mindful when applying this model to unseen graphs with a specific misleading pattern, which is especially important for some field in which making wrong decisions may incur an unaffordable cost.

Compared with the current state-of-the-art model-level explanation method for GNNs, for example XGNN (Yuan et al., 2020a), the quantitative and qualitative evaluation result shows that the explanation graphs generated by GNNInterpreter is more representative regarding the target class than the explanations generated by XGNN. Additionally, GNNInterpreter has the following advantages compared with XGNN:

- GNNInterpreter is a more general approach that can generate explanation graphs with different types of node features and edge features, whereas XGNN cannot generate graphs with continuous node features or any type of edge features.

- By taking advantage of the special design of our objective function, GNNInterpreter is more flexible in explaining different GNN models without the need of having domain-specific knowledge for the specific task, whereas XGNN requires domain-specific knowledge to manually design the reward function for the reinforcement learning agent.

- GNNInterpreter is more computationally efficient. For example, GNNInterpreter only takes less than a minute to explain one class in a GNN model, which is about 10 times faster than training a deep reinforcement learning agent as in XGNN.

- GNNInterpreter is a numerical optimization approach without introducing another blackbox to explain GNNs, unlike XGNN which trains a deep learning model to explain GNNs.

2 RELATED WORK

Graph Neural Network. Unlike images and texts, modeling graph data is very challenging due to the unique characteristics of graphs. Tons of research has been conducted to extend the previously existing deep learning algorithms to graph data, which gives rise to the emergence of GNNs. GNNs have achieved remarkable success in different machine learning tasks including graph classification

(Lee et al., 2018), node classification (Xu et al., 2019), and link prediction (Zhang & Chen, 2018). There exists a variety of GNN models (Kipf & Welling, 2017; Gilmer et al., 2017; Veličković et al., 2018), but they often share a common idea of message passing as described in section 3 with different time complexity (Wu et al., 2020).

Instance-Level Explanation of GNN. Encouraged by the success of explaining deep neural networks on image or text data, the first instance-level explanation method of GNNs (Pope et al., 2019) emerged in 2019. Since then, a multitude of instance-level explanation methods of GNNs has been proposed in the past few years. According to a recent survey (Yuan et al., 2020b), these instance-level explanation methods can be classified into four categories: gradient-based methods (Baldassarre & Azizpour, 2019), perturbation-based methods (Ying et al., 2019), decomposition methods (Schwarzenberg et al., 2019), and surrogate methods (Vu & Thai, 2020; Huang et al., 2020). These four categories all attempt to explain how a GNN model makes such a prediction for a specific input instance. However, if the ultimate goal is to validate whether this model is trustworthy, it is very time-consuming to manually check the instance-level explanation for many graph instances one by one before we can make any rigorous conclusion about the model reliability. Besides, all of them will fail to provide faithful explanation for a GNN model suffering from the bias attribution issue because the ground truth explanation edges for one of classes in this case will be an empty set (Faber et al., 2021).

Model-Level Explanation Method of GNN. Unlike instance-level explanation methods, model-level explanation methods aim to explain the general behavior of a model without respect to any specific input. The current state-of-the-art model-level explanation method for GNNs is called XGNN (Yuan et al., 2020a). Similar to the most of model-level explanation methods for other deep learning model (Simonyan et al., 2014; Nguyen et al., 2015), XGNN and GNNInterpreter share a common goal of generating explanation graphs to maximize the likelihood of the target prediction being made by the GNN model. However, XGNN adopts a completely different approach. To be more concrete, given a target class c, XGNN trains a deep graph generator f_c, which generates graphs by adding one edge at a step, in a reinforcement learning setting. After training is done, f_c is able to construct input graphs that attempts to maximize the score of class c in a pre-defined number of steps. Besides, it incorporates hand-crafted graph rules into the reward function so that f_c can consider these rules when providing explanations. However, specifying these graph rules requires domain-specific knowledge about the task. XGNN also has a limitation that it can only generate explanation graphs with a single categorical node feature or no node feature. In other words, it cannot generate explanation graphs with any types of edge features or continuous node features. Unlike XGNN, GNNInterpreter is a much more general approach that can generate explanation graphs with different types of node features and edge features without requiring domain-specific knowledge. Additionally, GNNInterpreter is more computationally efficient, because for each class to be explained, XGNN trains a reinforcement learning model, while GNNInterpreter directly optimizes a generative distribution.

3 BACKGROUND

Notations. A graph is represented as $G = (\mathbf{V}, \mathbf{E})$, where $\mathbf{V}$ and $\mathbf{E}$ are the sets of nodes and edges. Besides, the number of edges and nodes are denoted as M and N respectively. The topological information of a graph is described by an adjacency matrix $\mathbf{A} \in \{0, 1\}^{N \times N}$ where $a_{ij} = 1$ if there exists an edge between node i and node j, and $a_{ij} = 0$ otherwise. In addition, the node feature matrix $\mathbf{X} \in \mathbb{R}^{N \times k_V}$ and edge feature matrix $\mathbf{Z} \in \mathbb{R}^{M \times k_E}$ represent the features for N nodes and M edges.

Graph Neural Networks. In general, the high-level idea of GNN is message passing. For each layer, it aggregates information from neighboring nodes to learn the representation of each node. For hidden layer i, the message passing operation can be written as

$$\begin{cases} \mathbf{H}^0 &= \mathbf{X}, \\ \mathbf{H}^i &= f(\mathbf{H}^{i-1}, \mathbf{A}, \mathbf{Z}), \end{cases} \tag{1}$$

where $\mathbf{H}^i \in \mathbb{R}^{N \times F^i}$ is the hidden node representation output from i^{th} layer and F^i is the output feature dimension. The propagation rule f can be decomposed into three components: computing the messages according to the node embedding at the previous layer $\mathbf{H}^{i-1}$, aggregating the messages from neighboring nodes, and updating the hidden representation $\mathbf{H}^i$ for each node based upon the aggregated message. It is worth mentioning that GNNInterpreter can explain different GNNs that follow this message passing scheme.

4 GNNINTERPRETER

In this paper, we propose a model-level explanation method, GNNInterpreter, which is capable of disclosing the high-level decision-making process of the model for the purpose of examining model reliability. GNNInterpreter is a numerical optimization approach that is model-agnostic for explaining different GNNs as long as it follows the message passing scheme. Besides, it can generate explanation graphs with different types of edge features and node features. Specifically, we design a novel objective function for generating model-level explanation for GNNs, so that optimizing this objective function will result in both faithful and valid explanation graphs. That is to say, the generated explanation not only captures the discriminative features the GNN tries to detect when making a certain prediction, but also is a valid graph satisfying the domain-specific graph rules. Due to the discreteness nature of graph data, we learn a generative explanation graph distribution by adopting the Gumbel-Softmax trick (Maddison et al., 2016).

4.1 LEARNING OBJECTIVE

To reveal the high-level decision-making process of the model, one effective approach is to construct a explanation graph that can trigger a specific response from the model as much as possible. Similar to most of the model-level explanation methods for other deep learning models (Simonyan et al., 2014; Nguyen et al., 2015), the explanation for GNNs can be obtained by maximizing the likelihood of the explanation graph G being predicted as a target class by the GNN model. However, solely maximizing the likelihood without constraints may not necessarily result in meaningful explanations. This is because a local maxima in the objective landscape may lie outside of the training data distribution. The explanation yielded from this type of maxima are mathematically legitimate but may provide no meaningful insights on how the model actually reasons over the true data distribution. Especially when there exists domain-specific knowledge that restricts the validity of the data, the explanations are expected to stay inside the hard boundary of the true data distribution. XGNN (Yuan et al., 2020a) addresses this problem by manually specifying a set of graph rules and evaluating the validity of explanation graphs according to the specified rules as a part of the reward function for the reinforcement learning agent. The essential goal is to confine the distribution of the explanation graphs to the domain-specific boundary. Nevertheless, manually specifying rules not only is tedious and time-consuming, but also requires domain expertise which is not always available. Moreover, in many cases, the rules over data distribution can not even be programmatically specified. Therefore, we propose to leverage the abstract knowledge learned by the GNN itself to prevent the explanation from deviating from the true data distribution. This can be achieved by maximizing the similarity between the explanation graph embedding and the average embedding of all graphs from the target class in the training set. Thus, we mathematically formulate our learning objective as follows,

$$\max_{G} L(G) = \max_{\mathbf{A}, \mathbf{Z}, \mathbf{X}} L(\mathbf{A}, \mathbf{Z}, \mathbf{X}) = \max_{\mathbf{A}, \mathbf{Z}, \mathbf{X}} \phi_c(\mathbf{A}, \mathbf{Z}, \mathbf{X}) + \mu \mathrm{sim}_{\cos}(\psi(\mathbf{A}, \mathbf{Z}, \mathbf{X}), \bar{\psi}_c) \quad (2)$$

where L is the objective function; ϕ_c is the scoring function before Softmax corresponding to the class of interest c, predicted by the explained GNN; ψ is the graph embedding function of the explained GNN; $\bar{\psi}_c$ is the average graph embedding for all graphs belonging to class c in the training set; $\mathrm{sim}_{\cos}$ denotes the cosine similarity; and μ is a hyper-parameter representing the weight factor.

Given the learning objective defined above, one possible approach to obtain the explanation graph is that we can adopt the gradient ascent to iteratively update the explanation graph G toward maximizing the learning objective. However, this approach cannot be directly applied here because the discrete adjacency matrix $\mathbf{A}$ encoding the graph topology is non-differentiable, namely $\nabla_{\mathbf{A}} L(\mathbf{A}, \mathbf{Z}, \mathbf{X})$ does not exist. Therefore, in order to adopt the gradient ascent method, $\mathbf{A}$ needs to be relaxed to a continuous variable. In addition, if the training graphs of the GNN model have discrete edge features or discrete node features, then $\mathbf{Z}$ and $\mathbf{X}$ are also required to be relaxed to the continuous domain such that $\nabla_{\mathbf{Z}} L(\mathbf{A}, \mathbf{Z}, \mathbf{X})$ and $\nabla_{\mathbf{X}} L(\mathbf{A}, \mathbf{Z}, \mathbf{X})$ exist. Given that the continuous edge features and continuous node features do not require any special accommodation to adopt the gradient ascent, we will only discuss how to learn a continuously relaxed explanation graph with discrete edge features and discrete node features in the following sections.

4.2 Learning Generative Graph Distribution

To learn a probabilistic generative graph distribution such that the graph drawn from this distribution can maximize the learning objective, two assumptions have been made about the explanation graph. The first assumption is that the graph is a Gilbert random graph (Gilbert, 1959) in which every possible edge occurs independently with probability $0 < p < 1$. The second assumption is that the features for each node and edge are independently distributed. Given these two assumptions, the probability distribution of the graph G, a random graph variable, can be factorized as

$$P(G) = \prod_{i \in \mathbf{V}} P(x_i) \cdot \prod_{(i,j) \in \mathbf{E}} P(z_{ij}) P(a_{ij}) \tag{3}$$

where $a_{ij} = 1$ when there exists an edge between node i and j and $a_{ij} = 0$ otherwise, z_{ij} denotes the edge feature between node i and j, and x_i represents the node feature of node i.

Intuitively, a_{ij} can be modeled as a Bernoulli distribution in which the probability of success θ_{ij} represents the probability of an edge existing between node i and j in G. For the discrete edge feature z_{ij} and the discrete node feature x_i, we can assume that z_{ij} and x_i follow a Categorical distribution, a generalized Bernoulli distribution, with the parameter specifying the probability of each possible outcome for the categorical node feature and the categorical edge feature. In summary, the probability distribution of a_{ij}, x_i and z_{ij} can be written as

$$\begin{cases} a_{ij} \sim \text{Bernoulli}(\theta_{ij}), & \text{for } a_{ij} \in \mathbf{A} \text{ and } \theta_{ij} \in \mathbf{\Theta} \\ z_{ij} \sim \text{Categorical}(\mathbf{q}_{ij}), & \text{for } z_{ij} \in \mathbf{Z} \text{ and } \mathbf{q}_{ij} \in \mathbf{Q} \\ x_i \sim \text{Categorical}(\mathbf{p}_i), & \text{for } x_i \in \mathbf{X} \text{ and } \mathbf{p}_i \in \mathbf{P} \end{cases} \tag{4}$$

where $\|\mathbf{q}_{ij}\|_1 = 1$ and $\|\mathbf{p}_{ij}\|_1 = 1$. We define the number of edge categories $k_E = \dim(\mathbf{q}_{ij})$ and the number of node categories $k_V = \dim(\mathbf{p}_i)$. Thus, to learn the probabilistic distribution for explanation graphs, we can rewrite the learning objective as

$$\max_G L(G) = \max_{\mathbf{\Theta},\mathbf{Q},\mathbf{P}} \mathbb{E}_{G \sim P(G)}[\phi_c(\mathbf{A}, \mathbf{Z}, \mathbf{X}) + \mu \text{sim}_{\cos}(\psi(\mathbf{A}, \mathbf{Z}, \mathbf{X}), \bar{\psi}_c)]. \tag{5}$$

4.3 Continuous Relaxation with Reparameterization Trick

To adopt gradient ascent over the learning objective function with respect to a graph with the discrete edge feature z_{ij} and the discrete node feature x_i, we relax a_{ij}, z_{ij} and x_i to continuous random variables $\tilde{a}_{ij}$, $\tilde{\mathbf{z}}_{ij}$ and $\tilde{\mathbf{x}}_i$, respectively. Specifically, a_{ij} is relaxed to $\tilde{a}_{ij} \in [0,1]$; z_{ij} is relaxed to $\tilde{\mathbf{z}}_{ij} \in [0,1]^{k_E}, \|\tilde{\mathbf{z}}_{ij}\|_1 = 1$; and x_i is relaxed to $\tilde{\mathbf{x}}_i \in [0,1]^{k_V}, \|\tilde{\mathbf{x}}_i\|_1 = 1$. Given that the Concrete distribution (Maddison et al., 2016) is a family of continuous versions of Categorical random variables with closed form density, the distribution of continuously relaxed $\tilde{a}_{ij}$, $\tilde{z}_{ij}$ and $\tilde{x}_i$ can be written as

$$\begin{cases} \tilde{a}_{ij} \sim \text{BinaryConcrete}(\omega_{ij}, \tau_a), & \text{for } \tilde{a}_{ij} \in \tilde{\mathbf{A}} \text{ and } \omega_{ij} \in \mathbf{\Omega} \\ \tilde{z}_{ij} \sim \text{Concrete}(\boldsymbol{\eta}_{ij}, \tau_z), & \text{for } \tilde{z}_{ij} \in \tilde{\mathbf{Z}} \text{ and } \boldsymbol{\eta}_{ij} \in \mathbf{H} \\ \tilde{x}_i \sim \text{Concrete}(\boldsymbol{\xi}_i, \tau_x), & \text{for } \tilde{x}_i \in \tilde{\mathbf{X}} \text{ and } \boldsymbol{\xi}_i \in \mathbf{\Xi} \end{cases} \tag{6}$$

where $\tau \in (0, \infty)$ is the hyper-parameter representing the temperature, $\omega_{ij} = \log(\theta_{ij}/(1 - \theta_{ij}))$, $\eta_{ij} = \log \mathbf{q}_{ij}$, and $\xi_i = \log \mathbf{p}_i$. As the temperature approaches zero, the Concrete distribution is mathematically equivalent to the Categorical distribution.

However, in order to learn the generative explanation graph distribution, the sampling function for sampling $\tilde{a}_{ij}$, $\tilde{z}_{ij}$ and $\tilde{x}_i$ from the Concrete distribution is required to be differentiable. Thus, the reparametrization trick is adopted to approximate the sampling procedure of $\tilde{a}_{ij}$, $\tilde{z}_{ij}$ and $\tilde{x}_i$ by a differentiable function. Given an independent random variable $\epsilon \sim \text{Uniform}(0,1)$, the sampling function with the reparameterization trick is as follows,

$$\begin{cases} \tilde{a}_{ij} = \text{sigmoid}\left((\omega_{ij} + \log \epsilon - \log(1 - \epsilon))/\tau_a\right) \\ \tilde{z}_{ij} = \text{Softmax}\left((\eta_{ij} - \log(-\log \epsilon))/\tau_z\right) \\ \tilde{x}_i = \text{Softmax}\left((\xi_{ij} - \log(-\log \epsilon))/\tau_x\right) \end{cases} \tag{7}$$

Given this reparameterization trick, we can draw a sample $\tilde{a}_{ij}$ as an approximation of a_{ij}, where the probability of $\tilde{a}_{ij}$ to be close to 1 is the same as the probability of a_{ij} to equal 1 and vice versa.

Specifically, $P(\tilde{a}_{ij} \to 1) = 1 - P(\tilde{a}_{ij} \to 0) = P(a_{ij} = 1) = \theta_{ij} = \text{sigmoid}(\omega_{ij})$. Similarly, $\tilde{z}_{ij}$ and $\tilde{x}_i$ drawn from the Concrete distribution as in Equation 7 is an approximation of z_{ij} and x_i. Therefore, the learning objective with continuous relaxation and reparameterization trick can be approximated by the Monte Carlo method with K samples,

$$\max_{\boldsymbol{\Theta},\mathbf{Q},\mathbf{P}} \mathbb{E}_{G \sim P(G)}[L(\mathbf{A}, \mathbf{Z}, \mathbf{X})] \approx \max_{\boldsymbol{\Omega},\mathbf{H},\boldsymbol{\Xi}} \mathbb{E}_{\epsilon \sim U(0,1)}[L(\tilde{\mathbf{A}}, \tilde{\mathbf{Z}}, \tilde{\mathbf{X}})] \approx \max_{\boldsymbol{\Omega},\mathbf{H},\boldsymbol{\Xi}} \frac{1}{K} \sum_{k=1}^{K} L(\tilde{\mathbf{A}}, \tilde{\mathbf{Z}}, \tilde{\mathbf{X}}). \quad (8)$$

In order to facilitate optimization and ensure that the explanation graphs are constrained to desired properties, we apply multiple regularization terms to the latent parameters (see details in Appendix A). Also, the detailed algorithm of GNNInterpreter is illustrated in Appendix B.

4.4 THE GENERALIZABILITY OF GNNINTERPRETER

GNNInterpreter can generate explanation graphs with different types of node features and edge features if needed. If the node feature or edge feature is continuous, $\nabla_{\mathbf{X}} L(\mathbf{A}, \mathbf{Z}, \mathbf{X})$ and $\nabla_{\mathbf{Z}} L(\mathbf{A}, \mathbf{Z}, \mathbf{X})$ naturally exist, then we only need to relax the adjacency matrix $\mathbf{A}$ to a continuous random variable as in Equation 6. Additionally, unlike XGNN which can only learn graphs with a single categorical node feature, the number of edge features and node features are not limited in GNNInterpreter.

GNNInterpreter can explain different GNNs following the message passing scheme. In the original message passing scheme, messages are aggregated from their neighbors to update the current node embedding. To adapt the message passing scheme for GNNInterpreter, messages are passed from all the other nodes but each message is weighted by $\theta_{ij} = \text{sigmoid}(\omega_{ij})$. Therefore, if θ_{ij} approaches to 1, meaning that node i and node j are highly likely to be the neighbor, the message passed between them will be the same as in the original message passing scheme. With this small modification, GNNInterpreter can be easily applied to different GNNs following the message passing scheme.

5 EXPERIMENTAL STUDY

To comprehensively assess the effectiveness of GNNInterpreter, we carefully design experimental studies conducted on 4 datasets to demonstrate our flexibility of generating explanation graphs with various feature types and manifests our capability of explaining different GNNs. Specifically, we train a GNN classifier for each dataset and adopt GNNInterpreter to explain. In addition, we quantitatively and qualitatively compare the efficacy of GNNInterpreter with XGNN (Yuan et al., 2020a). Details about the experiments and synthetic datasets generation are presented in Appendix F,G,H, and I.

Table 1: The statistics of datasets and some technical details about their corresponding GNN models.

Dataset	# of Classes	Node Features	Edge Features	Average # of Edges	Average # of Nodes	GNN Type	GNN Test Accuracy
MUTAG (Kersting et al., 2016)	2	✓		19.79	17.93	GCN (Kipf & Welling, 2017)	0.9468
Cyclicity	3		✓	52.76	52.51	NNConv (Gilmer et al., 2017)	0.9921
Motif	5	✓		77.36	57.07	GCN (Kipf & Welling, 2017)	0.9964
Shape	5			71.86	30.17	GCN (Kipf & Welling, 2017)	0.9725

5.1 DATASETS

Synthetic Dataset. We synthetically generate 3 datasets which are Cyclicity, Motif, and Shape (see Table 1). (1) In **Cyclicity**, the graphs have an categorical edge feature with 2 possible values: green or red. There are 3 class labels in Cyclicity, which are Red-Cyclic graphs, Green-Cyclic graphs, and Acyclic graphs. Specifically, a graph will be labeled as a green/red cyclic graph only if it is cyclic and the edges forming that cycle are all green/red. If a graph is categorized as Acyclic, then it either does not contain a cycle at all or contains a cycle but with a mixture of green and red edges. (2) The graphs in **Motif** are labeled according to whether they contain a certain motif. There are 4 motifs (i.e., House, House-X, Complete-4, and Complete-5) will possibly appear in the graphs and each motif corresponds to one class label. There is another class that contains the graphs without any special motif. Besides, each node in the graphs has a categorical node feature with 5 possible values: red, orange, green, blue, and purple. (3) **Shape** contains 5 classes of graphs: Lollipop, Wheel, Grid, Star, and Others. In all the classes except the Others class, graphs are generated with the corresponding shape. For the Others class, graphs are randomly generated without any special topology.

Real-world Dataset. MUTAG (Kersting et al., 2016) is a real-world dataset with 2 classes: Mutagen and Nonmutagen. Each molecule graph is categorized according to its mutagenic effect (Debnath et al., 1991). Given the fact that the molecules with more NO_2 are more likely to mutate, the graphs in the Mutagen class tend to have more NO_2 than those in the Nonmutagen class. Besides, the Mutagen class and the Nonmutagen class share a common feature which is rings of carbon atoms.

5.2 RESULTS

To investigate whether we can truly explain the high-level decision-making process, we evaluated GNNInterpreter both quantitatively and qualitatively. Following XGNN (Yuan et al., 2020a), the class probability of the explanation graphs predicted by the GNN is adopted as the quantitative metric since GNNInterpreter and XGNN share a common objective of maximizing the target class score (Table 2). Also, to qualitatively evaluate GNNInterpreter, we present one explanation graph per class for all datasets in Figure 1, which are all predicted as the target class with the class probability of 1. Due to the page limit, more explanation graphs per class per dataset are presented in Appendix E.

Table 2: The quantitative results for 4 datasets. As the quantitative metric, we compute the average class probability of 1000 explanation graphs and the standard deviation of them for every class in all 4 datasets. In addition, the average training time per class of training 100 different GNNInterpreter and XGNN models, is also included for efficiency evaluation.

Dataset [Method]	Predicted Class Probability by GNN				Training Time Per Class
MUTAG [XGNN]	Mutagen 0.986 ± 0.057	Nonmutagen 0.991 ± 0.083			128 s
MUTAG [Ours]	Mutagen 1.000 ± 0.000	Nonmutagen 1.000 ± 0.000			12 s
Cyclicity [Ours]	Red Cyclic 1.000 ± 0.000	Green Cyclic 1.000 ± 0.000	Acyclic 1.000 ± 0.000		49 s
Motif [Ours]	House 0.918 ± 0.268	House-X 0.999 ± 0.032	Complete-4 1.000 ± 0.000	Complete-5 0.998 ± 0.045	83 s
Shape [Ours]	Lollipop 0.742 ± 0.360	Wheel 0.989 ± 0.100	Grid 0.996 ± 0.032	Star 1.000 ± 0.000	24 s

Figure 1: The qualitative results for 4 datasets. For each class in all datasets, the explanation graph with the class probability of 1 predicted by the GNNs is displayed on the left; as a reference, the example graph selected from the training data of the GNNs or the motif is displayed on the right. The different colors in the nodes and edges represent different values in the node feature and edge feature.

Since XGNN is the current state-of-the-art model-level explanation method for GNNs, we compare GNNInterpreter with XGNN quantitatively and qualitatively. However, given that XGNN cannot

generate explanation graphs with edge features, XGNN is not applicable to the Cyclicity dataset. For Motif and Shape, we attempted to adopt XGNN to explain the corresponding GNNs, but the explanation results were not acceptable even after our extensive efforts of trial-and-error on XGNN. Therefore, for a fair comparison, we only present the evaluation results of XGNN on the GNN trained on MUTAG, with the same hyper-parameter settings for MUTAG as they discussed in their paper. In addition to these 4 datasets, we also conducted experiments on the Is_Acyclic dataset synthesized by XGNN authors, but we failed to reproduce similar results claimed in the XGNN paper. The details of our comparative study on Is_Acyclic dataset against XGNN can be found in Appendix C.

MUTAG. The quantitative evaluation in Table 2 shows that all explanation graphs generated by GNNInterpreter are classified correctly with 100% probability for both classes with zero variance, which indicates that we can consistently generate the most representative explanation graphs in terms of the explained GNN for all three classes. On the contrary, the GNN is more hesitant or diffident when classifying the XGNN explanation graphs for both classes. Speaking of the time efficiency, for explaining the same GNN model trained on MUTAG, *we can generate an explanation graph about 10 times faster than XGNN on average* (see Table 2). In Figure 1, the GNNInterpreter explanation for Mutagen class contains 5 repeated NO_2 whereas the GNNInterpreter explanation for Nonmutagen class does not contain O atom at all, which are perfectly aligned with our background knowledge about the MUTAG dataset mentioned in subsection 5.1. In contrast, the XGNN explanation for Mutagen class only contains a single NO_2, which is a less accurate or ideal explanation than ours. In addition, according to our explanation graphs for both classes, they indicate that the GNN trained with MUTAG is likely to suffer from the bias attribution issue (Faber et al., 2021) because the explanation graph for Nonmutagen class does not contain any special pattern but achieve the class probability of 1. This finding is further verified by the additional experiments we conducted (see subsection D.2).

Cyclicity. In addition to the good quantitative performance shown in Table 2, the explanation graphs for Red Cyclic and Green Cyclic only contain multiple red cycles and multiple green cycles, respectively; the explanation graph for Acyclic does not contain any cycle with homogeneous edge colors (see Figure 1). These explanations are very accurate and reveal a pattern that the *more occurrences of the discriminative feature for the corresponding class (i.e., red cycle, green cycle, and cycle with heterogeneous edge color, respectively) substantially boost the confidence of the GNN during the decision-making process.*

Motif. The quantitative result in Table 2 shows that the explanations for all classes successfully identify the discriminative features the GNN tries to detect. In Figure 1, the explanation graphs for House and Complete-5 class match the exact motif. Even though the explanation graphs for House-X and Complete-4 do not match the exact motif, it still obtains the class probabilities of 1. By analyzing the commonality between the explanations and their corresponding ground truth motifs for House-X and Complete-4 respectively, we speculate the discriminative features the GNN tries to detect for these two classes is the following: in House-X graphs, the orange node and the red node should have 3 neighbors except the purple node, the green node and the blue node should have 4 neighbors in different color; in Complete-4 graphs, every node should have 3 neighbors in different color. *Clearly, the GNN with a test accuracy of 0.9964 (Table 1) perceives the wrong motifs as the House-X and Complete-4, which can potentially incur misclassification for unseen graphs with misleading patterns.*

Shape. In Table 2, the explanations for all the classes except Lollipop achieve a good quantitative performance. For Lollipop, the average class probability of 0.742 is still a reasonably high probability than 0.2 (the baseline probability of random guess for a classification task with 5 classes). Besides, the explanation graphs for all 4 classes presented in Figure 1 are almost consistent with the desired graph patterns. Nonetheless, it also discloses some interesting findings regarding the high-level decision-making process of the GNN. For Wheel and Grid class, the explanation graphs are not very perfect but with the predicted class probability of 1. Accordingly, we infer the true belief inside the GNN is that: the discriminative features of Wheel graph and Grid graph are a single common vertex shared by multiple triangles and multiple polygons sharing some common edges, respectively. *These might become the potential model pitfalls because, for example, the GNN will be easily tricked by a non-wheel graph in which there exists a common vertex shared by multiple triangles.*

Verification Study. Since the ground truth model-level explanation graphs are unknown, the correctness of our analysis regarding these potential GNN pitfalls cannot be directly justified. Therefore, to verify the correctness, we conduct controlled experimental studies to test how the GNN behaves on some carefully chosen input graphs with specific misleading patterns. As mentioned above, we

speculate the discriminative feature the GNN tries to detect for the House-X class is that "orange node and red node should have 3 neighbors except purple node, green node and blue node should have 4 neighbors in different color". We found 9 plausible motifs (including the ground truth House-X) which satisfy this rule (see Figure 2). Given a fixed set of 5000 base graphs, each of the 9 different motifs are attached to the same node of each base graphs respectively. Thus, we obtain 9 sets of graphs, each of which contains 5000 graphs corresponding to one of the motifs. For each motif set, the classification results are presented in Table 3. We can see that *motif 1-8 successfully fool the explained GNN because a large portion of the non-House-X graphs are incorrectly classified as House-X.* This verification result strongly supports our qualitative analysis regarding the potential model pitfall for House-X class. The verification studies for more classes are presented in Appendix D.

Plausible House-X Motifs

Figure 2: The ground truth class label for motif 1-8 and motif 9 is Others and House-X, respectively.

Table 3: The classification results of plausible House-X motifs.

	Motif 1	Motif 2	Motif 3	Motif 4	Motif 5	Motif 6	Motif 7	Motif 8	Motif 9 (GT)
Others	1434	2251	1808	1970	2183	597	1682	1696	10
House	0	0	0	0	0	0	0	0	0
House-X	3566	2749	3192	3030	2817	4403	3318	3304	4990
Complete-4	0	0	0	0	0	0	0	0	0
Complete-5	0	0	0	0	0	0	0	0	0

Ablation Study. In many cases, especially when true graphs are constrained with certain domain-specific rules, the second term of the objective function in Equation 2 plays a significant role in generating meaningful explanations. To assess the effectiveness of the second term, we take the Mutagen class from MUTAG dataset as an example to conduct an ablation study on this term. As shown in Figure 3, the explanation without the second term completely deviates from the true data distribution because the ground truth discriminative feature of the mutagen class (i.e., NO2) is completely missing in the explanation without the second term. Even though the explanation without second term achieve a significantly higher logits, it is difficult to gain the meaningful insights from the explanation without second term. That is to say, the out-of-distribution explanation graph generated without the second term might not provide meaningful insight on how the model actually reasons over the true data distribution, which is what we actually care about.

Figure 3: The ablation study of the second term on the mutagen class from MUTAG dataset. For each category (column), we present 2 explanation graphs with the class score before Softmax (logits).

6   CONCLUSION

We propose GNNInterpreter, a probabilistic generative model-level explanation method for GNNs, which learns a graph distribution to depict the representative pattern perceived by the GNNs regarding the target class. By optimizing the objective function we specifically designed, GNNInterpreter can generate both faithful and valid explanation without relying on manually specified domain-specific graph rules. Compared with XGNN, GNNInterpreter is more general and computationally efficient because it can generate explanations with different types of edge features and node features, about 10 times faster. This makes GNNInterpreter more practical and accessible in real-world applications. More importantly, the experimental results show that GNNInterpreter can not only produce more faithful results than XGNN on real-life dataset, but also reveal the potential model pitfalls such as the bias attribution issue and misclassification of unseen graphs with misleading graph pattern.

REFERENCES

Federico Baldassarre and Hossein Azizpour. Explainability techniques for graph convolutional networks. *ArXiv*, abs/1905.13686, 2019.

Alexander Binder, Grégoire Montavon, Sebastian Lapuschkin, Klaus-Robert Müller, and Wojciech Samek. Layer-wise relevance propagation for neural networks with local renormalization layers. In *ICANN*, 2016.

Shaosheng Cao, Wei Lu, and Qiongkai Xu. Deep neural networks for learning graph representations. AAAI'16, pp. 1145–1152. AAAI Press, 2016.

Asim Kumar Debnath, Rosa L. Lopez de Compadre, Gargi Debnath, Alan J. Shusterman, and Corwin Hansch. Structure-activity relationship of mutagenic aromatic and heteroaromatic nitro compounds. correlation with molecular orbital energies and hydrophobicity. *Journal of Medicinal Chemistry*, 34(2):786–797, 1991. doi: 10.1021/jm00106a046. URL https://doi.org/10.1021/jm00106a046.

Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. In *Advances in Neural Information Processing Systems*, 2016.

Alexandre Duval and Fragkiskos Malliaros. Graphsvx: Shapley value explanations for graph neural networks. In *European Conference on Machine Learning and Knowledge Discovery in Databases (ECML PKDD)*, 2021.

Lukas Faber, Amin K. Moghaddam, and Roger Wattenhofer. When comparing to ground truth is wrong: On evaluating gnn explanation methods. KDD '21, pp. 332–341, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450383325. doi: 10.1145/3447548.3467283. URL https://doi.org/10.1145/3447548.3467283.

E. N. Gilbert. Random graphs. *The Annals of Mathematical Statistics*, 30(4):1141–1144, 1959. ISSN 00034851. URL http://www.jstor.org/stable/2237458.

Justin Gilmer, Samuel Schoenholz, Patrick Riley, Oriol Vinyals, and George Dahl. Neural message passing for quantum chemistry. 04 2017.

William Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. 06 2017.

Q. Huang, Makoto Yamada, Yuan Tian, Dinesh Singh, Dawei Yin, and Yi Chang. Graphlime: Local interpretable model explanations for graph neural networks. *ArXiv*, abs/2001.06216, 2020.

Kristian Kersting, Nils M. Kriege, Christopher Morris, Petra Mutzel, and Marion Neumann. Benchmark data sets for graph kernels, 2016. URL http://graphkernels.cs.tu-dortmund.de.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *International Conference on Learning Representations (ICLR)*, 2017.

John Lee, Ryan Rossi, and Xiangnan Kong. Graph classification using structural attention. pp. 1666–1674, 07 2018. doi: 10.1145/3219819.3219980.

Dongsheng Luo, Wei Cheng, Dongkuan Xu, Wenchao Yu, Bo Zong, Haifeng Chen, and Xiang Zhang. Parameterized explainer for graph neural network. *Advances in Neural Information Processing Systems*, 33, 2020.

Christopher Maddison, Andriy Mnih, and Yee Teh. The concrete distribution: A continuous relaxation of discrete random variables. 11 2016.

Anh Nguyen, Jason Yosinski, and Jeff Clune. Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. pp. 427–436, 06 2015. doi: 10.1109/CVPR.2015.7298640.

Phillip Pope, Soheil Kolouri, Charles Martin, and Heiko Hoffmann. Explainability methods for graph convolutional neural networks. 06 2019. doi: 10.1109/CVPR.2019.01103.

Robert Schwarzenberg, Marc Hübner, David Harbecke, Christoph Alt, and Leonhard Hennig. Layerwise relevance visualization in convolutional text graph classifiers. *ArXiv*, abs/1909.10911, 2019.

Ramprasaath R. Selvaraju, Abhishek Das, Ramakrishna Vedantam, Michael Cogswell, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. *International Journal of Computer Vision*, 128:336–359, 2019.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. *CoRR*, abs/1312.6034, 2014.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph Attention Networks. *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=rJXMpikCZ. accepted as poster.

Minh N. Vu and My T. Thai. Pgm-explainer: Probabilistic graphical model explanations for graph neural networks. *ArXiv*, abs/2010.05788, 2020.

Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and Philip Yu. A comprehensive survey on graph neural networks. *IEEE Transactions on Neural Networks and Learning Systems*, PP:1–21, 03 2020. doi: 10.1109/TNNLS.2020.2978386.

Dongkuan Xu, Wei Cheng, Dongsheng Luo, Xiao Liu, and Xiang Zhang. Spatio-temporal attentive rnn for node classification in temporal attributed graphs. pp. 3947–3953, 08 2019. doi: 10.24963/ijcai.2019/548.

Rex Ying, Dylan Bourgeois, Jiaxuan You, Marinka Zitnik, and Jure Leskovec. Gnnexplainer: Generating explanations for graph neural networks. *Advances in neural information processing systems*, 32:9240–9251, 12 2019.

Wenchao Yu, Cheng Zheng, Wei Cheng, Charu C. Aggarwal, Dongjin Song, Bo Zong, Haifeng Chen, and Wei Wang. Learning deep network representations with adversarially regularized autoencoders. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, KDD '18, pp. 2663–2671, New York, NY, USA, 2018. Association for Computing Machinery. ISBN 9781450355520. doi: 10.1145/3219819.3220000. URL https://doi.org/10.1145/3219819.3220000.

Hao Yuan, Jiliang Tang, Xia Hu, and Shuiwang Ji. Xgnn: Towards model-level explanations of graph neural networks. pp. 430–438, 08 2020a. doi: 10.1145/3394486.3403085.

Hao Yuan, Haiyang Yu, Shurui Gui, and Shuiwang Ji. Explainability in graph neural networks: A taxonomic survey. *ArXiv*, abs/2012.15445, 2020b.

Jianming Zhang, Zhe L. Lin, Jonathan Brandt, Xiaohui Shen, and Stan Sclaroff. Top-down neural attention by excitation backprop. *International Journal of Computer Vision*, 126:1084–1102, 2017.

Muhan Zhang and Yixin Chen. Link prediction based on graph neural networks. 02 2018.

Appendix

Table of Contents

A   REGULARIZATION

In order to facilitate optimization and ensure that the explanation graphs are constrained to desired properties, we apply multiple regularization terms to the latent parameters.

$L1$ **and** $L2$ **Regularization.** $L1$ and $L2$ regularizations are widely used to encourage model sparsity and reduce the parameter size. In our case, both regularizations are applied on $\mathbf{\Omega}$ during the optimization to reduce its size, with the purpose of mitigating the saturating gradient problem caused by the sigmoid function in Equation 7. For $k \in \{1, 2\}$, L_k penalty term is defined as

$$R_{L_k} = \|\mathbf{\Omega}\|_k. \tag{9}$$

Budget Penalty. Budget penalty is employed in instance-level GNN explanation methods (i.e., PGExplainer (Luo et al., 2020) and GNNExplainer (Ying et al., 2019)) to generate compact and meaningful explanations. For the model-level explanation, budget penalty can prevent the size of explanation graphs from growing unboundedly with repeated discriminative patterns. Budget penalty is defined as

$$R_b = \mathrm{softplus}\left(\|\mathrm{sigmoid}(\mathbf{\Omega})\|_1 - B\right)^2, \tag{10}$$

where B is the expected maximum number of edges in the explanation graph. *Unlike PGExplainer, we utilize* $\mathrm{softplus}$ *instead of* ReLU *to slack the rate of gradient change near the boundary condition. In addition, the penalty is squared to further discourage extremely large graphs.*

Connectivity Constraint. Inspired by PGExplainer, we apply a connectivity constraint to encourage explanation graphs to be connected, by minimizing the Kullback–Leibler divergence between the

probabilities of each pair of edges that share a common node in the Gilbert random graph,

$$R_c = \sum_{i \in V} \sum_{j,k \in \mathcal{N}(i)} \mathrm{D_{KL}}(P_{ij} \| P_{ik}) \tag{11}$$

where P_{ij} denotes the Bernoulli distribution parameterized by $\mathrm{sigmoid}(\omega_{ij})$. *As opposed to PGExplainer, KL-divergence is chosen over cross-entropy in order to decouple the entropy of individual edge distributions from the connectivity constraint.*

B TRAINING PROCEDURE OF GNNINTERPRETER

Algorithm 1: Generate Explanation Graphs Using GNNInterpreter
---
1 Calculate the average graph embedding $\bar{\psi}_c$ from the training data of GNN model.
2 Initialize latent parameters $\mathbf{\Omega}$, $\mathbf{H}$, and $\mathbf{\Xi}$.
3 **while** not converged **do**
4   **for** $k \leftarrow 1...K$ **do**
5   Using the reparameterization trick, sample $\tilde{\mathbf{A}}, \tilde{\mathbf{E}}, \tilde{\mathbf{X}}$ with Equation 7.
6   Obtain the class score $s_c^{(k)} \leftarrow \phi_c(\tilde{\mathbf{A}}, \tilde{\mathbf{E}}, \tilde{\mathbf{X}})$.
7   Obtain the graph embedding $\mathbf{h}_c^{(k)} \leftarrow \psi_c(\tilde{\mathbf{A}}, \tilde{\mathbf{E}}, \tilde{\mathbf{X}})$.
8   **end**
9   Calculate $L \leftarrow \frac{1}{K} \sum_{k=1}^{K} \left[s_c^{(k)} + \mu \mathrm{sim_{cos}}(\mathbf{h}_c^{(k)}, \bar{\psi}_c) \right]$ with the regularization terms.
10   Calculate $\nabla_{\mathbf{\Omega}} L$, $\nabla_{\mathbf{H}} L$, and $\nabla_{\mathbf{\Xi}} L$, then update $\mathbf{\Omega}$, $\mathbf{H}$, and $\mathbf{\Xi}$ using gradient ascent.
11 **end**
12 Let $\mathbf{\Theta} = \mathrm{sigmoid}(\mathbf{\Omega})$, $\mathbf{P} = \mathrm{Softmax}(\mathbf{\Xi})$, $\mathbf{Q} = \mathrm{Softmax}(\mathbf{H})$.
13 **return** $G = (\mathbf{A}, \mathbf{E}, \mathbf{X})$, where $\mathbf{A}, \mathbf{E}, \mathbf{X}$ are sampled with Equation 4 parameterized by $\mathbf{\Theta}, \mathbf{P}, \mathbf{Q}$.

C THE EVALUATION RESULTS OF IS_ACYCLIC FROM XGNN PAPER

In order to conduct more comprehensive comparison with the current state-of-the-art method (XGNN), we managed to evaluate GNNInterpreter on Is_Acyclic data which is synthetically generated by the XGNN authors and posted at XGNN GitHub[1]. We trained a GCN classifier on this dataset with an accuracy of 1 (see the last row of Table 4) and adopted GNNInterpreter to explain the two classes in Is_Acyclic. The quantitative and qualitative evaluation of GNNInterpreter on Is_Acyclic is conducted in a similar manner of other datasets, which is shown in Table 5 and Figure 4, respectively.

However, it is unfortunate that XGNN could not provide any meaningful explanation for the GCN model we trained on Is_Acyclic (like what we experienced for the Shape and Motif dataset). We spent an extensive amount of time tuning the hyper-parameter of XGNN, but we still could not obtain meaningful and acceptable explanation graphs. We also attempted to conduct a comparative study on the GNN model trained by the XGNN authors because its model checkpoint is available in the google drive folder they shared. But unfortunately, the model definition of the GNN model on Is_Acyclic is not available on their GitHub (only the model definition of GNN for MUTAG is provided on their GitHub) so we cannot successfully load the model checkpoint they trained for Is_Acyclic. Even so, the quantitative and qualitative evaluation of XGNN on the GCN model we trained on Is_Acyclic is still presented in Table 5 and Figure 4.

Speaking of the evaluation results, the quantitative result in Table 5 shows that, for both classes, we can consistently generate faithful explanations containing the discriminative pattern of the target class perceived by the GNN. However, the XGNN explanations for both classes is less ideal because the average class probability over 1000 explanation graphs for Cyclic class is almost zero. This indicates that the explanation graphs generated for both classes will be classified as Acyclic by the GNN, no matter which is the target class to explain. In terms of the computational time, we can generate an explanation graph about 2 times faster than XGNN on average. Qualitatively speaking, our explanation graphs for both Cyclic and Acyclic class are consistent with the class definition with

---
[1] https://github.com/divelab/DIG/tree/main/dig/xgraph/XGNN

the expected properties (see Figure 4). Namely, the explanation graph for Cyclic contains cycles while the explanation graph for Acyclic does not contain any cycles. In contrast, for both classes, XGNN fails to generate an explanation graph beyond two nodes, even after our extensive trail-and-error effort.

Table 4: The statistics of datasets including Is_Acyclic and some technical details about their corresponding GNN models.

Dataset	# of Classes	Node Features	Edge Features	Average # of Edges	Average # of Nodes	GNN Type	GNN Test Accuracy
MUTAG (Kersting et al., 2016)	2	✓		19.79	17.93	GCN (Kipf & Welling, 2017)	0.9468
Cyclicity	3		✓	52.76	52.51	NNConv (Gilmer et al., 2017)	0.9921
Motif	5	✓		77.36	57.07	GCN (Kipf & Welling, 2017)	0.9964
Shape	5			71.86	30.17	GCN (Kipf & Welling, 2017)	0.9725
Is_Acyclic	2			30.04	28.46	GCN (Kipf & Welling, 2017)	1.0000

Table 5: The quantitative evaluation results for all 5 dataset including Is_Acyclic. As the quantitative metric, we compute the average class probability of 1000 explanation graphs and the standard deviation of them for the two classes. In addition, the average training time per class of training 100 different GNNInterpreter is also included for efficiency evaluation.

Dataset [Method]	Predicted Class Probability by GNN				Training Time Per Class
Is_Acyclic [XGNN]	Cyclic 0.076 ± 0.000	Acyclic 0.927 ± 0.000			45 s
Is_Acyclic [Ours]	Cyclic 0.999 ± 0.001	Acyclic 1.000 ± 0.000			20 s
MUTAG [XGNN]	Mutagen 0.986 ± 0.057	Nonmutagen 0.991 ± 0.083			128 s
MUTAG [Ours]	Mutagen 1.000 ± 0.000	Nonmutagen 1.000 ± 0.000			12 s
Cyclicity [Ours]	Red Cyclic 1.000 ± 0.000	Green Cyclic 1.000 ± 0.000	Acyclic 1.000 ± 0.000		49 s
Motif [Ours]	House 0.918 ± 0.268	House-X 0.999 ± 0.032	Complete-4 1.000 ± 0.000	Complete-5 0.998 ± 0.045	83 s
Shape [Ours]	Lollipop 0.742 ± 0.360	Wheel 0.989 ± 0.100	Grid 0.996 ± 0.032	Star 1.000 ± 0.000	24 s

Dataset [Method]	Generated Model-Level Explanation Graphs
Is_Acyclic[XGNN]	
Is_Acyclic[Ours]	

Figure 4: The qualitative results for Is_Acyclic. As a reference, the example graph selected from the training data of the GNNs is displayed on the right. Also, the class score after Softmax of the target class is presented above each corresponding explanation graph.

D A VERIFICATION STUDY OF OUR ANALYSIS ABOUT QUALITATIVE RESULTS

From Figure 1, we can see that the explanation graphs for some classes are different from the true graphs in the training data, which might indicate the potential pitfall of the explained GNN. However, since the ground truth model-level explanation graph does not exist, it is difficult to verify the correctness of our analysis regarding these potential pitfalls. In this section, we conducted the controlled experimental studies for MUTAG, House-X in Motif and Complete-4 in Motif, to verify our high-level interpretation of the explained GNN mentioned in the subsection 5.2.

D.1 MOTIF

Complete-4 In subsection 5.2, we infer that the discriminative feature the GNN tries to detect is that "every node should have 3 neighbors in different color". This rule is concluded from our observation of the commonality between our explanation graph and the ground truth motif. We found 8 different motifs (including the ground truth Complete-4) which satisfy this rule, as shown in Figure 5. Given a fixed set of 5000 Rome graphs, these 8 different motifs are attached to the same node of those 5000 Rome graphs. As a result, we obtain 8 sets of graphs, and each set includes 5000 graphs corresponding to a single motif. For each motif set, the average predicted class probability of each class and the total number of graphs which are classified as each class are presented in the Table 6 and Table 7, respectively. We can clearly see that motif 1-6 successfully fool the explained GNN because their predicted class probability of Complete-4 is significantly higher than their predicted class probability of Others. This results indicate that our previous analysis in subsection 5.2 regarding how the GNN makes prediction for Complete-4 is correct. Namely, the GNN trained with the Motif dataset is highly likely to incorrectly classify the graphs containing a misleading pattern identified by the GNNInterpreter, even though the GNN accuracy is as high as 0.9964 (see Table 1). *Therefore, GNNInterpreter can be served as a sanity check for GNNs, especially the one with high accuracy, and remind people to be cautious when applying GNNs to classify some unseen graphs containing the misleading patterns identified by the GNNInterpreter.*

Figure 5: Plausible Complete-4 motifs. The motifs satisfying the rule that every node should have 3 neighbors in different color. The motif 8 is the ground truth Complete-4 motif. The ground truth class label of motif 1-7 should be the Others class.

Table 6: The quantitative results of plausible Complete-4 motifs. For each motif set (column), the average predicted class probability of each class (row) is computed by averaging over 5000 graphs containing the corresponding motif.

	Motif 1	Motif 2	Motif 3	Motif 4	Motif 5	Motif 6	Motif 7	Motif 8 (GT)
Others	0.4123	0.4064	0.4122	0.4033	0.4116	0.4019	0.9974	0.0066
House	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0021	0.0000
House-X	0.0002	0.0006	0.0004	0.0007	0.0003	0.0002	0.0001	0.0000
Complete-4	0.5875	0.593	0.5874	0.596	0.5881	0.5978	0.0004	0.9934
Complete-5	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0001	0.0000

House-X In subsection 5.2, we speculate the discriminative feature perceived by the explained GNN is that "orange node and red node should have 3 neighbors except purple node, green node and blue node should have 4 neighbors in different color". This discriminative feature is also deduced from the commonality between our explanation for House-X and the ground truth motif. The 9 motifs satisfying this rule are shown in Figure 6. The controlled experimental study for House-X class is conducted in a similar manner as for Complete-4 class. The quantitative results for each motif set in Table 8 and Table 9 shows that all the plausible motifs satisfying the rule are highly likely to be classified as House-X, no matter what are their corresponding ground truth labels. Specifically, a large number of graphs from motif set 1-8 are misclassified to the House-X class, especially the motif

Table 7: The classification results of plausible Complete-4 motifs. For each motif set (column), the total number of graphs which are classified as the classes (row) is presented in this table. The sum of all columns should be 5000 because that is the total number of graphs in each motif set.

	Motif 1	Motif 2	Motif 3	Motif 4	Motif 5	Motif 6	Motif 7	Motif 8 (GT)
Others	2030	1983	2016	1985	2031	1966	4994	0
House	0	0	0	0	0	0	4	0
House-X	1	3	1	4	1	1	0	0
Complete-4	2969	3014	2983	3011	2986	3033	2	5000
Complete-5	0	0	0	0	0	0	0	0

1 and motif 6. It also indicates that the GNN are easily fooled by the graphs containing the plausible motifs satisfying the rule that "orange node and red node should have 3 neighbors except purple node, green node and blue node should have 4 neighbors in different color". In summary, speaking of the GNN trained on the Motif dataset with the accuracy of 0.9964, this verification study shows that our explanation results is faithful because it successfully reveals the true model pitfalls.

Figure 6: Plausible House-X motifs. The motifs satisfying the rule that orange node and red node should have 3 neighbors except purple node, green node and blue node should have 4 neighbors in different color. The motif 9 is the ground truth House-X motif. The ground truth class label of motif 1-8 should be the Others class.

Table 8: The quantitative results of plausible House-X motifs. For each motif set (column), the average predicted class probability of each class (row) is computed by averaging over 5000 graphs containing the corresponding motif.

	Motif 1	Motif 2	Motif 3	Motif 4	Motif 5	Motif 6	Motif 7	Motif 8	Motif 9 (GT)
Others	0.2929	0.4411	0.3558	0.3849	0.4317	0.1296	0.3351	0.3373	0.0022
House	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
House-X	0.7053	0.5581	0.6435	0.6144	0.5678	0.8700	0.6641	0.6620	0.9978
Complete-4	0.0002	0.0003	0.0004	0.0004	0.0004	0.0003	0.0008	0.0007	0.0000
Complete-5	0.0016	0.0004	0.0002	0.0003	0.0002	0.0001	0.0000	0.0000	0.0000

D.2 MUTAG

According to the explanation graphs provided in Figure 1, the discriminative feature captured by our explanation graph for the mutagen class is the occurrences of the NO2 group. However, there are no special pattern observed from our explanation graph for the non-mutagen class. To verify whether the occurrences of NO2 group is truly the discriminative feature GNN tries to detect when making prediction for the mutagen class, we designed a controlled experiment such that each set of graphs

Table 9: The classification results of plausible House-X motifs. For each motif set (column), the total number of graphs which are classified as the classes (row) is presented in this table. The sum of all columns should be 5000 because that is the total number of graphs in each motif set.

	Motif 1	Motif 2	Motif 3	Motif 4	Motif 5	Motif 6	Motif 7	Motif 8	Motif 9 (GT)
Others	1434	2251	1808	1970	2183	597	1682	1696	10
House	0	0	0	0	0	0	0	0	0
House-X	3566	2749	3192	3030	2817	4403	3318	3304	4990
Complete-4	0	0	0	0	0	0	0	0	0
Complete-5	0	0	0	0	0	0	0	0	0

contains different numbers of NO2 group while keeping other experimental settings the same. To be specific, given 1000 randomly generated Gabriel graphs with 5-10 nodes, each time we attach 15 nodes to these random graphs. These 15 nodes will be divided into 5 groups, and each group has 3 nodes. The frequency of NO2 group appearing in these 15 nodes varies from 0 to 5. For instance, in Figure 7, the example graph for 5 NO2 contains a Gabriel graph with 6 nodes and 5 NO2 groups; the example graph for 4 NO2 contains the same Gabriel graph, 4 NO2 groups, and a random group of 3 nodes. As a result, we will obtain 6 sets of graphs and each set includes 1000 graphs containing a fixed number of NO2 group.

Then, we feed these 6000 graphs into the GNN trained with the MUTAG dataset to obtain the quantitative results. Similar to what we did for Motif dataset, for each 1000 graphs with a fixed number of NO2 group, the average predicted class probability for each class and the number of graphs being classified as each class is presented in Table 10 and Table 11. We can clearly see that as more and more NO2 group occurs, the GNN become more and more certain about classifying these graphs as the mutagen class. That is to say, the number of occurrences of NO2 groups indeed are the discriminative features the GNN tries to detect when making prediction for the mutagen class, which is consistent with our previous finding when analyzing our explanations for both classes in subsection 5.2. Thus, this verification study proves that our explanations for MUTAG dataset are faithful and informative because it can correctly interpret the high-level decision-making procress of the GNN.

It has been shown that GNNs trained on binary classification task can suffer from the bias attribution issue (Faber et al., 2021). Essentially, the GNN with bias attribution issue will classify any graphs as class A unless it finds sufficient evidence of class B. From Table 10 and Table 11, it is interesting to observe that the GNN seems bias toward the non-mutagen class unless the GNN finds enough evidence (i.e., NO2 group) for the mutagen class. This indicates that this GNN is suffering from the bias attribution issue so that no special pattern is observed from our explanation graph for non-mutagen class in Figure 1. Therefore, this verification study also proves that the faithful explanation generated by GNNInterpreter can help us to diagnose whether the GNN is suffering from the bias attribution issue.

Table 10: The quantitative results of graphs with different numbers of NO2 groups. For each 1000 graphs with the fixed number of NO2 groups (column), the average predicted class probability of each class (row) is computed by averaging over 1000 graphs containing the fixed number of NO2 group.

15 Nodes	0 NO$_2$	1 NO$_2$	2 NO$_2$	3 NO$_2$	4 NO$_2$	5 NO$_2$
Non-Mutagen	0.9837	0.9651	0.9186	0.7593	0.3998	0.0714
Mutagen	0.0163	0.0349	0.0814	0.2407	0.6002	0.9286

Table 11: The classification results of graphs with different numbers of NO2 groups. For each 1000 graphs with the fixed number of NO2 groups (column), the number of graphs being classified as the classes (row) is presented. The sum of all columns should be 1000.

15 Nodes	0 NO$_2$	1 NO$_2$	2 NO$_2$	3 NO$_2$	4 NO$_2$	5 NO$_2$
Non-Mutagen	984	965	917	758	396	71
Mutagen	16	35	83	242	604	929

(a) Example Graphs

C	N	O	F
I	Cl	Br	

(b) Node Labels

Figure 7: The example graphs with different numbers of NO2 groups attached to the same Gabriel graph with 6 random nodes.

E   MULTIPLE EXPLANATION GRAPHS PER CLASS PER DATASET

For each dataset, multiple qualitative examples per class are shown in Figure 8.

F   EXPERIMENTAL SETUP

All the experiments are conducted on a single core of an Intel Core i9 CPU. Speaking of the software, all the models are implemented in Python 3.9. We use PyTorch 1.10 for auto-differentiation and numerical optimization. Besides, all the GNNs are implemented with PyTorch Geometric 2.0. We also use PyTorch-Scatter library to handle vector gather-scatter operations. Lastly, we utilize NetworkX for graph data generation and processing.

G   SYNTHETIC DATASET GENERATION

In the experimental study, we evaluate the efficacy of GNNInterpreter on 4 synthetic datasets: Cyclicity, Shape, Motif, and Is_Acyclic. Among them, Cyclicity and Motif are synthetically generated on top of Rome Dataset[2] which has 11534 undirected graphs with 10-100 nodes. The generation procedures for the first 3 synthetic datasets are specified in algorithm 2, algorithm 3, and algorithm 4, respectively. Lastly, Is_Acyclic dataset is a dataset synthetically generated by the XGNN authors (Yuan et al., 2020a).

H   EXPERIMENTAL DETAILS OF GNN CLASSIFIERS

In the experimental study, we adopt GNNInterpreter to explain 5 GNN classifiers which are trained on 5 different datasets. In this section, we will describe some experimental details about the GNN models for all 5 datasets. These experimental details include the model architecture, hyper-parameter settings, and test F1 scores per class obtained by the GNN models.

---

[2]http://www.graphdrawing.org/data.html

Figure 8: The qualitative results for 5 datasets. For each class in all datasets, multiple explanation graphs with the class probability of 1 predicted by the GNNs is displayed. If the dataset has the node feature or edge feature, the different colors in the nodes and edges correspondingly represent different values in the node feature and edge feature.

Algorithm 2: Cyclicity dataset generation procedure

Edge Classes: {RED, GREEN}
Graph Classes: {RED-CYCLIC, GREEN-CYCLIC, ACYCLIC}
Input: Rome Dataset
Output: A collection of pairs consisted of a graph and its label

1 **for** G in Rome Dataset **do**
2   Randomly label each edge in G as RED or GREEN.
3   **if** G is acyclic **then**
4   **yield** (G, ACYCLIC)
5   **break**
6   **end**
7   **while** more than one cycle exists in G **do**
8   Remove a random edge from a random cycle in G.
9   **end**
10   Randomly pick a color $C_{cycle} \in \{$RED, GREEN$\}$.
11   Relable all edges in the remaining cycle in G as C_{cycle}.
12   Randomly pick a color $C_{edge} \in \{$RED, GREEN$\}$.
13   Relable a random edge in the remaining cycle in G as C_{edge}.
14   **if** $C_{cycle} = C_{edge} = $ RED **then**
15   **yield** (G, RED-CYCLIC)
16   **else if** $C_{cycle} = C_{edge} = $ GREEN **then**
17   **yield** (G, GREEN-CYCLIC)
18   **else**
19   **yield** (G, ACYCLIC)
20   **end**
21 **end**

Algorithm 3: Motif dataset generation procedure

Node Classes: {RED, GREEN, ORANGE, BLUE, MAGENTA}
Graph Classes: {HOUSE, HOUSE-X, COMPLETE-4, COMPLETE-5, OTHERS}
Input: Rome Dataset
Output: A collection of pairs consisted of a graph and its label

1 Let $\{G_{\text{HOUSE}}, G_{\text{HOUSE-X}}, G_{\text{COMPLETE-4}}, G_{\text{COMPLETE-5}}\}$ be 4 motifs for the corresponding classes.
2 Define $\bigoplus$ as a graph operator such that $G_1 \bigoplus G_2$ generates a union graph $G_1 \cup G_2$ with an additional edge between a random node in G_1 and a random node in G_2.
3 **for** G in Rome Dataset **do**
4   Randomly select a label $L \in \{$OTHERS, HOUSE, HOUSE-X, COMPLETE-4, COMPLETE-5$\}$.
5   **if** $L = $ OTHERS **then**
6   Let G_{OTHERS} be a random motif in $\{G_{\text{HOUSE}}, G_{\text{HOUSE-X}}, G_{\text{COMPLETE-4}}, G_{\text{COMPLETE-5}}\}$ but with a random edge being removed.
7   **end**
8   **yield** ($G \bigoplus G_L$, L)
9 **end**

H.1 MUTAG

The GNN classifier we implemented for MUTAG dataset is a deep GCN model that contains 3 GCN layers of width 64, a global mean pooling layer, and 2 dense layers in the end. The model uses LeakyReLU as activation. Before training, the model parameters are initialized with Kaiming initializer. During training, AdamW optimizer is used for optimization with learning rate of 0.01 and weight decay of 0.01. The F1 scores for two classes in Table 12 shows that the GNN is more accurate when making decisions on Mutagen class.

H.2 CYCLICITY

The GNN classifier for Cyclicity dataset is a deep NNConv model that contains 5 NNConv layers of width 32 with a single-layered edge network, a global mean pooling layer, and 2 dense layers in the end. Before training, the model parameters are initialized with Kaiming initializer. During training, AdamW optimizer is used for optimization with learning rate of 0.01, learning rate decay of 0.01, and

---

Algorithm 4: Shape dataset generation procedure

Graph Classes: {LOLLIPOP, WHEEL, GRID, STAR, OTHERS}
Output: A collection of pairs consisted of a graph and its label

1 **for** *8000* times **do**
2   Randomly select a label $L \in$ {OTHERS, LOLLIPOP, WHEEL, GRID, STAR}.
3   **switch** L **do**
4   **case** LOLLIPOP **do**
5   Sample lollipop graph G_{LOLLIPOP} with random number of head nodes $n \in \{4, ..., 16\}$ and
              random number of tail nodes $m \in \{4, ..., 16\}$.
6   **case** WHEEL **do**
7   Sample wheel graph G_{WHEEL} with random number of non-center nodes $n \in \{4, ..., 64\}$.
8   **case** GRID **do**
9   Sample grid graph G_{GRID} with random width $w \in \{2, ..., 8\}$ and random height $h \in \{2, ..., 8\}$.
10   **case** STAR **do**
11   Sample star graph G_{STAR} with random number of non-center nodes $n \in \{4, ..., 64\}$.
12   **case** OTHERS **do**
13   Sample Binomial random graph G_{OTHERS} with random number of nodes $n \in \{8, ..., 32\}$ and
              random edge probability $p \in [0.2, 1]$.
14   **end**
15   Add random number of noisy edges to G_L with a random ratio $p \in [0, 0.2]$.
16   **yield** (G_L, L)
17 **end**

---

weight decay of 0.01. As shown in Table 12, all three classes have similar F1 scores, which means that the GNN model have a balanced performance on each class.

H.3   MOTIF

The Motif dataset uses exactly the same model architecture and hyper-parameter settings as MUTAG dataset. The F1 score per class presented in Table 12 indicates that the GNN achieves a perfect performance on Complete-5 class and a near-perfect performance on every other classes.

H.4   SHAPE

The Shape dataset uses the same model architecture and hyper-parameter settings as MUTAG dataset except that the model contains 4 GCN layers instead of 3 GCN layers. Also, the F1 score per class in Table 12 shows that the GNN can perfectly predict the Star class, whereas the predictions for the Lollipop class and the Grid class are less accurate.

H.5   IS_ACYCLIC

The Is_Acyclic dataset uses the same model architecture and hyper-parameter settings as Shape dataset except that max pooling is used instead of mean pooling for the global pooling layer, due to the nature of the task that the class prediction can be very sensitive to local patterns. The model is able to predict both classes perfectly with an F1 score of 1.0.

I   EXPERIMENTAL DETAILS OF GNNINTERPRETER

For all experiments, we choose to set the Concrete Distribution temperature $\tau = 0.2$. We use the sample size $K = 10$ for all Monte Carlo samplings. For optimization, we adopt SGD optimizer with the learning rate of 1 and terminate the learning procedure until convergence. Additionally, in the training objective, the embedding similarity weight μ is set to 1 for every dataset except MUTAG. For MUTAG dataset, we let $\mu = 10$ due to its nature that the structure of the graphs in the dataset needs to follow certain domain-specific rules. A higher value of μ allows the GNNInterpreter to implicitly capture these rules from the average graph embeddings. Speaking of the regularization weight, we employ grid search to obtain the best results under different combinations of regularization terms. To ensure the reproducibility of our experimental results, we also report the exact regularization

Table 12: The F1 score per class of the corresponding GNN classifiers for all datasets.

Dataset	F1 Scores of GNN Classifier			
MUTAG	Mutagen 0.961	Nonmutagen 0.917		
Cyclicity	Red Cyclic 0.995	Green Cyclic 0.992	Acyclic 0.993	
Motif	House 0.998	House-X 0.998	Complete-4 0.996	Complete-5 1.000
Shape	Lollipop 0.969	Wheel 0.994	Grid 0.966	Star 1.000
Is_Acyclic	Cyclic 1.000	Acyclic 1.000		

Table 13: The regularization weights of GNNInterpreter for explaining the GNN models corresponding to each dataset.

Dataset	Class	Regularization Weights			
		R_{L_1}	R_{L_2}	R_b	R_c
MUTAG	Mutagen	10	5	20	1
	Nonmutagen	5	2	10	2
Cyclicity	Red Cyclic	10	5	10000	100
	Green Cyclic	10	5	2000	50
	Acyclic	10	2	5000	50
Motif	House	1	1	5000	0
	House-X	5	2	2000	0
	Complete-4	10	5	10000	1
	Complete-5	10	5	10000	5
Shape	Lollipop	5	5	1	5
	Wheel	10	5	10	0
	Grid	1	1	2	0
	Star	10	2	200	0
Is_Acyclic	Cyclic	0	0	500	0
	Acyclic	1	5	500	5

weights used for all the quantitative and qualitative evaluations from the manuscript in Table 13. Note that we adopt a constant weight strategy for L1 regularization R_{L_1}, L2 regularization R_{L_2}, and connectivity constraint R_c throughout the training process. In contrast, for budget penalty R_b, we employ a 500-iteration initial warm up period to gradually increase the weight starting from 0.