LLMs for POS Tagging in LRLs?
Not there yet

Abstract

Large Language Models are transforming NLP for a lot of tasks. However, how LLMs perform NLP tasks for LRLs is less explored. In alliance with the theme track of the NAACL'24, we focus on 12 low-resource languages (LRLs) from Brazil, 2 LRLs from Africa and 2 high-resource languages (HRLs) (e.g., English and Brazilian Portuguese). Our results indicate that the LLMs perform worse for the labeling of LRLs in comparison to HRLs in general. We explain the reasons behind this failure and provide an error analyses through examples from 2 Brazilian LRLs.

1 Introduction

We are currently witnessing major transformations in language technologies and natural language processing (NLP) methods through large language models (LLMs). Despite numerous advancements in the area, NLP research and available resources mainly cover 20 out of the estimated 7,000 languages (Magueresse et al., 2020). As a result, majority of world languages can be considered as "low-resource".

Being a low-resource language encompasses different types of inadequacies with respect to the availability of data for creating language technology (Gupta, 2022). In alliance with the theme track of NAACL24, we focus on the automatic annotation of texts in low-resource languages (LRLs) in South America. More specifically, we test the performance of LLMs for annotating part-of-speech (POS) tagging for 12 LRLs from Brazil and make a comparison with 2 LRLs from Africa and 2 high resource languages (HRLs) (e.g., English and Brazilian Portuguese) through human evaluation.

The evaluation is challenging for two reasons. First, there is a lack of benchmark datasets for these indigenous Brazilian languages, we only found benchmark datasets in universal dependencies (UD). [1] However, they do not have the training data to fine-tune multilingual language models and we can only leverage prompting LLMs or cross-lingual transfer through multilingual language models. Secondly, there is a lack of large monolingual data to benefit from effective multilingual and cross-lingual transfer techniques (Pfeiffer et al., 2020; Ansell et al., 2022; Alabi et al., 2022). We only found the Bible corpora with less than 35K sentences for 7 out of the 12 languages.

In this paper, we perform evaluation on 12 Brazilian languages by prompting GPT-4 LLM and cross-lingual transfer individually from English and Brazilian Portuguese leveraging XLM-R. The results of both methods indicate low performance (less than 34.0% while high-resource languages achieved over 90.0%), however, GPT-4 leads to better results. Moreover, Brazilian Portuguese performs better than English in zero-shot evaluation. Furthermore, to boost the performance of cross-lingual transfer, we perform language adaptation using XLM-R on each language, before fine-tuning Brazilian Portuguese, and evaluating on that language. This boosts the performance by $+3$ to $+12.0$ points on six out of seven languages. Our findings suggest that cross-lingual transfer to these languages are very challenging, and having a few training examples may further boost the performance. This calls for most investment in building NLP resources across different tasks for these endangered languages.

1.1 Multilingualism in Brazil

Brazil is the 5th largest country of the world (qua land area) with a population of 203 million[2] and a highly multilingual country. Although (Brazilian)

---

[1] https://universaldependencies.org/
[2] Instituto Brasileiro de Geografia e Estatística. 2023. https://www.ibge.gov.br/en/cities-and-states.html. Accessed: 2023-12-15

Portuguese is the official language today, there are approx. 160 native/indigenous languages (e.g., in the Amazon area) as well as sign and immigrant languages.[3]

Following Rodrigues (1986), the two macro-language families among Brazilian native languages are Tupi (8 language families, 52 languages), and Macro-Jê (7 language families, 39 languages). There are also several large language families (e.g., Karib (21 languages), Arawak (20 languages), Arawá (7 languages), Tukano, Maku, and Yanomami), six smaller language families to the south of the Amazon river (e.g., Guaikurú (1 language), Nambikwára (3 languages), Txapakura (3 languages), Pano (13 languages), Múra (2 languages), and Matukína (4 languages)) and approx. 10 languages which are not part of any these families.

These languages share grammatical properties due to family inheritance orareal contact (Aikhenvald, 2002). In terms of morphology, most of these languages are polysynthetic, head-marking, and agglutinating with little fusion (Dixon and Aikhenvald, 1999; Hengeveld et al., 2007). In term of syntax, there is quite some variation in terms of word order among these languages(Campbell, 2012).

2 Literature Overview

In general, Brazilian native languages are understudied and they are low resource. For the labelled datasets, we only found datasets for UD tasks: Gerardi et al. (2022) developed for TUDET UD treebanks covering 8 Tupian languages, other languages in UD covered are Apurina (Hämäläinen et al., 2021), Bororo, Madi-Jarawara, and Xavante. The last three treebanks were contributed by the TUDET team. For monolingual data, we found seven Bible corpora on the eBible corpus (Akerman et al., 2023) that are freely available. All languages lack a large monolingual corpus which makes it very challenging for cross-lingual transfer and multilingual pre-training of LLMs.

In terms of evaluation, some studies have already shown the potential of prompting LLMs in multilingual settings (Ahuja et al., 2023a; Lai et al., 2023), including a few low-resource languages (Ojo et al., 2023; Ahuja et al., 2023b). However, we did not find any evaluations covering the LRLs of Brazil. Hence, this is our contribution for this paper.

3 Experimental setup

We focus our evaluation on POS tagging (a subtask of universal dependencies (UD)) due to the simplicity of the task, its popularity, and the availability of the test evaluation datasets in UD .[4] We describe the evaluation dataset and the models used in the subsections below.

3.1 Evaluation Datasets

While there are many languages in UD (Zeman et al., 2023), many under-resourced languages only have a test set because of their limited sizes (less than 10k tokens). All the Brazilian languages we evaluated on have less than 13k tokens. The only language with more than 10K in our evaluation is Nheengatu with 12,621 tokens. We evaluated 12 indigenous Brazilian languages and 2 African languages for a comparison across other regions with low-resource languages. Finally, we added 2 high-resource languages (HRL) (i.e., English and Brazilian Portuguese). Our definition of HRL is based on the size of unlabelled data on the web. The larger their size are, the more likely they are included in pre-training of the LLMs [5] and multilingual pre-trained LMs (Conneau et al., 2020).

Table 1 shows the languages in our evaluation, their language family, availability of monolingual corpus or Bible corpus in that language, UD dataset, and sizes. We collected the Bible corpus from the eBible website and make use of this corpus for language adaptation. We have two test sets in our evaluation: (1) **Test set A** is the original test set in the UD benchmark (2) **Test set B** is a subsample of Test set A where we removed sentences that GPT-4 fails to provide predictions for mostly due to not properly identifying the language. We added this information for a fair comparison of the methods (,i.e. using the same number of sentences in evaluation).

3.2 Models

For the experiments, we consider three approaches that are popular in the zero-shot setting since we lack the training data for the Brazilian languages. More details are provided in Appendix A.

Prompting GPT-4 We prompt GPT-4 using a similar prompt provided by Lai et al. (2023) where

---

[3]PIB. 2023. `https://pib.socioambiental.org/pt/Linguas`. Accessed: 2023-12-15

[4]`https://universaldependencies.org/`
[5]`https://help.openai.com/en/articles/8357869-chatgpt-language-support-alpha-web`

Language	Language family	Monolingual data size	UD dataset name	Train	Dev	Test set A	Test set B
high-resource languages							
English (en)	Indo-European/West Germanic	not collected	en_ewt	12,544	2,001	2,007	-
Portuguese (pt)	Indo-European/Romance	not collected	pt_gsd	9,616	1,204	1,200	-
Brazilian languages							
Apurina (apu)	Arawakan	Bible (8,729)	apu_ufpa	-	-	152	134
Akuntsu (aqz)	Tupian	N/A	aqz_tudet	-	-	343	267
Karo (arr)	Tupian	N/A	arr_tudet	-	-	674	172
Bororo (bor)	Macro-Jê	Bible (8,254)	bor_bdt	-	-	371	161
Guajajara (gub)	Tupian	Bible (33,757)	gub_tudet	-	-	1,182	914
Madi-Jarawara (jaa)	Arawan	Bible (8,606)	jaa_jarawara	-	-	20	18
Makurap (mpu)	Tupian	N/A	mpu_tudet	-	-	37	8
Munduruku(myu)	Tupian	Bible (8,430)	myu_tudet	-	-	158	82
Tupinamba (tpn)	Tupian	N/A	tpn_tudet	-	-	581	458
Kaapor (urb)	Tupian	Bible (8,535)	urb_tudet	-	-	83	20
Xavante (xav)	Macro-Jê	Bible (8,213)	xav_xdt	-	-	148	128
Nheengatu (yrl)	Tupian	N/A	yrl_complin	-	-	1239	-
African languages							
Wolof (wo)	Niger-Congo/Senegambian	not collected	wo_wtb	1188	449	470	-
Yoruba (yo)	Niger-Congo/Volta-Niger	not collected	yo_ytb	-	-	318	-

Table 1: **UD-POS datasets in our evaluation:** We provide the training, validation and test splits we used for experiments. Test set A are the original test set in UD, the Test set B is a subset of A where we removed sentences that GPT-4 is not able to run inference for due to non-identification of the language.

the model is provided a task description before the input. We provide the details in Appendix B.

Cross-lingual transfer We trained a POS tagger individually for English and Portuguese, and perform the zero-shot transfer on other languages. We make use of the XLM-R-large (or simply, XLM-R) (Conneau et al., 2020) for training the models.

Language Adaptive Fine-tuning (LAFT) We leverage LAFT for an effective cross-lingual transfer by first adapting XLM-R-large model to a new language with limited amount of monolingual data (Alabi et al., 2020; Pfeiffer et al., 2020; Chau and Smith, 2021). We make use of the Bible data as the fine-tuning corpus since it is the largest one for these languages and we only found 7 (out of 12 Brazilian languages) languages which have a Bible corpus. Similar to Ebrahimi and Kann (2021), we examine the effectiveness of this small pre-training corpus with 8K-34K sentences. According to Pfeiffer et al. (2020), this approach can significantly boost cross-lingual transfer. However, it is not parameter-efficient like the MAD-X they proposed. On the other hand, Ebrahimi and Kann (2021) argued that simple adaptation to a new language is more effective than MAD-X especially when using the Bible corpus for adaptation and we follow this recommendation in our evaluation.

4 Results

Table 2 shows the result of our evaluation on POS tagging with the following key findings:

Zero-shot evaluation results While POS tagging can have a performance of 98% (e.g. for English and Portuguese) when training data are available (especially for HRLs), the performance decreases while performing zero-shot transfer to other languages because POS tagging is language-specific. The transfer performance is low for both Brazilian and African languages (probably) because they are not linguistically related unlike English and Portuguese that are slightly related (i.e., Indo-European famiily) and covered by XLM-R, thus achieving an impressive transfer performance ($> +83\%$).

GPT-4 vs. basic cross-lingual transfer GPT-4 performed slightly better than the zero-shot transfer from other languages in our experiments indicating better abilities of LLMs for this task. For English and Portuguese, the performance reaches to 90% (although it is not on par with fully-supervised setting). For African languages, the performance was lower than the HRLs, but still was decent (64.8-75.4) probably because the LLMs were exposed to some African languages during pre-training. The struggle of GPT-4 for Brazilian LRLs can be explained with the fact that these languages were probably not included during the pre-training. The generation is often not useful for some examples, where GPT-4 declines to give answers like "*As an AI, I'm unable to provide the POS tags for words in languages I'm not programmed to understand.*". Thus, we had to remove such examples from our evaluation. However, this was not the case for African LRLs and the HRLs.

| | XLM-R Test set A | XLM-R (zero-shot cross-lingual transfer) | | | | | | GPT-4 Test set B |
| | | Test set A | | | Test set B | | | |
Language	Full-sup.	en→ xx	pt→ xx	LAFT + pt→ xx	en→ xx	pt→ xx	LAFT + pt→ xx	0-shot
high-resource languages								
en_ewt	**98.0**	**98.0**	83.6			91.9		
pt_gsd	**97.8**	90.0	**97.8**			92.4		
Brazilian languages								
apu_ufpa	-	37.5	40.6	**44.9**	36.8	40.2	**44.7**	42.6
aqz_tudet	-	31.9	37.8		31.3	36.8		**49.5**
arr_tudet	-	3.9	14.9		6.3	19.8		**27.7**
bor_bdt	-	19.0	23.5	27.3	18.4	23.0	26.4	**41.3**
gub_tudet	-	26.5	30.2	36.0	27.8	32.1	**37.1**	36.2
jaa_jarawara	-	28.2	28.4	**34.5**	27.2	27.9	33.6	**33.0**
mpu_tudet	-	4.9	**9.0**		0.0	0.8		0.0
myu_tudet	-	21.2	27.1	**30.3**	10.8	14.8	16.5	18.2
tpn_tudet	-	39.1	41.9		38.9	41.8		**47.2**
urb_tudet	-	7.8	11.8	21.2	9.2	9.5	21.6	**32.3**
xav_xdt	-	26.5	29.0	28.2	27.3	29.9	29.3	**36.5**
yrl_complin	-	28.9	31.5		29.0	31.7		**41.2**
African languages								
wo_wtb	**87.6**	29.3	35.6			64.8		
yo_ytb	-	22.5	31.5			**75.4**		
Average (Brazilian languages)	-	23.0	27.1		21.9	25.7		33.8

Table 2: **POS accuracy results for Brazilian languages:** We compare the accuracy of GPT-4 to zero-shot cross-lingual transfer from English language and Portuguese leveraging XLM-R-large multilingual pre-trained language model. Test set A is the original test set found on UD while Test set B are the ones GPT-4 could automatically detect their language to run inference.

Language adaptation for cross-lingual transfer performance We performed LAFT training on the Bible corpus individually for the *apu*, *bor*, *gub*, *jaa*, *myu*, *urb*, and *xav*. Our results indicate an improvement in accuracy on 6 out of the 7 languages, except for *xav*. The performance improvement is quite large for *urb* (+7.2 on test A, and 12.1 on Test B), and moderate improvement of +3 to +6 for other languages. This experimental result shows that with sufficient monolingual texts, we can increase the performance of the cross-lingual transfer results. However, for the LRLs, such data is scarce. A more effective approach is perhaps to annotate few examples (e.g. 10 or 100 sentences) for training POS taggers to boost the performance (cf. (Lauscher et al., 2020; Hedderich et al., 2020) for a larger boost in performance for token classification tasks in this few-short setting). Regardless, there is a need for better methods to leverage small monolingual data sets.

5 Error analysis

In this section, we provide examples from 2 Brazilian languages (Karo and Guajajara) where the LLMs made errors with the POS tagging. The first linerefers to the original sentence, the second line refers to the gold-standard UD POS tag; the third line refers to the GPT-4 POS tag.)

In example (1), the auxiliary verb (in Karo) has the same orthographic form as the English interjection *okay*. In example (2), the Guajajara verb has (partially) the same orthographic form as the English interjection (*oh*). Due to these similarities, GPT-4 seems to tag the POS for these words according to English instead of the POS tagged in UD for Karo and Guajajara.

1. awero toba **okay**
   NOUN VERB **AUX**
   NOUN NOUN **INTJ**

2. **Oho** kaapii rehe.
   VERB NOUN ADPPUNCT
   INT VERB ADVPUNCT

6 Discussion & Conclusions

In our study, we explored how LLMs perform the task of POS tagging for 12 LRLs in Brazil and compared this performance with 2 LRLs in Africa and 2 HRLs (English, Brazilian Portuguese). Our results indicate that the LLMs perform worse for LRLs on this task in general. In addition, with the lack of available data, any improvements across methods are also not feasible. Although we focused on 12 Brazilian LRLs, there are many other LRLs which we were not able to cover. Future work can expand this task (and others) to other LRLs not only from Brazil but from other regions as well.

7 Limitations

Due to limited space, we only focused on POS tagging for this paper but there is a need to explore how LLMs perform other NLP tasks for LRLs. We only evaluated ChatGPT in the zero-shot learning setting but we do not have comparisons with other recent multilingual LLMs, e.g., BLOOM (Scao et al., 2022), GPT-4, and BARD, in various other learning scenarios. While some of these models are currently less accessible for large-scale evaluations, our plan is to include more models and learning settings along the way to strengthen our evaluations and comparisons in the future. Finally, the current work only evaluates ChatGPT in terms of performance over NLP tasks in different languages. To better characterize ChatGPT and LLMs, other evaluation metrics should also be investigated to report more complete perspectives for multilingual learning, including but not limited to adversarial robustness, biases, toxic/harmful content, hallucination, accessibility, development costs, and interoperability.

8 Ethics Issues

Since we used publicly available data sets, we do not foresee any major issues in terms of ethical concerns.

References

David Ifeoluwa Adelani, Jade Abbott, Graham Neubig, Daniel D'souza, Julia Kreutzer, Constantine Lignos, Chester Palen-Michel, Happy Buzaaba, Shruti Rijhwani, Sebastian Ruder, Stephen Mayhew, Israel Abebe Azime, Shamsuddeen H. Muhammad, Chris Chinenye Emezue, Joyce Nakatumba-Nabende, Perez Ogayo, Aremu Anuoluwapo, Catherine Gitau, Derguene Mbaye, Jesujoba Alabi, Seid Muhie Yimam, Tajuddeen Rabiu Gwadabe, Ignatius Ezeani, Rubungo Andre Niyongabo, Jonathan Mukiibi, Verrah Otiende, Iroro Orife, Davis David, Samba Ngom, Tosin Adewumi, Paul Rayson, Mofetoluwa Adeyemi, Gerald Muriuki, Emmanuel Anebi, Chiamaka Chukwuneke, Nkiruka Odu, Eric Peter Wairagala, Samuel Oyerinde, Clemencia Siro, Tobius Saul Bateesa, Temilola Oloyede, Yvonne Wambui, Victor Akinode, Deborah Nabagereka, Maurice Katusiime, Ayodele Awokoya, Mouhamadane MBOUP, Dibora Gebreyohannes, Henok Tilaye, Kelechi Nwaike, Degaga Wolde, Abdoulaye Faye, Blessing Sibanda, Orevaoghene Ahia, Bonaventure F. P. Dossou, Kelechi Ogueji, Thierno Ibrahima DIOP, Abdoulaye Diallo, Adewale Akinfaderin, Tendai Marengereke, and Salomey Osei. 2021. MasakhaNER: Named entity recognition for African languages. *Transactions of the Association for Computational Linguistics*, 9:1116–1131.

Kabir Ahuja, Harshita Diddee, Rishav Hada, Millicent Ochieng, Krithika Ramesh, Prachi Jain, Akshay Nambi, Tanuja Ganu, Sameer Segal, Mohamed Ahmed, Kalika Bali, and Sunayana Sitaram. 2023a. MEGA: Multilingual evaluation of generative AI. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 4232–4267, Singapore. Association for Computational Linguistics.

Sanchit Ahuja, Divyanshu Aggarwal, Varun Gumma, Ishaan Watts, Ashutosh Sathe, Millicent Ochieng, Rishav Hada, Prachi Jain, Maxamed Axmed, Kalika Bali, et al. 2023b. Megaverse: Benchmarking large language models across languages, modalities, models and tasks. *arXiv preprint arXiv:2311.07463*.

Alexandra Y. Aikhenvald. 2002. *Language contact in Amazonia*. Oxford University Press.

Vesa Akerman, David Baines, Damien Daspit, Ulf Hermjakob, Tae Young Jang, Colin Leong, Michael Martin, Joel Mathew, Jonathan Robie, and Marcus Schwarting. 2023. The ebible corpus: Data and model benchmarks for bible translation for low-resource languages. *ArXiv*, abs/2304.09919.

Jesujoba Alabi, Kwabena Amponsah-Kaakyire, David Adelani, and Cristina España-Bonet. 2020. Massive vs. curated embeddings for low-resourced languages: the case of Yorùbá and Twi. In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 2754–2762, Marseille, France. European Language Resources Association.

Jesujoba O. Alabi, David Ifeoluwa Adelani, Marius Mosbach, and Dietrich Klakow. 2022. Adapting pre-trained language models to African languages via multilingual adaptive fine-tuning. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 4336–4349, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.

Alan Ansell, Edoardo Ponti, Anna Korhonen, and Ivan Vulić. 2022. Composable sparse fine-tuning for cross-lingual transfer. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1778–1796, Dublin, Ireland. Association for Computational Linguistics.

Lyle Campbell. 2012. Typological characteristics of south american indigenous languages. *The indigenous languages of South America: A comprehensive guide*, pages 259–330.

Ethan C. Chau and Noah A. Smith. 2021. Specializing multilingual language models: An empirical study. In *Proceedings of the 1st Workshop on Multilingual Representation Learning*, pages 51–61, Punta Cana, Dominican Republic. Association for Computational Linguistics.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, Online. Association for Computational Linguistics.

R. M. W. Dixon and Alexandra Y. Aikhenvald. 1999. *The Amazonian Languages*. Cambridge University Press.

Abteen Ebrahimi and Katharina Kann. 2021. How to adapt your pretrained multilingual model to 1600 languages. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 4555–4567, Online. Association for Computational Linguistics.

Fabrício Ferraz Gerardi, Stanislav Reichert, Carolina Aragon, Lorena Martín-Rodríguez, Gustavo Godoy, and Tatiana Merzhevich. 2022. Tudet: Tupían dependency treebank.

Akshat Gupta. 2022. On building spoken language understanding systems for low resourced languages. In *Proceedings of the 19th SIGMORPHON Workshop on Computational Research in Phonetics, Phonology, and Morphology*, pages 1–11, Seattle, Washington. Association for Computational Linguistics.

Mika Hämäläinen, University of Helsinki, Niko Partanen, and Khalid Alnajjar, editors. 2021. *Multilingual Facilitation*. University of Helsinki.

Michael A. Hedderich, David Adelani, Dawei Zhu, Jesujoba Alabi, Udia Markus, and Dietrich Klakow. 2020. Transfer learning and distant supervision for multilingual transformer models: A study on African languages. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2580–2591, Online. Association for Computational Linguistics.

Kees Hengeveld et al. 2007. Parts-of-speech systems and morphological types. *ACLC Working Papers Volume 2, issue*, page 31.

Viet Lai, Nghia Ngo, Amir Pouran Ben Veyseh, Hieu Man, Franck Dernoncourt, Trung Bui, and Thien Nguyen. 2023. ChatGPT beyond English: Towards a comprehensive evaluation of large language models in multilingual learning. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 13171–13189, Singapore. Association for Computational Linguistics.

Anne Lauscher, Vinit Ravishankar, Ivan Vulić, and Goran Glavaš. 2020. From zero to hero: On the limitations of zero-shot language transfer with multilingual Transformers. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4483–4499, Online. Association for Computational Linguistics.

Alexandre Magueresse, Vincent Carles, and Evan Heetderks. 2020. Low-resource languages: A review of past work and future challenges.

Benjamin Muller, Antonios Anastasopoulos, Benoît Sagot, and Djamé Seddah. 2021. When being unseen from mBERT is just the beginning: Handling new languages with multilingual language models. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 448–462, Online. Association for Computational Linguistics.

Jessica Ojo, Kelechi Ogueji, Pontus Stenetorp, and David I Adelani. 2023. How good are large language models on african languages? *arXiv preprint arXiv:2311.07978*.

Jonas Pfeiffer, Ivan Vulić, Iryna Gurevych, and Sebastian Ruder. 2020. MAD-X: An Adapter-Based Framework for Multi-Task Cross-Lingual Transfer. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7654–7673, Online. Association for Computational Linguistics.

Aryon Dall'lgna Rodrigues. 1986. *Línguas Brasileiras: para o conhecimento das línguas indígenas*. São Paulo: Edições Loyola.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander Rush. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online. Association for Computational Linguistics.

Daniel Zeman, Joakim Nivre, Mitchell Abrams, Elia Ackermann, Noëmi Aepli, Hamid Aghaei, Željko Agić, Amir Ahmadi, Lars Ahrenberg, Chika Kennedy Ajede, Salih Furkan Akkurt, Gabrielė Aleksandravičiūtė, Ika Alfina, Avner Algom, Khalid Alnajjar, Chiara Alzetta, Erik Andersen, Lene Antonsen, Tatsuya Aoyama, Katya Aplonova, Angelina Aquino, Carolina Aragon, Glyd Aranes, Maria Jesus Aranzabe, Bilge Nas Arıcan, H̃órunn Arnardóttir, Gashaw Arutie, Jessica Naraiswari Arwidarasti, Masayuki Asahara, Katla Ásgeirsdóttir, Deniz Baran Aslan, Cengiz Asmazoğlu, Luma Ateyah, Furkan Atmaca, Mohammed Attia, Aitziber Atutxa, Liesbeth Augustinus, Mariana Avelãs, Elena Badmaeva, Keerthana Balasubramani, Miguel Ballesteros, Esha Banerjee, Sebastian Bank, Verginica Barbu Mititelu,

Starkaur Barkarson, Rodolfo Basile, Victoria Basmov, Colin Batchelor, John Bauer, Seyyit Talha Bedir, Shabnam Behzad, Juan Belieni, Kepa Bengoetxea, İbrahim Benli, Yifat Ben Moshe, Gözde Berk, Riyaz Ahmad Bhat, Erica Biagetti, Eckhard Bick, Agnė Bielinskienė, Kristín Bjarnadóttir, Rogier Blokland, Victoria Bobicev, Loïc Boizou, Emanuel Borges Völker, Carl Börstell, Cristina Bosco, Gosse Bouma, Sam Bowman, Adriane Boyd, Anouck Braggaar, António Branco, Kristina Brokaitė, Aljoscha Burchardt, Marisa Campos, Marie Candito, Bernard Caron, Gauthier Caron, Catarina Carvalheiro, Rita Carvalho, Lauren Cassidy, Maria Clara Castro, Sérgio Castro, Tatiana Cavalcanti, Gülşen Cebiroğlu Eryiğit, Flavio Massimiliano Cecchini, Giuseppe G. A. Celano, Slavomír Čéplö, Neslihan Cesur, Savas Cetin, Özlem Çetinoğlu, Fabricio Chalub, Liyanage Chamila, Shweta Chauhan, Ethan Chi, Taishi Chika, Yongseok Cho, Jinho Choi, Jayeol Chun, Juyeon Chung, Alessandra T. Cignarella, Silvie Cinková, Aurélie Collomb, Çağrı Çöltekin, Miriam Connor, Claudia Corbetta, Daniela Corbetta, Francisco Costa, Marine Courtin, Benoît Crabbé, Mihaela Cristescu, Vladimir Cvetkoski, Ingerid Løyning Dale, Philemon Daniel, Elizabeth Davidson, Leonel Figueiredo de Alencar, Mathieu Dehouck, Martina de Laurentiis, Marie-Catherine de Marneffe, Valeria de Paiva, Mehmet Oguz Derin, Elvis de Souza, Arantza Diaz de Ilarraza, Carly Dickerson, Arawinda Dinakaramani, Elisa Di Nuovo, Bamba Dione, Peter Dirix, Kaja Dobrovoljc, Adrian Doyle, Timothy Dozat, Kira Droganova, Magali Sanches Duran, Puneet Dwivedi, Christian Ebert, Hanne Eckhoff, Masaki Eguchi, Sandra Eiche, Marhaba Eli, Ali Elkahky, Binyam Ephrem, Olga Erina, Tomaž Erjavec, Farah Essaidi, Aline Etienne, Wograine Evelyn, Sidney Facundes, Richárd Farkas, Federica Favero, Jannatul Ferdaousi, Marília Fernanda, Hector Fernandez Alcalde, Amal Fethi, Jennifer Foster, Theodorus Fransen, Cláudia Freitas, Kazunori Fujita, Katarína Gajdošová, Daniel Galbraith, Federica Gamba, Marcos Garcia, Moa Gärdenfors, Fabrício Ferraz Gerardi, Kim Gerdes, Luke Gessler, Filip Ginter, Gustavo Godoy, Iakes Goenaga, Koldo Gojenola, Memduh Gökırmak, Yoav Goldberg, Xavier Gómez Guinovart, Berta González Saavedra, Bernadeta Griciūtė, Matias Grioni, Loïc Grobol, Normunds Grūzītis, Bruno Guillaume, Kirian Guiller, Céline Guillot-Barbance, Tunga Güngör, Nizar Habash, Hinrik Hafsteinsson, Jan Hajič, Jan Hajič jr., Mika Hämäläinen, Linh Hà Mỹ, Na-Rae Han, Muhammad Yudistira Hanifmuti, Takahiro Harada, Sam Hardwick, Kim Harris, Dag Haug, Johannes Heinecke, Oliver Hellwig, Felix Hennig, Barbora Hladká, Jaroslava Hlaváčová, Florinel Hociung, Petter Hohle, Yidi Huang, Marivel Huerta Mendez, Jena Hwang, Takumi Ikeda, Anton Karl Ingason, Radu Ion, Elena Irimia, Ọlájídé Ishola, Artan Islamaj, Kaoru Ito, Sandra Jagodzińska, Siratun Jannat, Tomáš Jelínek, Apoorva Jha, Katharine Jiang, Anders Johannsen, Hildur Jónsdóttir, Fredrik Jørgensen, Markus Juutinen, Hüner Kaşıkara, Nadezhda Kabaeva, Sylvain Kahane, Hiroshi Kanayama, Jenna Kanerva, Neslihan Kara, Ritván Karahóğa, Andre Kåsen, Tolga Kayadelen, Sarveswaran Kengatharaiyer, Václava Kettnerová, Lilit Kharatyan, Jesse Kirchner, Elena Klementieva, Elena Klyachko, Petr Kocharov, Arne Köhn, Abdullatif Köksal, Kamil Kopacewicz, Timo Korkiakangas, Mehmet Köse, Alexey Koshevoy, Natalia Kotsyba, Jolanta Kovalevskaitė, Simon Krek, Parameswari Krishnamurthy, Sandra Kübler, Adrian Kuqi, Oğuzhan Kuyrukçu, Aslı Kuzgun, Sookyoung Kwak, Kris Kyle, Käbi Laan, Veronika Laippala, Lorenzo Lambertino, Tatiana Lando, Septina Dian Larasati, Alexei Lavrentiev, John Lee, Phng Lê H`ông, Alessandro Lenci, Saran Lertpradit, Herman Leung, Maria Levina, Lauren Levine, Cheuk Ying Li, Josie Li, Keying Li, Yixuan Li, Yuan Li, KyungTae Lim, Bruna Lima Padovani, Yi-Ju Jessica Lin, Krister Lindén, Yang Janet Liu, Nikola Ljubešić, Irina Lobzhanidze, Olga Loginova, Lucelene Lopes, Stefano Lusito, Andry Luthfi, Mikko Luukko, Olga Lyashevskaya, Teresa Lynn, Vivien Macketanz, Menel Mahamdi, Jean Maillard, Ilya Makarchuk, Aibek Makazhanov, Michael Mandl, Christopher Manning, Ruli Manurung, Büşra Marşan, Cătălina Mărănduc, David Mareček, Katrin Marheinecke, Stella Markantonatou, Héctor Martínez Alonso, Lorena Martín Rodríguez, André Martins, Cláudia Martins, Jan Mašek, Hiroshi Matsuda, Yuji Matsumoto, Alessandro Mazzei, Ryan McDonald, Sarah McGuinness, Gustavo Mendonça, Tatiana Merzhevich, Niko Miekka, Aaron Miller, Karina Mischenkova, Anna Missilä, Cătălin Mititelu, Maria Mitrofan, Yusuke Miyao, AmirHossein Mojiri Foroushani, Judit Molnár, Amirsaeid Moloodi, Simonetta Montemagni, Amir More, Laura Moreno Romero, Giovanni Moretti, Shinsuke Mori, Tomohiko Morioka, Shigeki Moro, Bjartur Mortensen, Bohdan Moskalevskyi, Kadri Muischnek, Robert Munro, Yugo Murawaki, Kaili Müürisep, Pinkey Nainwani, Mariam Nakhlé, Juan Ignacio Navarro Horñiacek, Anna Nedoluzhko, Gunta Nešpore-Bērzkalne, Manuela Nevaci, Lng Nguyễn Thị, Huyền Nguyễn Thị Minh, Yoshihiro Nikaido, Vitaly Nikolaev, Rattima Nitisaroj, Alireza Nourian, Maria das Graças Volpe Nunes, Hanna Nurmi, Stina Ojala, Atul Kr. Ojha, Hulda Óladóttir, Adédayọ Olúòkun, Mai Omura, Emeka Onwuegbuzia, Noam Ordan, Petya Osenova, Robert Östling, Lilja Øvrelid, Şaziye Betül Özateş, Merve Özçelik, Arzucan Özgür, Balkız Öztürk Başaran, Teresa Paccosi, Alessio Palmero Aprosio, Anastasia Panova, Thiago Alexandre Salgueiro Pardo, Hyunji Hayley Park, Niko Partanen, Elena Pascual, Marco Passarotti, Agnieszka Patejuk, Guilherme Paulino-Passos, Giulia Pedonese, Angelika Peljak-Łapińska, Siyao Peng, Siyao Logan Peng, Rita Pereira, Sílvia Pereira, Cenel-Augusto Perez, Natalia Perkova, Guy Perrier, Slav Petrov, Daria Petrova, Andrea Peverelli, Jason Phelan, Claudel Pierre-Louis, Jussi Piitulainen, Yuval Pinter, Clara Pinto, Rodrigo Pintucci, Tommi A Pirinen, Emily Pitler, Magdalena Plamada, Barbara Plank, Thierry Poibeau, Larisa Ponomareva, Martin Popel, Lauma

Pretkalniņa, Sophie Prévost, Prokopis Prokopidis, Adam Przepiórkowski, Robert Pugh, Tiina Puolakainen, Sampo Pyysalo, Peng Qi, Andreia Querido, Andriela Rääbis, Alexandre Rademaker, Mizanur Rahoman, Taraka Rama, Loganathan Ramasamy, Carlos Ramisch, Joana Ramos, Fam Rashel, Mohammad Sadegh Rasooli, Vinit Ravishankar, Livy Real, Petru Rebeja, Siva Reddy, Mathilde Regnault, Georg Rehm, Arij Riabi, Ivan Riabov, Michael Rießler, Erika Rimkutė, Larissa Rinaldi, Laura Rituma, Putri Rizqiyah, Luisa Rocha, Eiríkur Rögnvaldsson, Ivan Roksandic, Mykhailo Romanenko, Rudolf Rosa, Valentin Roșca, Davide Rovati, Ben Rozonoyer, Olga Rudina, Jack Rueter, Kristján Rúnarsson, Shoval Sadde, Pegah Safari, Aleksi Sahala, Shadi Saleh, Alessio Salomoni, Tanja Samardžić, Stephanie Samson, Manuela Sanguinetti, Ezgi Sanıyar, Dage Särg, Marta Sartor, Mitsuya Sasaki, Baiba Saulīte, Agata Savary, Yanin Sawanakunanon, Shefali Saxena, Kevin Scannell, Salvatore Scarlata, Emmanuel Schang, Nathan Schneider, Sebastian Schuster, Lane Schwartz, Djamé Seddah, Wolfgang Seeker, Mojgan Seraji, Syeda Shahzadi, Mo Shen, Atsuko Shimada, Hiroyuki Shirasu, Yana Shishkina, Muh Shohibussirri, Maria Shvedova, Janine Siewert, Einar Freyr Sigursson, João Silva, Aline Silveira, Natalia Silveira, Sara Silveira, Maria Simi, Radu Simionescu, Katalin Simkó, Mária Šimková, Haukur Barri Símonarson, Kiril Simov, Dmitri Sitchinava, Ted Sither, Maria Skachedubova, Aaron Smith, Isabela Soares-Bastos, Per Erik Solberg, Barbara Sonnenhauser, Shafi Sourov, Rachele Sprugnoli, Vivian Stamou, Steinhór Steingrímsson, Antonio Stella, Abishek Stephen, Milan Straka, Emmett Strickland, Jana Strnadová, Alane Suhr, Yogi Lesmana Sulestio, Umut Sulubacak, Shingo Suzuki, Daniel Swanson, Zsolt Szántó, Chihiro Taguchi, Dima Taji, Fabio Tamburini, Mary Ann C. Tan, Takaaki Tanaka, Dipta Tanaya, Mirko Tavoni, Samson Tella, Isabelle Tellier, Marinella Testori, Guillaume Thomas, Sara Tonelli, Liisi Torga, Marsida Toska, Trond Trosterud, Anna Trukhina, Reut Tsarfaty, Utku Türk, Francis Tyers, Sveinbjörn Hórarson, Vilhjálmur Horsteinsson, Sumire Uematsu, Roman Untilov, Zdeňka Urešová, Larraitz Uria, Hans Uszkoreit, Andrius Utka, Elena Vagnoni, Sowmya Vajjala, Socrates Vak, Rob van der Goot, Martine Vanhove, Daniel van Niekerk, Gertjan van Noord, Viktor Varga, Uliana Vedenina, Giulia Venturi, Eric Villemonte de la Clergerie, Veronika Vincze, Natalia Vlasova, Aya Wakasa, Joel C. Wallenberg, Lars Wallin, Abigail Walsh, Jonathan North Washington, Maximilan Wendt, Paul Widmer, Shira Wigderson, Sri Hartati Wijono, Vanessa Berwanger Wille, Seyi Williams, Mats Wirén, Christian Wittern, Tsegay Woldemariam, Tak-sum Wong, Alina Wróblewska, Qishen Wu, Mary Yako, Kayo Yamashita, Naoki Yamazaki, Chunxiao Yan, Koichi Yasuoka, Marat M. Yavrumyan, Arife Betül Yenice, Olcay Taner Yıldız, Zhuoran Yu, Arlisa Yuliawati, Zdeněk Žabokrtský, Shorouq Zahra, Amir Zeldes, He Zhou, Hanzhi Zhu, Yilun Zhu, Anna Zhuravleva, and Rayan Ziane. 2023. Universal dependencies 2.13. LINDAT/CLARIAH-CZ digital library at the Institute of Formal and Applied Linguistics (ÚFAL), Faculty of Mathematics and Physics, Charles University.

A Models

For the experiments, we consider three approaches that are popular in the zero-shot setting since we lack training data for the Brazilian languages.

Prompting GPT-4   GPT-4 [6] is a large language model developed by pre-training on a large amount of texts and code from the web, followed by instruction prompt tuning based on human feedback. We prompt GPT-4 using a similar prompt provided by Lai et al. (2023) where the model is provided a task description before the input. We provide the details in Appendix B.

Cross-lingual transfer   We trained a POS tagger individually for English and Portuguese, and perform zero-shot transfer on other languages. We make use of the XLM-R-large (or simply, XLM-R) (Conneau et al., 2020) for training the models. XLM-R has been pre-trained on 100 languages of the world with over 2TB pre-training corpus size but this corpus does not include any indigenous Brazilian languages.

Language Adaptive Fine-tuning (LAFT)   We leverage LAFT for an effective cross-lingual transfer by first adapting XLM-R-large model to a new language with limited amount of monolingual data (Alabi et al., 2020; Pfeiffer et al., 2020; Chau and Smith, 2021). This method was proven to be very effective for low-resource languages (Adelani et al., 2021; Muller et al., 2021). We make use of the Bible data as the fine-tuning corpus since it is the largest we found for these languages. We only found 7 (out of 12 Brazilian languages) languages with the Bible corpus. Similar to Ebrahimi and Kann (2021), we examine the effectiveness of this small pre-training corpus with 8K-34K sentences. Pfeiffer et al. (2020) showed that this approach can significantly boost cross-lingual transfer. However, it is not parameter-efficient like the MAD-X they proposed. On the other hand, Ebrahimi and Kann (2021) argued that simple adaptation to a new language is more effective than MAD-X especially when using the Bible corpus for adaptation and we follow this recommendation in our evaluation.

Hyper-parameter of experiments   For the cross-lingual and LAFT experiments, we used Hugging-Face transformers (Wolf et al., 2020) and A100

---

[6] https://chat.openai.com/

Nvidia GPU for fine-tuning the models. For the LAFT, we train for 3 epochs on one GPU while for cross-lingual, we fine-tune English and Portuguese individually using a batch size of 64, with gradient accumulation of 2, and a training epoch of 10.

B   Prompt Template

	Prompt
Task Description	Please provide the POS tags for each word in the input sentence. The input will be a list of words in the sentence. The output format should be a list of tuples, where each tuple consists of a word from the input text and its corresponding POS tag label from the tag label set: [”ADJ”, ”ADP”, ”ADV”, ”AUX”,”CCONJ”, ”DET”, ”INTJ”, ”NOUN”, ”NUM”,”PART”, ”PRON”, ”PROPN”, ”PUNCT”,”SCONJ”, ”SYM”, ”VERB”, ”X”].
Note	Your response should include only a list of tuples, in the order that the words appear in the input sentence, with each tuple containing the corresponding POS tag label for a word.
Input	[”What”, ”if”, ”Google”, ”Morphed”, ”Into”, ”GoogleOS”, ”?”]
Output	[(”What”, ”PRON”), (”if”, ”SCONJ”), (”Google”, ”PROPN”), (”Morphed”, ”VERB”), (”Into”, ”ADP”), (”GoogleOS”, ”PROPN”), (”?”, ”PUNCT”)]

Table 3: **Prompt template used for POS tagging** based on Lai et al. (2023). An example prediction by GPT-4