Conformalized Fairness via Quantile Regression

Abstract

Algorithmic fairness has received increased attention in socially sensitive domains. While rich literature on mean fairness has been established, research on quantile fairness remains sparse but vital. To fulfill great needs and advocate the significance of quantile fairness, we propose a novel framework to learn a real-valued quantile function under the fairness requirement of *Demographic Parity* with respect to sensitive attributes, such as race or gender, and thereby derive a reliable *fair* prediction interval. Using optimal transport and functional synchronization techniques, we establish theoretical guarantees of distribution-free coverage and exact fairness for the induced prediction interval constructed by fair quantiles. A hands-on pipeline is provided to incorporate flexible quantile regressions with an efficient fairness adjustment post-processing algorithm. We demonstrate the superior empirical performance of this approach on several benchmark datasets. Our results show the model's ability to uncover the mechanism underlying the fairness-accuracy trade-off in a wide range of societal and medical applications.

1 Introduction

We are increasingly leaning on machine learning systems to tackle human problems. A primary objective is to develop intelligent algorithms that can automatically produce accurate decisions which also enjoy equitable properties, as unintended social bias has been identified as a major concern [13, 17].

As a means of providing quantitative measures of fairness, a number of metrics have been proposed. These metrics can be categorized into three broad categories: group fairness [3], individual fairness [22], and causality-based fairness [27]. In contrast to causality-based fairness that requires domain knowledge to develop a fair causal structure and individual fairness that seeks equality only between similar individuals, group fairness does not require any prior knowledge and seeks equality for groups as a whole [6]. Among the metrics defined for group fairness such as equalized odds [9, 26] and predictive rate parity [10], demographic parity (DP) is generic since it does not allow prediction results in aggregate to depend on sensitive attributes [1, 19, 12, 34]. In particular, an algorithm is said to satisfy DP if its prediction is independent of any given sensitive attribute.

There have been a number of studies on algorithmic fairness concerning DP [1, 11, 12, 19, 28, 34]. In the context regression analysis, much attention have been paid on conditional mean inferences [1, 11, 12, 28], few are concerned with conditional quantiles [32, 34]. As real-world data often exhibit heterogeneity, contain extreme outliers, or do not meet satisfactory distributional assumptions, like Gaussianity, a fairness discussion on conditional quantiles may be more rational and essential since they are able to provide a more complete understanding of the dependence structure between response and explanatory variables [34], as well as better accommodate asymmetry and extreme

tail behavior [33]. It should also be noted that bias or unfairness that arises in mean regression may also be propagated through quantile regression, therefore it must be properly dealt with separately: a graphic demonstration can be found in Figure 1. More intuitively, we may take an example from a Spanish labor market study [16, 17]. The study found that in Spain, also in line with other countries, the mean wage gap between men and women is quite substantial: on average, women earn around 70 percent of what men earn. While wage gaps are not uniform across all pay scales, they are greater at higher quantiles than at lower quantiles. As biases and disparities at different quantiles tend to be overshadowed by the mean behavior of the entire population, we propose a novel framework for searching for fair predictions at different quantiles. It uses optimal transport techniques [2, 12] by transforming *bias-affected* distributions into an *only-fair* Wasserstein-2 barycenter through a kernel-based functional synchronization method [8, 38], in order to provide fair quantile estimators.

Figure 1: An illustration of quantile fairness: for a skewed and heteroscedastic quantile estimation $\{q_{\alpha,i}\}_{i=1}^N$ affected by the sensitive attribute $S \in \{0,1\}$, for example, the lower quantile of the salary distribution, the optimal fair quantile prediction $Q_{g_\alpha}(t), t \in (0,1)$ is derived through a convex combination of the conditional quantile functions of $Q_{q_\alpha|S=0}$ and $Q_{q_\alpha|S=1}$.

Since quantile fairness poses a number of theoretical challenges, no previous literature has been able to provide any inference results such as prediction intervals concerning quantile fairness. It is imperative to keep in mind that fairness is only one of two legs of the primary goal of modern machine learning algorithms, the other being accuracy. Building a reliable prediction with valid confidence is a significant challenge that is encountered by many machine learning algorithms [37]. Towards this end, we propose the conformalized fair quantile prediction (CFQP) inspired by the works of Romano et al. [29, 30]. Our analysis demonstrates, both mathematically and experimentally, that CFQR provides finite sample, distribution-free validity, DP fairness for different quantiles, and precise control of the miscoverage rate, regardless of the underlying quantile algorithm.

Contributions and Outlines. In this paper, we propose a new quantile based method with valid inference that enhances both accuracy and fairness while maintaining a balance between the two. It is a novel framework that allows an exact control of quantile prediction miscoverages while ensuring quantile fairness simultaneously. The main contributions are summarized as follows:

i. We successfully transform the problem of searching quantiles under DP fairness to the construction of multi-marginal Wasserstein-2 barycenters via the optimal transport theory [2, 12, 18]. We incorporate a novel kernel smoothing step into the preceding method, which is particularly advantageous for subgroups whose sample sizes are too small to obtain reliable quantile function estimations.

ii. In Section 4, we propose a conformalized fair quantile regression prediction interval (CFQP) inspired by the works of Romano et al. [29, 30]. It is mathematically proved to achieve a finite sample, distribution-free validity, demographic parity on different quantiles, and an exact control of miscoverage rates, regardless of the quantile algorithm used. The theoretical validity of prediction interval constructed by CFQP and exact DP of the fair quantile estimators are given in Section 5 and the supplement.

iii. The experimental results presented in Section 6 include a numerical comparison of the proposed CFQP and fair quantile estimation with both state-of-the-art conformal and fairness-oriented

methods. By reducing the discriminatory bias dramatically, our method outperforms the state-of-the-art methods while maintaining reasonable short interval lengths.

Related works. Existing approaches for building a fair mean regression broadly fall into three classes: pre-processing, in-processing and post-processing. In particular, preprocessing methods focus on transforming the data to remove any unwanted bias [5, 27, 36]; in-processing methods aim to build in fairness constraints into the training step [1, 4, 22, 26]; post-processing methods target to modify the trained predictor [11, 12, 25]. As few previous works have focused on the quantile fairness of and fair prediction interval, the most related are Yang et al. [34], where a different fairness measure was used. While Agarwal et al. [1] mentioned that their reduction-based approach can be adapted into quantile regression, Williamson and Menon [32] brought forward a novel conditional variance at risk fairness measure aiming to control the largest subgroup risk. For interval fairness measure, the approach by Romano et al. [29] achieved equalized coverage among groups without fairness on interval endpoints. Methodologically, integrating algorithmic fairness with Wasserstein distance based barycenter problem has been studied in [2, 11, 12, 18, 20]. Both in-processing [1, 20] and post-processing [11, 12] methods were proposed to solve classification and mean regression problems. As a post-processing method, our work is distinct from above-mentioned methods by constructing the DP-fairness for each population quantile, and generating a fair prediction interval accordingly.

Notations. We denote by $[K]$ the set $\{1, \ldots, K\}$ for arbitrary integer K. $|\mathcal{S}|$ represents the cardinality for a finite set $\mathcal{S}$. E and P represent the expectation and probability and $\mathbb{1}\{\cdot\}$ is the indicator function. Let $\{Z_n\}_{n=1}^{\infty}$ be a sequence of random variables, and $\{k_n\}_{n=1}^{\infty}$ be a sequence of positive numbers, we say that $Z_n = O_p(k_n)$, if $\lim_{T \to \infty} \limsup_{n \to \infty} P(|Z_n| > Tk_n) = 0$, then $Z_n/k_n = O_p(1)$. To denote the equality in distribution of two random variables A and B, we write $A \stackrel{d}{=} B$.

2   Problem statement

Consider the regression problem where a "sensitive characteristic" S is available, which by the U.S. law [18, 29] can be enumerated as sex, race, age, disability, etc. One observes the triplets $(X_1, S_1, Y_1), \ldots, (X_n, S_n, Y_n)$, where we denote (X_i, S_i, Y_i) by Z_i, $i = 1, \ldots, n$ and Z_i is a random variable in $\mathbb{R}^p \times [K] \times \mathbb{R}$, and aim to predict the unknown value of Y_{n+1} at a test point X_{n+1}, S_{n+1}. Let P be the joint distribution of Z, we assume that all the samples $\{Z_i\}_{i=1}^{n+1}$ are drawn exchangeable, where i.i.d. is a special case.

Our goal is to construct a marginal distribution-free prediction band $C(X_{n+1}, S_{n+1}) \subseteq \mathbb{R}$ that is likely to cover the unknown response Y_{n+1} with finite-sample (nonasymptotic) validity. Formally, given a desired miscoverage rate α, the predicted interval satisfies

$$P\{Y_{n+1} \in C(X_{n+1}, S_{n+1})\} \geq 1 - \alpha \tag{1}$$

for any joint distribution P and any sample size n, while the left and right endpoint of $C(X_{n+1}, S_{n+1})$ satisfies the fairness constraint of Demographic Parity concerning the sensitive variable S.

Demographic Parity. We introduce the quantitative definition of DP on fair regression and connect the DP-fairness with a quantile regressor q_α. We invoke the result that q_α can be projected to fairness using optimal transport. In particular, given a fixed quantile level α (it may refer to $q_{\alpha_{\text{lo}}}$ or $q_{\alpha_{\text{hi}}}$ indicating the left and right endpoint, which will then given by the upper and lower quantile estimates for the prediction band $C(X_{n+1}, S_{n+1})$), let $q_\alpha : \mathbb{R}^p \times [K] \to \mathbb{R}$ represent an arbitrary conditional quantile predictor. Denote by $\nu_{q_\alpha|s}$ the distribution of $(q_\alpha(X, S) \mid S = s)$, the Cumulative Distribution Function (CDF) of $\nu_{q_\alpha|s}$ is given by

$$F_{\nu_{q_\alpha|s}}(t) = P(q_\alpha(X, S) \leq t \mid S = s). \tag{2}$$

The quantile function $Q_{\nu_{q_\alpha|s}} = F_{\nu_{q_\alpha|s}}^{-1} : [0, 1] \to \mathbb{R}$, namely, the generalized inverse of $F_{\nu_{q_\alpha|s}}$, can thus be defined as for all levels $t \in (0, 1]$,

$$Q_{\nu_{q_\alpha|s}}(t) = \inf\{y \in \mathbb{R} : F_{\nu_{q_\alpha|s}}(y) \geq t\} \text{ with } Q_{\nu_{q_\alpha|s}}(0) = Q_{\nu_{q_\alpha|s}}(0+). \tag{3}$$

To simplify the notations, we will write $F_{q_\alpha|s}$ and $Q_{q_\alpha|s}$ instead of $F_{\nu_{q_\alpha|s}}$ and $Q_{\nu_{q_\alpha|s}}$ respectively, for any prediction rule q_α.

In the following, we introduce the definition of Demographic Parity (DP), which is most commonly used in the context of fairness research [1, 11, 12, 19, 26].

Definition 1 (Demographic Parity). An arbitrary prediction $g : \mathbb{R}^d \times [K] \to \mathbb{R}$ satisfies demographic parity under a distribution P over (X, S, Y) if $g(X, S)$ is statistically independent of the sensitive attribute S, namely, for every $s, s' \in [K]$,

$$\sup_{t \in \mathbb{R}} |P(g(X, S) \leq t \mid S = s) - P(g(X, S) \leq t \mid S = s')| = 0.$$

Demographic Parity (DP) requires the predictions to be independent of the sensitive attribute, and it demands the Kolmogorov-Smirnov distance [23] (the difference between CDFs measured in the l_∞ norm) between $\nu_{g|s}$ and $\nu_{g|s'}$ to vanish for all categories s, s'.

3 Quantile Regression and Conformal Prediction

In this section, we recall the CQR approach for finite sample, distribution-free prediction interval inference. Quantile regression was proposed by Koenker and Bassett [21] to estimate the α-th quantile of the conditional distribution of Y given $\tilde{X} := (X, S)$ for some quantile level $\alpha \in (0, 1)$, since then it has become more pervasive with various applications, such as providing prediction intervals, detecting outliers, or perceiving the entire distribution [24]. Denote the conditional cumulative distribution of Y given $\tilde{X}$ by $F(y \mid \tilde{X} = \tilde{x}) := P\{Y \leq y \mid \tilde{X} = \tilde{x}\}$. The α-th conditional quantile prediction is defined as $q_\alpha(\tilde{x}) := \inf\{y \in \mathbb{R} : F(y \mid \tilde{X} = \tilde{x}) \geq \alpha\}$. Quantile regression can be cast as an optimization problem[24], by minimizing the expected check loss function $E(\rho_\alpha) = E[\rho_\alpha(y, q)|\tilde{X} = \tilde{x}]$, where

$$\rho_\alpha(y, q_\alpha(\tilde{x})) = \begin{cases} \alpha|y - q_\alpha(\tilde{x})| & \text{if } y \geq q_\alpha(\tilde{x}), \\ (1 - \alpha)|y - q_\alpha(\tilde{x})| & \text{if } y < q_\alpha(\tilde{x}). \end{cases} \tag{4}$$

Quantile regression offers a principled way of judging the reliability of predictions by building a prediction interval for the new observation $(\tilde{X}_{n+1}, Y_{n+1})$. In contrast to asymptopia, Romano et al. [29, 30] brought forward the conformalized quantile regression (CQR) by combining the merits of robust quantile regression with conformal prediction; thus finite sample validity in (1) is guaranteed. Inspired by the split conformal method, a split CQR likewise starts with splitting the data into a proper training set and a calibration set, indexed by $\mathcal{I}_1, \mathcal{I}_2$ respectively. Given any quantile regression algorithm $\mathcal{Q}$, we then fit two conditional quantile functions $\hat{q}_{\alpha_{lo}}$ and $\hat{q}_{\alpha_{hi}}$ on the proper training set: $\{\hat{q}_{\alpha_{lo}}, \hat{q}_{\alpha_{hi}}\} \leftarrow \mathcal{Q}\left(\left\{\left(\tilde{X}_i, Y_i\right) : i \in \mathcal{I}_1\right\}\right)$. Then the conformity scores are calculated to quantify the error made by the plug-in prediction interval $\hat{C}(\tilde{x}) = [\hat{q}_{\alpha_{lo}}(\tilde{x}), \hat{q}_{\alpha_{hi}}(\tilde{x})]$. We evaluate the scores on the calibration set as $E_k := \max\left\{\hat{q}_{\alpha_{lo}}(\tilde{X}_k) - Y_k, Y_k - \hat{q}_{\alpha_{hi}}(\tilde{X}_k)\right\}$ for each $k \in \mathcal{I}_2$, where both undercoverage and overcoverage of the interval are taken into consideration [30]. Given a new input data $\tilde{X}_{n+1}$, we construct the prediction interval for Y_{n+1} as $C\left(\tilde{X}_{n+1}\right) = \left[\hat{q}_{\alpha_{lo}}\left(\tilde{X}_{n+1}\right) - Q_{1-\alpha}(E, \mathcal{I}_2), \hat{q}_{\alpha_{hi}}\left(\tilde{X}_{n+1}\right) + Q_{1-\alpha}(E, \mathcal{I}_2)\right]$, where $Q_{1-\alpha}(E, \mathcal{I}_2) := (1 - \alpha)(1 + 1/|\mathcal{I}_2|)$-th empirical quantile of $\{E_k : k \in \mathcal{I}_2\}$ conformalizes the plug-in prediction interval. Note that the constructed interval $C(\tilde{X}_{n+1})$ could be highly influenced by the sensitive variable S.

4 Conformal fair quantile prediction (CFQP)

We formally describe our proposed conformal fair prediction (CFQP) framework for constructing DP fairness constrained prediction intervals in this section. A kernel smoothing quantile function is introduced during the functional synchronization, which can improve the estimation when some subgroups are too small to give reliable sample quantile function estimations.

Definition 2 (Wasserstein-2 distance). Let μ and ν be two univariate probability measures with finite second moments. The squared Wasserstein-2 distance between μ and ν is defined as

$$\mathcal{W}_2^2(\mu,\nu) = \inf\left\{\int_{\mathbb{R}\times\mathbb{R}}|x-y|^2 d\gamma(x,y), \gamma \in \Gamma_{\mu,\nu}\right\}$$

where $\Gamma_{\mu,\nu}$ is the set of probability measures (couplings) on $\mathbb{R}\times\mathbb{R}$ having μ and ν as marginals.

Proposition 1 (Fair optimal prediction [12]). Assume, for each $s \in [K]$, that the univariate measure $\nu_{q_\alpha|s}$ has a density and let $p_s = P(S=s)$. Then,

$$\min_{g_\alpha \text{ is fair}} E\left(q_\alpha(X,S) - g_\alpha(X,S)\right)^2 = \min_\nu \sum_{s\in[K]} p_s \mathcal{W}_2^2\left(\nu_{q_\alpha|s}, \nu\right). \tag{5}$$

Moreover, if g_α and ν solve the l.h.s. and the r.h.s. problems respectively, then $\nu = \nu_{g_\alpha}$ and specifically,

$$g_\alpha(x,s) = \sum_{s'\in[K]} p_{s'} Q_{q_\alpha|s'} \circ F_{q_\alpha|s} \circ q_\alpha(x,s). \tag{6}$$

Proposition 1 implies that the optimal fair quantile predictor for an input (x,s) is obtained by a nonlinear transformation of the vector $[q_\alpha(x,s)]_{s=1}^K$ linking to a Wasserstein barycenter problem[2, 12].

The explicit closed form solution comes from [2, 12, 15], which relies on the classical characterization of optimal coupling in one dimension of the Wasserstein-2 distance. A rigorous proof is given in [12, 20]. It shows that a minimizer g_α of the L_2-risk can be used to construct ν and vice-versa, given ν, there is a explicit expression Eq. (6) for the multi-marginal Wasserstein barycenter [2].

We start with splitting the whole training data into a proper training set $\mathcal{I}_1$ and a calibration set $\mathcal{I}_2$, then fit an arbitrary quantile regression algorithm $\mathcal{Q}$ on $\mathcal{I}_1$, $\{\hat{q}_{\alpha_{\text{lo}}}, \hat{q}_{\alpha_{\text{hi}}}\} \leftarrow \mathcal{Q}\left(\left\{\left(\tilde{X}_i, Y_i\right) : i \in \mathcal{I}_1\right\}\right)$. We apply the fitted quantile algorithm $\mathcal{Q}$ on the calibration set $\mathcal{I}_2$ to obtain the predicted $\{\hat{q}_{\alpha_{\text{lo}}}(\tilde{X}_i), \hat{q}_{\alpha_{\text{hi}}}(\tilde{X}_i)\}_{i\in\mathcal{I}_2}$. Since the quantile estimates for $\mathcal{I}_2$ will be used for conformalization, it is essential to transform them into fair ones, i.e. $\hat{g}_{\alpha,i}, \forall i \in \mathcal{I}_2$ (Eq. (9)), through Algorithm 2. Finally, for a test point $\tilde{X}_{n+1}$, we will predict two quantile estimates $\hat{q}_\alpha(x,s)$ affected by the sensitive variable S by $\mathcal{Q}$, then apply the functional synchronization (details in Algorithm 2) and calibration (Algorithm 1) steps in turn to generate the fair constraint prediction interval $C(\tilde{X}_{n+1})$ for Y_{n+1}.

Next, we explicate in detail how to remove the effect of the sensitive variable for the predicted quantile estimates. By Proposition 1, the optimal fair quantiles take the form of Eq. (6). Therefore, we propose an empirical optimal fair quantile estimator $\hat{g}_\alpha$ that relies on the plug-in principle. In particular, Eq.(6) indicates that for each quantile level α and each category $s \in [K]$, we only need estimators for the regression function $\hat{q}_\alpha$, the proportion $\hat{p}_s$, the cumulative distribution function $F_{\hat{q}_\alpha|s}$ and the quantile function $Q_{\hat{q}_\alpha|s}$.

Note that we can empirically estimate the CDF and quantile function for each sensitive group in the calibration set $\mathcal{I}_2$ separately. Hence for each quantile level α, let $N_s := |\mathcal{I}_2^s|$, and the quantile estimators $(\hat{q}_1^s, \hat{q}_2^s, \ldots, \hat{q}_{N_s}^s)^1$ are calculated through the fitted quantile regression $\mathcal{Q}$ with training set $\mathcal{I}_1$. We define the augmented random variable for each data point in $\mathcal{I}_2$,

$$\tilde{q}_i^s := \hat{q}_i^s + U_i^s([-\sigma,\sigma]) \quad \forall i \in \mathcal{I}_2^s, s \in [K],$$

where U_i^s are i.i.d. random variables, uniformly distributed on $[-\sigma,\sigma]$ for some small positive σ, and independent from all the previously introduced random variables. it serves as a smoothing random variable, for the random variables $\tilde{q}_i^s := \hat{q}_i^s + U_i^s$ are i.i.d. continuous for any $P(Y|\tilde{X})$ and $\mathcal{Q}$. Otherwise, the original $\hat{q}_i^s$ might have atoms resulting in a non-zero probability to observe ties in the group $\{q_i^s\}$ for $s = 1, \ldots, K$. This trick, also called jittering [7, 12] is often used for data

---

[1]$\hat{q}_i^s$ depends on the quantile level α, we suppress α for notational simplification.

visualization for tie-breaking. Using the above quantities, we build the CDF and quantile function estimators for each subgroup $s' \in [K]$ as follows,

$$\hat{F}_{q_\alpha|s'}(t) = N_s^{-1} \sum_{i=1}^{N_s} \mathbb{1}\left\{\tilde{q}_i^{s'} \le t\right\}, \quad \text{for all } t \in \mathbb{R}, \tag{7}$$

$$\hat{Q}_{2,q_\alpha|s'}(t) = \int_0^1 \hat{F}_{q_\alpha|s'}^{-1}(v) K_h(t-v) dv, \quad t \in (0,1). \tag{8}$$

The smoothed kernel estimator Eq.(8) was firstly proposed by Cheng and Parzen [8], where $K_h(\cdot) = K(\cdot/h)/h$ is a kernel function chosen as a probability density function that is symmetric around zero with bandwidth parameter $h > 0$.

If the quantile functions $Q_{2,q_\alpha|s'}$ is differentiable, the derivative $Q'_{s'}(t) := Q'_{2,q_\alpha|s'}(t)$ for $t \in (0,1)$ is the quantile density function [8, 38]. We hereby give an estimation bound for Eq. (8) using kernel smoothing. For this purpose, we invoke the conditions (A1) - (A3) that are needed for deducing the following proposition. They can also be found from [38] and are included in the supplementary material.

Proposition 2. Under conditions (A1), (A2), and (A3), we have

$$\sup_{s'} \sup_{t\in[0,1]} \left|\hat{Q}_{2,q_\alpha|s'}(t) - Q_{q_\alpha|s'}(t)\right| = O_p\left(N^{-1/2}\right), \quad s' = 1, \ldots, K.$$

The motivation for including a smoothing step is twofold: First, smoothing the quantile function eliminates the troublesomeness in defining arbitrary quantiles from the empirical one when the sample sizes of subgroups are small. Second, the proposed kernel smoothing improves second-order efficiency by alleviating the so-called relative deficiency [14, 38].

Remark 1. One can utilize various kernels such as the Gaussian or Epanechnikov kernel with adaptive bandwidth for better practical performance. Furthermore, other smoothing methods such as splines or local linear fitting can be applied with equal effectiveness.

Consequently, for each quantile level α, the functional synchronized quantile estimator is

$$\hat{g}_{\alpha,i} = \sum_{s'=1}^{K} \hat{p}_{s'} \hat{Q}_{2,q_\alpha|s'} \circ \hat{F}_{q_\alpha|s} \circ \tilde{q}_i^s, \quad \forall i \in \mathcal{I}_2. \tag{9}$$

The proposed estimator can be deemed as the empirical counterpart with additional randomization of the explicit fair optimal formula Eq.(6).

To conformalize the adjusted fair quantiles Eq (9), we need to compute the conformity scores E_i for each $i \in \mathcal{I}_2$ that quantify the error made by the plug-in fair prediction interval $\hat{C}^g(\tilde{x}) = [\hat{g}_{\alpha_{\text{lo}}}(\tilde{x}), \hat{g}_{\alpha_{\text{hi}}}(\tilde{x})]$. The scores are evaluated on the calibration set as

$$E_i := \max\{\hat{g}_{\alpha_{\text{lo}},i} - Y_i, Y_i - \hat{g}_{\alpha_{\text{hi}},i}\}. \tag{10}$$

At the last stage, for a new data point $\tilde{X}_{n+1} = (x, s)$, and $\alpha \in \{\alpha_{\text{lo}}, \alpha_{\text{hi}}\}$, by defining

$$\tilde{q}_{1,i}^s = \hat{q}_i^s + U_i^s([-\sigma, \sigma]) \quad \forall i \in \mathcal{I}_1^s \quad \text{and} \quad \tilde{q}_\alpha(x,s) = \hat{q}_\alpha(x,s) + U([-\sigma, \sigma]).$$

We use the empirical CDF of training set [2]

$$\hat{F}_{1,q_\alpha|s}(t) := \frac{1}{|\mathcal{I}_1^s|+1}\left(\sum_{i=1}^{|\mathcal{I}_1^s|} \mathbb{1}\left\{\tilde{q}_{1,i}^s < t\right\} + U([0,1])\left(1 + \sum_{i=1}^{|\mathcal{I}_1^s|} \mathbb{1}\left\{\tilde{q}_{1,i}^s = t\right\}\right)\right) \tag{11}$$

to estimate the location $\hat{F}_{1,q_\alpha|s} \circ \tilde{q}_\alpha(x,s)$. Thus the fair quantile estimator is built as follows

$$\hat{g}_\alpha(x,s) = \sum_{s'=1}^{K} \hat{p}_{s'} \hat{Q}_{2,q_\alpha|s'} \circ \hat{F}_{1,q_\alpha|s} \circ \tilde{q}_\alpha(x,s), \forall \alpha \in \{\alpha_{\text{lo}}, \alpha_{\text{hi}}\}. \tag{12}$$

---

[2] Still, $\hat{q}_i^s$ depends on quantile level α.

The fair prediction interval for Y_{n+1} is constructed as

$$C(\tilde{X}_{n+1}) = [\hat{g}_{\alpha_{lo}}(x,s) - Q_{1-\alpha}(E, \mathcal{I}_2), \hat{g}_{\alpha_{hi}}(x,s) + Q_{1-\alpha}(E, \mathcal{I}_2)], \qquad (13)$$

where $Q_{1-\alpha}(E, \mathcal{I}_2) := (1-\alpha)(1 + 1/|\mathcal{I}_2|)$-th empirical quantile of $\{E_i : i \in \mathcal{I}_2\}$ will adjust the plug-in fair prediction interval. We present the pseudo-codes of CFQP as well as the construction of $\hat{g}_\alpha$ for Eq. 9 in Algorithm 1, 2 respectively.

Algorithm 1 Split Conformal Fair Prediction (CFQP)

Input: $\mathcal{D} = \{(X_i, S_i, Y_i)\}_{i=1}^n$; miscoverage level $\alpha \in (0,1)$; quantile regression algorithm $\mathcal{Q}$.
 1: Randomly split $[n]$ into disjoint proper training and calibration indices $\mathcal{I}_1, \mathcal{I}_2$.
 2: Fit two conditional quantile functions on the training set $\{\hat{q}_{\alpha_{lo}}, \hat{q}_{\alpha_{hi}}\} \leftarrow \mathcal{Q}(\{(X_i, S_i, Y_i), i \in \mathcal{I}_1\})$.
 3: Call functional Synchronization (Algorithm 2) to calculate $\{\hat{g}_{\alpha_{lo}}, \hat{g}_{\alpha_{hi}}\}$ for each $i \in \mathcal{I}_2$.
 4: Compute $E_i \leftarrow \max\{\hat{g}_{\alpha_{lo}}(X_i) - Y_i, Y_i - \hat{g}_{\alpha_{hi}}(X_i)\}$ for $\forall i \in \mathcal{I}_2$.
 5: Compute $Q_{1-\alpha}(E, \mathcal{I}_2) \leftarrow (1-\alpha)(1 + 1/|\mathcal{I}_2|)$-th empirical quantile of $\{E_i : i \in \mathcal{I}_2\}$.
 6: For a new test point (x,s), compute $\{\hat{g}_{\alpha_{lo}}(x,s), \hat{g}_{\alpha_{hi}}(x,s)\}$ through Algorithm 2
Output: Fair prediction interval $C(x,s) = [\hat{g}_{\alpha_{lo}}(x,s) - Q_{1-\alpha}(E, \mathcal{I}_2), \hat{g}_{\alpha_{hi}}(x,s) + Q_{1-\alpha}(E, \mathcal{I}_2)]$ for $(X_{n+1}, S_{n+1}) = (x,s)$.

Algorithm 2 Functional Synchronization

Input: Calibration set $\{(X_i, S_i)\}_{i \in \mathcal{I}_2}$ or new point (x,s); base quantile estimator $\mathcal{Q}$;
     slack parameter σ; training set $\{(X_i, S_i)\}_{i \in \mathcal{I}_1}$;
 1: **if** Calibration set $\{(X_i, S_i)\}_{i \in \mathcal{I}_2}$ **then**
 2:    **for** $\alpha \in \{\alpha_{lo}, \alpha_{hi}\}$ **do**
 3:       $\{\tilde{q}_\alpha(X_i, S_i)\} \leftarrow \{q_\alpha(X_i, S_i) + U([-\sigma, \sigma])\}_{i \in \mathcal{I}_2}$ $\triangleright U([-\sigma, \sigma])$ are used for tie-breaking
 4:       **for** $s' \in [K]$ **do**
 5:          Compute $\hat{F}_{q_\alpha|s'}(t)$, and $\hat{F}_{2,q_\alpha|s'}^{-1}(t)$ by Eq. (7) and (8).
 6:          Obtain $\hat{g}_\alpha(X_i, S_i) \leftarrow \sum_{s'=1}^K \hat{p}_{s'} \hat{F}_{2,q_\alpha|s'}^{-1} \circ \hat{F}_{q_\alpha|s'} \circ \tilde{q}_\alpha(X_i, S_i), \forall i \in \mathcal{I}_2$
 7:       **end for**
 8:    **end for**
 9: **else if** New test point (x,s) **then**
10:    **for** $\alpha \in \{\alpha_{lo}, \alpha_{hi}\}$ **do**
11:       $\{\tilde{q}_{1,\alpha}^s\} \leftarrow \{\hat{q}_\alpha^s + U([-\sigma, \sigma])\}_{i \in \mathcal{I}_1^s}$ and $\tilde{q}_\alpha(x,s) \leftarrow q_\alpha(x,s) + U([-\sigma, \sigma])$
12:       Compute $\hat{g}_\alpha(x,s) \leftarrow \sum_{s'=1}^K \hat{p}_{s'} \hat{F}_{2,q_\alpha|s'}^{-1} \circ \hat{F}_{1,q_\alpha|s} \circ \tilde{q}_\alpha(x,s)$ by Eq. (8) and (7)
13:    **end for**
14: **end if**
Output: fair quantile prediction $\hat{g}_\alpha$ for calibration set or new test point (x,s).

---

5 Theoretical results

In this section, we provide a statistical analysis of the proposed algorithm with coverage and DP-fairness guarantees.

Theorem 1 (Prediction coverage guarantee). *If $(\tilde{X}_i, Y_i), i = 1, \ldots, n+1$ are exchangeable, then the prediction interval $C(\tilde{X}_{n+1})$ constructed by the split CFQP algorithm satisfies*

$$P\{Y_{n+1} \in C(\tilde{X}_{n+1})\} \geq 1 - \alpha.$$

Moreover, if the conformity scores E_i are almost surely distinct, the prediction interval is nearly exactly calibrated,

$$P\{Y_{n+1} \in C(\tilde{X}_{n+1})\} \leq 1 - \alpha + 1/(|\mathcal{I}_2| + 1).$$

Remark 2. We give an extension for the conformalization step which allows coverage errors to be spread arbitrarily over the left and right tails as Corollary 1 in the supplement. Controlling the left and right tails independently yields a stronger coverage guarantee.

Theorem 2 (Demographic parity guarantee). *For any joint distribution P of (X, S, Y), any $\sigma > 0$, as well as the base quantile estimator $\hat{q}_\alpha : \mathbb{R}^p \times [K] \to \mathbb{R}$ constructed on labeled data, the estimator $\hat{g}_\alpha$ defined in Eq. (12) satisfies*

$$(\hat{g}_\alpha(X, S) \mid S = s) \stackrel{d}{=} (\hat{g}_\alpha(X, S) \mid S = s') \quad \forall s, s' \in [K].$$

To prove Theorem 2, we leverage distribution-free properties on rank and order statistics presented in Lemma 3 in the supplementary material. Theorem 2 and the estimator $\hat{g}$ improve upon the estimator of Chzhen et al. [12], Chzhen and Schreuder [11], for which only approximate fairness is established.

6 Experiments

To evaluate our proposed method[3], we report the performance of post-processing fairness adjustment on quantiles through four benchmark datasets: Law School (LAW), Community&Crime (CRIME), MEPS 2016 (MEPS), Government Salary (GOV). A detailed description of these datasets can be found in the supplementary material.

We measure the violation of DP-fairness of the quantiles required by Definition 1 through the empirical Kolmogorov-Smirnov (KS) distance. The value represents the disparity between groups $\mathcal{Z}^s = \{(X, S, Y) \in \mathcal{Z} : S = s\}$ for all $s \in [K]$,

$$\mathrm{KS}(g_\alpha) = \max_{s,s' \in [K]} \sup_{t \in \mathbb{R}} \left| \frac{1}{|\mathcal{Z}^s|} \sum_{(X,S,Y) \in \mathcal{Z}^s} \mathbb{1}\{g_\alpha(X, S) \le t\} - \frac{1}{|\mathcal{Z}^{s'}|} \sum_{(X,S,Y) \in \mathcal{Z}^{s'}} \mathbb{1}\{g_\alpha(X, S) \le t\} \right|.$$

Experiment results. In Table 1, we report the average performance of the proposed CFQP over 200 randomly training-test splits as well as the baseline model CQR by the coverage rate, length of prediction interval, and the KS distance of the interval endpoint. 80% of the examples are used for training, and the remaining 20% to test. We split the training part into proper training and calibration sets of equal sizes. Throughout the experiments, the nominal miscoverage rate is fixed to $\alpha = 0.1$. Among preexisting quantile algorithms, we select three leading variants: **linear model**[21], **random forests** [24] and **neural networks** [31]. Overall, our CFQP likewise CQR constructs prediction bands attaining desirable coverage around 90%, as claimed in Theorem 1. Random forest based approaches tend to be slightly more conservative than the other two w.r.t the coverage rate.

	LAW				CRIME			
	Coverage	Length	KS(lo)	KS(hi)	Coverage	Length	KS(lo)	KS(hi)
Ln-CQR	90.16±0.47	0.46±.004	0.39±0.03	0.11±0.02	90.22±1.88	1.30±0.05	0.62±0.06	0.53±0.06
Ln-CFQP	90.02±0.51	0.46±.004	0.02±0.01	0.02±0.01	90.44±1.84	1.64±0.05	0.11±0.03	0.12±0.04
RF-CQR	90.25±0.55	0.39±.005	0.20±0.02	0.15±0.02	90.27±1.66	1.15±0.03	0.64±0.05	0.59±0.05
RF-CFQP	90.11±0.48	0.38±.004	0.02±.008	0.02±.009	90.34±1.84	1.54±0.04	0.12±0.04	0.12±0.03
NN-CQR	90.00±0.50	0.40±0.02	0.41±0.07	0.18±0.05	90.01±1.89	1.16±0.05	0.70±0.05	0.63±0.06
NN-CFQP	90.01±0.51	0.39±0.01	0.02±.009	0.03±.009	89.95±1.62	1.54±0.12	0.12±0.04	0.12±0.03
	MEPS				GOV			
	Coverage	Length	KS (lo)	KS(hi)	Coverage	Length	KS (lo)	KS(hi)
Ln-CQR	89.92±0.66	0.66±0.01	0.09±0.03	0.33±0.05	90.00±0.19	0.79±.002	0.26±.014	0.44±0.02
Ln-CFQP	89.99±0.69	0.66±0.01	0.03±0.01	0.03±0.01	90.02±0.19	0.78±.002	0.05±0.01	0.04±0.01
RF-CQR	90.07±0.65	0.38±.009	0.19±0.02	0.30±0.03	90.03±0.17	0.61±.002	0.29±0.01	0.28±0.02
RF-CFQP	90.38±0.60	0.39±0.01	0.02±0.01	0.03±0.01	90.03±0.17	0.62±.002	0.05±0.01	0.04±0.01
NN-CQR	89.95±0.68	0.37±0.04	0.24±0.09	0.37± 0.06	90.01±0.19	0.58±0.01	0.28±0.03	0.32±0.04
NN-CFQP	89.97±0.61	0.37±0.04	0.03±0.01	0.04±0.01	90.01±0.18	0.59±0.01	0.05±0.01	0.05±0.01

Table 1: Results reported on test set of 200 repeated experiments with $\alpha = 0.1$. CQR refers to the conformalized quantile regression in [30]. Ln, RF, and NN denote the linear, random forest, as well as neural network quantile regression models proposed in [21, 24, 31] respectively. Our methods are shown in bold.

In the KS column concerning the DP-fairness of interval endpoints, our CFQP method greatly reduces the discriminatory bias (quantified by KS) by 70% up to 90% compared to that of CQR. In addition, the lengths of the prediction intervals mostly remain the same except for the Crime dataset, which is due to the reason of its inherent high discriminatory bias among sensitive groups.

Figure 2 presents the comparison of our post-processing fairness adjustment procedure on quantiles $\hat{g}_\alpha$ on the test set $\mathcal{Z}_{test} = \{(X_i, S_i, Y_i)\}_{i=1}^{n_{test}}$ with some state-of-the-art fairness algorithms. Since

---

[3]we utilize the local linear fitting smoothing method in the experiments.

most of the algorithms are targeted at mean prediction, there is no direct comparison with our quantile
fairness method; we accordingly modified the existing methods into quantile versions for comparison.
A detailed description can be found in the supplementary material.

The points in Figure 2 represents the mean of 200 repeated experiments with x-axis as KS distance
and y-axis as Mean Absolute Error(MAE), defined as $\text{MAE}(g_\alpha) = {}^1\!/n_{test} \sum_{\mathcal{Z}_{test}} |Y - g_\alpha(X, S)|$
to measure the prediction error of quantiles, the bars is the standard error on both axis. The optimal
point should be located at the bottom left corner of the graph, where the smaller KS distance, as
well as smaller MAE, are achieved. In each subplot, our method consistently performs better with
the smallest KS distance while keeping the MAE equal or slightly higher than the others or unfair
version. Overall, CFQP is more robust according to the standard errors over experiment repetitions.
Note that due to the highly right skewness of real datasets, the MAE of the upper quantile estimation
is larger than that of the lower quantile for all approaches as well as datasets.

Figure 2: Results for estimating the lower (α_{lo}) and upper (α_{hi}) quantiles using some state-of-the-art
DP-fairness requirement methods on all the datasets. 'Unfair', 'Chzhen', and 'Agarwal' stand for
the linear quantile model without fairness adjustment, barycenter method [12] and reduction-based
algorithm [1] respectively. We present the MAE and KS of lower quantile estimation, as well as
upper quantile estimation. We applied linear quantile models in this comparison.

7   Conclusion and future work

Conformal fair quantile regression is a novel approach for creating fair prediction intervals that
attain valid coverage and reach independence between sensitive attributes while making minimal
modifications to the quantile endpoints simultaneously. It becomes superior within heteroskedastic
and/or asymmetric datasets and robust to outliers. CFQP is supported by rigorous distribution-free
coverage and exact DP-fairness guarantees, as proved in theoretical parts. We conducted several
real data examples demonstrating the effectiveness of our method in achieving exact coverage while
imposing DP-fairness in practice. The method outperforms several state-of-the-art approaches by
comparison.

A limitation in our numerical experiments is that we simply utilize the local linear smoothing method
in defining quantile functions of the subgroups; we believe incorporating flexible kernel smoothing
approaches [35, 38] would improve the experimental performances. As potential future works, it
would be valuable to introduce a DP relaxation framework based on an unfairness measure in a similar
manner as [11, 32], allowing controlling the level of unfairness in quantile estimates. We also expect
to extend the scope to other potential fairness metrics which is dependent on the underlying response
like equalizing quantile loss across groups by incorporating a fairness penalty term in training, or the
fairness metric defined for conditional variance-at-risk.

References

[1] A. Agarwal, M. Dudík, and Z. S. Wu. Fair regression: Quantitative definitions and reduction-based algorithms. In *International Conference on Machine Learning*, page 120–129. PMLR, 2019.

[2] M. Agueh and G. Carlier. Barycenters in the wasserstein space. *SIAM Journal on Mathematical Analysis*, 43(2):904–924, 2011. doi: 10.1137/100805741.

[3] S. Barocas, M. Hardt, and A. Narayanan. Fairness in machine learning. *Nips tutorial*, 1:2, 2017.

[4] R. Berk, H. Heidari, S. Jabbari, M. Joseph, M. Kearns, J. Morgenstern, S. Neel, and A. Roth. A convex framework for fair regression. *arXiv preprint arXiv:1706.02409*, 2017.

[5] F. Calmon, D. Wei, B. Vinzamuri, K. Natesan Ramamurthy, and K. R. Varshney. Optimized pre-processing for discrimination prevention. *Advances in neural information processing systems*, 30, 2017.

[6] A. Castelnovo, R. Crupi, G. Greco, D. Regoli, I. G. Penco, and A. C. Cosentini. A clarification of the nuances in the fairness metrics landscape. *Scientific Reports*, 12(1):1–21, 2022.

[7] J. M. Chambers, W. S. Cleveland, B. Kleiner, and P. A. Tukey. *Graphical methods for data analysis*. Chapman and Hall/CRC, 2018.

[8] C. Cheng and E. Parzen. Unified estimators of smooth quantile and quantile density functions. *Journal of statistical planning and inference*, 59(2):291–307, 1997.

[9] J. Cho, G. Hwang, and C. Suh. A fair classifier using kernel density estimation. *Advances in Neural Information Processing Systems*, 33:15088–15099, 2020.

[10] A. Chouldechova. Fair prediction with disparate impact: A study of bias in recidivism prediction instruments. *Big data*, 5(2):153–163, 2017.

[11] E. Chzhen and N. Schreuder. A minimax framework for quantifying risk-fairness trade-off in regression. *arXiv:2007.14265 [math, stat]*, Jan 2022. arXiv: 2007.14265.

[12] E. Chzhen, C. Denis, M. Hebiri, L. Oneto, and M. Pontil. Fair regression with wasserstein barycenters. *Advances in Neural Information Processing Systems*, 33:7321–7331, 2020.

[13] P. Czarnowska, Y. Vyas, and K. Shah. Quantifying social biases in nlp: A generalization and empirical comparison of extrinsic fairness metrics. *Transactions of the Association for Computational Linguistics*, 9: 1249–1267, 2021.

[14] M. Falk. Relative deficiency of kernel type estimators of quantiles. *The Annals of Statistics*, pages 261–268, 1984.

[15] S. Gallón, J.-M. Loubes, and E. Maza. Statistical properties of the quantile normalization method for density curve alignment. *Mathematical biosciences*, 242(2):129–142, 2013. doi: 10.1016/j.mbs.2012.12.007.

[16] J. García, P. J. Hernández, and A. López-Nicolás. How wide is the gap? an investigation of gender wage differences using quantile regression. *Empirical Economics*, 26(1):149–167, Mar 2001. doi: 10.1007/s001810000050.

[17] J. Gardeazabal and A. Ugidos. Gender wage discrimination at quantiles. *Journal of Population Economics*, 18(1):165–179, Mar 2005. doi: 10.1007/s00148-003-0172-z.

[18] T. L. Gouic, J.-M. Loubes, and P. Rigollet. Projection to fairness in statistical learning. *arXiv:2005.11720 [cs, math, stat]*, Jun 2020. arXiv: 2005.11720.

[19] H. J. Holzer and D. Neumark. Affirmative action: What do we know? *Journal of policy analysis and management*, 25(2):463–490, 2006.

[20] R. Jiang, A. Pacchiano, T. Stepleton, H. Jiang, and S. Chiappa. Wasserstein fair classification. In *Proceedings of The 35th Uncertainty in Artificial Intelligence Conference*, page 862–872. PMLR, Aug 2020.

[21] R. Koenker and G. Bassett. Regression quantiles. *Econometrica: journal of the Econometric Society*, pages 33–50, 1978.

[22] M. J. Kusner, J. Loftus, C. Russell, and R. Silva. Counterfactual fairness. *Advances in neural information processing systems*, 30, 2017.

[23] E. L. Lehmann, J. P. Romano, and G. Casella. *Testing statistical hypotheses*, volume 3. Springer, 2005.

[24] N. Meinshausen and G. Ridgeway. Quantile regression forests. *Journal of Machine Learning Research*, 7 (6), 2006.

[25] S. Milli, J. Miller, A. D. Dragan, and M. Hardt. The social cost of strategic classification. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*, pages 230–239, 2019.

[26] L. Oneto, M. Donini, and M. Pontil. General fair empirical risk minimization. *arXiv:1901.10080 [cs, stat]*, Dec 2019. arXiv: 1901.10080.

[27] D. Plecko and N. Meinshausen. Fair data adaptation with quantile preservation. *Journal of Machine Learning Research*, 21(242):1–44, 2020.

[28] D. Plečko, N. Bennett, and N. Meinshausen. fairadapt: Causal reasoning for fair data pre-processing. *arXiv preprint arXiv:2110.10200*, 2021.

[29] Y. Romano, R. Barber, C. Sabatti, and E. Candès. With malice towards none: Assessing uncertainty via equalized coverage. *ArXiv*, 2019. doi: 10.1162/99608f92.03f00592.

[30] Y. Romano, E. Patterson, and E. Candes. Conformalized quantile regression. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

[31] J. W. Taylor. A quantile regression neural network approach to estimating the conditional density of multiperiod returns. *Journal of Forecasting*, 19(4):299–311, 2000.

[32] R. Williamson and A. Menon. Fairness risk measures. In *International Conference on Machine Learning*, pages 6786–6797. PMLR, 2019.

[33] Z. Xiao and R. Koenker. Conditional quantile estimation for generalized autoregressive conditional heteroscedasticity models. *Journal of the American Statistical Association*, 104(488):1696–1712, 2009.

[34] D. Yang, J. Lafferty, and D. Pollard. Fair quantile regression. *arXiv preprint arXiv:1907.08646*, 2019.

[35] S.-S. Yang. A smooth nonparametric estimator of a quantile function. *Journal of the American Statistical Association*, 80(392):1004–1011, 1985. ISSN 0162-1459. doi: 10.2307/2288567.

[36] R. Zemel, Y. Wu, K. Swersky, T. Pitassi, and C. Dwork. Learning fair representations. In *International conference on machine learning*, pages 325–333. PMLR, 2013.

[37] G. Zeni, M. Fontana, and S. Vantini. Conformal prediction: a unified review of theory and new challenges. *arXiv preprint arXiv:2005.07972*, 2020.

[38] Z. Zhang and H.-G. Müller. Functional density synchronization. *Computational Statistics & Data Analysis*, 55(7):2234–2249, 2011. doi: 10.1016/j.csda.2011.01.007.