TEACHER GUIDED ARCHITECTURE SEARCH

ABSTRACT

Strong improvements in neural network performance in vision tasks have resulted from the search of alternative network architectures, and prior work has shown that this search process can be automated and guided by evaluating candidate network performance following limited training (Performance Guided Architecture Search or PGAS). However, because of the large architecture search spaces and the high computational cost associated with evaluating each candidate model, further gains in computational efficiency are needed. Here we present a method termed *Teacher Guided Search for Architectures by Generation and Evaluation (TG-SAGE)* that produces up to an order of magnitude in search efficiency over PGAS methods. Specifically, TG-SAGE guides each step of the architecture search by evaluating the similarity of internal representations of the candidate networks with those of the (fixed) *teacher* network. We show that this procedure leads to significant reduction in required per-sample training and that, this advantage holds for two different search spaces of architectures, and two different search algorithms. We further show that in the space of convolutional cells for visual categorization, TG-SAGE finds a cell structure with similar performance as was previously found using other methods but at a total computational cost that is *two orders of magnitude* lower than Neural Architecture Search (NAS) and more than *four times* lower than progressive neural architecture search (PNAS). These results suggest that TG-SAGE can be used to accelerate network architecture search in cases where one has access to some or all of the internal representations of a *teacher* network of interest, such as the brain.

1 INTRODUCTION

The accuracy of deep convolutional neural networks (CNNs) for visual categorization has advanced substantially from 2012 levels (AlexNet (Krizhevsky et al., 2012)) to current state-of-the-art CNNs like ResNet (He et al., 2015), Inception (Szegedy et al., 2014), DenseNet (Huang et al., 2016). This progress is mostly due to discovery of new network architectures. Yet, even the space of feedforward neural network architectures is essentially infinite and given this complexity, the design of better architectures remains a challenging and time consuming task.

Several approaches have been proposed to automate the discovery of neural network architectures, including random search (Pinto et al., 2009), reinforcement learning (Zoph & Le, 2017), evolution (Real et al., 2016), and sequential model based optimization (SMBO) (Liu et al., 2017; Bergstra et al., 2012a). These methods operate by iteratively sampling from the hyperparameter space, training the corresponding architecture, evaluating it on a validation set, and using the search history of those scores to guide further architecture sampling. But even with recent improvements in search efficiency, the total cost of architecture search is still outside the reach of many groups and thus impedes the research in this area (e.g. some of the recent work in this area has spent 40-557k GPU-hours for each search experiment (Real et al., 2018; Zoph & Le, 2017)).

What drives the total computational cost of running a search? For current architectural search procedures (above), the parameters of each sampled architecture must be trained before its performance can be evaluated and the amount of such training turns out to be a key driver in the total computational cost. Thus, to reduce that total cost, each architecture is typically only partially trained to a *premature* state and its *premature* performance is used as a proxy of its *mature* performance (i.e. the performance it would have achieved if was actually fully trained).

Because the search goal is high *mature* performance in a task of interest, the most natural choice of an architecture evaluation score is its *premature* performance. However, this may not be the best choice of evaluation score. For example, it has been observed that, as a network is trained, multiple sets of internal features begin to emerge over network layers, and the quality of these internal features determines the ultimate behavioral performance of the neural network as a whole. Based on these observations, we reasoned that, if we could evaluate the quality of a network's internal features even in a very *premature* state, we might be able to more quickly determine if a given architecture is likely to obtain high levels of *mature* performance.

But without a reference set of high quality internal features, how can we determine the quality of a network's internal features? The main idea proposed here is to use features of a high performing "teacher" network as a reference to identify promising sample architectures at a much earlier *premature* state. Our proposed method is inspired by prior work showing that the internal representations of a high-performing *teacher* network can be used to optimize the parameters of smaller, shallower, or thinner student networks (Ba & Caruana, 2014; Hinton et al., 2015; Romero et al., 2014). It is also inspired by the fact that such internal representation measures can potentially be obtained from primate brain and thus could be used as an ultimate teacher. While our ability to simultaneously record from large populations of neurons is fast growing, these measurements have already been shown to have remarkable similarities to internal features of CNNs (Yamins et al., 2014; Schrimpf et al., 2018).

We refer to this method as Teacher Guided Search for Architectures by Generation and Evaluation (TG-SAGE). Specifically, TG-SAGE guides each step of an architecture search by evaluating the similarity of several internal feature representations of each sampled architecture with those of a fixed, high-performing teacher network with unknown architectural parameters but observable internal states. We found that when this evaluation is combined with the usual performance evaluation (above), we can predict the mature performance of sampled architectures with an order of magnitude less *premature* training and thus an order of magnitude less total computational cost. We then use this observation to execute multiple runs of TG-SAGE for different model search spaces to confirm that TG-SAGE can indeed discover network architectures of comparable mature performance to those discovered with performance-only search methods, but with far less total computational cost.

2   Previous Work

There have been several studies on automatic design of neural network architectures in the past few years. Real et al. (Real et al., 2016; 2018) used an evolutionary approach in which samples taken from a pool of models were engaged in a pairwise competition game. This method searches for optimal architectures and weights jointly by reusing all or part of weights from the parent network in an effort to reduce the computation cost associated with training the candidate models as well as the final retraining of the best found models. However, it is not clear to what degree this procedure is cutting down on the computational cost compared to alternative search method that depend on (some) training for each candidate model starting from an initial point. There have been several studies on using reinforcement learning in agents that learn to design high performing neural network architectures (Baker et al., 2016; Zoph & Le, 2017). Of special relevance to this work is Neural Architecture Search (NAS) (Zoph & Le, 2017) in which a long short-term memory network (LSTM) trained using REINFORCE was used to learn to design neural network architectures for object recognition and natural language processing tasks. A variation of this approach was later used to design convolutional cell structures similar to those used in Inception network that could be transferred to larger datasets like Imagenet (Zoph et al., 2017).

While most of these works have focused on discovering higher performing architectures, there has been a number of efforts emphasizing the computational efficiency in hyperparameter search. In order to reduce the computational cost of architecture search, Brock et al. (Brock et al., 2017) proposed to use a hypernetwork to predict the layer weights for any arbitrary candidate architecture instead of retraining from random initial values. The hypernetwork was trained to predict the layer weights given the layer embedding as input (Ha et al., 2016). Some recent work attempt to jointly optimize for the network hyperparameters as well as the trainable weights themselves. While this is a very interesting idea that significantly reduces the computational cost of architecture search, in its current form it can only be applied in the spaces of models in which the number of trainable weights

don not change as a result of hyperparameter choices (e.g. when the number of filters in a CNN is fixed). Efficient NAS (Pham et al., 2018) and DARTS (Liu et al., 2018) methods proposed to share the trainable parameters across all candidate models and to jointly optimize for the hyperparameters and the network weights during the search. While these approaches led to significant reduction in total search cost, they did so by constraining the search space due to considerations regarding the shared trainable weights. More recently progressive neural architecture search (PNAS) (Liu et al., 2017) proposed a sequential model based optimization (SMBO) approach that learned a predictive model of performance given the hyperparameters through a procedure which gradually increased the complexity of the space. This approach led to an impressive $20\times$ improvement in the computational cost of search compared to NAS.

3 METHODS

3.1 REPRESENTATIONAL SIMILARITY WITH A TEACHER NETWORK AS SURROGATE

The largest portion of cost associated with neural network architecture search comes from training the sampled models, which is proportional to the number of training steps (SGD updates) performed on the model. Due to the high cost of fully training each sampled model, in most cases a surrogate score is used as a proxy for the *mature* performance. Correlation between the surrogate and *mature* score may affect the architecture search performance as poor proxy values could guide the search algorithm towards suboptimal regions of the space. Previous work on architecture search in the space of Convolutional Neural Networks (CNN) have concurred with the empirical surrogate measure of *premature* performance after about 20 epochs of training. While 20 epochs is much lower than the usual number of epochs used to fully train a CNN network (300-900 epochs), it still forces a large cost on conducing architecture searches. We propose that evaluating the internal representations of a model would be a more reliable measure of architecture quality during the early phase of training (e.g. after several hundreds of SGD iterations), when the features are starting to be formed but the network is not yet performing reliably on the task.

Here we use Representational Dissimilarity Matrix (RDM) (Kriegeskorte et al., 2008) as a statistic of the internal representations learned by a model at a given layer. RDM could be computed for any feature set in response to a set of inputs and summarizes the response patterns to different categories of stimuli at any given layer. To compute the RDM for a given feature matrix $F \in \mathbb{R}^{n_i \times n_f}$ which contains n_f features measured in response to n_i inputs, we follow the following two steps: First we take a random subsample of features (neurons or model features; for faster implementation) and compute the average response over all image instances of the same object category $c_i, i \in [1, n_c]$. This reduces the feature matrix to a matrix of size $F^c \in \mathbb{R}^{n_c \times n_f}$. Second, we derive RDM (M^F) by computing the pairwise distances between average object response vectors (rows in F_c) using a distance measure like correlation residual.

$$M^F \in \mathbb{R}^{n_c \times n_c}, M_{i,j} = 1 - corr(F_i^c, F_j^c) \tag{1}$$

We evaluate each sampled model by measuring RDM similarity to those extracted from the teacher network. To this end, we compute RDM for all or a subset of layers in the network and then compute the correlation between all pairs of student and teacher RDMs. To score a candidate network against a given layer of the teacher network, we consider the highest RDM similarity to teacher calculated over all layers of the student network. Finally, we construct an overall score by taking the mean of the RDM scores which we call TG (Teacher Guidance). We also define a combined Performance + TG (P+TG) score which is formulated as weighted sum of *premature* performance and TG score in the form of $P + \alpha TG$. In this fashion, the combined validation score guides the architecture search to maximize performance as well as representational similarity with the teacher architecture. We consider the teacher architecture as any high-performing model with unknown architecture but observable activations. We can have one or several measured endpoints from the teacher model that each could potentially be used to generate a similarity score.

3.2 HYPERPARAMETER SEARCH WITH REINFORCEMENT LEARNING (RL)

We follow the method proposed by (Zoph & Le, 2017) to learn the probability of hyperparameter choices ($\mathcal{X} = x_1, x_2, ..., x_n$) that maximize the unknown but observable reward function $f : \mathcal{X} \to \mathbb{R}$. A 2-layer long short-term memory (LSTM) is used as the controller that chooses

each hyperparameter in the network at every unrolling step. The LSTM network, models the conditional probability distribution of optimal hyperparameter choices as a function of all previous choices $P(x_j | x_1, x_2, ..., x_{j-1}, \theta)$ in which θ is the set of all tunable parameters in the LSTM network. Since a differentiable loss function is not known for this problem, usual maximum likelihood methods could not be used in this setting. Instead parameters are optimized through reinforcement learning based approaches (e.g. REINFORCE (Williams, 1992)) by increasing the likelihood of each hyperparameter choice according to the reward (score) computed for each sampled model (or a batch of sampled models). Relative to (Zoph & Le, 2017), we made two modifications. First, since the order of dependencies between different hyperparameters in each layer/block is arbitrary, we ran the LSTM controller for one step per layer (instead of once per hyper-parameter). This results in shorter choice sequences generated by the LSTM controller and therefore shorter sequence dependencies. Second, we chose a Boltzman policy method for action selection to allow the search to continue the exploration throughout the search experiment. Hyperparameter values were selected according to the probability distribution over all action choices. Compared to ϵ-greedy method, following the softmax policy reduces the likelihood of sub-optimal actions throughout the training.

For each hyperparameter, choice probability is computed using a linear transformation (e.g. $W_{K_h}, W_{N_{filters}}$) from LSTM output at the last layer (h_l^2) followed by a softmax. To reduce the number of tunable parameters and more generalization across layers, we used shared parameters between layers.

$$\hat{P}_{l,x} = \text{softmax}(W_t^T h_l^2) \tag{2}$$
$$l \in \{1, 2, ..., N_l\}$$
$$t \in \{K_h, K_w, N_{filters}, \text{stride}, \text{normalization}, \text{activation}\}$$

Probability distribution over possible number of layers is formulated as a function of the first output value of the LSTM ($\hat{P}_{N_l} = \text{softmax}(W_{N_l}^T h_0^2)$). In addition to layers' hyperparameters we also search over layers' connections. Similar to the approach taken in (Zoph & Le, 2017) we formulated the probability of a connection between layer i and j as a function of the state of the LSTM at each of these layers (h_i^2, h_j^2).

$$\hat{P}_{i,j}^c = \text{sigmoid}(W_{src}^T h_i^2 + W_{dst}^T h_j^2) \tag{3}$$

where $\hat{P}_{i,j}^c$ represents the probability of a connection between layer i output to j's input. W_{src} and W_{dst} are tunable parameters that link the hidden state of LSTM to probability of a connection existing between the two layers.

3.3 Hyperparameter Search with Tree of Parzen Estimators (TPE)

Sequential Model-Based Optimization (SMBO) (Hutter et al., 2011) approaches are greedy numerical methods used to optimize a given function $f : \mathcal{X} \to \mathbb{R}$. They are usually applied in settings where evaluating the function at each point is costly and it's important to minimize the number of evaluations to reach the optimal value. Various SMBO approaches were previously proposed (Bergstra et al., 2012b; Bardenet & Kegl, 2010) and some have been used for hyperparameter optimization in neural networks (Bergstra et al., 2011; 2012a; Liu et al., 2017). Bayesian SMBO approaches model the posterior or conditional probability distribution of values (scores) and use a criteria to iteratively suggest new samples while the probability distribution is updated to incorporate the history of previous sample tuples (x, y) where $x = (x^{(1)}, ..., x^{(n)})$ is a sample hyperparameter vector and y is the received score (or loss). Here we adopted Tree of Parzen Estimators (TPE) because of its intuitiveness and successful application in various domains with high dimensional spaces. Unlike most other Bayesian SMBO methods that directly model the posterior distribution of values $P(y|x)$, TPE models the conditional distribution $P(x|y)$ with two non-parametric densities.

$$P(x|y) = \begin{cases} l(x) & \forall \, y \leq y^* \\ g(x) & \forall \, y > y^* \end{cases} \tag{4}$$

We consider y to be the loss value which we are trying to minimize (e.g. error rate of a network on a given task). For simplicity, value of y^* could be taken as some quantile of values observed so far (γ). At every iteration, TPE fits a Gaussian Mixture Model (GMM) to subset of observed samples with lowest loss value ($l(x)$) and another to those with highest loss ($g(x)$). Ideally we want to find x that

minimizes y. Expected Improvement (EI) is the expected reduction in $f(x)$ compared to threshold y^* under current model of f. Maximizing EI, encourages the model to further explore parts of the space which lead to lower loss values and can be used to suggest new hyperparameter samples.

$$EI(x) = \int_{-\infty}^{y^*} (y^* - y)P(y|x)dy = \frac{\int_{-\infty}^{y^*} (y^* - y)P(x|y)P(y)dy}{P(x)} \tag{5}$$

Given that $P(y < y^*) = \gamma$ and $P(x|y) = l(x)$ for $y < y^*$, it has been shown (Bergstra et al., 2011) that EI would be proportional to $\left(\gamma + \frac{g(x)}{l(x)}(1 - \gamma)\right)^{-1}$. Therefore the EI criterion can be maximized by taking samples with minimum probability under $g(x)$ and maximum probability under $l(x)$. For simplicity, at every iteration n_d samples are drawn from $l(x)$ and the hyperparameter choice with lowest $g(x)/l(x)$ ratio is suggested as the next sample.

4 EXPERIMENTS AND RESULTS

4.1 TEACHER GUIDANCE FOR ARCHITECTURE SEARCH

We first investigated if a teacher similarity evaluation measure (P+TG) of premature networks improves the prediction of *mature* performance (compared to evaluation of only *premature* performance, P). To do this, we made a pool of CNN architectures for which we computed the *premature* and *mature* performances as well as the *premature* RDMs (a measure of the internal feature representation, see 3.1) at every model layer. We populated the pool by selecting the top 5 models found at a range of checkpoints (every 100 samples) of the performance guided architecture searches. We included models (n=116) from two RL searches for 10-layer and another two for 20-layer CNNs with 20 epoch/sample training (see description of search spaces in the supp. material). In this way we included sample models with a wide range of performance that also included the best models found during each search.

In experiments throughout this paper, we used a variant of ResNet model (He et al., 2015) with 54 convolutional layers ($n = 9$) as the teacher model. This architecture was selected as the *teacher* because it is high performing (top-1 accuracy of 94.75% and 75.89% on CIFAR10 and CIFAR100 datasets respectively). Notably, the teacher architecture is not in our search spaces (see supp. material). The features (after each of the three stacks of residual blocks, here named L1-L3) were chosen as the teacher's internal features, and a RDM was created from each using random subsample of features in that layer. We did not attempt to optimize this choice these were chosen simply because they sampled approximately evenly over the full depth of the teacher.

We found that the earlier teacher layers (L1) are better predictors of the *mature* performance compared to other layers early on during the training (<2epochs) but as the training progresses, the later

Figure 1: Comparison of performance and P+TG measures at premature state (epochs≈1.5) as predictors of mature performance. (left) scatter plot of premature and mature performance values. (middle) scatter plot of premature P+TG measure and mature performance. (right) Correlation between performance, single layer RDMs, and combined P+TG measures with mature performance at varying number of premature training epochs.

layers (L2 and L3) become better predictors ($\sim$3epochs) and with more training ($>$3epochs) the *premature* performance becomes the best single predictor of the *mature* (i.e. fully trained) performance. However the combined "P+TG" score (see 3.1) composes the best predictor of *mature* performance during most of the training period (Figure 1-right). This observation was consistent with previous findings that learning in deep networks predominantly happen "bottom-up" (Raghu et al., 2017).

In order to find the optimum TG weight factor, we varied the α parameter (section 3.1) and measured the change in correlation between the P+TG score and the *mature* performance (see Figure 3 in supplementary material). We found that for networks trained for $\sim$2 epochs, a value of $\alpha = 1$ is close to optimum. In addition to ResNet, we also analyzed a second teacher network, namely NASNet (see section 2 in supp. material) and confirmed our findings using the alternative teacher network. We also found that NASNet features (which performs higher than ResNet; 82.12% compared to 75.9%) form a better predictor of *mature* performance in almost all training regimes (Figure 4 in supp. material).

4.2   Teacher Guided Search in the Space of Convolutional Networks

As outlined in the Introduction, we expected that the (P+TG) evaluation score's improved predictivity (Figure 1) should enable it to support a more efficient architecture search than performance evaluation alone (P). To test this directly, we used the (P+TG) evaluation score in full architectural search experiments using a range of configurations. For these experiments, we searched two spaces of convolutional neural networks similar to previous search experiments (Zoph & Le, 2017) (maximum network depth of either 10 or 20 layers). These architectural search spaces are important and interesting because they are large. In addition, because networks in these search spaces are relatively inexpensive to train to maturity, we could evaluate the true underlying search progress at a range of checkpoints (below). We ran searches in each space using four different search methods: using the (P+TG) evaluation score at 2 or 20 epochs of premature training, and using the (P) evaluation score at either 2 or 20 epochs of premature training. For these experiments, we used Random, RL, as well as TPE architecture selection algorithm (see Methods), and we halted the search after 1000 or 2000 sampled architectures (for the 10- and 20-layer search spaces, respectively). We conducted our search experiments on CIFAR100 instead of CIFAR10 because of larger number of classes in the dataset that provided a higher dimensional RDM.

Table 1 summarizes results of our search experiments. We found that, for all search configurations, the (P+TG) driven search algorithm (i.e. TG-SAGE) consistently outperformed the performance-only driven algorithm (P) in that, using equal computational cost it always discovered higher performing models. This gain was substantial in that TG-SAGE found models with approximately the same performance as (P) search but at $\sim 10\times$ less computational cost (2 vs. 20 epochs; Table 1).

To assess and track the efficiency of these searches, we measured the maximum validation set performance of the fully trained network architectures returned by each search as its current choice of the top-5 architectures. We repeated each search experiment three times to estimate variance in these measures resulting from both search sampling and network initial filter weight sampling. Figure 2 shows that the teacher guided search (P+TG) leads to finding models that were on par with performance guided search (P) throughout the search runs while being $10\times$ more efficient.

Table 1: Comparison of premature performance and representational similarity measure in architecture search using RL and TPE algorithms. P: premature performance as validation score; P+TG: combined premature performance and RDMs as the validation score. Values are $\mu \pm \sigma$ across 3 search runs.

Search Algorithm	RL				TPE	
Search Space	**10 layer**		**20 layer**		**10 layer**	**20 layer**
# Epoch/Sample	2	20	2	20	2	2
Random - Best C100 Error (%)	45.4$\pm$ 2.5	41.3$\pm$ 1.5	41.2$\pm$ 1.8	38.3$\pm$ 4.8	45.4$\pm$ 2.5	41.2$\pm$ 1.8
P - Best C100 Error (%)	41.0$\pm$ 0.5	40.5$\pm$ 0.4	37.5$\pm$ 0.2	32.7$\pm$ 0.9	42.5$\pm$ 5.7	37.0$\pm$ 3.0
P+TG - Best C100 Error (%)	**38.3$\pm$ 1.1**	**39.2$\pm$ 0.9**	**33.2$\pm$ 1.4**	**32.2$\pm$ 0.8**	**37.6$\pm$ 1.2**	**33.0$\pm$ 2.4**
Performance Improvement (%)	2.7	1.3	4.3	0.5	4.9	4

Figure 2: Effect of different surrogate measures on architecture search performance. (left) shows the average C100 performance of the best model found during different stages of three runs of RL search in each case (see text). (right) same as the plot on left but displayed with respect to the total computational cost invested (number of training images × number of epochs × number of samples).

4.3 TEACHER GUIDED SEARCH IN THE SPACE OF CONVOLUTIONAL CELLS

In order to find architectures that are transferable across datasets we applied TPE search algorithm with P+TG score to the space of convolutional cells similar to the one used in (Liu et al., 2017). After a cell structure is sampled, the full architecture is constructed by stacking the same cell multiple times with a predefined structure (see supplementary material). While both RL and TPE search methods led to similar outcomes in our experiments in section 4.1, average TPE results were slightly higher for both experiments. Hence, we chose to conduct the search experiment in this section using TPE algorithm with the same setup as in section 4.1 using CIFAR100 with 1000 samples.

For each sample architecture, we computed RDMs for each cell's output. Considering that we had $N = 2$ cell repetitions in each block during search, we ended up with 8 RDMs in each sampled cell that were compared with 3 precomputed RDMs from the teacher network (24 comparisons over validation set of 5000 images). Due to the imperfect correlation between the *premature* and *mature* performances, doing a small post-search reranking step increases the chance of finding slightly better cell structures. We chose the top 10 discovered cells and trained them for 300 epochs on the training set and evaluated on the validation set (5k samples). Cell structure with the highest validation performance was then fully trained on the complete training set (50k samples) for 600 epochs using the procedure described in (Zoph et al., 2017) and evaluated on the test set[1].

Table 2: Performance of discovered cells on CIFAR10 and CIFAR100 datasets. *indicates error rates from training all models using the same training pipeline on 2-GPUs. [†]we did not further explore these hyperparameters because of compute limitations and adopted the values reported in (Zoph et al., 2017).

Model	B	N	F	# Params	C10 Error*	C100 Error*	M_1	E_1	M_2	E_2	Cost
NASNet-A	5	6	32	3.4M	3.72	17.88	20000	0.9M	250	13.5M	21.4-29.3B
PNASNet-5	5	3	48	3.2M	4.06	19.26	1160	0.9M	0	0	1.0B
SAGENet	5	6[†]	32[†]	6.0M	**3.66**	**17.42**	**1000**	**90K**	10	13.5M	**225M**
SAGENet-sep				**2.7M**	3.88	17.51					

We compared our best found cell structure with those found using NAS (Zoph et al., 2017) and PNAS (Liu et al., 2017) methods on CIFAR-10, CIFAR-100, and Imagenet datasets (Tables 2 and 3). To rule out any differences in performance that might have originated from slight differences in training procedure, we used the same training pipeline to train our model (SAGENet) as well as

---

[1]our best model was ranked 3^{rd} and with a score difference of 0.004 with the top model.

the as well as the two baselines (NASNet and PNASNet). We found that on all datasets, SAGENet performed on par with the other two baseline models we had considered.

With regard to compactness, SAGENet had more parameters and FLOPS compared to NASNet and PNASNet due mostly to symmetric 7×1 and 1×7 convolutions. But we had not considered any costs associated with the number of parameters or the number of FLOPS when conducting the search experiments. For this reason, we also considered another version of SAGENet in which we replaced the symmetric convolutions with "7×7 separable" convolutions (SAGENet-sep). SAGENet-sep had half the number of parameters and FLOPS compared to SAGENet and slightly higher error rates.

To compare the cost and efficiency of different search procedures we adopt the same measures as in (Liu et al., 2017). Total cost of search is computed as the total number of examples that were processed with SGD throughout the search procedure. This includes M_1 sampled cell structures that were trained with E_1 examples during the search and M_2 top cells trained on E_2 examples post-search to find the top performing cell structure. The total cost is then calculated as $M_1 E_1 + M_2 E_2$. While SAGENet performed on par to both NASNet and PNASNet top models on all C10, C100, and Imagenet, the cost of search was about 100 and 4.5 times less than NASNet and PNASNet respectively (Table 2). A unique features of this cell is the large number of skip connections (both within blocks and across cells) (see Figure 5 in supp. material). Interestingly, at *mature* state our top architecture performed better than the teacher network (ResNet) on C10 and C100 datasets (96.34% and 82.58% on C10 and C100 for TG-SAGE as compared to 94.75% and 75.89% for our teacher-ResNet).

Table 3: Performance of discovered cells on Imagenet dataset in mobile settings.*indicates error rates from training all models using the same training pipeline on 2-GPUs.

Model	B	N	F	Top-1 Err*	Top-5 Err*	# Params (M)	FLOPS (B)
NASNet-A	5	4	44	31.07	11.41	5.3	1.16
PNASNet-5	5	3	56	**29.92**	**10.63**	5.4	1.30
SAGENet	5	4	48	31.81	11.79	9.7	2.15
SAGENet-sep				31.9	11.99	**4.9**	**1.03**

5 DISCUSSION AND FUTURE DIRECTIONS

We here demonstrate that, when the internal neural representations of a powerful teacher neural network are partially observable (such as the brain's neural network), that knowledge can substantially accelerate the discovery of high performing machine networks. We propose a new method to accomplish that acceleration (TG-SAGE) and demonstrate its ability using a previous state-of-the-art model as the teacher. Essentially, TG-SAGE jointly maximizes a model's *premature* performance and its representational similarity to those of a partially observable teacher network. With the architecture space and search settings tested here, we report a computational efficiency gain of $\sim 10\times$ in discovering CNNs for visual categorization. This gain in efficiency of the search (with maintained performance) was achieved without any additional constraints on the search space as in more efficient search methods like ENAS (Pham et al., 2018) or DARTS (Liu et al., 2018). We empirically demonstrated this by performing searches in several CNN architectural spaces. It remains to be seen if that acceleration holds for other settings and whether internal representations from actual brains (e.g. neural population patterns of responses to many images) which are obtainable in the near future can be used as the teacher to potentially achieve even better acceleration.

An important aspect of teacher guided architecture search relates to the metrics used for evaluating similarity of representational spaces. Here we used representational dissimilarity matrix to achieve this goal. However, we acknowledge that RDM might not be the most accurate or fastest metric for this purpose. Exploring other representational analysis metrics like Singular Vector Canonical Correlation Analysis (SVCCA) are an important direction we would like to pursue in the future.

Another interesting future direction would be to conduct the architecture search by iteratively substituting the teacher network with the best network discovered so far. This approach would make the procedure independent of the choice of the teacher network and make it possible to perform efficient search when good teacher architectures have not been deployed yet.

REFERENCES

Jimmy Ba and Rich Caruana. Do deep nets really need to be deep? In *Advances in neural information processing systems*, pp. 2654–2662, 2014.

Bowen Baker, Otkrist Gupta, Nikhil Naik, and Ramesh Raskar. Designing neural network architectures using reinforcement learning. *arXiv preprint arXiv:1611.02167*, 2016.

Remi Bardenet and Balazs Kegl. Surrogating the surrogate: accelerating gaussian-process-based global optimization with a mixture cross-entropy algorithm. In *27th International Conference on Machine Learning (ICML 2010)*, pp. 55–62. Omnipress, 2010.

J. Bergstra, D. Yamins, and D. D. Cox. Making a Science of Model Search. pp. 1–11, 2012a. URL http://arxiv.org/abs/1209.5111.

James Bergstra, Remi Bardenet, Yoshua Bengio, and Balazs Kegl. Algorithms for Hyper-Parameter Optimization. pp. 1–9, 2011. doi: 2012arXiv1206.2944S.

James Bergstra, Nicolas Pinto, and David Cox. Machine learning for predictive auto-tuning with boosted regression trees. In *Innovative Parallel Computing (InPar), 2012*, pp. 1–9. IEEE, 2012b.

James Bergstra, Dan Yamins, and David D Cox. Hyperopt: A python library for optimizing the hyperparameters of machine learning algorithms. In *Proceedings of the 12th Python in Science Conference*, pp. 13–20. Citeseer, 2013.

Andrew Brock, Theodore Lim, J. M. Ritchie, and Nick Weston. SMASH: One-Shot Model Architecture Search through HyperNetworks. 2017.

David Ha, Andrew Dai, and Quoc V. Le. HyperNetworks. 2016.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. *Arxiv.Org*, 7(3):171–180, 2015. ISSN 1664-1078.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Gao Huang, Zhuang Liu, Laurens van der Maaten, and Kilian Q. Weinberger. Densely Connected Convolutional Networks. 2016. URL http://arxiv.org/abs/1608.06993.

Frank Hutter, Holger H Hoos, and Kevin Leyton-Brown. Sequential model-based optimization for general algorithm configuration. In *International Conference on Learning and Intelligent Optimization*, pp. 507–523. Springer, 2011.

Diederik Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. *International Conference on Learning Representations*, pp. 1–13, 2014.

Nikolaus Kriegeskorte, Marieke Mur, and Peter a. Bandettini. Representational similarity analysis - connecting the branches of systems neuroscience. *Frontiers in systems neuroscience*, 2 (November), 2008. ISSN 1662-5137.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. ImageNet Classification with Deep Convolutional Neural Networks. *Advances In Neural Information Processing Systems*, pp. 1–9, 2012.

Chenxi Liu, Barret Zoph, Jonathon Shlens, Wei Hua, Li-Jia Li, Li Fei-Fei, Alan Yuille, Jonathan Huang, and Kevin Murphy. Progressive Neural Architecture Search. 2017. URL http://arxiv.org/abs/1712.00559.

Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: Differentiable Architecture Search. 2018.

Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training Recurrent Neural Networks. (2), 2012. ISSN 1045-9227. doi: 10.1109/72.279181.

Hieu Pham, Melody Y. Guan, Barret Zoph, Quoc V. Le, and Jeff Dean. Efficient Neural Architecture Search via Parameters Sharing. 2018. URL https://arxiv.org/abs/1802.03268.

Nicolas Pinto, David Doukhan, James J DiCarlo, and David D Cox. A high-throughput screening approach to discovering good forms of biologically inspired visual representation. *PLoS computational biology*, 5(11):e1000579, 2009.

Maithra Raghu, Justin Gilmer, Jason Yosinski, and Jascha Sohl-Dickstein. SVCCA: Singular Vector Canonical Correlation Analysis for Deep Learning Dynamics and Interpretability. (Nips), 2017. ISSN 10495258. doi: 1706.05806.

Esteban Real, Sherry Moore, Andrew Selle, Saurabh Saxena, Yutaka Leon Suematsu, Quoc Le, and Alex Kurakin. Large-Scale Evolution of Image Classifiers. 2016.

Esteban Real, Alok Aggarwal, Yanping Huang, and Quoc V Le. Regularized Evolution for Image Classifier Architecture Search. (2017), 2018. URL http://arxiv.org/abs/1802.01548.

Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. FitNets: Hints for Thin Deep Nets. pp. 1–13, 2014.

Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J Majaj, Rishi Rajalingham, Elias B Issa, and Kohitij Kar. Brain-Score : Which Artificial Neural Network for Object Recognition is most Brain-Like ? pp. 1–9, 2018.

Karen Simonyan and Andrew Zisserman. Very Deep Convolutional Networks for Large-Scale Image Recognition. pp. 1–10, 2014. ISSN 09505849.

Christian Szegedy, Vincent Vanhoucke, Jonathon Shlens, and Zbigniew Wojna. Rethinking the Inception Architecture for Computer Vision. 2014.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

D. L. K. Yamins, H. Hong, C. F. Cadieu, E. A. Solomon, D. Seibert, and J. J. DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the National Academy of Sciences*, 111(23):8619–8624, 2014. ISSN 0027-8424.

Barret Zoph and Quoc V Le. Neural architecture Search With reinforcement learning. *ICLR*, 2017.

Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V. Le. Learning Transferable Architectures for Scalable Image Recognition. 10, 2017.

SUPPLEMENTARY MATERIAL

EFFECT OF WEIGHTING TEACHER GUIDANCE ON PREDICTING MATURE PERFORMANCE

For each candidate model, we computed an overall "Teacher Guidance (TG)" score by averaging the best RDM scores for all teacher layers. The combined "P+TG" score was formulated as weighted sum of premature performance and TG score in the form of $P + \alpha TG$. We varied the α parameter and measured the change in correlation between the P+TG score and the mature performance (Figure 3). We observed that higher α led to larger gains in predicting the mature performance when models were trained only for few epochs ($\leq$2.5 epochs). However, with more training, larger α values reduced the predictability.

Figure 3: Effect of TG weight α on predicting the mature performance.

ALTERNATIVE TEACHER NETWORK - NASNET

We examined the effect of choosing an alternative teacher network, namely NASNet and performed a set of analyses similar to those done on ResNet. We observed that similar to ResNet, early layers are better predictors of the mature performance during early stages of the training. With additional training, the premature performance becomes a better single-predictor of the mature performance but during most of the training the combined P+TG score best predicts the mature performance (Figure 4-left). We also varied the "TG" weight factor and found that compared to ResNet, higher α values led to increased gains in predicting the mature performance. $\alpha = 5$ was used to compute the P+TG scores shown in Figure 4.

Overall, we found that NASNet representations were significantly better predictors of mature performance for all evaluated time points during training when compared to ResNet (Figure 4-right).

Figure 4: (left) Comparison of single layer and combined RDMs with premature performance as predictors of mature performance on NASNet. P+TG was computed using $\alpha = 5$. (middle) Gain in predicting the mature performance with varying TG weight. (right) Comparison of combined RDM scores using two alternative teacher models at various stages of training. α values of 1 and 5 were used for ResNet and NASNet respectively.

DATASETS AND PREPROCESSING

CIFAR: We followed the standard image preprocessing for CIFAR labeled dataset, a 100-way object classification task (He et al., 2015). Images were zero-padded to size 40×40. A random crop of size 32×32 was selected, randomly flipped along the horizontal axis, and standardized over all pixel values in each image to have zero mean and standard deviation of 1. We split the training set into training set (45,000 images) and a validation set (5,000 images) by random selection.

Imagenet: We used standard VGG preprocessing (Simonyan & Zisserman, 2014) on images from Imagenet training set. During training, images were resized to have their smaller side match a random number between 256 and 512 while preserving the aspect ratio. A random crop of size 224 was then cut out from the image and randomly flipped along the central vertical axis. The central crop of size 224 was used for evaluation.

DETAILS OF SEARCH ALGORITHMS

RL Search Algorithm: We used a two-layer LSTM with 32 hidden units in each layer as the controller. Parameters were trained using Adam optimizer (Kingma & Ba, 2014) with a batch size of 5. For all searches, the learning rate was 0.001, and the Adam first momentum coefficient was zero $\beta_1 = 0$. Gradients were clipped according to global gradient norm with a clipping value of 1 (Pascanu et al., 2012).

TPE Search Algorithm: We used the python implementation of TPE hyperparameter search from HyperOpt package (Bergstra et al., 2013). We employed the linear sample forgetting as suggested in (Bergstra et al., 2012a) and set the threshold $y^* = \sqrt{N}/4$ for the set of N observed samples. Each search run started with 20 random samples and continued with TPE suggestion algorithm. At every iteration, $n_d = 24$ draws were taken from $l(x)$ and choice of hyperparameter $argmin_i g(x_i)/l(x_i)$ was used as the next sample (see section 3.3 in the main text).

EXPERIMENTAL DETAILS FOR SEARCH IN SPACE OF CONVOLUTIONAL NETWORKS

Search Space: Similar to (Zoph & Le, 2017) we defined the hyperparameter space as the following independent choices for each layer: $N_{filters} \in [32, 64, 128]$, $(K_{width}, K_{height}) \in [1, 3, 5, 7]$, $K_{stride} \in [1, 2]$, activation $\in [Identity, ReLU]$, normalization $\in [none, BN]$. In addition we searched over number of layers ($N_{layers} \in [1, N_L]$) and possible connections between the layers. In this space of CNNs, the input to every layer could have originated from the input image or the output of any of the previous layers. We considered two particular spaces in our experiments that differed in the value of N_L (=10 or 20).

CIFAR Training: Selected networks were trained on CIFAR training set (45k samples) from random initial weights using SGD with Nesterov momentum of 0.9 for 300 epochs on the training set. The initial learning rate was 0.1 and was divided by 10 after every 100 epochs. Mature performance was then evaluated on the validation set (above).

EXPERIMENTAL DETAILS FOR SEARCH IN SPACE OF CONVOLUTIONAL CELLS

Search Space: We used the same search space and model generation procedure as in (Zoph et al., 2017; Liu et al., 2017) with the exception that we added two extra hyperparameters which could force each of the cell inputs (from previous cell or the one prior to that) to be directly concatenated in the output of the cell even if they were already connected to some of the blocks in the cell. This extra hyperparameter choice was motivated by the open-source implementation of NASNet at the time of conducting the search experiments that contained similar connections[2].

Each cell receives two inputs which are the outputs of the previous two cells. In early layers, the missing inputs are substituted by the input image. Each cell consists of B blocks with a prespecified structure. Each block receives two inputs, an operation is applied on each input independently and the results are added together to form the output of the block. The search algorithm picks each of the

---

[2]available at `https://github.com/tensorflow/models/blob/376dc8dd0999e6333514bcb8a6beef2b5b1bb8da/research/slim/nets/nasnet/nasnet_utils.py`

operations and inputs for every block in the cell. Operations are selected from a pool of 8 possible choices: {identity, 3×3 average pooling, 3×3 max pooling, 3×3 dilated convolution, 1×7 followed by 7×1 convolution, 3×3 depthwise-separable convolution, 5×5 depthwise-separable convolution, 7×7 depthwise-separable convolution}.

Imagenet Training: For our Imagenet training experiments, we used a batch size of 128 images of size 224×224 pixels. Each batch was divided between two GPUs and the gradients computed on each half were averaged before updating the weights. We used an initial learning rate of 0.1 with a decay of 0.1 after every 15 epochs. Each network was trained for 40 epochs on the Imagenet training set and validated on the central crop for all images from Imagenet validation. No dropout or drop-path was used when training the networks. RMSProp optimizer with a decay rate of 0.9 and momentum rate of 0.9 was used during training and gradients were normalized by their global norm when the norm value exceeded a threshold of 10. L2-norm regularizer was applied on all trainable weights with a weight decay rate of 4×10^{-5}.

CIFAR Training: The networks were trained on CIFAR10/CIFAR100 training set including all 50,000 samples for 600 epochs with an initial learning rate of 0.025 and a single period cosine decay (Zoph et al., 2017). We used SGD with Nesterov momentum rate of 0.9. We used L2 weight decay on all trainable weights with a rate of 5×10^{-4}. Gradient clipping similar to that used for Imagenet and a threshold of 5 was used.

Best Discovered Convolutional Cell: Figure 5 shows the structure of the best discovered cell. Only four (out of ten) operations contain trainable weights and there are several bypass connections in the cell.

Figure 5: SAGENet - Structure of the best cell discovered during the search with TG-SAGE.

IMPLEMENTATION DETAILS

Because of heavy computational load associated with training neural networks and in particular in large-scale model training, we need a scalable and efficient framework to facilitate the search procedure. Our proposed framework was implemented in four main modules: (i) explorer, (ii) trainer, (iii) evaluator, and (iv) tracker. The explorer module contains the search algorithm. The trainer module optimizes the proposed architecture parameters on an object recognition task using a large-scale image dataset. Once the training job is complete the evaluator module extracts the model features in response to a set of predetermined image-set and assesses the similarity of representations to the bank of neural and behavioral benchmarks (derived from human and non-human primates). The tracker module consists of a database which tracks details and status of every proposed architectures and acts as a bridge between all three modules. During the search experiments, the explorer module proposes a new candidate architecture and writes the details as a new job into the database (tracker module). It also continuously monitors the database for new processed models and updates its weights upon receiving adequate number of samples (i.e. when a new batch is complete). Active workers periodically monitor the database for newly added untrained models, and train the archi-

tecture on the assigned dataset. Upon completion of the training phase, evaluator module extracts the features from all layers in response to the evaluation set and computes premature-performance and RDM consistencies and writes back the results on the database. Trainer and evaluator modules will then be free to process new candidate models. This framework enabled us to run many worker programs on several clusters speeding up the search procedure. An overview of the implemented framework is illustrated in Figure 6. Experiments reported in this paper were run on three server clusters with up to 40 GPUs in total.

Figure 6: Implementation of a distributed framework for conducting architecture search.