KERNEL RECURRENT LEARNING (KeRL)

ABSTRACT

We describe Kernel Recurrent Learning (KeRL), a reduced-rank, temporal eligibility trace-based approximation to backpropagation through time (BPTT) for training recurrent neural networks (RNNs) that gives competitive performance to BPTT on long time-dependence tasks. The approximation replaces the rank-4 credit assignment tensor by a simple reduced-rank product of a sensitivity weight and a temporal eligibility trace. In this structured approximation motivated by node perturbation, the sensitivity weights and eligibility kernel time scales are themselves learned by applying perturbations. The rule represents another step toward biologically plausible or neurally inspired ML, with lower complexity in terms of relaxed architectural requirements (no symmetric return weights), a smaller memory demand (no unfolding and storage of states over time), and a shorter feedback time. Finally, we show that KeRL can learn long time-scales more efficiently than BPTT in an online setting.

1 INTRODUCTION

Animals and humans excel at learning tasks that involve long-term temporal dependencies. A key challenge of learning such tasks is the problem of spatiotemporal credit assignment: the learner must find which of many past neural states is causally connected to the currently observed error, then allocate credit across neurons in the brain. When the time-dependencies between network states and errors are long, learning becomes difficult.

In machine learning, the current standard for training recurrent architectures is *Backpropagation Through Time* (BPTT, Rumelhart et al. (1985), Werbos (1990)). BPTT assigns temporal credit or blame by unfolding a recurrent neural network in time up to a horizon length T, processing the input in a forward pass, and then backpropagating the error back in time in a backward pass (see Fig. 1a).

From a biological perspective, BPTT – like backpropagation in feedforward neural networks – is implausible for many reasons. For each weight update, BPTT requires using the transpose of the recurrent weights to transmit errors backwards in time and assign credit for how past activity affected present performance. Running the network with transposed weights requires that the network either has two-way synapses, or uses a symmetric copy of the feedforward weights to backpropagate error. In either case, the network must alternatingly gate its dynamical process to run forward or backward, and switch from nonlinear to linear dynamics, depending on whether activity or errors are being sent through the network.

From both biological and engineering perspectives, there is a heavy memory demand: the complete network states, going T timesteps back in time, must be stored. The time-complexity of computation of the gradient in BPTT scales like T, making each iteration slow when training tasks with long time scale dependencies. Although T should match the length of the task or the maximum temporal lag between network states and errors for unbiased gradient learning, in practice T is often truncated to mitigate these computational costs, introducing a bias.

The present work is another step in the direction of providing heuristics and relaxed approximations to backpropagation-based gradient learning for recurrent networks. KeRL confronts the problems of efficiency and biological plausibility. It replaces the lengthy, linearized backward-flowing backpropagation phase with a product of a forward-flowing temporal eligibility trace and a spatial sensitivity weight. Instead of storing all details of past states in memory, synapses integrate their past activity during the forward pass (see Fig. 1b). The network does not have to recompute the entire gradient

at each update, as the time-scales of the eligibility trace and the sensitivity weight are learned over time.

2 RELATED WORK

In recent years, much work has been devoted to implementing backpropagation algorithms in a more biologically plausible way, partly in the hope that more plausible implementations might also be simpler. The symmetry requirement between the forwards and backwards weights can be alleviated by using random return weights (Lillicrap et al. (2016) and Nøkland (2016)), however, learning still requires a separate backward pass through a network with linearized dynamics. Neurons may be able to extract error information in the time derivative of their firing rates using an STDP-like learning rule (Bengio et al. (2015)), with error backpropagation computed as a relaxation to equilibrium (Scellier & Bengio (2017)), at least for learning fixed points.

Other work has focused replacing batch learning with online learning: typically, BPTT is implemented in a setting where data is prepared into batches of fixed sequence length T and used to perform learning in a T-step unrolled graph; however, online learning, with a constant stream of data error signals, is a more natural description of how the world supplies a learning system with data. BPTT without truncation struggles with online learning, as it must repeatedly backpropagate the error all the way through a continuously expanding graph. Since computation of the unbiased gradient scales with the length of the graph, gradient computation increases linearly with time. For a task with T timesteps, the total computation of the gradients scales like T^2.

Real Time Recurrent Learning (RTRL, Williams & Zipser (1989)) and Unbiased Online Gradient Optimization (UORO, Tallec & Ollivier (2017), Ollivier et al. (2015)) deal with this issue by keeping track of the credit assignment tensor in a feedforward way. Decoupled Neural Interfaces (DNI Jaderberg et al. (2016)) estimates the truncated part of the gradient by continually predicting the future loss with respect to the hidden state.

KeRL offers this same advantage, in addition to other benefits. RTRL requires that the network keep track of an unwieldy rank-3 tensor, which could not be stored by any known biological entities. UORO factorizes this into rank-2 objects but still requires non-local computations like vector norm operations. Finally, DNI requires an entire separate network to keep track of the synthetic gradient. KeRL is distinguished by its simplicity, requiring only rank-2 tensors. All computations are local, and synapses need to integrate over only a few relevant quantities.

3 THE LEARNING RULE

Consider a single-layer RNN in discrete time (indexed by t) with readout, input, and hidden layer activations given by $\mathbf{y}^t, \mathbf{x}^t$, and $\mathbf{h}^t$, respectively (boldface represents vectors, with vector entries denoting the activity of individual units). The dynamics of the recurrently connected hidden units are given by:

$$\mathbf{h}^{t+1} = \sigma\left(\mathbf{g}^{t+1}\right) = \sigma\left(W^{rec}\mathbf{h}^t + W^{in}\mathbf{x}^t + \mathbf{b}\right) \tag{1}$$

where W^{rec}, W^{in} are the recurrent and input weights, $\mathbf{b}$ are the hidden biases, σ is a general pointwise non-linearity, and $\mathbf{g}^t$ represents the summed inputs (pre-nonlinearity) to the neurons at time t. The readout is given by $\mathbf{y}^t = \sigma^{out}(W^{out}\mathbf{h}^t + \mathbf{b}^{out})$. The objective function is $C = C(\{\hat{\mathbf{y}}^T, \mathbf{y}^T)\})$, where $\hat{\mathbf{y}}^T$ is the target output, in the case where error feedback is received at the end of an episode of length T, and $C = \sum_{t=0}^T C^t$ when errors $C^t = C(\{\hat{\mathbf{y}}^t, \mathbf{y}^t)\})$ are received continuously over the episode. The parameters $W^{in}, W^{rec}, W^{out}, \mathbf{b}, \mathbf{b}^{out}$ are trainable.

Assuming the readout weights and biases $(W^{out}, \mathbf{b}^{out})$ are trained in the usual way, the KeRL update rule for the RNN weights $W = \{W^{in}, W^{rec}\}$ is simply:

$$(\Delta W_{jk})^t = -\eta \sum_i \delta_i^t \beta_{ij} e_{jk}^t, \tag{2}$$

where $\delta_i^t \equiv \frac{dC^t}{dh_i^t} = \sum_l \frac{dC^t}{dy_l^t}\frac{dy_l^t}{dh_i^t}$ is the gradient of the cost with respect to the current hidden state, β_{ij} is a set of learned *sensitivity weights*, and

$$e_{jk}^t \equiv \sum_\tau K(\tau, \gamma_j) \sigma'(u) \Big|_{g_j^{t-\tau}} s_k^{t-\tau} \tag{3}$$

is a *local eligibility trace* (Williams (1992)) consisting of a temporally filtered version of the product of presynaptic activation and a postsynaptic activity factor. The temporal filter or kernel K in the eligibility has learnable time-scales; in this manuscript we use the simplest version of a low-pass temporal filter, a decaying exponential with a single time-constant γ_j per neuron: $K(\tau, \gamma_j) = \exp(-\gamma_j \tau)$, though one can imagine many other function choices with multiple timescales. The role of the eligibility is to specify how strongly a synapse W_{jk} should be held responsible for any errors in neuron j at the present time, on the basis on how far in the past the presynaptic neuron k was active. Here $s_k^{t-\tau} = \{x_k^{t-\tau}, h_k^{t-\tau-1}\}$ stands in for the activation of the neuron presynaptic to the synapse being updated. [1]. Since the eligibility trace can be computed during the forward pass, KeRL does not require backpropagating the error through time. Furthermore, KeRL only uses at most rank-2 tensors, so neurons and synapses could plausibly do all of the required computation. The contrast between BPTT and KeRL is depicted in Fig. 1a,b.

Figure 1: a), b) Schematic depicting the difference in the flow of information between a) BPTT, b) KeRL. c) Schematic depicting how KeRL (Blue) can be used to find long term memory solutions when BPTT (red) struggles

KeRL emerges from the following Ansatz:

$$\frac{\partial h_i^t}{\partial h_j^{t-\tau}} \approx \beta_{ij} K(\tau, \gamma_j) \tag{4}$$

We call $\partial h_i^t / \partial h_j^{t-\tau}$, a key term in the computation of the gradient, the *sensitivity tensor* in an extension of the usage in Fiete & Seung (2006)). This sensitivity describes how the activity of neuron j at a previous time $t - \tau$ affects the activity of neuron i at the current time t. While the true sensitivity is a 4-index tensor summarizing many interactions based on the many paths through which activity propagates forward in a recurrent network, we approximate it with a product of a (learnable) rank-2 sensitivity weight matrix β and a temporal kernel K with (learnable) inverse-time coefficients γ. The sensitivity weights β_{ij} describe how strongly neuron j affects neuron i on average, while the temporal kernel describes how far into the future the activity of a neuron impacts the other neurons. We describe how to learn these parameters (β, γ) in the next section.

We arrive at KeRL by using our ansatz for the sensitivity (4) in the computation of a gradient-based weight update, instead of using the true sensitivity. First, we write down the full gradient rule for a recurrent network. If the parameters W_{ij} are treated as functions that can vary over time during a trial, then the derivative can be written as a functional derivative:

$$\frac{dC^t}{dW_{jk}} = \frac{1}{T} \sum_0^T \frac{\delta C^t}{\delta W_{jk}(t)}. \tag{5}$$

This is simply mathematical notation for the "unfolding-in-time" trick, in which the network and weights are assumed to be replicated for each time-step of the dynamics of a recurrent network, and separate gradients are computed for each time-replica of the weights; the actual weight updates are simply the average of the separate weight variations for each time-replica. We next apply the

---

[1]The rule to update the hidden layer biases is given by $(\Delta b_i)^t = -\eta \sum_i \delta_i^t \beta_{ij} e_j^t$ where $e_j^t = \sum_\tau \exp(-\gamma_j \tau) \sigma'(g_j^{t-\tau})$ integrates over a clamped input

sensitivity lemma Fiete & Seung (2006) to express gradients with respect to weights as gradients with respect to input activations, times the presynaptic activity: $\frac{\delta C}{\delta W_{jk}(t)} = \frac{\delta C}{\delta g_j(t)} s_k(t)$. Thus,

$$
\frac{dC^t}{dW_{jk}} = \sum_\tau \frac{\delta C^t}{\delta g_j(t-\tau)} s_k(t-\tau) \quad = \quad \sum_k \sum_\tau \frac{\delta C^t}{\delta h_i(t)} \frac{\delta h_i(t)}{\delta g_j(t-\tau)} s_k(t-\tau) \tag{6}
$$

$$
= \quad \sum_k \sum_{\tau=0}^{t} \frac{\delta C^t}{\delta h_i(t)} \frac{\delta h_i(t)}{\delta h_j(t-\tau)} \sigma'(u)\Big|_{g_j(t-\tau)} s_k(t-\tau) \tag{7}
$$

By replacing the sensitivity $\delta h_i(t)/\delta h_j(t-\tau)$ with our Ansatz (4), we arrive at our learning rule, KeRL(2).

The time-dependent part of the computation– a leaky integral of the product of the presynaptic activity multiplied by the instantaneous change in the postsynaptic activity– can be computed during the forwards pass, without any backpropagation of activity or error signals.

4 LEARNING THE SENSITIVITY WEIGHTS AND INVERSE-TIMESCALES

For our Ansatz to align as well as possible with the gradient, we allow the sensitivity weights β and inverse-timescales γ to be learned. We learn these parameters by tracking the effect of small i.i.d. hidden perturbations ξ during the forward pass. In order to do so our hidden neurons must store two values, the true hidden state $\mathbf{h}$, and a perturbed hidden state $\tilde{\mathbf{h}}$, which is generated by applying noise to the neurons during the forward pass:

$$
\tilde{\mathbf{h}}^{t+1} = \sigma\left(W^{rec}(\tilde{\mathbf{h}}^t + \xi^t) + W^{in}\mathbf{x}^t + \mathbf{b}\right), \tag{8}
$$

The effect of previous noise on the current hidden state can be computed using the sensitivity

$$
\tilde{h}_i^t - h_i^t = \sum_\tau \sum_j \frac{\partial h_i^t}{\partial h_j^{t-\tau}} \xi_j^{t-\tau} \tag{9}
$$

We train γ, β to predict the network's response to these noisy perturbations. We take gradients with respect to the objective function.

$$
C_\beta = \left(\tilde{h}_i^t - h_i^t - \sum_j \beta_{ij} \sum_\tau \exp(-\gamma_j \tau) \xi_j^{t-\tau}\right)^2 \tag{10}
$$

which we have generated by substituting our Ansatz (4) into (9). [2]

Taking gradients with respect to this objective function gives us the following update rule for the sensitivity weights and inverse-timescales.

$$
\Delta \beta_{ij}^t = -\eta_m \delta_{\beta_i}^t \Omega_j^t(\xi)
$$
$$
\Delta \gamma_j^t = -\eta_m \sum_i \delta_{\beta_i}^t \beta_{ij} \Gamma_j^t(\xi) \tag{11}
$$

Here $\delta_{\beta_i}{}^t \equiv \sum_j \beta_{ij}\Omega_j^t - (\tilde{h}_i^t - h_i^t)$ represents the error in reconstructing the effect of the perturbation via the sensitivity weights and $\Omega_j^t(\xi) \equiv \sum_\tau \exp(-\gamma_j\tau)\xi_j^{t-\tau}$ and $\Gamma_j^t(\xi) \equiv \frac{d\Omega_j^t}{d\gamma_j} = -\sum_\tau \tau \exp(-\gamma_j\tau)\xi_j^{t-\tau}$ are integrals that neuron h_j performs over the applied perturbation ξ. In our implementation, we update these parameters immediately before we compute the gradient using (2). The full update rule is described in the pseudocode table.

---

[2]If we don't care about the size of the gradients and only the direction, we can use the cost function $C_\beta = \frac{(\tilde{\mathbf{h}}^t - \mathbf{h}^t) \cdot \mathbf{O}^t}{||\tilde{\mathbf{h}}^t - \mathbf{h}^t||\, ||\mathbf{O}^t||}$ where $O_i^t = \sum_j \beta_{ij} \sum_\tau \exp(-\gamma_j\tau)\xi_j^{t-\tau}$. This cost function works for algorithms where the gradient is divided by a running average of its magnitude (RMSProp, Adam).

Algorithm 1 Pseudocode table describing the implementation of Online-KeRL on an RNN. For Batched-KeRL we only update parameters when t = T

---

while $t \leq T$ **do**

   $\mathbf{h}^t \leftarrow \sigma\left(W\mathbf{h}^{t-1} + W^{in}\mathbf{x}^{t-1} + \mathbf{b}\right)$ /* propagate data forwards */

   $\tilde{\mathbf{h}}^t \leftarrow \sigma\left(W(\tilde{\mathbf{h}}^{t-1} + \xi^{t-1}) + W^{in}\mathbf{x}^{t-1} + \mathbf{b}\right)$ /*propagate noisy network forwards */

   ${\Omega_j}^t \leftarrow \exp(-\gamma_j){\Omega_j}^{t-1} + {\xi_j}^t$ /*Integrate over perturbations*/

   ${\Gamma_j}^t \leftarrow \exp(-\gamma_j){\Gamma_j}^{t-1} - \exp(-\gamma_j){\Omega_j}^{t-1}$ /*Derivative of $\mathbf{\Omega}^t$ w.r.t. γ^t */

   $e_{jk}^t \leftarrow e^{-\gamma_j}e_{jk}^{t-1} + \sigma'(\mathbf{g}_j^t)s_k^t$ /*Update eligibility traces*/

   $\delta_{\beta_i}^t \leftarrow \sum_j \beta_{ij}\Omega_j^t - (\tilde{h}_j^t - h_j^t)$ /* Calculate error in predicting effect of perturbations */

   $\beta_{ij}^t \leftarrow \beta_{ij}^{t-1} - \eta_m \delta_{\beta_i}^t \Omega_j^t$ /*Update sensitivity weights */

   $\gamma_j^t \leftarrow \gamma_j^{t-1} - \eta_m \sum_i \delta_{\beta_i}^t \beta_{ij}\Gamma_j^t$ /*Update kernel coefficients */

   $\delta_i^t = \sum_l \frac{dC}{dy_l^t}W_{li}^{out}$ /*Compute error in hidden state */

   $W_{jk}^t \leftarrow W_{jk}^{t-1} - \eta \sum_i \delta_i^t \beta_{ij}e_{jk}^t$ /*Compute and apply gradients*/

end while

---

5 EMPIRICAL RESULTS

We test KeRL on several benchmark tasks that require memory and computation over time, showing that it is competitive with BPTT across these tasks. We implemented batch learning with KeRL and BPTT on two tasks: the adding problem (Hochreiter & Schmidhuber (1997); Hochreiter et al. (2001)) and pixel-by-pixel MNIST (LeCun et al. (1998)). We implemented an online version of KeRL with an LSTM network on the A^n, B^n task (Gruslys et al. (2016)) to compare with results from the UORO algorithm (Tallec & Ollivier (2017)). [3]

The tuned hyperparameters for BPTT and KeRL were the learning rate, η, the gradient clipping parameter, gc (Pascanu et al. (2013)). For KeRL, we additionally permitted a shared learning rate parameter for the sensitivity weights and kernels, η_m. In practice, the same hyperparameter settings η, gc tended to work well for both BPTT and KeRL. The additional hyperparameter for KeRL, η_m, did not need to be find tuned, and often worked well across several orders of magnitude.

We implemented both the RMSprop (Tieleman & Hinton (2012)) and Adam (Kingma & Ba (2014)) optimizers and reported the best result.

5.1 ADDING PROBLEM

In the adding problem, the network receives two input streams, one a sequence of random numbers in $[0, 1]$, and the second a mask vector of zeros, with two entries set randomly to one in each trial. The network's task is to sum the input from the first stream whenever there is a non-zero entry in the second. This task requires remembering sparse pieces of information over long time scales and ignoring long sequences of noise, which is difficult for RNNs when the sequences are long.

We tested the performance of two networks on a variety of sequence lengths, up to 400, using both BPTT and KeRL, Table 2. The networks were an IRNN, which is an RNN with a ReLU non-linearity where the recurrent weight matrix is initialized to identity, and a RNN with tanh nonlinearity. The implementation details are described in Appendix A.

Untruncated BPTT applied to an IRNN performed very well on this task, but less so on the RNN with tanh nonlinearity. KeRL was unstable on the IRNN, but it outperformed BPTT with the tanh nonlinearity (Fig. 2).

We believe that KeRL outperforms BPTT on the tanh nonlinearity because our Ansatz allows the sensitivity $\frac{d\mathbf{h}^t}{d\mathbf{h}^{t-\tau}}$ to have relatively long timescales, while the BPTT sensitivities are squashed by the tanh nonlinearity. By applying gradients generated by our Ansatz (instead of the true gradients) we

---

[3]KeRL can be implemented more generally on any circuit dynamics with Markov architecture, including LSTMs. For LSTMs, the gradient terms are slightly more complicated in form, but still easy to compute (Appendix).

Learning Rule, Network	Algorithm	η	gc	η_m
BPTT, tanh RNN	RMS Prop	10^{-3}	100.0	–
BPTT, ReLU IRNN	RMS Prop	10^{-4}	100.0	–
KeRL, tanh RNN	RMS Prop	10^{-3}	100.0	10^{-5}

Table 1: Best hyperparameters for the adding problem with sequence length 400

Figure 2: Single-trial example of cross validation loss on the adding problem for sequences of length 200,300,400.

push our network toward a solution with longer time scales via a feedback alignment-like mechanism (Lillicrap et al. (2016),Nøkland (2016)), as schematized in Fig. 1c.

To investigate the importance of learning the kernel timescales, we implemented KeRL without training the sensitivity weights (β) or the inverse timescales (γ). When these parameters are not learned, KeRL is still able to perform the task for the shorter 200-length sequence (Table 2) implying that a feedback-alignment-like mechanism (Lillicrap et al. (2016), Nøkland (2016)) may be enabling learning even when the error signals are not delivered along the instantaneous gradients.

For longer sequences, however, learning the sensitivity and timescale parameters is important. Surprisingly, learning the inverse timescales is even more important than learning the sensitivity weights. We hypothesize that as long as the timescales over which error is correlated with outcome are appropriate, sensitivity weights are relatively less important because of feedback-alignment-like mechanisms. We show an example of how the timescales may change in Fig. 3.

Seq. Len.	200	400
Fix β, Fix γ	0.014	0.180
Learn β, Fix γ	0.170	0.171
Fix β, Learn γ	0.031	0.076
Learn β, Learn γ	0.008	0.031
BPTT	0.020	0.171

Figure 3 & Table 2: Varying which parameters of KeRL are learned. Left: Histogram of inverse time coefficients before training (blue) and after 70,000 minibatches (orange). Right: Performance on various versions of KeRL and BPTT after 70,000 minibatches

5.2 PIXEL-BY-PIXEL MNIST

Our second task is pixel-by-pixel MNIST (LeCun, 1998). Here the RNN is given a stream of pixels left-to-right, top-to-bottom for a given handwritten digit from the MNIST data set. At the end of the sequence, the network is tasked with identifying the digit it was shown. This problem is difficult, as the RNN must remember an long sequence of 784 singly-presented pixels. We tuned over the same hyperparameters as in the adding problem, looking at performance after $100,000$ training steps. Neither KeRL nor BPTT worked well with a tanh nonlinearity, but both were performed relatively well on an IRNN, Fig. 3. KeRL preferred a slightly lower learning rate η than BPTT.

The BPTT gradients and the KeRL gradient are very strongly aligned during training, Fig. 3. As a result we expect that

$$\Delta C = \frac{dC}{dW_{jk}} \cdot (\Delta W_{jk})_{KeRL} = -\eta * c * |\frac{dC}{dW_{jk}}|^2 < 0 \tag{12}$$

where c is the alignment between the two gradients. So given a small enough learning rate, we expect KeRL to demonstrate hill climbing.

Figure 4: Cross validation accuracy on pixel-by-pixel MNIST using BPTT (red) and KeRL(blue). Normalized dot product between gradients (purple) and RMSProp gradients (green) computed by KeRL and BPTT

Learning Rule	Algorithm	η	gc	η_m
BPTT	RMSProp	10^{-5}	100.0	-
KeRL	RMSProp	10^{-6}	100.0	10^{-8}

Table 3: Hyperparameters for pixel-by-pixel MNIST

While the KeRL algorithm is able to learn almost as quickly on pixel-by-pixel MNIST, it does not converge to as high an asymptotic performance. Still, it performs reasonably well relative to BPTT on the task.

5.3 ONLINE KERL

While KeRL is comparable in speed to BPTT for batch learning, we expect it to be significantly faster for online learning when the time-dependencies are of length T. Untruncated BPTT requires information sent back T steps in time for each weight update, thus the wallclock speed of computation of the gradients at each weight update in online learning scales as T, and the total scaling is thus of order T^2. If BPTT updates are truncated $S < T$ steps back in time, the scaling is ST. KeRL requires no backward unrolling in time, thus online KeRL requires only $O(1)$ time per weight update, for a total scaling of T. As a result, optimized-speed online-KeRL should run faster than truncated online BPTT by a factor T when the trunctation time is similar to the total time-dependencies in the problem.

We tested the performance of online KeRL against UORO, another online learning algorithm, and online BPTT on the A^n, B^n task, where the network must predict the next character in a stream of letters. Each stream consists first of a sequence of n As followed by a sequence of n Bs. The length, n, of the sequences is randomly generated in some range. The network cannot solve this task perfectly, as it can not predict the number of As before it has seen the sequence, but can do well by matching the number of Bs to the number of As. We generated $n \in \{1, 32\}$. The minimum achievable average bit-loss for this task is 0.14.

To compare with results in the literature, we implemented KeRL in an LSTM layer, with $\mathbf{h}$ representing a concatenation of the hidden and cell states (Details in Appendix B). Instead of optimizing

common hyperparameters, we simply used the values from Tallec & Ollivier (2017), which included decaying the learning rate in time as $\eta^t = \eta/(1 + \alpha\sqrt{t})$. However, we varied the learning rate η_m, with $\eta_m^t = \eta_m/(1 + \alpha\sqrt{t})$.

Algorithm-Optimizer	η	η_m	α
KeRL-Adam	10^{-3}	10^{-2}	0.03

Table 4: A^n, B^n hyperparameters

Algorithm	KeRL	1 Step BPTT	2 Steps BPTT	16 Step BPTT	UORO
Bit Loss	0.149	0.178	0.149	.144	.147

Table 5: Average cross-entropy bit-loss (over 10^4 minibatches) on the online A^n, B^n task after 10^6 training steps

Results other than those for KeRL are from Tallec & Ollivier (2017). With very little hyperparameter tuning, online KeRL is able to do very well on the A^n, B^n task, coming close to the minimum entropy. Although 17-step BPTT and UORO outperformed KeRL, we expect speed-optimized versions of KeRL to be much faster (wall clock speed) in direct comparisons.

To test how computation time for truncated-BPTT and KeRL compare in the online setting, we implemented a dummy RNN, where we undertook the required tensor operations using a random vector for both the input data and the error signal (Details in Appendix A). We show the results in Table 6. We see that KeRL is faster than truncated BPTT outside of short truncation lengths.

Algorithm	KeRL	1 Step BPTT	3 Step BPTT	10 Step BPTT	20 Step BPTT
CPU Time	14.1	4.23	7.22	17.8	30.9

Table 6: Average CPU time (in units of 10^{-5} sec.) per time step for truncated BPTT and KeRL.

6 CONCLUSIONS, DISCUSSION & FUTURE WORK

In this paper we show that KeRL, a reduced-rank and forward-running approximation to backpropagation in RNNs, is able to perform roughly comparably to BPTT on a range of hard RNN tasks with long time-dependencies. One may view KeRL as imposing a strong prior on the way in which neural activity from the past should be assigned credit for current performance, through the choice of the temporal kernels K in the eligibility trace, and the choice of the sensitivity weights β. This product of two rank-2 tensors in KeRL (replacing the rank-4 sensitivity tensor for backpropagation in RNNs), assumes that the strength of influence of a neuron on another at fixed time-delay can be summarized by a simple sensitivity weight matrix, β_{ki}, [4], and a decay due to the time difference given by K. This strong simplifying assumption is augmented or mitigated by the ability to (meta)learn the parameters of the sensitivity weights and eligibility trace, giving the rule simultaneous simplicity and flexibility. The form of the KeRL ansatz or prior, if well-suited to learning problems in recurrent networks, serves as a regularizer on the types of solutions the network can find, and could even, for good choices of kernel K, provide better solutions than BPTT. We present limited evidence that KeRL algorithm may combat the vanishing gradient problem with tanh units by imposing a prior of long time-dependencies through the eligibility. Finally, we show that KeRL can be implemented online, where it has a shorter computation cycle than BPTT.

KeRL is a step towards biologically plausible learning. It eschews the segmented two phase backpropagation algorithm for a computation that is largely feedforward. It does not require the segmentation and storage of all past states, instead using an integrated activity or eligibility trace, and it gives rise to a naturally asymmetric structure that is more similar to the brain.

While we show empirically that KeRL performs hill-climbing, there is no guarantee that the gradients computed by KeRL are unbiased. In the future, we hope to show empirically that KeRL is able to perform well on more realistic tasks, and obtain some analytical guarantees on the performance of KeRL. We hope the present contribution inspires more work on training RNNs with shorter, more plausible feedback paths. More generally, we hope that the present work shows how, with the use of reduced-rank tensor products and eligibility traces, to construct entire nested families of relaxed approximations to gradient learning in RNNs.

---

[4]This isn't an unreasonable assumption since we're assuming that some static set of weights W_{ki}^* can produce a desirable time-varying trajectory on the task

REFERENCES

Yoshua Bengio, Thomas Mesnard, Asja Fischer, Saizheng Zhang, and Yuhuai Wu. Stdp as presynaptic activity times rate of change of postsynaptic activity. *arXiv preprint arXiv:1509.05936*, 2015.

Ila R Fiete and H Sebastian Seung. Gradient learning in spiking neural networks by dynamic perturbation of conductances. *Physical review letters*, 97(4):048104, 2006.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256, 2010.

Audrunas Gruslys, Rémi Munos, Ivo Danihelka, Marc Lanctot, and Alex Graves. Memory-efficient backpropagation through time. In *Advances in Neural Information Processing Systems*, pp. 4125–4133, 2016.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.

Sepp Hochreiter, Yoshua Bengio, Paolo Frasconi, Jürgen Schmidhuber, et al. Gradient flow in recurrent nets: the difficulty of learning long-term dependencies, 2001.

Max Jaderberg, Wojciech Marian Czarnecki, Simon Osindero, Oriol Vinyals, Alex Graves, David Silver, and Koray Kavukcuoglu. Decoupled neural interfaces using synthetic gradients. *arXiv preprint arXiv:1608.05343*, 2016.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Timothy P Lillicrap, Daniel Cownden, Douglas B Tweed, and Colin J Akerman. Random synaptic feedback weights support error backpropagation for deep learning. *Nature communications*, 7:13276, 2016.

Arild Nøkland. Direct feedback alignment provides learning in deep neural networks. In *Advances in neural information processing systems*, pp. 1037–1045, 2016.

Yann Ollivier, Corentin Tallec, and Guillaume Charpiat. Training recurrent networks online without backtracking. *arXiv preprint arXiv:1507.07680*, 2015.

Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural networks. In *International Conference on Machine Learning*, pp. 1310–1318, 2013.

David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning internal representations by error propagation. Technical report, California Univ San Diego La Jolla Inst for Cognitive Science, 1985.

Benjamin Scellier and Yoshua Bengio. Equilibrium propagation: Bridging the gap between energy-based models and backpropagation. *Frontiers in computational neuroscience*, 11:24, 2017.

Corentin Tallec and Yann Ollivier. Unbiased online recurrent optimization. *arXiv preprint arXiv:1702.05043*, 2017.

Tijmen Tieleman and Geoffrey Hinton. Lecture 6.5-rmsprop: Divide the gradient by a running average of its recent magnitude. *COURSERA: Neural networks for machine learning*, 4(2):26–31, 2012.

Stéfan van der Walt, S Chris Colbert, and Gael Varoquaux. The numpy array: a structure for efficient numerical computation. *Computing in Science & Engineering*, 13(2):22–30, 2011.

Paul J Werbos. Backpropagation through time: what it does and how to do it. *Proceedings of the IEEE*, 78(10):1550–1560, 1990.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

Ronald J Williams and David Zipser. A learning algorithm for continually running fully recurrent neural networks. *Neural computation*, 1(2):270–280, 1989.

A   IMPLEMENTATION DETAILS

For the adding problem and pixel-by-pixel, we tested performance by varying η and gc over several orders of magnitude: $\eta = \{1e-03, 1e-04, 1e-05, 1e-06, 1e-07\}$, $gc = \{1, 10, 100\}$, using both Adam (Kingma & Ba (2014)) and RMSProp (Tieleman & Hinton (2012)). We then varied $\eta_m = \{1e-03, 1e-04, 1e-05, 1e-06, 1e-07\}$ on KeRL. We found that KeRL was relatively robust across η_m. We chose the hyperparameters that performed best on the task for sequence length 400. Besides the recurrent weights of the IRNN, all other weight matrices were initialized using Xavier initialization (Glorot & Bengio (2010)). We initialized β with Xavier initialization for the tanh RNN, and to the identity for the IRNN. This choice was motivated by the initial sensitivity of the IRNN ($\frac{\partial h_i^t}{\partial h_j^{t-\tau}} = \delta_{ij}$). For the kernels, we initialized $\gamma_j = (\frac{1}{\text{sequence length}})^{n_j}$ where the $n_j \sim U([0,2])$ are sampled uniformly and independently. Finally we used the alternative cost function described in footnote 2. We trained on both of these tasks using the numpy (Walt et al. (2011)) package in python.

For the dummy RNN, we used the numpy package (Walt et al. (2011)) in python for our matrix algebra, and we chose 100 hidden nodes, 100 input nodes and a tanh nonlinearity. We called "matmul" for matrix multiplication and "einsum" for other tensor operations. We used the "tanh" and "cosh" functions to compute the nonlinearity and its derivatives.

B   IMPLEMENTING KeRL ON AN LSTM

In this section we describe how to implement KeRL on an LSTM Hochreiter & Schmidhuber (1997) in more detail. The dynamics of the LSTM (without peepholes) are as follows

$$
\begin{aligned}
\mathbf{i}^t &= \sigma(W^{ii}\mathbf{x}^t + W^{ih}\mathbf{h}^{t-1} + b^i) \\
\mathbf{f}^t &= \sigma(W^{fi}\mathbf{x}^t + W^{fh}\mathbf{h}^{t-1} + b^f) \\
\mathbf{g}^t &= \tanh(W^{gi}\mathbf{x}^t + W^{gh}\mathbf{h}^{t-1} + b^g) \\
\mathbf{o}^t &= \sigma(W^{oi}\mathbf{x}^t + W^{oh}\mathbf{h}^{t-1} + b^o) \\
\mathbf{c}^t &= \mathbf{f}^t\mathbf{c}^{t-1} + \mathbf{g}^t\mathbf{i^t} \\
\mathbf{h}^t &= \mathbf{o}^t\tanh(\mathbf{c}^t)
\end{aligned}
\tag{13}
$$

where $\mathbf{h}^t$ is the hidden state, $\mathbf{c}^t$ is the cell state and $\mathbf{i}^t, \mathbf{f}^t, \mathbf{g}^t, \mathbf{o}^t$ are the input, forget, cell and output gates respectively. In order to implement KeRL we consider the total hidden state $\mathbf{H} = \{\mathbf{h}, \mathbf{c}\}$ to be a concatenation of the hidden and cell states. This a suitable choice, as the next total hidden state can be fully determined by the current total hidden state and the parameters of the network. We let the first n indices of $\mathbf{H}$ be the hidden state and the next n be the cell state. Derivatives with respect to the cost function are given by

$$
\frac{dC}{d\theta} = \sum_{i,j} \frac{\partial C}{\partial H_i^t} \frac{\partial H_i^t}{\partial H_j^{t-\tau}} \frac{\partial H_j^{t-\tau}}{\partial \theta}
\tag{14}
$$

where θ stands in for the twelve trainable weights and biases. Our sensitivity Ansatz is $\frac{\partial H_i^t}{\partial H_j^{t-\tau}} = \beta_{ij}e^{-\gamma_j\tau}$. The input terms are now partial derivatives of this total hidden state with respect to the input parameters. As an example

$$
\frac{\partial H_j^t}{\partial W_{lk}^{ii}} =
\begin{cases}
\frac{\partial h_j^t}{\partial W_{lk}^{ii}} & \text{if } j \leq n \\
\frac{\partial c_{j-n}^t}{\partial W_{lk}^{ii}} & \text{if } j > n
\end{cases}
=
\begin{cases}
0 & \text{if } j \leq n \\
\frac{\partial c_{j-n}^t}{\partial W_{lk}^{ii}} & \text{if } j > n
\end{cases}
\tag{15}
$$

where $\frac{\partial h_j^t}{\partial W^{ii}} = 0$ since the hidden state only depends on these parameters through the cell state. As earlier, we train our input weights and kernels by tracking the effect of applying perturbations during the forward pass. Our sensitivity weights β are a 2 x 2 array of matrices linking the cell and hidden states of the past to the current cell and hidden states. Since readout occurs from the hidden state, $\frac{\partial C}{\partial c_i^t} = 0$, and we only need to consider $\frac{\partial h_i^t}{\partial c_j^{t-\tau}} = \beta_{ij}^{hc} e^{-\gamma_j^c \tau}$ and $\frac{\partial h_i^t}{\partial h_j^{t-\tau}} = \beta_{ij}^{hh} e^{-\gamma_j^h \tau}$. The sensitivity weights β^{hc}, β^{hh} and time scales γ^c, γ^h can be learned as in the case of the simple recurrent network by applying perturbations $\xi^{h,t}, \xi^{c,t}$ to hidden and cell state and minimizing the cost function: $C_{\beta,\gamma} = \sum_i (\tilde{h}_i^t - h_i^t - \sum_{\tau,j} \beta_{ij}^{hc} \exp(-\gamma_j^c \tau) \xi_j^{c,t-\tau} - \sum_{\tau,j} \beta_{ij}^{hh} \exp(-\gamma_j^h \tau) \xi_j^{h,t-\tau})^2$. Our example gradient with respect to the input weights of the input gate is given by

$$\frac{dC}{dW_{jk}^{ii}} = \sum_i \frac{dC}{dh_i^t} \beta_{ij}^{hc} \sum_{\tau=0} \exp(-\gamma_j^c \tau) g_j^{t-\tau} \sigma'(\mathbf{g}_j^{t-\tau}) x_k^{t-\tau} \tag{16}$$

where net_j^t represents the presynaptic input to i_j^t. The other gradients can be calculated in an analogous manner.