REINFORCEMENT LEARNING ON WEB INTERFACES USING WORKFLOW-GUIDED EXPLORATION

ABSTRACT

Reinforcement learning (RL) agents improve through trial-and-error, but when reward is sparse and the agent cannot discover successful action sequences, learning stagnates. This has been a notable problem in training deep RL agents to perform web-based tasks, such as booking flights or replying emails, where a single mistake can ruin the entire sequence of actions. A common remedy is to "warm-start" the agent by pre-training it to mimic expert demonstrations, but this is prone to overfitting. Instead, we propose to *constrain exploration* using demonstrations. From each demonstration, we induce high-level "workflows" which constrain the allowable actions at each time step to be similar to those in the demonstration (e.g., "Step 1: click on a textbox; Step 2: enter some text"). Our exploration policy then learns to identify successful workflows and samples actions that satisfy these workflows. Workflows prune out bad exploration directions and accelerate the agent's ability to discover rewards. We use our approach to train a novel neural policy designed to handle the semi-structured nature of websites, and evaluate on a suite of web tasks, including the recent World of Bits benchmark. We achieve new state-of-the-art results, and show that *workflow-guided exploration* improves sample efficiency over behavioral cloning by more than 10x.

1 INTRODUCTION

We are interested in training reinforcement learning (RL) agents to use the Internet (e.g., to book flights or reply to emails) by directly controlling a web browser. Such systems could expand the capabilities of AI personal assistants (Stone & Soper, 2014), which are currently limited to interacting with machine-readable APIs, rather than the much larger world of human-readable web interfaces.

A reinforcement learning agent improves itself through trial-and-error interaction with its environment (Sutton & Barto, 1998). But this learning process can be very slow in tasks with sparse reward, where the vast majority of naive action sequences lead to no reward signal (Nair et al., 2017; Veceriki et al., 2017). This is the case for many web tasks, which involve a large action space (the agent can type or click anything) and require a well-coordinated sequence of actions to succeed.

A common countermeasure in RL is to pre-train the agent to mimic expert demonstrations via behavioral cloning (Pomerleau, 1991; Kim et al., 2013), encouraging it to take similar actions in similar states. But in environments with diverse and complex states such as websites, demonstrations may cover only a small slice of the state space, and it is difficult to generalize beyond these states (overfitting). Indeed, previous work has found that warm-starting with behavioral cloning often fail to improve over pure RL (Shi et al., 2017). At the same time, simple strategies to combat overfitting (e.g. using fewer parameters or regularization) will cripple the policy's flexibility (Bitzer et al., 2010), which is required for complex spatial and structural reasoning in user interfaces.

In this work, we propose a different method for leveraging demonstrations. Rather than training an agent to directly mimic them, we use demonstrations to *constrain exploration*. By pruning away bad exploration directions, we can accelerate the agent's ability to discover sparse rewards. Furthermore, because the agent is not directly exposed to demonstrations, we are free to use a sophisticated neural policy with a reduced risk of overfitting.

To constrain exploration, we employ the notion of a "workflow" (Deka et al., 2016). For instance, given an expert demonstration of how to forward an email, we might infer the following workflow:

Preprocessing:
    for all demonstrations d **do**
        Induce workflow lattice from d

Every iteration:
    Observe goal g
    Choose a workflow lattice based on g
    π_w samples a workflow from the lattice
    Roll out an episode e from the workflow
    Use e to update π_w
    if e gets reward $+1$ **then**
        Add e to buffer

Periodically:
    if buffer size > threshold **then**
        Sample episodes from buffer
        Update π_n with episodes
    π_n rolls out episode e
    Update π_n and critic V with e
    if e gets reward $+1$ **then**
        Add e to buffer

Figure 1: *Workflow-guided exploration (WGE).* After inducing workflow lattices from demonstrations, the workflow policy π_w performs exploration by sampling episodes from sampled workflows. Successful episodes are saved to a replay buffer, which is used to train the neural policy π_n.

Click an email title → Click a "Forward" button
→ Type an email address into a textbox → Click a "Send" button

</div>

This workflow is more *high-level* than an actual policy: it does not tell us exactly which email to click or which textbox to type into, but it helpfully constrains the set of actions at each timestep. Furthermore, unlike a policy, it does not depend on the environment state: it is just a sequence of steps that can be followed blindly. In this sense, a workflow is *environment-blind*. A learned policy certainly cannot be environment-blind, but we find that this is a good inductive bias for exploration in many web-based tasks.

To leverage workflows, we propose the *workflow-guided exploration* (WGE) framework as illustrated in Figure 1:

1. For each demonstration, we extract a lattice of workflows that are consistent with the actions observed in the demonstration (Section 3).

2. We then define a *workflow exploration policy* π_w (Section 4), which explores by first selecting a workflow, and then sampling actions that fit the workflow. This policy gradually learns which workflow to select through trial-and-error reinforcement learning.

3. Reward-earning episodes discovered during exploration enter a replay buffer, which we use to train a more powerful and expressive neural network policy π_n (Section 5).

A key difference between the web and traditional RL domains such as robotics (Atkeson & Schaal, 1997) or game-playing (Bellemare et al., 2013) is that the state space involves a mix of structured (e.g. HTML) and unstructured inputs (e.g. natural language and images). This motivates us to propose a novel neural network policy (DOMNET), specifically designed to perform flexible relational reasoning over the tree-structured HTML representation of websites.

We evaluate *workflow-guided exploration* and DOMNET on a suite of web interaction tasks, including the MiniWoB benchmark of (Shi et al., 2017), the flight booking interface for Alaska Airlines, and a new collection of tasks that we constructed to study additional challenges such as noisy environments, variation in natural language, and longer time horizons. Compared to previous results on MiniWoB Shi et al. (2017), which used 10 minutes of demonstrations per task (approximately 200 demonstrations on average), our system achieves much higher success rates and establishes new state-of-the-art results with only 3–10 demonstrations per task, enabling agents that can learn new tasks with guidance from just a single user.

Figure 2: From each demonstration, we induce a workflow lattice based on the actions in that demonstration. Given a new environment, the workflow policy samples a workflow (a path in the lattice, as shown in bold) and then samples actions that fit the steps of the workflow.

2 SETUP

In the standard reinforcement learning setup, an agent learns a policy $\pi(a|s)$ that maps a state s to a probability distribution over actions a. At each time step t, the agent observes an environment state s_t and chooses an action a_t, which leads to a new state s_{t+1} and a reward $r_t = r(s_t, a_t)$. The goal is to maximize the expected return $\mathbb{E}[R]$, where $R = \sum_t \gamma^t r_{t+1}$ and γ is a discount factor. Typical reinforcement learning agents learn through trial-and-error: rolling out episodes $(s_1, a_1, \ldots, s_T, a_T)$ and adjusting their policy based on the results of those episodes.

We focus on settings where the reward is delayed and sparse. Specifically, we assume that (1) the agent receives reward only at the end of the episode, and (2) the reward is high (e.g., $+1$) for only a small fraction of possible trajectories and is uniformly low (e.g., -1) otherwise. With large state and action spaces, it is difficult for the exploration policy to find episodes with positive rewards, which prevents the policy from learning effectively.

In all the web interaction tasks we study, we further assume that the agent is given a goal g, which can either be a structured key-value mapping (e.g., {task: forward, from: Bob, to: Alice}) or a natural language utterance (e.g., *"Forward Bob's message to Alice"*). The agent's state s consists of the goal g and the state of the current web page, represented as an HTML DOM tree. We restrict the action space to click actions `Click(e)` and type actions `Type(e,t)`, where `e` is a leaf element of the DOM tree, and `t` is a string from the goal g (a value from a structured goal, or consecutive tokens from a natural language goal). Figure 2 shows an example episode for an email processing task. The agent receives $+1$ reward if the task is completed correctly, and -1 reward otherwise.

3 INDUCING WORKFLOWS FROM DEMONSTRATIONS

Given a collection of expert demonstrations $d = (\tilde{s}_1, \tilde{a}_1, \ldots, \tilde{s}_T, \tilde{a}_T)$, we would like explore actions a_t that are "similar" to the demonstrated actions $\tilde{a}_t$. Workflows capture this notion of similarity by specifying a set of similar actions at each time step. Formally, a workflow $z_{1:T}$ is a sequence of workflow steps, where each step z_t is a function that takes a state s and returns a constrained set $z_t(s)$ of similar actions. We use a compositional constraint language (Appendix A) to describe workflow steps. For example, with $z = $ `Click(Tag("img"))`, the set $z(s)$ contains click actions on any DOM element in s with tag `img`.

We induce a set of workflows from each demonstration $d = (\tilde{s}_1, \tilde{a}_1, \ldots, \tilde{s}_T, \tilde{a}_T)$ as follows. For each time step t, we enumerate a set Z_t of all possible workflow steps z_t such that $\tilde{a}_t \in z_t(\tilde{s}_t)$. The set of workflows is then the cross product $Z_1 \times \cdots \times Z_T$ of the steps. We can represent the induced workflows as paths in a *workflow lattice* as illustrated in Figure 2.

To handle noisy demonstrations where some actions are unnecessary (e.g., when the demonstrator accidentally clicks on the background), we add shortcut steps that skip certain time steps. We also add shortcut steps for any consecutive actions that can be collapsed into a single equivalent action (e.g., collapsing two type actions on the same DOM element into a single `Type` step). These shortcuts allow the lengths of the induced workflows to differ from the length of the demonstration. We henceforth ignore these shortcut steps to simplify the notation.

The induced workflow steps are not equally effective. For example in Figure 2, the workflow step `Click(Near(Text("Bob")))` (Click an element near text "Bob") is too specific to the demonstration scenario, while `Click(Tag("div"))` (Click on any `<div>` element) is too general and covers too many irrelevant actions. The next section describes how the workflow policy π_w learns which workflow steps to use.

4 WORKFLOW EXPLORATION POLICY

Our workflow policy interacts with the environment to generate an episode in the following manner. At the beginning of the episode, the policy conditions on the provided goal g, and selects a demonstration d that carried out a similar goal:

$$d \sim p(d|g) \propto \exp[\rho(g, g_d)] \tag{1}$$

where ρ is a similarity function over goals and g_d is the goal in demonstration d. In our tasks, we simply let ρ be 1 if the structured goals share the same fields, and $-\infty$ otherwise.

Then, at each time step t with environment state s_t, we sample a workflow step z_t according to the following distribution:

$$z_t \sim \pi_w(z|d, t) \propto \exp(\psi_{z,t,d}), \tag{2}$$

where each $\psi_{z,t,d}$ is a separate scalar parameter to be learned. Finally, we sample an action a_t uniformly from the set $z_t(s_t)$.

$$a_t \sim p(a|z_t, s_t) = |z_t(s_t)|^{-1} \tag{3}$$

The overall probability of exploring an episode $e = (s_1, a_1, \ldots, s_T, a_T)$ is then:

$$p(e|g) = p(d|g) \prod_{t=1}^{T} p(s_t|s_{t-1}, a_{t-1}) \sum_z p(a_t|z, s_t) \pi_w(z|d, t) \tag{4}$$

where $p(s_t|s_{t-1}, a_{t-1})$ is the environment transition model.

Note that $\pi_w(z|d, t)$ is not a function of the environment states s_t at all. Its decisions only depend on the selected demonstration and the current time t. This *environment-blindness* means that the workflow policy uses far fewer parameters than a state-dependent policy.

Sampled episodes from the workflow policy that receive a positive reward are stored in a replay buffer, which will be used for training the neural policy π_n.

To train the workflow policy, we use a variant of the REINFORCE algorithm (Williams, 1992; Sutton & Barto, 1998). In particular, we roll out an episode $e = (s_1, a_1, \ldots, s_T, a_T)$ according to $p(e|g)$, and then approximate the gradient using the unbiased estimate

$$\sum_t (G_t - v_{d,t}) \nabla_\psi \log \sum_z p(a_t|z, s_t) \pi_w(z|d, t), \tag{5}$$

where G_t is the return at time step t and $v_{d,t}$ is a baseline term for variance reduction.

5 NEURAL POLICY

As outlined in Figure 1, the neural policy is learned using both on-policy and off-policy updates (where episodes are drawn from the replay buffer). Both updates use A2C, the synchronous version

of the advantage actor-critic algorithm (Mnih et al., 2016). Since only episodes with reward $+1$ enter the replay buffer, the off-policy updates behave similarly to supervised learning on optimal trajectories. Furthermore, successful episodes discovered during on-policy exploration are also added to the replay buffer.

Model architecture. We propose DOMNET, a neural architecture that captures the spatial and hierarchical structure of the DOM tree. As illustrated in Figure 5, the model first embeds the DOM elements and the input goal, and then applies a series of attentions on the embeddings to finally produce a distribution over actions $\pi_n(a|s)$ and a value function $V(s)$, the critic. We highlight our novel DOM embedder, and defer other details to Appendix C.

We design our DOM embedder to capture the various interactions between DOM elements, similar to recent work in graph embeddings. In particular, DOM elements that are "related" (e.g., a checkbox and its associated label) should pass their information to each other.

To embed a DOM element e, we first compute the *base embedding* v_{base}^e by embedding and concatenating its attributes (tag, classes, text, etc.). In order to capture the relationships between DOM elements, we next compute two types of *neighbor embeddings*:

1. We define *spatial neighbors* of e to be any element e' within 30 pixels from e, and then sum up their base embeddings to get the *spatial neighbor embedding* v_{spatial}^e.

2. We define *depth-k tree neighbors* of e to be any element e' such that the least common ancestor of e and e' in the DOM tree has depth at most k. Intuitively, tree neighbors of a higher depth are more related. For each depth k, we apply a learnable affine transformation f on the base embedding of each depth-k tree neighbor e', and then apply max pooling to get $v_{\text{tree}[k]}^e = \max f(v_{\text{base}}^{e'})$. We let the *tree neighbor embedding* v_{tree}^e be the concatenation of $v_{\text{tree}[k]}^e$ for $k = 3, 4, 5, 6$.

Finally, we define the *goal matching embedding* v_{match}^e to be the sum of the embeddings of all words in e that also appear in the goal. The final embedding v_{DOM}^e of e is the concatenation of the four embeddings $[v_{\text{base}}^e; v_{\text{spatial}}^e; v_{\text{tree}}^e; v_{\text{match}}^e]$.

6 EXPERIMENTS

6.1 TASK SETUPS

We evaluate workflow-guided exploration and DOMNET on a suite of interactive web tasks:

1. *MiniWoB*: the MiniWoB benchmark of Shi et al. (2017)

2. *MiniWoB++*: a new set of tasks that we constructed to incorporate additional challenges not present in MiniWoB, such as stochastic environments and variation in natural language.

3. *Alaska*: the mobile flight booking interface for Alaska Airlines, inspired by the FormWoB benchmark of Shi et al. (2017).

We describe the common task settings of the MiniWoB and MiniWoB++ benchmarks, and defer the description of the Alaska benchmark to Section 6.3.3.

Environment. Each task contains a 160px $\times$ 210px environment and a goal specified in text. The majority of the tasks return a single sparse reward at the end of the episode; either $+1$ (success) or -1 (failure). For greater consistency among tasks, we disabled *all* partial rewards in our experiments. The agent has access to the environment via a Selenium web driver interface.

The public MiniWoB benchmark[1] contains 80 tasks. We filtered for the 40 tasks that only require actions in our action space, namely clicking on DOM elements and typing strings from the input goal. Many of the excluded tasks involve somewhat specialized reasoning, such as being able to compute the angle between two lines, or solve algebra problems. For each task, we used Amazon

---

[1]`http://alpha.openai.com/miniwob/`

Figure 3: Success rates of different approaches (Blue = SHI17, Orange = DOMNET+BC+RL, Red = DOMNET+WGE) on the MiniWoB tasks. DOMNET+WGE outperforms SHI17 on all but two tasks and effectively solves a vast majority.

Task	Description	Steps	BC+RL	π_w only	WGE
click-checkboxes	Click 0–6 specified checkboxes	7	98	81	**100**
click-checkboxes-large[+]	…5–12 targets	13	0	43	**84**
click-checkboxes-soft[+]	…specifies synonyms of the targets	7	51	34	**94**
click-checkboxes-transfer[+]	…training data has 0-3 targets	7	**64**	17	**64**
click-tab-2	Search in 3 tabs for the right link	3	64	33	**98**
click-tab-2-hard[+]	…2–6 tabs	6	47	39	**92**
multi-ordering[+]	Fill a form with varying field orderings	4	5	78	**100**
multi-layout[+]	Fill a form with varying UIs layouts	4	99	9	**100**
social-media	Do an action on the specified Tweet	2	15	2	**100**
social-media-all[+]	…on all matching Tweets	12	**1**	0	0
social-media-some[+]	…on specified no. of matching Tweets	12	2	3	**42**
email-inbox	Perform tasks on an email inbox	4	43	3	**99**
email-inbox-nl[+]	…natural language goal	4	28	0	**93**

Table 1: Results on additional tasks. (+ = MiniWoB++, Steps = maximum number of steps needed)

Mechanical Turk to collect 10 demonstrations, which record all mouse and keyboard events along with the state of the DOM when each event occurred.

Evaluation metric. We report *success rate*: the percentage of test episodes with reward +1. Since we have removed partial rewards, success rate is a linear scaling of the average reward, and is equivalent to the definition of success rate in Shi et al. (2017).

6.2 MAIN RESULTS

In Figure 3, we compare the success rates across the MiniWoB tasks of the following approaches:

- SHI17: the system from Shi et al. (2017), pre-trained with behavioral cloning on 10 minutes of demonstrations (approximately 200 episodes on average) and fine-tuned with RL. Unlike DOMNET, this system primarily uses a pixel-based representation of the state.[2]

- DOMNET+BC+RL: our proposed neural policy, DOMNET, but pre-trained with behavioral cloning and fine-tuned with RL, like SHI17. We apply early stopping based on the reward on a validation set.

- DOMNET+WGE: our proposed neural policy, DOMNET, trained with workflow-guided exploration. Like DOMNET+BC+RL, we also apply early stopping.

We observe that even with standard BC+RL training, DOMNET already provides significant improvements over SHI17 on most tasks. Workflow-guided exploration then enables DOMNET to perform even better on several of the more difficult tasks, which we analyze in the next section. Some of the workflows that the workflow policy π_w learns are shown in Appendix B.

6.3 ANALYSIS

6.3.1 MINIWOB++ BENCHMARK

We constructed and released the MiniWoB++ benchmark of tasks to study additional challenges a web agent might encounter, including: longer time horizons (click-checkboxes-large), "soft" reasoning about natural language (click-checkboxes-soft), and stochastically varying layouts (multi-orderings, multi-layouts). Table 1 provides details of the tasks, and compares the performance of three different policies: DOMNET trained with BC+RL, DOMNET trained with WGE (our full approach), and π_w (the learned workflow exploration policy).

We include π_w to illustrate that the neural policy learned with WGE can achieve high success rates even when the workflow policy π_w performs poorly. The workflow policy by itself is too simplistic to work well at test time for several reasons:

1. Workflows ignore environment state and therefore cannot respond to unexpected events, such as the popups that appear in login-user-popup.
2. The workflow constraint language lacks the expressivity to specify certain actions, such as clicking on synonyms of a particular word in click-checkboxes-soft.
3. The workflow policy lacks the expressivity to always select the correct workflow for a given goal.

Nonetheless the workflow policy is sufficiently constrained to discover reward some of the time, and the neural policy is able to learn the right behavior from such episodes.

Comparing BC+RL and WGE, we noticed two common failure modes which seem to be mitigated by WGE: first, the model has a tendency to take actions which prematurely end the episode (e.g., hitting "Submit" in click-checkboxes-large before all the necessary boxes are checked), and second, the model can occasionally get stuck in cyclic behavior such as repeatedly checking and unchecking the same checkbox.

6.3.2 NATURAL LANGUAGE INPUTS

While MiniWoB tasks provide structured goals, we can also apply our approach to natural language goals. In the email-inbox-nl task, we collected natural language templates by asking annotators to paraphrase the task goals (e.g., *"Forward Bob's message to Alice"* → *"Email Alice the email I got from Bob"*) and then abstracting out the fields (*"Email <TO> the email I got from <FROM>"*).

During training, the workflow policy π_w receives states with both the structured goal and the natural language utterance generated from a random template, while the neural policy π_n receives only the utterance. At test time, the neural policy is evaluated on unseen utterances. The results in Table 1 show that the WGE model can learn to understand natural language goals (93% success rate).

Note that the workflow policy needs access to the structured inputs only because our constraint language for workflow steps operates on structured inputs. The constraint language could potentially be modified to work with utterances directly (e.g., `After("to")` extracts the utterance word after *"to"*), but we leave this for future work.

6.3.3 SCALING TO REAL WORLD TASKS

We applied our approach on the Alaska benchmark, a more realistic flight search task on the Alaska Airlines mobile site inspired by the FormWoB task in Shi et al. (2017). In this task, the agent must complete the flight search form with the provided information (6–7 fields). We ported the web page to the MiniWoB framework with a larger 375px $\times$ 667px screen, replaced the server backend with a surrogate JavaScript function, and clamped the environment date to March 1.

Following Shi et al. (2017), we give partial reward based on the fraction of correct fields in the submitted form if all required fields are filled in. Despite this partial reward scheme, the reward is still extremely sparse: there are approximately 80 DOM elements (compared to $\approx$ 10–50 in MiniWoB tasks), and a typical episode requires at least 11 actions involving various types of widgets such as

---

[2]It is augmented with filters that activate on textual elements which overlap with goal text.

Figure 4: Average test reward vs. time using different numbers of demonstrations. (Blue = DOM-NET+BC+RL 10 demonstrations, Cyan = DOMNET+BC+RL 250 demonstrations, Red = DOM-NET+WGE 10 demonstrations, Purple = DOMNET+WGE 5 demonstrations)

autocompletes and date pickers. The probability that a random agent gets positive reward is less than 10^{-20}.

We first performed experiments on Alaska-Shi17, a clone of the original Alaska Airlines task in Shi et al. (2017), where the goal always specifies a roundtrip flight (two airports and two dates). On their dataset, our approach, using only 1 demonstration, achieves an average reward of 0.97, compared to their best result of 0.57, which uses around 80 demonstrations.

Our success motivated us to test on a more difficult version of the task which additionally requires selecting flight type (a checkbox for one-way flight), number of passengers (an increment-decrement counter), and seat type (hidden under an accordion). We achieve an average reward of 0.86 using 10 demonstrations. This demonstrates our method can handle long horizons on real-world websites.

6.3.4 SAMPLE EFFICIENCY

We investigate the demonstration efficiency of BC+RL and WGE in Figure 4. Notably, training with 250 using BC+RL still does not achieve the performance of WGE with 10 demonstrations. In addition, WGE achieves the same asymptotic test reward even when decreasing the number of demonstrations to 5, although training is considerably slower in click-tab-2-hard.

7 DISCUSSION

Learning agents for the web. Previous work on learning agents for web interactions falls into two main categories. First, simple programs may be specified by the user (**?**) or may be inferred from demonstrations (Allen et al., 2007). Second, soft policies may be learned from scratch or "warm-started" from demonstrations (Shi et al., 2017). Notably, sparse rewards prevented (Shi et al., 2017) from successfully learning, even when using a moderate number of demonstrations. Our work combines ideas from both approaches by inferring workflows from demonstrations to guide a neural policy, which allows us to learn even in the face of sparse rewards.

Sparse rewards without prior knowledge. Numerous works attempt to address sparse rewards without incorporating any additional prior knowledge. Exploration methods (Osband et al., 2016; Chentanez et al., 2005; Weber et al., 2017) help the agent better explore the state space to encounter more reward; shaping rewards (Ng et al., 1999) directly modify the reward function encourage certain behaviors; and other works (Jaderberg et al., 2016; Andrychowicz et al., 2017) augment the reward signal with additional unsupervised reward. However, without prior knowledge, helping the agent receive additional reward is difficult in general. We discuss two main methods that do incorporate prior knowledge below: imitation learning and hierarchical reinforcement learning.

Imitation learning. In the cases where the above methods don't work, demonstrations can be used for additional powerful supervision. Imitation learning methods fall into two main categories: 1) methods that directly learn the policy from the demonstrations (Ross et al., 2011; Ross & Bagnell,

2010; Nair et al., 2017) and 2) inverse reinforcement learning (IRL) methods, which first learn a reward function from the demonstrations and then use the reward function to learn policy (Abbeel & Ng, 2004; Finn et al., 2016; Ho & Ermon, 2016; Stadie et al., 2017; Baram et al., 2017).

Hierarchical reinforcement learning. Hierarchical reinforcement learning (HRL) methods decompose complex tasks into simpler subtasks that are easier to learn. Three main HRL frameworks exist: abstract actions (Sutton et al., 1999; Konidaris & Barto, 2007; Hauser et al., 2008), abstract partial policies (Parr & Russell, 1998) and abstract states (Roderick et al., 2017; Dietterich, 1998; Li et al., 2006). These frameworks require varying amounts of prior knowledge. The original formulations required programmers to manually specify the decomposition of the complex task, while Andreas et al. (2016) only requires supervision to identify subtasks, and Bacon et al. (2017); Daniel et al. (2016) learn the decomposition fully automatically, at the cost of performance.

Within the HRL methods, our work is closest to Parr & Russell (1998) and the line of work on constraints in robotics (Phillips et al., 2016; Perez-D'Arpino & Shah, 2017). Parr & Russell (1998) specifies partial policies, which constrain the set of possible actions at each state, similar to our workflow items. However, instantiations of the HAM framework (Andre, 2003; Marthi & Guestrin, 2005), require programmers to specify these constraints. In contrast, in our work, we automatically induce these constraints from user demonstrations, which do not require special skills to provide. Phillips et al. (2016); Perez-D'Arpino & Shah (2017) also resemble our work, in learning constraints from demonstrations, but differ in the way they use the demonstrations. Whereas our work uses the learned constraints for exploration, Phillips et al. (2016) only uses the constraints for planning and Perez-D'Arpino & Shah (2017) build a knowledge base of constraints to use at test time.

Summary. Our workflow-guided framework represents a judicious combination of demonstrations, abstractions, and expressive neural policies. We leverage the targeted information of demonstrations and the inductive bias of workflows. But this is only used for exploration, protecting the expressive neural policy from overfitting. As a result, we are able to learn rather complex policies from a very sparse reward signal and very few demonstrations.

Reproducibility. Our code and data is made available at https://github.com/anonymous.

REFERENCES

P. Abbeel and A. Ng. Apprenticeship learning via inverse reinforcement learning. In *International Conference on Machine Learning (ICML)*, 2004.

J. Allen, N. Chambers, G. Ferguson, L. Galescu, H. Jung, M. Swift, and W. Taysom. PLOW: A collaborative task learning agent. In *Association for the Advancement of Artificial Intelligence (AAAI)*, pp. 1514–1519, 2007.

D. Andre. *Programmable reinforcement learning agents*. PhD thesis, University of California, Berkeley, 2003.

J. Andreas, D. Klein, and S. Levine. Modular multitask reinforcement learning with policy sketches. *arXiv preprint arXiv:1611.01796*, 2016.

M. Andrychowicz, F. Wolski, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, P. Abbeel, and W. Zaremba. Hindsight experience replay. *arXiv preprint arXiv:1707.01495*, 2017.

C. G. Atkeson and S. Schaal. Robot learning from demonstration. In *International Conference on Machine Learning (ICML)*, volume 97, pp. 12–20, 1997.

P. Bacon, J. Harb, and D. Precup. The option-critic architecture. In *Association for the Advancement of Artificial Intelligence (AAAI)*, pp. 1726–1734, 2017.

N. Baram, O. Anschel, I. Caspi, and S. Mannor. End-to-end differentiable adversarial imitation learning. In *International Conference on Machine Learning (ICML)*, pp. 390–399, 2017.

M. G. Bellemare, Y. Naddaf, J. Veness, and M. Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research (JAIR)*, 47: 253–279, 2013.

S. Bitzer, M. Howard, and S. Vijayakumar. Using dimensionality reduction to exploit constraints in reinforcement learning. In *International Conference on Intelligent Robots and Systems (IROS)*, pp. 3219–3225, 2010.

N. Chentanez, A. G. Barto, and S. P. Singh. Intrinsically motivated reinforcement learning. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 1281–1288, 2005.

C. Daniel, G. Neumann, O. Kroemer, and J. Peters. Hierarchical relative entropy policy search. *Journal of Machine Learning Research (JMLR)*, 17:3190–3239, 2016.

B. Deka, Z. Huang, and R. Kumar. Erica: Interaction mining mobile apps. In *User Interface Software and Technology (UIST)*, pp. 767–776, 2016.

T. G. Dietterich. The MAXQ method for hierarchical reinforcement learning. In *International Conference on Machine Learning (ICML)*, 1998.

C. Finn, S. Levine, and P. Abbeel. Guided cost learning: Deep inverse optimal control via policy optimization. In *International Conference on Machine Learning (ICML)*, pp. 49–58, 2016.

K. Hauser, T. Bretl, K. Harada, and J. Latombe. Using motion primitives in probabilistic sample-based planning for humanoid robots. *Algorithmic foundation of robotics*, 7:507–522, 2008.

J. Ho and S. Ermon. Generative adversarial imitation learning. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 4565–4573, 2016.

M. Jaderberg, V. Mnih, W. M. Czarnecki, T. Schaul, J. Z. Leibo, D. Silver, and K. Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. *arXiv preprint arXiv:1611.05397*, 2016.

B. Kim, A. massoud Farahmand, J. Pineau, and D. Precup. Learning from limited demonstrations. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 2859–2867, 2013.

G. Konidaris and A. G. Barto. Building portable options: Skill transfer in reinforcement learning. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2007.

L. Li, T. J. Walsh, and M. L. Littman. Towards a unified theory of state abstraction for mdps. In *International Symposium on Artificial Intelligence and Mathematics (ISAIM)*, 2006.

B. Marthi and C. Guestrin. Concurrent hierarchical reinforcement learning. In *International Joint Conference on Artificial Intelligence (IJCAI)*, 2005.

V. Mnih, A. P. Badia, M. Mirza, A. Graves, T. P. Lillicrap, T. Harley, D. Silver, and K. Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International Conference on Machine Learning (ICML)*, 2016.

A. Nair, B. McGrew, M. Andrychowicz, W. Zaremba, and P. Abbeel. Overcoming exploration in reinforcement learning with demonstrations. *arXiv preprint arXiv:1709.10089*, 2017.

A. Y. Ng, D. Harada, and S. Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *International Conference on Machine Learning (ICML)*, volume 99, pp. 278–287, 1999.

I. Osband, C. Blundell, A. Pritzel, and B. V. Roy. Deep exploration via bootstrapped DQN. In *Advances In Neural Information Processing Systems*, pp. 4026–4034, 2016.

R. Parr and S. J. Russell. Reinforcement learning with hierarchies of machines. In *Advances in Neural Information Processing Systems (NIPS)*, pp. 1043–1049, 1998.

C. Perez-D'Arpino and J. A. Shah. C-learn: Learning geometric constraints from demonstrations for multi-step manipulation in shared autonomy. In *International Conference on Robotics and Automation (ICRA)*, pp. 4058–4065, 2017.

M. Phillips, V. Hwang, S. Chitta, and M. Likhachev. Learning to plan for constrained manipulation from demonstrations. *Autonomous Robots*, 40(1):109–124, 2016.

D. A. Pomerleau. Efficient training of artificial neural networks for autonomous navigation. *Neural Computation*, 3(1):88–97, 1991.

M. Roderick, C. Grimm, and S. Tellex. Deep abstract Q-networks. *arXiv preprint arXiv:1710.00459*, 2017.

S. Ross and D. Bagnell. Efficient reductions for imitation learning. In *Artificial Intelligence and Statistics (AISTATS)*, pp. 661–668, 2010.

S. Ross, G. Gordon, and A. Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Artificial Intelligence and Statistics (AISTATS)*, 2011.

T. Shi, A. Karpathy, L. Fan, J. Hernandez, and P. Liang. World of bits: An open-domain platform for web-based agents. In *International Conference on Machine Learning (ICML)*, 2017.

B. C. Stadie, P. Abbeel, and I. Sutskever. Third-person imitation learning. *arXiv preprint arXiv:1703.01703*, 2017.

B. Stone and S. Soper. *Amazon Unveils a Listening, Talking, Music-Playing Speaker for Your Home*. Bloomberg L. P., 2014.

R. S. Sutton and A. G. Barto. *Reinforcement learning: An introduction*, volume 1. MIT Press MIT press Cambridge, 1998.

R. S. Sutton, D. Precup, and S. Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Articial intelligence*, 112:181–211, 1999.

M. Veceriki, T. Hester, J. Scholz, F. Wang, O. Pietquin, B. Piot, N. Heess, T. Rothorl, T. Lampe, and M. Riedmiller. Leveraging demonstrations for deep reinforcement learning on robotics problems with sparse rewards. *arXiv preprint arXiv:1707.08817*, 2017.

T. Weber, S. Racanière, D. P. Reichert, L. Buesing, A. Guez, D. J. Rezende, A. P. Badia, O. Vinyals, N. Heess, Y. Li, et al. Imagination-augmented agents for deep reinforcement learning. *arXiv preprint arXiv:1707.06203*, 2017.

R. J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3):229–256, 1992.

A CONSTRAINT LANGUAGE FOR WORKFLOW STEPS

constraint	::=	`Click(`*elementSet*`)`
		[Any click action on an element in *elementSet*]
	|	`Type(`*elementSet*`,`*string*`)`
		[Any type action that types *string* on an element in *elementSet*]
	|	`Type(`*elementSet*`,Field(*))`
		[Any type action that types a goal field value on an element in *elementSet*]
elementSet	::=	`Tag(`*tag*`)`
		[Any element with HTML tag *tag*]
	|	`Text(`*string*`)`
		[Any element with text *string*]
	|	`Like(`*string*`)`
		[Any element whose text is a substring of *string*]
	|	`Near(`*elementSet*`)`
		[Any element that is within 30px from an element in *elementSet*]
	|	`SameRow(`*elementSet*`)`
		[Any element that aligns horizontally with an element in *elementSet*]
	|	`SameCol(`*elementSet*`)`
		[Any element that aligns vertically with an element in *elementSet*]
	|	`And(`*elementSet*`,Class(`*classes*`))`
		[Any element from *elementSet* matching some class name in *classes*]
tag	::=	a valid HTML tag name
string	::=	a string literal
	|	`Field(`*fieldName*`)`
		[The value from the goal field *fieldName*]
classes	::=	a list of valid HTML class names

To avoid combinatorial explosion of relatively useless constraints, we limit the number of nested *elementSet* applications to 3, where the third application must be the `Class` filter. When we induce workflow steps from a demonstration, the valid literal values for *tag*, *string*, and *classes* are extracted from the demonstration state.

B EXAMPLES OF LEARNED WORKFLOWS

login-user
Enter the username "ashlea" and password "k0UQp" and press login.
{username: ashlea, password: k0UQp}

```
Type(Tag("input_text"),Field("username"))
Type(Tag("input_password"),Field("password"))
              Click(Like("Login"))
```

email-inbox
Find the email by Ilka and forward it to Krista.
{task: forward, name: Ilka, to: Krista}

```
              Click(Near(Field("by")))
             Click(SameCol(Like("Forward")))
Type(And(Near("Subject"),Class("forward-sender")),Field("to"))
                  Click(Tag("span"))
```

search-engine
Enter "Cheree" and press "Search", then find and click the 5th search result.
{target: Cheree, rank: 5}

```
Type(Near(Tag("button")),Field(*))
      Click(Text("Search"))
         Click(Like(">"))
      Click(Text(Field("target")))
```

Alaska
{departure city: Tampa, destination city: Seattle, ticket type: return flight,
departure day: 6, returning Day: 16, passengers: 3, seat type: first }

```
Type(And(Near(Like("From")),Class("text-input-pad")),Field("departure city"))
     Click(And(SameRow(Tag("label")),Class(["input-selection","last"])))
Type(And(Near(Like("To")),Class("text-input-pad")),Field("destination city"))
                Click(Like(Field("destination city")))
       Click(And(SameCol(Tag("a")),Class(["calbg","text-input"])))
               Click(Text(Field("departure day")))
                        Click(Like("Done"))
        Click(Near(Like("Return")),Class(["calbg","text-input"]))
               Click(Text(Field("returning day")))
                        Click(Like("Done"))
                         Click(Like("+"))
                         Click(Like("+"))
                         Click(Tag("h2"))
                       Click(Text("First"))
             Click(And(Near(Tag("body")),Class("button")))
```

C   DETAILS OF THE NEURAL MODEL ARCHITECTURE

Embeddings. From the input state, we first embed the DOM elements e and the goal units u, where u is a key-value pair for structured goals and a token for natural language goals.

The process for computing the embedding v_{DOM}^e of DOM elements is already described in Section 5. For the goal unit embedding v_{goal}^u, we embed each key-value pair as the sum of word embeddings, and embed natural language goals with an LSTM.

Attentions. After obtaining the embedding v_{DOM}^e of each DOM element e and v_{goal}^u of each goal unit u, we apply a series of attentions to relate the DOM elements with the goal:

1. *DOM context*: we applied max-pooling on v_{DOM}^e to get a query vector, and then attend over the DOM embeddings v_{DOM}^e. The DOM context is the weighted average of the attended DOM embeddings.

2. *Goal contexts*: we use the DOM context as the query vector to attend over the goal embeddings v_{goal}^u. We compute two goal contexts from two different attention heads. Each head uses sentinel attention, where part of the attention can be put on a learned NULL vector, which is useful for ignoring the goal when the next action should not depend on the goal.

3. *DOM element selection*: We concatenate the DOM context and goal contexts into a query vector to attend over on the DOM embeddings v_{DOM}^e. We use two attention heads, and combine the attention weights from the two heads based on ratio computed from the goal contexts. The result is a distribution over the target DOM elements e.

4. *Typed string and action selection*: For a given target DOM element e, we combine the goal context and the embedding e^e of e to get a query vector to attend over the goal embeddings v_{goal}^u. For structured queries, we get a distribution over the goal fields, while for natural language queries, we get distributions of the start and end tokens. The same query vector is also used to compute the distribution over the action types (click or type).

Figure 5: The architecture of the neural policy π_n. The inputs from the state are denoted in blue, while the outputs are denoted in red. **Q** = query vector; **M** = memory matrix.