ON CONVERGENCE AND STABILITY OF GANS

ABSTRACT

We propose viewing GAN training dynamics as regret minimization, which is in contrast to the popular view that there is consistent minimization of a divergence between real and generated distributions. We analyze the convergence of GANs from this new point of view to understand why mode collapse happens. We hypothesize the existence of undesirable *local equilibria* in this non-convex game to be responsible for mode collapse. We observe that these local equilibria often exhibit sharp gradients of the discriminator function around some real data points. We demonstrate that these degenerate local equilibria can be avoided with a gradient penalty scheme called DRAGAN. We show that DRAGAN enables faster training, achieves improved stability with fewer mode collapses, and leads to generator networks with better modeling performance across a variety of architectures and objective functions.

1 INTRODUCTION

Generative modeling involves taking a set of samples drawn from an unknown data generating distribution P_{real} and finding an estimate P_{model} that closely resembles it. Generative adversarial networks (GAN) (Goodfellow et al., 2014) are a powerful framework used for fitting *implicit* generative models. The basic setup consists of two networks, the generator and the discriminator, playing against each other in a repeated zero-sum game setting. The goal here is to reach an equilibrium where P_{real}, P_{model} are close, and the alternating gradient update procedure is used to achieve this. However, this process is highly unstable and often results in mode collapse (Goodfellow, 2017). This calls for an deeper investigation into training dynamics of GANs.

In this paper, we propose viewing GAN training as a repeated game in which both the players are using no-regret algorithms (Cesa-Bianchi & Lugosi, 2006) and discuss how the alternating gradient update procedure falls under this paradigm of regret minimization. In contrast, much of the theory (Goodfellow et al., 2014; Arjovsky & Bottou, 2017) and recent developments (Nowozin et al., 2016; Arjovsky et al., 2017; Gulrajani et al., 2017) in this field are based on the idea that the discriminator is playing optimally at each step and that there is consistent minimization of a divergence between real and generated distributions. This corresponds to players using best-response algorithms, and the resulting training dynamics can be completely different in both these cases (Nisan et al., 2007). Thus, there is a clear disconnect between theoretical arguments used as motivation in recent literature and what actually happens in practice.

We would like to point out that the latter view can still be useful for reasoning about the asymptotic equilibrium situation but we argue that regret minimization is the more appropriate way to think about GAN training dynamics. So, we analyze the convergence of GANs from this new point of view to understand why mode collapse happens. We start with the analysis of a simple convex-concave case of the GAN game and use it to introduce some important concepts. This artificial setting has a unique solution and guaranteed convergence (of averaged iterates) using no-regret algorithms, which can be shown using arguments from online learning and game theory. Here, we make an important connection between the alternating gradient update procedure used for GAN training and regret minimization. This is previously not widely known in the GAN literature.

However, these convergence results do not hold when the game objective function is non-convex, which is the more realistic case when deep neural networks are used. In non-convex games, (global) regret minimization is hard in general and alternating gradient updates can end up cycling (Mertikopoulos et al., 2017) or converging to a potentially bad local equilibrium (Hazan et al., 2017).

We hypothesize these to be the reasons for cycling and mode collapse observed in GAN training, respectively. In this work, we do not explore the cycling issue but focus our attention on the mode collapse problem. The natural question is how can we avoid such undesirable equilibria?

We discuss a simple observation that in the GAN game, mode collapse situations are often accompanied by sharp gradients of the discriminator function around some real data points. So, one strategy would be to regularize the discriminator so as to constrain its gradients in the domain space. We demonstrate that this indeed improves the stability using a toy experiment with one hidden layer neural networks in section 2.4. This gives rise to a new explanation for why gradient penalties might improve the stability of GAN training – they are mitigating the mode collapse problem during GAN training by keeping the gradients of the discriminator function small in domain space. From this motivation, we propose a novel gradient penalty scheme which enables faster training, achieves improved stability and performance (over WGAN-GP (Gulrajani et al., 2017) which is the state-of-the-art stable training procedure) across a variety of architectures and objective functions.

Below, we provide a short literature review. Several recent works focus on stabilizing the training of GANs. While some solutions (Radford et al., 2015; Salimans et al., 2016) require the usage of specific architectures/modeling objectives, some (Che et al., 2016; Zhao et al., 2016) significantly deviate from the original GAN framework. Other promising works in this direction (Metz et al., 2016; Arjovsky et al., 2017; Qi, 2017; Gulrajani et al., 2017) impose a significant computational overhead. Thus, a fast and versatile method for consistent stable training of GANs is still missing in the literature. Our work is aimed at addressing this.

To summarize, our contributions are as follows:

- We discuss convergence guarantees in the artificial convex-concave case of the GAN game and make an important (previously not widely known) connection between GAN training process and regret minimization.

- We discuss the non-convex setting in which alternating gradient updates can cycle or converge to a potentially bad local equilibrium. We hypothesize the latter to be responsible for mode collapse during GAN training.

- We discuss a simple observation that mode collapse situations can often be characterized by sharp gradients of the discriminator function around some real data points.

- A novel gradient penalty scheme is introduced based on this observation and it enables faster training, improved stability, and better performance compared to WGAN-GP.

2 THEORETICAL ANALYSIS OF GAN DYNAMICS

In this section, we start with a brief description of the GAN framework (subsection 2.1). We discuss guaranteed convergence in the artificial convex-concave case, introduce necessary concepts along the way and finally, we make an important connection between GAN training process and regret minimization (subsection 2.2). Then, we consider the more realistic non-convex case and discuss how the alternating gradient update procedure can converge to a potentially bad local equilibrium here (subsection 2.3). A simple observation is discussed about how mode collapse situations often exhibit sharp gradients of the discriminator function around some real data points. This naturally leads to the introduction of our novel gradient penalty scheme (subsection 2.4). We end this section with a discussion and comparison with other gradient penalties in the literature (subsection 2.5).

2.1 BACKGROUND

The GAN framework can be viewed as a repeated zero-sum game, consisting of two players - the *generator*, which produces synthetic data given some noise source and the *discriminator*, which is trained to distinguish generator's samples from the real data. The generator model G is parameterized by ϕ, takes a noise vector $\mathbf{z}$ as input, and produces a synthetic sample $G_\phi(\mathbf{z})$. The discriminator model D is parameterized by θ, takes a sample $\mathbf{x}$ as input and computes $D_\theta(\mathbf{x})$, which can be interpreted as the probability that $\mathbf{x}$ is real.

The models G, D can be selected from any arbitrary class of functions – in practice, GANs typical rely on deep networks for both. Their cost functions are defined as

$$J^{(D)}(\phi, \theta) := -\mathbb{E}_{x \sim p_{real}} \log D_\theta(x) - \mathbb{E}_{\mathbf{z}} \log(1 - D_\theta(G_\phi(z))), \text{ and}$$

$$J^{(G)}(\phi, \theta) := -J^{(D)}(\phi, \theta)$$

And the complete game can be specified as -

$$\min_\phi \max_\theta \left\{ J(\phi, \theta) = \mathbb{E}_{x \sim p_{real}} \log D_\theta(x) + \mathbb{E}_{\mathbf{z}} \log(1 - D_\theta(G_\phi(z))) \right\}$$

The generator distribution P_{model} asymptotically converges to the real distribution P_{real} if updates are made in the function space (Goodfellow et al., 2014).

2.2 CONVEX-CONCAVE CASE AND NO-REGRET ALGORITHMS

According to Sion's theorem (Sion, 1958), if $\Phi \subset \mathbb{R}^m$, $\Theta \subset \mathbb{R}^n$ such that they are compact and convex sets and the function $J : \Phi \times \Theta \to \mathbb{R}$ is convex in its first argument and concave in its second, then we have -

$$\min_{\phi \in \Phi} \max_{\theta \in \Theta} J(\phi, \theta) = \max_{\theta \in \Theta} \min_{\phi \in \Phi} J(\phi, \theta)$$

That is, an equilibrium is guaranteed to exist in this setting where players' payoffs correspond to the unique value of the game (Neumann, 1928).

A natural question then is how we can find such an equilibrium. A simple procedure that players can use is best-response algorithms (BRD). In each round, best-responding players play their optimal strategy given their opponent's current strategy. Despite its simplicity, BRD are often computationally intractable and they don't lead to convergence even in simple games. In contrast, a technique that is both efficient and provably works is regret minimization. If both players update their parameters using no-regret algorithms, then it is easy to show that their averaged iterates will converge to an equilibrium pair (Nisan et al., 2007). Let us first define no-regret algorithms.

Definition 2.1 (**No-regret algorithm**). Given a sequence of convex loss functions $L_1, L_2, \ldots :$ $K \to \mathbb{R}$, an algorithm that selects a sequence of k_t's, each of which may only depend on previously observed $L_1, \ldots, L_{t-1}$, is said to have *no regret* if $\frac{R(T)}{T} = o(1)$, where we define

$$R(T) := \sum_{t=1}^T L_t(k_t) - \min_{k \in K} \sum_{t=1}^T L_t(k)$$

We can apply no-regret learning to our problem of equilibrium finding in the GAN game $J(\cdot, \cdot)$ as follows. The generator imagines the function $J(\cdot, \theta_t)$ as its loss function on round t, and similarly the discriminator imagines $-J(\phi_t, \cdot)$ as its loss function at t. After T rounds of play, each player computes the average iterates $\bar{\phi}_T := \frac{1}{T} \sum_{t=1}^T \phi_t$ and $\bar{\theta}_T := \frac{1}{T} \sum_{t=1}^T \theta_t$. If V^* is the equilibrium value of the game, and the players suffer regret $R_1(T)$ and $R_2(T)$ respectively, then one can show using standard arguments (Freund & Schapire, 1999) that -

$$V^* - \frac{R_2(T)}{T} \leq \max_{\theta \in \Theta} J(\bar{\phi}_T, \theta) - \frac{R_2(T)}{T} \leq \min_{\phi \in \Phi} J(\phi, \bar{\theta}_T) + \frac{R_1(T)}{T} \leq V^* + \frac{R_1(T)}{T}.$$

In other words, $\bar{\theta}_T$ and $\bar{\phi}_T$ are "almost optimal" solutions to the game, where the "almost" approximation factor is given by the average regret terms $\frac{R_1(T) + R_2(T)}{T}$. Under the no-regret condition, the former will vanish, and hence we can guarantee convergence in the limit. Next, we define a popular family of no-regret algorithms.

Definition 2.2 (**Follow The Regularized Leader**). FTRL (Hazan et al., 2016) selects k_t on round t by solving for $\arg \min_{k \in K} \{ \sum_{s=1}^{t-1} L_s(k) + \frac{1}{\eta} \Omega(k) \}$, where $\Omega(\cdot)$ is some convex regularization function and η is a learning rate.

Remark: Roughly speaking, if you select the regularization as $\Omega(\cdot) = \frac{1}{2} \| \cdot \|^2$, then FTRL becomes the well-known online gradient descent (OGD (Zinkevich, 2003). Ignoring the case of constraint violations, OGD can be written in a simple iterative form: $k_t = k_{t-1} - \eta \nabla L_{t-1}(k_{t-1})$.

The typical GAN training procedure using alternating gradient updates is exactly this - both the players applying online gradient descent. Notice that the min/max objective function in GANs involves a stochastic component, with two randomized inputs given on each round, x and z which are sampled from the data distribution and a standard multivariate normal, respectively. But the above online learning procedure is still valid with stochastic inputs. That is, the equilibrium computation would proceed similarly, where on each round we sample x_t and z_t, and follow the updates

$$\phi_{t+1} \leftarrow \phi_t - \eta \nabla_\phi J_{x_t, z_t}(\phi_t, \theta_t). \quad \text{and} \quad \theta_{t+1} \leftarrow \theta_t + \eta' \nabla_\theta J_{x_t, z_t}(\phi_t, \theta_t)$$

To summarize, we discussed in this subsection about how the artificial convex-concave case is easy to solve through regret minimization, and we introduced definitions and concepts that we will be using in the sections below. While these are standard results in game theory and online learning literature, they are not widely known in GAN literature. For instance, Salimans et al. (2016) and Goodfellow (2017) discuss a toy game which is convex-concave and claim convergence is not possible using gradient-based methods. The simple solution in that case is to average the iterates. Beyond such toy examples though, it is hard to construct convex-concave cases of, say the GAN game.

Further, we made an important connection between no-regret algorithms and alternating gradient updates procedure which gives a novel way to reason about GAN training dynamics. This might seem straightforward but it is previously not known in GAN literature. In contrast, the popular view of GAN training dynamics as consistently minimizing a divergence arises if we use BRD and thus, it has little to do with the actual training process of GANs. As a result, this calls into question the motivation behind many recent developments like gradient penalties among others which improve the training stability of GANs. In the next subsection, we discuss the practical non-convex case and why training instability arises. This provides the necessary ideas to investigate gradient penalties from our new perspective.

2.3 Non-convex case and Local equilibria

In practice, we choose G, D to be deep neural networks and the function $J(\phi, \theta)$ need not be convex-concave anymore. The nice properties we had in the convex-concave case like the existence of a unique solution and guaranteed convergence through regret minimization no longer hold. In fact, regret minimization and equilibrium computation are computationally hard in general non-convex settings. However, analogous to the case of non-convex optimization (also intractable) where we focus on finding local minima, we can look for tractable solution concepts in non-convex games.

Recent work by Hazan et al. (2017) introduces the notion of *local regret* and shows that if both the players use a *smoothed* variant of OGD to minimize this quantity, then the non-convex game converges to some form of local equilibrium under mild assumptions. The usual training procedure of GANs corresponds to using a window size of 1 in their formulation. Thus, GAN training will eventually converge (approximately) to a local equilibrium which is described below or the updates will cycle. We leave it to future works to explore the equally important cycling issue and focus here on the former case.

Definition 2.3 (**Local Equilibrium**). A pair (ϕ^*, θ^*) is called an ϵ-approximate local equilibrium if it holds that

$$\forall \phi', \|\phi' - \phi^*\| \leq \eta : J(\phi^*, \theta^*) \leq J(\phi', \theta^*) + \epsilon$$
$$\forall \theta', \|\theta' - \theta^*\| \leq \eta : J(\phi^*, \theta^*) \geq J(\phi^*, \theta') - \epsilon$$

That is, in a local equilibrium, both the players do not have much of an incentive to switch to any other strategy within a small neighborhood of their current strategies. Now, we turn our attention to the mode collapse issue which poses a significant challenge to the GAN training process. The training is said to have resulted in mode collapse if the generator ends up mapping multiple $\mathbf{z}$ vectors to the same output $\mathbf{x}$, which is assigned a high probability of being real by the discriminator (Goodfellow, 2017). We hypothesize this to be the result of the game converging to bad local equilibria.

The prevalent view of mode collapse and instability in GAN training (Arjovsky & Bottou, 2017; Roth et al., 2017) is that it is caused due to the supports of real and model distributions being disjoint or lying in low-dimensional manifolds. This would result in strong distance measures like KL-divergence or JS-divergence getting maxed out, and the generator cannot get useful gradients to

learn. In fact, this is the motivation for the introduction of Wasserstein GAN (Arjovsky et al., 2017). But, we argue that GAN training does not consistently minimize a divergence as that would require using intractable best-response algorithms. To demonstrate this, see Figure 4 (top row) where the vanilla GAN algorithm is successful at capturing the swissroll distribution. This is the case even if we test it on multiple runs. Notice that by divergence minimization hypothesis, $JS(P_{real}||P_{model})$ should not provide useful gradients to the generator in this case as the supports are clearly disjoint initially but progress takes place anyways.

To summarize, the consistent divergence minimization hypothesis is based on unrealistic assumptions, and cannot explain why GANs succeed in cases where they clearly should not. Hence, such a theory is not suitable to discuss convergence or to address instability of the GAN training. Our new view of GAN training process as regret minimization is closer to what is used in practice and provides an alternate explanation for mode collapse - the existence of bad local equilibria. The natural question now is how we can avoid them?

2.4   Mode collapse and Gradient Penalties

The problem of dealing with multiple equilibria in games and how to avoid undesirable ones is an important question in algorithmic game theory (Nisan et al., 2007). In this work, we constrain ourselves to the GAN game and aim to characterize the undesirable local equilibria (mode collapse) in an effort to avoid them. In this direction, after empirically studying multiple mode collapse cases, we found that it is often accompanied by the discriminator function having sharp gradients around some real data points (See Figure 1). This intuitively makes sense from the definition of mode collapse discussed earlier. Such sharp gradients encourage the generator to map multiple z vectors to a single output x and lead the game to a degenerate equilibrium. Now, a simple strategy to mitigate this failure case would be to regularize the discriminator using the following penalty -

$$\lambda \cdot \mathbb{E}_{x \sim P_{real}, \delta \sim N_d(0,cI)} \left[\|\nabla_{\mathbf{x}} D_\theta(x + \delta)\|^2 \right]$$

This strategy indeed improves the stability of GAN training. We show the results of a toy experiment with one hidden layer neural networks in Figure 2 and Figure 3 to demonstrate this. This explains the success of gradient penalties in the recent literature (Gulrajani et al., 2017; Qi, 2017) and why they improve the training stability of GANs despite being motivated by reasoning based on unrealistic assumptions. However, we noticed that this scheme can be brittle w.r.t hyperparameters and if over-penalized, the discriminator can end up assigning both a real point x and noise $x + \delta$, the same probability of being real. Thus, a better choice of penalty is -

$$\lambda \cdot \mathbb{E}_{x \sim P_{real}, \delta \sim N_d(0,cI)} \left[\max \left(0, \|\nabla_{\mathbf{x}} D_\theta(x + \delta)\|^2 - k \right) \right]$$

Finally, due to practical optimization considerations, we instead use the penalty shown below in all our experiments.

$$\lambda \cdot \mathbb{E}_{x \sim P_{real}, \delta \sim N_d(0,cI)} \left[\|\nabla_{\mathbf{x}} D_\theta(x + \delta)\| - k \right]^2 \tag{1}$$

This works as long as small perturbations of real data, $x + \delta$ are likely to lie off the data manifold which is true in the case of image domain and some other settings. Because, in these cases, we do want our discriminator to assign different probabilities of being real to training data and noise. We caution the practitioners to keep this important point in mind while making their choice of penalty. All of the above schemes have the same effect of constraining the norm of discriminator's gradients around real points to be small and can therefore, mitigate the mode collapse situation. We refer to GAN training using these penalty schemes or heuristics as DRAGAN algorithm (Deep Regret Analytic GAN).

Additional details:

- We use the vanilla GAN objective in our experiments, but our penalty improves stability using other objective functions as well. This is demonstrated in section 3.3.

- The penalty scheme used in our experiments is the one shown in equation 1.

- We use small pixel-level noise but it is possible to find better ways of imposing this penalty. However, this exploration is beyond the scope of our paper.

- The optimal configuration of the hyperparameters for DRAGAN depends on the architecture, dataset and data domain. We set them to be $\lambda \sim 10$, $k = 1$ and $c \sim 10$ in all our experiments.

Figure 1: One hidden layer networks as G and D (MNIST). On the left we plot inception score against time and on the right, we plot the squared norm of discriminator's gradients around real data points in the same experiment. Notice how this quantity changes before, during and after mode collapse events.

Figure 2: One hidden layer networks as G and D (MNIST). On the left, losses for both the players are shown for vanilla GAN and on the right, we added a regularization term to penalize the gradients of $D(x)$ around real data points. Notice the improved stability.

2.5 COUPLED VS LOCAL SMOOTHING

Several recent works have also proposed regularization schemes which constrain discriminator's gradients in the domain space to improve the stability of GAN training. Despite being from different motivations, WGAN-GP and LS-GAN are closely related approaches to ours.

First, we show that these two approaches are very similar, which is not widely known in the literature. Qi (2017) introduced LS-GAN with the idea of maintaining a margin between losses assigned to real and fake samples. Further, they also impose Lipschitz constraint on D and the two constraints together result in a situation where the following holds for any real and fake sample pair (roughly) -

$$D_\theta(x) - D_\theta(G_\phi(z)) \approx ||x, G_\phi(z)|| \qquad (2)$$

The authors argue that the resulting function would have non-vanishing gradients almost everywhere between real and fake samples (Section 6 of Qi (2017)). Gulrajani et al. (2017) proposed an extension to address various shortcomings of the original WGAN and they impose the following condition on D -

$$||\nabla_x D_\theta(\hat{x})|| \approx 1 \qquad (3)$$

where $\hat{x} = (\epsilon)x + (1 - \epsilon)G_\phi(z)$ is some point on the line between a real and a fake sample, both chosen independently at random. This leads to D having norm-1 gradients almost everywhere between real and fake samples. Notice that this behavior is very similar to that of LS-GAN's discriminator function. Thus, WGAN-GP is a slight variation of the original LS-GAN algorithm and we refer to these methods as "coupled smoothing". On a side note, we also want to point out that WGAN-GP's penalty doesn't actually follow from KR-duality as claimed in their paper and this adds more credence to our theory about why gradient penalties mitigate mode collapse. By Lemma 1 of Gulrajani et al. (2017), the optimal discriminator D^* will have norm-1 gradients (almost everywhere) only between those x and $G_\phi(z)$ pairs which are sampled from the optimal coupling

Figure 3: One hidden layer networks as G and D (MNIST). On the left, inception score is shown for vanilla GAN and on the right, we added a regularization term to penalize the gradients of $D(x)$ around real data points. Notice how mode collapse is mitigated.

or joint distribution π^*. Therefore, there is no basis for WGAN-GP's penalty (equation 3) where arbitrary pairs of real and fake samples are used.

The most important distinction between coupled smoothing methods and ours is that we only impose gradient constraints in local regions around real samples. We refer to such penalty schemes as "local smoothing". Coupled smoothing involves imposing gradient constraints between real and generated samples. The resulting class of functions when coupled smoothing is used will be highly restricted compared to our method and this affects modeling performance. We refer the reader to Figure 4 and supplementary section 5.2.3 to see this effect. Our algorithm works with alternating gradient updates, while WGAN-GP needs multiple inner iterations to optimize D. This is because generated samples can be anywhere in the domain space and they change from one iteration to the next. In contrast, we consistently regularize $D_\theta(x)$ only along the real-data manifold. To conclude, appropriate constraining of the discriminator's gradients can mitigate mode collapse but we should be careful so that it doesn't have any negative effects. We refer the reader to section 3 for further experimental results.

Figure 4: Swissroll experiment (different phases of training) - Vanilla GAN (top), WGAN-GP (middle), and DRAGAN (bottom). Real samples are marked orange and generated samples are green. Level sets of $D_\theta(x)$ are shown in the background where yellow is high and purple is low.

3 EXPERIMENTAL RESULTS

In section 3.1, we compare the modeling performance of our algorithm against vanilla GAN and WGANs in the standard DCGAN/CIFAR-10 setup. Section 3.2 demonstrates DRAGAN's superior stability properties across a variety of architectures. In section 3.3, we show that our method also works with other objective functions. Appendix contains samples for inspection, some of the plots

and some additional results. Throughout, we use inception score (well-studied, reliable metric in the literature) and sample quality to measure the performance.

3.1 Inception Scores on CIFAR-10 using DCGAN architecture

DCGAN is a family of architectures designed to perform well with the vanilla training procedure. They are ubiquitous in the GAN literature owing to the instability of vanilla GAN in general settings. We use this architecture to model CIFAR-10 and compare against vanilla GAN, WGAN and WGAN-GP. As WGANs need 5 discriminator iterations for every generator iteration, comparing the modeling performance can be tricky. To address this, we report two scores for vanilla GAN and DRAGAN - one using the same number of generator iterations as WGANs and one using the same number of discriminator iterations. The results are shown in Figure 5 and samples are included in the appendix (Figure 8). Notice that DRAGAN beats WGANs in both the configurations, while vanilla GAN performs the best. A key point to note here is that our algorithm is fast compared to WGANs, so in practice, the performance will be closer to the $DRAGAN^d$ case.

(a) Inception score plot

Algorithm	Score
WGAN	3.25
WGAN-GP	5.99
$DRAGAN^g$	6.11
$DRAGAN^d$	6.90
Vanilla GAN^g	6.3
Vanilla GAN^d	6.99

(b) Inception scores

Figure 5: Comparison of modeling performance on CIFAR10

3.2 BogoNet score to measure stability across architectures

One of the key advantages of our algorithm is that it improves stability in a wider range of architectures (other than DCGANs). Similar to Arjovsky et al. (2017) and Gulrajani et al. (2017), we removed stabilizing components of DCGAN and demonstrated improved stability compared to the vanilla GAN (see section 5.2.4 in appendix). However, this is a small set of architectures and it is not clear if stability is improved in general.

To address this, we introduce a metric termed the *BogoNet* score to compare stability of different training procedures in the GAN setting. The basic idea is to choose random architectures for players G and D independently and evaluate the performance of different algorithms in the resulting games. A good algorithm should achieve stable performance without failing to learn or resulting in mode collapse despite the potentially imbalanced architectures. In our experiment, each player is assigned a network from a diverse pool of architectures belonging to three families (MLP, ResNet, DCGAN).

To demonstrate that our algorithm is more stable compared to vanilla GAN and WGAN-GP, we created 100 such instances of hard games. Each instance is trained using these algorithms on CIFAR-10 and we plot how inception score changes over time. For each algorithm, we calculated the average of final inception scores and area under the curve (AUC) over all 100 instances. The results are shown in Table 1. Notice that we beat the other algorithms in both metrics, which indicates some improvement in stability.

Further, we perform some qualitative analysis to verify that BogoNet score indeed captures the improvements in stability. We create another set of 50 hard architectures and compare DRAGAN against vanilla GAN. Each instance is worth 5 points and we split this bounty between the two algorithms depending on their performance. If both perform well or perform poorly, they get 2.5 points each. This is to nullify the effect of architectures where both the algorithms perform well or fail. However, if one algorithm achieves stable performance compared to the other (in terms of failure

Table 1: Summary of inception score statistics across 100 architectures

Algorithm	Final score		Area under curve		Qual. score
	Mean	Std	Mean	Std	Total
Vanilla GAN	2.91	1.44	277.72	126.09	92.5
DRAGAN	**3.70**	1.71	**312.15**	135.35	**157.5**
WGAN-GP	3.49	1.30	300.09	100.96	-

to learn or mode collapses), we assign it higher portions of the bounty. Results were judged by two of the authors in a blind manner: The curves were shown side-by-side with the choice of algorithm for each side being randomized and unlabeled. The vanilla GAN received an average score of 92.5 while our algorithm achieved an average score of 157.5 and this correlates with BogoNet score from earlier. See section 5.3 in appendix for some additional details regarding this experiment.

3.3 STABILITY USING DIFFERENT OBJECTIVE FUNCTIONS

Our algorithm can be used with a variety of objective functions and we demonstrate this using the following experiment. Nowozin et al. (2016) show that we can interpret GAN training as minimizing various f-divergences when an appropriate game objective function is used. We show experiments using the objective functions developed for Forward KL, Reverse KL, Pearson χ^2, Squared Hellinger, and Total Variation divergence minimization. We use a hard architecture from the previous subsection to demonstrate the improvements in stability. Our algorithm is stable in all cases except for Total Variation while the vanilla algorithm failed in all cases (see Figure 6 for two examples and Figure 15 in appendix for all five). Thus, practitioners can now choose their game objective from a larger set of functions and use DRAGAN (unlike WGANs which requires a specific objective function).

(a) Reverse KL   (b) Pearson χ^2

Figure 6: Inception score plots for two divergence measures, demonstrating superior stability for our algorithm.

4 CONCLUSIONS

In this paper, we propose to view GAN training process as regret minimization, which is in contrast to the popular view that there is consistent minimization of a divergence between real and generated distribution. We analyze convergence from this view and hypothesize that mode collapse occurs due to the existence of undesirable local equilibria in the GAN game. A simple observation is discussed about how mode collapse situation is often accompanied by sharp gradients of the discriminator function around real data points. This idea explains the workings of previously proposed gradient penalties and motivates our DRAGAN penalty scheme. We show evidence of improved stability and the resulting improvements in modeling performance in a variety of settings. We leave it to future works to explore our idea further and come up with improved training algorithms.

REFERENCES

Martin Arjovsky and Léon Bottou. Towards principled methods for training generative adversarial networks. *arXiv preprint arXiv:1701.04862*, 2017.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan. *arXiv preprint arXiv:1701.07875*, 2017.

Nicolo Cesa-Bianchi and Gábor Lugosi. *Prediction, learning, and games*. Cambridge university press, 2006.

Tong Che, Yanran Li, Athul Paul Jacob, Yoshua Bengio, and Wenjie Li. Mode regularized generative adversarial networks. *arXiv preprint arXiv:1612.02136*, 2016.

Yoav Freund and Robert E Schapire. Adaptive game playing using multiplicative weights. *Games and Economic Behavior*, 29(1-2):79–103, 1999.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 27*, pp. 2672–2680. Curran Associates, Inc., 2014. URL http://papers.nips.cc/paper/5423-generative-adversarial-nets.pdf.

Ian J. Goodfellow. NIPS 2016 tutorial: Generative adversarial networks. *CoRR*, abs/1701.00160, 2017. URL http://arxiv.org/abs/1701.00160.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron Courville. Improved training of wasserstein gans. *arXiv preprint arXiv:1704.00028*, 2017.

Elad Hazan, Karan Singh, and Cyril Zhang. Efficient regret minimization in non-convex games. *arXiv preprint arXiv:1708.00075*, 2017.

Elad Hazan et al. Introduction to online convex optimization. *Foundations and Trends® in Optimization*, 2(3-4):157–325, 2016.

Panayotis Mertikopoulos, Christos Papadimitriou, and Georgios Piliouras. Cycles in adversarial regularized learning. *arXiv preprint arXiv:1709.02738*, 2017.

Luke Metz, Ben Poole, David Pfau, and Jascha Sohl-Dickstein. Unrolled generative adversarial networks. *CoRR*, abs/1611.02163, 2016. URL http://arxiv.org/abs/1611.02163.

J. von Neumann. Zur theorie der gesellschaftsspiele. *Mathematische Annalen*, 100:295–320, 1928. URL http://eudml.org/doc/159291.

Noam Nisan, Tim Roughgarden, Eva Tardos, and Vijay V Vazirani. *Algorithmic game theory*, volume 1. Cambridge University Press Cambridge, 2007.

Sebastian Nowozin, Botond Cseke, and Ryota Tomioka. f-gan: Training generative neural samplers using variational divergence minimization. In *Advances in Neural Information Processing Systems*, pp. 271–279, 2016.

Guo-Jun Qi. Loss-sensitive generative adversarial networks on lipschitz densities. *CoRR*, abs/1701.06264, 2017. URL http://arxiv.org/abs/1701.06264.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised Representation Learning with Deep Convolutional Generative Adversarial Networks. *arXiv:1511.06434 [cs]*, November 2015. URL http://arxiv.org/abs/1511.06434. arXiv: 1511.06434.

Kevin Roth, Aurelien Lucchi, Sebastian Nowozin, and Thomas Hofmann. Stabilizing training of generative adversarial networks through regularization. *arXiv preprint arXiv:1705.09367*, 2017.

Tim Salimans, Ian J. Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *CoRR*, abs/1606.03498, 2016. URL http://arxiv.org/abs/1606.03498.

Maurice Sion. On general minimax theorems. *Pacific J. Math*, 8(1):171–176, 1958.

Junbo Zhao, Michael Mathieu, and Yann LeCun. Energy-based generative adversarial network. *arXiv preprint arXiv:1609.03126*, 2016.

Martin Zinkevich. Online convex programming and generalized infinitesimal gradient ascent. In *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, pp. 928–936, 2003.

5   APPENDIX

5.1   SAMPLES AND LATENT SPACE WALKS

In this section, we provide samples (Figure 7) from additional experiments run on CelebA dataset. The samples from the experiment in section 3.1 are shown in Figure 8.

Further, Radford et al. (2015) suggest that walking on the manifold learned by the generator can expose signs of memorization. We use DCGAN to model MNIST and CelebA using DRAGAN, and latent space walks of the learned models are shown in Figures (6,7). They demonstrate that our generator learns smooth transitions between different images.

Figure 7: Modeling CelebA with DRAGAN using DCGAN architecture.

(a) Vanilla GAN

(b) DRAGAN

(c) WGAN

(d) WGAN-GP

Figure 8: Modeling CIFAR-10 with DRAGAN using DCGAN architecture.

Figure 9: Latent space walk of the model learned on MNIST using DRAGAN

Figure 10: Latent space walk of the model learned on CelebA using DRAGAN

5.2 ADDITIONAL EXPERIMENTS

5.2.1 ONE LAYER NETWORK TO MODEL MNIST

We design a simple experiment where G and D are both fully connected networks with just one hidden layer. Vanilla GAN performs poorly even in this simple setting and we observe severe mode collapses. In contrast, our algorithm is stable throughout and obtains decent quality samples despite the constrained setup.

(a) Vanilla GAN
(b) DRAGAN

Figure 11: One layer network to model MNIST - Inception score[†] plots

(a) Vanilla GAN
(b) DRAGAN

Figure 12: One layer network to model MNIST - Samples

5.2.2 8-GAUSSIANS EXPERIMENT

We analyze the performance of WGAN-GP and DRAGAN on the 8-Gaussians dataset over time. As it can be seen in Figure 13, both of them approximately converge to the real distribution but notice that in the case of WGAN-GP, $D_\theta(x)$ seems overly constrained in the domain space. In contrast, DRAGAN's discriminator is more flexible in the domain space.

Improved WGAN

DRAGAN

Figure 13: Comparing the performance of WGAN-GP and DRAGAN on the 8-Gaussians dataset. Orange is real samples, green is generated samples. The level sets of $D_\theta(x)$ are shown in the background, with yellow as high and purple as low.

5.2.3 STABILITY ACROSS DCGAN ARCHITECTURE VARIATIONS

DCGANs have been designed following specific guidelines to make them stable (Radford et al., 2015). We restate the suggested rules here.

1. Use all-convolutional networks which learn their own spatial downsampling (discriminator) or upsampling (generator)

2. Remove fully connected hidden layers for deeper architectures

3. Use batch normalization in both the generator and the discriminator

4. Use ReLU activation in the generator for all layers except the output layer, which uses $tanh$

5. Use LeakyReLU activation in the discriminator for all layers

We show that such constraints can be relaxed for our algorithm and hence, practitioners are free to choose from a more diverse set of architectures. Below, we present a series of experiments in which we remove different stabilizing components from DCGAN architecture and analyze the performance of our algorithm. Specifically, We choose the following four architectures which are difficult to train (in each case, we start with base DCGAN architecture and apply the changes) -

- No BN and a constant number of filters in the generator

- 4-layer 512-dim ReLU MLP generator

- $tanh$ nonlinearities everywhere

- $tanh$ nonlinearity in the generator and 4-layer 512-dim LeakyReLU MLP discriminator

Notice that, in each case, our algorithm is stable while the vanilla GAN fails. A similar approach is used to demonstrate the stability of training procedures in Arjovsky et al. (2017) and Gulrajani et al. (2017).

(a) tanh activation

(b) FC generator

(c) Constant filter   (d) FC discriminator

Figure 14: Comparing performance of DRAGAN and Vanilla GAN in hard variations of DCGAN architecture.

5.2.4 STABILITY ACROSS OBJECTIVE FUNCTIONS

Due to space limitations, we only showed plots for two divergence measures in section 3.3. Below we show results for all five measures.

(a) Reverse KL   (b) Pearson χ^2

(c) Forward KL   (d) Total Variation

(e) Squared Hellinger

Figure 15: Comparing performance of DRAGAN and Vanilla GAN (training) using different objective functions.

5.3 BOGONET DETAILS

We used three families of architectures with probabilities - DCGAN (0.6), ResNet (0.2), MLP (0.2). Next, we further parameterized each family to create additional variation. For instance, the DCGAN family can result in networks with or without batch normalization, have LeakyReLU or Tanh non-linearities. The number and width of filters, latent space dimensionality are some other possible variations. Similarly, the number of layers and hidden units in each layer for MLP are chosen randomly. For ResNets, we chose their depth randomly. This creates a set of hard games which test the stability of a given training algorithm.

We did qualitative analysis of the inception score plots in section 3.2 to verify that BogoNet score indeed captures improvements in stability. Below, we show examples of how the bounty splits were done. The plots in Figure 14 were scored as:

A - (5, 0), B - (3.5, 1.5), C – (2.25, 2.75), D – (2, 3)

in (DRAGAN,Vanilla) order.