Semi-supervised Ensemble Learning with Weak Supervision for Biomedical Relationship Extraction

Abstract

Natural language understanding research has recently shifted towards complex Machine Learning and Deep Learning algorithms. Such models often outperform significantly their simpler counterparts. However, their performance relies on the availability of large amounts of labeled data, which are rarely available. To tackle this problem, we propose a methodology for extending training datasets to arbitrarily big sizes and training complex, data-hungry models using weak supervision. We apply this methodology on biomedical relationship extraction, a task where training datasets are excessively time-consuming and expensive to create, yet has a major impact on downstream applications such as drug discovery. We demonstrate in a small-scale controlled experiment that our method consistently enhances the performance of an LSTM network, with performance improvements comparable to hand-labeled training data. Finally, we discuss the optimal setting for applying weak supervision using this methodology.

1. Introduction

The amount of scientific papers in the biomedical field is ever increasing. Published papers contain important information, however, encoded in unstructured text, making it difficult for researchers to locate it. Extracting this information in a structured format and storing it within a knowledge base can have a remarkable impact on a variety of important tasks, ranging from drug design to detecting adverse drug effects. During the past decade, there have been efforts towards automation of Information Extraction [Wei et al., 2016, Krallinger et al., 2017a, Wei et al., 2015b], due to the fact that manual annotation of documents from domain experts is labor-intensive and impossible to perform on a large scale [Krallinger et al., 2017b].

The broader focus of this work is the extraction of semantic triples of regulations between chemicals and proteins (or genes) from biomedical abstracts. A chemical regulates a protein when increases (up-regulates) or decreases (down-regulates) the production of the specific protein. This specific relation is particularly important in drug discovery and design, as it will enable researchers to filter out or select chemical substances with specific properties,

much faster. [Krallinger et al., 2017b] Extracting semantic triples of regulations is a structured Information Extraction problem (subject: CHEMICAL, predicate: REGULATES, object: PROTEIN/GENE). First, one needs to identify the entities of interest (subjects & objects) in the unstructured text (Named Entity Recognition), optionally distinguishing them with a unique identifier (Entity Resolution & Linking), and then build a classifier to recognize whether the text describes the target relationship (Relationship Extraction).

Our main focus lies on the last subtask, that of the Relationship Extraction. As this is a complex and challenging task, increasing the capacity of the learning algorithm is justified, but should coincide with an appropriate increase in the training dataset size [Goodfellow et al., 2016]. However, annotating training datasets for this task is an excessively labor- and cost-intensive process. To tackle this problem, we propose a new methodology based on weak supervision, which combines and incorporates ideas from semi-supervised and ensemble learning. The outline of this methodology is the following: (a) We train multiple base learners on a small labeled dataset and use them to predict the labels of a bigger unlabeled dataset; (b) we then use a denoiser to derive weak labels for the unlabeled set using the predictions of the base learners; and (c) we finally train a strong meta-learner using weak supervision on the (previously) unlabeled set.

Our main contributions include: (a) proposing a detailed methodology specific to relationship extraction, which can be adapted and generalized to most supervised learning tasks; (b) demonstrating the effectiveness and usability of this methodology in a small-scale controlled experiment; (c) investigating the effect of various denoising methods in the overall system behavior and performance.

2. Related work

In Subsection 2.1 we discuss literature related to Information Extraction, whereas in Subsection 2.2 we specifically focus on Relationship Extraction from biomedical text. We conclude with Subsection 2.3, describing methods that jointly use semi-supervised and ensemble learning.

2.1 Information extraction

Information extraction is typically modeled as a fully-, semi- or un-supervised learning problem. Unsupervised methods, such as Open Information Extraction [Banko et al., 2007], do not make use of any training data, but they can only be used for unstructured Information Extraction. On the contrary, fully-supervised methods rely rely on labeled examples, which have to be manually annotated. Semi-supervised or bootstrapping methods are more similar to our approach, as they try to leverage both labeled and unlabeled data. One of the first bootstrapping algorithms was DIRPE [Brin, 1998], which starts from some seed (positive) examples, extracts patterns from them and use them for finding new positive examples. Other semi-supervised algorithms include Snowball [Agichtein and Gravano, 2000], Know-ItAll [Etzioni et al., 2004] and TextRunner [Banko et al., 2007]. All of the aforementioned work focuses on bootstrapping new data to avoid excessive manual annotation, however, different from this work, it does not use the combination of learning algorithms to do so.

Distant supervision [Mintz et al., 2009] is a method to generate weak labels for unlabeled data on relationship extraction problems. Specifically, it uses a Knowledge Base (KB)

containing relationships of entities and assumes that each sentence that mentions a pair of entities known to have a specific relationship constitutes a positive example for this relationship. Of course, this leads to the creation of many noisy examples, but it has been widely used on large-scale (or web-scale) datasets, as no human annotation is required. The core idea of creating weakly-labeled datasets is the same as in our approach, but is achieved by different means. For the creation of the weak labels, we use classifiers pretrained in a small labeled dataset, instead of large Knowledge Bases which might be unavailable.

2.2 Relationship extraction from biomedical text

Most of the research on biomedical relation extraction has been motivated by BioCreative competitions and their corresponding annotated documents (datasets). BioCreative V (CDR task) focused on extracting Chemically-induced Diseases on a document-level [Wei et al., 2015b]. The best performing team implemented an ensemble of Support Vector Machines [Xu et al., 2015], while more recent research demonstrated that extending the training set using distant supervision improves the performance [Peng et al., 2016]. A following competition (BioCreative VI - CPR task) focused on identifying relations between Chemicals and Proteins (or Genes) on a sentence level [Krallinger et al., 2017a]. The best-performing team implemented an ensemble of LSTM, CNN and SVMs, using majority voting and stacking [Peng et al., 2018]. The second highest score was achieved using a Support-Vector Machines algorithm with a rich set of features, while other approaches using solely Deep Neural Networks demonstrated overfitting problems [Mehryary et al., 2018].

Those results highlight the importance of the lack of training data in this particular domain and demonstrate the suitability of ensemble methods for improving generalization, especially when Deep Neural Networks are used. To that end, our work aims to combine the advantages of those techniques with semi-supervised learning, a subject which to the best of our knowledge has not been investigated for this task. Further, we provide a framework where all of the aforementioned work can be used as an input.

2.3 Semi-supervised and ensemble learning methods

Both semi-supervised and ensemble learning techniques aim to improve the performance of Machine Learning algorithms. Ensemble learning typically reduces high variance by combining multiple learners, while semi-supervised learning tries to take advantage of unlabeled data to improve generalization. Although ensembles have been studied thoroughly and used in many application, their combination with semi-supervised has not. Zhou et al. [Zhou, 2011] argues about the helpfulness of this combination and demonstrate how those methods can be beneficial to each other. Specifically, ensembles enhance semi-supervised learning by providing multiple views and therefore allow the system to perform better, earlier (using less data). On the other hand, expanding the dataset with unlabeled data is likely to increase diversity between the learners, compared to as if only the original, small labeled set was used. The first system of this kind proposed was co-training [Blum and Mitchell, 1998], a paradigm where two distinct (independent) learning algorithms take advantage of unlabeled data. To satisfy the assumption of independence, Nigam et. al. [Nigam and Ghani, 2000] proposed splitting the features in different classifiers to create different views. Later research indicated that the independence assumption was too luxurious for a real-world

setting and relaxed the initial constraints of co-training [Balcan et al., 2005]. Specifically, the authors showed that iterative co-training can succeed as long as there is an expansion on the underlying data distribution.

Tri-training [Zhou and Li, 2005] is an extension of co-training to three learners. In this case, when two learners agree on the label of a new data point, they teach (re-train) the third learner using this example. Co-forest [Li and Zhou, 2007] is an extension to even more learners, where the decision on whether an unlabeled example should be added in the re-training stack is made by an ensemble system, using all learners.

The fundamental difference between our methodology and those earlier described, is that the learners included in the ensemble system (base learners) are not used for the final prediction; they are only used as a mean for generating the weak labels. For this reason, we do not aim to re-train or improve the base learners. This allows us to use all of the unlabeled data, whereas in the paradigms above only a few examples annotated with high confidence were added to the stack for re-training.

3. Background on Weak Supervision and Data Programming

In this section, we briefly describe the weak supervision and data programming paradigms, which have highly influenced the development of our methodology.

Weak supervision revolves around the idea of creating training labels of questionable quality. This is especially useful, when no ground-truth labels are available for training purposes. This is also the main focus of data programming [Ratner et al., 2016, 2017b], a newly-introduced paradigm for programmatic creation of large training sets. Data programming can be briefly described in the following steps:

(1) Providing weak supervision sources: A set of K weak supervision sources is defined and encoded into *Labeling Functions (LF)*. Typical weak sources of supervision include patterns and regular expressions for textual data, distant supervision (for relationship extraction problems) and crowd-sourced labels. Weak sources are modeled as voters, providing a label on some of the examples, while also retaining the option to abstain from voting.

(2) Unifying the weak supervision sources: The Labeling Functions are applied over the unlabeled set and construct a KxM (possibly incomplete) vote matrix. The intent now is to combine these votes in an optimal way and derive M weak labels, which are as close as possible to the (unknown) true labels. To denoise the votes and produce the weak labels, data programming uses a probabilistic Generative Model (GM), modeling the behavior, correlations and accuracy of the weak sources based on disagreements [Ratner et al., 2016, 2017a]. To estimate them without access to the ground truth, the likelihood that the observed votes occur under the Generative Model is optimized, for all possible ground-truth labels. The GM is subject to several hyperparameters, e.g. number of possible correlations, which can be automatically selected using a validation dataset [Bach et al., 2017]. Finally, weak labels are estimated as the posterior probability of the labels being y_1, given the observed votes $L1$: $P(y_1 \mid L_1)$

(3) Training a discriminative model with weak supervision: The weak labels are used to train a noise-aware discriminative model, which constitutes the final predictor. This model is noise-aware, in the sense that it minimizes the empirical loss with respect to the (marginal) probabilistic labels, estimated in the previous step.

4. Methodology

Based on the concepts of weak supervision and data programming, we propose a methodology for semi-supervised learning, with the intent to capitalize the advantages of multiple learners. In contrast to the typical data programming paradigm where no ground-truth labels are available, we focus on the scenario where a gold-labeled training set (D_G) is available, but we consider its size insufficient for training a complex (and therefore more data-hungry) model. We advocate that it would be beneficial to augment additional lower quality training data and effortlessly scale the dataset size. Another difference between data programming and our method is that instead of relying on heuristics, distant supervision or crowd-sourced labels, we use machine learning models of lower complexity to act as weak supervision sources (Labeling Functions). This also comes with the major advantage of adapting an already implemented pipeline with little or no additional effort to similar tasks.

4.1 Data collection

In terms of data, we assume that we are provided with a labeled training set D_G of size m, relevant to the task T we are trying to solve. Additionally to that, we require an unlabeled, arbitrarily large dataset D_U of size $M >> m$, with the requirement of being drawn from the same distribution as D_G. Lastly, we assume that we are also provided with a validation set D_V for hyperparameter tuning and a held-out test set D_T for evaluation purposes. Given the aforementioned datasets the proposed methodology can be described by the following steps:

4.2 Constructing diverse base learners

We use D_G to train K base learners on solving T. As in a typical ensemble learning scenario, we try to maximize their individual performance while making them capture different "views"' of the data. To produce multiple learners we rely on varying hyperparameters and design choices throughout the relation extraction pipeline, which allow us to create a variety of base learners. Below, we outline the different design choices we are varying in this work.

(1) Text trimming: Biomedical literature often contains lengthy and complex sentences. Therefore, words appearing within a sentence might be irrelevant to the entities of interest. For this reason, one can keep only the words between the two entities of interest. Alternatively, we can additionally include words appearing within a window before/after the entities. We can also resort to a more complex approach, incorporating syntactic information. One way to do so is to construct the dependency-based parse tree and include only words contained within the shortest path connecting the entities of interest. In this work we investigate (a) No trimming, (b) Trimming window of 0, (c) Trimming window of 5, and (d) Shortest Dependency path.

(2) Sequential features: Additionally to the simple bag-of-words approach, it is also possible to include contiguous sets of tokens as features. In our approach, we use up to tri-grams.

(3) Text representation: To convert our corpus to a numerical representation, we use token occurrences (binary counts) or TF-IDF weights.

(4) Machine learning algorithms: When the feature matrix is ready, we employ different machine learning algorithms, including Logistic Regression, Support Vector Machines (using Gaussian and linear kernels), Random Forest Classifiers, Long-Short Term Memory Networks and Convolutional Neural Networks. It is important to note, that when the last two models (LSTMs & CNNs) were used, none of the aforementioned feature engineering steps, (1) – (3), was applied.

4.3 Base learner selection

After producing all possible baselLearners, we select only a subset of them. This is necessary due to computational cost and the fact that we should avoid including many similar classifiers in a disagreement-based method. To illustrate this, consider a case where 10 simple Bag-of-Word models are used along with a more complex classifier, which also includes sequential features. The complex classifier is likely to disagree more with the rest, without necessarily having an inferior performance.

Hence, our objective is to maximize both the individual performance of the base learners and their diversity. Since this is complex and still an open issue [Zhou, 2011], we resort to a simple method, where we discard all classifiers having a lower performance than a certain threshold (evaluated on D_V), while maximizing diversity. Setting a performance threshold is also desirable, due to the fact that the base learners where automatically created with limited hyperparameter tuning. We set this threshold above the random guess baseline, but low enough to allow less accurate and more diverse classifiers to be part of the ensemble.

To select the most diverse classifiers, we employ a similarity-based clustering method. Using the predictions of the K base learners on D_V, we construct a KxK similarity matrix. In this matrix, each row and column refers to a base learner, while each cell consists of the corresponding pairwise inter-annotator agreement rates (Cohen Kappa coefficient). We perform K-means clustering [MacQueen et al., 1967] on this matrix and pick the base learners closest to the cluster centroids as most representative of their cluster. To pick an appropriate number of clusters (and therefore base learners), we refer to the silhouette score coefficient [Rousseeuw, 1987].

4.4 Producing weak labels

We predict the labels of D_U using the selected base learners and obtain a KxM (binary) prediction matrix, containing the "knowledge" our base learners have distilled from D_G. Consequently, we use a denoiser to reduce the vote matrix into M weak labels. We use the probabilistic *Generative Model* of data programming (described in Section 3) and select the hyperparameters using the validation dataset. Additionally, we consider two simpler denoisers to unify the label matrix: (a) a *Majority Vote* denoiser producing binary weak labels and (b) an *Average Vote* denoiser calculating an unweighted average of all base learner votes, therefore producing marginal weak labels.

4.5 Training a meta-learner

In the last step, we use a discriminative model (as described in Section 3) as a meta-learner. In practice, when training the meta-learner with weak supervision, we trade off label quality

Dataset	# docs	# entities	# candidates
CHEMPROT (training)	1020	25700	9917
CHEMPROT (development)	612	15500	6227
CHEMPROT (test)	800	19800	8285
CHEMPROT (all sets)	2432	61000	24429

Table 1: Basic dataset statistics

for quantity. This can be proven to be beneficial in cases where the performance of the meta-learner is upper-bounded by the training set size. By using high-capacity models such as Deep Neural Networks as meta-learners, we allow them to learn their own features and hopefully build a more accurate representation by relying on a much larger, even though noisy, training dataset.

5. Experimental Setup

To perform our experiments we use part of the functionality of Snorkel [Ratner et al., 2017b,a], a framework build for relation extraction with data programming and weak supervision.

5.1 Datasets

For the needs of our task, we use the official BioCreative VI CHEMPROT (Chemical-Protein interaction) dataset [Krallinger et al., 2017a], which consists of $2,432$ annotated PubMed [1] abstracts (split in a training, development and test set – Table 1).

As described in Subsection 4.1, our methodology requires three gold-labeled datasets. In our experiments, we use the original CHEMPROT test set as our held-out test set (D_T) and keep half of the development set for validation purposes (D_V). We merge and shuffle the remaining documents (training set + 1/2 development set) for training purposes. We use about a third of them (400 documents) to train the base learners (D_B), while treating the rest (926 documents) as if they were unlabeled (D_U).
Using this dataset setup, we can make sure that two important requirements are satisfied: (a) there is no bias during the document selection process, i.e. we ensure that the training, validation, test and unlabeled dataset are drawn from the same distribution, and (b) all documents have gone through the same pre-processing steps., i.e. labeled datasets have manually annotated entities, while a randomly drawn unlabeled dataset would require applying some Named Entity Recognition algorithm. We do so to better control the effect of such choices on the results of our algorithm. Another advantage with this controlled approach is that we are able to compare the performance of the meta-learner trained with weak supervision to the optimal performance, which would be achieved if the ground-truth labels were available.

---

1. https://www.ncbi.nlm.nih.gov/pubmed/

5.2 Text pre-processing and named entity recognition

Most of the steps in our text pre-processing pipeline are performed by SpaCy (v1.0), an open-source library for Natural Language Processing. More specifically, SpaCy performs the following tasks in our pipeline: Sentence splitting, Tokenization, Dependency parsing. Sentence splitting is required to extract same-sentence relation candidates, while the rest of the tasks are required for training our machine learning models (Base Learners & Meta Learner). The CHEMPROT dataset contains manually annotated Named Entity Tags for Proteins & Chemicals and therefore we do not need to rely on Named Entity Recognition algorithms, which are likely to introduce noise in our system.

5.3 Candidate extraction

After recognizing all entities within the text, we search for relationship candidates. We do not consider cross-sentence relations as they account for less than 1% of the total relationships [Peng et al., 2018] and proceed only with candidates found in the same sentence. We use Snorkel [Ratner et al., 2017b] for candidate extraction and mapping the candidates to their ground-truth labels.

5.4 Entity replacement

While building a relationship classifier, it is important to train an algorithm which can understand the Natural Language, rather than memorize the pairs which interact with each other. For this reason, we replace all entities of interest (chemicals & proteins). Specifically, we use the tokens 'ENTITY1' and 'ENTITY2' for the entities we want to predict. If additional entities are included in the sentence (eg. two chemicals), we replace them with the tokens 'CHEMICAL' and 'GENE' accordingly.

5.5 Meta-learner selection & training

In our experiments, we use a simple bi-directional Long-Short Term Memory network, which is one of the most commonly used and better performing Deep Neural Networks, on tasks related to Natural Language. Before training, we perform a random under-sampling (keeping an equal class balance). In terms of hyperparameters, we use different dropout values $(0, 0.25$ and $0.5)$ and train the LSTM for up to 30 epochs. We select the best hyperparameters using the validation dataset D_V.

6. Research Questions and Experimental Design

In this section, we form the research questions that we aim to answer, accompanied by our motivation to explore them. We discuss more details regarding RQ1 and RQ2 in Subsections 6.1 and 6.2 accordingly.

RQ1 Can we enhance biomedical relationship extraction when using Machine Learning classifiers as sources of weak supervision?

RQ2 Which is the optimal setting for using weak supervision on this task?

6.1 Machine learning classifiers as weak supervision sources

Related literature provides theoretical warranties, that in this setting and given specific requirements, adding weakly labeled data will improve the performance of the meta-learner [Ratner et al., 2016]. Additionally, as the amount of weakly labeled data increases, the performance of the meta-learner is expected to improve quasi-linearly (almost as good) compared to the scenario where the ground-truth labels were provided [Ratner et al., 2017a]. Those requirements include that the weak supervision sources should have accuracy better than random guess, overlap and disagree with each other enough (so that their accuracy can be estimated) while capturing different 'views' of the problem (diversity). In other words, when combined they should be able to model the problem space sufficiently, so that meaningful weak labels can be produced.

However, to the best of our knowledge, Machine Learning classifiers have not been used so far as weak supervision sources in such a setting, nor in this specific task. Therefore, it is unclear whether there is a diverse and sufficiently big set of base learners, that satisfies those conditions after being trained on the same dataset. This is a critical question, which actively affects the usability of the described methodology. To evaluate whether weak supervision helps, we conduct several experiments under different setups and compare the performance of the meta-learner when trained on three different modes: (a) full-supervision on D_B, (b) weak-supervision on D_U, (c) weak-supervision on D_U combined with full-supervision on D_B. Additionally, we can evaluate whether weak-supervision can achieve results comparable to full-supervision, after training the meta-learner using all ground-truth labels ($D_U + D_B$).

6.2 Optimal setting for applying this methodology

Number of base learners: Selecting the optimal number of classifiers to be used as base learners is not a straightforward task. Naturally, we can construct only a few top-performing learners and as we add more of them, we start to sacrifice performance in favor of diversity [Zhou, 2011]. To examine this, we gradually increase the number of Base Learners while benchmarking the performance of the weak labels and the meta-learner.

Comparison of various denoising methods: The denoising component is fundamental to this method, as it dictates the quality of the weak labels the final learner will be trained on. We use the three denosing methods described in Subsection 4.4 and assess the quality of the results.

Meta-learner performance under different weak label distributions: The denoiser can produce either binary or marginal (non-binary) weak labels. Additionally, marginal weak labels might be following different distributions, ranging from extremely U-shaped (almost binary) to more uniformly distributed. We perform an error analysis to investigate their effect on the training and the final performance of the meta-learner.

7. Results and Analysis

In Subsection 7.1 we answer RQ1, that is whether supervised machine learning classifiers can be used as weak classifiers, while in Subsection 7.2 we answer RQ2, that is what is the optimal setting for applying weak supervision.

7.1 Weak classifiers

To select the base learners, we use the strategy described on Subsection 4.3. We experiment with different number of base learners and benchmark results in intervals of 5 $(5, 10, 15$ and $20)$ and where the silhouette scores are maximized $(10, 13, 20)$.

training dataset	training set size	training set size (undersampled)	F1 score
D_B	3840	2060	44.7%
D_U	8221	4516	—
$D_B + D_U$	12061	6576	55.3%

Table 2: LSTM performance with gold labels

Base Learners		F1 score of weak labels		F1 score of meta-learner (LSTM)		
# B.L.	mean B.L. performance	Majority Vote	Generative Model	using M.V. labels	using AVG marginals	using GM marginals
5	53.20	58.91	61.07	50.11	53.56	52.40
10	54.30	63.04	62.22	52.66	56.45	52.93
13	54.00	63.09	61.28	54.16	58.03	52.65
15	53.67	63.11	61.48	51.01	56.32	53.40
20	53.95	63.57	61.91	50.05	55.60	54.73

Table 3: Performance achieved with weak supervision

We compare the results achieved with weak supervision on D_U (Table 3), versus full-supervision (Table 2). It is evident that weak supervision with a 3.5-fold increase in the training set size always performs better compared to training on the small gold labeled dataset (44.7%). This proves that we can successfully augment additional training data using weak supervision, as long as they are drawn from the same distribution. We can also observe that weak supervision can achieve a performance comparable to full-supervision (55.3%), using the same training set. In other words, for this dataset scale the meta-learner performs almost as good as if the labels were gold. Interestingly enough, there are even cases where weak supervision achieves slightly better results. However, differences are minor and not statistically significant, as there is a high variance on the F1 score of the LSTM. We also recognize that whenever this happened, the under-sampled training set size of the final learner was bigger and the Average Vote marginals were used. We further discuss how the distribution of the weak labels produced by this specific denoiser might have influenced the training of the meta-learner in Subsection 7.2. Another noteworthy observation, is that a simple Majority Vote would outperform our meta-learner. However, this is an expected result and does not undermine the importance of our results, as we can verify from Table 2 that a simple LSTM can only achieve an F1 score of 55.3% on such a small training dataset.

At last, we visualize the learning curves of the meta-learner (starting from the ground-truth labels) to ensure that the weak labels are meaningful and do actually improve performance. Figures 1b, 1c and 1d indicate an upward trend, while the outlined confidence

(a) Gold training labels

(b) Majority Vote weak labels

(c) Averaging weak marginals

(d) Generative Model weak marginals

Figure 1: LSTM learning curves

intervals indicate that the results are statistically significant. Moreover, we observe that the F1 score on the training set is always much higher than the test score. This is a sign that our meta-learner suffers from high variance (overfitting), as the model capacity is far from being fulfilled. Therefore, additional training data are expected to improve the performance of the meta-learner.

7.2 Optimal setting

The complexity of the problem and the methodology, along with the small dataset size do not allow us to draw definite answers in some of the following questions. However, we will perform an analysis based on our experimental results and discuss our findings.

Number of base learners: We can see from Table 3 that the $F1$ score of the weak Majority Vote labels is equally good when more than 10 learners are used. When it comes to the Generative model weak marginals, we cannot observe any significant pattern, as the F1 score always deviates within 1.5 points. The performance of the meta-learner when trained with Average Vote marginals deviates to a certain extent when more than 10 base learners are used, but always performs better compared to when only 5 base learners are used. Using Generative model marginals, performance seems to slightly improve as the

(a) Generative Model denoiser   (b) Average Vote denoiser

Figure 2: Error analysis

number of base learners increases. It is also noteworthy, that when unweighted voting labels (MV & AVG weak labels) were used, the meta-learner performed best with 13 base learners, which is roughly consistent with the silhouette scores (cluster coherency).

Comparison of various denoising methods: In all cases, the meta-learner achieves the best greater performance when trained with Average Marginals. Generative Model marginals also seem to improve its performance compared to Majority Vote weak labels, with one exception. However, it is worth highlighting the fact that GM marginals depend on hyperparameters, which are chosen based on the F1 score on a validation dataset. Later on this section, we argue and demonstrate why this particular measure cannot fully reflect the quality of marginal weak labels. Therefore, it is not certain whether we have achieved the optimal performance in cases where the Generative Model was used as the denoiser.

Performance under different weak label distributions: The denoisers can produce weak labels which are either binary or marginal (non-binary). We can conclude that marginal weak labels improve the performance of the meta-learner compared to binary labels. This is a straightforward comparison, as Majority Vote weak labels always perform worse than Average marginals while none of them is subject to hyperparameter tuning.

Moreover, we observe that the Generative Model tends to create marginals following a U-shaped distribution (close to 0 or 1) in contrast to the average marginals, which are spread more uniformly. This is evident from the error analysis we perform on the validation set, using a classification boundary of 0.5 (Figure 2a and 2b). In both cases, the amount of misclassified weak labels and therefore their F1 score is the same. However, it is evident that Average Vote labels are of higher quality, as most of their misclassified labels are relatively closer to 0.5. This is inevitable, as the vast majority of the GM marginals are very close to 0 and 1. Furthermore, these figures demonstrate the unsuitability of the $F1$ score for the evaluation of marginal weak labels.

On Figure 3, we can see how the training loss and validation scores change as we train the LSTM for more epochs. We can see that when marginal labels are used, the training error remains relatively high. This is especially true with the Average weak marginals, which are

Figure 3: LSTM training loss and validation score per training epoch

spread more uniformly. On the contrary, it only takes a few epochs for the LSTM to start predicting accurately the binary training labels, despite a small delay on the noisy-labeled MV weak labels. Ultimately, training a classifier using marginal labels can be thought of as a regression problem. In practice, we ask the classifier to predict an exact number (the output of the denoiser) and penalize it every time he fails to do so.

Lastly, we can see that the distributions of predicted logits (on unseen examples) become more spread as the training marginals distributions become more uniform (Figures 4a and 4b). This is something we would also expect to see when doing regression instead of classification.

(a) Generative Model training marginals   (b) Average training marginals

Figure 4: Histogram of predicted logits of LSTM

8. Unlabeled dataset expansion

In this section we discuss our efforts to apply our methodology on the same task, while expanding the labeled and unlabeled datasets. We use all of the CHEMPROT documents

(a) tSNE between training - test set   (b) tSNE between training - unlabeled set

Figure 5: tSNE visualization of data

(excluding validation and test sets) to train the base learners. To acquire D_U, we use the PubMed API [2] and download two different collections: (a) the outgoing citations of CHEMPROT documents (b) the 25 most similar documents of each CHEMPROT document (using the PMRA similarity metric [Lin and Wilbur, 2007]). In both cases, the performance of the meta-learner decreases as we add weakly labeled data, indicating a problem with the quality of D_U or the generated weak labels. We also observe a predicted class imbalance of 1:14 on the outgoing citations dataset compared to 1:4 on the original, indicating inherently different dataset distributions. To validate this, we visualize candidate samples drawn only from the original set (Figure 5a) and samples drawn from both sets (Figure 5b). It becomes evident that most candidates of the new dataset lie in specific regions of the $2D$ space, confirming that it is unsuitable for our use case. To that end, the best practices of constructing appropriate unlabeled datasets, must be further investigated.

9. Conclusions & future work

We have shown that weak supervision is a tool which can be used for enhancing the performance of complex models, such as deep neural networks, while utilizing both unlabeled data and multiple base learners. Additionally, we have shown that the proposed methodology is practically feasible for the task at hand, as we have succeeded on defining a combination of base learners, which model the problem space sufficiently and allow us to take advantage of additional, unlabeled data. This comes under the requirement that the unlabeled data are drawn from the same domain/distribution as our labeled data, so that our base learners can generalize and perform adequately on D_U.

In practice, our methodology shifts the human effort from hand-labeling examples to feature engineering and construction of diverse learners. More importantly, once a satisfactory set of diverse learners is in place, we can use this method to scale the training datasets

---

2. https://www.ncbi.nlm.nih.gov/pmc/tools/developers/

in arbitrarily high levels while consistently improving the performance over the supervised learning paradigm. Moreover, the same pipeline can be re-used on similar tasks with the only requirement of providing the appropriate datasets. In our use case for instance, adding more relationships would be possible with no major changes on the pipeline. On the contrary, in the typical supervised learning paradigm, we would have to repeatedly hand-label large datasets.

Despite demonstrating the usability of our method using a controlled, small-scale dataset, it is crucial to further explore the requirements of constructing a large enough unlabelled dataset and perform the same experiments there. That would likely improve performance further (which is currently upper-bounded by the small dataset size) and allow us to draw stronger conclusions on the research questions of Subsection 6.2. Additionally it would allow us to inspect how performance improves with the increase of D_U in a different scale of magnitude and if there seems to be a certain performance threshold, which we cannot surpass using weak supervision. Our preliminary experiments demonstrate that drawing an appropriate unlabeled dataset given a labeled one is a challenging task itself, along with the definition of "appropriate", and semi-supervised algorithms should not take the existence of an appropriate unlabeled dataset for granted.

Further, it would be very important to conclude on a more appropriate metric than the F1 score for the evaluation of marginal weak labels. Currently, the abscence of an appropriate metric prevents us from drawing conclusions directly from the weak labels, without having to introduce an additional step (train the meta-learner). This would also allow us to select the optimal hyperparameters of the Generative Model and could have a significant impact upon the final performance. Metrics used in Information Retrieval (such as the Mean Average Precision) might prove more appropriate. However, we should highlight that such metrics usually take into account the order of the results, while our intent would be to measure errors while taking into consideration the corresponding confidence levels. Another important property of the desired metric would be robustness to high class imbalance, which is common in Information Extraction tasks.

Last, it would be interesting to examine how this system would behave if the Base Learners abstained from voting on the examples they are less certain about. A naive approach to do that would be to delete a percentage (eg. 50%) of the votes which are closer to the classification boundary. A more advanced approach would be to perform a probability calibration on each Base Learner (so that predicted logits correspond to probabilities) and choose a confidence threshold below which they would abstain voting. This could also provide the Generative Model with a modeling advantage, compared to unweighted methods (such as Majority Voting), as described in an analysis related to the trade-offs of weak supervision [Ratner et al., 2017a].

References

Eugene Agichtein and Luis Gravano. Snowball: Extracting relations from large plain-text collections. In *Proceedings of the fifth ACM conference on Digital libraries*, pages 85–94. ACM, 2000.

Stephen H. Bach, Bryan He, Alexander Ratner, and Christopher R. Learning the Structure of Generative Models without Labeled Data. *arXiv:1703.00854 [cs, stat]*, March 2017. URL http://arxiv.org/abs/1703.00854. arXiv: 1703.00854.

Maria-Florina Balcan, Avrim Blum, and Ke Yang. Co-training and expansion: Towards bridging theory and practice. In *Advances in neural information processing systems*, pages 89–96, 2005.

Michele Banko, Michael J Cafarella, Stephen Soderland, Matthew Broadhead, and Oren Etzioni. Open information extraction from the web. In *IJCAI*, volume 7, pages 2670–2676, 2007.

Avrim Blum and Tom Mitchell. Combining labeled and unlabeled data with co-training. In *Proceedings of the eleventh annual conference on Computational learning theory*, pages 92–100. ACM, 1998.

Sergey Brin. Extracting patterns and relations from the world wide web. In *International Workshop on The World Wide Web and Databases*, pages 172–183. Springer, 1998.

David Campos, Sérgio Matos, and José Luís Oliveira. A modular framework for biomedical concept recognition. *BMC bioinformatics*, 14(1):281, 2013.

Oren Etzioni, Michael Cafarella, Doug Downey, Stanley Kok, Ana-Maria Popescu, Tal Shaked, Stephen Soderland, Daniel S Weld, and Alexander Yates. Web-scale information extraction in knowitall:(preliminary results). In *Proceedings of the 13th international conference on World Wide Web*, pages 100–110. ACM, 2004.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT press Cambridge, 2016.

Martin Krallinger, Obdulia Rabal, Saber A Akhondi, Martín Pérez Pérez, Jesús Santamaría, Gael Pérez, Georgios Tsatsaronis Rodríguez, Ander Intxaurrondo, José Antonio López1 Umesh Nandal, and Erin Van Buel. Overview of the biocreative vi chemical-protein interaction track. In *Proceedings of the sixth BioCreative challenge evaluation workshop*, volume 1, pages 141–146, 2017a.

Martin Krallinger, Obdulia Rabal, Anlia Loureno, Julen Oyarzabal, and Alfonso Valencia. Information Retrieval and Text Mining Technologies for Chemistry. *Chemical Reviews*, 117(12):7673–7761, June 2017b. ISSN 0009-2665, 1520-6890. doi: 10.1021/acs.chemrev. 6b00851. URL http://pubs.acs.org/doi/10.1021/acs.chemrev.6b00851.

Robert Leaman, Chih-Hsuan Wei, and Zhiyong Lu. tmChem: a high performance approach for chemical named entity recognition and normalization. *Journal of Cheminformatics*,

7(Suppl 1 Text mining for chemistry and the CHEMDNER track):S3, 2015. ISSN 1758-2946. doi: 10.1186/1758-2946-7-S1-S3.

Ming Li and Zhi-Hua Zhou. Improve computer-aided diagnosis with machine learning techniques using undiagnosed samples. *IEEE Transactions on Systems, Man, and Cybernetics-Part A: Systems and Humans*, 37(6):1088–1098, 2007.

Jimmy Lin and W John Wilbur. Pubmed related articles: a probabilistic topic-based model for content similarity. *BMC bioinformatics*, 8(1):423, 2007.

Daniel M Lowe and Roger A Sayle. Leadmine: a grammar and dictionary driven approach to entity recognition. *Journal of cheminformatics*, 7(1):S5, 2015.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of machine learning research*, 9(Nov):2579–2605, 2008.

James MacQueen et al. Some methods for classification and analysis of multivariate observations. In *Proceedings of the fifth Berkeley symposium on mathematical statistics and probability*, pages 281–297. Oakland, CA, USA, 1967.

Farrokh Mehryary, Jari Björne, Tapio Salakoski, and Filip Ginter. Combining support vector machines and lstm networks for chemical-protein relation extraction. In *Proceedings of the BioCreative VI Workshop*, pages 175–179, 2018.

Mike Mintz, Steven Bills, Rion Snow, and Dan Jurafsky. Distant supervision for relation extraction without labeled data. In *Proceedings of the Joint Conference of the 47th Annual Meeting of the ACL and the 4th International Joint Conference on Natural Language Processing of the AFNLP: Volume 2-Volume 2*, pages 1003–1011. Association for Computational Linguistics, 2009.

Kamal Nigam and Rayid Ghani. Analyzing the effectiveness and applicability of co-training. In *Proceedings of the ninth international conference on Information and knowledge management*, pages 86–93. ACM, 2000.

Yifan Peng, Chih-Hsuan Wei, and Zhiyong Lu. Improving chemical disease relation extraction with rich features and weakly labeled data. *Journal of Cheminformatics*, 8 (1), December 2016. ISSN 1758-2946. doi: 10.1186/s13321-016-0165-z. URL http://jcheminf.springeropen.com/articles/10.1186/s13321-016-0165-z.

Yifan Peng, Anthony Rios, Ramakanth Kavuluru, and Zhiyong Lu. Chemical-protein relation extraction with ensembles of SVM, CNN, and RNN models. *arXiv preprint arXiv:1802.01255*, 2018.

Alexander Ratner, Stephen H. Bach, Henry Ehrenberg, Jason Fries, Sen Wu, and Christopher R. Snorkel: rapid training data creation with weak supervision. *Proceedings of the VLDB Endowment*, 11(3):269–282, November 2017a. ISSN 21508097. doi: 10.14778/3157794.3157797. URL http://dl.acm.org/citation.cfm?doid=3173074.3173077.

Alexander J. Ratner, Christopher M. De Sa, Sen Wu, Daniel Selsam, and Christopher R. Data programming: Creating large training sets, quickly. In *Advances in Neural Information Processing Systems*, pages 3567–3575, 2016.

Alexander J. Ratner, Stephen H. Bach, Henry R. Ehrenberg, and Chris Ré. Snorkel: Fast training set generation for information extraction. In *Proceedings of the 2017 ACM International Conference on Management of Data*, SIGMOD '17, pages 1683–1686, New York, NY, USA, 2017b. ACM. ISBN 978-1-4503-4197-4. doi: 10.1145/3035918.3056442. URL http://doi.acm.org/10.1145/3035918.3056442.

Peter J. Rousseeuw. Silhouettes: A graphical aid to the interpretation and validation of cluster analysis. *Journal of Computational and Applied Mathematics*, 20:53–65, November 1987. ISSN 03770427. doi: 10.1016/0377-0427(87)90125-7. URL http://linkinghub.elsevier.com/retrieve/pii/0377042787901257.

Chih-Hsuan Wei, Hung-Yu Kao, and Zhiyong Lu. Gnormplus: an integrative approach for tagging genes, gene families, and protein domains. *BioMed research international*, 2015, 2015a.

Chih-Hsuan Wei, Yifan Peng, Robert Leaman, Allan Peter Davis, Carolyn J. Mattingly, Jiao Li, Thomas C. Wiegers, and Zhiyong Lu. Overview of the BioCreative V chemical disease relation (CDR) task. In *Proceedings of the fifth BioCreative challenge evaluation workshop*, pages 154–166. Sevilla Spain, 2015b.

Chih-Hsuan Wei, Yifan Peng, Robert Leaman, Allan Peter Davis, Carolyn J Mattingly, Jiao Li, Thomas C Wiegers, and Zhiyong Lu. Assessing the state of the art in biomedical relation extraction: overview of the biocreative v chemical-disease relation (cdr) task. *Database*, 2016, 2016.

Jun Xu, Yonghui Wu, Yaoyun Zhang, Jingqi Wang, Ruiling Liu, Qiang Wei, and Hua Xu. UTH-CCB@ BioCreative V CDR task: identifying chemical-induced disease relations in biomedical text. In *Proceedings of the Fifth BioCreative Challenge Evaluation Workshop*, pages 254–259, 2015.

Zhi-Hua Zhou. When semi-supervised learning meets ensemble learning. *Frontiers of Electrical and Electronic Engineering in China*, 6(1):6–16, 2011.

Zhi-Hua Zhou and Ming Li. Tri-training: Exploiting unlabeled data using three classifiers. *IEEE Transactions on knowledge and Data Engineering*, 17(11):1529–1541, 2005.