# THE VARIATIONAL DEFICIENCY BOTTLENECK

## ABSTRACT

We introduce a bottleneck method for learning data representations based on channel deficiency, rather than the more traditional information sufficiency. A variational upper bound allows us to implement this method efficiently. The bound itself is bounded above by the variational information bottleneck objective, and the two methods coincide in the regime of single shot Monte Carlo approximations. The notion of deficiency provides a principled way of approximating complicated channels by relatively simpler ones. The deficiency of one channel w.r.t. another has an operational interpretation in terms of the optimal risk gap of general decision problems, capturing classification as a special case. Unsupervised generalizations are possible, such as the deficiency autoencoder, which also can be formulated in a variational form. Experiments demonstrate that the deficiency bottleneck can provide advantages in terms of minimal sufficiency as measured by information bottleneck curves, while retaining a good test performance in classification and reconstruction tasks.

*Keywords:* Variational Information Bottleneck, Blackwell Sufficiency, Le Cam Deficiency, Information Channel

## 1 INTRODUCTION

The information bottleneck (IB) is an approach to learning data representations based on a notion of minimal sufficiency. The general idea is to map an input source into a representation that retains as little information as possible about the input (*minimality*), but retains as much information as possible in relation to a target variable of interest (*sufficiency*). See Figure 1. For example, in a classification problem the target variable could be the class label of the input data. In a reconstruction problem, the target variable could be a denoised reconstruction of the input. Intuitively, a representation which is minimal in relation to a given task, will discard nuisances in the inputs that are irrelevant to the task, and hence distill more meaningful information and allow for a better generalization.

In a typical bottleneck paradigm, an input variable $X$ is first mapped to an intermediate representation variable $Z$, and then $Z$ is mapped to an output variable of interest $Y$. We call the mappings, resp., a representation model (*encoder*) and an inference model (*decoder*). The channel $\kappa$ models the true relation between the input $X$ and the output $Y$. In general, the channel $\kappa$ is unknown, and only accessible through a set of examples $(x^{(i)}, y^{(i)})_{i=1}^N$. We would like to obtain an approximation of $\kappa$ using a probabilistic *model* that comprises of the *encoder-decoder pair*.

The IB methods (Witsenhausen & Wyner, 1975; Tishby et al., 1999; Harremoës & Tishby, 2007; Hsu et al., 2018) have found numerous applications, e.g., in representation learning, clustering, classification, generative modelling, reinforcement learning, neural networks, among others (see, e.g., Shamir et al., 2008; Gondek & Hofmann, 2003; Alemi et al., 2016).

In the traditional IB, minimality and sufficiency are measured in terms of the mutual information. Computing the mutual information can be challenging in practice. Various recent works have formulated more tractable functions by way of variational bounds on the mutual information (Chalk et al., 2016; Alemi et al., 2016; Kolchinsky et al., 2017), sandwiching the objective function of interest.

Instead of approximating the sufficiency term of the IB, we formulate a new bottleneck method that minimizes deficiency. Deficiencies provide a principled way of approximating complicated channels by relatively simpler ones. The deficiency of a decoder with respect to the true channel between

Figure 1: The Bottleneck paradigm: The general idea of a bottleneck method is to first map an input $X$ to an intermediate representation $Z$, and then map $Z$ to an output $Y$. We call the mappings, resp., an encoder ($e$) and a decoder ($d$). The channel $\kappa$ models the true relation between the input $X$ and the output $Y$. In general, the channel $\kappa$ is unknown, and only accessible through a set of training examples. We would like to obtain an approximation of $\kappa$.

input and output variables quantifies the extent to which any pre-processing of the decoder (by way of randomized encodings) can be used to approximate the true channel (in the KL-distance sense). Deficiencies have a rich heritage in theory of comparison of statistical experiments (Blackwell, 1953; Le Cam, 1964; Torgersen, 1991). From this angle, the formalism of deficiencies has been used to obtain bounds on optimal risk gaps of statistical decision problems. As we show, the deficiency bottleneck minimizes a regularized risk gap. Moreover, the proposed method has an immediate variational formulation and that can be easily implemented as a modification of the Variational Information Bottleneck (VIB) (Alemi et al., 2016). In fact, both method coincide in the limit of single-shot Monte Carlo approximations. We call our method the Variational Deficiency Bottleneck (VDB).

As we show in Proposition 2, perfect optimization of the IB sufficiency corresponds to perfect minimization of the DB deficiency. However, when working over a parametrized model and adding the bottleneck regularizer, both methods have different preferences, with the DB being closer to the optimal risk gap. Experiments on basic data sets show that the VDB is able to obtain more compressed representations than the VIB while performing equally well or better in terms of test accuracy.

We describe the details of our method in Section 2. We elaborate on the theory of deficiencies in Section 3. Experimental results with the VDB are presented in Section 4.

## 2 THE VARIATIONAL DEFICIENCY BOTTLENECK (VDB)

Let $X$ denote an observation or *input* variable and $Y$ an *output* variable of interest. Let $p(x, y) = \pi(x)\kappa(y|x)$ be the true joint distribution, where the conditional distribution or *channel* $\kappa(y|x)$ describes how the output depends on the input. We consider the situation where the true channel is unknown, but we are given a set of $N$ independent and identically distributed (i.i.d.) samples $(x^{(i)}, y^{(i)})_{i=1}^N$ from $p$. Our goal is to use this data to learn a more structured version of the channel $\kappa$, by first "compressing" the input $X$ to an intermediate *representation* variable $Z$ and subsequently mapping the representation back to the output $Y$. The presence of an intermediate representation can be regarded as a bottleneck, a model selection problem, or as a regularization strategy.

We define a *representation model* and an *inference model* using two parameterized families of channels $e(z|x)$ and $d(y|z)$. We will refer to $e(z|x)$ and $d(y|z)$ as an *encoder* and a *decoder*. The encoder-decoder pair induces an equivalent model $\widehat{\kappa}(y|x) = \int d(y|z)e(z|x)dz$. Equivalently, we write $\widehat{\kappa} = d \circ e$.

Given a representation, we want the decoder to be as powerful as the original channel $\kappa$ in terms of ability to recover the output. The deficiency of a decoder $d$ w.r.t. $\kappa$ quantifies the extent to which any pre-processing of $d$ (by way of randomized encodings) can be used to approximate $\kappa$ (in the KL-distance sense). Let $\mathsf{M}(\mathcal{X}; \mathcal{Y})$ denote the space of all channels from $\mathcal{X}$ to $\mathcal{Y}$. We define the deficiency of $d$ w.r.t. $\kappa$ as follows.

**Definition 1.** Given the channel $\kappa \in \mathsf{M}(\mathcal{X}; \mathcal{Y})$ from $X$ to $Y$, and a decoder $d \in \mathsf{M}(\mathcal{Z}; \mathcal{Y})$ from some $Z$ to $Y$, the *deficiency of $d$ w.r.t. $\kappa$* is defined as

$$\delta^\pi(d, \kappa) = \min_{e \in \mathsf{M}(\mathcal{X}; \mathcal{Z})} D_{\mathrm{KL}}(\kappa \| d \circ e | \pi). \tag{1}$$

Here $D_{\mathrm{KL}}(\cdot\|\cdot)$ is the conditional KL divergence (Csiszár & Körner, 2011). The definition is similar in spirit to Lucien Le Cam's notion of weighted deficiencies of one channel w.r.t. another (Le Cam, 1964), (Torgersen, 1991, Section 6.2) and its recent generalization by Raginsky Raginsky (2011).

We propose to train the model by minimizing the deficiency of $d$ w.r.t. $\kappa$ subject to a regularization that penalizes complex representations. The regularization is achieved by limiting the *rate* $I(Z; X)$, the mutual information between the representation and the raw inputs. We call our method the Deficiency Bottleneck (DB). The DB minimizes the following objective over all tuples $(e \in \mathsf{M}(\mathcal{X}; \mathcal{Z}), d \in \mathsf{M}(\mathcal{Z}; \mathcal{Y}))$.

$$\mathcal{L}_{DB}(e, d) := \delta^\pi(d, \kappa) + \beta I(Z; X). \tag{2}$$

The parameter $\beta \geq 0$ allows us to adjust the level of regularization.

For any distribution $r(z)$, the rate term admits a simple variational upper bound (Csiszár & Körner, 2011, Eq. (8.7)).

$$I(Z; X) \leq \int p(x, z) \log \tfrac{e(z|x)}{r(z)} \, dx \, dz \,. \tag{3}$$

Let $\hat{p}_{\mathrm{data}}$ be the empirical distribution of the data (input-output pairs). By noting that $\delta^\pi(d, \kappa) \leq D_{\mathrm{KL}}(\kappa \| d \circ e | \pi)$ for any $e \in \mathsf{M}(\mathcal{X}; \mathcal{Z})$, and ignoring (unknown) data-dependent constants, we obtain the following optimization objective which we call the Variational Deficiency Bottleneck (VDB) objective.

$$\mathcal{L}_{VDB}(e, d) := \mathbb{E}_{(x,y) \sim \hat{p}_{\mathrm{data}}} \left[ -\log d \circ e(y|x) + \beta D_{\mathrm{KL}}(e(Z|x) \| r(Z)) \right]. \tag{4}$$

The computation is simplified by defining $r(z)$ to be a standard multivariate Gaussian distribution $\mathcal{N}(0, I)$ and using an encoder that outputs a Gaussian distribution. More precisely, we consider an encoder of the form $e(z|x) = \mathcal{N}(z|f_\phi(x))$, where $f_\phi$ is a neural network that outputs the parameters of a Gaussian distribution. Using the reparametrization trick (Kingma & Welling, 2013; Rezende et al., 2014), we then write $e(z|x)dz = p(\epsilon)d\epsilon$, where $z = f(x, \varepsilon)$ is a function of $x$ and the realization $\epsilon$ of a standard normal distribution. This allows us to do stochastic backpropagation through a single sample $z$. The KL term admits an analytic expression for a choice of Gaussian $r(z)$ and encoders. We train the model by minimizing the following empirical objective.

$$\frac{1}{N} \sum_{i=1}^{N} \left[ -\log\left(\frac{1}{M} \sum_{j=1}^{M} [d(y^{(i)}|f(x^{(i)}, \epsilon^{(j)}))]\right) + \beta D_{\mathrm{KL}}(e(Z|x^{(i)}) \| r(Z)) \right]. \tag{5}$$

For batch training, we choose a mini-batch size of $N = 100$. For Monte Carlo estimates of the expectation inside the log, we choose $M = 3, 6, 12$ samples from the encoding distribution.

We note that the Variational Information Bottleneck (VIB) (Alemi et al., 2016) leads to a similar-looking objective function, with the only difference that the sum over $j$ is outside of the log. By Jensen's inequality, the VIB loss is an upper bound to our loss. If one uses a single sample from the encoding distribution (i.e., $M = 1$), the VDB and the VIB objective functions coincide.

The average log-loss and the rate term in the VDB objective equation 4 are the two fundamental quantities that govern the probability of error when the model is a classifier. For a detailed discussion of these relations see Appendix A.

# 3 BLACKWELL SUFFICIENCY AND CHANNEL DEFICIENCY

In this section, we discuss an intuitive geometric interpretation of the deficiency in the space of probability distributions over the output variable. We also give an operational interpretation of the deficiency as a deviation from Blackwell sufficiency (in the KL-distance sense). Finally, we discuss its relation to the log-loss.

## 3.1 DEFICIENCY AND DECISION GEOMETRY

We first formulate the learning task as a decision problem. We show that $\delta^\pi(d, \kappa)$ quantifies the gap in the optimal risks of decision problems when using the channel $d$ rather than $\kappa$.

Let $\mathcal{X}$, $\mathcal{Y}$ denote the space of possible inputs and outputs and let $\mathbb{P}_\mathcal{Y}$ be the set of all distributions on $\mathcal{Y}$. For every $x \in \mathcal{X}$, define $\kappa_x \in \mathbb{P}_\mathcal{Y}$ as $\kappa_x(y) = \kappa(y|x)$, $\forall y \in \mathcal{Y}$. Nature draws $x \sim \pi$ and $y \sim \kappa_x$. The learner observes $x$ and *quotes* a distribution $q_x \in \mathbb{P}_\mathcal{Y}$ that expresses her uncertainty about the true value $y$. The quality of a quote $q_x$ in relation to $y$ is measured by an extended real-valued loss function called the *score* $\ell \colon \mathcal{Y} \times \mathbb{P}_\mathcal{Y} \to \overline{\mathbb{R}}$. For a background on such special kind of loss functions (see, e.g., Grünwald et al., 2004; Gneiting & Raftery, 2007; Parry et al., 2012). Ideally, the quote $q_x$ should to be as close as possible to the true conditional distribution $\kappa_x$. This is achieved by minimizing the expected loss $L(\kappa_x, q_x) := \mathbb{E}_{y \sim \kappa_x} \ell(y, q_x)$, for all $x \in \mathcal{X}$. The score is called *proper* if $\kappa_x \in \arg\min_{q_x \in \mathbb{P}_\mathcal{Y}} L(\kappa_x, q_x)$. Define the *Bayes act* against $\kappa_x$ as the optimal quote

$$q_x^* := \arg\min_{q_x \in \mathbb{P}_\mathcal{Y}} L(\kappa_x, q_x).$$

If multiple Bayes acts exist then select one arbitrarily. Define the *Bayes risk* for the distribution $p_{XY}(x, y) = \pi(x)\kappa(y|x)$ as $R(p_{XY}, \ell) := \mathbb{E}_{x \sim \pi} L(\kappa_x, q_x^*)$. A score is *strictly proper* if the Bayes act is unique. An example of a strictly proper score is the log-loss function defined as $\ell_L(y, q) := -\log q(y)$. For the log-loss, the Bayes act is $q_x^* = \kappa_x$ and the Bayes risk is just the conditional entropy.

$$R(p_{XY}, \ell_L) = \mathbb{E}_{x \sim \pi} \mathbb{E}_{y \sim \kappa_x} \big[ -\log q_x^*(y) \big] = \mathbb{E}_{x \sim \pi} \mathbb{E}_{y \sim \kappa_x} \big[ -\log \kappa_x(y) \big] = H(Y|X). \quad (6)$$

Given a representation $z \in \mathcal{Z}$ (output by some encoder), when using the decoder channel $d$, the learner is constrained to quote a distribution from a subset of $\mathbb{P}_\mathcal{Y}$ which is the convex hull of the points $\{d_z\}_{z \in \mathcal{Z}} \in \mathbb{P}_\mathcal{Y}$. Let $C = \mathrm{conv}(\{d_z : z \in \mathcal{Z}\}) \subset \mathbb{P}_\mathcal{Y}$. The Bayes act against $d_z$ is

$$q_{x_Z}^* := \arg\min_{q_x \in C \subset \mathbb{P}_\mathcal{Y}} \mathbb{E}_{y \sim \kappa_x} \big[ -\log q_x(y) \big]. \quad (7)$$

$q_{x_Z}^*$ has an interpretation as the *reverse I-projection* of $\kappa_x$ to the convex set of probability measures $C \subset \mathbb{P}_\mathcal{Y}$ (Csiszár & Matuš, 2003)[1]. We call the associated Bayes risk as the *projected Bayes risk* $R_Z(p_{XY}, \ell_L)$ and the associated conditional entropy as the *projected conditional entropy* $H_Z(Y|X)$.

$$R_Z(p_{XY}, \ell_L) = \mathbb{E}_{x \sim \pi} \mathbb{E}_{y \sim \kappa_x} \big[ -\log q_{x_Z}^*(y) \big] = H_Z(Y|X). \quad (8)$$

The gap in the optimal risks, $\Delta R := R_Z(p_{XY}, \ell_L) - R(p_{XY}, \ell_L)$ when making a decision based on an intermediate representation and a decision based on the input data is just the deficiency. This follows from noting that

$$\Delta R = H_Z(Y|X) - H(Y|X) = \sum_{x \in \mathcal{X}} \pi(x) \min_{q_x \in C \subset \mathbb{P}_\mathcal{Y}} D_{\mathrm{KL}}(\kappa_x \| q_x)$$

$$= \min_{e \in \mathsf{M}(\mathcal{X}; \mathcal{Z})} \sum_{x \in \mathcal{X}} \pi(x) D_{\mathrm{KL}}(\kappa_x \| d \circ e_x)$$

$$= \min_{e \in \mathsf{M}(\mathcal{X}; \mathcal{Z})} D_{\mathrm{KL}}(\kappa \| d \circ e | \pi) = \delta^\pi(d, \kappa). \quad (9)$$

$\Delta R$ vanishes if and only if the optimal quote against $d_z$, $q_{x_Z}^*$ matches $\kappa_x$ for all $x, y$. This gives an intuitive geometric interpretation of a vanishing deficiency in the space of distributions over $\mathcal{Y}$.

Given a decoder channel $d$, since $\delta^\pi(d, \kappa) \leq D_{\mathrm{KL}}(\kappa \| d \circ e | \pi)$ for any $e \in \mathsf{M}(\mathcal{X}; \mathcal{Z})$, the loss term in the VDB objective is a variational upper bound on the projected conditional entropy $H_Z(Y|X)$. However, this loss is still a lower bound to the standard cross-entropy loss in the VIB objective (Alemi et al., 2016), i.e.,

$$\mathbb{E}_{(x,y) \sim \hat{p}_{\mathrm{data}}} \left[ -\log d \circ e(y|x) \right] \leq \mathbb{E}_{(x,y) \sim \hat{p}_{\mathrm{data}}} \left[ -e(z|x) \log d(y|z) \right]. \quad (10)$$

This follows simply from the convexity of the negative logarithm function.

---

[1]Such a projection exists and is not necessarily unique since the set we are projecting onto is not log-convex. If nonunique, we arbitrarily select one of the minimizers as the Bayes act.

## 3.2 DEFICIENCY AS A KL-DISTANCE FROM INPUT-BLACKWELL SUFFICIENCY

In a seminal paper (Blackwell, 1953), David Blackwell asked the following question: if a learner wishes to make an optimal decision about some target variable of interest and she can choose between two channels with a *common input* alphabet, which one should she prefer? She can rank the channels by comparing her optimal risks: she will *always* prefer one channel over another if her optimal risk when using the former is at most that when using the latter for any decision problem. She can also rank the variables purely probabilistically: she will *always* prefer the former if the latter is an *output-degraded* version of the former, in the sense that she can simulate a single use of the latter by randomizing at the output of the former. Blackwell showed that these two criterias are equivalent.

Very recently, Nasser (2017) asked the same question, only now the learner has to choose between two channels with a *common output* alphabet. Given two channels, $\kappa \in \mathsf{M}(\mathcal{Z}; \mathcal{Y})$ and $d \in \mathsf{M}(\mathcal{X}; \mathcal{Y})$, we say that $\kappa$ is *input-degraded* from $d$ and write $d \succeq_{\mathcal{Y}} \kappa$ if $\kappa = d \circ e$ for some $e \in \mathsf{M}(\mathcal{X}; \mathcal{Z})$. Stated in another way, $d$ can be reduced to $\kappa$ by applying a randomization at its input. Nasser (2017) gave a characterization of input-degradedness that is similar to Blackwell's theorem (Blackwell, 1953). We say, $d$ is *input-Blackwell sufficient* for $\kappa$ if $d \succeq_{\mathcal{Y}} \kappa$.

Input-Blackwell sufficiency induces a preorder on the set of all channels with the same output alphabet. In practice, most channels are uncomparable, i.e., one cannot be reduced to another by a randomization. When such is the case, our deficiency quantifies how far the true channel $\kappa$ is from being a randomization (by way of all input encodings) of the decoder $d$. This is similar in spirit with Le Cam's notion of weighted channel deficiencies (Le Cam, 1964; Torgersen, 1991) and its recent generalization by Raginsky (Raginsky, 2011). See Appendix B for a brief summary of Le Cam theory which provides a principled way of approximating complicated channels by relatively simpler ones.

## 3.3 DEFICIENCY AND THE LOG-LOSS

When $Y - X - Z$ is a Markov chain, the conditional mutual information $I(Y; X|Z)$ is the Bayes risk gap for the log-loss. This is apparent from noting that $I(Y; X|Z) = H(Y|Z) - H(Y|XZ) = H(Y|Z) - H(Y|X) = R(p_{ZY}, \ell_L) - R(p_{XY}, \ell_L)$. This risk gap is closely related to Blackwell's original notion of sufficiency. Since the log-loss is strictly proper, a vanishing $I(Y; X|Z)$ implies that the risk gap is zero for all loss functions. This suggests that minimizing the log-loss risk gap under a suitable regularization constraint is a potential recipe for constructing representations $Z$ that are *approximately sufficient* for $X$ w.r.t. $Y$, since in the limit when $I(Y; X|Z) = 0$ one would achieve $I(Y; Z) = I(Y; X)$. This is indeed the basis for the IB algorithm (Tishby et al., 1999) and related generalizations, clustering with Bregman divergences (Banerjee et al., 2005) and loss-insensitive feature learning (Van Rooyen & Williamson, 2014).

One can also approximate a sufficient statistic by *minimizing deficiencies* instead. This follows from noting the following equivalence. The proof is in Appendix C.

**Proposition 2.** When $Y - X - Z$ is a Markov chain, $\delta^\pi(d, \kappa) = 0 \iff I(Y; X|Z) = 0$.

In general, for the bottleneck paradigms involving the conditional mutual information (IB) and the deficiency (DB), we have the following relationship.

$$\min_{e(z|x): I(Y;X|Z) \leq \epsilon} I(X; Z) \geq \min_{e(z|x): \delta^\pi(d,\kappa) \leq \epsilon} I(X; Z). \tag{11}$$

It is clear from Proposition 2 that the representations are going to be the same only in the limit of *exact sufficiency*. Our experiments corroborate that for achieving the same level of sufficiency, one needs to store less information about the input $X$ when minimizing the deficiencies than when minimizing the conditional mutual information.

## 4 EXPERIMENTS

We present some experiments on the MNIST dataset (LeCun & Cortes, 2010). Classification on MNIST is a very well studied problem. The main objective of our experiments is to evaluate the

Figure 2: Effect of the regularization parameter $\beta$. Accuracy on test data after training. Mutual information values after training. The curves are averages over 5 repetitions of the experiment. Each curve corresponds to one value of $M = 1, 3, 6, 12$. Notice the generalization gap in the lower right panel, which happens at small values of the regularization parameter $\beta$. This indicates that the bottleneck regularization allows for a better generalization of the mutual informations between representation and label. The lower right panel shows a gap between the levels of compression depending on $M$. Higher values of $M$ (our method) lead to a more compressed representation. Here $L$ corresponds to the number of posterior samples (this is not used in training, but just at test time).

information theoretic properties of the representations learned by the VDB and whether it can match the classification accuracy provided by other bottleneck methods.

For the encoder we use a fully connected feedforward network with 784 input units 1024 ReLUs 1024 ReLUs 512 linear units. The deterministic output of this network is interpreted as the vector of means and variances of a 256 dimensional Gaussian distribution. The decoder is a simple logistic regression model with a softmax layer outputting 10-ary logits. These are the same settings of the model presented by Alemi et al. (2016). We implement the algorithm in Tensorflow and train for 200 epochs using the Adam optimizer.

As can be seen from Figure 2, the test accuracy improves with increasing $M$. We note that $M = 1$ is just the VIB model (Alemi et al., 2016). Our best test accuracy results are for $\beta$ in the range of $10^{-5}$ and $10^{-4}$. Figures showing the dynamics of learning are provided in Appendix D.

The lower left panel of Figure 2 shows the information bottleneck curve. This is the comparison of mutual informations between representation and input vs representation and output, at the end of training, depending on the value of the regularization parameter $\beta$. For orientation, lower values of $\beta$ have higher values of $I(Z; X)$ (towards the right of the plot). For small values of $\beta$, when the effect of the regularization is negligible, the bottleneck allows more information from the input through the representation. For smaller values of $\beta$, the mutual information between the representation and the label increases on the training set, but not necessarily on the test set. This gives a gap between train and test curves indicative of a degradation in generalization.

For $\beta$ in the range between $10^{-8}$ and $10^{-4}$, we note that for the same level of sufficiency, setting $M = 12$ consistently achieves more compression of the input compared to the setting $M = 1$

(roughly 20 bits less). Moreover, we see that the generalization gap (in the lower left panel) is smaller for larger values of $M$ (our method).

The dynamics of the information quantities during training are also interesting. We provide figures on these in Appendix D.

Figure 3: We trained the VDB on MNIST with the basic encoder given by a fully connected network with two layers of ReLUs producing the means and variance of 2D independent Gaussian latent representation. Ellipses representing the posterior distributions of 1000 input images from in latent space after training with $\beta = 10^0, 10^{-1}, 10^{-3}, 10^{-5}$ and $M = 1, 3, 6, 12$. Color corresponds to the class label.

In order to visualize the representations, we also train the VDB on MNIST with a 2 dimensional representation. Here, we use the same settings as before, with the only difference that the dimension of the output layer of the encoder is 4, with two coordinates representing the mean, and two coordinates representing a diagonal covariance matrix. The results are shown in Figure 3. For $\beta = 10^{-5}$, the representations are well separated, depending on the class. For related figures in the setting of unsupervised learning see Appendix E. The dynamics of the mutual information and the learning curves in terms of classification accuracy are shown in Figure 4. The figure shows that, in terms of classification accuracy, higher values of $M$ (our method) usually lead to better accuracy. An exception is when the number $L$ of posterior samples for classification is very large. These have an interpretation in terms of a phase where the model is fitting the input-output relationship and hence increasing the mutual information $I(Z; Y)$, followed by a compression phase, where $I(Z; X)$ is reduced, leading to a better generalization.

## 5    DISCUSSION

We have formulated a bottleneck method based on channel deficiencies. The deficiency of a decoder with respect to the true channel between the input and output quantifies how well a randomization at the decoder input (by way of stochastic encodings) can be used to simulate the true channel. The VDB has a natural variational formulation, which recovers the VIB in the limit of a single sample

Figure 4: Learning curves for MNIST, where the encoder was a MLP of size 784–1024–1024–$2K$, the last layer being a $K = 2$ dimensional diagonal Gaussian. The decoder was simply a softmax with 10 classes. The left figure plots the mutual information between the representation at the last layer of the encoder and the input, $I(Z; X)$, against the mutual information between representation and the class label, $I(Z; Y)$, as training progresses. The latter increases monotonically, while the former increases and then decreases.

of the encoder output. Experiments demonstrate that the VDB can learn more compressed representations while retaining the same discriminative capacity. The method has a statistical decision-theoretic appeal. The resulting variational objective resembles the VIB and can be implemented as an easy modification of the former, with little to no computational overhead.

Given two channels that convey information about a target variable of interest, two different notions of deficiencies arise depending on whether the target resides at the common input or output of the given channels. When the target is at the common output of the two channels, as is in a typical bottleneck setting (see Figure 1), our Definition 1 has a natural interpretation as a KL-distance from input-Blackwell sufficiency (Nasser, 2017). Here sufficiency is achieved by applying a randomization at the input of the decoder with the goal of simulating the true channel. The notion of input-Blackwell sufficiency contrasts with Blackwell's original notion of sufficiency Blackwell (1953) in the sense that Blackwell's theory compares two channels with a common input. One can again define a notion of deficiency in this setting (see Appendix B for a discussion on deficiencies in the classical Blackwell setup). The associated channels (one from $\mathcal{Y}$ to $\mathcal{Z}$ and the other from $\mathcal{Y}$ to $\mathcal{X}$) do not however have a natural interpretation in a typical bottleneck setting. In contrast, the input-Blackwell setup appears to be much more intuitive in this context. This subtle distinction seems to have largely gone unnoticed in the literature (see e.g. Van Rooyen & Williamson, 2014; van Rooyen & Williamson, 2015).

The more detailed view of information emerging from this analysis explains various effects and opens the door to multiple generalizations. In the spirit of the VDB, one can formulate a VAE as well (see preliminary experiments in the Appendix). On a related note, we mention that the deficiency is a lower bound to a quantity called the *Unique information* (Bertschinger et al., 2014; Banerjee et al., 2018a) (see Appendix C to see a relation with the IB). An alternating minimization algorithm similar in spirit to the classical Blahut-Arimoto algorithm (Blahut, 1972) is proposed in Banerjee et al. (2018b) to compute this quantity. Such an algorithm however, is not feasible in a deep neural network implementation. In the limit $\beta \to 0$, the VDB algorithm gives a means to estimating a lower bound to the unique information from data. This might be of independent interest in improving the practicality of the theory of information decompositions.

# REFERENCES

Alexander A. Alemi, Ian Fischer, Joshua V. Dillon, and Kevin Murphy. Deep variational information bottleneck, 2016. URL http://arxiv.org/abs/1612.00410. ICLR17.

Arindam Banerjee, Srujana Merugu, Inderjit S Dhillon, and Joydeep Ghosh. Clustering with bregman divergences. *Journal of machine learning research*, 6(Oct):1705–1749, 2005.

Pradeep Kr Banerjee, Eckehard Olbrich, Jürgen Jost, and Johannes Rauh. Unique informations and deficiencies. *arXiv preprint arXiv:1807.05103*, 2018a.

Pradeep Kr Banerjee, Johannes Rauh, and Guido Montúfar. Computing the unique information. In *Proc. IEEE ISIT*, pp. 141–145. IEEE, 2018b.

Nils Bertschinger and Johannes Rauh. The blackwell relation defines no lattice. In *Proc. IEEE ISIT*, pp. 2479–2483. IEEE, 2014.

Nils Bertschinger, Johannes Rauh, Eckehard Olbrich, Jürgen Jost, and Nihat Ay. Quantifying unique information. *Entropy*, 16(4):2161–2183, 2014.

David Blackwell. Equivalent comparisons of experiments. *The Annals of Mathematical Statistics*, 24(2):265–272, 1953.

R. Blahut. Computation of channel capacity and rate-distortion functions. *IEEE Transactions on Information Theory*, 18(4):460–473, 1972.

Stéphane Boucheron, Olivier Bousquet, and Gábor Lugosi. Theory of classification: A survey of some recent advances. *ESAIM: probability and statistics*, 9:323–375, 2005.

Matthew Chalk, Olivier Marre, and Gasper Tkacik. Relevant sparse codes with variational information bottleneck. In *Advances in Neural Information Processing Systems*, pp. 1957–1965, 2016.

Imre Csiszár. A class of measures of informativity of observation channels. *Periodica Mathematica Hungarica*, 2(1-4):191–213, 1972.

Imre Csiszár and János Körner. *Information theory: coding theorems for discrete memoryless systems*. Cambridge University Press, 2011.

Imre Csiszár and František Matuš. Information projections revisited. *IEEE Transactions on Information Theory*, 49(6):1474–1490, 2003.

Tilmann Gneiting and Adrian E Raftery. Strictly proper scoring rules, prediction, and estimation. *Journal of the American Statistical Association*, 102(477):359–378, 2007.

David Gondek and Thomas Hofmann. Conditional information bottleneck clustering. In *In 3rd IEEE International Conference on Data Mining, Workshop on Clustering Large Data Sets*, 2003.

Peter D Grünwald, A Philip Dawid, et al. Game theory, maximum entropy, minimum discrepancy and robust bayesian decision theory. *the Annals of Statistics*, 32(4):1367–1433, 2004.

Malte Harder, Christoph Salge, and Daniel Polani. A bivariate measure of redundant information. *Physical Review E*, 87:012130, Jan 2013.

Peter Harremoës and Naftali Tishby. The information bottleneck revisited or how to choose a good distortion measure. In *Proc. IEEE ISIT*, pp. 566–570. IEEE, 2007.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. 2016.

Hsiang Hsu, Shahab Asoodeh, Salman Salamatian, and Flavio P Calmon. Generalizing bottleneck problems. *arXiv preprint arXiv:1802.05861*, 2018.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Artemy Kolchinsky, Brendan D Tracey, and David H Wolpert. Nonlinear information bottleneck. *arXiv preprint arXiv:1705.02436*, 2017.

J. Körner and K. Marton. Comparison of two noisy channels. In *Topics in information theory*, volume 16, pp. 411–423. Colloquia Mathematica Societatis Jnos Bolyai, Keszthely (Hungary), 1975.

L Le Cam. Sufficiency and approximate sufficiency. *The Annals of Mathematical Statistics*, pp. 1419–1455, 1964.

Yann LeCun and Corinna Cortes. MNIST handwritten digit database. 2010. URL `http://yann.lecun.com/exdb/mnist/`.

Friedrich Liese and Igor Vajda. On divergences and informations in statistics and information theory. *IEEE Transactions on Information Theory*, 52(10):4394–4412, 2006.

Rajai Nasser. On the input-degradedness and input-equivalence between channels. In *Proc. IEEE ISIT*, pp. 2453–2457. IEEE, 2017.

Matthew Parry, A Philip Dawid, Steffen Lauritzen, et al. Proper local scoring rules. *The Annals of Statistics*, 40(1):561–592, 2012.

Maxim Raginsky. Shannon meets blackwell and le cam: Channels, codes, and statistical experiments. In *Proc. IEEE ISIT*, pp. 1220–1224. IEEE, 2011.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

Ohad Shamir, Sivan Sabato, and Naftali Tishby. Learning and generalization with the information bottleneck. In *International Conference on Algorithmic Learning Theory*, pp. 92–107. Springer, 2008.

N. Tishby, F. Pereira, and W. Bialek. The information bottleneck method. In *Proceedings of the 37-th Annual Allerton Conference on Communication, Control and Computing*, pp. 368–377, 1999.

Erik Torgersen. *Comparison of statistical experiments*, volume 36. Cambridge University Press, 1991.

Brendan Van Rooyen and Robert C Williamson. Le cam meets lecun: Deficiency and generic feature learning. *arXiv preprint arXiv:1402.4884*, 2014.

Brendan van Rooyen and Robert C Williamson. A theory of feature learning. *arXiv preprint arXiv:1504.00083*, 2015.

Matías Vera, Pablo Piantanida, and Leonardo Rey Vega. The role of information complexity and randomization in representation learning. *arXiv preprint arXiv:1802.05355*, 2018.

H Witsenhausen and A Wyner. A conditional entropy bound for a pair of discrete random variables. *IEEE Transactions on Information Theory*, 21(5):493–501, 1975.

APPENDIX

## A    MISCLASSIFICATION ERROR AND THE AVERAGE LOG-LOSS

In a classification task, the goal is to use the training dataset to learn a classifier $\widehat{\kappa}(y|x)$ that minimizes the *probability of error* under the true data distribution, defined as follows.

$$P_{\mathcal{E}}(\widehat{\kappa}) := 1 - \mathbb{E}_{(x,y)\sim p}\left[\widehat{\kappa}(y|x)\right]. \tag{12}$$

It is well known that the optimal classifier that gives the smallest probability of error is the Bayes classifier (Boucheron et al., 2005). Since we do not know the true data distribution we try to learn based on the empirical error. Directly minimizing the empirical probability of error over the training dataset is in general a NP-hard problem. In practice, one minimizes a surrogate loss function that is a convex upper bound on $P_{\mathcal{E}}$. A natural surrogate is the average log-loss function $\mathbb{E}_{(x,y)\sim p}\left[-\log \widehat{\kappa}(y|x)\right]$. When the model is $\widehat{\kappa} = d \circ e$, the following upper bounds are immediate from using Jensen's inequality.

$$
\begin{aligned}
P_{\mathcal{E}}(\widehat{\kappa}) &\leq 1 - \exp\left(-\mathbb{E}_{(x,y)\sim p}\left[-\log d \circ e(y|x)\right]\right) \\
&\leq 1 - \exp\left(-\mathbb{E}_{(x,y)\sim p}\mathbb{E}_{z\sim e(z|x)}\left[-\log d(y|z)\right]\right)
\end{aligned}
\tag{13}
$$

The bound using the standard cross-entropy loss is evidently weaker than the average log-loss. A lower bound on the probability of error is controlled by a convex functional of the mutual information between the representation and the raw inputs $I(Z;X)$ (Vera et al., 2018, see, e.g., Lemma 4). The average log-loss and the rate term in the VDB objective equation 4 are two fundamental quantities that govern the probability of error.

## B    CLASSICAL THEORY OF COMPARISON OF CHANNELS

In this section, we discuss the classical theory of comparison of channels due to Blackwell (1953) and its extension by Le Cam (1964); Torgersen (1991) and more recently by Raginsky (2011).

Suppose that a learner wishes to predict the value of a random variable $Y$ that takes values in a set $\mathcal{Y}$. She has a set of actions $\mathcal{A}$. Each action incurs a loss $\ell(y,a)$ that depends on the true state $y$ of $Y$ and the chosen action $a$. Let $\pi_Y$ encode the learners' uncertainty about the true state $y$. The tuple $(\pi_Y, \mathcal{A}, \ell)$ is called a *decision problem*. Before choosing her action, the learner observes a random variable $X$ through a *channel* from $\mathcal{Y}$ to $\mathcal{X}$. A channel is simply a family $\{\kappa_y\}_{y\in\mathcal{Y}}$ of probability measures on $\mathcal{X}$, one for each possible input $y \in \mathcal{Y}$. We write $\mathsf{M}(\mathcal{Y};\mathcal{X})$ to denote the space of all channels from $\mathcal{Y}$ to $\mathcal{X}$. An ideal learner chooses a strategy $\rho \in \mathsf{M}(\mathcal{X};\mathcal{A})$ that minimizes her expected loss or *risk* $R(\pi_Y, \kappa, \rho, \ell) := \mathbb{E}_{y\sim\pi_Y}\mathbb{E}_{a\sim\rho\circ\kappa_y}\ell(y,a)$. The *optimal risk* when using the channel $\kappa$ is $R(\pi_Y, \kappa, \ell) := \min_{\rho\in\mathsf{M}(\mathcal{X};\mathcal{A})} R(\pi_Y, \kappa, \rho, \ell)$.

Suppose now that the learner has to choose between $X$ and another random variable $Z$ that she observes through a second channel $\mu \in \mathsf{M}(\mathcal{Y};\mathcal{Z})$ with common input $Y$. She can *always* discard $X$ in favor of $Z$ if, knowing $Z$, she can simulate a single use of $X$ by randomly sampling a $x' \in \mathcal{X}$ after each observation $z \in \mathcal{Z}$.

**Definition 3.** We say that $X$ is *output-degraded* from $Z$ w.r.t. $Y$, denoted $Z \sqsupseteq'_Y X$, if there exists a random variable $X'$ such that the pairs $(Y,X)$ and $(Y,X')$ are stochastically indistinguishable, and $Y - Z - X'$ is a Markov chain.

She can also discard $X$ if her optimal risk when using $Z$ is at most that when using $X$ for any decision problem. Write $Z \sqsupseteq_Y X$ if $R(\pi_Y, \kappa, \ell) \geq R(\pi_Y, \mu, \ell)$ for any decision problem. Blackwell (1953) showed the equivalence of these two relations.

**Theorem 4.** (Blackwell's Theorem) $Z \sqsupseteq'_Y X \iff Z \sqsupseteq_Y X$.

Write $\mu \sqsupseteq_{\mathcal{Y}} \kappa$ if $\kappa = \lambda \circ \mu$ for some $\lambda \in \mathsf{M}(\mathcal{Z};\mathcal{X})$. If $\pi_Y$ has full support, then it easy to check that $\mu \sqsupseteq_{\mathcal{Y}} \kappa \iff Z \sqsupseteq'_Y X$ (Bertschinger & Rauh, 2014, Theorem 4).

The learner can also compare $\kappa$ and $\mu$ by comparing the mutual informations $I(Y;X)$ and $I(Y;Z)$ between the common input $Y$ and the channel outputs $X$ and $Z$.

**Definition 5.** $\mu$ is said to be *more capable* than $\kappa$, denoted $\mu \sqsupseteq^{mc}_{\mathcal{Y}} \kappa$, if $I(Y; Z) \geq I(Y; X)$ for all probability distribution on $\mathcal{Y}$.

It follows from the data processing inequality that $\mu \sqsupseteq_{\mathcal{Y}} \kappa \implies \mu \sqsupseteq^{mc}_{\mathcal{Y}} \kappa$. However, the converse implication is not true in general (Körner & Marton, 1975).

The relation $\sqsupseteq'_Y$ is a preorder on observed variables. In general, one cannot expect two random variables to be comparable in the Blackwell sense, i.e., one can always be simulated by a randomization of the other. The converse to the Blackwell's theorem states that if the relation $Z \sqsupseteq'_Y X$ does not hold, then there exists a set of actions $\mathcal{A}$ and a loss function $\ell(y, a) \in \mathbb{R}^{\mathcal{Y} \times \mathcal{A}}$ such that $R(\pi_Y, \kappa, \ell) < R(\pi_Y, \mu, \ell)$. Le Cam introduced the concept of a *deficiency* of $\mu$ w.r.t. $\kappa$ to express this deficit in optimal risks (Le Cam, 1964) in terms of an approximation of $\kappa$ from $\mu$ via Markov kernels.

**Definition 6.** The *deficiency of $\mu$ w.r.t. $\kappa$* is

$$\delta(\mu, \kappa) := \inf_{\lambda \in \mathsf{M}(\mathcal{Z}; \mathcal{X})} \sup_{y \in \mathcal{Y}} \|\lambda \circ \mu_y - \kappa_y\|_{\mathsf{TV}}, \tag{14}$$

where $\| \cdot \|_{\mathsf{TV}}$ denotes the total variation distance.

When the distribution of the common input to the channels is fixed, one can define a *weighted deficiency* (Torgersen, 1991, Section 6.2).

**Definition 7.** Given $Y \sim \pi_Y$, the *weighted deficiency of $\mu$ w.r.t. $\kappa$* is

$$\delta^\pi(\mu, \kappa) := \inf_{\lambda \in \mathsf{M}(\mathcal{Z}; \mathcal{X})} \mathbb{E}_{y \sim \pi_Y} \|\lambda \circ \mu_y - \kappa_y\|_{\mathsf{TV}}. \tag{15}$$

Le Cam's *randomization criterion* (Le Cam, 1964) shows that deficiencies quantify the maximal gap in the optimal risks of decision problems when using the channel $\mu$ rather than $\kappa$.

**Theorem 8** (Le Cam (1964)). Fix $\mu \in \mathsf{M}(\mathcal{Y}; \mathcal{Z})$, $\kappa \in \mathsf{M}(\mathcal{Y}; \mathcal{Z})$ and a probability distribution $\pi_Y$ on $\mathcal{Y}$ and write $\|\ell\|_\infty = \max_{y,a} \ell(y, a)$. For every $\epsilon > 0$, $\delta^\pi(\mu, \kappa) < \epsilon$ if and only if $R(\pi_Y, \mu, \ell) - R(\pi_Y, \kappa, \ell) < \epsilon \|\ell\|_\infty$ for any set of actions $\mathcal{A}$ and any bounded loss function $\ell$.

Raginsky (2011) introduced a broad class of deficiency-like quantities using the notion of a generalized divergence between probability distributions that satisfies a monotonicity property w.r.t. data processing. The family of $f$-divergences due to Csiszár belongs to this class (Liese & Vajda, 2006).

**Definition 9.** The *$f$-deficiency of $\mu$ w.r.t. $\kappa$* is

$$\delta_f(\mu, \kappa) := \inf_{\lambda \in \mathsf{M}(\mathcal{Z}; \mathcal{X})} \sup_{y \in \mathcal{Y}} D_f(\kappa_y \| \lambda \circ \mu_y), \tag{16}$$

Many common divergences, such as the Kullback-Leibler (KL) divergence, the reverse-KL divergence, and the total variation distance are $f$-divergences. When the channel $\mu$ is such that its output is constant, no matter what the input, the corresponding $f$-deficiency is called $f$-informativity (Csiszár, 1972). The $f$-informativity associated with the KL divergence is just the channel capacity which has a geometric interpretation as an "information radius".

We can also define a weighted $f$-deficiency of $\mu$ w.r.t. $\kappa$.

**Definition 10.** The *weighted $f$-deficiency of $\mu$ w.r.t. $\kappa$* is

$$\delta_f(\mu, \kappa) := \inf_{\lambda \in \mathsf{M}(\mathcal{Z}; \mathcal{X})} D_f(\kappa_y \| \lambda \circ \mu_y | \pi_Y), \tag{17}$$

Specializing to the KL divergence, we have the following definition.

**Definition 11.** The *weighted output deficiency of $\mu$ w.r.t. $\kappa$* is

$$\delta^\pi_o(\mu, \kappa) := \min_{\lambda \in \mathsf{M}(\mathcal{Z}; \mathcal{X})} D_{\mathrm{KL}}(\kappa \| \lambda \circ \mu | \pi_Y), \tag{18}$$

where the subscript $o$ in $\delta^\pi_o$ emphasizes the fact that the randomization is at the *output* of the channel $\mu$.

Note that $\delta^\pi_o(\mu, \kappa) = 0$ if and only if $Z \sqsupseteq'_Y X$, which captures the intuition that if $\delta^\pi_o(\mu, \kappa)$ is small, then $X$ is *approximately output-degraded* from $Z$ w.r.t. $Y$. Using Pinsker's inequality, we have

$$\delta^\pi(\mu, \kappa) \leq \sqrt{\tfrac{\ln(2)}{2} \delta^\pi_o(\mu, \kappa)}. \tag{19}$$

## C   UNIQUE INFORMATION BOTTLENECK

In this section, we give a new perspective on the Information Bottleneck paradigm using nonnegative mutual information decompositions. The quantity we are interested in is the notion of *Unique information* proposed in (Bertschinger et al., 2014). Work in similar vein include (Harder et al., 2013) and more recently (Banerjee et al., 2018a) which gives an operationalization of the unique information.

Consider three random variables $Y$, $X$, and $Z$ with joint distribution $P$. The mutual information between $Y$ and $X$ can be decomposed into information that $X$ has about $Y$ that is *unknown* to $Z$ (we call this the *unique* information of $X$ w.r.t. $Z$) and information that $X$ has about $Y$ that is *known* to $Z$ (we call this the *shared* information).

$$I(Y;X) = \underbrace{\widetilde{UI}(Y;X \backslash Z)}_{\text{unique } X \text{ wrt } Z} + \underbrace{\widetilde{SI}(Y;X,Z)}_{\text{shared (redundant)}}. \tag{20}$$

Conditioning on $Z$ destroys the shared information but creates *complementary* or *synergistic* information from the interaction of $X$ and $Z$.

$$I(Y;X|Z) = \underbrace{\widetilde{UI}(Y;X \backslash Z)}_{\text{unique } X \text{ wrt } Z} + \underbrace{\widetilde{CI}(Y;X,Z)}_{\text{complementary (synergistic)}}. \tag{21}$$

Using the chain rule, the total information that the pair $(X, Z)$ conveys about $Y$ can be decomposed into four terms.

$$I(Y;XZ) = I(Y;X) + I(Y;Z|X) \tag{22}$$
$$= \widetilde{UI}(Y;X \backslash Z) + \widetilde{SI}(Y;X,Z) + \widetilde{UI}(Y;Z \backslash X) + \widetilde{CI}(Y;X,Z). \tag{23}$$

$\widetilde{UI}$, $\widetilde{SI}$, and $\widetilde{CI}$ are nonnegative functions that depend continuously on the joint distribution of $(Y, X, Z)$.

For completeness, we rewrite the information decomposition equations below.

$$I(Y;X) = \widetilde{UI}(Y;X \backslash Z) + \widetilde{SI}(Y;X,Z), \tag{24a}$$
$$I(Y;Z) = \widetilde{UI}(Y;Z \backslash X) + \widetilde{SI}(Y;X,Z), \tag{24b}$$
$$I(Y;X|Z) = \widetilde{UI}(Y;X \backslash Z) + \widetilde{CI}(Y;X,Z), \tag{24c}$$
$$I(Y;Z|X) = \widetilde{UI}(Y;Z \backslash X) + \widetilde{CI}(Y;X,Z), \tag{24d}$$

One can interpret the unique information as either the conditional mutual information without the synergy, or as the mutual information without the redundancy.

When $Y - X - Z$ is a Markov chain, the information decomposition is

$$\widetilde{UI}(Y;Z \backslash X) = 0, \tag{25a}$$
$$\widetilde{UI}(Y;X \backslash Z) = I(Y;X|Z) = I(Y;X) - I(Y;Z), \tag{25b}$$
$$\widetilde{SI}(Y;X,Z) = I(Y;Z), \tag{25c}$$
$$\widetilde{CI}(Y;X,Z) = 0. \tag{25d}$$

The Information bottleneck (Tishby et al., 1999) minimizes the following objective

$$\mathcal{L}_{IB}(e) = I(Y;X|Z) + \beta I(X;Z), \tag{26}$$

over all encoders $e \in \mathsf{M}(\mathcal{X};\mathcal{Z}) : Y - X - Z$. From equation 25b, it follows that one can equivalently write the IB objective function as

$$\mathcal{L}_{IB}(e) = \widetilde{UI}(Y;X \backslash Z) + \beta I(X;Z). \tag{27}$$

From an information decomposition perspective, the original IB is actually minimizing just the unique information subject to a regularization constraint. This is a simple consequence of the fact

that the synergistic information $\widetilde{CI} = 0$ (see equation 25d) when we have the Markov chain condition $Y - X - Z$. Hence, one might equivalently call the original IB as the Unique information bottleneck.

Given $Y - X - Z$, the sufficiency term in the IB objective, $I(Y; X|Z)$ depends only on the pairwise marginals $(Y, X)$ and $(Y, Z)$ and not on the full joint $P$. The minimality term depends on the $(Y, Z)$-marginal. For constructing an approximate sufficient statistic for $X$ w.r.t. $Z$ for $Y$, this dependence on the pairwise marginals avoids complicated synergies and clearly delineates the roles of the sufficiency and minimality terms. Utilizing tools from decision theory, Bertschinger et al. (2014) defined the function $\widetilde{UI}$ based on the idea of approximating one channel from the other by a randomization at the *output*.

**Definition 12.** Let $(Y, X, Z) \sim P$, $Y \sim \pi_Y$ and let $\kappa \in \mathsf{M}(\mathcal{Y}; \mathcal{X})$, $\mu \in \mathsf{M}(\mathcal{Y}; \mathcal{X})$ be two channels with the same input alphabet such that $P_{YX}(y, x) = \pi_Y(y)\kappa_y(x)$ and $P_{YZ}(y, z) = \pi_Y(y)\mu_y(z)$. Define

$$\Delta_P = \big\{ Q \in \mathbb{P}_{\mathcal{Y} \times \mathcal{X} \times \mathcal{Z}} : Q_{YX}(y, x) = \pi_Y(y)\kappa_y(x),$$
$$Q_{YZ}(y, z) = \pi_Y(y)\mu_y(z) \big\}, \tag{28a}$$

$$UI(Y; X \backslash Z) = \min_{Q \in \Delta_P} I_Q(Y; X|Z), \tag{28b}$$

$$UI(Y; Z \backslash X) = \min_{Q \in \Delta_P} I_Q(Y; Z|X), \tag{28c}$$

$$SI(Y; X, Z) = I(Y; X) - UI(Y; X \backslash Z), \tag{28d}$$

$$CI(Y; X, Z) = I(Y; X|Z) - UI(Y; X \backslash Z), \tag{28e}$$

where the subscript $Q$ in $I_Q$ denotes that joint distribution on which the quantities are computed.

The functions $UI$, $SI$ and $CI$ give a nonnegative decomposition of the mutual information $I(Y; XZ)$.

The function $UI$ satisfies the following intuitive property in relation to Blackwell's theorem 4.

**Proposition 13.** (Bertschinger et al., 2014, Lemma 6) $UI(Y; X \backslash Z) = 0 \iff Z \sqsupseteq'_Y X$.

The equivalence in Proposition 2 follows from noting that $\delta^\pi(d, \kappa) = 0 \iff UI(Y; X \backslash Z) = 0$ (Banerjee et al., 2018a, Proposition 28) and the fact that $UI(Y; X \backslash Z) = I(Y; X|Z)$ when $Y - X - Z$ is a Markov chain.

Since in the IB setting, there is no complementary information equation 25, one can choose to minimize either $UI(Y; X \backslash Z)$ which is in fact equal to $I(Y; X|Z)$ (the original IB objective) or minimize the deficiency $\delta^\pi(d, \kappa)$. From the discussion above, it is clear that the results are going to be equivalent only in the limit of *exact sufficiency* since $\delta^\pi(d, \kappa) = 0 \iff I(Y; X|Z) = 0$. In all other cases, we expect to find something (subtly) different from IB. In general, for the bottlenecks, we have:

$$\min_{e(z|x):\, I(Y;X|Z)\leq\epsilon} I(X; Z) \geq \min_{e(z|x):\, \delta^\pi(d,\kappa)\leq\epsilon} I(X; Z). \tag{29}$$

Hence, for achieving the same level of sufficiency, one needs to store less information about the input $X$ when minimizing the deficiencies than when minimizing the conditional mutual information.

## D    ADDITIONAL FIGURES ON VDB EXPERIMENTS

Figure 5: Evolution of mutual information between representation and input vs representation and output over 200 training epochs (dark to light color) on MNIST. The curves are averages over 20 repetitions of the experiment. At early epochs, training mainly effects fitting of the input-output relationship and an increase of $I(Z;Y)$. At later epochs, training mainly effects a decrease of $I(Z;X)$, which corresponds to the representation increasingly discarding information from the input. An exception is when the regularization parameter $\beta$ is very small. In this case the representation captures more information about the input, and longer training decreases $I(Z;Y)$, which is indicative of overfitting to the training data. Higher values of $M$ (our method) lead to the representation capturing more information about the target, while at the same time discarding more information about the input. $M = 1$ corresponds to the Variational Information Bottleneck.

# E UNSUPERVISED REPRESENTATION LEARNING USING THE VDB

In this section, we discuss some preliminary results on an unsupervised version of the VDB objective which bears some resemblance to the $\beta$-VAE (Higgins et al., 2016). The cross entropy loss that appears in an autoencoder is similar to the cross entropy that appears in the information bottleneck. In the same spirit of the VDB, we can formulate a Deficiency Autoencoder. We call the unsupervised version the Variational Deficiency Autoencoder (VDAE).

The VDAE minimizes the following objective over all tuples ($e \in \mathsf{M}(\mathcal{X}; \mathcal{Z}), d \in \mathsf{M}(\mathcal{Z}; \mathcal{Y}), r \in \mathbb{P}_Z$).

$$\mathcal{L}_{VDAE}(e, d, r) := \mathbb{E}_x\left[-\log(d \circ e(x))\right] + \beta\mathbb{E}_x D_{\mathrm{KL}}(e(Z|y)\|r(Z)). \tag{30}$$

The $\beta$-VAE (Higgins et al., 2016) minimizes the following objective over all tuples ($e \in \mathsf{M}(\mathcal{X}; \mathcal{Z}), d \in \mathsf{M}(\mathcal{Z}; \mathcal{Y}), r \in \mathbb{P}_Z$).

$$\mathcal{L}_{VAE}(e, d, r) := \mathbb{E}_x\mathbb{E}_{z \sim e(Z|x)}\left[-\log d(y|z)\right] + \beta\mathbb{E}_x D_{\mathrm{KL}}(e(Z|x)\|r(Z)). \tag{31}$$

We note that the $\beta$-VAE has a similar-looking training objective as the VDAE, with the only difference that the expectation is outside the log.

The next figures show experiments on MNIST. The representations are optically comparable with results obtained in other works via the Variational Autoencoder.

Figure 6: The learned MNIST manifold for the VDAE with $M = 3$. The left part shows the representation (mean values of the posterior) for 5000 test examples. The right shows samples obtained from a grid of values of the latent variable.

$M = 1$         $M = 2$

$M = 3$         $M = 6$

Figure 7: Sampling grids in latent space for the VDAE. These plots show the geometric coherence in latent space of the decoder. The settings are as in Figure 6.