PIRA: Preference-Oriented Instruction-Tuned Reward Models with Dual Aggregation

Abstract

Reward models are crucial for aligning Large Language Models (LLMs) with human preferences but face two representative challenges. First, traditional discriminative reward models usually concatenate questions and responses directly as input, resulting in low data efficiency. Second, reward models are vulnerable to reward overoptimization. We propose **PIRA**, a training paradigm addressing these issues through three strategies: (1) Reformulating question–answer pairs into preference-based instructions for clearer and more explicit task specification, (2) aggregating rewards from diverse preference tasks to reduce bias and improve robustness, and (3) averaging value-head outputs under varying dropout rates to stabilize rewards. Extensive experiments have demonstrated the effectiveness of PIRA.

1 Introduction

Reinforcement Learning from Human Feedback (RLHF) has become a standard approach for aligning large language models (LLMs) with human preferences (Ouyang et al., 2022; Bai et al., 2022). The accuracy and robustness of the reward model directly determine the effectiveness of RLHF (Ouyang et al., 2022; Touvron et al., 2023).

Despite its importance, training reliable reward models remains challenging. On the one hand, discriminative reward models often concatenate questions and answers directly without explicitly modeling the task intent (Dorka, 2024; von Werra et al., 2020; Liu et al., 2024; Havrilla et al., 2023). This underutilizes the instruction-following capabilities of LLMs, leading to inefficient data usage, as the model requires more data to implicitly learn latent task instructions that are not explicitly specified in the prompts. Generative reward models better leverage reasoning abilities and reduce annotation cost, but they introduce high inference latency due to autoregressive generation (Mahan et al., 2024; Zhang et al., 2024). On the other hand, reward models also face the long-standing issue of reward overoptimization. Recent methods such as Thomas (Truong et al.) apply inference-time dropout to capture uncertainty and encourage broader preference exploration, and WARM (Ramé et al., 2024), which averages model weights to improve robustness under distribution shifts.

To address these issues, we propose **PIRA**, which integrates three key strategies: (1) reformulating question–answer pairs into preference-oriented task instructions, (2) averaging rewards across multiple reformulated instructions to reduce bias and improve robustness, and (3) averaging rewards under different dropout rates to stabilize rewards. Experiments on multiple public preference datasets demonstrate that PIRA outperforms traditional discriminative reward models and alleviates reward overoptimization in RLHF pipelines. Furthermore, cross-domain evaluations confirm that PIRA generalizes effectively across out-of-distribution tasks, establishing it as a practical and scalable paradigm for reward modeling.

2 Related work

Reward models can be discriminative, generative, or hybrid. Discriminative models (e.g., ArmoRM (Wang et al., 2024b), HAF-RM (Liu et al., 2024), QRM (Dorka, 2024)) predict scalar rewards from question–answer pairs, while generative models (e.g., GenRM (Mahan et al., 2024), Con-J (Ye et al., 2024)) use LLM reasoning but are slower. Hybrid models like CLoud (Ankner et al., 2024) combine both. Discriminative reward models are more efficient in inference but have lower data utilization.

A main issue is reward overoptimization, where models exploit flaws to gain high scores but lose alignment (Gao et al., 2023). Solutions include keeping policy updates close to preference

data (Moskovitz et al., 2023) and improving model robustness through ensembles or weight averaging (Eisenstein et al., 2023; Coste et al., 2023).

3 PIRA: Methodology

Model decomposition. Let h_θ denote the backbone language model that maps a token sequence z to a representation $u = h_\theta(z)$, and let g_ψ denote a scalar value head that maps u to a reward. The overall reward model is $f_\phi = g_\psi \circ h_\theta$ with parameters $\phi = (\theta, \psi)$.

Preference Instruction Set The Preference Instruction Set ($\mathcal{T} = \{t_1, \ldots, t_K\}$) comprises evaluation instructions generated by a large language model and refined through human review (see Appendix C). Each instruction serves as a holistic rubric for assessing model responses, rather than a list of dimension-specific criteria. Variations in phrasing and emphasis across instructions provide complementary perspectives, leading to a more balanced evaluation. Functionally, $\mathcal{T}$ acts as a generative evaluation prompt for a discriminative reward model. In generative architectures like GPT, this final state integrates prompt and content information, yielding an embedding that effectively supports downstream discriminative or evaluative tasks.

Preference-Oriented Instruction Reformulation Given a question–response pair (x, y) with two possible answers, we denote the preferred response as y^c and the rejected one as y^r. To make the reward model explicitly aware of the preference task, we prepend a task-specific instruction $t \in \mathcal{T}$ to the input, forming

$$r_\phi(x, y \mid t) = f_\phi([t; x; y]) = g_\psi\big(h_\theta([t; x; y])\big).$$

Since the reward head is randomly initialized, it initially lacks any understanding of scoring and must learn preferences entirely from data. The input formulation thus becomes crucial for stable learning. Conventional approaches simply concatenate the question and answer without clarifying that the task involves scoring. As a result, the model must simultaneously learn both the concept of scoring and how to apply it, which increases training difficulty.

Training Objective We train the model using the standard Bradley–Terry objective (Bradley and Terry, 1952). For a preference dataset $\mathcal{D} = (x_i, y_i^c, y_i^r)_{i=1}^N$, the loss function is

$$\mathcal{L}(\phi) = - \sum_{(x_i, y_i^c, y_i^r) \in \mathcal{D}} \log \sigma[r_\phi(x_i, y_i^c \mid t) - r_\phi(x_i, y_i^r \mid t)],$$

where $\sigma(\cdot)$ is the logistic function, and t is randomly sampled from $\mathcal{T}$ for each instance. Dropout is applied to both g_ψ and h_θ.

The backbone h_θ and reward head g_ψ are updated with different learning rates to reflect their distinct roles. Since h_θ already encodes rich linguistic knowledge from pretraining, it is fine-tuned conservatively to maintain stability and avoid catastrophic forgetting. Conversely, g_ψ, a lightweight module, uses a higher learning rate for faster adaptation to preference signals and more effective supervision.

Inference-Time Instruction-Set Reward Averaging Rather than using a single preference instruction to evaluate each sample, PIRA computes rewards by averaging over multiple instructions $\mathcal{T} = \{t_1, \ldots, t_K\}$. For a given (x, y), the aggregated reward is

$$R_{\text{inst}}(x, y) = \frac{1}{K} \sum_{k=1}^K r_\phi(x, y \mid t_k),$$

where $r_\phi(x, y \mid t_k)$ is the reward predicted under instruction t_k. This averaging incorporates diverse evaluative perspectives, reducing prompt-specific bias and enhancing robustness.

Inference-Time Stochastic Value-Head Averaging PIRA improves estimation stability by applying Monte Carlo dropout (Gal and Ghahramani, 2016) only to the value head g_ψ. Unlike standard Monte Carlo dropout with a fixed rate, PIRA varies the dropout rate to strengthen robustness and generalization. Let δ_m denote the m-th dropout rate within g_ψ. For a preference instruction t,

$$r^{(m)}(x, y \mid t) = g_\psi^{(\delta_m)}\big(h_\theta([t; x; y])\big),$$
$$m = 1, \ldots, M.$$

The final reward is the mean of these samples:

$$R_{\text{stoc}}(x, y \mid t) = \frac{1}{M} \sum_{m=1}^M r^{(m)}(x, y \mid t).$$

During inference, h_θ performs a single deterministic forward pass (without dropout), while multiple stochastic passes through g_ψ yield an ensemble estimate at minimal computational cost.

Model	Method	HH	Oasst	SHP	UltraFeedback	Alpaca-farm	HH-cleaned	Average
Mistral-7B-v0.1	Baseline	63.3	72.6	66.9	65.5	57.9	68.1	65.7
	Thomas	63.2	72.0	67.1	66.4	56.7	67.9	65.6
	Thomas*	63.8	**73.6**	69.1	**72.0**	58.8	77.5	69.1
	PIRA	**64.0**	73.3	**70.9**	71.3	**60.4**	**80.4**	**70.1**
LLaMA3-8B	Baseline	61.4	72.0	67.2	67.5	57.6	64.3	65.0
	Thomas	61.7	72.3	68.1	67.0	56.8	64.9	65.1
	Thomas*	64.9	73.5	69.4	**70.5**	59.9	**76.6**	69.1
	PIRA	**66.8**	**75.5**	**70.5**	69.3	**61.2**	75.5	**69.8**
Qwen2.5-1.5B	Baseline	58.6	68.5	64.6	62.6	55.6	62.6	62.1
	Thomas	59.6	67.2	64.2	61.8	56.5	62.6	62.0
	Thomas*	64.3	70.6	66.4	**69.6**	**59.7**	63.0	65.6
	PIRA	**66.0**	**71.5**	**67.0**	68.0	59.6	**64.6**	**66.1**
Qwen2.5-7B	Baseline	60.2	69.2	66.0	64.6	57.4	63.4	63.5
	Thomas	60.4	71.3	65.5	64.9	56.9	65.0	64.0
	Thomas*	64.4	71.9	67.2	70.6	60.6	76.9	68.6
	PIRA	**66.4**	**73.0**	**68.0**	**72.0**	**62.6**	**77.0**	**69.8**

Table 1: Performance comparison across various models and datasets.

Dual aggregation The final reward score is computed as:

$$R(x,y) = \frac{1}{K} \sum_{k=1}^{K} R_{\text{stoc}}(x, y \mid t_k)$$

$$= \frac{1}{K} \sum_{k=1}^{K} \left(\frac{1}{M} \sum_{m=1}^{M} r^{(m)}(x, y \mid t_k) \right).$$

We sample $\delta_m \sim \text{Uniform}(0.1, 0.4)$ and choose small K and M (e.g., $K \leq 6$, $M \leq 12$) to balance stability and efficiency. This two-level averaging—across preference instructions and stochastic value-head realizations—reduces estimator standard deviation, enhances robustness, and mitigates reward overoptimization.

4 Experiments

4.1 Experimental Setup

We conduct experiments with LLaMA3-8B (Dubey et al., 2024), Mistral-7B-v0.1 (Jiang et al., 2023), and Qwen2.5 (1.5B, 7B) (Qwen et al., 2025). Training and evaluation use multiple preference datasets, including HH (Bai et al., 2022), HH-cleaned (Wang et al., 2024a), SHP (Ethayarajh et al., 2022), Alpaca-farm (Dubois et al., 2023), Oasst (Köpf et al., 2023), and UltraFeedback (Cui et al., 2023).

Fine-tuning is performed with LoRA (Hu et al., 2022) (rank 128, $\alpha = 128$, dropout 0.05), applied to query/value projections and the value head. Optimization uses AdamW with batch size 32, 2 epochs, and a 0.05 warm-up ratio. Learning rates are 1×10^{-6} for h_θ and 5×10^{-4} for g_ψ. We set $K = 6$ and $M = 12$.

All experiments run on NVIDIA A800 GPUs, with results averaged over three seeds (42, 22, 33).

4.2 Main Results

Performance Comparison We evaluate PIRA against the baseline and Thomas methods. The baseline employs simple concatenation of questions and answers, and Thomas method performs sampling using different dropout masks (dropout rate = 0.25) with 4 forward passes, as described in Thomas's paper. Thomas* denotes applying preference-oriented instruction reformulation to Thomas, as done in PIRA. As shown in Table 1, PIRA consistently outperforms both baseline and Thomas methods on average.

Reward Hacking Mitigation During PPO training, both the reward and policy models were trained using Qwen2.5-1.5B, while the gold reward model used Qwen2.5-7B. Training employed the Alpaca-farm dataset and used a small KL penalty (0.0005). In baseline PPO runs, we observed sharp spikes in KL divergence and rapid reward inflation (Figure 1 and Figure 2). The gold rewards initially increase but later decline, indicating potential reward hacking. By contrast, PIRA-trained models keep the policy close to the data-supported region: KL divergence remains bounded, reward inflation is suppressed, and gold rewards improve monotonically over training rather than peaking early and collapsing.

Figure 1: Baseline vs. PIRA   Figure 2: Thomas* vs. PIRA   Figure 3: End-to-End Evaluation

Method	K	M	HH-cleaned Acc. ↑	SHP Acc. ↑	Standard Deviation ↓
Baseline	–	–	64.3	67.2	2.1
+ Preference-oriented Task Instruction	–	–	73.0	69.2	1.6
+ Instruction-Set Averaging	4	–	73.9	69.5	1.1
+ Value-Head Stochastic Averaging	4	4	75.1	70.2	0.8
PIRA (both)	**6**	**12**	**75.5**	**70.5**	**0.7**

Table 2: The effects of different parts of PIRA on accuracy and stability.

4.3 Ablation Studies

Joint Effect of Instruction and Stochastic Averaging Using LLaMA3-8B, Table 2 shows that combining instruction-set averaging and value-head stochastic averaging (PIRA; (K=6, M=12)) achieves the best overall results—highest HH-cleaned (75.5) and SHP (70.5) accuracies, and lowest standard deviation (0.7) for HH-cleaned. The preference-oriented task instruction contributes most significantly to PIRA, while instruction-set averaging and value-head stochastic averaging more effectively reduce the standard deviation in predicted rewards.

Impact of Instruction-Set Averaging and Value-Head Stochastic Averaging We examine how varying the number of preference instructions (K) and stochastic forward passes (M) affects LLaMA3-8B's performance. As shown in Table 3 in the Appendix, increasing K from 1 to 6 significantly reduces accuracy standard deviation and consistently improves results. Similarly, Table 4 in the Appendix demonstrates that larger M values enhance both stability and accuracy. Because dropout is applied solely to the lightweight value head, the computational overhead remains minimal—about a 7% latency increase at $M = 12$—confirming that head-only averaging effectively approximates full ensembling with negligible cost.

End-to-End Evaluation We perform pairwise human-like preference evaluations using GPT-4o as the evaluator to assess model alignment quality after RLHF. Each comparison between the PIRA-optimized policy and the reference models (SFT, Baseline, and Thomas*) is repeated three times under randomized prompts. Final win rates are computed via majority voting across evaluation rounds. Results indicate that the PIRA-optimized policy consistently outperforms all baselines (Figure 3).

Data Efficiency and Generalization PIRA demonstrates strong adaptability across varying data conditions, showing notable benefits in low-data scenarios and stable gains as data increases. It also generalizes well across different datasets, maintaining robustness under distribution shifts while revealing response length as a key influencing factor. Detailed results are provided in Appendix A and B.

5 Conclusion

PIRA introduces a simple yet effective framework for building robust reward models. By combining instruction reformulation and dual aggregation, it enhances stability, reduces bias, and mitigates reward overoptimization. Experiments show consistent gains across models and datasets, making PIRA a practical solution for preference-aligned LLM training.

Limitations

PIRA has not yet been evaluated on larger-scale language models, and its scalability to models beyond 8B parameters remains to be investigated. Additionally, value-head stochastic averaging introduces

a slight inference overhead, while instruction-set averaging incurs a more substantial overhead.

References

Zachary Ankner, Mansheej Paul, Brandon Cui, Jonathan D Chang, and Prithviraj Ammanabrolu. 2024. Critique-out-loud reward models. *arXiv preprint arXiv:2408.11791*.

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, and 1 others. 2022. Training a helpful and harmless assistant with reinforcement learning from human feedback. *ArXiv preprint*, abs/2204.05862.

Ralph Allan Bradley and Milton E Terry. 1952. Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, 39(3/4):324–345.

Thomas Coste, Usman Anwar, Robert Kirk, and David Krueger. 2023. Reward model ensembles help mitigate overoptimization. *arXiv preprint arXiv:2310.02743*.

Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Bingxiang He, Wei Zhu, Yuan Ni, Guotong Xie, Ruobing Xie, Yankai Lin, and 1 others. 2023. Ultrafeedback: Boosting language models with scaled ai feedback. *arXiv preprint arXiv:2310.01377*.

Nicolai Dorka. 2024. Quantile regression for distributional reward models in rlhf. *ArXiv preprint*, abs/2409.10164.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Yann Dubois, Chen Xuechen Li, Rohan Taori, Tianyi Zhang, Ishaan Gulrajani, Jimmy Ba, Carlos Guestrin, Percy S Liang, and Tatsunori B Hashimoto. 2023. Alpacafarm: A simulation framework for methods that learn from human feedback. *Advances in Neural Information Processing Systems*, 36:30039–30069.

Jacob Eisenstein, Chirag Nagpal, Alekh Agarwal, Ahmad Beirami, Alex D'Amour, DJ Dvijotham, Adam Fisch, Katherine Heller, Stephen Pfohl, Deepak Ramachandran, and 1 others. 2023. Helping or herding? reward model ensembles mitigate but do not eliminate reward hacking. *arXiv preprint arXiv:2312.09244*.

Kawin Ethayarajh, Yejin Choi, and Swabha Swayamdipta. 2022. Understanding dataset difficulty with $\mathcal{V}$-usable information. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 5988–6008. PMLR.

Yarin Gal and Zoubin Ghahramani. 2016. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pages 1050–1059. PMLR.

Leo Gao, John Schulman, and Jacob Hilton. 2023. Scaling laws for reward model overoptimization. In *International Conference on Machine Learning*, pages 10835–10866. PMLR.

Alexander Havrilla, Maksym Zhuravinskyi, Duy Phung, Aman Tiwari, Jonathan Tow, Stella Biderman, Quentin Anthony, and Louis Castricato. 2023. trlx: A framework for large scale reinforcement learning from human feedback. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 8578–8595.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. Lora: Low-rank adaptation of large language models. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7b. *arXiv preprint arXiv:2310.06825*.

Andreas Köpf, Yannic Kilcher, Dimitri Von Rütte, Sotiris Anagnostidis, Zhi Rui Tam, Keith Stevens, Abdullah Barhoum, Duc Nguyen, Oliver Stanley, Richárd Nagyfi, and 1 others. 2023. Openassistant conversations-democratizing large language model alignment. *Advances in neural information processing systems*, 36:47669–47681.

Shujun Liu, Xiaoyu Shen, Yuhang Lai, Siyuan Wang, Shengbin Yue, Zengfeng Huang, Xuanjing Huang, and Zhongyu Wei. 2024. Haf-rm: A hybrid alignment framework for reward model training. *ArXiv preprint*, abs/2407.04185.

Dakota Mahan, Duy Van Phung, Rafael Rafailov, Chase Blagden, Nathan Lile, Louis Castricato, Jan-Philipp Fränken, Chelsea Finn, and Alon Albalak. 2024. Generative reward models. *ArXiv preprint*, abs/2410.12832.

Ted Moskovitz, Aaditya K Singh, DJ Strouse, Tuomas Sandholm, Ruslan Salakhutdinov, Anca D Dragan, and Stephen McAleer. 2023. Confronting reward model overoptimization with constrained rlhf. *arXiv preprint arXiv:2310.04373*.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, and 25 others. 2025. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

Alexandre Ramé, Nino Vieillard, Léonard Hussenot, Robert Dadashi, Geoffrey Cideron, Olivier Bachem, and Johan Ferret. 2024. Warm: On the benefits of weight averaged reward models. *arXiv preprint arXiv:2401.12187*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, and 1 others. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Sang T Truong, Duc Quang Nguyen, Tho Quan, and Sanmi Koyejo. Thomas: Learning to explore human preference via probabilistic reward model. In *ICML 2023 Workshop The Many Facets of Preference-Based Learning*.

Leandro von Werra, Younes Belkada, Lewis Tunstall, Edward Beeching, Tristan Thrush, Nathan Lambert, Shengyi Huang, Kashif Rasul, and Quentin Gallouédec. 2020. Trl: Transformer reinforcement learning. https://github.com/huggingface/trl.

Binghai Wang, Rui Zheng, Lu Chen, Yan Liu, Shihan Dou, Caishuang Huang, Wei Shen, Senjie Jin, Enyu Zhou, Chenyu Shi, and 1 others. 2024a. Secrets of rlhf in large language models part ii: Reward modeling. *arXiv preprint arXiv:2401.06080*.

Haoxiang Wang, Wei Xiong, Tengyang Xie, Han Zhao, and Tong Zhang. 2024b. Interpretable preferences via multi-objective reward modeling and mixture-of-experts. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 10582–10592, Miami, Florida, USA. Association for Computational Linguistics.

Ziyi Ye, Xiangsheng Li, Qiuchi Li, Qingyao Ai, Yujia Zhou, Wei Shen, Dong Yan, and Yiqun Liu. 2024. Beyond scalar reward model: Learning generative judge from preference data. *ArXiv preprint*, abs/2410.03742.

Lunjun Zhang, Arian Hosseini, Hritik Bansal, Mehran Kazemi, Aviral Kumar, and Rishabh Agarwal. 2024. Generative verifiers: Reward modeling as next-token prediction. *arXiv preprint arXiv:2408.15240*.

A Impact of Data Scale on Model Performance

Figure 4 shows that PIRA yields the largest relative gains in low-data regimes (100–1000 examples). For example, at 500 HH examples, PIRA improves accuracy by +9 over the baseline. With larger datasets ($\geq$ 10k), performance converges but PIRA maintains a consistent margin.

Figure 4: Impact of training data size on model performance: baseline vs. PIRA.

B Cross-Dataset Generalization

We evaluate on OOD test sets to assess robustness. As shown in Figure 5, PIRA consistently outperforms the baseline on Oasst and HH-cleaned, confirming adaptability under distribution shift. Performance degrades on UltraFeedback, whose longer and more complex responses reduce instruction prompt effectiveness. Length-controlled subsets confirm that the drop is largely due to response length, highlighting an area for future work.

Figure 5: Performance improvements achieved by the PIRA method over the baseline across cross-dataset combinations.

C Instructions

The preference task instruction consists of three parts: the preference task instruction description,

K	HH-cleaned Acc. ↑	Standard Deviation ↓
1	73.2	1.8
2	73.6	1.6
4	73.5	1.5
6	74.4	1.2

Table 3: Impact of Instruction-Set Averaging.

M	HH-cleaned Acc. ↑	Standard Deviation ↓	Latency ↑ (%)
1	72.9	1.9	+0
2	72.9	1.8	+2
4	73.7	1.3	+3
8	74.0	1.3	+5
12	74.2	1.0	+7

Table 4: Impact of Value-Head Stochastic Averaging.

represented by t; the question slot, represented by q; and the answer slot, represented by a.

Here is a complete preference instruction template:

Preference Task Instruction Template

$\{t\}$

question:
$\{q\}$

response:
$\{a\}$

The following list enumerates all t values used in the experiment:

1. Evaluate whether the response demonstrates a reliable grasp of facts and reasoning. Consider if any parts appear speculative, misleading, or inconsistent with known information. Provide your overall judgment of its truthfulness.

2. Judge the extent to which the response stays aligned with the user's intent and avoids digressions. Highlight any parts that seem tangential or dilute the main purpose of the answer.

3. Determine whether the response clearly fulfills the user's underlying intent. Focus on how directly and understandably it addresses the core question without overcomplicating or oversimplifying.

4. Assess whether the response demonstrates logical flow, internal consistency, and coherent argumentation. Note if reasoning steps are missing, circular, or contradictory.

5. Evaluate the response's utility for a general user. Does it offer sufficient detail, context, and actionable insight? Consider whether it is understandable to non-experts and avoids unnecessary technical jargon.

6. Examine how well the response justifies its claims. Does it provide reasoning that is sound, evidence-based, and transparent? Identify whether the explanation shows deep understanding or shallow paraphrasing.

7. Assess the clarity, conciseness, and stylistic balance of the response. Is it fluent and engaging while remaining precise? Note both stylistic strengths and weaknesses that affect readability.

8. Reflect on how faithfully the response follows the original instruction while maintaining creative, well-structured expression. Evaluate whether the tone, structure, and style enhance or detract from the intent.

9. Analyze the response critically: what are its major strengths, weaknesses, and possible risks if used in a real context (e.g., misunderstanding, misinformation, or harm)? Offer a short paragraph on each.

10. Provide an overall evaluation of the response's completeness, tone, and coherence. Discuss whether it could be improved, and if so, which aspects—content, logic, or presentation—should be prioritized.