Distributionally Robust Neural Networks for Group Shifts: On the Importance of Regularization for Worst-Case Generalization

Shiori Sagawa[*]
Stanford University
ssagawa@cs.stanford.edu

Pang Wei Koh[*]
Stanford University
pangwei@cs.stanford.edu

Tatsunori B. Hashimoto
Microsoft
tahashim@microsoft.com

Percy Liang
Stanford University
pliang@cs.stanford.edu

Abstract

Overparameterized neural networks can be highly accurate *on average* on an i.i.d. test set, yet consistently fail on atypical groups of the data (e.g., by learning spurious correlations that hold on average but not in such groups). Distributionally robust optimization (DRO) allows us to learn models that instead minimize the *worst-case* training loss over a set of pre-defined groups. However, we find that naively applying group DRO to overparameterized neural networks fails: these models can perfectly fit the training data, and any model with vanishing average training loss also already has vanishing worst-case training loss. Instead, the poor worst-case performance arises from poor *generalization* on some groups. By coupling group DRO models with increased regularization—stronger-than-typical ℓ_2 regularization or early stopping—we achieve substantially higher worst-group accuracies, with 10–40 percentage point improvements on a natural language inference task and two image tasks, while maintaining high average accuracies. Our results suggest that regularization is important for worst-group generalization in the overparameterized regime, even if it is not needed for average generalization. Finally, we introduce a stochastic optimization algorithm for the group DRO setting and provide convergence guarantees for the new algorithm.

1 Introduction

Machine learning models are typically trained to minimize average loss on a training set with the goal of achieving high accuracy on an independent and identically distributed (i.i.d.) test set. However, even models that are highly accurate on average can consistently fail on rare and atypical examples (Hovy & Sgaard, 2015; Blodgett et al., 2016; Tatman, 2017; Hashimoto et al., 2018; Duchi et al., 2019). Such models are problematic when they violate equity considerations (Jurgens et al., 2017; Buolamwini & Gebru, 2018) or rely on *spurious correlations*: misleading heuristics that work for most training examples but do not always hold. For example, in natural language inference (NLI)—determining if two sentences agree or contradict—negation words like 'never' are strongly correlated with contradiction due to artifacts in crowdsourced training data (Gururangan et al., 2018; McCoy et al., 2019). A model could achieve high average accuracy on an i.i.d. test set by learning this spurious correlation, but perform poorly on (sub)groups of data where the correlation does not hold (e.g., the group of contradictory sentences with no negation words).

To avoid the pitfalls of optimizing for average loss—also known as empirical risk minimization (ERM)—we instead optimize for the *worst-case* loss over various groups in the data, using prior knowledge of spurious correlations (e.g., between negation words and contradiction) to choose these groups. This is an instance of distributionally robust optimization (DRO), which optimizes for the worst-case loss over potential test distributions (Ben-Tal et al., 2013; Duchi et al., 2016). Existing

---

[*]Equal contribution.

Figure 1: Representative training and test examples for the datasets we consider. The correlation between the label y and the spurious attribute a at training time does not hold at test time.

work on DRO has focused on models that cannot approach zero training loss, such as generative models (Oren et al., 2019) or convex predictive models with limited capacity (Maurer & Pontil, 2009; Shafieezadeh-Abadeh et al., 2015; Namkoong & Duchi, 2017; Duchi & Namkoong, 2018; Hashimoto et al., 2018).

We study group DRO in the context of overparameterized neural networks in three applications (Figure 1)—natural language inference with the MultiNLI dataset (Williams et al., 2018), facial attribute recognition with CelebA (Liu et al., 2015), and bird photograph recognition with our modified version of the CUB dataset (Wah et al., 2011). The problem with applying DRO to overparameterized models is that if a model can achieve zero training loss, then it will be optimal in both the worst-case (DRO) and the average-case (ERM) settings (Zhang et al., 2017; Wen et al., 2014). In the vanishing-training-loss regime, we find that group DRO models do no better than ERM models: both models have high average test accuracies and worst-group *training* accuracies, but low worst-group *test* accuracies (Section 3.1). This observation suggests that the generalization gap is small on average, but large for the worst group.

In contrast, we show that strongly-regularized group DRO models that do not attain vanishing training loss can significantly outperform regularized and unregularized ERM models. We consider ℓ_2 regularization, early stopping (Section 3.2), and *group adjustments* that minimize a risk measure which accounts for the differences in generalization gaps between groups (Section 3.3). Across the three applications, regularized group DRO improves worst-case test accuracies by 10–40 percentage points while maintaining high average test accuracies. These results give a new perspective on generalization in neural networks: regularization might not be important for good average performance (e.g., models can "train longer and generalize better" on average (Hoffer et al., 2017)) but it appears important for good worst-case performance.

Finally, to carry out the experiments, we introduce a new stochastic optimizer for group DRO that is stable and scales to large models and datasets. We derive convergence guarantees for our algorithm in the convex case and empirically show that it behaves well in our non-convex models (Section 5).

2 SETUP

Consider predicting labels $y \in \mathcal{Y}$ from input features $x \in \mathcal{X}$. Given a model family Θ, loss $\ell : \Theta \times (\mathcal{X} \times \mathcal{Y}) \to \mathbb{R}_+$, and training data drawn from some distribution P, the standard goal is to find a model $\theta \in \Theta$ that minimizes the expected loss $\mathbb{E}_P[\ell(\theta; (x, y)]$ under the same distribution P. The standard training procedure for this goal is empirical risk minimization (ERM):

$$\hat{\theta}_{\text{ERM}} := \underset{\theta \in \Theta}{\arg\min}\ \mathbb{E}_{(x,y) \sim \hat{P}}[\ell(\theta; (x, y))], \qquad (1)$$

where $\hat{P}$ is the empirical distribution over the training data.

In distributionally robust optimization (DRO) (Ben-Tal et al., 2013; Duchi et al., 2016), we aim instead to minimize the worst-case expected loss over an uncertainty set of distributions $\mathcal{Q}$:

$$\min_{\theta \in \Theta}\left\{\mathcal{R}(\theta) := \sup_{Q \in \mathcal{Q}} \mathbb{E}_{(x,y) \sim Q}[\ell(\theta; (x, y))]\right\}. \qquad (2)$$

The uncertainty set $\mathcal{Q}$ encodes the possible test distributions that we want our model to perform well on. Choosing a general family $\mathcal{Q}$, such as a divergence ball around the training distribution P, confers robustness to a wide set of distributional shifts, but this also leads to overly pessimistic models which optimize for implausible worst-case distributions (Duchi et al., 2019).

We thus consider the *group DRO* setting (Hu et al., 2018; Oren et al., 2019) where the training distribution P is assumed to be a mixture of m groups P_g indexed by $\mathcal{G} = \{1, 2, \ldots, m\}$.[1] Further, we assume the mixture weights can differ arbitrarily at train and test time, i.e., $\mathcal{Q} := \{\sum_{g=1}^{m} q_g P_g : q \in \Delta_m\}$, where Δ_m is the $(m-1)$-dimensional probability simplex; this choice of $\mathcal{Q}$ allows us to learn models that are robust to group shifts. Because the optimum of a linear program is attained at a vertex, the worst-case risk (2) is equivalent to a maximum over the expected loss of each group,

$$\mathcal{R}(\theta) = \max_{g \in \mathcal{G}} \mathbb{E}_{(x,y) \sim P_g}[\ell(\theta; (x, y))]. \tag{3}$$

We assume that we know which group each training point comes from—i.e., the training data comprises (x, y, g) triplets—though we do not assume we observe g at test time, so the model cannot use g directly. Instead, we learn a *group DRO* model minimizing the empirical worst-group risk $\hat{\mathcal{R}}(\theta)$:

$$\hat{\theta}_{\text{DRO}} := \arg\min_{\theta \in \Theta} \left\{ \hat{\mathcal{R}}(\theta) := \max_{g \in \mathcal{G}} \mathbb{E}_{(x,y) \sim \hat{P}_g}[\ell(\theta; (x, y))] \right\}, \tag{4}$$

where each group $\hat{P}_g$ is an empirical distribution over all training points (x, y, g') with $g' = g$ (or equivalently, a subset of training examples drawn from P_g). Group DRO learns models with good worst-group *training* loss across groups. This need not imply good worst-group *test* loss because of the *generalization gap* $\delta := \mathcal{R}(\theta) - \hat{\mathcal{R}}(\theta)$. We will show that for overparameterized neural networks, δ is large unless we apply sufficient regularization.

2.1 Applications

In the rest of this paper, we study three applications that share a similar structure (Figure 1): each data point (x, y) has some input attribute $a(x) \in \mathcal{A}$ that is spuriously correlated with the label y, and we use this prior knowledge to form $m = |\mathcal{A}| \times |\mathcal{Y}|$ groups, one for each value of (a, y). We expect that models that learn the correlation between a and y in the training data would do poorly on groups for which the correlation does not hold and hence do worse on the worst-group loss $\mathcal{R}(\theta)$.

Object recognition with correlated backgrounds (Waterbirds dataset). Object recognition models can learn to make predictions from the image background instead of the actual object (Ribeiro et al., 2016). We investigate this by constructing a new dataset, Waterbirds, which combines bird photographs from the Caltech-UCSD Birds-200-2011 (CUB) dataset (Wah et al., 2011) with image backgrounds from the Places dataset (Zhou et al., 2017). We label each bird as one of $\mathcal{Y} = \{\text{waterbird}, \text{landbird}\}$ and place it on one of $\mathcal{A} = \{\text{water background}, \text{land background}\}$, with waterbirds (landbirds) more frequently appearing against a water (land) background (Appendix C.1). There are $n = 4795$ training examples and 56 in the smallest group (waterbirds on land).

Object recognition with correlated demographics (CelebA dataset). Object recognition models (and other ML models more generally) have also been shown to learn spurious associations between the target label and demographic information like gender and ethnicity (Buolamwini & Gebru, 2018). We examine this on the CelebA celebrity face dataset (Liu et al., 2015), using hair color ($\mathcal{Y} = \{\text{blond}, \text{dark}\}$) as the target and gender ($\mathcal{A} = \{\text{male}, \text{female}\}$) as the spurious attribute. There are $n = 162770$ training examples, with 1387 in the smallest group (blond-haired males).

Natural language inference (MultiNLI dataset). In natural language inference, the task is to determine if a given hypothesis is entailed by, neutral with, or contradicts a given premise. Prior work has shown that crowdsourced training datasets for this task have significant annotation artifacts, such as the spurious correlation between contradictions and the presence of the negation words *nobody*, *no*, *never*, and *nothing* (Gururangan et al., 2018). We divide the MultiNLI dataset (Williams et al., 2018) into $m = 6$ groups, one for each pair of labels $\mathcal{Y} = \{\text{entailed}, \text{neutral}, \text{contradictory}\}$

---

[1] In our main experiments, $m = 4$ or 6; we also use $m = 64$ in our supplemental experiments.

and spurious attributes $\mathcal{A} = \{\text{no negation}, \text{negation}\}$. There are $n = 206175$ examples in the training set, with 1521 examples in the smallest group (entailment with negations); we modify the standard MultiNLI split to better estimate accuracy on small groups (Appendix C.1).

3   Comparison between group DRO and ERM

To study the behavior of group DRO vs. ERM in the overparametrized setting, we fine-tuned ResNet50 models (He et al., 2016) on Waterbirds and CelebA and a BERT model (Devlin et al., 2019) on MultiNLI. These are standard models for image classification and natural language inference which achieve high average test accuracies on their respective tasks.

We train the ERM (1) and group DRO (4) models using standard (minibatch) stochastic gradient descent and (minibatch) stochastic algorithm introduced in Section 5, respectively. We tune the learning rate for ERM and use the same setting for DRO (Appendix C.2).

For each model, we measure its *average* (in-distribution) accuracy over training and test sets drawn from the same distribution, as well as its *worst-group* accuracy on the worst-performing group.

3.1   ERM and DRO have poor worst-group accuracy in the overparameterized regime

Overparameterized neural networks can perfectly fit the training data and still generalize well on average (Zhang et al., 2017). We start by investigating if these overparameterized models also generalize well on the worst-case group—i.e., if they attain high *worst-group* test accuracy—after they are trained to convergence using standard hyperparameter settings (He et al., 2016; Devlin et al., 2019).[2]

ERM.   As expected, ERM models attain near-perfect worst-group training accuracies of at least 99.9% on all three datasets and also obtain high average test accuracies (97.3%, 94.8%, and 82.5% on Waterbirds, CelebA, and MultiNLI). However, they perform poorly on the worst-case group at test time with worst-group accuracies of 60.0%, 41.1%, and 65.7% respectively (Table 1, Figure 2). Their low worst-group accuracies imply that these models are brittle under group shifts.

DRO.   In this vanishing-training-loss regime, there exist models that do almost perfectly on both the ERM (1) and DRO (4) objectives. We train group DRO models in the same way as above, and indeed find that they perform similarly to ERM models, attaining near-perfect training accuracies and high average test accuracies, but poor worst-group test accuracies (Table 1, Figure 2).

Discussion.   The ERM and DRO models attain near-perfect training accuracy and vanishing training loss even in the presence of default regularization (batch normalization and ℓ_2 regularization for ResNet50, and dropout for BERT). However, they do *not* generalize well on the worst-case group, and consequently suffer from low worst-group accuracies. This gap between average and worst-group test accuracies arises not from poor worst-group training performance—the models are near-perfect at training time, even on the worst-case groups—but from variations in the generalization gaps across groups. Surprisingly, even though DRO is designed to improve worst-group performance, we find no improvements on worst-group test accuracies since the models already achieve vanishing worst-group losses on the *training* data.

3.2   DRO improves worst-group accuracy under appropriate regularization

Classically, we can control the generalization gap with regularization techniques that constrain the model family's capacity to fit the training data. In the modern overparameterized regime, explicit regularization is not critical for average performance: models can do well on average even when all regularization is removed (Zhang et al., 2017), and default regularization settings (like in the models

---

[2] Training to convergence is a widespread practice for image models (Zhang et al., 2017; Hoffer et al., 2017). Pre-trained language models are typically pretrained until convergence (Devlin et al., 2019; Radford et al., 2019) but fine-tuned for a fixed small number of epochs because average test accuracy levels off quickly; we verified that training to convergence gave equally high average test accuracy.

			Average Accuracy		Worst-Group Accuracy	
			ERM	DRO	ERM	DRO
Standard Regularization	Waterbirds	Train	100.0	100.0	100.0	100.0
		Test	97.3	97.4	60.0	76.9
	CelebA	Train	100.0	100.0	99.9	100.0
		Test	94.8	94.7	41.1	41.1
	MultiNLI	Train	99.9	99.3	99.9	99.0
		Test	82.5	82.0	65.7	66.4
Strong ℓ_2 Regularization	Waterbirds	Train	97.6	99.1	35.7	97.5
		Test	95.7	96.6	21.3	84.6
	CelebA	Train	95.7	95.0	40.4	93.4
		Test	95.8	93.5	37.8	86.7
Early Stopping	Waterbirds	Train	86.2	80.1	7.1	74.2
		Test	93.8	93.2	6.7	86.0
	CelebA	Train	91.3	87.5	14.2	85.1
		Test	94.6	91.8	25.0	88.3
	MultiNLI	Train	91.5	86.1	78.6	83.3
		Test	82.8	81.4	66.0	77.7

Table 1: Average and worst-group accuracies for each training method. Both ERM and DRO models perform poorly on the worst-case group in the absence of regularization (top). With regularization (middle, bottom), DRO achieves high worst-group performance, significantly improving from ERM. Cells are colored by accuracy, from low (red) to medium (white) to high (blue) accuracy.

Figure 2: Training (light) and validation (dark) accuracy for CelebA throughout training. With default hyperparameters and training to convergence, ERM and DRO models achieve perfect training accuracy across groups, but generalize badly on the worst-case group (red line in the left panels). With strong ℓ_2 regularization, ERM models get high average train and test accuracies at the cost of the rare group (panel 3). DRO models achieve high train and test accuracies across groups (panel 4).

trained above) still allow models to perfectly fit the training data. Here, we study if increasing regularization strength—until the models no longer perfectly fit the training data—can rescue worst-case performance. We find that departing from the vanishing-training-loss regime allows DRO models to significantly outperform ERM models on worst-group test accuracy while maintaining high average accuracy. We investigate two types of regularization:

ℓ_2 **regularization.** The default ℓ_2 regularization strength (i.e., the coefficient of the ℓ_2-norm penalty $\lambda\|\theta\|_2^2$) in ResNet50 is $\lambda = 0.0001$ (He et al., 2016). We find that increasing λ by several orders of magnitude—to $\lambda = 1.0$ for Waterbirds and $\lambda = 0.1$ for CelebA—does two things: 1) it prevents both ERM and DRO models from achieving perfect training accuracy, and 2) substantially reduces the generalization gap for each group.

With strong ℓ_2 regularization, both ERM and DRO models still achieve high average test accuracies. However, because no model can achieve perfect training accuracy in this regime, ERM models sacrifice worst-group training accuracy (35.7% and 40.4% on Waterbirds and CelebA; Table 1, Figure 2) and consequently obtain poor worst-group test accuracies (21.3% and 37.8%, respectively).

In contrast, DRO models attain high worst-group training accuracy (97.5% and 93.4% on Waterbirds and CelebA). The small generalization gap in the strong ℓ_2 regularization regime means that high worst-group training accuracy translates to high worst-group test accuracy, which improves over ERM from 21.3% to 84.6% on Waterbirds and from 37.8% to 86.7% on CelebA.

While these results show that strong ℓ_2 regularization has a striking impact on ResNet50 models for Waterbirds and CelebA, our initial experiments did not show a similar effect on BERT model for MultiNLI. ℓ_2 regularization is not typically tuned for this task (Devlin et al., 2019), so we turn to other forms of regularization.

Early stopping. A different, implicit form of regularization is early stopping (Hardt et al., 2016b). We use the same settings in Section 3.1, but only train each model for a fixed (small) number of epochs (Section C.2). As with strong ℓ_2 regularization, curtailing training reduces the generalization gap and prevents models from fitting the data perfectly. In this setting, DRO also does substantially better than ERM on worst-group test accuracy, improving from 6.7% to 86.0% on Waterbirds, 25.0% to 88.3% on CelebA, and 66.0% to 77.7% on MultiNLI. Average test accuracies are comparably high in both ERM and DRO models, though there is a small drop of $1-3\%$ for DRO (Table 1, Figure 2).

Discussion. We conclude that regularization—preventing the model from perfectly fitting the training data—does matter for worst-group accuracy. Specifically, regularization controls the generalization gap for each group, even on the worst-case group. Good worst-group test accuracy then becomes a question of good worst-group training accuracy. Since no model can perfectly fit the training data, ERM and DRO models make different training trade-offs in the regularized regime: ERM models sacrifice worst-group for average training accuracy and do poorly at test time, while DRO models maintain high worst-group training accuracy and therefore do well at test time. Our findings raise questions about the nature of generalization in neural networks, which has been predominantly studied only in the context of average accuracy (Zhang et al., 2017; Hoffer et al., 2017).

3.3 ACCOUNTING FOR GENERALIZATION THROUGH GROUP ADJUSTMENTS IMPROVES DRO

We have optimized thus far for the worst-group *training* loss via DRO (4), relying on regularization to translate good training loss to good test loss by controlling the generalization gap δ. However, even with regularization, the generalization gap varies across groups. Here, we show that we can improve performance by directly optimizing for an estimated upper bound on the worst-group test loss, inspired by ideas from structural risk minimization (Vapnik, 1992). The key consideration is that each group corresponding to g has its own generalization gap $\delta_g = \mathbb{E}_{(x,y)\sim P_g}[\ell(\theta; (x, y))] - \mathbb{E}_{(x,y)\sim \hat{P}_g}[\ell(\theta; (x, y))]$. To approximate optimizing for the worst-group test loss $\mathcal{R}(\theta) = \max_{g\in\mathcal{G}} \mathbb{E}_{(x,y)\sim \hat{P}_g}[\ell(\theta; (x, y))] + \delta_g$, we propose using the simple, parameter-independent heuristic $\hat{\delta}_g = C/\sqrt{n_g}$, where n_g is the group size for g and C is a model capacity constant which we treat as a hyperparameter. This gives the *group-adjusted* DRO estimator

$$\hat{\theta}_{\text{adj}} := \underset{\theta\in\Theta}{\arg\min} \; \underset{g\in\mathcal{G}}{\max} \; \left\{ \mathbb{E}_{(x,y)\sim \hat{P}_g}[\ell(\theta; (x, y))] + \frac{C}{\sqrt{n_g}} \right\}. \tag{5}$$

The scaling with $1/\sqrt{n_g}$ reflects how smaller groups are more prone to overfitting than larger groups, and is inspired by the general size dependence of model-complexity-based generalization bounds (see, e.g., Cao et al. (2019)). Indeed, even in the regularized setting of Section 3.2, different groups g can have significant differences in their generalization gaps δ_g: for example, in the strongly-regularized DRO model, the smallest group in Waterbirds has a train-test worst-group accuracy generalization gap of 15.4% compared to just 1.0% for the largest group. By incorporating group adjustments in (5), we encourage the model to focus more on fitting the smaller groups.

Results. We evaluate group adjustments in the strong-ℓ_2-regularization setting of Section 3.2. In Waterbirds ($\lambda = 1.0$), group adjustments improve worst-group test accuracy by 5.9%, cutting the error rate by more than a third (Table 2 and Figure 3). The improvements in CelebA ($\lambda = 0.1$) are more modest, with worst-group accuracy increasing by 1.1%; ℓ_2 regularization is more effective in CelebA and there is not as much variation in the generalization gaps by group at $\lambda = 0.1$.

Empirically, we find that group adjustments also help in the early stopping setting of Section 3.2 (in the benchmark in the next section, we consider models with group adjustments and early stopping

	Average Accuracy		Worst-Group Accuracy	
	Naïve	Adjusted	Naïve	Adjusted
Waterbirds	96.6	93.7	84.6	90.5
CelebA	93.5	93.4	86.7	87.8

Table 2: Average and worst-group test accuracies with and without group adjustments. Group adjustments improve worst-group accuracy, though average accuracy drops for Waterbirds.

Figure 3: Training (light) and validation (dark) accuracies for each group over training progress, for different values of the adjustment constant C. When $C = 0$, the generalization gap for waterbirds on land (green line) is large, dragging down worst-group accuracy; at $C = 2$ (which has the best worst-group validation accuracy), the accuracies are balanced; and at $C = 4$, we overcompensate for group sizes, so smaller groups (e.g., waterbirds on land) do better at the expense of larger groups (e.g., landbirds on land).

across a grid of ℓ_2 regularization strengths, and report on the one with highest validation accuracy). However, it is difficult to rigorously study the effects of early stopping (e.g., because the group losses have not converged to a stable value), so we leave a more thorough investigation of the interaction between early stopping and group adjustments to future work.

4 COMPARISON BETWEEN DRO AND IMPORTANCE WEIGHTING

Our results above show that strongly-regularized DRO models can be significantly more robust than ERM models. Here, we show theoretically and empirically that DRO also outperforms a strong importance weighting baseline that is commonly used in machine learning tasks where the train and test distributions differ (Shimodaira, 2000; Byrd & Lipton, 2019). Recall that in our setting, the test distribution can be any mixture of the group distributions. For some assignment of weights $w \in \Delta_m$ to groups, an importance-weighted estimator would learn

$$\hat{\theta}_w := \arg\min_{\theta \in \Theta} \; \mathbb{E}_{(x,y,g) \sim \hat{P}}[w_g \, \ell(\theta; (x, y))]. \tag{6}$$

Empirical comparison. We consider an importance-weighted baseline with weights set to the inverse training frequency of each group, $w_g = 1/\mathbb{E}_{g' \sim \hat{P}}[\mathbb{I}(g' = g)]$. This optimizes for a test distribution with uniform group frequencies and is analogous to the common upweighting technique for label shifts (Cui et al., 2019; Cao et al., 2019); intuitively, this attempts to equalize average and worst-group error by upweighting the minority groups. Concretely, we train our weighted model by sampling from each group with equal probability (Shen et al., 2016), since a recent study found this to be more effective than similar reweighting/resampling methods (Buda et al., 2018).

Unlike group DRO, upweighting the minority groups does not necessarily yield uniformly low training losses across groups in practice, as some groups might be easier to fit than others. To compare upweighting (UW) with ERM and DRO, we train models across the same grid of ℓ_2 regularization strengths and early stopping at the epoch with best worst-group validation accuracy (Table 3).[3] In CelebA and Waterbirds, upweighting performs much better than ERM but is slightly outperformed by DRO. However, upweighting fails on MultiNLI, achieving lower average and worst-group accuracies than even ERM. With upweighting, it appears that the rare group is overemphasized and extremely low training accuracy is achieved for that group at the cost of others.

---

[3]To avoid advantaging the DRO models by allowing them to tune additional hyperparameters, we restrict our search for group adjustments to the one ℓ_2 regularization strength used in Section 3.3. See Appendix C.2.

	Average Accuracy			Worst-Group Accuracy		
	ERM	UW	DRO	ERM	UW	DRO
Waterbirds	**97.0 (0.2)**	95.1 (0.3)	93.5 (0.3)	63.7 (1.9)	88.0 (1.3)	**91.4 (1.1)**
CelebA	**94.9 (0.2)**	92.9 (0.2)	92.9 (0.2)	47.8 (3.7)	83.3 (2.8)	**88.9 (2.3)**
MultiNLI	**82.8 (0.1)**	81.2 (0.1)	81.4 (0.1)	66.4 (1.6)	64.8 (1.6)	**77.7 (1.4)**

Table 3: Average and worst-group test accuracies of the models with the best worst-group validation accuracies for ERM, upweighting (UW), and group DRO, with binomial standard deviation in parenthesis. For each objective, we conduct a grid search over ℓ_2 regularization strength, number of epochs, and group adjustments and report the performance of the model with highest validation accuracy. These numbers differ from the previous tables because of the larger grid search.

Figure 4: Toy example illustrating that DRO and importance weighting are not equivalent. The DRO solution is θ^*, while any importance weighting would result in solutions at θ_1 or θ_2.

Theoretical comparison. Should we expect importance weighting to learn models with good worst-case loss? We show that importance weighting and DRO can learn equivalent models in the convex setting under some importance weights, but not necessarily when the models are non-convex.

We analyze the general framework of having weights $w(z)$ for each data point z, which is more powerful than the specific choice above of assigning weights by groups. By minimizing the weighted loss $\mathbb{E}_{z \sim P}[w(z)\ell(\theta; z)]$ over some source distribution P, we can equivalently minimize the expected loss $\mathbb{E}_{z \sim Q}[\ell(\theta; z)]$ over a target distribution Q where $Q(z) \propto w(z)P(z)$.

However, we want good worst-case performance over a family of $Q \in \mathcal{Q}$, instead of a single Q. Are there weights w such that the resulting model $\hat{\theta}_w$ achieves optimal worst-group risk? In the convex regime, standard duality arguments show that this is the case (see Appendix A.1 for the proof):

Proposition 1. *Suppose that the loss $\ell(\cdot; z)$ is continuous and convex for all z in $\mathcal{Z}$, and let the uncertainty set $\mathcal{Q}$ be a set of distributions supported on $\mathcal{Z}$. Assume that $\mathcal{Q}$ and the model family $\Theta \subseteq \mathbb{R}^d$ are convex and compact, and let $\theta^* \in \Theta$ be a minimizer of the worst-group objective $\mathcal{R}(\theta)$. Then there exists a distribution $Q^* \in \mathcal{Q}$ such that $\theta^* \in \arg\min_\theta \mathbb{E}_{z \sim Q^*}[\ell(\theta; z)]$.*

However, this equivalence breaks down when the loss ℓ is non-convex:

Counterexample 1. *Consider a uniform data distribution P supported on two points $\mathcal{Z} = \{z_1, z_2\}$, and let $\ell(\theta; z)$ be as in Figure 4, with $\Theta = [0, 1]$. The DRO solution θ^* achieves a worst-case loss of $\mathcal{R}(\theta^*) = 0.6$. Now consider any weights $(w_1, w_2) \in \Delta_2$ and w.l.o.g. let $w_1 \geq w_2$. The minimizer of the weighted loss $w_1\ell(\theta; z_1) + w_2\ell(\theta; z_2)$ is θ_1, which only attains a worst-case loss of $\mathcal{R}(\theta^*) = 1.0$.*

This negative result implies that in the non-convex setting, there may not be *any* choice of weights w such that the resulting minimizer $\hat{\theta}_w$ is robust. Even if such weights did exist, they depend on θ^* and obtaining these weights requires that we solve a dual DRO problem, making reweighting no easier to implement than DRO. Common choices of weights, such as inverse group size, are heuristics that may not yield robust solutions (as observed for MultiNLI in Table 3).

5 ALGORITHM

To train group DRO models efficiently, we introduce an online optimization algorithm with convergence guarantees. Prior work on group DRO has either used batch optimization algorithms, which do not scale to large datasets, or stochastic optimization algorithms without convergence guarantees.

In the convex and batch case, there is a rich literature on distributionally robust optimization which treats the problem as a standard convex conic program (Ben-Tal et al., 2013; Duchi et al., 2016; Bertsimas et al., 2018; Lam & Zhou, 2015). For general non-convex DRO problems, two types of stochastic optimization methods have been proposed: (i) stochastic gradient descent (SGD) on the Lagrangian dual of the objective (Duchi & Namkoong, 2018; Hashimoto et al., 2018), and (ii) direct minimax optimization (Namkoong & Duchi, 2016). The first approach fails for group DRO because the gradient of the dual objective is difficult to estimate in a stochastic and unbiased manner.[4] An algorithm of the second type has been proposed for group DRO (Oren et al., 2019), but this work does not provide convergence guarantees, and we observed instability in practice under some settings.

Recall that we aim to solve the optimization problem (4), which can be rewritten as

$$\min_{\theta \in \Theta} \sup_{q \in \Delta_m} \sum_{g=1}^{m} q_g \mathbb{E}_{(x,y) \sim P_g} [\ell(\theta; (x,y))]. \tag{7}$$

Extending existing minimax algorithms for DRO (Namkoong & Duchi, 2016; Oren et al., 2019), we interleave gradient-based updates on θ and q. Intuitively, we maintain a distribution q over groups, with high masses on high-loss groups, and update on each example proportionally to the mass on its group. Concretely, we interleave SGD on θ and exponentiated gradient ascent on q (Algorithm 1). The key improvement from the existing group DRO algorithm (Oren et al., 2019) is that q is updated using gradients instead of picking the group with worst average loss at each iteration, which is important for stability and obtaining convergence guarantees. The run time of the algorithm is similar to that of SGD for a given number of epochs (less than a 5% difference), as run time is dominated by the computation of the loss and its gradient.

Algorithm 1: Online optimization algorithm for group DRO

Input: Step sizes η_q, η_θ; P_g for each $g \in \mathcal{G}$
Initialize $\theta^{(0)}$ and $q^{(0)}$
for $t = 1, \dots, T$ **do**
    $g \sim \text{Uniform}(1, \dots, m)$
    $x, y \sim P_g$
    $q' \leftarrow q^{(t-1)}$
    $q'_g \leftarrow q'_g \exp(\eta_q \ell(\theta^{(t-1)}; (x,y)))$
    $q^{(t)} \leftarrow q' / \sum_g q'_g$
    $\theta^{(t)} \leftarrow \theta^{(t-1)} - \eta_\theta q_g^{(t)} \nabla \ell(\theta^{(t-1)}; (x,y))$
end

We analyze the convergence rate by studying the error ε_T of the average iterate $\bar{\theta}^{(1:T)}$:

$$\varepsilon_T = \max_{q \in \Delta_m} L(\bar{\theta}^{(1:T)}, q) - \min_{\theta \in \Theta} \max_{q \in \Delta_m} L(\theta, q), \tag{8}$$

where $L(\theta, q) := \sum_{g=1}^{m} q_g \mathbb{E}_{(x,y) \sim P_g} [\ell(\theta; (x,y))]$ is the expected worst-case loss. Applying results from Nemirovski et al. (2009), we can show that Algorithm 1 has a standard convergence rate of $O(1/\sqrt{T})$ in the convex setting (proof in Section A.2):

Proposition 2. *Suppose that the loss $\ell(\cdot; (x,y))$ is non-negative, convex, B_∇-Lipschitz continuous, and bounded by B_ℓ for all (x,y) in $\mathcal{X} \times \mathcal{Y}$, and $\|\theta\|_2 \leq B_\theta$ for all $\theta \in \Theta$ with convex $\Theta \subseteq \mathbb{R}^d$. Then, the average iterate of Algorithm 1 achieves an expected error at the rate*

$$\mathbb{E}[\varepsilon_T] \leq 2m \sqrt{\frac{10(B_\theta^2 B_\nabla^2 + B_\ell^2 \log m)}{T}}. \tag{9}$$

where the expectation is taken over the randomness of the algorithm.

6 RELATED WORK

The problem of non-uniform accuracy. Other existing approaches to addressing non-uniform accuracy over the data distribution include domain adaptation techniques for *known* target distribu-

---

[4] The dual optimization problem for group DRO is $\min_{\theta, \beta} \frac{1}{\alpha} \mathbb{E}_g [\max(0, \mathbb{E}_{x,y \sim \hat{P}_g} [\ell(\theta; (x,y)) \mid g] - \beta)] + \beta$ for constant α. The max over *expected* loss makes it difficult to obtain an unbiased, stochastic gradient estimate.

tions (Ben-David et al., 2006; Ganin & Lempitsky, 2015) and work in ML fairness (Dwork et al., 2012; Hardt et al., 2016a; Kleinberg et al., 2017). As we discuss in Section 4, importance weighting is a classic example of the former (Shimodaira, 2000). Byrd & Lipton (2019) empirically study importance weighting in neural networks and demonstrate that it has little effect unless regularization is applied. This is consistent with the theoretical analysis in Wen et al. (2014), which points out that weighting has little impact in the zero-loss regime, and with our own observations in the context of DRO.

Distributionally robust optimization. Prior work in DRO typically defines the uncertainty set $\mathcal{Q}$ as a divergence ball around the training distribution over (x, y) (Ben-Tal et al., 2013; Lam & Zhou, 2015; Duchi et al., 2016; Miyato et al., 2018; Esfahani & Kuhn, 2018; Bertsimas et al., 2018; Blanchet & Murthy, 2019). With small divergence balls of radii $O(1/n)$, DRO acts as a regularizer (Shafieezadeh-Abadeh et al., 2015; Namkoong & Duchi, 2017). However, when the radius is larger, the resulting $\mathcal{Q}$ can be too pessimistic. In contrast, group DRO considers $\mathcal{Q}$ that is of wider radius but with fewer degrees of freedom (shifts over groups instead of over (x, y)). Prior work proposed group DRO in the context of label shifts (Hu et al., 2018) and shifts in data sources (Oren et al., 2019). Our work studies group DRO in the overparameterized regime with vanishing training loss and poor worst-case generalization. In contrast, most DRO work has focused on the classic (underparameterized) model setting (Namkoong & Duchi, 2017; Hu et al., 2018; Duchi et al., 2019). Sinha et al. (2018) study neural networks but with a more conservative Wasserstein uncertainty set that leads to non-vanishing training loss; and Oren et al. (2019) study neural networks but for generative modeling where loss tradeoffs arise naturally.

Generalization of robust models. There is extensive work investigating generalization of neural networks in terms of average loss, theoretically and empirically (Hardt et al., 2016b; Szegedy et al., 2016; Hoffer et al., 2017). However, analysis on robust losses is limited. For label shifts, prior work has observed overfitting on rare labels and proposed algorithms to mitigate it (Buda et al., 2018; Cui et al., 2019; Cao et al., 2019). In the DRO literature, generalization bounds on the DRO objective exist for particular uncertainty sets (Duchi & Namkoong, 2018), but these bounds do not apply directly to group DRO . Invariant prediction models from the causal inference literature similarly aim to achieve high performance on a range of test distributions (Peters et al., 2016; Bühlmann & Meinshausen, 2016; Heinze-Deml & Meinshausen, 2017; Rothenhäusler et al., 2018; Yang et al., 2019). The maximin regression framework (Meinshausen & Bühlmann, 2015) also assumes group-based shifts, but focuses on settings without the generalization problems identified in our work.

7 DISCUSSION

In this paper, we analyzed group DRO in overparameterized neural networks and highlighted the importance of regularization for worst-case group generalization. When strongly regularized, group DRO significantly improves worst-group accuracy at a small cost in average accuracy.

As an application, we showed that group DRO can prevent models from learning pre-specified spurious correlations. Our supplemental experiments also suggest that group DRO models can maintain high worst-group accuracy even when groups are imperfectly specified (Appendix B). While handling shifts beyond pre-specified group shifts is important future work, existing work has identified many distributional shifts that can be expressed with pre-specified groups: e.g., batch effects in biology (Leek et al., 2010), or image artifacts (Oakden-Rayner et al., 2019) and patient demographics (Badgeley et al., 2019) in medicine.

More generally, our observations call for a deeper analysis of average vs. worst-case generalization in the overparameterized regime. Such analysis may shed light on the failure modes of deep neural networks as well as provide additional tools (beyond strong ℓ_2 regularization or early stopping) to counter poor worst-case generalization while maintaining high average accuracy.

ACKNOWLEDGMENTS

We are grateful to Shyamal Buch, Yair Carmon, Zhenghao Chen, John Duchi, Jean Feng, Christina Heinze-Deml, Robin Jia, Daphne Koller, Ananya Kumar, Tengyu Ma, Jesse Mu, Hongseok Namkoong, Emma Pierson, and Fanny Yang for helpful discussions and suggestions. This work was funded by an Open Philanthropy Project Award. Toyota Research Institute ("TRI") also provided funds to assist the authors with their research but this article solely reflects the opinions and conclusions of its authors and not TRI or any other Toyota entity. SS was supported by a Stanford Graduate Fellowship and PWK was supported by the Facebook Fellowship Program.

REPRODUCIBILITY

Code for training group DRO models is available at `https://github.com/kohpangwei/group_DRO`. All code, data, and experiments are available on the CodaLab platform at `https://worksheets.codalab.org/worksheets/0x621811fe446b49bb818293bae2ef88c0`.

REFERENCES

M. A. Badgeley, J. R. Zech, L. Oakden-Rayner, B. S. Glicksberg, M. Liu, W. Gale, M. V. McConnell, B. Percha, T. M. Snyder, and J. T. Dudley. Deep learning predicts hip fracture using confounding patient and healthcare variables. *npj Digital Medicine*, 2, 2019.

S. Ben-David, J. Blitzer, K. Crammer, and F. Pereira. Analysis of representations for domain adaptation. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 137–144, 2006.

A. Ben-Tal, D. den Hertog, A. D. Waegenaere, B. Melenberg, and G. Rennen. Robust solutions of optimization problems affected by uncertain probabilities. *Management Science*, 59:341–357, 2013.

D. P. Bertsekas. *Convex Optimization Theory*. Athena Scientific Belmont, 2009.

D. Bertsimas, V. Gupta, and N. Kallus. Data-driven robust optimization. *Mathematical Programming Series A*, 167, 2018.

J. Blanchet and K. Murthy. Quantifying distributional model risk via optimal transport. *Mathematics of Operations Research*, 44(2):565–600, 2019.

S. L. Blodgett, L. Green, and B. O'Connor. Demographic dialectal variation in social media: A case study of African-American English. In *Empirical Methods in Natural Language Processing (EMNLP)*, pp. 1119–1130, 2016.

S. Boyd and L. Vandenberghe. *Convex Optimization*. Cambridge University Press, 2004.

M. Buda, A. Maki, and M. A. Mazurowski. A systematic study of the class imbalance problem in convolutional neural networks. *Neural Networks*, 106:249–259, 2018.

P. Bühlmann and N. Meinshausen. Magging: maximin aggregation for inhomogeneous large-scale data. In *IEEE*, 2016.

J. Buolamwini and T. Gebru. Gender shades: Intersectional accuracy disparities in commercial gender classification. In *Conference on Fairness, Accountability and Transparency*, pp. 77–91, 2018.

J. Byrd and Z. Lipton. What is the effect of importance weighting in deep learning? In *International Conference on Machine Learning (ICML)*, pp. 872–881, 2019.

K. Cao, C. Wei, A. Gaidon, N. Arechiga, and T. Ma. Learning imbalanced datasets with label-distribution-aware margin loss. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

Y. Cui, M. Jia, T. Lin, Y. Song, and S. Belongie. Class-balanced loss based on effective number of samples. In *Computer Vision and Pattern Recognition (CVPR)*, pp. 9268–9277, 2019.

J. Devlin, M. Chang, K. Lee, and K. Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Association for Computational Linguistics (ACL)*, pp. 4171–4186, 2019.

J. Duchi and H. Namkoong. Learning models with uniform performance via distributionally robust optimization. *arXiv preprint arXiv:1810.08750*, 2018.

J. Duchi, P. Glynn, and H. Namkoong. Statistics of robust optimization: A generalized empirical likelihood approach. *arXiv*, 2016.

J. Duchi, T. Hashimoto, and H. Namkoong. Distributionally robust losses against mixture covariate shifts. `https://cs.stanford.edu/~thashim/assets/publications/condrisk.pdf`, 2019.

C. Dwork, M. Hardt, T. Pitassi, O. Reingold, and R. Zemel. Fairness through awareness. In *Innovations in Theoretical Computer Science (ITCS)*, pp. 214–226, 2012.

P. M. Esfahani and D. Kuhn. Data-driven distributionally robust optimization using the wasserstein metric: Performance guarantees and tractable reformulations. *Mathematical Programming*, 171 (1):115–166, 2018.

Y. Ganin and V. Lempitsky. Unsupervised domain adaptation by backpropagation. In *International Conference on Machine Learning (ICML)*, pp. 1180–1189, 2015.

S. Gururangan, S. Swayamdipta, O. Levy, R. Schwartz, S. Bowman, and N. A. Smith. Annotation artifacts in natural language inference data. In *Association for Computational Linguistics (ACL)*, pp. 107–112, 2018.

M. Hardt, E. Price, and N. Srebo. Equality of opportunity in supervised learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 3315–3323, 2016a.

M. Hardt, B. Recht, and Y. Singer. Train faster, generalize better: Stability of stochastic gradient descent. In *International Conference on Machine Learning (ICML)*, pp. 1225–1234, 2016b.

T. B. Hashimoto, M. Srivastava, H. Namkoong, and P. Liang. Fairness without demographics in repeated loss minimization. In *International Conference on Machine Learning (ICML)*, 2018.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Computer Vision and Pattern Recognition (CVPR)*, 2016.

C. Heinze-Deml and N. Meinshausen. Conditional variance penalties and domain shift robustness. *arXiv preprint arXiv:1710.11469*, 2017.

E. Hoffer, I. Hubara, and D. Soudry. Train longer, generalize better: closing the generalization gap in large batch training of neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, pp. 1731–1741, 2017.

D. Hovy and A. Sgaard. Tagging performance correlates with age. In *Association for Computational Linguistics (ACL)*, pp. 483–488, 2015.

W. Hu, G. Niu, I. Sato, and M. Sugiyama. Does distributionally robust supervised learning give robust classifiers? In *International Conference on Machine Learning (ICML)*, 2018.

S. Ioffe and C. Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning (ICML)*, pp. 448–456, 2015.

D. Jurgens, Y. Tsvetkov, and D. Jurafsky. Incorporating dialectal variability for socially equitable language identification. In *Association for Computational Linguistics (ACL)*, pp. 51–57, 2017.

J. Kleinberg, S. Mullainathan, and M. Raghavan. Inherent trade-offs in the fair determination of risk scores. In *Innovations in Theoretical Computer Science (ITCS)*, 2017.

H. Lam and E. Zhou. Quantifying input uncertainty in stochastic optimization. In *2015 Winter Simulation Conference*, 2015.

J. T. Leek, R. B. Scharpf, H. C. Bravo, D. Simcha, B. Langmead, W. E. Johnson, D. Geman, K. Baggerly, and R. A. Irizarry. Tackling the widespread and critical impact of batch effects in high-throughput data. *Nature Reviews Genetics*, 11(10), 2010.

Z. Liu, P. Luo, X. Wang, and X. Tang. Deep learning face attributes in the wild. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 3730–3738, 2015.

A. Maurer and M. Pontil. Empirical bernstein bounds and sample variance penalization. In *Conference on Learning Theory (COLT)*, 2009.

R. T. McCoy, E. Pavlick, and T. Linzen. Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference. In *Association for Computational Linguistics (ACL)*, 2019.

N. Meinshausen and P. Bühlmann. Maximin effects in inhomogeneous large-scale data. *Annals of Statistics*, 43, 2015.

T. Miyato, S. Maeda, S. Ishii, and M. Koyama. Virtual adversarial training: a regularization method for supervised and semi-supervised learning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2018.

H. Namkoong and J. Duchi. Stochastic gradient methods for distributionally robust optimization with f-divergences. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2016.

H. Namkoong and J. Duchi. Variance regularization with convex objectives. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

A. Nemirovski, A. Juditsky, G. Lan, and A. Shapiro. Robust stochastic approximation approach to stochastic programming. *SIAM Journal on optimization*, 19(4):1574–1609, 2009.

L. Oakden-Rayner, J. Dunnmon, G. Carneiro, and C. Ré. Hidden stratification causes clinically meaningful failures in machine learning for medical imaging. *arXiv preprint arXiv:1909.12475*, 2019.

Y. Oren, S. Sagawa, T. Hashimoto, and P. Liang. Distributionally robust language modeling. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

J. Peters, P. Bühlmann, and N. Meinshausen. Causal inference by using invariant prediction: identification and confidence intervals. *Journal of the Royal Statistical Society. Series B (Methodological)*, 78, 2016.

A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, and I. Sutskever. Language models are unsupervised multitask learners. *OpenAI Blog*, 1(8), 2019.

M. T. Ribeiro, S. Singh, and C. Guestrin. "why should I trust you?": Explaining the predictions of any classifier. In *International Conference on Knowledge Discovery and Data Mining (KDD)*, 2016.

D. Rothenhäusler, P. Bühlmann, N. Meinshausen, and J. Peters. Anchor regression: heterogeneous data meets causality. *arXiv preprint arXiv:1801.06229*, 2018.

S. Shafieezadeh-Abadeh, P. M. Esfahani, and D. Kuhn. Distributionally robust logistic regression. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2015.

L. Shen, Z. Lin, and Q. Huang. Relay backpropagation for effective learning of deep convolutional neural networks. In *European Conference on Computer Vision*, pp. 467–482, 2016.

H. Shimodaira. Improving predictive inference under covariate shift by weighting the log-likelihood function. *Journal of Statistical Planning and Inference*, 90:227–244, 2000.

A. Sinha, H. Namkoong, and J. Duchi. Certifiable distributional robustness with principled adversarial training. In *International Conference on Learning Representations (ICLR)*, 2018.

N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov. Dropout: A simple way to prevent neural networks from overfitting. *Journal of Machine Learning Research (JMLR)*, 15(1):1929–1958, 2014.

C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna. Rethinking the Inception architecture for computer vision. In *Computer Vision and Pattern Recognition (CVPR)*, pp. 2818–2826, 2016.

R. Tatman. Gender and dialect bias in youtubes automatic captions. In *Workshop on Ethics in Natural Langauge Processing*, volume 1, pp. 53–59, 2017.

V. Vapnik. Principles of risk minimization for learning theory. In *Advances in Neural Information Processing Systems*, pp. 831–838, 1992.

C. Wah, S. Branson, P. Welinder, P. Perona, and S. Belongie. The Caltech-UCSD Birds-200-2011 dataset. Technical report, California Institute of Technology, 2011.

J. Wen, C. Yu, and R. Greiner. Robust learning under uncertain test distributions: Relating covariate shift to model misspecification. In *International Conference on Machine Learning (ICML)*, pp. 631–639, 2014.

A. Williams, N. Nangia, and S. Bowman. A broad-coverage challenge corpus for sentence understanding through inference. In *Association for Computational Linguistics (ACL)*, pp. 1112–1122, 2018.

F. Yang, Z. Wang, and C. Heinze-Deml. Invariance-inducing regularization using worst-case transformations suffices to boost accuracy and spatial robustness. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

C. Zhang, S. Bengio, M. Hardt, B. Recht, and O. Vinyals. Understanding deep learning requires rethinking generalization. In *International Conference on Learning Representations (ICLR)*, 2017.

B. Zhou, A. Lapedriza, A. Khosla, A. Oliva, and A. Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(6): 1452–1464, 2017.

A PROOFS

A.1 EQUIVALENCE OF DRO AND IMPORTANCE WEIGHTING IN THE CONVEX SETTING

Proposition 1. *Suppose that the loss $\ell(\cdot; z)$ is continuous and convex for all z in $\mathcal{Z}$, and let the uncertainty set $\mathcal{Q}$ be a set of distributions supported on $\mathcal{Z}$. Assume that $\mathcal{Q}$ and the model family $\Theta \subseteq \mathbb{R}^d$ are convex and compact, and let $\theta^* \in \Theta$ be a minimizer of the robust objective $\mathcal{R}(\theta)$. Then there exists a distribution $Q^* \in \mathcal{Q}$ such that $\theta^* \in \arg\min \mathbb{E}_{z \sim Q^*}[\ell(\theta; z)]$.*

Proof. Let $h(\theta, Q) := \mathbb{E}_{Z \sim Q}[\ell(\theta; Z)]$. Since the loss $\ell(\theta; Z)$ is continuous and convex in θ for all Z in $\mathcal{Z}$, we have that $h(\theta, Q)$ is continuous, convex in θ, and concave (linear) in Q. Moreover, since convexity and lower semi-continuity are preserved under arbitrary pointwise suprema, $\sup_{Q \in \mathcal{Q}} h(\theta, Q)$ is also convex and lower semi-continuous (therefore proper).

Together with the compactness of Θ and $\mathcal{Q}$, the above conditions imply (by Weierstrass' theorem, proposition 3.2.1, Bertsekas (2009)), that the optimal value of the DRO objective

$$\inf_{\theta \in \Theta} \mathcal{R}(\theta) = \inf_{\theta \in \Theta} \sup_{Q \in \mathcal{Q}} h(\theta, Q). \tag{10}$$

is attained at some $\theta^* \in \Theta$.

A similar argument implies that the sup-inf objective

$$\sup_{Q \in \mathcal{Q}} \inf_{\theta \in \Theta} h(\theta, Q) \tag{11}$$

attains its optimum at some $Q^* \in \mathcal{Q}$.

Moreover, because Θ and $\mathcal{Q}$ are compact and h is continuous, we have the max-min equality (see, e.g., Ex 5.25 in Boyd & Vandenberghe (2004))

$$\sup_{Q \in \mathcal{Q}} \inf_{\theta \in \Theta} h(\theta, Q) = \inf_{\theta \in \Theta} \sup_{Q \in \mathcal{Q}} h(\theta, Q). \tag{12}$$

Together, the above results imply that (θ^*, Q^*) form a saddle point (proposition 3.4.1, Bertsekas (2009)), that is,

$$\sup_{Q \in \mathcal{Q}} h(\theta^*, Q) = h(\theta^*, Q^*) = \inf_{\theta \in \Theta} h(\theta, Q^*). \tag{13}$$

In particular, the second equality indicates that the optimal DRO model θ^* also minimizes the weighted risk $h(\theta, Q^*) = \mathbb{E}_{Z \sim Q}[\ell(\theta; Z)]$, as desired.

$\square$

A.2 CONVERGENCE RATE OF ALGORITHM 1

Proposition 2. *Suppose that the loss $\ell(\cdot; (x, y))$ is non-negative, convex, B_∇-Lipschitz continuous, and bounded by B_ℓ for all (x, y) in $\mathcal{X} \times \mathcal{Y}$, and $\|\theta\|_2 \leq B_\theta$ for all $\theta \in \Theta$ with convex $\Theta \subseteq \mathbb{R}^d$. Then, the average iterate of Algorithm 1 achieves an expected error at the rate*

$$\mathbb{E}[\varepsilon_T] \leq 2m \sqrt{\frac{10[B_\theta^2 B_\nabla^2 + B_\ell^2 \log m]}{T}}. \tag{14}$$

where the expectation is taken over the randomness of the algorithm.

Proof. Our proof is an application of the regret bound for online mirror descent on saddle point optimization from Nemirovski et al. (2009).

We first introduce the existing theorem. Consider the saddle-point optimization problem

$$\min_{\theta \in \Theta} \max_{q \in \Delta_m} \sum_{g=1}^{m} q_g f_g(\theta) \tag{15}$$

under the following assumptions:

Assumption 1. *f_g is convex on Θ.*

Assumption 2. *$f_g(\theta) = \mathbb{E}_{\xi \sim q}[F_g(\theta; \xi)]$ for some function F_g.*

Assumption 3. *We generate i.i.d. examples $\xi \sim q$. For a given $\theta \in \Theta$ and $\xi \in \Xi$, we can compute $F_g(\theta, \xi)$ and unbiased stochastic subgradient $\nabla F_g(\theta; \xi)$, that is, $\mathbb{E}_{\xi \sim q}[\nabla F_g(\theta; \xi)] = \nabla f_g(\theta)$.*

Online mirror descent with some c-strongly convex norm $\|\cdot\|_\theta$, yielding iterates $\theta^{(1)}, \dots, \theta^{(T)}$ and $q^{(1)}, \dots, q^{(T)}$, has the following guarantee.

Theorem 1 (Nemirovski et al. (2009), Eq 3.23). *Suppose that Assumptions 1-3 hold. Then the pseudo-regret of the average iterates $\bar{q}_g^{(1:T)}$ and $\bar{q}_g^{(1:T)}$ can be bounded as*

$$\mathbb{E}\left[\max_{q \in \Delta_m} \sum_{g=1}^{m} q_g f_g(\bar{\theta}^{(1:T)}) - \min_{\theta \in \Theta} \sum_{g=1}^{m} \bar{q}_g^{(1:T)} f_g(\theta)\right] \leq 2\sqrt{\frac{10[R_\theta^2 M_{*,\theta}^2 + M_{*,q}^2 \log m]}{T}}, \tag{16}$$

where

$$\mathbb{E}\left[\left\|\nabla_\theta \sum_{g=1}^{m} q F_g(\theta; \xi)\right\|_{*,\theta}^2\right] \leq M_{*,\theta} \tag{17}$$

$$\mathbb{E}\left[\left\|\nabla_q \sum_{g=1}^{m} q F_g(\theta; \xi)\right\|_{*,q}^2\right] \leq M_{*,q} \tag{18}$$

$$R_\theta^2 = \frac{1}{c}(\max_\theta \|\theta\|_\theta^2 - \min_\theta \|\theta\|_\theta^2) \tag{19}$$

for online mirror descent with c-strongly convex norm $\|\cdot\|_\theta$.

It remains to formulate our algorithm as an instance of online mirror descent applied to the saddle-point problem above. We start by defining the following:

Definition 1. *Let q be a distribution over $\xi = (x, y, g)$ that is a uniform mixture of individual group distributions P_g:*

$$(x, y, g) \sim q := \frac{1}{m} \sum_{g'=1}^{m} P_{g'}. \tag{20}$$

Definition 2. *Let $F_{g'}(\theta; (x, y, g))) := m\mathbb{I}[g = g']\ell(\theta; (x, y))$. Correspondingly, let $f_{g'} := \mathbb{E}_{P_{g'}}[\ell(\theta; (x, y))]$.*

We now check that Assumptions 1-3 hold under the original assumptions in the statement of Theorem 2:

1. We assume that the loss $\ell(\cdot; (x, y))$ is non-negative, continuous, and convex for all (x, y) in $\mathcal{X} \times \mathcal{Y}$. As a result, $f_g(\theta)$ is non-negative, continuous, and convex on Θ.

2. The expected value of $F_g(\theta)$ over distribution q is $f_g(\theta)$:

$$
\begin{aligned}
\mathbb{E}_{x,y,g\sim q}[F_{g'}(\theta; (x, y, g))] &= \frac{1}{m} \sum_{i=1}^{m} \mathbb{E}_{P_i}[F_{g'}(\theta; (x, y, g)) \mid g = i] \\
&= \frac{1}{m} \mathbb{E}_{P_{g'}}[F_{g'}(\theta; (x, y, g)) \mid g = g'] \\
&= \frac{1}{m} \mathbb{E}_{P_{g'}}[m\ell(\theta; x, y) \mid g = g'] \\
&= \mathbb{E}_{P_{g'}}[\ell(\theta; x, y) \mid g = g'] \\
&= f_{g'}(\theta).
\end{aligned}
$$

3. We can compute an unbiased stochastic subgradient $\nabla F_{g'}(\theta; (x, y, g))$

$$
\begin{aligned}
\mathbb{E}_{x,y,g\sim q}[\nabla F_{g'}(\theta; (x, y, g))] &= \mathbb{E}_{x,y,g\sim q}[\nabla m\mathbb{I}[g = g']\ell(\theta; (x, y))] \\
&= \frac{1}{m} \sum_{i=1}^{m} \mathbb{E}_{P_i}[\nabla m\mathbb{I}[g = g']\ell(\theta; x, y)] \\
&= \mathbb{E}_{Q_{g'}}[\nabla \ell(\theta; (x, y))] \\
&= \nabla f_g(\theta).
\end{aligned}
$$

Finally, we compute the constants required for the regret bound in Theorem 1. Recalling the original assumptions of Theorem 2,

1. Bounded losses: $\ell(\theta; (x, y)) \le B_\ell$ for all x, y, θ

2. Bounded gradients: $\|\nabla \ell(\theta; (x, y))\|_2 \le B_\nabla$ for all θ, x, y

3. Bounded parameter norm: $\|\theta\|_2 \le B_\theta$ for all $\theta \in \Theta$,

we obtain:

$$\mathbb{E}\left[\left\|\nabla_\theta \sum_{g'=1}^{m} q_{g'} F_{g'}(\theta; (x, y, g))\right\|_{*,\theta}^2\right] \le m^2 B_\nabla^2 = M_{*,\theta} \tag{21}$$

$$\mathbb{E}\left[\left\|\nabla_q \sum_{g'=1}^{m} q_{g'} F_{g'}(\theta; (x, y, g))\right\|_{*,q}^2\right] \le m^2 B_\ell^2 = M_{*,q} \tag{22}$$

$$R_\theta^2 = \max_\theta \|\theta\|_\theta^2 - \min_\theta \|\theta\|_\theta^2 = B_\theta^2. \tag{23}$$

Plugging in these constants into the regret bound from Theorem 1, we obtain

$$\mathbb{E}\left[\max_{q \in \Delta_m} \sum_{g=1}^m q_g f_g(\bar{\theta}^{(1:T)}) - \min_{\theta \in \Theta} \sum_{g=1}^m \bar{q}_g^{(1:T)} f_g(\theta)\right] \leq 2m\sqrt{\frac{10[B_\theta^2 B_\nabla^2 + B_\ell^2 \log m]}{T}} \tag{24}$$

This implies Theorem 2 because the minimax game is convex-concave. $\square$

B   Supplementary experiments

Group DRO can maintain high robust accuracy even when spurious attributes are not perfectly specified. We repeat the CelebA experiment on strong ℓ_2 regularization (Section 3.2) but with inexact group specifications:

1. Instead of the ground-truth spurious attribute *Male*, we provide a related attribute *Wearing Lipstick*, and
2. We also specify four distractor/non-spurious attributes (*Eyeglasses*, *Smiling*, *Double Chin*, and *Oval Face*).

Optimizing for worst-case performance over all $2^6 = 64$ groups (for all combinations of 5 attributes and 1 label), the DRO model attains 78.9% robust accuracy across the 4 original groups (dark-haired males and females, and blond males and females). These robust accuracies are not far off from the original DRO model with just the ground-truth spurious attribute (86.7%) and significantly outperform the ERM model (37.8%).

C   Experimental details

C.1   Datasets

MultiNLI.   The standard MultiNLI train-test split allocates most examples (approximately 90%) to the training set, with another 5% as a publicly-available development set and the last 5% as a held-out test set that is only accessible through online competition leaderboards (Williams et al., 2018). To accurately estimate performance on rare groups in the validation and test sets, we combine the training set and development set and then randomly resplit it to a $50 - 20 - 30$ train-val-test split that allocates more examples to the validation and test sets than the standard split.

We use the provided gold labels as the target, removing examples with no consensus gold label (as is standard procedure). We annotate an example as having a negation word if any of the words *nobody*, *no*, *never*, and *nothing* appear in the hypothesis (Gururangan et al., 2018).

Waterbirds.   The CUB dataset (Wah et al., 2011) contains photographs of birds annotated by species as well as and pixel-level segmentation masks of each bird. To construct the Waterbirds dataset, we label each bird as a *waterbird* if it is a seabird (albatross, auklet, cormorant, frigatebird, fulmar, gull, jaeger, kittiwake, pelican, puffin, or tern) or waterfowl (gadwall, grebe, mallard, merganser, guillemot, or Pacific loon). Otherwise, we label it as a *landbird*.

To control the image background, we use the provided pixel-level segmentation masks to crop each bird out from its original background and onto a water background (categories: *ocean* or *natural lake*) or land background (categories: *bamboo forest* or *broadleaf forest*) obtained from the Places dataset (Zhou et al., 2017). In the training set, we place 95% of all waterbirds against a water background and the remaining 5% against a land background. Similarly, 95% of all landbirds are placed against a land background with the remaining 5% against water.

We refer to this combined CUB-Places dataset as the Waterbirds dataset to avoid confusion with the original fine-grained species classification task in the CUB dataset.

We use the official train-test split of the CUB dataset, randomly choosing 20% of the training data to serve as a validation set. For the validation and test sets, we allocate equal numbers of birds to

each of the four groups (i.e., landbirds and waterbirds are uniformly distributed on land and water backgrounds) so as to be able to more accurately measure the performance of the rare groups. This is particularly important for the Waterbirds dataset because of its relatively small size; otherwise, the smaller groups (waterbirds on land and landbirds on water) would have too few samples to accurately estimate performance on. We note that we can only do this for the Waterbirds dataset because we control the generation process; for the other datasets, we cannot generate more samples from the rare groups.

Due to the above procedure, when reporting average test accuracy in our experiments, we calculate the average test accuracy over each group and then report a weighted average, with weights corresponding to the relative proportion of each group in the (skewed) training dataset.

CelebA. We use the official train-val-test split that accompanies the CelebA celebrity face dataset (Liu et al., 2015). We use the *Blond_Hair* attribute as the target label and the *Male* attribute as the spuriously-associated variable.

C.2 MODELS

ResNet50. We use the Pytorch `torchvision` implementation of the ResNet50 model, starting from pretrained weights.

We train the ResNet50 models using stochastic gradient descent with a momentum term of 0.9 and a batch size of 128; the original paper used batch sizes of 128 or 256 depending on the dataset (He et al., 2016). As in the original paper, we used batch normalization (Ioffe & Szegedy, 2015) and no dropout (Srivastava et al., 2014). For simplicity, we train all models without data augmentation.

We use a fixed learning rate instead of the standard adaptive learning rate schedule to make our different model types easier to directly compare, since we expected the scheduler to interact differently with different model types (e.g., due to the different definition of loss). The interaction between batch norm and ℓ_2 regularization means that we had to adjust learning rates for each different setting of ℓ_2 regularization (and each dataset). The learning rates below were chosen to be the highest learning rates that still resulted in stable optimization.

For the standard training experiments in Section 3.1, we use a ℓ_2 regularization strength of $\lambda = 0.0001$ (as in He et al. (2016)) for both Waterbirds and CelebA, with a learning rate of 0.001 for Waterbirds and 0.0001 for CelebA. We train the CelebA models for 50 epochs and the Waterbirds models for 300 epochs.

For the early stopping experiments in Section 3.2, we train each ResNet50 model for 1 epoch. For the strong ℓ_2 regularization experiments in that section, we use $\lambda = 1.0$ for Waterbirds and $\lambda = 0.1$ for CelebA, with both datasets using a learning rate of 0.00001. These settings of λ differ because we found that the lower value was sufficient for controlling overfitting on CelebA but not on Waterbirds.

For the group adjustment experiments in Section 3.3, we use the same settings of $\lambda = 1.0$ for Waterbirds and $\lambda = 0.1$ for CelebA, with both datasets using a learning rate of 0.00001. For both datasets, we use the value of $C \in \{0, 1, 2, 3, 4, 5\}$ found in the benchmark grid search described below.

For the benchmark in Section 4 (Table 3), we grid search over ℓ_2 regularization strengths of $\lambda \in \{0.0001, 0.1, 1.0\}$ for Waterbirds and $\lambda \in \{0.0001, 0.01, 0.1\}$ for CelebA, using the corresponding learning rates for each λ and dataset listed above. (Waterbirds and CelebA at $\lambda = 0.1$, which is not listed above, both use a learning rate of 0.0001.) To avoid advantaging DRO by allowing it to try many more hyperparameters, we only test group adjustments (searching over $C \in \{0, 1, 2, 3, 4, 5\}$) on the ℓ_2 regularization strengths used in Section 3.3, i.e., $\lambda = 1.0$ for Waterbirds and $\lambda = 0.1$ for CelebA. All benchmark models were evaluated at the best early stopping epoch (as measured by robust validation accuracy).

BERT. We use the Hugging Face `pytorch-transformers` implementation of the BERT `bert-base-uncased` model, starting from pretrained weights (Devlin et al., 2019).[5] We use the default tokenizer and model settings from that implementation, including a fixed linearly-decaying

---

[5] https://github.com/huggingface/pytorch-transformers

learning rate starting at 0.00002, AdamW optimizer, dropout, and no ℓ_2 regularization ($\lambda = 0$), except that we use a batch size of 32 (as in Devlin et al. (2019)) instead of 8. We found that this slightly improved robust accuracy across all models and made the optimization less noisy, especially on the ERM model.

For the standard training experiments in Section 3.1, we train for 20 epochs.

For the ℓ_2 regularization experiments in Section 3.2, we tried regularization strengths of $\lambda \in \{0.01, 0.03, 0.1, 0.3, 1.0, 3.0, 10.0\}$. However, these models had similar or worse robust accuracies compared to the default model with no ℓ_2 regularization.

For the early stopping experiments in Section 3.2, we train for 3 epochs, which is the suggested early-stopping time in Devlin et al. (2019).

For the benchmark in Section 4 (Table 3), we similarly trained for 3 epochs. All benchmark models were evaluated at the best early stopping epoch (as measured by robust validation accuracy).