Hierarchical Policy Learning for Long Horizon Interactive Instruction Following

Abstract

Robotic agents performing domestic chores using natural language directives require to learn a complex task of navigating an environment and interacting with objects in it. To address such composite tasks, we propose a hierarchical modular approach to learn agents that navigate and manipulate objects in a divide-and-conquer manner for the diverse nature of the entailing tasks. Specifically, our policy operates at three levels of hierarchy. We first infer a sequence of subgoals to be executed based on language instructions by high-level *policy composition controller* (PCC). We then discriminatively control the agent's navigation by a *master policy* by alternating between navigation policy and various independent interaction policies. Finally, we infer manipulation actions with the corresponding object masks using the appropriate *interaction policy*. Our hierarchical agent, named *HACR (Hierarchical Approach for Compositional Reasoning)*, generates a human interpretable and short sequence of sub-objectives, leading to efficient interaction with an environment, and achieves the state-of-the-art performance on the challenging ALFRED benchmark.

Figure 1: 'Flat policy learning' vs. proposed 'Hierarchical policy learning'. The flat policy learning has been employed in prior arts, training an agent to directly learn the low-level actions. In contrast, our hierarchical policy decomposes a long-horizon task into multiple subtasks and leverages the high-level abstract planning, which enables an agent to better address long-horizon planning.

1 Introduction

For the long-awaited dream of building a robot to assist humans in daily life, we now witness rapid advances in various embodied AI tasks such as visual navigation (Anderson et al., 2018; Chen et al., 2019; Chaplot et al., 2017; Krantz et al., 2020), object interaction (Zhu et al., 2017; Misra

et al., 2017) and interactive reasoning (Das et al., 2018; Gordon et al., 2018). Towards building such realistic robotic assistant, the agent should be capable of all of these tasks to address more complex problems. A typical approach for combining these abilities is to build a unified model (Shridhar et al., 2020; Singh et al., 2021) to jointly perform different sub-tasks. For example, the type of reasoning necessary for navigation differs significantly from the reasoning required for object interaction; the former focuses on inferring the free space and a search strategy to reach a target location while the latter requires detection of objects and inferring their distances and states (Singh et al., 2021). Meanwhile, human cognition process learns to divide a task into sub-objectives such as navigation or interaction, which enables humans to facilitate complex reasoning in a variety of circumstances (Hayes-Roth & Hayes-Roth, 1979). Inspired by those, we propose a hierarchical agent that learns and infers low-level policies for different sub-tasks. To evaluate our proposal in a challenging scenarios, we particularly focus on the task of interactive instruction following, where the goal is to execute a set of navigation and object interaction tasks specified by natural language. This task poses numerous challenges including long-term planning, partial observability, and irreversible state changes. To complete a task successfully, an agent needs to navigate through hundreds of action sequences and interact with various objects in novel environments (*e.g.*, dining room, and kitchen *etc*.) which necessitates a thorough comprehension of both visual scenes and natural language instructions.

Specifically, we propose to disentangle the task into high-level subgoals which are executed by the respective subgoal policies. Our agent is composed of (1) a policy composition controller (PCC) that specifies sub-policy execution sequence, (2) a master policy (MP) that specialises in navigation and provides a signal to conduct interaction tasks, and (3) several interaction policies (IP), which execute autonomous low-level interactions for each subgoal type. This disentanglement results in *human interpretable subtasks* with shorter horizons. This in turn enables parallel computation making training efficient. Additionally, the output of the PCC correspond to semantic sub-objectives that provides a significantly higher interpretability of the agent's execution as compared to directly predicting primitive actions.

There are two main advantages of our design compared to previous hierarchical models for embodied AI tasks; (1) a three level hierarchy that results in better generalisation and interpretability, (2) the agent achieves state of the art performance by a simple imitation learning.

To further improve the task completion performance, we propose an *object encoding module* (OEM) that provides target object information and serves as a navigation subgoal monitor, inspired by visual navigation literature (Yang et al., 2018; Wortsman et al., 2019), that exploits the target object information for action prediction. During navigation to locate an object, the agent faces uncertain obstacles that forces it to traverse in a loop (deadlock state). We additionally propose a loop escape module (LEM) that assist the agent in circumventing such obstacles, based on a stored history of prior visual observations, thus resulting in better navigation.

We summarize our contributions as follows;

- We propose a hierarchical framework that decomposes the instruction following task into semantic subgoals and effectively addresses them with corresponding submodules.
- To further improve the performance, we propose object encoding module (OEM) that encodes object information from natural language instructions for effective navigation and a loop escape module (LEM) to escape a deadlock state with a stochastic policy.
- The proposed agent generates human interpretable action sequences.
- The proposed agent achieves state-of-the-art performance on the ALFRED benchmark.

2 RELATED WORK

Prior works propose numerous task setups and benchmarks for developing an agent to complete complicated tasks given natural language directives, such as agents trained to navigate (Li et al., 2020; Xu et al., 2021) or solve household tasks (Shridhar et al., 2020). However, the vast majority of approaches for these tasks employ a flat reasoning (Singh et al., 2021; Nguyen et al., 2021), in which the agent decides on the low-level actions accessible while moving through the environment (Gupta et al., 2017; Zhu et al., 2020). When the prior arts seek to define subtasks, they are frequently defined in a shallow manner with only one level of hierarchy (Zhang & Chai, 2021; Corona

et al., 2020; Blukis et al., 2021; Andreas et al., 2017; Gordon et al., 2018; Yu et al., 2019; Das et al., 2019). Furthermore, these strategies are inefficient in terms of data requirements. Natural Language is subjective, and even a seemingly simple command can contain several unstated meanings. Because of this semantic gap, most present solutions involve either a large amount of labelled data or trial-and-error learning to map language to low-level actions. Compounding errors also impede performance for activities with a long and complex horizon (Xu et al., 2019). We introduce a system for representing and using hierarchical knowledge in order to better the control of embodied agents doing complex tasks stated in natural language directives. Furthermore, because of the modular structure, our agent reasons and accomplishes tasks along longer paths than previous studies, spanning numerous subgoals.

The task of interactive instruction following necessitates not only navigation but also the interaction with surrounding objects by following natural language directives. (Shridhar et al., 2020) proposed a CNN-LSTM-based baseline agent with progress tracking (Ma et al., 2019). (Singh et al., 2021) offer a modular strategy that factorises perception for mask prediction and policy for action prediction. (Nottingham et al., 2021) offer a modular system in which language encoding, visual state extraction, and action prediction are all trained independently in different modules. (Nguyen et al., 2021) suggested a system for predicting actions and masks corresponding to different instructions independently. They combine numerous visual inputs from navigable directions to provide a larger field of view for improved navigation. (Zhang & Chai, 2021) propose a Transformer-based hierarchical agent whereas (Suglia et al., 2021) present a Transformer-based agent that uses object landmarks for navigation. (Pashevich et al., 2021) present a Transformer-based agent that uses a multimodal Transformer for exploiting the multiple input modalities. (Blukis et al., 2021) propose a technique for successful high-level reasoning by reconstructing a 3D map for encode spatial semantic representation. Finally, a modular policy with a two levels of hierarchy for instruction following have previously been proposed by (Corona et al., 2020) which results in poor generalisation on long-horizon task. In contrast, our policy operates at three hierarchical levels exploiting the fact that navigation and interaction are semantically diverse activities that necessitate independent processing.

3 APPROACH

To address this complex task of long horizon instruction following, we propose to learn policy structure on the fly from a collection of specialised independent modules in a hierarchical fashion. We first analyze each language instruction, and use the information to determine the basic interaction policies required to perform the task. Depending on the underlying composition, the control of the agent is alternated between (1) master policy and (2) various specialised policies for object interaction. Importantly, all interaction policies are composable and independent, which allows formulating an instance specific policy execution sequence. The compositional nature helps us create novel policy compositions that are not seen during training.

Specifically, we design our modular architecture with three levels of hierarchy; (1) A high-level policy composition controller (PCC) that uses language instructions to generate a sequence of subobjectives, (2) a master policy that specialises in navigation and determines when and where the agent is required to perform the interaction task, and (3) an interaction policy that is a collection of subgoal policies that specialises in precise interaction tasks. We require such structure because the PCC improves interpretability by providing semantically meaningful subgoal sequence. Navigation and interaction must be distinguished because the former requires a much broader set of information, such as temporal history and broad perception data, whereas the latter entails object handling, which benefits from succinct and precise language instruction as well as local egocentric vision.

In particular, we learn seven interaction policies, each of which specialises in a different subobjective and can be integrated in a precise order to accomplish long-horizon planning tasks. We illustrate the overview of our proposed agent in Figure 2.

3.1 POLICY COMPOSITION CONTROLLER

The complex task of instruction following necessitates interpretable modules for compositional reasoning. Every task is divided into several meaningful subgoals and detailed instructions are provided for each subgoal. We propose a policy composition controller (PCC), shown in Figure 2

Figure 2: **Model Architecture.** The model architecture comprises of tree main components (1) policy composition controller for defining the policy structure based on the given instructions, (2) a master policy (MP) responsible for navigation, and (3) a set of interaction policies (IP) specialising in the manipulation tasks. I_t^d denotes an RGB frame from an explorable direction, $d \in [0, D]$, at the time step, t where $d = 0$ indicates the egocentric direction. We encode I_t^d using a pretrained ResNet and acquire a visual feature, v_t^d. $\hat{x}_i$ denotes each step-by-step instruction. l_n denotes encoded instructions for each subtask and l_n is attended for each time step, resulting in $\hat{l}_{t,n}, \hat{l}_{t,m}$, and $\hat{l}_{t,v}$. In our master policy, OEM outputs object encoding, o_t, using $\hat{l}_{t,n}$. 'VL-Ground' uses dynamic filters to capture the correspondence between visual and language features and outputs attended visual features, $\hat{v}_t^{pan}$ and $\hat{v}_t^{ego}$.

which generates a sequence of subgoals $\mathcal{S} = s_i$ for the given 'step-by-step' instructions. The PCC's predictions correlate to semantic subgoals, subjecting the agent's logic to observation ('What is the agent attempting to accomplish right now?') in a more interpretable way than the low-level actions. Specifically, we use a Bi-LSTM to encode the language instructions, which is followed by a self-attention module. We use the encoded step-by-step language instructions $\hat{x}_i$ as an input to the PCC to generate the subgoal sequences. The agent must complete these subgoals in the order specified by PCC to accomplish the goal task. Formally, given the language instruction $\hat{x}_i$, the PCC defines a distribution over the subgoal space as:

$$s_i = \arg\max_k (FC_1(\hat{x}_i)), \quad \text{where } k \in [1, N_{subgoals}], \tag{1}$$

where FC_1 denotes a single layer perceptron, and $N_{subgoals}$ denotes the number of subgoals *i.e.* 7. We train the PCC module in a supervised manner with the associated subgoal labels. On the ALFRED validation set, the controller achieves 98.5% accuracy.

3.2 MASTER POLICY

We observed that the agent does not require information about the interactions it must perform for the given task when navigating in an environment. We require the agent to learn how to move from one interaction location to another with the help of language instruction. This necessitates an independent module that can perform navigation while simultaneously mark the locations for object interaction along the way. For the task, we propose a master policy, which is illustrated by the upper-right block in Figure 2, for generating the navigational action sequence based on the multi-modal inputs. Let $\mathcal{A}_n$ denote the set of primitive navigation actions {MoveAhead, RotateRight, RotateLeft, LookUp, LookDown}. The master policy learns to navigate in the environment by learning a distribution over $\mathcal{A}_n \cup$ <MANIPULATE>, where <MANIPULATE> is the abstract token we introduced for the agent to signify when to move control to the next level of hierarchy, *i.e.*, the interaction policies, for completing manipulation sub-tasks. The master policy comprises of three basic modules: (1) an *object encoding module* that provides information about the object the agent needs to locate for interaction. (2) a navigation policy that outputs the navigation action sequence based on the multi-modal input for traversing the environment. (3) a loop escape module that helps the agent in escaping deadlock states.

3.2.1 SUBTASK LANGUAGE COMBINATION

For better utilization of language information, we propose a novel combination of the language instructions. Specifically, a subtask is a combination of 'navigation to discover the relevant object'

and the 'corresponding interactions'. For instance, in the subtask *Turn around and walk forward to the garbage bin on the floor by the TV. Pick up the blue credit card on the TV stand.*, the agent needs to interact with the credit card, which is a crucial information for the agent and also serves as a navigational criterion, *i.e.*, the agent should stop if it encounters the credit card in close vicinity. This information is missing in the first navigation command, but is present in the second interaction instruction. The navigation instruction provides the low-level information about the path to be traversed and the interaction instruction provides information about the object the agent needs to locate for appropriate interaction. We encode these instructions using an instruction encoder comprised of a Bi-directional LSTM followed by a self attention module. $L = \{l_n\}$ denotes the collection of encoded language subtask features.

3.2.2 OBJECT ENCODING MODULE

The task of instruction following can be broken down into two components, according to our observations: 1) locating the required object, and 2) interacting with the object. We propose a module that takes as input the subtask language instruction l_n and outputs an encoding for the object the agent must locate for interaction. This guides the agent's navigation, and we recommend using it as a subgoal monitor to signify the completion of the current navigation subgoal.

Navigation Subgoal Monitor. The master policy learns to output an abstract token <MANIPULATE> along its navigation route, which passes control to a pretrained object detector (Mask RCNN) that validates whether the object provided by the OEM is present in the current frame or not. If the agent discovers the item, it switches to the appropriate interaction policy; otherwise, it continues with the navigation. The object encoder is composed of a Bi-LSTM, followed by a two layer perceptron which outputs the object class. For this object, the master policy utilises a learnable 100-dimensional embedding as input, as demonstrated in Eq. 2.

3.2.3 NAVIGATION POLICY

The navigation policy $\prod_n$ receives the processed multi-modal data as input and produces a sequence of actions as output. The architecture is based on the action prediction module of (Singh et al., 2021). It uses visual features, subtask instruction features (Sec. 3.2.1), and the embedding of the preceding time step action as inputs. Moreover, the object encoding supplied by the *object encoding module* (Sec. 3.2.2) is provided as input in order to further enhance the navigation capabilities of the agent.

The subtask instruction encoding l_n provides low-level information relevant for navigation as well as the information about the object that the agent needs to interact with. This aids the agent in arriving at the correct location. To capture the relationship between the visual observation and language instructions, we dynamically generate filters based on the attended language features and convolve visual features with the filters, denoted by "VL-Ground" in Figure 2. To summarise, the LSTM hidden state $h_{t,n}$ of the master policy decoder, LSTM$_n$, is updated with four different features concatenated together as:

$$
\begin{aligned}
o_t &= \underset{k'}{\operatorname{argmax}}(\text{FC}_o(\hat{l}_{t,n})) \quad where \; k' \in [1, N_{objects}] \\
h_{t,n} &= \text{LSTM}_n([\hat{v}_t^{pan}; \; \hat{l}_{t,n}; \; a_{t-1,n}; \; o_t]) \\
a_{t,n} &= \underset{k}{\operatorname{argmax}}(\text{FC}_n([\hat{v}_t^{pan}; \hat{l}_{t,n}; a_{t-1,n}; o_t; h_{t,n}])) \quad where \; k \in [1, |\mathcal{A}_n| + 1]
\end{aligned}
\tag{2}
$$

where $\hat{v}_t^{pan}$ denotes the attended visual features for the surrounding view as explained in Sec. A.2 in Appendix at time step t, $\hat{l}_{t,n}$ denotes the attended subtask language features, $a_{t-1,n}$ represents the action given by $\prod_n$ in the previous time step, and o_t denotes the object encoding given by the *object encoding module*. In addition, we use the subgoal progress and overall progress monitors similar to (Shridhar et al., 2020) for training the navigation policy. Details about the surrounding views is given in Sec. A.2 in the Appendix.

3.2.4 LOOP ESCAPE MODULE

While navigating through an environment, the agent is prone to be caught around unanticipated obstructions such as tables or chairs, which might cause navigation failure. To circumvent such

(a) Deadlock State   (b) Loop Escape Module

Figure 3: **Loop Escape Module.** The objective of the agent at the current time step is to move to a target object (a garbage can). (a) and (b) show an example of a deadlock state and the behavior of loop escape module when finding the target object, respectively. Each dark-blue square denotes the position of the agent. ∘ denotes the target object that the agent should navigate to. → denotes the view direction of the agent. The dashed ∘ and → indicate that the target object is invisible to the agent due to occlusion. → denotes actions taken by the agent a path taken in a deadlock state. In a deadlock state, the loop escape module cancels the current action that results in the deadlock state, ×, and takes a random navigation action, →.

obstructions during navigation, (Singh et al., 2021) introduced obstruction evasion (OE). However, in the scenario where the agent predicts a repeated series of activities (i.e., a deadlock state), the agent may fail to navigate even without such barriers, resulting in limited exploration. The OE mechanism is unable to handle such challenges since repeated sequences of visual observations might not be recognised as obstacles based on visual similarity in consecutive frames. To address the problem, we propose a loop escape module, which allows for improved exploration at inference time by avoiding deadlock conditions. We use an external memory to memorise the history of visual observations, inspired by (Du et al., 2020). The agent identifies a deadlock state if any t' exists that satisfies Equation 3, given a history of visual observations, $v_{0:t}$, up to the present time step, t.

$$v_{t'+w} = v_{t+w-W}, \quad \forall w \in [1, W], \tag{3}$$

where W is a hyperparameter that indicates the length of the repeated actions. In the event of a deadlock, the stochastic policy executes a random navigation action to assist the agent in escaping.

Figure 3 depicts an example of a deadlock state and the behaviour of loop escape module in the case when the agent is unable to find a target object (a garbage can) due to occlusion (by the counter-top). As shown in Figure 3(a), the agent in a deadlock state tries to revisit previously explored areas, which may limit exploration. Loop escape module assists the agent in escaping the impasse condition, thus finding the garbage can, as depicted in Figure 3(b).

3.3 INTERACTION POLICIES

To abstract a visual observation to a consequent action, the agent necessitates a global scene-level comprehension of the visual observation whereas for localisation task, the agent must focus on both global as well local object specific information. Inspired by (Singh et al., 2021), we exploit separate streams for action prediction and object localization due to the contrasting nature of the two tasks, illustrated as 'Interaction Policy$_k$' in Figure 2.

The task require execution of varied subgoals with different levels of complexity. For instance, *Heat Subgoal* might require interaction with either a stove or a microwave whereas for *Pickup Subgoal* there is a variety of receptibles but the action sequence is simpler. To focus on individual sub-objectives, we train a module, $\prod_{m,k}$, for each subgoal where $k \in [1, N_{subgoals}]$. We observed that each interaction has its own properties and the navigation information history is irrelevant to the task that makes it necessary to use an isolated hidden state for each interaction subgoal. More details about the architecture can be found in Sec. A.1 in the Appendix.

Model	Validation				Test			
	Seen		*Unseen*		*Seen*		*Unseen*	
	Task	GC	Task	GC	Task	GC	Task	GC
Seq2Seq (Shridhar et al., 2020)	3.70	10.00	0.00	6.90	3.98	9.42	0.39	7.03
LAV (Nottingham et al., 2021)	12.70	23.40	-	-	13.35	23.21	6.38	17.27
FPP (Singh et al., 2021)	25.85	34.92	5.36	16.18	26.81	33.20	7.65	15.73
EmBERT (Suglia et al., 2021)	37.44	44.62	5.73	15.91	31.77	39.27	7.52	16.33
E.T. (Pashevich et al., 2021)	33.78	42.48	3.17	13.12	28.77	36.47	5.04	15.01
E.T. + synth. data (Pashevich et al., 2021)	**46.59**	52.82	7.32	20.87	38.42	45.44	8.57	18.56
LWIT (Nguyen et al., 2021)	33.70	43.10	9.70	23.10	30.92	40.53	9.42	20.91
HiTUT (Zhang & Chai, 2021)	25.24	34.85	12.44	23.71	21.27	29.97	13.87	20.31
HLSM (Blukis et al., 2021)	25.00	36.37	11.80	24.70	25.11	35.79	16.29	**27.24**
HACR (Ours)	46.09	**54.69**	**20.09**	**38.41**	**40.66**	**47.62**	**16.70**	26.17

Table 1: **Task and Goal-Condition Success Rate.** We provide the highest values corresponding to each fold and each metric in **blue**.

4 RESULTS AND DISCUSSION

First, we carry out a quantitative analysis of task success (Success Rate or SR) and goal condition success rates (Goal Condition or GC), and summarize the findings with prior approaches in Table 1. HACR outperforms the preceding approaches on all metrics, as indicated in the table. Its ability to generalise in unknown situations is evidenced by its increased success rate in unseen environments. For the validation fold, HACR outperforms the state-of-the-art (Blukis et al., 2021) with an improvement of 84.36 % in seen task SR, and 70.25 % in unseen task SR. For the test fold, HACR shows an improvement of 61.92 % in seen SR, and 2.5 % in in unseen SR. It indicates that our approach enhances the agent's overall grasp of all sub-tasks and their connection needed to complete a task successfully. We also discuss performance over individual subgoals in Table 5 in Appendix.

4.1 COMPARISON BETWEEN HIERARCHICAL AND FLAT POLICY AGENTS

We present the analysis of the learning process for the hierarchical and flat policy agents for seen and unseen environments. The performance of our hierarchical agent and the flat agent are compared quantitatively in relation to the number of iterations (expressed in terms of epochs), and the results are presented in Figure 4. As shown, hierarchical policy gives a major improvement over the flat policy. Its ability to generalise in novel environments is evidenced by its increased success rate in unseen scenes. In seen and unseen task SR, the hierarchical agent outperforms the flat policy by 9.6% and 48.6%, respectively. In both seen and unseen 'Goal-Condition' metrics, the hierarchical approach outperforms, with improvements of 8.2% and 28.0%, respectively. The greater performance of the hierarchical approach on both overall task success rate and goal condition suggests its comprehension of both short-term subtasks and long-horizon whole tasks.

Also, the hierarchical agent approach convergences significantly sooner than the monolithic agent (25th epoch vs 37th epoch), as shown in Figure 4a, demonstrating the computation-efficiency of our approach. Our policies go through two stages of training. We start by training the seven interaction policies, which collectively take two epochs to converge. We included them in the computation and began the hierarchical curve from the third epoch, which is the first epoch of our master policy.

Figure 4b represents the average length of a successful trajectory traversed by the hierarchical or flat policy agent, contrasting the efficiency of each agent. The hierarchical agent consist of the master policy that is dedicated solely to navigation, giving it a significant advantage over the flat policy agent that learns everything using the same network parameters. It was observed that due to the wide action space, the flat policy agent occasionally executes irrelevant interactions along the trajectory, which is not the case with HACR. The dedicated action sets for the master policy and interaction policies improve HACR by allowing the agent to avoid any unnecessary interactions while traversing to discover the desired object. The interaction policy modules also perform significantly better because they only master certain short-horizon tasks, which speeds up and simplifies the learning process. Table 5 in Appendix provides information on the subgoal performances for each module.

(a) Success rate (SR)   (b) Mean episode lengths

Figure 4: **Hierarchical policy learns faster and more efficient action sequences.** Plot (a) shows the learning curves (success rates vs epochs) of the hierarchical and flat policy agents for unseen and seen environments. Plot (b) presents the average length of an episode traversed by a hierarchical or flat policy for the seven task types in ALFRED (Shridhar et al., 2020). The flat policy denotes the NIH ablated agent (#f) in Table 2.

4.2 INTERPRETABLE SUBGOAL MODULES

One of the noticeable benefits of the proposed approach is that it generates semantically meaningful subgoals by PCC. The generated subgoals are far more interpretable than a low-level action sequence. For instance, the low-level *put* action might be associated to any of the subgoals such as Heat, Cool, or Put. The high-level semantics are reasoned about by the hierarchical agent, and the agent's intent is considerably clearer. If the agent attempts to place the object in a refrigerator, it is most likely cooling it; if the receptacle is a microwave, it is attempting to heat it; and if the receptacle is a table, it is simply a pickup subgoal. In contrast, the flat policy agent considers it as a single atomic action regardless of the object and receptable. We present an example for more detail in Figure 5 in Appendix.

4.3 COMPARISON BETWEEN MODULAR AND NON-MODULAR POLICY AGENTS

Modular networks split the decision making process into a set of neural networks. Modules are each specialized for particular functions, and then composed into a structure specific to each example to complete the task. Because of their compositional nature, modular network generalizes better in new environments than its flat counterpart. . We present a quantitative comparison of interaction policies' modular structure (Table 2 #f). For this experiment, we train a single policy module to learn all seven interaction tasks. The decoupled pipeline for action and mask prediction, as well as the rest of the settings, are preserved. The modular agent outperforms the non-modular agent by 2.14% and 7.14% in seen and unseen task SR, respectively. It also performs significantly well in both seen and unseen 'Goal-Condition' criteria, with gains of 2.16% and 7.14%, respectively. The greater performance of the modular policy in both task and goal-condition metrics highlights the modular structure's benefits in long-horizon planning and its superior generalisation capabilities.

4.4 ABLATION STUDY

We conduct a series of ablation analysis on the components of HACR and report the results in Table 2 to evaluate the significance of each module with empirical studies.

(a) Data augmentation (DA). We start by ablating the data augmentations which lowers the performance across the board, highlighting its usefulness in training a smarter agent by reducing imitation learning sample complexity. This results in a performance drop of 12.95% and 26.03% in the seen and unseen task success rate respectively.

	Components						Validation-Seen		Validation-Unseen	
#	MIP	OCMP	FIP	NIH	OEM	DA	Task	Goal-Cond.	Task	Goal-Cond.
-	✓	✓	✓	✓	✓	✓	46.09	54.69	20.09	38.41
(a)	✓	✓	✓	✓	✓		40.12	45.47	14.86	34.48
(b)	✓	✓	✓	✓		✓	36.70	42.20	12.30	28.53
(c)	✓	✓	✓		✓	✓	42.07	50.56	13.52	30.00
(d)	✓	✓		✓	✓	✓	27.19	38.54	10.96	33.06
(e)	✓		✓	✓	✓	✓	9.14	20.91	2.43	21.60
(f)		✓	✓	✓	✓	✓	45.12	53.53	18.75	35.85

Table 2: **Ablation study for each component of HACR.** For each metric, we report the success rate. The absence of checkmark denotes that the corresponding component is removed from HACR. Here NIH, and MIP refer to the Navigation-Interaction Hierarchy (Sec. 4.1) and Modular Interaction Policy (Sec. 4.3) respectively. FIP, OCMP, OEM and DA stands for Factorized Interaction Policy, Object-Centric Mask Prediction, Object Encoding Module and Data Augmentation respectively. Kindly see Sec. 4.4 for details.

(b) Object encoding module (OEM). Then we investigate the OEM's ablation. We remove the navigation subgoal monitor and train the navigation policy without object information. The agent can complete some objectives, but it lacks object information, which functions as a stopping criterion, preventing it from navigating properly. Therefore, it is unable to completely comprehend the relationship between the step-by-step instruction and the visual trajectory, limiting the agent's capacity to explore and connect various interaction policies required for the task's completion, thus resulting in a huge performance drop.

(c) Navigation interaction hierarchy (NIH). Next, we demonstrate the importance of hierarchy between navigation and interaction policies. We utilize the same network parameters for learning the navigation and interaction action prediction. For target class prediction, we preserved the IPM from the subgoal modules and trained the entire agent in an end-to-end manner. To eliminate the benefit of the language distribution, we use the concatenation of all step-by-step instructions as the language input and conduct action and mask prediction while leaving the other modules unaltered. The ablated model's task success rates drop dramatically, showing that it is unable to effectively utilise the available inputs. It is interesting to note that the agent has considerably better performance than (Singh et al., 2021) which enhances the effectiveness of our object based navigation approach.

(d) Factorised interaction policies (FIP). Then, under the interaction policies, we replaced the decoupled pipeline with a unified pipeline for both action sequence prediction and interaction mask generation. Due to shared processing for mask and action modules, the ablated model's performance drops substantially, showing that its inability to effectively utilize the language information.

(e) Object-centric mask prediction (OCMP). Finally, we train the interaction policies without the use of OCMP (Singh et al., 2021). Similar to (Shridhar et al., 2020), we directly upsample the joint embedding using deconvolution layers to generate the interaction mask. We see a significant decline in performance on both seen and unseen folds due to poor mask generating ability, emphasising the need of object information for consistently accurate mask formation.

5 CONCLUSION

We address the problem of interactive instruction following. To effectively tackle the long horizon task, we propose Hierarchical Approach for Compositional Reasoning (HACR), that decomposes the task into high-level subgoals and accomplishes each subgoal with a specialized submodule. We propose a policy composition controller (PCC) to disentangle the task into high-level subgoals. For improving the navigation performance, we propose an object encoding module (OEM) to explicitly encode target object information during internal state update. We also propose a loop escape module to circumvent the deadlock states during navigation, for better exploration. Our agent outperforms prior arts by significant margins and achieves a new state-of-the-art with superior generalization.

ETHICS STATEMENT

The embodied AI research will expedite the deployment of AI systems to help humans by its versatility of adapting to a new environment out of the factory or research labs. As all embodied AI, however, would suffer from adversarially annotated data as well as data bias in a form of language instructions, which may cause ethnic, gender or biased gender issues, the proposed method would not be an exception. Although the proposed method has *no intention* to allow such problematic cases, the method may be exposed to such threats. Relentless efforts should be made to develop mechanisms to prevent such usage cases in order to make the robotics AI safer and enjoyable to be used by humans.

REPRODUCIBILITY STATEMENT

We take the reproducibility of research very seriously and describe the algorithm in detail in Sec. 3 and Sec. A.1. We also solemnly promise to release all codes, environment information, learned models, and complete task configurations in a public repository.

REFERENCES

Peter Anderson, Qi Wu, Damien Teney, Jake Bruce, Mark Johnson, Niko Sünderhauf, Ian Reid, Stephen Gould, and Anton van den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *CVPR*, 2018.

Jacob Andreas, Dan Klein, and Sergey Levine. Modular multitask reinforcement learning with policy sketches. In *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, 2017.

Valts Blukis, Chris Paxton, Dieter Fox, Animesh Garg, and Yoav Artzi. A persistent spatial semantic representation for high-level natural language instruction execution. *arXiv preprint arXiv:2107.05612*, 2021.

Devendra Singh Chaplot, Kanthashree Mysore Sathyendra, Rama Kumar Pasumarthi, Dheeraj Rajagopal, and Ruslan Salakhutdinov. Gated-attention architectures for task-oriented language grounding. In *AAAI*, 2017.

Howard Chen, Alane Suhr, Dipendra Misra, Noah Snavely, and Yoav Artzi. Touchdown: Natural language navigation and spatial reasoning in visual street environments. In *CVPR*, 2019.

Rodolfo Corona, Daniel Fried, Coline Devin, Dan Klein, and Trevor Darrell. Modular networks for compositional instruction following. *arXiv preprint arXiv:2010.12764*, 2020.

Ekin Dogus Cubuk, Barret Zoph, Dandelion Mane, Vijay Vasudevan, and Quoc V. Le. Autoaugment: Learning augmentation policies from data. In *CVPR*, 2019.

Abhishek Das, Samyak Datta, Georgia Gkioxari, Stefan Lee, Devi Parikh, and Dhruv Batra. Embodied Question Answering. In *CVPR*, 2018.

Abhishek Das, Georgia Gkioxari, Stefan Lee, Devi Parikh, and Dhruv Batra. Neural Modular Control for Embodied Question, Answering. 2019.

Heming Du, Xin Yu, and Liang Zheng. Learning object relation graph and tentative policy for visual navigation. In *ECCV*, 2020.

Daniel Gordon, Aniruddha Kembhavi, Mohammad Rastegari, Joseph Redmon, Dieter Fox, and Ali Farhadi. Iqa: Visual question answering in interactive environments. In *CVPR*, 2018.

Saurabh Gupta, James Davidson, Sergey Levine, Rahul Sukthankar, and Jitendra Malik. Cognitive mapping and planning for visual navigation. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, 2017.

B. Hayes-Roth and F. Hayes-Roth. A cognitive model of planning. *Cognitive Science*, 3:275–310, 1979.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Daniel Gordon, Yuke Zhu, Abhinav Gupta, and Ali Farhadi. AI2-THOR: An Interactive 3D Environment for Visual AI. arXiv:1712.05474, 2017.

Jacob Krantz, Erik Wijmans, Arjun Majumdar, Dhruv Batra, and Stefan Lee. Beyond the nav-graph: Vision-and-language navigation in continuous environments. arXiv:2004.02857, 2020.

Yang Li, Jiacong He, Xin Zhou, Yuan Zhang, and Jason Baldridge. Mapping natural language instructions to mobile UI action sequences. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, 2020.

Chih-Yao Ma, Jiasen Lu, Zuxuan Wu, Ghassan AlRegib, Zsolt Kira, Richard Socher, and Caiming Xiong. Self-monitoring navigation agent via auxiliary progress estimation. In *ICLR*, 2019. URL https://arxiv.org/abs/1901.03035.

Dipendra Misra, John Langford, and Yoav Artzi. Mapping instructions and visual observations to actions with reinforcement learning. In *EMNLP*, 2017.

Van-Quang Nguyen, Masanori Suganuma, and Takayuki Okatani. Look wide and interpret twice: Improving performance on interactive instruction-following tasks. *arXiv:2106.00596*, 2021.

Kolby Nottingham, Litian Liang, Daeyun Shin, Charless C. Fowlkes, Roy Fox, and Sameer Singh. Modular framework for visuomotor language grounding. In *Embodied AI Workshop CVPR*, 2021.

Alexander Pashevich, Cordelia Schmid, and Chen Sun. Episodic transformer for vision-and-language navigation. *arXiv preprint arXiv:2105.06453*, 2021.

Mohit Shridhar, Jesse Thomason, Daniel Gordon, Yonatan Bisk, Winson Han, Roozbeh Mottaghi, Luke Zettlemoyer, and Dieter Fox. Alfred: A benchmark for interpreting grounded instructions for everyday tasks. In *CVPR*, 2020.

Kunal Pratap Singh, Suvaansh Bhambri, Byeonghwi Kim, Roozbeh Mottaghi, and Jonghyun Choi. Factorizing perception and policy for interactive instruction following. *arXiv preprint arXiv:2012.03208*, 2021.

Alessandro Suglia, Qiaozi Gao, Jesse Thomason, Govind Thattai, and Gaurav Sukhatme. Embodied bert: A transformer model for embodied, language-guided visual task completion. *arXiv preprint arXiv:2108.04927*, 2021.

Mitchell Wortsman, Kiana Ehsani, Mohammad Rastegari, Ali Farhadi, and Roozbeh Mottaghi. Learning to learn how to learn: Self-adaptive visual navigation using meta-learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6750–6759, 2019.

Danfei Xu, Roberto Martín-Martín, De-An Huang, Yuke Zhu, Silvio Savarese, and Fei-Fei Li. Regression planning networks. In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, 2019.

Nancy Xu, Sam Masling, Michael Du, Giovanni Campagna, Larry Heck, James Landay, and Monica Lam. Grounding open-domain instructions to automate web support tasks. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, 2021.

Wei Yang, Xiaolong Wang, Ali Farhadi, Abhinav Gupta, and Roozbeh Mottaghi. Visual semantic navigation using scene priors. *arXiv preprint arXiv:1810.06543*, 2018.

Licheng Yu, Xinlei Chen, Georgia Gkioxari, Mohit Bansal, Tamara L. Berg, and Dhruv Batra. Multi-target embodied question answering. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, 2019.

Yichi Zhang and Joyce Chai. Hierarchical task learning from language instructions with unified transformers and self-monitoring. *arXiv preprint arXiv:2106.03427*, 2021.

Fengda Zhu, Yi Zhu, Xiaojun Chang, and Xiaodan Liang. Vision-language navigation with self-supervised auxiliary reasoning tasks. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, 2020.

Yuke Zhu, Daniel Gordon, Eric Kolve, Dieter Fox, Li Fei-Fei, Abhinav Gupta, Roozbeh Mottaghi, and Ali Farhadi. Visual semantic planning using deep successor representations. In *ICCV*, 2017.

A APPENDIX

A.1 ARCHITECTURE DETAILS FOR INTERACTION POLICY

Let $\mathcal{A}_m$ denote the set of primitive interaction actions {Open, Close, ToggleOn, ToggleOff, Pickup, Put}. The APM architecture consist of an LSTM decoder that takes as input the attended language encoding $\hat{l}_{t,m}$ corresponding to the current manipulation subgoal, the egocentric visual features $\hat{v}_{t,m}^{ego}$ and the previous time step action $a_{t,m}$ and outputs a distribution over the manipulation action space $\mathcal{A}_m \cup \texttt{<STOP>}$. The manipulation policy uses $\texttt{<STOP>}$ token as an indicator for completion of the interaction task and shifts the control to the master policy for further task completion.

Formally:

$$
\begin{aligned}
h_{t,m}^{apm} &= \text{LSTM}_m([\hat{v}_{t,m}^{ego}; \hat{l}_{t,m}; a_{t-1,m}]), \\
a_{t,m} &= \underset{k}{\text{argmax}}(\text{FC}_m([\hat{v}_t^{ego}; \hat{l}_{t,m}; a_{t-1,m}; h_{t,m}^{apm}])) \quad where\ k \in [1, |\mathcal{A}_m| + 1].
\end{aligned}
\tag{4}
$$

The IPM uses the same inputs as APM and outputs the object class that the agent needs to interact with at the current time step. Similar to (Singh et al., 2021), we use a pretrained Mask-RCNN to obtain the interaction mask corresponding to the object class. For more details about the architecture, kindly refer to (Singh et al., 2021).

$$
\begin{aligned}
h_{t,v}^{vpm} &= \text{LSTM}_v([\hat{v}_{t,v}^{ego}; \hat{l}_{t,v}; a_{t-1,v}]), \\
c_{t,v} &= \underset{k}{\text{argmax}}(\text{FC}_v([\hat{v}_t^{ego}; \hat{l}_{t,v}; a_{t-1,v}; h_{t,v}^{vpm}])) \quad where\ k \in [1, N_{objects}].
\end{aligned}
\tag{5}
$$

A.2 SURROUNDING PERCEPTION

HACR investigates and perceives surrounding views to improve the agent's perception and gain a better comprehension of the environment. Let v_t^d be a visual feature from each navigable direction, $d \in [0, D]$, at the time step, t, where D represents the number of navigable directions and $d = 0$ the agent's egocentric direction. After gathering additional observations, $v_t^{0:D}$, we acquire attended visual features, $\hat{v}_t^{pan}$, using the dynamic filters and concatenate all attended visual features as:

$$
\hat{v}_t^{pan} = [\hat{v}_t^0; \hat{v}_t^1; \cdots; \hat{v}_t^D].
\tag{6}
$$

Using the attended visual features, we update the master policy decoder and predict masks and actions as described in Equation 2.

A.3 EXPERIMENTAL DETAILS

Dataset and Metrics. For training and evaluation, we used the ALFRED benchmark (Shridhar et al., 2020). This benchmark provides expert trajectories for the agents performing household tasks (e.g. Boil an egg) in a simulated environment on AI2-THOR (Kolve et al., 2017). The dataset is divided into three parts; 'train', 'validation', and 'test' set. To evaluate the generalisation ability of an embodied agent to novel environments, the benchmark further divides 'validation' and 'test' trajectories into *seen* and *unseen* splits. Unseen comprises a set of rooms which are held out during training and scenes that are exposed to the agent during the training are termed as *seen*. The benchmark provides a high-level Goal Statement describing the final task and several low-level Step-by-Step Instruction describing each subgoal that needs to be accomplished in the given order for successful completion of goal task.

Following the common evaluation protocols , we evaluate our agent on two metrics. Success rate (SR) provides the percentage of tasks that had all successful goal conditions. Goal condition rate (GC) is the percentage of satisfied goal-conditions across all tasks.

Training and Evaluation. We begin by assessing the performance of each subgoal policy in relation to its specific task. On the ALFRED validation set, we present the success rate for each subgoal (as shown in supplementary). To accomplish this, we employ the expert trajectory to guide the agent through the episode until it reaches the subgoal task. The agent then uses the task specific policy to

Input Ablations	Validation-Seen		Validation-Unseen	
	Task	GC	Task	GC
HACR (Ours)	46.09	54.69	20.09	38.41
Egocentric View Only	30.48	36.13	12.42	23.72
No Vision	0.61	6.87	0.24	8.25
No Language	3.65	10.66	1.21	7.78
Goal-Only	8.53	16.50	2.07	10.04
Single Navigation Instruction	12.19	23.71	3.04	14.95
w/o Loop Escape Module	45.43	54.18	19.88	37.98

Table 3: **Input Ablations. and Loop Escaping Ablation**

infer based on the language directive and current visual frame. Following that, we train and evaluate the master policy's performance during independent behaviour cloning on expert trajectories, i.e. assuming oracle subgoal-policies. With ground truth subgoal sequences, the master policy is able to generalise effectively and achieves 29.96% success rate (SR) on unseen validation data. Then we train the Object Encoding Module and the Policy Composition Controller in isolation and combine all the modules together as described in Sec. 3.

Implementation Details. Visual features are encoded with a pretrained ResNet-18 (He et al., 2016) after resizing input images to 224×224. To perceive surrounding views, we additionally gather visual observations from four navigable directions (i.e., ROTATELEFT, ROTATERIGHT, LOOKUP, and LOOKDOWN). We train each module of our approach independently using the Adam Optimizer with the initial learning rate of 10^{-3}. We augment visual features by shuffling the channel order of each image (Singh et al., 2021) and applying predefined image augmentations (Cubuk et al., 2019). We set the coefficients for the subgoal and overall progress monitor objectives as 0.2, and 0.3 respectively.

A.4 FURTHER ABLATION STUDY ON INPUT

To further investigate our agent's vision and language bias, we ablate the inputs to our model in Table 3.

Egocentric View only. This ablation specifies the condition under which the agent is deprived of its surrounding views (Sec A.2) while navigating without affecting any other module. The agent continues to perform admirably and outperforms the HLSM (Blukis et al. (2021)) on the validation fold by a large margin in seen trajectories, while also providing a significant improvement in task success rate in unseen environment. This demonstrates the significance of peripheral perceptions in navigating a novel environment.

No Language. We discovered that when the agent receives only visual inputs without the language instructions, it is still capable of doing some tasks by memorising common sequences and target classes in the 'seen' fold. but does not adapt to the unseen environment.

No Vision. This ablation demonstrates that the agent can still perform some subgoals, mostly navigation, by following the instructions to move along a few short trajectories, but not able to complete goal tasks because it involves mask generation (object selection), which is entirely dependent on visual observation.

Goal-Only. We define the setting where both the navigation and interaction policies receive only the goal task information. It gives a general idea of the task but doesn't contain any information about the tedious action combinations the agent needs to perform to get the task done. This leads to a significant depletion in the task success rate.

Single Navigation Instruction. This is when the master policy only receives the navigation instruction corresponding to the current navigational subgoal. The agent is able to somewhat navigate but doesn't have the object information that acts as the stopping criterion which hinders the agent's

ability to perform interaction at the correct place in the environment. This demonstrates the benefit of our object-centric navigational approach.

A.5 ADDITIONAL EXPERIMENTAL RESULTS

Table 4 presents the comparison between performance of monolithic policy, a general seq2seq model (Shridhar et al. (2020)) and our hierarchical approach, on the ALFRED validation set across the seven task categories. In both seen and unseen situations, our technique surpasses others by a significant margin.

Table 5 presents the performance of individual subgoal policies on corresponding subgoals. Our hierarchical agent relatively outperforms the flat policy by 50% and 21% average on unseen and seen validation set respectively. The modular nature of our interaction policies allows them to learn specific short horizon subgoal tasks as illustrated in Figure 6-11 which reduces the complexity and makes the learning faster and easier.

Task-type	Seq2Seq		Flat policy		HACR (Ours)	
	Seen	Unseen	Seen	Unseen	Seen	Unseen
Pick & Place	7.0	0.0	57.2	5.2	**62.7**	**8.0**
Cool & Place	4.0	0.0	40.9	19.9	**46.0**	**31.2**
Stack & Place	0.9	0.0	23.2	10.3	**24.3**	**13.8**
Heat & Place	1.9	0.0	47.7	11.4	**52.3**	**16.9**
Clean & Place	1.8	0.0	38.8	24.6	**43.7**	**38.1**
Examine	9.6	0.0	48.5	10.3	**52.1**	**13.9**
Pick Two & Place	0.8	0.0	35.0	14.9	**39.5**	**22.2**
Average	3.7	0.0	41.6	13.8	**45.8**	**20.6**

Table 4: **Success rates across seven task types in ALFRED.** 'Seq2Seq' refers to the method by Shridhar et al. (2020). 'Flat policy' refers to... We indicate the highest values in **blue** and all numbers are in percentage. We evaluate the agents on the **Validation** set.

Task-type	Seq2Seq		Flat policy		HACR (Ours)	
	Seen	Unseen	Seen	Unseen	Seen	Unseen
Pickup	32	21	66	39	**82**	**68**
Put	81	46	73	45	**90**	**68**
Cool	88	92	77	90	**95**	**94**
Heat	85	**89**	69	49	**85**	87
Clean	81	57	65	51	**81**	**73**
Slice	25	12	65	49	**73**	**79**
Toggle	100	50	79	30	**97**	**53**
Average	70	46	71	50	**86**	**75**

Table 5: **Subgoal success rate.** The highest values per fold and task are shown in **blue**.

Figure 5: **Inference of the task 'Heat and Chill a potato.' using hierarchical policy vs. using flat policy.** The hierarchical agent decompose the instructions into subtasks each including a navigation and an interaction subgoal. The PCC at the bottom outputs a sequence of subgoals used for selecting the appropriate interaction policy. The object column demonstrates the output of the OEM. The master policy uses the subtask instruction, object encoding, and visual observation to infer the navigation action at every time step as shown at the top. It predicts the <MANIPULATE> token to shift the agent's control to the interaction policies along the way. On completion on the interaction task, the control is shifted bask to the navigation policy. The hidden state of the navigation policy is kept continuous keep an encoding of navigation history without any interference of the interaction policy whereas each interaction policy uses an independent hidden state. The flat policy shown at the top, on the other hand shares the same parameters for learning both navigation and interaction subtasks. This disentanglement results in simpler and faster learning by enabling parallel computation for various policies.

Figure 6: Pickup Object interaction policy agent completes a subgoal task 'Take the remote.' in an unseen environment.

Figure 7: Put Object interaction policy agent completes a subgoal task "Put the plunger below the sink." in an unseen environment.

Figure 8: Clean Object interaction policy agent completes a subgoal task "Clean the mug in the sink." in an unseen environment.

Figure 9: Cool Object interaction policy agent completes a subgoal task "Chill the apple in the refrigerator." in an unseen environment.

Figure 10: Toggle Object interaction policy agent completes a subgoal task "Turn on the lamp." in an unseen environment.

(a) Heat Object

Figure 11: Heat Object interaction policy agent completes a subgoal task "Heat the apple slice in the microwave." in an unseen environment.

(a) Slice Object

Figure 12: Slice Object interaction policy agent completes a subgoal task "Make slices of the bread." in an unseen environment.