PowerQuant: Automorphism Search for Non-Uniform Quantization

Abstract

Deep neural networks (DNNs) are nowadays ubiquitous in many domains such as computer vision. However, due to their high latency, the deployment of DNNs hinges on the development of compression techniques such as quantization which consists in lowering the number of bits used to encode the weights and activations. Growing concerns for privacy and security have motivated the development of data-free techniques, at the expanse of accuracy. In this paper, we identity the uniformity of the quantization operator as a limitation of existing approaches, and propose a data-free non-uniform method. More specifically, we argue that to be readily usable without dedicated hardware and implementation, non-uniform quantization shall not change the nature of the mathematical operations performed by the DNN. This leads to search among the continuous automorphisms of $(\mathbb{R}_+^*, \times)$, which boils down to the power functions defined by their exponent. To find this parameter, we propose to optimize the reconstruction error of each layer: in particular, we show that this procedure is locally convex and admits a unique solution. At inference time, we show that our approach, dubbed PowerQuant, only require simple modifications in the quantized DNN activation functions. As such, with only negligible overhead, it significantly outperforms existing methods in a variety of configurations.

1 Introduction

Deep neural networks (DNNs) tremendously improved algorithmic solutions for a wide range of tasks. In particular, in computer vision, these achievements come at a consequent price, as DNNs deployment bares a great energetic price. Consequently, the generalization of their usage hinges on the development of compression strategies. Quantization is one of the most promising such technique, that consists in reducing the number of bits needed to encode the DNN weights and/or activations, thus limiting the cost of data processing on a computing device.

Existing DNN quantization techniques, for computer vision tasks, are numerous and can be distinguished by their constraints. One such constraint is data usage, as introduced in Nagel et al. (2019), and is based upon the importance of data privacy and security concerns. Data-free approaches such as Banner et al. (2019); Cai et al. (2020); Choukroun et al. (2019); Fang et al. (2020); Garg et al. (2021); Zhao et al. (2019); Nagel et al. (2019), exploit heuristics and weight properties in order to perform the most efficient weight quantization without having access to the training data. As compared to data-driven methods, the aforementioned techniques are more convenient to use but usually come with higher accuracy loss at equivalent compression rates. Data-driven methods performance offer an upper bound on what can be expected from data-free approaches and in this work, we aim at further narrowing the gap between these methods.

To achieve this goal, we propose to leverage a second aspect of quantization: uniformity. For simplicity reasons, most quantization techniques such as Nagel et al. (2019); Zhao et al. (2019); Cong et al. (2022) perform *uniform* quantization, *i.e.* they consist in mapping floating point values to an evenly spread, discrete space. However, non-uniform quantization can theoretically provide a closer fit to the network weight distributions, thus better preserving the network accuracy. Previous work on non-uniform quantization either focused on the search of binary codes (Banner et al., 2019; Hubara et al., 2016; Jeon et al., 2020; Wu et al., 2016; Zhang et al., 2018) or leverage logarithmic distribution (Miyashita et al., 2016; Zhou et al., 2017). However, these approaches map floating

Figure 1: Comparison of the proposed method to other data-free quantization schemes on DenseNet 121 pre-trained on ImageNet. The proposed method (right bin in blue) drastically improves upon the existing data-free methods especially in the challenging W4/A4 quantization.

point multiplications operations to other operations that are hard to leverage on current hardware (e.g. bit-shift) as opposed to uniform quantization which maps floating point multiplications to integer multiplications (Gholami et al., 2021; Zhou et al., 2016). To circumvent this limitation and reach a tighter fit between the quantized and original weight distributions, in this work, we propose to search for the best possible quantization operator that preserves the nature of the mathematical operations. We show that this search boils down to the space defined by the continuous automorphisms of $(\mathbb{R}_+^*, \times)$, which is limited to power functions defined by their exponent. We optimize the value of this parameter by minimizing the error introduced by quantization. This allows us to reach superior accuracy, as illustrated in Fig 1. To sum it up, our contributions are:

- We search for the best quantization operator that do not change the nature of the mathematical operations performed by the DNN, *i.e.* the automorphisms of $(\mathbb{R}_+^*, \times)$. We show that this search can be narrowed down to finding the best exponent for power functions.

- We find the optimal exponent parameter to more closely fit the original weight distribution compared with existing (e.g. uniform and logarithmic) baselines. To do so, we propose to optimize the quantization reconstruction error. We show that this problem is locally convex and admits a unique solution.

- In practice, we show that the proposed approach, dubbed PowerQuant, only requires simple modifications in the quantized DNN activation functions. Furthermore, we demonstrate through extensive experimentation that our method achieves outstanding results on various and challenging benchmarks with only negligible computational overhead.

2 RELATED WORK

2.1 QUANTIZATION

In this section, we provide a background on the current state of DNNs quantization. Notice that while certain approaches are geared towards memory footprint reduction (e.g. without quantizing inputs and activations) (Chen et al., 2015; Gong et al., 2014; Han et al., 2016; Zhou et al., 2017), in what follows, we essentially focus on methods that aim at reducing the inference time. In particular, motivated by the growing concerns for privacy and security, data-free quantization methods (Banner et al., 2019; Cai et al., 2020; Choukroun et al., 2019; Fang et al., 2020; Garg et al., 2021; Zhao et al., 2019; Nagel et al., 2019; Cong et al., 2022) are emerging and have significantly improved over the recent years.

The first breakthrough in data-free quantization (Nagel et al., 2019) was based on two mathematical ingenuities. First, they exploited the mathematical properties of piece-wise affine activation functions (such as e.g. ReLU based DNNs) in order to balance the per-channel weight distributions by iteratively applying scaling factors to consecutive layers. Second, they proposed a bias correction

scheme that consists in updating the bias terms of the layers with the difference between the expected quantized prediction and the original predictions. They achieved near full-precision accuracy in int8 quantization. Since this seminal work, two main categories of data-free quantization methods have emerged. First, data-generation based methods, such as Cai et al. (2020); Garg et al. (2021), that used samples generated by Generative Adversarial Networks (GANs) (Goodfellow et al., 2014) as samples to fine-tune the quantized model through knowledge distillation (Hinton et al., 2014). Nevertheless, these methods are time-consuming and require significantly more computational resources. Other methods, such as Banner et al. (2019); Choukroun et al. (2019); Fang et al. (2020); Zhao et al. (2019); Nagel et al. (2019); Cong et al. (2022), focus on improving the quantization operator but usually achieve lower accuracy. One limitation of these approaches is that they are essentially restricted to uniform quantization, while considering non-uniform mappings between the floating point and low-bit representation might be key to superior performance.

2.2 NON-UNIFORM QUANTIZATION

Indeed, in uniform settings, continuous variables are mapped to an equally-spaced grid in the original, floating point space. Such mapping introduces an error: however, applying such uniform mapping to an *a priori* non-uniform weight distribution is likely to be suboptimal in the general case. To circumvent this limitation, non-uniform quantization has been introduced (Banner et al., 2019; Hubara et al., 2016; Jeon et al., 2020; Wu et al., 2016; Zhang et al., 2018; Miyashita et al., 2016; Zhou et al., 2017). We distinguish two categories of non-uniform quantization approaches. First, methods that introduce a code-base and require very sophisticated implementations for actual inference benefits such as Banner et al. (2019); Hubara et al. (2016); Jeon et al. (2020); Wu et al. (2016); Zhang et al. (2018). Second, methods that simply modify the quantization operator such as Miyashita et al. (2016); Zhou et al. (2017). In particular, Miyashita et al. (2016) proposes a log-quantization technique where multiplications are replaced by bit shifts. Nevertheless, one limitation of this approach is that because the very nature of the mathematical operations is intrinsically altered, in practice, it is hard to leverage without dedicated hardware and implementation. Instead of transforming floating point multiplications in integer multiplications, they change floating point multiplications into bit-shifts or even look up tables (LUTs). Some of these operations are very specific to some hardware (e.g. LUTs are thought for FPGAs) and may not be well supported on most hardware. Conversely, in this work, we propose a non-uniform quantization scheme that preserves the nature of the mathematical operations by mapping floating point multiplications to standard integer multiplications. As a result, our approach boils down to simple modifications of the computations in the quantized DNN, hence allowing higher accuracies than uniform quantization methods while leading to straightforward, ready-to-use inference speed gains. Below we describe the methodology behind the proposed approach.

3 METHODOLOGY

Let F be a trained feed forward neural network with L layers, each comprising a weight tensor W_l. Let Q be a quantization operator such that the quantized weights $Q(W_l)$ are represented on b bits. We note F^Q the quantized neural network. Assuming a bell-shaped distribution for W_l, the standard approach for non-uniform quantization consists in applying a logarithmic distribution where the quantization steps increase exponentially instead of linearly. Practically speaking, the quantized multiplications can then be replaced by bit-shift operations. Furthermore these methods have limited adaptability as the increment speed is hardware dependent.

Taking aside the rounding operation in quantization, we want to define the space $\mathcal{Q}$ of functions Q such that

$$\forall Q \in \mathcal{Q}, \exists Q^{-1} \in \mathcal{Q} \quad \text{s.t.} \ \forall x, y \quad Q^{-1}(Q(x) * Q(y)) = x \times y \tag{1}$$

where $*$ is the intern composition law of the quantized space and $\times$ is the standard multiplication. In the case of uniform quantization and our work $*$ will be the multiplication while in other non-uniform work it often corresponds to hard to leverage operations such bit-shift. In other words, for now, we omit the error introduced by quantization. These functions encapsulated with the rounding operation will define our novel quantization operator. The proposed PowerQuant method consists in the search for the best suited operator for a given trained neural network and input statistics.

Figure 2: Influence of the power parameter a on the quantized distribution associated to a Gaussian prior. In such instance, the reconstruction error is minimized for $a < 1$.

3.1 Automorphisms of $(R_+^*, \times)$

Let Q be a transformation from $\mathbb{R}_+$ to $\mathbb{R}_+$ such that, for all $x, y \in \mathbb{R}_+^2$, $*$ in equation 1 shall denote the multiplication operation $\times$ and also $Q(x) \times Q(y) = Q(x \times y)$. In order to define a de-quantization operation, we need Q^{-1} to be defined *i.e.* Q is bijective. Thus $\mathcal{Q}$ is a group automorphism of $(R_+^*, \times)$. This will be the set of continuous functions that map (floating point) multiplications to (integer) multiplications and will serve as a founding block for our quantization method. For this purpose, we recall a known result: continuous automorphisms of $(R_+^*, \times)$ are power functions. Here, the innovation consists in using this property for quantization.

Lemma 1. *The set of continuous automorphisms of $(R_+^*, \times)$ is defined by the set of power functions* $\mathcal{Q} = \{Q : x \mapsto x^a | a \in \mathbb{R}\}$.

A proof of this result can be found in Appendix A. For the sake of clarity, we will now include the rounding operation in the quantization operators.

$$\mathcal{Q} = \left\{ Q_a : W \mapsto \left\lfloor (2^{b-1} - 1) \frac{\text{sign}(W) \times |W|^a}{\max |W|^a} \right\rfloor \Big| a \in \mathbb{R} \right\} \tag{2}$$

As functions of W, the quantization operators defined in equation 2 are (signed) power functions, *i.e.* they can be expressed as $W \mapsto |W|^a \times \lambda$ where λ is a constant depending on fixed values computed once (scales and signs). We propose the following interpretation of the value of parameter a based on Fig 2. Uniform quantization and $a = 1$ are equivalent and correspond to a quantization invariant to the weight distribution. For $a < 1$, the quantization is more fine-grained on weight values with low absolute value and coarse on high absolute values. To the contrary, for $a > 1$, the quantization is fine-grained on high absolute values. Intuitively, for centered and mono-modal distributions such as a standard Gaussian, the optimal value of a should be below 1. We now define the search protocol in the proposed search space $\mathcal{Q}$.

3.2 Automorphism Search as a Minimization Problem

We propose to use the error introduced by quantization on the weights as a proxy on the distance between the quantized and the original model.

Reconstruction Error Minimization: The operator Q_a is not a bijection. Thus, quantization introduces a reconstruction error summed over all the layers of the network, and defined as follows:

$$\epsilon(F, a) = \sum_{l=1}^{L} \left\| W_l - Q_a^{-1}(Q_a(W_l)) \right\|_p \tag{3}$$

where $\| \cdot \|_p$ denotes the L^p vector norm (in practice $p = 2$, see appendix B) and the de-quantization operator Q_a^{-1} is defined as:

$$Q_a^{-1}(W) = \text{sign}(W) \times \left| W \times \frac{\max |W|}{2^{b-1} - 1} \right|^{\frac{1}{a}} \tag{4}$$

In practice, the problem of finding the best exponent $a^* = \arg\min_a \epsilon(F, a)$ in equation 3 is a locally convex optimization problem (Appendix C.1) which has a unique minimum (see Appendix C.2). We find the optimal value for a using the Nelder–Mead method (Nelder & Mead, 1965) which solves problems for which derivatives may not be known or, in our case, are almost-surely zero (due to the rounding operation). In practice, more recent solvers are not required in order to reach the optimal solution, this is empirically justified in Appendix D. Lastly, we discuss the limitations of the proposed metric in Appendix G.

3.3 FUSED DE-QUANTIZATION AND ACTIVATION FUNCTION

Based on equation 2, the quantization process of the weights necessitates the storage and multiplication of W with a signs tensor, which is memory and computationally intensive as highlighted in Yvinec et al. (2022a). However, in practice, this operation can be computed once at quantization time and folded within the quantized weight tensor. The same problem arises when quantizing the activations. However, in case of ReLU, we do not have to store the sign of the activations as they are positive. Furthermore, in the case of two consecutive ReLU layers, we apply the power operation only once per layer (as calling the operations $x \rightarrow x^{a^*}$ and $x \rightarrow x^{\frac{1}{a^*}}$ resp. for quantization and de-quantization cancel each other). Conversely, for non-ReLU feed forward networks such as EfficientNets or Image Transformers, activations are not necessarily positive, *i.e.* they are signed. This difficulty can be tackled by exploiting other properties: for instance, for both SiLU (EfficientNets) and GeLU (Image Transformers), the activations are bounded below. $C_{\text{SiLU}} = 0.27846$ and $C_{\text{GeLU}} = 0.169971$ are examples of bounds for SiLU and GeLU respectively. Consequently, assuming a layer with SiLU activation with input x and weights W then we have:

$$Q_a^{-1}\left(Q_a(x + C_{\text{SiLU}})Q_a(W)\right) \approx \left((x + C_{\text{SiLU}})^a W^a\right)^{\frac{1}{a}} = xW + C_{\text{SiLU}}W \tag{5}$$

In other words, the shift introduced by the term C_{SiLU} can be folded with the bias, similarly to Nagel et al. (2019). This bias comes at the cost of a fraction of the inference as we show in our experiments. Using the adequate value for the bias corrector, we can generalize equation 5 to any activation function σ.

The quantization process and inference with the quantized DNN are summarized in Algorithm 1 and 2. The proposed representation is fully compatible with integer multiplication as defined in Jacob et al. (2018), thus it is fully compatible with integer only inference (see appendix F for more details).

Algorithm 1 Weight Quantization Algorithm

Require: trained neural network F with L layers to quantize, number of bits b

    $a \leftarrow \text{solver}(\min\{\text{error}(F, a)\})$ ▷ in practice we use the Nelder–Mead method

    for $l \in \{1, \ldots, L\}$ **do**

        $W_{\text{sign}} \leftarrow \text{sign}(W_l)$ ▷ save the sign of the scalar values in W

        $W_l \leftarrow W_{\text{sign}} \times |W_l|^a$ ▷ power transformation

        $s \leftarrow \frac{\max |W_l|}{2^{b-1}-1}$ ▷ get quantization scale

        $Q : W_l \mapsto \left\lfloor \frac{W_l}{s} \right\rceil$ ▷ quantization by rounding

        $Q^{-1} : W \mapsto W_{\text{sign}} \times |W \times s|^{\frac{1}{a}}$ ▷ definition of the de-quantization operation

    end for

---

4 EXPERIMENTS

In this section, we empirically validate our method. First, we discuss the optimization of the exponent parameter a of PowerQuant using the reconstruction error, showing its interest as a proxy for the quantized model accuracy from an experimental standpoint. We show that the proposed approach preserves this reconstruction error significantly better, allowing a closer fit to the original weight distribution through non-uniform quantization. Second, we show through a variety of benchmarks that the proposed approach significantly outperforms state-of-the-art data-free methods, thanks to more efficient power function quantization with optimized exponent. Third, we show that the proposed approach comes at a negligible cost in term of inference speed.

Algorithm 2 Simulated Inference Algorithm

Require: trained neural network F quantized with L layers, input X and exponent a^*

  for $l \in \{1, \ldots, L\}$ **do**

    $X \leftarrow X^{a^*}$ $\triangleright$ X is assumed positive (see equation equation 5)

    $X^Q \leftarrow \lfloor X s_X \rceil$ $\triangleright$ where s_X is a scale in the input range

    $O \leftarrow F_l(X^Q)$ $\triangleright$ O contains the quantized output of the layer

    $X \leftarrow \left(\frac{\sigma(O)}{s_X s_W} \right)^{\frac{1}{a^*}}$ $\triangleright$ where σ is the activation function and s_W the weight scale

  end for

  return X

4.1 DATASETS AND IMPLEMENTATION DETAILS

We validate the proposed PowerQuant method on ImageNet classification (Deng et al., 2009) ($\approx$ 1.2M images train/50k test). In our experiments we used pre-trained MobileNets (Sandler et al., 2018), ResNets (He et al., 2016), EfficientNets (Tan & Le, 2019) and DenseNets (Huang et al., 2017). We used Tensorflow implementations of the baseline models from official repositories, achieving standard baseline accuracies. The quantization process was done using Numpy library. Activations are quantized as unsigned integers and weights are quantized using a symmetric representation. We fold batch-normalization layers as in Yvinec et al. (2022a).

We performed ablation study using the uniform quantization operator over weight values from Krishnamoorthi (2018) and logarithmic quantization from Miyashita et al. (2016). For our comparison with state-of-the-art approaches in data-free quantization, we implemented the more complex quantization operator from SQuant (Cong et al., 2022). To compare with strong baselines, we also implement bias correction (Nagel et al., 2019) (which measures the expected difference between the outputs of the original and quantized models and updates the biases terms to compensate for this difference) as well as input weight quantization (Nagel et al., 2019).

4.2 EXPONENT PARAMETER FITTING

Fig 3 illustrates the evolution of both the accuracy of the whole DNN and the reconstruction error summed over all the layers of the network, as functions of the exponent parameter a. Our target is the highest accuracy with respect to the value of a: however, in a data-free context, we only have access to the reconstruction error. Nevertheless, as shown on Fig 3, these metrics are strongly anti-correlated. Furthermore, while the reconstruction curve is not convex it behaves well for simplex based optimization method such as the Nelder-Mead method. This is due to two properties: locally convex (Appendix C.1) and has a unique minimum (Appendix C.2).

Empirically, optimal values a^* for the exponent parameter are centered on 0.55, which approximately corresponds to the first distribution in Fig 2. Still, as shown on Table 1 we observe some variations on the best value for a which motivates the optimization of a for each network and bit-width. Furthermore, our results provide a novel insight on the difference between pruning and quantization. In the pruning literature (Han et al., 2015; Frankle & Carbin, 2018; Molchanov et al., 2019), the baseline method consists in setting the smallest scalar weight values to zero and keeping unchanged the highest non-zero values, assuming that small weights contribute less to the network prediction. In a similar vein, logarithmic or power quantization with $a > 1$ roughly quantizes (almost zeroing it out) small scalar values to better preserve the precision on larger values. In practice, in our case, lower reconstruction errors, and better accuracies, are achieved by setting $a < 1$: this suggests that the assumption behind pruning can't be straightforwardly applied to quantization, where in fact we argue that finely quantizing smaller weights is paramount to preserve the patterns learned at each layer, and the representation power of the whole network.

Another approach that puts more emphasis on the nuances between low valued weights is logarithmic based non-uniform quantization. In Table 1 and Appendix E, we compare the proposed power method to both uniform and logarithmic approaches. By definition, the proposed power method necessarily outperforms the uniform method in every scenario as uniform quantization is included in the search space. For instance, in int4, the proposed method improves the accuracy by 13.22 points on ResNet 50. This improvement can also be attributed to a better quantization of the inputs

Figure 3: Relationship between the accuracy and reconstruction error for ResNet and DenseNet quantized in W4/A4.

Table 1: Comparison between logarithmic, uniform and the proposed quantization scheme on ResNet 50 trained for ImageNet classification task. We report for different quantization configuration (weights noted W and activations noted A) both the top1 accuracy and the reconstruction error (equation 3).

Architecture	Method	W-bit	A-bit	a^*	Accuracy	Reconstruction Error
	Baseline	32	32	-	76.15	-
	uniform	8	8	1	76.15	1.1×10^{-4}
	logarithmic	8	8	-	76.12	2.0×10^{-4}
ResNet 50	PowerQuant	8	8	0.55	**76.15**	$\mathbf{1.0} \times 10^{-4}$
	uniform	4	4	1	54.68	3.5×10^{-3}
	logarithmic	4	4	-	57.07	2.1×10^{-3}
	PowerQuant	4	4	0.55	**70.29**	$\mathbf{1.9} \times 10^{-3}$

of each layers, especially on ResNet 50 where the gap in the reconstruction error (over the weights) is relatively small.

4.3 COMPARISON WITH DATA-FREE QUANTIZATION METHODS

In table 2, we report the performance of several data-free quantization approaches on ResNet 50. Although no real training data is involved in these methods, some approaches such as ZeroQ (Cai et al., 2020), DSG (Zhang et al., 2021) or GDFQ (Xu et al., 2020) rely on data generation (DG) in order to calibrate parameters of the method or to apply fine-tuning to preserve the accuracy through quantization. As shown in table 2, in the W8/A8 setup, the proposed PowerQuant method outperforms other data-free solutions, fully preserving the accuracy of the floating point model. The gap is even wider on the more challenging low bit quantization W4/A4 setup, where the PowerQuant improves the accuracy by 1.93 points over SQuant (Cong et al., 2022) and by 14.88 points over GDFQ. This shows the effectiveness of the method on ResNet 50. We provide more results on DenseNet (Huang et al., 2017), MobileNet (Sandler et al., 2018), Efficient Net (Tan & Le, 2019) in Appendix I. These results demonstrate the versatility of the method on both large and very compact convnets. To put it in a nutshell, the proposed PowerQuant vastly outperforms other data-free quantization scheme in every case, thus narrowing the gap between data-free and data-driven quantization. We provide more details in Appendix H. In what follows, we evaluate the PowerQuant method on recent transformer architectures for both image and language applications.

4.4 EVALUATION ON TRANSFORMER ARCHITECTURES

In Table 3, we quantized the weight tensors of a ViT Dosovitskiy et al. (2021) with $85M$ parameters and baseline accuracy ≈ 78 as well as DeiT T,S and B Touvron et al. (2021) with baseline accuracies 72.2, 79.9 and 81.8 and $\approx 5M$, $\approx 22M$, $\approx 87M$ parameters respectively. Similarly to ConvNets, the image transformer is better quantized using PowerQuant rather than standard uniform quantization schemes such as DFQ. Furthermore, more complex and recent data-free quantization schemes such as SQuant, tend to under-perform on the novel Transformer architectures as compared to ConvNets. This is not the case for PowerQuant which maintains its very high performance even in low bit

Table 2: Comparison between state-of-the-art post training quantization techniques on ResNet 50 on ImageNet. We distinguish methods relying on data (synthetic or real) or not. In addition to being fully data-free, our approach significantly outperforms existing methods.

Architecture	Method	Data	W-bit	A-bit	Accuracy	gap
	Baseline	-	32	32	76.15	-
	DFQ Nagel et al. (2019)	No	8	8	75.45	-0.70
	ZeroQ Cai et al. (2020)	Synthetic	8	8	75.89	-0.26
	DSG Zhang et al. (2021)	Synthetic	8	8	75.87	-0.28
	GDFQ Xu et al. (2020)	Synthetic	8	8	75.71	-0.44
	SQuant Cong et al. (2022)	No	8	8	76.04	-0.11
ResNet 50	PowerQuant	No	8	8	**76.15**	**0.00**
	DFQ Nagel et al. (2019)	No	4	4	0.10	-76.05
	ZeroQ Cai et al. (2020)	Synthetic	4	4	7.75	-68.40
	DSG Zhang et al. (2021)	Synthetic	4	4	23.10	-53.05
	GDFQ Xu et al. (2020)	Synthetic	4	4	55.65	-20.50
	SQuant Cong et al. (2022)	No	4	4	68.60	-7.55
	PowerQuant	No	4	4	**70.53**	**-5.62**

Table 3: Comparison of different Data-Free quantization processes on ViT and DeiT Image Transformers trained on ImageNet.

model	method	W / A	accuracy
	baseline	-/-	78.05%
	DFQ (ICCV 2019)	8/8	70.33%
	SQuant (ICLR 2022)	8/8	68.85%
	PSAQ (arxiv 2022)	8/8	37.36%
ViT	PowerQuant	8/8	**77.46%**
	DFQ (ICCV 2019)	4/8	66.63%
	SQuant (ICLR 2022)	4/8	64.62%
	PSAQ (arxiv 2022)	4/8	25.34%
	PowerQuant	4/8	**75.24%**

(a) Evaluation for ViT Base

model	method	W / A	accuracy
	baseline	-/-	72.21%
	DFQ (ICCV 2019)	8/8	71.32%
	SQuant (ICLR 2022)	8/8	71.11%
	PSAQ (arxiv 2022)	8/8	71.56%
DeiT T	PowerQuant	8/8	**72.23%**
	DFQ (ICCV 2019)	4/8	67.71%
	SQuant (ICLR 2022)	4/8	67.58%
	PSAQ (arxiv 2022)	4/8	65.57%
	PowerQuant	4/8	**69.77%**

(b) Evaluation for DeiT Tiny

model	method	W / A	accuracy
	baseline	-/-	79.85%
	DFQ (ICCV 2019)	8/8	78.76%
	SQuant (ICLR 2022)	8/8	78.94%
	PSAQ (arxiv 2022)	8/8	76.92%
DeiT S	PowerQuant	8/8	**79.33%**
	DFQ (ICCV 2019)	4/8	76.75%
	SQuant (ICLR 2022)	4/8	76.61%
	PSAQ (arxiv 2022)	4/8	73.23%
	PowerQuant	4/8	**78.16%**

(c) Evaluation for DeiT Small

model	method	W / A	accuracy
	baseline	-/-	81.85%
	DFQ (ICCV 2019)	8/8	80.72%
	SQuant (ICLR 2022)	8/8	80.60%
	PSAQ (arxiv 2022)	8/8	79.10%
DeiT B	PowerQuant	8/8	**81.26%**
	DFQ (ICCV 2019)	4/8	79.41%
	SQuant (ICLR 2022)	4/8	79.21%
	PSAQ (arxiv 2022)	4/8	77.05%
	PowerQuant	4/8	**80.67%**

(d) Evaluation for DeiT Base

representations. This is best illustrated on ViT where PowerQuant W4/A8 out performs both DFQ and SQuant even when they are allowed 8 bits for the weights (W8/A8) by a whopping 4.91 points. The proposed PowerQuant even outperforms methods dedicated to transformer quantization such as PSAQ Li et al. (2022) on every image transformer tested.

We further compare the proposed power quantization, in W4/A32, on natural language processing (NLP) tasks and report results in Table 4. We evaluate a BERT model (Devlin et al., 2018) on GLUE (Wang et al., 2018) and report both the original (reference) and our reproduced (baseline) results. We compare the three quantization processes: uniform, logarithmic and PowerQuant. Similarly to computer vision tasks, the power quantization outperforms the other methods in every instances which further confirms its ability to generalize well to transformers and NLP tasks. In what follows, we

Table 4: Complementary Benchmarks on the GLUE task. We consider the BERT transformer architecture. We provide the reference performance of BERT on GLUE as well as our reproduced results (baseline).

task	(reference)	baseline	uniform	log	power
CoLA	49.23	47.90	46.24	46.98	**47.77**
SST-2	91.97	92.32	91.28	91.85	**92.32**
MRPC	89.47/85.29	89.32/85.41	86.49/81.37	86.65/82.86	**89.32/85.41**
STS-B	83.95/83.70	84.01/83.87	83.25/83.14	**84.01**/83.81	**84.01/83.87**
QQP	88.40/84.31	90.77/84.65	90.23/84.61	90.76/**84.65**	**90.77/84.65**
MNLI	80.61/81.08	80.54/80.71	79.72/79.13	79.22/79.71	**80.54/80.71**
QNLI	87.46	91.47	90.32	91.43	**91.47**
RTE	61.73	61.82	59.23	61.27	**61.68**
WNLI	45.07	43.76	40.85	42.80	**42.85**

Table 5: ACE cost of the overhead computations introduced by PowerQuant.

Architecture	overhead cost	accuracy in W6/A6
ResNet 50	0.63%	75.07
DenseNet 121	0.97%	72.71
MobileNet V2	0.57%	52.20
EfficientNet B0	0.80%	58.24

show experimentally that our approach induces very negligible overhead at inference time, making this accuracy enhancement virtually free from a computational standpoint.

4.5 INFERENCE COST AND PROCESSING TIME

The ACE metrics was recently introduced in Zhang et al. (2022) to provide a hardware-agnostic measurement of the overhead computation cost in quantized neural networks. In Table 5, we evaluate the cost in the inference graph due to the change in the activation function. We observe very similar results to Table 12. The proposed changes are negligible in terms of computational cost on all tested networks. Furthermore, DenseNet has the highest cost due to its very dense connectivity. On the other hand, using this metric it seems that the overhead cost due to the zero-point technique from section 3.3 for EfficientNet has no significant impact as compared to MobileNet and ResNet. In addition, we provide a more detailed discussion on the inference and processing cost of PowerQuant on specific hardware using dedicated tools in Appendix J.

5 CONCLUSION

In this paper, we pinpointed the uniformity of the quantization as a limitation of existing data-free methods. To address this limitation, we proposed a novel data-free method for non-uniform quantization of trained neural networks for computer vision tasks, with an emphasis on not changing the nature of the mathematical operations involved (e.g. matrix multiplication). This led us to search among the continuous automorphisms of $(\mathbb{R}_+^*, \times)$, which are restricted to the power functions $x \rightarrow x^a$. We proposed an optimization of this exponent parameter based upon the reconstruction error between the original floating point weights and the quantized ones. We show that this procedure is locally convex and admits a unique solution. At inference time, the proposed approach, dubbed PowerQuant, involves only very simple modifications in the quantized DNN activation functions. We empirically demonstrate that PowerQuant allows a closer fit to the original weight distributions compared with uniform or logarithmic baselines, and significantly outperforms existing methods in a variety of benchmarks with only negligible computational overhead at inference time. In addition, we also discussed and addressed some of the limitations in terms of optimization (per-layer or global) and generalization (non-ReLU networks).

Future work involves the search of a better proxy error as compared with the proposed weight reconstruction error as well as the extension of the search space to other internal composition law of R_+ that are suited for efficient calculus and inference.

6 REPRODUCIBILITY STATEMENT

Reproducibility is a mandatory aspect of scientific research. Regarding this matter, we provided a detailed section entirely dedicated to implementation details (sec 4.1). On top of that, to simplify re-implementations, we summarized the quantization and inference processes in Algorithm 1 and Algorithm 2 respectively. Ultimately, we shared some of our quantized networks in the supplementary files. All necessary elements for model loading as well as model inspection are available from a set of python files. The preprocesses are the same as those of the tensorflow source and the vit-keras source for the ResNet model and the ViT model respectively.

REFERENCES

Ron Banner, Yury Nahshan, and Daniel Soudry. Post training 4-bit quantization of convolutional networks for rapid-deployment. *NeurIPS*, pp. 7950–7958, 2019.

Yaohui Cai, Zhewei Yao, Zhen Dong, Amir Gholami, Michael W Mahoney, and Kurt Keutzer. Zeroq: A novel zero shot quantization framework. *CVPR*, pp. 13169–13178, 2020.

Wenlin Chen, James Wilson, et al. Compressing neural networks with the hashing trick. *ICML*, pp. 2285–2294, 2015.

Vladimir Chikin and Vladimir Kryzhanovskiy. Channel balancing for accurate quantization of winograd convolutions. In *CVPR*, pp. 12507–12516, 2022.

Yoni Choukroun, Eli Kravchik, Fan Yang, and Pavel Kisilev. Low-bit quantization of neural networks for efficient inference. *ICCV Workshops*, pp. 3009–3018, 2019.

Guo Cong, Qiu Yuxian, Leng Jingwen, Gao Xiaotian, Zhang Chen, Liu Yunxin, Yang Fan, Zhu Yuhao, and Guo Minyi. Squant: On-the-fly data-free quantization via diagonal hessian approximation. *ICLR*, 2022.

Andrew R Conn, Katya Scheinberg, and Ph L Toint. On the convergence of derivative-free methods for unconstrained optimization. *Approximation theory and optimization: tributes to MJD Powell*, pp. 83–108, 1997.

J. Deng, W. Dong, et al. ImageNet: A Large-Scale Hierarchical Image Database. *CVPR*, 2009.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *ICLR*, 2021.

Jun Fang, Ali Shafiee, Hamzah Abdel-Aziz, David Thorsley, Georgios Georgiadis, and Joseph H Hassoun. Post-training piecewise linear quantization for deep neural networks. *ECCV*, pp. 69–86, 2020.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *ICLR*, 2018.

Sahaj Garg, Anirudh Jain, Joe Lou, and Mitchell Nahmias. Confounding tradeoffs for neural network quantization. *arXiv preprint arXiv:2102.06366*, 2021.

Amir Gholami, Sehoon Kim, Zhen Dong, Zhewei Yao, Michael W Mahoney, and Kurt Keutzer. A survey of quantization methods for efficient neural network inference. *arXiv preprint arXiv:2103.13630*, 2021.

Yunchao Gong, Liu Liu, Ming Yang, and Lubomir Bourdev. Compressing deep convolutional networks using vector quantization. *arXiv preprint arXiv:1412.6115*, 2014.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *NeurIPS*, 27, 2014.

Zbigniew Hajduk. High accuracy fpga activation function implementation for neural networks. *Neurocomputing*, 247:59–61, 2017.

Kun Han, Yuxuan Wang, DeLiang Wang, William S Woods, Ivo Merks, and Tao Zhang. Learning spectral mapping for speech dereverberation and denoising. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 23(6):982–992, 2015.

Song Han, Huizi Mao, and William J Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. *ICLR*, 2016.

Kaiming He, Xiangyu Zhang, et al. Deep residual learning for image recognition. *CVPR*, pp. 770–778, 2016.

Horst Herrlich. *Axiom of choice*, volume 1876. Springer, 2006.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *NeurIPS*, 2014.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. *CVPR*, pp. 4700–4708, 2017.

Itay Hubara, Matthieu Courbariaux, Daniel Soudry, Ran El-Yaniv, and Yoshua Bengio. Binarized neural networks. *NeurIPS*, 29, 2016.

Benoit Jacob, Skirmantas Kligys, Bo Chen, Menglong Zhu, Matthew Tang, Andrew Howard, Hartwig Adam, and Dmitry Kalenichenko. Quantization and training of neural networks for efficient integer-arithmetic-only inference. *CVPR*, pp. 2704–2713, 2018.

Yongkweon Jeon, Baeseong Park, Se Jung Kwon, Byeongwook Kim, Jeongin Yun, and Dongsoo Lee. Biqgemm: matrix multiplication with lookup table for binary-coding-based quantized dnns. *SC20: International Conference for High Performance Computing, Networking, Storage and Analysis*, pp. 1–14, 2020.

Yongkweon Jeon, Chungman Lee, Eulrang Cho, and Yeonju Ro. Mr. biq: Post-training non-uniform quantization based on minimizing the reconstruction error. In *CVPR*, pp. 12329–12338, 2022.

Sehoon Kim, Amir Gholami, Zhewei Yao, Michael W Mahoney, and Kurt Keutzer. I-bert: Integer-only bert quantization. In *International conference on machine learning*, pp. 5506–5518. PMLR, 2021.

Raghuraman Krishnamoorthi. Quantizing deep convolutional networks for efficient inference: A whitepaper. *arXiv preprint arXiv:1806.08342*, 2018.

Maximilian Lam, Michael Mitzenmacher, Vijay Janapa Reddi, Gu-Yeon Wei, and David Brooks. Tabula: Efficiently computing nonlinear activation functions for secure neural network inference. *arXiv preprint arXiv:2203.02833*, 2022.

Zhikai Li, Liping Ma, Mengjuan Chen, Junrui Xiao, and Qingyi Gu. Patch similarity aware data-free quantization for vision transformers. *arXiv preprint arXiv:2203.02250*, 2022.

Daisuke Miyashita, Edward H Lee, and Boris Murmann. Convolutional neural networks using logarithmic data representation. *arXiv preprint arXiv:1603.01025*, 2016.

Pavlo Molchanov, Arun Mallya, Stephen Tyree, Iuri Frosio, and Jan Kautz. Importance estimation for neural network pruning. *CVPR*, pp. 11264–11272, 2019.

Markus Nagel, Mart van Baalen, et al. Data-free quantization through weight equalization and bias correction. *ICCV*, pp. 1325–1334, 2019.

John A Nelder and Roger Mead. A simplex method for function minimization. *The computer journal*, 7(4):308–313, 1965.

Michael JD Powell. An efficient method for finding the minimum of a function of several variables without calculating derivatives. *The computer journal*, 7(2):155–162, 1964.

Charbel Sakr, Steve Dai, Rangha Venkatesan, Brian Zimmer, William Dally, and Brucek Khailany. Optimal clipping and magnitude-aware differentiation for improved quantization-aware training. In *ICML*, pp. 19123–19138. PMLR, 2022.

Mark Sandler, Andrew Howard, et al. Mobilenetv2: Inverted residuals and linear bottlenecks. *CVPR*, pp. 4510–4520, 2018.

Mingxing Tan and Quoc V Le. Efficientnet: Rethinking model scaling for convolutional neural networks. *ICML*, pp. 6105–6114, 2019.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, pp. 10347–10357. PMLR, 2021.

Mart van Baalen, Brian Kahne, Eric Mahurin, Andrey Kuzmin, Andrii Skliar, Markus Nagel, and Tijmen Blankevoort. Simulated quantization, real power savings. In *CVPR*, pp. 2757–2761, 2022.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 353–355, Brussels, Belgium, November 2018. Association for Computational Linguistics. doi: 10.18653/v1/W18-5446. URL https://aclanthology.org/W18-5446.

Jiaxiang Wu, Cong Leng, Yuhang Wang, Qinghao Hu, and Jian Cheng. Quantized convolutional neural networks for mobile devices. *CVPR*, pp. 4820–4828, 2016.

Shoukai Xu, Haokun Li, Bohan Zhuang, Jing Liu, Jiezhang Cao, Chuangrun Liang, and Mingkui Tan. Generative low-bitwidth data free quantization. *ECCV*, pp. 1–17, 2020.

Edouard Yvinec, Arnaud Dapogny, and Kevin Bailly. To fold or not to fold: a necessary and sufficient condition on batch-normalization layers folding. *IJCAI*, 2022a.

Edouard Yvinec, Arnaud Dapogny, Matthieu Cord, and Kevin Bailly. Spiq: Data-free per-channel static input quantization. *arXiv preprint arXiv:2203.14642*, 2022b.

Dongqing Zhang, Jiaolong Yang, Dongqiangzi Ye, and Gang Hua. Lq-nets: Learned quantization for highly accurate and compact deep neural networks. *ECCV*, pp. 365–382, 2018.

Xiangguo Zhang, Haotong Qin, Yifu Ding, Ruihao Gong, Qinghua Yan, Renshuai Tao, Yuhang Li, Fengwei Yu, and Xianglong Liu. Diversifying sample generation for accurate data-free quantization. *CVPR*, pp. 15658–15667, 2021.

Yichi Zhang, Zhiru Zhang, and Lukasz Lew. Pokebnn: A binary pursuit of lightweight accuracy. In *CVPR*, pp. 12475–12485, 2022.

Ritchie Zhao, Yuwei Hu, Jordan Dotzel, Chris De Sa, and Zhiru Zhang. Improving neural network quantization without retraining using outlier channel splitting. *ICML*, pp. 7543–7552, 2019.

Aojun Zhou, Anbang Yao, Yiwen Guo, Lin Xu, and Yurong Chen. Incremental network quantization: Towards lossless cnns with low-precision weights. *ICLR*, 2017.

Shuchang Zhou, Yuxin Wu, Zekun Ni, Xinyu Zhou, He Wen, and Yuheng Zou. Dorefa-net: Training low bitwidth convolutional neural networks with low bitwidth gradients. *arXiv preprint arXiv:1606.06160*, 2016.

A   PROOF OF LEMMA 1: AUTOMORPHISMS

In this section, we provide a simple proof for lemma 1 as well as a discussion on the continuity hypothesis.

Proof. We have that $\forall x \in \mathbb{R}_+, Q(x) \times Q(0) = Q(0)$ and $\forall x \in \mathbb{R}_+, Q(x) \times Q(1) = Q(x)$ which induces that Q is either the constant 1 or $Q(0) = 0$ and $Q(1) = 1$. Because Q is an automorphism we can eliminate the first option. Now, we will demonstrate that Q is necessarily a power function. Let n be an integer, then

$$Q(x^n) = Q(x) \times Q(x^{n-1}) = Q(x)^2 \times Q(x^{n-2}) = \cdots = Q(x)^n. \tag{6}$$

Similarly, for fractions, we get $Q(x^{\frac{1}{n}}) \times \cdots \times Q(x^{\frac{1}{n}}) = Q(x) \Leftrightarrow Q(x^{\frac{1}{n}}) = Q(x)^{\frac{1}{n}}$. Assuming Q is continuous, we deduce that for any rational $a \in \mathbb{R}$, we have

$$Q(x^a) = Q(x)^a \tag{7}$$

In order to verify that the solution is limited to power functions, we use a *reductio ad absurdum*. Assume Q is not a power function. Therefore, there exists $(x, y) \in \mathbb{R}_+^2$ and $a \in \mathbb{R}$ such that $Q(x) \neq x^a$ and $Q(y) = y^a$. By definition of the logarithm, there exists b such that $x^b = y$. We get the following contradiction, from equation 7,

$$\begin{cases} Q(x^{b^a}) = Q(y^a) = y^a \\ Q(x^{b^a}) = Q(x^{ab}) = Q(x^a)^b \neq \left(x^{ab} = y^a \right) \end{cases} \tag{8}$$

Consequently, the suited functions Q are limited to power functions *i.e.* $\mathcal{Q} = \{Q : x \mapsto x^a | a \in \mathbb{R}\}$. □

We would also like to put the emphasis on the fact that there are other Automorphisms of $(\mathbb{R}, \times)$. However, the construction of such automorphisms require the axiom of choice Herrlich (2006). Such automorphisms are not applicable in our case which is why the key constraint is being an automorphism rather than the continuous property.

B   NORM SELECTION

In the minimization objective, we need to select a norm to apply. In this section, we provide theoretical arguments in favor of the l^2 vector norm. Let F be a feed forward neural network with L layers to quantize, each defined by a set of weights $W_l = (w_l)_{i,j} \in \mathbb{R}^{n_l \times m_l}$ and bias $b_l \in \mathbb{R}^{n_l}$. We note $(\lambda_l^{(i)})_i$ the eigenvalues associated with W_l. We want to study the distance $d(F, F_a)$ between the predictive function F and its quantized version F_a defined as

$$d(F, F_a) = \max_{x \in \mathcal{D}} \|F(x) - F_a(x)\|_p \tag{9}$$

where $\mathcal{D}$ is the domain of F. We prove that minimizing the reconstruction error with respect to a is equivalent to minimizing $d(F, F_a)$ with respect to a. Assume $L = 1$ for the sake of simplicity and we drop the notation l. With the proposed PowerQuant method, we minimize the vector norm

$$\|W - Q_a^{-1}(Q_a(W))\|_p^p = \sum_{i <= n} \max_{j <= m} |w_{i,j} - Q_a^{-1}(Q_a(w_{i,j}))|^p \tag{10}$$

For $p = 2$, the euclidean norm is equal to the spectral norm, thus minimizing $\|W - Q_a^{-1}(Q_a(W))\|_2$ is equivalent to minimizing $d(F, F_a)$ for $L = 1$. However, we know that minimizing for another value of p may result in a different optimal solution and therefore not necessarily minimize $d(F, F_a)$.

In the context of data-free quantization, we want to avoid uncontrollable changes on F, which is why we recommend the use of $p = 2$.

C MATHEMATICAL PROPERTIES

C.1 LOCAL CONVEXITY

We prove that the minimization problem defined in equation 3 is locally convex around the solution a^*. Formally we prove that

$$x \mapsto \left\| x - Q_a^{-1}\left(Q_a(x)\right) \right\|_p \tag{11}$$

is locally convex around a^* defined as $\arg\min_a \left\| x - Q_a^{-1}\left(Q_a(x)\right) \right\|_p$.

Lemma 2. *The minimization problem defined as*

$$\arg\min_a \left\{ \left\| x - Q_a^{-1}\left(Q_a(x)\right) \right\|_p \right\} \tag{12}$$

is locally convex around any solution a^*.

Proof. We recall that $\frac{\partial x^a}{\partial a} = x^a \log(x)$. The function $\left\| x - Q_a^{-1}\left(Q_a(x)\right) \right\|$ is differentiable. We assume $x \in \mathbb{R}$, then we can simplify the sign functions (assume x positive without loss of generality) and note $y = \max|x|$, then

$$\frac{\partial Q_a^{-1}\left(Q_a(x)\right)}{\partial a} = \frac{\partial \left| \left\lfloor (2^{b-1}-1)\frac{x^a}{y^a} \right\rfloor \frac{y^a}{2^{b-1}-1} \right|^{\frac{1}{a}}}{\partial a}. \tag{13}$$

This simplifies to

$$\frac{\partial Q_a^{-1}\left(Q_a(x)\right)}{\partial a} = y \frac{\partial \left(\frac{\left\lfloor B\left(\frac{x}{y}\right)^a \right\rfloor}{B} \right)^{\frac{1}{a}}}{\partial a}, \tag{14}$$

with $B = 2^{b-1}-1$. By using the standard differentiation rules, we know that the rounding operator has a zero derivative a.e.. Consequently we get,

$$\frac{\partial Q_a^{-1}\left(Q_a(x)\right)}{\partial a} = -a^2 y \left(\frac{\left\lfloor B\left(\frac{x}{y}\right)^a \right\rfloor}{B} \right)^{\frac{1}{a}} \log \left(\frac{\left\lfloor B\left(\frac{x}{y}\right)^a \right\rfloor}{B} \right). \tag{15}$$

Now we can compute the second derivative of $Q_a^{-1}\left(Q_a(x)\right)$,

$$\frac{\partial^2 Q_a^{-1}\left(Q_a(x)\right)}{\partial a^2} = a^4 y \left(\frac{\left\lfloor B\left(\frac{x}{y}\right)^a \right\rfloor}{B} \right)^{\frac{1}{a}} \log^2 \left(\frac{\left\lfloor B\left(\frac{x}{y}\right)^a \right\rfloor}{B} \right). \tag{16}$$

From this expression, we derive the second derivative, using the property $(f \circ g)'' = f'' \circ g \times g'^2 + f' \circ g \times g''$ and the derivatives $|\cdot|^{\frac{1}{p}'} = \frac{x|x|^{\frac{1}{p}-2}}{p}$ and $|\cdot|^{\frac{1}{p}''} = \frac{1-p}{p^2}\frac{|x|^{\frac{1}{p}}}{x^2}$, then for any $x_i \in x$

$$\begin{aligned}
\frac{\partial^2 \left| x_i - Q_a^{-1}(Q_a(x_i)) \right|}{\partial a^2} &= \frac{1-p}{p^2} \frac{|x_i - Q_a^{-1}(Q_a(x_i))|^{\frac{1}{p}}}{(x_i - Q_a^{-1}(Q_a(x_i))^2} \left(\frac{\partial Q_a^{-1}(Q_a(x))}{\partial a} \right)^2 \\
&+ \frac{(x_i - Q_a^{-1}(Q_a(x_i))|x_i - Q_a^{-1}(Q_a(x_i)|^{\frac{1}{p}-2}}{p} \frac{\partial^2 Q_a^{-1}(Q_a(x))}{\partial a^2}
\end{aligned} \tag{17}$$

We now note the first term in the previous addition $T_1 = \frac{1-p}{p^2} \frac{|x_i - Q_a^{-1}(Q_a(x_i))|^{\frac{1}{p}}}{(x_i - Q_a^{-1}(Q_a(x_i))^2} \left(\frac{\partial Q_a^{-1}(Q_a(x))}{\partial a} \right)^2$ and the second term as a product of $T_2 = \frac{(x_i - Q_a^{-1}(Q_a(x_i))|x_i - Q_a^{-1}(Q_a(x_i)|^{\frac{1}{p}-2}}{p}$ times $T_3 = \frac{\partial^2 Q_a^{-1}(Q_a(x))}{\partial a^2}$. We know that $T_1 > 0$ and $T_3 > 0$, consequently, and T_2 is continuous in a. At a^* the terms with $|x_i - Q_a^{-1}\left(Q_a(x_i)\right)|$ are negligible in comparison with $\frac{\partial^2 Q_a^{-1}(Q_a(x))}{\partial a^2}$ and $\left(\frac{\partial Q_a^{-1}(Q_a(x))}{\partial a} \right)^2$.

Consequently, there exists an open set around a^* where $T_1 > |T_2|T_3$, and $\frac{\partial^2 |x_i - Q_a^{-1}(Q_a(x_i))|}{\partial a^2} > 0$. This concludes the proof. $\qquad\square$

Table 6: Minimization of the reconstruction error on a MobileNet V2 for W6/A6 quantization with different solvers.

Solver	a^*	reconstruction error	accuracy
Nelder-Mead	0.750	1.12	64.248
Powell (Powell, 1964)	0.744	1.10	64.104
COBYLA (Conn et al., 1997)	0.752	1.11	64.364

C.2 UNIQUENESS OF THE SOLUTION

In this section we provide the elements of proof on the uniqueness of the solution of the minimization of the quantization reconstruction error.

Lemma 3. *The minimization problem over $x \in \mathbb{R}^N$ defined as*

$$\arg\min_a \left\{ \left\| x - Q_a^{-1}(Q_a(x)) \right\|_p \right\} \tag{18}$$

has almost surely a unique global minimum a^*.

Proof. We assume that x can not be exactly quantized, *i.e.* $\min_a \left\{ \left\| x - Q_a^{-1}(Q_a(x)) \right\|_p \right\} > 0$ which is true almost everywhere. We use a *reductio ad absurdum* and assume that there exist two optimal solutions a_1 and a_2 to the optimization problem. We expand the expression $\left\| x - Q_a^{-1}(Q_a(x)) \right\|_p$ and get

$$\left\| x - Q_a^{-1}(Q_a(x)) \right\|_p = \left\| x - \left\lfloor (2^{b-1} - 1)\frac{\text{sign}(x) \times |x|^a}{\max |x|^a} \right\rceil \frac{\max |x|^a}{2^{b-1} - 1} \right\|^{\frac{1}{a}} \text{sign}(x) \right\|_p \tag{19}$$

We note the rounding term R_a and get

$$\left\| x - Q_a^{-1}(Q_a(x)) \right\|_p = \left\| x - \left| R_a \frac{\max |x|^a}{2^{b-1} - 1} \right|^{\frac{1}{a}} \text{sign}(x) \right\|_p. \tag{20}$$

Assume $R_{a_1} = R_{a_2} = R$, the minimization problem $\arg\min_a \left\| x - \left| R\frac{\max |x|^a}{2^{b-1}-1} \right|^{\frac{1}{a}} \text{sign}(x) \right\|_p$ is convex and has a unique solution, thus $a_1 = a_2$. Now assume $R_{a_1} \neq R_{a_2}$.

Let's denote $D(R)$ the domain of power values a over which we have $\left\lfloor (2^{b-1} - 1)\frac{\text{sign}(x) \times |x|^a}{\max |x|^a} \right\rceil = R$. If there is a value a outside of $D(R_{a_1}) \cup D(R_{a_2})$ such that R' has each of its coordinate strictly between the coordinates of R_{a_1} and R_{a_2}, then, without loss of generality, assume that at least half of the coordinates of R_{a_1} are further away from the corresponding coordinates of x than one quantization step. This implies that there exists a value a' in $D(R')$ such that $\left\| x - Q_{a'}^{-1}(Q_{a'}(x)) \right\|_p < \left\| x - Q_{a_1}^{-1}(Q_{a_1}(x)) \right\|_p$. which goes against our hypothesis. Thus, there are up to N possible values for R that minimize the problem which happens iff x satisfies at least one coordinate can be either ceiled or floored by the rounding. The set defined by this condition has a zero measure. □

D SOLVER FOR MINIMIZATION

In the main article we state that we can use Nelder-Mead (Nelder & Mead, 1965) solver to find the optimal a^*. We tested several other solvers and report the results in Table 6. The empirical results show that basically any popular solver can be used, and that the Nelder-Mead solver is sufficient for the minimization problem.

E COMPARISON BETWEEN LOG, NAIVE AND POWER QUANTIZATION COMPLEMENTARY RESULTS

To complement the results provided in the main paper on ResNet 50, we list in Table 7 more quantization setups on ResNet 50 as well as DenseNet 121. To put it in a nutshell, The proposed power

Table 7: Comparison between logarithmic, uniform and the proposed quantization scheme on ResNet 50 and DenseNet 121 trained for ImageNet classification task. We report for different quantization configuration (weights noted W and activations noted A) both the top1 accuracy and the reconstruction error (equation 3).

Architecture	Method	W-bit	A-bit	a^*	Accuracy	Reconstruction Error
ResNet 50	Baseline	32	32	-	76.15	-
	uniform	8	8	1	76.15	1.1×10^{-4}
	logarithmic	8	8	-	76.12	2.0×10^{-4}
	PowerQuant	8	8	0.55	**76.15**	$\mathbf{1.0} \times 10^{-4}$
	uniform	6	6	1	75.07	8.0×10^{-4}
	logarithmic	6	6	-	75.37	4.6×10^{-4}
	power (ours)	6	6	0.50	**75.95**	$\mathbf{4.3} \times 10^{-4}$
	uniform	4	4	1	54.68	3.5×10^{-3}
	logarithmic	4	4	-	57.07	2.1×10^{-3}
	PowerQuant	4	4	0.55	**70.29**	$\mathbf{1.9} \times 10^{-3}$
DenseNet 121	Baseline	32	32	-	75.00	-
	uniform	8	8	1	75.00	2.8×10^{-4}
	logarithmic	8	8	-	74.91	2.5×10^{-4}
	PowerQuant	8	8	0.60	**75.00**	$\mathbf{2.2} \times 10^{-4}$
	uniform	6	6	1	74.47	1.1×10^{-3}
	logarithmic	6	6	-	72.71	1.0×10^{-3}
	power (ours)	6	6	0.50	**74.84**	$\mathbf{0.7} \times 10^{-3}$
	uniform	4	4	1	54.83	4.7×10^{-3}
	logarithmic	4	4	-	5.28	4.8×10^{-3}
	PowerQuant	4	4	0.55	**68.04**	$\mathbf{3.1} \times 10^{-3}$

quantization systematically achieves significantly higher accuracy and lower reconstruction error than the logarithmic and uniform quantization schemes. On a side note, the poor performance of the logarithmic approach on DenseNet 121 can be attributed to the skewness of the weight distributions. Formally, ResNet 50 and DenseNet 121 weight values show similar average standard deviations across layers (0.0246 and 0.0264 respectively) as well as similar kurtosis (6.905 and 6.870 respectively). However their skewness are significantly different: 0.238 for ResNet 50 and more than twice as much for DenseNet 121, with 0.489. The logarithmic quantization, that focuses on very small value is very sensible to asymmetry which explains the poor performance on DenseNet 121. In contrast, the proposed method offers a robust performance in all situations.

F How to perform Matrix Multiplication with PowerQuant

The proposed PowerQuant method preserves the multiplication operations, *i.e.* a multiplication in the floating point space remains a multiplication in the quantized space (integers). This allows one to leverage current implementations of uniform quantization available on most hardware Gholami et al. (2021); Zhou et al. (2016). However, while PowerQuant preserves multiplications it doesn't preserve additions which are significantly less costly than multiplications. Consequently, in order to infer under the PowerQuant transformation, instead of accumulating the quantized products, as done in standard quantization Jacob et al. (2018), one need to accumulate the powers of said products. Formally, let's consider two quantized weights w_1, w_2 and their respective quantized inputs x_1, x_2. The standard accumulation would be performed as follows $w_1 x_1 + w_2 x_2$. In the case of PowerQuant, this would be done as $(w_1 x_1)^{\frac{1}{a}} + (w_2 x_2)^{\frac{1}{a}}$. Previous studies on quantization have demonstrated that such power functions can be computed with very high fidelity at almost no latency cost Kim et al. (2021).

G Limitations of the Reconstruction Error Metric

In the proposed PowerQuant method, we fit the parameter a based on the reconstruction error over all the weights, *i.e.* over all layers in the whole network. Then, we perform per-channel quantization layer by layer independently. However, if the final objective is to minimize the reconstruction

Table 8: Comparison between the per-layer and global method of power parameter a fitting on a ResNet 5à trained for ImageNet classification task.

Architecture	Method	W-bit	A-bit	Accuracy	Reconstruction Error
	Baseline	32	32	76.15	-
	per-layer	8	8	76.14	**0.8** $\times 10^{-4}$
ResNet 50	global	8	8	**76.15**	1.0 $\times 10^{-4}$
	per-layer	4	4	64,19	**1.7** $\times 10^{-3}$
	global	4	4	**70.29**	1.9 $\times 10^{-3}$

Table 9: Performance Gap as compared to Data-driven techniques on ResNet 50 quantization in W4/A4. The relative gap improvement to the state-of-the-art SQuant [6], is measured as $\frac{gs-gp}{gs}$ with $gs = \frac{*-SQuant}{*}$ and $gp = \frac{*-PowerQuant}{*}$ where $*$ is the performance of a data-driven method

data-driven method	SQuant	PowerQuant	relative gap
OCTAV Sakr et al. (2022) (ICML)	8,72%	**6,15%**	+29,47%
SQ van Baalen et al. (2022) (CVPR)	8,64%	**6,07%**	+29,74%
WinogradQ Chikin & Kryzhanovskiy (2022) (CVPR)	9,55%	**7,00%**	+26,66%
Mr BiQ Jeon et al. (2022) (CVPR)	8,74%	**6,17%**	+29,38%

error from equation equation 3, a more efficient approach would consist in fitting the parameter a separately for each layer. We note a_l^* such that for every layer l we have

$$a_l^* = \arg\min_a \left\{ \left\| W_l - Q_a^{-1}(Q_a(W_l)) \right\|_p \right\} \tag{21}$$

Then the network $(F, (a_l)^*)$ quantized with a per-layer fit of the power parameter will satisfy

$$\sum_{l=1}^{L} \left\| W_l - Q_{a_l}^{-1}(Q_{a_l}(W_l)) \right\|_p < \sum_{l=1}^{L} \left\| W_l - Q_a^{-1}(Q_a(W_l)) \right\|_p \tag{22}$$

if and only if their exists at least one l such that $a_l \neq a$. Consequently, if the reconstruction error was a perfect estimate of the resulting accuracy, the per-layer strategy would offer an even higher accuracy than the proposed PowerQuant method. Unfortunately, the empirical evidence, in table 8, shows that the proposed PowerQuant method achieves better results in every benchmark. This observation demonstrates the limits of the measure of the reconstruction error. We explain this phenomenon by the importance of inputs and activations quantization. This can be seen as some form of overfitting the parameters a_l on the weights which leads to poor performance on the activation quantization and prediction. In the general sens, this highlights the limitations of the reconstruction error as a proxy for maximizing the accuracy. Previous results can be interpreted in a similar way. For instance, in SQuant Cong et al. (2022) the author claim that it is better to minimize the absolute sum of errors rather than the sum of absolute errors and achieve good performance in data-free quantization.

H   IMPROVEMENT WITH RESPECT TO QAT

In the introduction, we argued that data-driven quantization schemes performance define an upper-bound on data-free performance. Our goal was to narrow the resulting gap between these methods. In Table 9, we report the evolution in the gap between data-free and data-driven quantization techniques. These empirical results validate the significant improvement of the proposed method at narrowing the gap between data-free and data-driven quantization methods by 26.66% to 29.74%.

I   COMPARISON TO STATE-OF-THE-ART DATA-FREE QUANTIZATION ON OTHER CONVNETS

In addition to our evaluation on ResNet, we propose some complementary results on DenseNet in Table 10 as well as the challenging and compact architectures MobileNet and EfficientNet in Table

Table 10: Comparison between state-of-the-art post-training quantization techniques on DenseNet 121 on ImageNet. We distinguish methods relying on data (synthetic or real) or not. In addition to being fully data-free. our approach significantly outperforms existing methods.

Architecture	Method	Data	W-bit	A-bit	Accuracy	gap
	Baseline	-	32	32	75.00	-
	DFQ Nagel et al. (2019)	No	8	8	74.75	-0.25
	SQuant Cong et al. (2022)	No	8	8	74.70	-0.30
	OMSE Choukroun et al. (2019)	Real	8	8	74.97	-0.03
	SPIQ Yvinec et al. (2022b)	No	8	8	**75.00**	**-0.00**
DenseNet 121	PowerQuant	No	8	8	**75.00**	**-0.00**
	DFQ Nagel et al. (2019)	No	4	4	0.10	-74.90
	SQuant Cong et al. (2022)	No	4	4	47.14	-27.86
	SPIQ Yvinec et al. (2022b)	No	4	4	51.83	-23.17
	OMSE Choukroun et al. (2019)	Real	4	4	57.07	-17.93
	PowerQuant	No	4	4	**69.37**	**-5.63**

Table 11: Complementary Benchmarks on ImageNet

Architecture	Method	Data	W-bit	A-bit	Accuracy	gap
	Baseline	-	32	32	71.80	-
	DFQ [1]	No	8	8	70.92	-0.88
	SQuant [2]	No	8	8	71.68	-0.12
	SPIQ [3]	No	8	8	71.79	-0.01
MobileNet V2	PowerQuant	No	8	8	**71.81**	**+0.01**
	DFQ [1]	No	4	4	27.1	-44.70
	SQuant [2]	No	4	4	28.21	-43.59
	SPIQ [3]	No	4	4	31.28	-40.52
	PowerQuant	No	4	4	**45.84**	**25.96**
	Baseline	-	32	32	77.10	-
	DFQ [1]	No	8	8	76.89	-0.21
	SQuant [2]	No	8	8	76.93	-0.17
	SPIQ [3]	No	8	8	77.02	-0.08
EfficientNet B0	PowerQuant	No	8	8	**77.05**	**-0.05**
	DFQ [1]	No	6	6	43.08	-34.02
	SQuant [2]	No	6	6	54.51	-32.59
	SPIQ [3]	No	6	6	74.67	-2.43
	PowerQuant	No	6	6	**75.13**	**-1.97**

11. In table 10, we report the performance of other data-free quantization processes on DenseNet 121. The OMSE method (Choukroun et al., 2019) is a post-training quantization method that leverages validation examples during quantization, thus cannot be labelled as data-free. Yet, we include this work in our comparison as they show strong performance in terms of accuracy at a very low usage of real data. As showcased in table 10, the proposed PowerQuant method almost preserves the floating point accuracy in W8/A8 quantization. Additionally, on the challenging W4/A4 setup, our approach improves the accuracy by a remarkable 12.30 points over OMSE and 17.54 points over SQuant. This is due to the overall better efficiency of non-uniform quantization, that allows a theoretically closer fit to the weight distributions of each DNN layer. The results on MobileNet and EfficientNet from Table 11 confirm our previous findings. We observe a significant boost in performance from PowerQuant as compared to the other very competitive data-free solutions.

J   OVERHEAD COST DISCUSSION

In this section, we provide more empirical results on the inference cost of the proposed method. Table 12 shows the inference time of DNNs quantized with our approach (which only implies modifications of the activation function and a bias correction-see Section 3.3). For DenseNet, ResNet and MobileNet V2, the baseline activation function is the ReLU, which is particularly fast to compute. Nevertheless, our results show that our approach leads to only increasing by 1% the whole inference

Table 12: Inference time, in seconds, over ImageNet using batches of size 16 of several networks on a 2070 RTX GPU. We also report the accuracy for W6/A6 quantization setup.

Architecture	Method	inference time (gap)	accuracy
ResNet 50	Uniform	164	75.07
	Power Function	164 (+0.2)	75.95
DenseNet 121	Uniform	162	72.71
	Power Function	167 (+4.8)	74.84
MobileNet V2	Uniform	85	52.20
	Power Function	86 (+0.7)	64.09
EfficientNet B0	Uniform	125	58.24
	Power Function	127 (+2.2)	66.38

Table 13: Inference cost each component of a convolutional layer and percentage of total in terms of number of cycles on a wide range of simulated hardware using nntool from GreenWaves.

operation	number of cycles	number of ops	% of total cycels	% of total ops
convolution	22950	442368	85.482%	99.310%
bias	2033	1024	7.573%	0.229%
relu	924	1024	3.442%	0.229%
power function	940	1024	3.502%	0.229%

Table 14: We report the processing time in seconds (on an Intel(R) Core(TM) i9-9900K CPU) required to quantize a trained neural network such as ResNet, MobileNet, DenseNet or EfficientNet.

Architecture	GDFQ	SQuant	Uniform	Power
MobileNet V2	7.10^3	134	<**1**	<**1**
ResNet 50	11.10^3	320	<**1**	1.3

time on most networks. More precisely, in the case of ResNet 50, the change in activation function induces a slowdown of 0.15%. The largest runtime increase is obtained on DenseNet with a 3.4% increase. Lastly, note that our approach is also particularly fast and efficient on EfficientNet B0, which uses SiLU activation, thanks to the bias correction technique introduced in Section 3.3. Overall, the proposed approach can be easily implemented and induces negligible overhead in inference on GPU. To furthermore justify the practicality of the proposed quantization process, we recall that the only practicality concern that may arise is on the activation function as the other operations are strictly identical to standard uniform quantization. According to Kim et al. (2021) efficient power functions can be implemented for generic hardware as long as they support standard integer arithmetic, i.e. as long as they support uniform quantization. When it comes to Field-Programmable Gate Array (FPGA), activation functions are implemented using look-up tables (LUT) as detailed in Hajduk (2017). More precisely, they are pre-computed using Padé approximation which are quotients of polynomial functions. Consequently the proposed approach would simply change the polynomial values but not the inference time as it would still rely on the same number of LUTs.

In general, activation functions that are non-linear can be very effectively implemented in quantization runtime Lam et al. (2022). However these considerations are hardware agnostic. In order to circumvent this limitation and address any concerns to our best, we conducted a small study using the simulation tool nntool from GreenWaves, a risc-v chips manufacturer that enables to simulate inference cost of quantized neural networks on their gap unit. We tested a single convolutional layer with bias and relu activation plus our power quantization operation and reported the number of cycles and operations. These results demonstrate that even without any optimization the proposed method has a marginal computational cost on MCU inference which corroborates our previous empirical results. We would like to put the emphasis on the fact that this cost could be further reduced via optimizing the computation of the power function using existing methods such as Kim et al. (2021). Similarly, we measure the empirical time required to perform the proposed quantization method on several neural networks and report the results in table 14. These results show that the proposed PowerQuant method offers outstanding trade-offs in terms of compression and accuracy at virtually no cost over the processing and inference time as compared to other data-free quantization methods. For instance, SQuant is a sophisticated method that requires heavy lifting in order to

efficiently process a neural network. On a CPU, it requires at least 100 times more time to reach a lower accuracy than the proposed method as we will showcase in our comparison to state-of-the-art quantization schemes.