PRIVACY-PRESERVING TASK-AGNOSTIC VISION TRANSFORMER FOR IMAGE PROCESSING

ABSTRACT

Distributed collaborative learning approaches such as federated and split learning have attracted significant attention lately due to their ability to train neural networks using data from multiple sources without sharing data. However, they are not usually suitable in applications where each client carries out different tasks with its own data. Inspired by the recent success of Vision Transformer (ViT), here we present a new distributed learning framework for image processing applications, allowing clients to learn multiple tasks with their private data. The key idea arises from a novel task-agnostic Vision Transformer that is introduced to learn the global attention independent of specific tasks. Specifically, by connecting task-specific heads and tails at client sides to a task-agnostic Transformer body at a server side, each client learns a translation from its own task to a common representation, while the Transformer body learns global attention between the features embedded in the common representation. To enable decomposition between the task-specific and common representation, we propose an alternating training strategy in which task-specific learning for the heads and tails is run on the clients by fixing the Transformer, which alternates with task-agnostic learning for the Transformer on the server by freezing the heads and tails. Experimental results on multi-task learning for various image processing show that our method synergistically improves the performance of the task-specific network of each client while maintaining privacy.

1 INTRODUCTION

Deep learning approaches have demonstrated the state-of-the-art performance and fast inference time in computer vision tasks (Ronneberger et al., 2015; Zhang et al., 2017a; Wang et al., 2017). In particular, convolutional neural networks (CNN) can learn the hierarchy of complex image features, so that a variety of CNN-based methods have been developed for denoising (Zhang et al., 2017b; Chang et al., 2020), deraining (Wei et al., 2019; Ren et al., 2019), deblurring (Nah et al., 2017; Kupyn et al., 2019), deblocking (Li et al., 2020a; Maleki et al., 2018), etc. However, the performance of CNN typically depends on a large number of training data (Chervenak et al., 2000; Krizhevsky et al., 2017), and it is often difficult to collect data from various entities due to privacy and regulation issues (Price & Cohen, 2019). Since the amount of data from a single source may not be enough, a deep learning framework that can leverage many datasets without violating privacy is required in real-world applications.

To address this, distributed collaborative learning (DCL) approaches, which jointly train a single network on multiple systems or devices without revealing distributed data to a central entity or to each device, have been investigated (Konečnỳ et al., 2016; McMahan et al., 2017a; Gupta & Raskar, 2018). For example, federated learning (FL) (McMahan et al., 2017a; Li et al., 2020b) is studied to aggregate all data to the center under privacy constraints. Thanks to the parallel communication between each client, FL enables fast training of the network across multiple clients. Also, split learning (SL) (Gupta & Raskar, 2018; Vepakomma et al., 2018) is developed as an enhanced privacy-preserving model that splits a network into clients and server so that each client does not share all network parameters but only train a part of networks. From the advantages of FL and SL, a combination of split and federated learning, named splitfed learning (SFL) (Thapa et al., 2020), has been recently proposed to provide efficient training and a high level of privacy with a less computational burden. However, the existing CNN-based methods are difficult to determine the proper layer of the network to split. Also, although training data are distributed across each client, all clients usually consider a common learning task.

Meanwhile, in many practical image processing applications, it is unlikely that all the clients are interested in the same applications. For example, some of the clients may be interested in image denoising (Zhang et al., 2017b), whereas the other clients are focused on image deblurring (Nah et al., 2017), deraining (Wei et al., 2019), deblocking (Li et al., 2020a), etc. As each task is different from the others, the existing distributed learning framework may not work. That said, these image processing tasks still require the understanding of common image representation, so one may wonder whether there is any systematic way of synergistically learning multiple image processing tasks in a privacy-preserving manner.

One of the most important contributions of this work is to show that *Task-agnostic Vision Transformer* (TAViT), composed of the CNN-based head and tail and ViT-based body, is nicely fit to this purpose. Specifically, the head and tail are placed on each client to learn specific image processing tasks, while the body is stored and trained on a server to learn common representation across all tasks of clients. In contrast to the existing SL framework where the network split is arbitrary, TAViT provides a systematic way of splitting neural networks between clients and servers for privacy-preserving training without losing any performance. Furthermore, TAViT allows clients to use a common Transformer body model to learn multiple image processing tasks and synergistically improve the performance of their task-specific networks.

One may think that the proposed method is similar to the image processing transformer (IPT) (Chen et al., 2020), which consists of CNN-based heads and tails and a Transformer body. However, IPT requires centralized data and large computation resources for both pretraining and task-specific fine-tuning the whole model. Also, the Transformer in IPT has an encoder-decoder architecture which needs an explicit conditioning vector to convert the Transformer for a specific task. Thus, to our best knowledge, IPT is not suitable for distributed learning. In contrast, the body of TAViT is made of an encoder-only Transformer architecture to learn global embedding features of multiple tasks without any condition. Besides, by imposing computation of this Transformer body on the server rather than clients, our framework enables clients to reduce the computational burden while maintaining the overall performance for specific image processing tasks.

In addition, TAViT views the heads and tail at the clients and the body at the server as two-part players and updates them alternately. Specifically, our training step is composed of task-specific learning and task-agnostic learning: the former is to train the client-side heads and tails to learn each task of the client, while the latter is to train the server-side Transformer body to learn general feature interpretation over multiple tasks. When there are more than two clients for any single task, parameters of their heads and tails can be aggregated through FL. Accordingly, TAViT offers seamless integration between SL and FL approaches to protect privacy.

We validate the performance of TAViT on multiple image processing tasks: deblocking, denoising, deraining, and deblurring. Experimental results show that our multi-task distributed learning framework using the alternating training strategy outperforms the end-to-end learning of each individual task thanks to the decomposition of the task-agnostic Transformer body and task-specific networks. This suggests that our framework is a promising approach for learning multiple tasks with distributed privacy-sensitive data. In sum, our contributions are summarized as follows:

- We propose a novel distributed learning framework, TAViT, that carries out multiple image processing tasks using distributed data.

- The proposed method consists of task-specific heads and tails on clients and a task-agnostic Transformer body on a server, which reduces the computational cost of clients and does not require centralized data for multi-task learning.

- An alternating training strategy between the task-specific and task-agnostic learning for the split networks shows the synergy effect of performance improvement, which is demonstrated by experimental results on multiple tasks.

2 RELATED WORKS

Federated learning   In the FL setting, multiple clients learn locally stored data while one server aggregates information of clients by various methods including *FedAvg* (McMahan et al., 2017a). For the efficient implementation of FL, practical challenges of unstable networks, hardware capacity

Figure 1: Overall framework of TAViT. (a) By subscribing a task-agnostic Transformer body, (b) clients train their heads and tails with the fixed body in parallel by task-specific learning, while a server trains the body with the fixed head and tail of randomly chosen client for each iteration by task-agnostic learning, (c) and that the body consists of encoder-only Transformer architecture.

difference, and statistical heterogeneity of data distributions (Li et al., 2020b; Smith et al., 2017; Li et al., 2018) have been actively studied. Corinzia et al. (2019) performs FL with multiple classification tasks when data for each task is distributed to each client. He et al. (2020) loads a huge network to a server and small CNNs to clients and trains them by knowledge distillation. In contrast to these approaches, our method is presented for task heterogeneity as well as distributed data so that a single framework learns multiple image processing tasks effectively.

Split learning   Split learning (SL) is designed to train networks over distributed data by splitting networks into two parts, which updates client-part and server-part networks sequentially (Gupta & Raskar, 2018). By extending this idea, Vepakomma et al. (2018) presents several ways to use SL. Also, the application SL to 1D CNN models (Abuadbba et al., 2020) and a combination of FL and SL (Thapa et al., 2020) have been developed. However, these existing split learning methods are designed for a single task using CNN-based models, and to our best knowledge, there is no principled way of splitting the network for the best performance.

Vision Transformer for image processing   Recently, inspired by the success of Transformer in natural language processing (Vaswani et al., 2017; Devlin et al., 2018), Transformer-based image processing methods have been extensively explored (He et al., 2021; Han et al., 2021). In particular, Dosovitskiy et al. (2020) proposes a Vision Transformer (ViT) with an encoder-only architecture to learn image recognition tasks. Also, Chen et al. (2020) presents an image processing Transformer (IPT) that learns low-level vision tasks by pretraining and task-specific fine-tuning. However, to the best of our knowledge, there are no existing works that exploit ViT architecture for distributed learning applications.

3   PRIVACY-PRESERVING TASK-AGNOSTIC VISION TRANSFORMER

3.1   SUBSCRIPTION-BASED SERVICE MODEL

As illustrated in Figure 1(a), TAViT is designed for subscription-based services. Specifically, a client subscribes to a task-agnostic Transformer model at the server side that has learned global attention over the image features from other datasets. Then, the client can build the head and tail proper to its own image processing task, and connect them to the Transformer body at the server. At the subscription time, there may be already multiple clients that subscribe to the same Transformer body. Accordingly, each client can train its own head and tail using its local data whereas the common Transformer body is regularly updated using embedding features from all subscribers through alternating training strategy as shown in Figure 1(b). As a result, the latest version of the Transformer body trained using more training data can be maintained on the server side so that it can be offered to new clients at the next subscription. Since the local data are not centralized to one device and are not shared with other clients, our framework can preserve data privacy.

Figure 2: Training scheme of the proposed TAViT, where S denotes a common server, and C denotes clients. The FedAvg with dashed line is applied at the weight aggregation steps.

In the proposed framework, we consider the features from the head as a sequence of tokens similar to natural language processing. Specifically, as shown in Figure 1(c), we reshape the features f with $Y \times X \times D$ size into a sequence of patches $\mathbf{f} = \{f_1, f_2, \ldots, f_S\}$, where X, Y, D denote width, height, and channel dimension of image features, respectively, S is the number of patches, i.e. $S = YX/p^2$ for patch size p, and f_s denotes the s-th patch of the features with $p^2 \times D$ size. Then, these reshaped features $\mathbf{f}$ are taken into the Transformer body as an input sequence, which is added to learnable positional embeddings to keep the position information of each feature patch. The Transformer body consists of several encoder layers proposed in Vaswani et al. (2017) so that the encoded features pass through several multi-head self-attention modules and feed-forward modules for each layer. And then, the body output of transformed features is reshaped into the original shape of features f to be used as input for the tail CNN.

Here, for the Transformer body, we employ the encoder-only architecture as a task-agnostic network, compared to IPT that uses both encoder and decoder of Transformer. The encoder-only Transformer learns the global relationship between features in the input corpus, and that global attention may be all we need for better performance in vision tasks as demonstrated in ViT. Therefore, the body of our framework can be trained to translate the input embedding features into globally self-attended features independent of specific tasks. Moreover, the heads are guided to learn the task-specific embedding from the input images to the common feature representation, and the tails are trained to learn the attended features for the specific image processing tasks. This architectural modification enables the framework to be suitable for multi-task distributed learning.

3.2 TRAINING SCHEME

For distributed datasets of different tasks, we apply the alternating training strategy between clients and the server by considering them as two players. Specifically, as shown in Figure 2, TAViT trains the client-side task-specific head and tail networks and the server-side task-agnostic body network in an alternating manner. In the task-specific learning, clients train their own heads and tails with the fixed body weights in parallel using locally stored datasets. In contrast, in the task-agnostic learning, the server trains the Transformer body with the fixed head and tail of a randomly chosen client for each iteration. More details are as follows.

3.2.1 TASK-SPECIFIC LEARNING

Let $\mathcal{C} = \bigcup_{k=1}^{K} C_k$ be a group of client sets participating different image processing tasks, where K denotes the number of tasks, and C_k has one or more clients with different datasets for the k-th task, i.e. $C_k = \{c_1^k, c_2^k, \ldots, c_{N_k}^k\}$ with $N_k \geq 1$. Each client $c \in C_k$ has task-specific own network architecture for a head H_c and a tail T_c, which are connected to the Transformer body B in the server.

In the task-specific learning, for the given freezed Transformer B at the server and the local training data $\{(x_c^{(i)}, y_c^{(i)})\}_{i=1}^{N_c}$, the c-th client then trains the neural networks H_c and T_c by solving the following

Algorithm 1 TAViT: $\mathcal{C} = \{C_1, C_2, \ldots, C_K\}$ is a group of client sets with different tasks each other. I_s and I_a denote the number of optimization iterations for each task-specific and task-agnostic step in one cycle. H_c and T_c are the head and the tail of a client c, and B is the Transformer body on the server.

Initialization: H, T to all clients, B to a body
for i in [1, num_cycles] **do**
    for i_s in [1, I_s] **do**   // task-specific learning (heads & tails)
        for each client $c \in C_k \subset \mathcal{C}$ **in parallel do**
            | update H_c, T_c with fixed B
        end
        if i_s is aggregation step **then**   // for case of multi-clients with one task
           for each client subset $C_k \subset \mathcal{C}$, s.t. $|C_k| > 1$ **do**
               | unify H_c and T_c of client $c \in C_k$ (e.g. FedAvg)
           end
        end
    end
    for i_a in [1, I_a] **do**   // task-agnostic learning (body)
         | $k \leftarrow$ randomly selected task
           update B with fixed H_c, T_c, s.t. $c \in C_k$
    end
end
Output: H, T, B

---

optimization problem:

$$\min_{H_c, T_c} \sum_{i=1}^{N_c} \ell_c(y_c^{(i)}, T_c(B(H_c(x_c^{(i)})))), \tag{1}$$

where $\ell_c(y, \hat{y})$ refers to the c-th client specific loss between the target y and the estimate $\hat{y}$. The parameters of H_c and T_c are iteratively updated using $\partial \ell_c / \partial T_c$ and $\partial \ell_c / \partial H_c$. These gradients are calculated by back-propagation through the entire model which can be expressed by the chain rule:

$$\frac{\partial \ell_c}{\partial T_c} = \frac{\partial \ell_c}{\partial \hat{y}} \cdot \frac{\partial \hat{y}}{\partial T_c} \tag{2}$$

$$\frac{\partial \ell_c}{\partial H_c} = \frac{\partial \ell_c}{\partial f_H} \cdot \frac{\partial f_H}{\partial H_c} = \frac{\partial \ell_c}{\partial f_B} \cdot \frac{\partial f_B}{\partial f_H} \cdot \frac{\partial f_H}{\partial H_c} \tag{3}$$

where $f_H = H_c(x_c^{(i)})$, $f_B = B(f_H)$ and $\hat{y} = T_c(f_B)$. This implies that to update the head H_c and the tail T_c, the gradient $\partial \ell_c / \partial f_B$ is transmitted to the server after back-propagation through the tail, and also the $\partial \ell_c / \partial f_H$ computed from back-propagation through the body is transported to each client.

Federated learning In the task-specific learning, when there are multiple clients for the same task k (i.e. $N_k > 1$), their heads and tails can be trained in parallel. Suppose that c_i^k has training dataset size of $|\mathcal{D}_i|$ and the total size of dataset in C_k is $\sum |\mathcal{D}_i| = |\mathcal{D}|$. In this case, the back-propagation and optimization process are the same with the single client case, but additionally applies *FedAvg*(McMahan et al., 2017a) to the parameters H_c and T_c of $c \in C_k$ for every assigned period, which is written as:

$$(H_{c_j}, T_{c_j}) \leftarrow \left(\sum_{i=1}^{N_k} \frac{|\mathcal{D}_i|}{|\mathcal{D}|} H_{c_i}, \sum_{i=1}^{N_k} \frac{|\mathcal{D}_i|}{|\mathcal{D}|} T_{c_i} \right), \quad \text{where } 1 \leq j \leq N_k. \tag{4}$$

The period of the weight aggregation is adjustable (50 epochs in our experiments). From this federated learning, clients corresponding to the k-th task share the same parameters at the end of task-specific learning as shown in Figure 2.

3.2.2 TASK-AGNOSTIC LEARNING

Once the heads and tails of multiple clients are trained, the Transformer body is trained by fixing the heads and tails at the clients. To train the Transformer body that learns the common representation in

a task-agnostic manner, we construct a subset of the client $\mathcal{C}_B$ by selecting one client from each task:

$$\mathcal{C}_B = \{c_{n_1}^1, c_{n_2}^2, \ldots, c_{n_K}^K\}, \quad c_{n_k}^k \in C_k. \tag{5}$$

Then, the training data $\{x_c^{(i)}, y_c^{(i)}\}_{i=1}^{N_c}$ corresponding to the task of the client are also selected, and the Transformer body in the server is updated by solving the optimization problem as follows:

$$\min_B \sum_{c \in \mathcal{C}_B} \sum_{i=1}^{N_c} \ell_c(y_c^{(i)}, T_c(B(H_c(x_c^{(i)})))). \tag{6}$$

Similar to the task-specific learning, the parameters of B are updated using $\partial \ell_c / \partial B$, where the client c is randomly chosen from $\mathcal{C}_B$ at each optimization step. The required gradients also come from back-propagation as following:

$$\frac{\partial \ell_c}{\partial B} = \frac{\partial \ell_c}{\partial f_B} \cdot \frac{\partial f_B}{\partial B}, \quad \text{where} \quad \frac{\partial \ell_c}{\partial f_B} = \frac{\partial \ell_c}{\partial \hat{y}} \cdot \frac{\partial \hat{y}}{\partial f_B}, \tag{7}$$

where $f_B = B(f_H)$ and $\hat{y} = T_c(f_B)$. Here, the gradient $\partial \ell_c / \partial f_B$ is only transported to the server after back-propagation through the tail. Through this task-agnostic learning, the Transformer body in the server learns global embedding representation and provides task-agnostic self-attended features for various image processing.

The pseudocode of the overall TAViT is described in Algorithm 1. For more details, refer to Appendix A.

4 EXPERIMENTAL RESULTS

We examine the performance of TAViT with the following image processing tasks: deblocking (JPEG artifact removal), denoising, deraining, and deblurring. With a single server, we set two clients to carry out FL on the deblocking task and set one client for each of the other tasks, so the total number of clients is five in our experiments. We evaluate results using two metrics of PSNR and SSIM.

Datasets The public datasets we used are as follows. For deblocking and denoising, we use 10,582 images from PASCAL VOC 2012 (Everingham et al., 2010) and Segmentation Boundaries Dataset (SBD) (Hariharan et al., 2011). Particularly, for FL on the deblocking, we split the data into two sets with 5,291 images and distribute them to each client. Deblocking results are evaluated on Berkely Segmentation Database (BSD500) (Martin et al., 2001b) that provides 200 test images. For the denoising, we apply random Gaussian noise with the level of $\sigma = 30$ to images. The Denoising model is evaluated on CBSD68 that contains 68 test images extracted from the BSD500. For deraining, following the experiment setting of Jiang et al. (2020), we use data from Rain14000 (Fu et al., 2017b), Rain1800 (Yang et al., 2017), Rain800 (Zhang et al., 2019), and Rain12 (Li et al., 2016) that provide 13,711 pairs of clean and synthetic rain images. Deraining results are evaluated on Rain100H and Rain100L (Yang et al., 2017), each of which has 100 synthetic rainy images. Deblurring is performed using a GoPro dataset (Nah et al., 2017) that contains 2,103 and 1,111 pairs of sharp and blurry images for training and test sets, respectively.

Implementation details To implement our TAViT, we use the encoder and decoder of DDPM (Ho et al., 2020) with three stages as our backbone of each head and tail at the client. For the Transformer body in the server, we use 8 encoder layers of the vanilla Transformer (Vaswani et al., 2017) with 256 words and 512 embedding dimensions. The total number of parameters for networks at each client and the server is about 28M and 17M, respectively. Using 4 Nvidia Quadro RTX 6000 cards and 2 Nvidia Geforce GTX 1080Ti cards, we train the networks using Adam optimizer with a learning rate of 3×10^{-5}. We initialize parameters of the networks with those of the pre-trained model by an autoencoder scheme. For the data augmentation, we apply random horizontal and vertical flipping, rotating with 90 degrees, and cropping by a patch size of $64 \times 64 \times 3$. For three cycles, by setting the batch size as 20, we perform the task-specific learning for 200, 400, 400, and 2000 epochs on deblocking, denoising, deraining, and deblurring, respectively. Also, we perform the task-agnostic learning for 1000 epochs with $1/4$ data for each task. We implement our TAViT using PyTorch library under BSD-style license using *Flower* federated learning protocol (Beutel et al., 2020) under Apache 2.0 License. The details of datasets and implementation are described in Appendix B.

4.1 RESULTS

Convergence of TAViT for multi-task distributed learning We evaluated the results of the proposed TAViT of multi-task distributed learning with all participated clients and one common Transformer body in the server. Figure 3 shows the gradual progression of quality metrics through the alternating training scheme. The performance of all tasks from our method increased and outperformed as the task-specific learning and the task-agnostic learning continued. This demonstrates the synergistic improvement of the task-specific heads/tails and the task-agnostic body: the heads and tails learn more accurate feature embedding for given tasks, and the common body learns the global attention general to multiple image processing tasks by looking at various datasets. Although there were some tasks in which the score of each step was slightly lower than that of the previous step by the interaction of different task datasets, the overall performance of TAViT was improved as the cycle progressed. Detailed quantitative results for each cycle are described in Appendix C.

Figure 3: Results of TAViT for multi-task distributed learning. Each column shows the PSNR and SSIM according to i-th cycle for the deblocking, denoising, deraining, and deblurring, respectively.

Comparison of TAViT to other strategies We compared our TAViT with other distributed learning strategies: SL and FL. We conducted both SL and FL with the two clients assigned for the deblocking task. For SL, as designed in Vepakomma et al. (2018), we placed the head and tail networks on clients and the body on the server, and trained those split networks without the weight aggregation for the head and tail. For FL, we placed the entire model composed of the head, body, and tail on each client, and trained the network in parallel by carrying out the aggregation with *FedAvg* (McMahan et al., 2017a)) using a common server. Figure 4 shows these scenarios, where C1 and C2 are clients for the deblocking, C3, C4, and C5 are clients for the denoising, deraining, deblurring, and S is the server. As reported in Table 1, the proposed method achieves better performance compared to the other strategies even though ours learns multiple tasks.

Figure 4: Scenarios of our TAViT (pink arrow) and other distributed learning strategies: (a-b) SL, and (c) FL, where C# is clients and S is the server.

Table 1: Comparison result of our TAViT to other distributed learning strategies. Q# denotes the quality of JPEG images for deblocking task.

Method	Device	Q10		Q50	
		PSNR	SSIM	PSNR	SSIM
Split learning (SL)	C1, S	27.55	0.781	32.97	0.921
Split learning (SL)	C2, S	27.51	0.781	32.88	0.921
Federated learning (FL)	C1, C2, S	27.46	0.780	32.79	0.919
TAViT (Ours)	C1, C2, S	**27.69**	**0.786**	**33.21**	**0.924**

Table 2: Comparison results on Benchmark datasets. For Transformer-based methods, EL is the end-to-end learning, STL is the single-task learning, and ours is the multi-task learning using TAViT.

Task		Method								
Dataset	**Metric**	**CNN-based**							**Transformer-based**		

Deblocking

Dataset	Metric	Input	DnCNN	AR-CNN	QCN	EL	STL	Ours
BSDS500 (Q10)	PSNR	25.67	26.70	26.42	27.66	27.67	27.59	**27.69**
	SSIM	0.719	0.755	0.777	**0.811**	0.785	0.785	0.786
BSDS500 (Q50)	PSNR	31.51	32.70	-	33.00	33.01	32.93	**33.20**
	SSIM	0.902	0.918	-	**0.934**	0.923	0.924	0.924

Denoising

Dataset	Metric	Input	CBM3D	DnCNN	FFDNet	IRCNN	DHDN	SADNet	EL	STL	Ours
CBSD68 (σ=30)	PSNR	19.03	29.71	30.32	30.31	30.22	30.41	30.64	30.43	30.65	**30.69**
	SSIM	0.336	0.843	0.861	0.860	0.861	0.864	-	0.864	0.870	**0.871**

Deraining

Dataset	Metric	Input	DerainNet	SEMI	UMRL	PreNet	MSPFN	EL	STL	Ours
Rain100H	PSNR	12.13	14.92	16.56	26.01	26.77	28.66	28.88	28.95	**29.35**
	SSIM	0.349	0.592	0.486	0.832	0.858	0.860	0.863	0.864	**0.875**
Rain100L	PSNR	25.52	27.03	25.03	29.18	32.44	32.40	32.93	32.50	**34.30**
	SSIM	0.825	0.884	0.842	0.923	**0.950**	0.933	0.937	0.935	0.949

Deblurring

Dataset	Metric	Input	DeblurGAN	Nah et al. (2017)	Zhang et al. (2018a)	DeblurGANv2	EL	STL	Ours
GoPro	PSNR	25.64	28.70	29.08	29.19	29.55	28.62	29.28	**30.06**
	SSIM	0.790	0.858	0.914	0.931	**0.934**	0.864	0.877	0.894

Comparison of TAViT to learning each separate task To verify the capability of the task-agnostic Transformer body learning multiple tasks, we compared TAViT with the models independently trained on each individual task. Under the setting of centralized data for each task, we implemented this study in two manners: end-to-end learning (EL) and single-task learning (STL). For EL, we trained the whole network in one device through the end-to-end optimization scheme. For STL, we distributed the decomposable head, body, and tail to a client and a server as the proposed method, and trained the networks by the alternating training strategy for one cycle. Table 2 reports the results on Benchmark datasets for each task. This shows that our TAViT trained on multiple tasks simultaneously outperforms both EL and STL, which suggests that the task-agnostic body of our framework does not degrade the model by task heterogeneity but enhances the performance for various tasks.

Comparison of TAViT to CNN-based models To compare the performance of TAViT with CNN-based deep learning models, we tested several existing methods on benchmark datasets for each task. Table 2 and Figure 5 show the qualitative and visual comparison results, respectively. For the deblocking, when comparing with DnCNN Zhang et al. (2017a), AR-CNN Dong et al. (2015), and QCN (Li et al., 2020a), the proposed method outperforms for both the 10 and 50 levels of quantization quality. Visual comparisons also show that the proposed method removes block artifacts clearly compared to the others. For the denoising, we compared our method with CBM3D (Dabov et al., 2007), DnCNN (Zhang et al., 2017a), FFDNet (Zhang et al., 2018b), IRCNN (Zhang et al., 2017b), DHDN (Park et al., 2019), and SADNet (Chang et al., 2020). The results show that our TAViT achieves better PSNR/SSIM scores, and also provides more clearly denoised images while preserving structure and texture details than the comparisons. For the deraining, we tested our model in addition to DerainNet (Fu et al., 2017a), SEMI (Wei et al., 2019), UMRL (Yasarla & Patel, 2019), PreNet (Ren et al., 2019), and MSPFN (Jiang et al., 2020). We used Y channel in YCbCr color space followed by Jiang et al. (2020) for the evaluation. As a result, our model outperforms the comparative methods on both Rain100H and Rain100L. Also, the images restored by ours are closer to the references by removing rain streaks than the others. For the deblurring, we employed DeblurGAN (Kupyn et al., 2018), Nah et al. (2017), Zhang et al. (2018a), DeblurGANv2 (Kupyn et al., 2019) for comparisons. The results show that the proposed method achieves comparable performance to the existing approaches. Visual results show that our TAViT restores blurry images with sharp edges, while the others still contain blurry artifacts or position shifting of objects compared to the references.

5 CONCLUSION

In this work, we present a multi-task distributed learning framework called TAViT. In TAViT, the task-specific head CNN and the tail CNN are distributed to clients that have their own data, which are

Figure 5: Visual comparisons for multiple tasks: (a) deblocking, (b) denoising, (c) deraining, and (d) deblurring. Yellow values are PSNR, and inset box is a magnified view of a red rectangle.

connected to a common Transformer body placed in the server. With an alternating training scheme, the heads and tails on client sides are trained by task-specific learning, while the body is trained by task-agnostic learning. We conduct experiments on four different image processing tasks, which show the success of task-agnostic learning of the Transformer body and its synergistic improvement with the task-specific heads and tails. We expect that the proposed TAViT can be used for efficient learning of various image processing tasks over multiple devices without sharing local data.

Ethics statement   As our work utilizes distributed learning models, potential concerns arise with the systems of FL and SL themselves that our method may be vulnerable to privacy attacks against the server such as inversion attacks (Yin et al., 2021). Although the proposed framework is designed with a deep network that performs multiple tasks by encoding the feature maps and gradients under Flower protocol to make it difficult for attackers to restore the original data, the hidden feature may leak the raw data to some degree. Thus, privacy-related techniques such as differential privacy (McMahan et al., 2017b) and authenticated encryption of data (Rogaway, 2002) should be analyzed for practical applications.

Reproducibility statement The source code and our trained models to reproduce the proposed method are available at `https://github.com/TAViT2022/TAViT`. For the detailed pseudocode, refer to Appendix A. Also, the data processing steps for datasets used in the experiments are provided in Appendix B.

REFERENCES

Sharif Abuadbba, Kyuyeon Kim, Minki Kim, Chandra Thapa, Seyit A Camtepe, Yansong Gao, Hyoungshick Kim, and Surya Nepal. Can we use split learning on 1d cnn models for privacy preserving training? In *Proceedings of the 15th ACM Asia Conference on Computer and Communications Security*, pp. 305–318, 2020.

Pablo Arbeláez, Michael Maire, Charless Fowlkes, and Jitendra Malik. Contour detection and hierarchical image segmentation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 33(5):898–916, 2011. doi: 10.1109/TPAMI.2010.161.

Daniel J Beutel, Taner Topal, Akhil Mathur, Xinchi Qiu, Titouan Parcollet, and Nicholas D Lane. Flower: A friendly federated learning research framework. *arXiv preprint arXiv:2007.14390*, 2020.

Meng Chang, Qi Li, Huajun Feng, and Zhihai Xu. Spatial-adaptive network for single image denoising. In *European Conference on Computer Vision*, pp. 171–187. Springer, 2020.

Hanting Chen, Yunhe Wang, Tianyu Guo, Chang Xu, Yiping Deng, Zhenhua Liu, Siwei Ma, Chunjing Xu, Chao Xu, and Wen Gao. Pre-trained image processing transformer. *arXiv preprint arXiv:2012.00364*, 2020.

Ann Chervenak, Ian Foster, Carl Kesselman, Charles Salisbury, and Steven Tuecke. The data grid: Towards an architecture for the distributed management and analysis of large scientific datasets. *Journal of network and computer applications*, 23(3):187–200, 2000.

Luca Corinzia, Ami Beuret, and Joachim M Buhmann. Variational federated multi-task learning. *arXiv preprint arXiv:1906.06268*, 2019.

Kostadin Dabov, Alessandro Foi, Vladimir Katkovnik, and Karen Egiazarian. Image denoising by sparse 3-d transform-domain collaborative filtering. *IEEE Transactions on image processing*, 16 (8):2080–2095, 2007.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Chao Dong, Yubin Deng, Chen Change Loy, and Xiaoou Tang. Compression artifacts reduction by a deep convolutional network. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 576–584, 2015.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Mark Everingham, Luc Van Gool, Christopher KI Williams, John Winn, and Andrew Zisserman. The pascal visual object classes (voc) challenge. *International journal of computer vision*, 88(2): 303–338, 2010.

Xueyang Fu, Jiabin Huang, Xinghao Ding, Yinghao Liao, and John Paisley. Clearing the skies: A deep network architecture for single-image rain removal. *IEEE Transactions on Image Processing*, 26(6):2944–2956, 2017a.

Xueyang Fu, Jiabin Huang, Delu Zeng, Yue Huang, Xinghao Ding, and John Paisley. Removing rain from single images via a deep detail network. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3855–3863, 2017b.

Otkrist Gupta and Ramesh Raskar. Distributed learning of deep neural network over multiple agents. *Journal of Network and Computer Applications*, 116:1–8, 2018.

Kai Han, An Xiao, Enhua Wu, Jianyuan Guo, Chunjing Xu, and Yunhe Wang. Transformer in transformer. *arXiv preprint arXiv:2103.00112*, 2021.

Bharath Hariharan, Pablo Arbeláez, Lubomir Bourdev, Subhransu Maji, and Jitendra Malik. Semantic contours from inverse detectors. In *2011 International Conference on Computer Vision*, pp. 991–998. IEEE, 2011.

Chaoyang He, Murali Annavaram, and Salman Avestimehr. Group knowledge transfer: Federated learning of large cnns at the edge. *arXiv preprint arXiv:2007.14513*, 2020.

Shuting He, Hao Luo, Pichao Wang, Fan Wang, Hao Li, and Wei Jiang. Transreid: Transformer-based object re-identification. *arXiv preprint arXiv:2102.04378*, 2021.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *arXiv preprint arXiv:2006.11239*, 2020.

Kui Jiang, Zhongyuan Wang, Peng Yi, Chen Chen, Baojin Huang, Yimin Luo, Jiayi Ma, and Junjun Jiang. Multi-scale progressive fusion network for single image deraining. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8346–8355, 2020.

Jakub Konečnỳ, H Brendan McMahan, Daniel Ramage, and Peter Richtárik. Federated optimization: Distributed machine learning for on-device intelligence. *arXiv preprint arXiv:1610.02527*, 2016.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, 60(6):84–90, 2017.

Orest Kupyn, Volodymyr Budzan, Mykola Mykhailych, Dmytro Mishkin, and Jiří Matas. Deblurgan: Blind motion deblurring using conditional adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 8183–8192, 2018.

Orest Kupyn, Tetiana Martyniuk, Junru Wu, and Zhangyang Wang. Deblurgan-v2: Deblurring (orders-of-magnitude) faster and better. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 8878–8887, 2019.

Jianwei Li, Yongtao Wang, Haihua Xie, and Kai-Kuang Ma. Learning a single model with a wide range of quality factors for jpeg image artifacts removal. *IEEE Transactions on Image Processing*, 29:8842–8854, 2020a.

Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated optimization in heterogeneous networks. *arXiv preprint arXiv:1812.06127*, 2018.

Tian Li, Anit Kumar Sahu, Ameet Talwalkar, and Virginia Smith. Federated learning: Challenges, methods, and future directions. *IEEE Signal Processing Magazine*, 37(3):50–60, 2020b.

Yu Li, Robby T Tan, Xiaojie Guo, Jiangbo Lu, and Michael S Brown. Rain streak removal using layer priors. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2736–2744, 2016.

Danial Maleki, Soheila Nadalian, Mohammad Mahdi Derakhshani, and Mohammad Amin Sadeghi. Blockcnn: A deep network for artifact removal and image compression. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 2555–2558, 2018.

D. Martin, C. Fowlkes, D. Tal, and J. Malik. A database of human segmented natural images and its application to evaluating segmentation algorithms and measuring ecological statistics. In *Proceedings Eighth IEEE International Conference on Computer Vision. ICCV 2001*, volume 2, pp. 416–423 vol.2, 2001a. doi: 10.1109/ICCV.2001.937655.

D. Martin, C. Fowlkes, D. Tal, and J. Malik. A database of human segmented natural images and its application to evaluating segmentation algorithms and measuring ecological statistics. In *Proc. 8th Int'l Conf. Computer Vision*, volume 2, pp. 416–423, July 2001b.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Statistics*, pp. 1273–1282. PMLR, 2017a.

H Brendan McMahan, Daniel Ramage, Kunal Talwar, and Li Zhang. Learning differentially private recurrent language models. *arXiv preprint arXiv:1710.06963*, 2017b.

Seungjun Nah, Tae Hyun Kim, and Kyoung Mu Lee. Deep multi-scale convolutional neural network for dynamic scene deblurring. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3883–3891, 2017.

Bumjun Park, Songhyun Yu, and Jechang Jeong. Densely connected hierarchical network for image denoising. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops*, pp. 0–0, 2019.

W Nicholson Price and I Glenn Cohen. Privacy in the age of medical big data. *Nature medicine*, 25 (1):37–43, 2019.

Dongwei Ren, Wangmeng Zuo, Qinghua Hu, Pengfei Zhu, and Deyu Meng. Progressive image deraining networks: A better and simpler baseline. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3937–3946, 2019.

Phillip Rogaway. Authenticated-encryption with associated-data. In *Proceedings of the 9th ACM Conference on Computer and Communications Security*, pp. 98–107, 2002.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 234–241. Springer, 2015.

Virginia Smith, Chao-Kai Chiang, Maziar Sanjabi, and Ameet Talwalkar. Federated multi-task learning. *arXiv preprint arXiv:1705.10467*, 2017.

Chandra Thapa, Mahawaga Arachchige Pathum Chamikara, and Seyit Camtepe. Splitfed: When federated learning meets split learning. *arXiv preprint arXiv:2004.12088*, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *arXiv preprint arXiv:1706.03762*, 2017.

Praneeth Vepakomma, Otkrist Gupta, Tristan Swedish, and Ramesh Raskar. Split learning for health: Distributed deep learning without sharing raw patient data. *arXiv preprint arXiv:1812.00564*, 2018.

Xiaolong Wang, Abhinav Shrivastava, and Abhinav Gupta. A-fast-rcnn: Hard positive generation via adversary for object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2606–2615, 2017.

Wei Wei, Deyu Meng, Qian Zhao, Zongben Xu, and Ying Wu. Semi-supervised transfer learning for image rain removal. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3877–3886, 2019.

Wenhan Yang, Robby T Tan, Jiashi Feng, Jiaying Liu, Zongming Guo, and Shuicheng Yan. Deep joint rain detection and removal from a single image. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1357–1366, 2017.

Rajeev Yasarla and Vishal M Patel. Uncertainty guided multi-scale residual learning-using a cycle spinning cnn for single image de-raining. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8405–8414, 2019.

Hongxu Yin, Arun Mallya, Arash Vahdat, Jose M Alvarez, Jan Kautz, and Pavlo Molchanov. See through gradients: Image batch recovery via gradinversion. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16337–16346, 2021.

He Zhang, Vishwanath Sindagi, and Vishal M Patel. Image de-raining using a conditional generative adversarial network. *IEEE transactions on circuits and systems for video technology*, 30(11): 3943–3956, 2019.

Jiawei Zhang, Jinshan Pan, Jimmy Ren, Yibing Song, Linchao Bao, Rynson WH Lau, and Ming-Hsuan Yang. Dynamic scene deblurring using spatially variant recurrent neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2521–2529, 2018a.

Kai Zhang, Wangmeng Zuo, Yunjin Chen, Deyu Meng, and Lei Zhang. Beyond a gaussian denoiser: Residual learning of deep cnn for image denoising. *IEEE transactions on image processing*, 26(7): 3142–3155, 2017a.

Kai Zhang, Wangmeng Zuo, Shuhang Gu, and Lei Zhang. Learning deep cnn denoiser prior for image restoration. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3929–3938, 2017b.

Kai Zhang, Wangmeng Zuo, and Lei Zhang. Ffdnet: Toward a fast and flexible solution for cnn-based image denoising. *IEEE Transactions on Image Processing*, 27(9):4608–4622, 2018b.

A   DETAILS OF TAViT WITH PSEUDOCODE

As described in the main paper, the task-specific heads and tails in clients and the Transformer body in the server are trained in an alternating manner between the proposed task-specific learning and the task-agnostic learning. In the following, we describe each step in more detail in terms of its implementation.

Pseudocode for the task-specific learning   Algorithm 2 shows the pseudocode for the task-specific learning. Given K image processing tasks, the task-specific learning updates the heads H and the tails T in each client with the fixed body B. The server first initializes global weights of the heads

---

Algorithm 2 Task-specific learning of TAViT: I_s denotes the number of iterations for the task-specific learning in one cycle. (H_c, T_c) denote the head and the tail in a client $c \in C_k$ for the k-th task, and B denotes the Transformer body in a common server. (H_{C_k}, T_{C_k}) are global weights of the heads and the tails for the task k. (f_H, f_B) are output feature maps from the head and the body, and $\hat{y}$ is the output of the tail. ℓ_c is the task-specific loss of the client c. $|\mathcal{D}_j|$ is the size of training data at c_j, and $|\mathcal{D}|$ is the total size of training data at C_k, i.e. $|\mathcal{D}|=\sum_j |\mathcal{D}_j|$.

```
/* run on the server (with fixed B) */
```
Initialize H_{C_k}, T_{C_k}
Send H_{C_k}, T_{C_k} to all clients $c \in C_k$
for i_s in $[1, I_s]$ **do**
    for each client $c \in C_k$, where $k = \{1, 2, \ldots, K\}$ **in parallel do**
        $f_H \leftarrow$ `ClientPhase1()`
        $f_B \leftarrow B(f_H)$ // body output
        $\frac{\partial \ell_c}{\partial f_B} \leftarrow$ `ClientPhase2`(f_B)
        $\frac{\partial \ell_c}{\partial f_H} \leftarrow \frac{\partial \ell_c}{\partial f_B} \cdot \frac{\partial f_B}{\partial f_H}$ // backpropagation through body
        `ClientUpdate(`$\frac{\partial \ell_c}{\partial f_H}$`)`
    end
    if i_s is weight aggregation step for $|C_k| > 1$ **then**
        Get (H_{c_j}, T_{c_j}) from client c_j, where $j \in \{1, 2, \ldots, N_k\}$
        $H_{C_k} \leftarrow \sum_{j=1}^{N_k} \frac{|\mathcal{D}_j|}{|\mathcal{D}|} H_{c_j}$ // FedAvg for head
        $T_{C_k} \leftarrow \sum_{j=1}^{N_k} \frac{|\mathcal{D}_j|}{|\mathcal{D}|} T_{c_j}$ // FedAvg for tail
        Send (H_{C_k}, T_{C_K}) to all clients $c \in C_k$
    end
end

```
/* run on client c */
```
Function `ClientPhase1()`
    $x, y \leftarrow$ set current data and label
    $f_H \leftarrow H_c(x)$ // head output
    return f_H

```
/* run on client c */
```
Function `ClientPhase2`(f_B)
    $\hat{y} \leftarrow T_c(f_B)$ // tail output
    $\ell_c \leftarrow Loss(y, \hat{y})$
    $\frac{\partial \ell_c}{\partial T_c} \leftarrow \frac{\partial \ell_c}{\partial \hat{y}} \cdot \frac{\partial \hat{y}}{\partial T_c}$ // computation of tail gradients
    $\frac{\partial \ell_c}{\partial f_B} \leftarrow \frac{\partial \ell_c}{\partial T_c} \cdot \frac{\partial T_c}{\partial f_B}$
    return $\frac{\partial \ell_c}{\partial f_B}$

```
/* run on client c */
```
Function `ClientUpdate(`$\frac{\partial \ell_c}{\partial f_H}$`)`
    $\frac{\partial \ell_c}{\partial H_c} \leftarrow \frac{\partial \ell_c}{\partial f_H} \cdot \frac{\partial f_H}{\partial H_c}$ // computation of head gradients
    update H_c, T_c using $\frac{\partial \ell_c}{\partial H_c}$ and $\frac{\partial \ell_c}{\partial T_c}$ by optimizer e.g. Adam

---

Algorithm 3 Task-agnostic learning of TAViT: I_a denotes the number of optimization iterations for task-agnostic learning in one cycle. (H_c, T_c) denote the head and tail in a client c in a client $c \in C_k$ for the k-th task, and B denotes the Transformer body in a common server. (f_H, f_B) are output feature maps from the head and the body, and $\hat{y}$ is the output of the tail. ℓ_c is the task-specific loss of the client c.

```
/* run on the server */
```
Initialize $\mathcal{C}_B = \{c_{n_1}^1, c_{n_2}^2, \ldots, c_{n_K}^K\}$ where $c_{n_k}^k \in C_k$
for i_a in $[1, I_a]$ **do**

$\quad c \leftarrow c_{n_k}^k \in \mathcal{C}_B$ `// Random selection of client with task k`

$\quad f_H \leftarrow$ `ClientPhase1()`

$\quad f_B \leftarrow B(f_H)$ `// body output`

$\quad \frac{\partial \ell_c}{\partial f_B} \leftarrow$ `ClientPhase2`(f_B)

$\quad \frac{\partial \ell_c}{\partial B} \leftarrow \frac{\partial \ell_c}{\partial f_B} \cdot \frac{\partial f_B}{\partial B}$ `// computation of body gradients`

$\quad$ update B using $\frac{\partial \ell_c}{\partial B}$ by optimizer e.g. Adam

end

```
/* run on client c (with fixed H_c, T_c) */
```
Function `ClientPhase1()`

$\quad x, y \leftarrow$ set current data and label

$\quad f_H \leftarrow H_c(x)$ `// head output`

$\quad$ **return** f_H

```
/* run on client c (with fixed H_c, T_c) */
```
Function `ClientPhase2`(f_B)

$\quad \hat{y} \leftarrow T_c(f_B)$ `// tail output`

$\quad \ell_c \leftarrow Loss(y, \hat{y})$

$\quad \frac{\partial \ell_c}{\partial f_B} \leftarrow \frac{\partial \ell_c}{\partial \hat{y}} \cdot \frac{\partial \hat{y}}{\partial f_B}$ `// backpropagation through tail`

$\quad$ **return** $\frac{\partial \ell_c}{\partial f_B^c}$

---

and the tails and sends them to all clients in C_k, where C_k is a set of clients with different datasets for the k-th task. When each client $c \in C_k$ takes local training data x and provides a feature map f_H by the head H_c to the server (line 5 with `ClientPhase1`), the server-side Transformer body takes the feature map f_H as an input embedding and estimates the self-attended features f_B that is independent of specific tasks. Once the f_B in the server is sent to the client, the client computes the task-specific loss ℓ_c between the label y and the tail output $\hat{y}$ (line 24 in `ClientPhase2`). The gradient of the tail $\partial \ell_c / \partial T_c$ is also computed in the client at `ClientPhase2` (line 25), which is used to compute $\partial \ell_c / \partial f_B$ that is transported to the server. Then, in the server, $\partial \ell_c / \partial f_H$ is calculated by backpropagation through the body, which is sent to the client so as to compute the head gradient $\partial \ell_c / \partial H_c$ and finally update H_c and T_c (lines 28-30 of `ClientUpdate`) using a single optimizer.

Here, when there are multiple clients for the k-th task, i.e. $|C_k| > 1$, we apply the federated learning for the heads and the tails of those clients as described in lines 11-16 in Algorithm 2. The heads and the tails are trained in parallel, and their weights are aggregated by *FedAvg* (McMahan et al., 2017a) on the server side for every weight aggregation period. Then, these updated global weights of the heads H_{C_k} and the tails T_{C_k} and are transmitted to all clients in C_k so that the clients train their own head and tail using the new global weights from the next step.

Pseudocode for the task-agnostic learning In the task-agnostic learning, the Transformer body in the server is updated with the fixed heads and tails of clients. Algorithm 3 shows the pseudocode for the task-agnostic learning of TAViT. Given a subset of clients, $\mathcal{C}_B$, by selecting one client among C_k for each task, the client $c \in \mathcal{C}_B$ is randomly chosen for every iteration. Then, compared to the task-specific learning, the implementation of the task-agnostic learning is similarly conducted but does not need `ClientUpdate` process in Algorithm 2. In other words, after the gradient $\partial \ell_c / \partial f_B$ is computed on the client side at `ClientPhase2` (line 14-18) and transmitted to the server (line 6), the server updates the Transformer body by computing the body gradients $\partial \ell_c / \partial B$ (lines 7-8), which is the final step of each iteration.

B DETAILS OF DATASETS AND IMPLEMENTATION

B.1 LICENSE/SOURCE FOR EACH DATASET

In our experiments, we use the public datasets for image deblocking, denoising, deraining, and deblurring tasks. Here, we describe the specific information of each data set such as license and source link.

PASCAL VOC 2012 The PASCAL VOC data set (Everingham et al., 2010) is publicly available, which includes images obtained from the "flickr" website under SmugMug or its third-party licensors. The data are protected by the United States and international intellectual property laws. The data source is from the URL: `http://host.robots.ox.ac.uk/pascal/VOC/`.

BSDS500 and CBSD68 The Berkeley Segmentation Data Set and Benchmarks 500 (BSDS500) (Arbeláez et al., 2011) data set is an extended version of BSDS300 (Martin et al., 2001b), which is a public data set originally provided for image segmentation and boundary detection by Berkeley Computer Vision Group. This data set is widely used for measuring image restoration performance. The color BSD68 data set (CBSD68) is extracted from the BSDS500. The BSDS500 can be downloaded at `https://www2.eecs.berkeley.edu/Research/Projects/CS/vision/grouping/resources.html`.

Synthetic rainy images The synthetic rainy data set for training is collected from Rain14000 synthesized by Fu et al. (2017b), Rain1800 authored by Yang et al. (2017), Rain800 created by Zhang et al. (2019), and Rain12 made by Li et al. (2016). We test our method on the synthetic rainy data sets of Rain100H and Rain100L, both of which are authored by Yang et al. (2017). All these data sets are publicly available and can be downloaded at the following links:

- *Rain14000*: `https://xueyangfu.github.io/projects/cvpr2017.html`
- *Rain1800*: `https://www.icst.pku.edu.cn/struct/Projects/joint_rain_removal.html`
- *Rain800*: `https://github.com/hezhangsprinter/ID-CGAN`
- *Rain12*: `https://yu-li.github.io/`
- *Rain100L & Rain100H*: `https://www.icst.pku.edu.cn/struct/Projects/joint_rain_removal.html`

GoPro The GoPro dataset (Nah et al., 2017) provides training and test sets for deblurring. The data are available at `https://seungjunnah.github.io/Datasets/gopro.html`.

B.2 DATA PROCESSING

All datasets we used in experiments provide natural images that have three RGB channels and pixel values with a range of [0, 255]. Upon these datasets, we performed the following data processing according to the image processing tasks.

For the image deblocking task, we quantized the images following JPEG compression. We first transformed RGB image into YUV color space using the following equations.

$$Y = 0.257R + 0.504G + 0.098B + 16 \tag{8}$$
$$U = -0.148R - 0.291G + 0.439B + 128 \tag{9}$$
$$V = 0.439R + 0.368G - 0.071B + 128 \tag{10}$$

Then, we split the image into 8x8 blocks without overlapping and apply Discrete Cosine Transform (DCT) to each block. According to the level of quantization quality, we divided each element of the DCT coefficients by proper predefined matrices. After that, we apply inverse DCT and aggregate all blocks into an image, and then, we transformed the image from YUV to RGB color space.

$$R = 1.164(Y - 16) + 1.596(V - 128) \tag{11}$$
$$G = 1.164(Y - 16) - 0.392(U - 128) - 0.813(V - 128) \tag{12}$$
$$B = 1.164(Y - 16) + 2.017(U - 128) \tag{13}$$

For the denoising task, we added Gaussian noise to the clean images. Specifically, we applied random Gaussian noise with the level of $(\mu, \sigma) = (0, 30)$ to images, and then clipped the values into [0, 255].

For the other tasks, the datasets named Rain# and GoPro provide synthetic rainy images and blurry images, respectively. Since we used these datasets for the deraining and deblurring tasks, we did not perform any preprocessing such as the synthesis of rain artifacts blurry effect.

After the above data processing for all tasks, we randomly cropped the images by a patch size of $64 \times 64 \times 3$. Also, we applied data augmentation using random flipping and rotating with 90 degrees. Then, we normalized the images with the scale of pixel values from [0,255] to [-1, 1], which are final inputs to the model.

B.3 NETWORK ARCHITECTURES

For the task-specific head and tail for each task, we use the network architecture of DDPM (Ho et al., 2020) that is composed of residual blocks and attention modules. We set the number of two-times downsampling/upsampling stages as 3. For each stage, the channel size is set as 128, 256, and 512, respectively. Accordingly, given an input image $x \in \mathbb{R}^{64 \times 64 \times 3}$, the head provides a feature map $f_H \in \mathbb{R}^{16 \times 16 \times 512}$ that passes through the body, and the tail generates an output of the same size as the input.

On the other hand, for the Transformer body, we use the encoder part of the vanilla Transformer (Vaswani et al., 2017). As described in the main paper, the Transformer body takes a sequence of patches $\mathbf{f}$ by reshaping the feature map f_H as an embedding of the words. In the experiments, the length of the input sequence is 256 by setting the patch size as 1, and the sequence dimension is 512. Then, once the input sequence is added to learnable positional encodings, the encoded features h pass through L encoder layers ($L = 8$ in our experiments). Table 3 shows the structure of each encoder layer of the body.

Table 3: The Transformer body architecture and its parameters in our experiments. For each encoder layer l, MHA is the multi-head attention modules, LN is the layer-normalization, $DropOut$ is the dropout layer, $Linear$ is the fully-connected layer, and $ReLU$ is the ReLU activation function.

Encoder layer	Parameters		
	Notation	Value	Meaning
$a^l = MHA(h^l) \in \mathbb{R}^{n \times d}$			
$u^l = LN(h^l + DropOut(a^l)) \in \mathbb{R}^{n \times d}$	L	8	The number of encoder layers
$v_1^l = ReLU(Linear(u^l)) \in \mathbb{R}^{n \times d_h}$	n	256	The length of sequence
$v_2^l = DropOut(Linear(v_1^l)) \in \mathbb{R}^{n \times d}$	d	512	The sequence dimension
$h^{l+1} = LN(u^l + v_2^l) \in \mathbb{R}^{n \times d}$	d_h	1024	The hidden dimension

Model sizes Table 4 shows the model sizes of the task-specific head and tail, and the Transformer body we used. When comparing the number of parameters and the size of networks, we can observe that the client-side networks composed of the head and the tail is larger than the task-agnostic Transformer body. Considering the experimental results in the main paper, this model size suggests that the body estimates task-agnostic self-attended features that provide the synergy effect in the task-specific and task-agnostic learning even if the body size is smaller than the sum of head and tail.

Table 4: Model sizes of the head, body, and tail in our experiment.

Network	Head	Body	Tail
# Parameters	22,341,891	16,822,272	5,610,629
Size (MB)	103.54	64.98	39.00

C EXPERIMENTAL RESULTS

C.1 TAViT ON MULTIPLE IMAGE PROCESSING TASKS

Evaluation results of TAViT Table 5 reports the quantitative evaluation results of TAViT on multiple image processing tasks, which is visualized with graphs of scores for the cycles in the main paper. Figure 6 shows the qualitative results of TAViT. This shows that the performance of each task is improved according to the cycles between the task-specific and task-agnostic learning.

Table 5: Quantitative results of TAViT according to the cycles, which are visualized with graphs in the main paper. The best results are highlighted in bold.

Task	Deblocking				Denoising		Deraining				Deblurring	
	BSDS500 (Q10)		BSDS500 (Q50)		CBSD68 ($\sigma = 30$)		Rain100H		Rain100L		GoPro	
Cycle	PNSR	SSIM	PNSR	SSIM	PNSR	SSIM	PNSR	SSIM	PNSR	SSIM	PNSR	SSIM
0.5	27.53	0.781	32.92	0.921	30.57	0.868	28.24	0.860	33.17	0.939	28.94	0.871
1.0	27.57	0.782	33.01	0.922	30.62	0.869	28.75	0.862	32.69	0.936	29.09	0.873
1.5	27.61	0.784	33.05	0.923	30.57	0.870	28.57	0.869	33.58	0.945	29.63	0.885
2.0	27.65	0.785	33.14	0.924	30.66	0.870	28.79	0.867	33.50	0.944	29.72	0.887
2.5	27.64	0.785	33.14	0.924	30.62	0.870	29.25	0.875	**34.30**	**0.949**	29.96	0.893
3.0	**27.69**	**0.786**	**33.21**	**0.924**	**30.69**	**0.871**	**29.35**	**0.875**	33.88	0.947	**30.06**	**0.894**

Figure 6: Qualitative results of TAViT according to the cycles. From the left to the right columns, the deblocking results on images with the quantization quality 10 and 50, the denoising results, the deraining results on Rain100H and Rain100L, and the deblurring results. The yellow value is PSNR, and an inset box is a magnified view of a red rectangle.

Qualitative comparisons   Besides the results presented in the main paper, here, we show more visual comparisons of our TAViT to the existing methods. Figure 7, 8, 9, and 10 display the deblocking, denoising, deraining, and deblurring results, respectively. All these results verify that our TAViT as a distributed learning for multiple image processing tasks outperforms the comparisons.

Figure 7: Visual comparisons of image deblocking task using BSDS500 (Arbeláez et al., 2011). The yellow value of each result is PSNR. We compare our TAViT with DnCNN (Zhang et al., 2017a), AR-CNN (Dong et al., 2015), and QCN (Li et al., 2020a).

Figure 8: Visual comparisons of image denoising task using CBSD68 (Martin et al., 2001a). The yellow value of each result is PSNR. We compare the proposed TAViT with CBM3D (Dabov et al., 2007), DnCNN (Zhang et al., 2017a), FFDNet (Zhang et al., 2018b), IRCNN (Zhang et al., 2017b), and DHDN (Park et al., 2019).

Figure 9: Visual comparisons of image deraining task using Rain100H and Rain100L data sets (Yang et al., 2017). The yellow value of each result is PSNR. DerainNet (Fu et al., 2017a), SEMI (Wei et al., 2019), UMRL (Yasarla & Patel, 2019), and PreNet (Ren et al., 2019) are used to compare our TAViT. (a) Results on Rain100H data set. (b) Results on Rain100L data set.

Figure 10: Visual comparisons of image deblurring task using GoPro (Nah et al., 2017) dataset. For visualization, we enlarge a region of red inset box (left column) for all images and denote PSNR of each result with yellow. We compare our TAViT with DeblurGAN (Kupyn et al., 2018), Nah et al. (2017), and DeblurGANv2 (Kupyn et al., 2019).

C.2 ABLATION STUDY OF TAViT

Study on the amount of data for each task in the task-agnostic learning In the main paper, we implemented our method using 1/4 of the dataset for each task in the task-agnostic learning. To verify that this amount of data is enough for the task-agnostic learning, we performed the ablation study using different amounts of data with a 1/2 ratio for each deblocking, denoising, deraining, and deblurring task. Table 6 and Figure 11 show the quantitative results of TAViT on the multiple tasks using 1/2 data in the task-agnostic learning. Similar to the results with a 1/4 data ratio, the scores of PSNR and SSIM tend to increase as the cycle continues. When comparing the best results from the 1/4 and 1/2 data ratio, we can observe that performance for each task using even 1/4 amount of data is comparable or better than using 1/2 data. This suggests that using 1/4 of data for each task in the task-agnostic learning is sufficient to train the Transformer body and obtain high performance.

Table 6: Quantitative results of TAViT on multiple image processing tasks with 1/2 data for each task in the task-agnostic learning. The best results are highlighted in bold.

Task	Deblocking				Denoising		Deraining				Deblurring	
	BSDS500 (Q10)		BSDS500 (Q50)		CBSD68 ($\sigma = 30$)		Rain100H		Rain100L		GoPro	
Cycle	PNSR	SSIM	PNSR	SSIM	PNSR	SSIM	PNSR	SSIM	PNSR	SSIM	PNSR	SSIM
0.5	27.53	0.781	32.92	0.921	30.57	0.868	28.24	0.860	33.17	0.939	28.94	0.871
1.0	27.57	0.782	33.02	0.922	30.62	0.869	28.78	0.862	32.47	0.933	29.18	0.875
1.5	27.63	0.784	33.10	0.923	30.58	0.870	28.92	0.867	33.28	0.942	29.63	0.887
2.0	27.65	0.785	33.15	0.924	30.67	0.870	29.18	0.870	33.71	**0.946**	29.83	0.890
2.5	27.66	0.785	33.15	0.923	30.56	0.870	29.35	0.875	**33.83**	0.945	29.94	0.893
3.0	**27.69**	**0.786**	**33.20**	**0.924**	**30.69**	0.870	**29.53**	**0.877**	33.68	0.945	**30.18**	**0.897**
* 1/4 data for each task												
Best	**27.69**	**0.786**	33.21	0.924	30.69	0.871	29.35	0.875	34.30	0.949	30.06	0.894

Figure 11: Results of TAViT with 1/2 data for each task in the task-agnostic learning. Each column shows PSNR and SSIM according to i-th cycle for the deblocking, denoising, deraining, and deblurring, respectively.

Table 7: Results of study on the weight aggregation period of FL for image deblocking task. The best results are highlighted in bold. Q# denotes the quantization quality of JPEG images.

Aggregation period	Q10		Q50	
	PSNR	SSIM	PSNR	SSIM
per 20 epochs	26.53	0.769	30.91	0.910
per 50 epochs	**27.53**	**0.781**	**32.92**	**0.921**
per 100 epochs	26.73	0.772	31.16	0.910

Study on the weight aggregation period In the main paper, we conducted the experiment of TAViT by applying FL to the deblocking task that has two clients with their own data. In FL, the weights of the network in each client are averaged in the server for every weight aggregation period

that is given as a hyperparameter. Here, since this period can influence learning performance in that the clients and the common server communicate to aggregate network weights, we performed the ablation study on the weight aggregation period for training the client-side networks. As reported in Table 7, for the deblocking task, we trained the model with the aggregation period of 20, 50, and 100 epochs. When we evaluated the deblocking results, the weight aggregation per 50 epochs provides better performance with 27.53dB/0.781 and 32.92dB/0.921 of PSNR/SSIM for the quality 10 and 50, respectively, compared to the other methods. This verifies that the weight aggregation period of 50 epochs presented in the main paper is proper to train and evaluate the proposed TAViT in our experiments.