MARKOVIAN TRANSFORMERS FOR INFORMATIVE LANGUAGE MODELING

ABSTRACT

Chain-of-Thought (CoT) reasoning holds great promise for explaining the outputs of language models, but recent studies have highlighted significant challenges in its practical application for interpretability. We propose to address this issue via two key components: a technique to factor next-token prediction through intermediate CoT text, ensuring the CoT is causally load-bearing, and a reinforcement learning approach to train CoT to predict future tokens independently of other context. This results in "Markovian" language models, where CoT serves as a fixed-size state for future token prediction. Our approach optimizes for "informativeness" – the improvement in next-token predictions using a trained CoT compared to a baseline. We demonstrate our method's effectiveness using Proximal Policy Optimization (PPO) on arithmetic problems and achieve an 11% performance boost on the GSM8K benchmark using Mistral 7B Inst V2. The increased sensitivity of model performance to CoT perturbations provides strong evidence of CoT reliance. This work advances the development of more transparent and interpretable language models, potentially enabling their extension to arbitrarily long contexts and enhancing AI reasoning capabilities across various domains.

1 INTRODUCTION

The rapid advancement of language models (LMs) has revolutionized the field of artificial intelligence, demonstrating remarkable capabilities in tackling complex cognitive tasks (Brown et al., 2020). However, it can be challenging to understand why an LM gave a particular answer (Burns et al., 2023; Gurnee & Tegmark, 2024; Lamparth & Reuel, 2023), which can be problematic in high-stakes scenarios (Rivera et al., 2024; Lamparth et al., 2024; Grabb et al., 2024). Interpretability techniques analyze the patterns and activations of a neural network in order to extract an explanation of the network's behavior (Casper et al., 2023; Meng et al., 2022; Geva et al., 2022; Geiger et al., 2022; Wang et al., 2022; Nanda et al., 2023; Lamparth & Reuel, 2023). However, since language models already speak natural language and have been trained to be able to use their own internal representations, we could in principle simply ask the language model why it gave a particular answer to a question. Asking the language model to explain its reasoning in a "step-by-step" fashion before answering a question is known as Chain-of-Thought (CoT) (Wei et al., 2022; Nye et al., 2022) prompting.

However, there are concerns that CoT is an inadequate or *unfaithful* explanation for LM-generated text. For example, Turpin et al. (2023) show that biasing the LM to believe a particular answer via a supposedly irrelevant in-context feature such as multiple choice answer order will cause the CoT to rationalize that answer without mentioning the background feature. Also some LMs give the same answers to questions despite changes to the CoT reasoning in their context window (Lanham et al., 2023). While this has some benefits – the model can still answer correctly despite intermediate reasoning errors – it is also an indicator that the CoT does not fully capture the LM's reasoning process. This raises a critical issue with using CoT as a tool for interpretability.

Our work introduces a novel perspective on this issue. Rather than aiming for faithfulness – which implies that the CoT reflects some underlying causal process in the model – we focus on *informativeness*. Our key insight is to make the CoT text itself causally important in the model's reasoning. We propose a reinforcement learning (RL) based training technique that trains an LM to generate a minimal-length CoT such that the model can predict the answer given *only* that CoT. This approach

ensures that the CoT is not merely an ex-post rationalization but an integral, causal component of the reasoning process.

Ideally, a CoT explanation would be both *complete* (i.e., each necessary step is included) and *maximally fragile* (i.e., removing or changing the meaning of any step breaks the CoT and thus leads to a different result). Our approach aims to achieve these properties by making the CoT itself a bottleneck in the flow of information that the language model uses to produce text.

We assume the LM receives a sequence of *observations* to predict – this could be a question-answer pair (length two sequence) or many adjacent segments of generic internet text. Our conceptual arguments rely on the size of each observation being larger than the CoT – otherwise the LM could put the answer immediately in the CoT. Though for pragmatic reasons we use short observations, the model does not learn the undesirable behavior of directly answering in the CoT due to the relative difficulty of predicting the answer without any CoT.

The primary contributions of this work are:

1. We introduce a formal definition of informativeness which is used as an optimization target.

2. We demonstrate our training algorithm's effectiveness by training Mistral 7B (Jiang et al., 2023) to solve fifteen-term arithmetic problems and achieve an 11% performance gain on the GSM8K (Cobbe et al., 2021) reasoning dataset.

3. We verify that the model utilizes the generated CoT during inference, ensuring that the model's future token distribution is inherently a function of the CoT.

4. We validate that the generated CoT is meaningful and usable by other models, showcasing its interpretability and transferability.

By making CoT causally important in the model's reasoning, we aim to improve the interpretability and reliability of language models. This approach offers a novel perspective on understanding and steering LM behavior by leveraging the model's own generated explanations, rather than relying solely on the analysis of its internal parameters.

Figure 1: Refined illustration of the training method. Left: Single timestep process from Question to CoT to Answer. Right: Causal structure showing the generation of states from observations and previous states using the state update function $u_\theta(s'|o, s)$, and the prediction of observations from states using the policy $\pi(o|s)$. Observations are generated by the causal data distribution. In experiments, both u_θ and π are Mistral 7B Inst V2, but only the weights of u_θ are updated during training. The state update u_θ also involves concatenating the observation and state letting Mistral generate the next state's worth of tokens.

2 RELATED WORK

Prior work shows that CoT prompting improves language model reasoning capabilities (Wei et al., 2022; Nye et al., 2022). We *train* the model to produce a strong CoT, as opposed to prompting

Figure 2: The log probability $\ln \pi(ans \mid cot)$ of the answer ans given a CoT cot, where cot is sampled from the trained weights $cot \sim u_\theta(cot \mid q, cot_{init})$ and cot' is sampled from the unmodified weights $cot' \sim u(cot \mid q, cot_{init})$. We train to produce CoTs which are sufficient to predict the correct answer even without the original question, enforcing a text bottleneck in the language model's information flow, forcing the CoT to be causally load-bearing to production of the answer. Because of high variance, we plot the point-wise maximum for each training technique across 4 separate training runs.

strategies as in Wei et al. (2022). Scratchpad (Nye et al., 2022) also trains the model to produce a CoT, but they supply correct CoTs during training, whereas our model has to discover useful CoTs for itself. Zelikman et al. (2024) also use RL to improve CoT reasoning, but they do not restrict the model's attention to the previously generated CoT, making the CoT less of a standalone explanation. State space models also generate state to remember their history (Gu et al., 2021; 2022; Gu & Dao, 2023), but we use natural language instead of activation vectors for interpretability.

Lyu et al. (2023) improved faithfulness of language model reasoning by restricting the output to a particular formal language so that a deterministic solver could provide the rest of the answer, whereas we do not restrict to production of a formal language, because our future goal is to target general language modeling. Ranaldi & Freitas (2024) directly fine-tune a smaller model using CoT from a more capable model. In contrast, we do not require the existence of a more competent model to learn useful CoTs. Lanham et al. (2023) use robustness to reasoning perturbations as an indicator of unfaithfulness, which we adapt by replacing the variation in multiple choice accuracy with the variation in log probability assigned to the correct observation. Bentham et al. (2024) respond that robustness might simply be an indicator of accuracy, which we ameliorate by removing history from the context window. In order to address this concern more thoroughly, we would need to demonstrate the ability to further compress our CoTs.

3 MARKOVIAN LANGUAGE MODELS AND INFORMATIVENESS OF UPDATE FUNCTIONS

We would like a mathematical structure which describes the shape of a language model with a CoT bottleneck, so that we can derive an reinforcement learning algorithm with respect to that formalism. For this reason, we introduce the concept of Markovian Language Models and define a measure of informativeness for their update functions.

3.1 MARKOVIAN LANGUAGE MODELS

A regular autoregressive LM can use its entire context when predicting the next token. In particular, when the LM takes a question, produces some reasoning and finishes with a final answer, the generation of the final answer can still attend back to the question. Thus, there is no guarantee that the CoT is causally linked to the answer tokens. In contrast, in a Markovian LM, the model is only given access to limited state to make predictions.

Formally, we define a Markovian Language Model as a tuple $M = (\mathcal{V}, \mathcal{S}, \pi, u, s_1)$, where:

- $\mathcal{V}$ is a finite vocabulary,
- $\mathcal{S}$ is a set of states, representing CoT reasoning,
- $\pi : \mathcal{S} \to \Delta(\mathcal{V}^k)$ is a state-conditional distribution over k-token sequences, where $\Delta(\mathcal{V}^k)$ is the probability simplex over k-token sequences from $\mathcal{V}$,
- $u : \mathcal{V}^k \times \mathcal{S} \to \Delta(\mathcal{S})$ is a stochastic update function,
- $s_1 \in \mathcal{S}$ is the initial state.

The MLM operates sequentially: given a current state $s_t \in \mathcal{S}$ and observation $x_t \in \mathcal{V}^k$, it produces a probability distribution $\pi(s_t)$ over the next k-token sequence, and stochastically updates its state to $s_{t+1} \sim u(s_t, x_t)$.

3.2 Data-Generating Distribution

Let P be the true data-generating distribution over sequences of length T. We can sample from this distribution using:

$$x_t \sim P(x_t | x_{<t}) \quad \text{for } t = 1 \text{ to } T \tag{1}$$

where $x_{<t}$ denotes all observations before time t.

3.3 Parameterized Update Function

We consider a parameterized update function u_θ, where θ represents the parameters to be optimized. We compare this to a baseline update function u', which uses the original set of weights before fine-tuning. Both u_θ and u' operate in conjunction with the same prediction function π, which also uses the original set of weights.

3.4 Informativeness of Update Functions

We define the informativeness of the update function u relative to a baseline update function u' as:

$$I(u, u', P) = \mathbb{E}_{\tau \sim P, u, u'}[R(\tau)] \tag{2}$$

where $\tau = (x_1, s_1, s'_1, ..., x_T, s_T, s'_T)$ is a trajectory, with:

- $x_t \sim P(x_t | x_{<t})$
- $s_{t+1} \sim u(s_{t+1} | x_t, s_t)$
- $s'_{t+1} \sim u'(s'_{t+1} | x_t, s'_t)$

The reward $R(\tau)$ for a trajectory is defined as:

$$R(\tau) = \sum_{t=1}^{T}[\ln \pi(x_t | s_t) - \ln \pi(x_t | s'_t)] \tag{3}$$

Now, let's consider optimizing this informativeness using policy gradient methods. We parameterize u by some weights θ, giving us u_θ. The objective function is:

$$J(\theta) = I(u_\theta, u', P) \tag{4}$$

The gradient of this objective with respect to θ is:

$$\nabla_\theta J(\theta) = \mathbb{E}_{\tau \sim P, u_\theta, u'} \left[R(\tau) \sum_{t=1}^{T-1} \nabla_\theta \ln u_\theta(s_{t+1} | x_t, s_t) \right] \tag{5}$$

In practice, we estimate this gradient using Monte Carlo sampling:

$$\nabla_\theta J(\theta) \approx \frac{1}{N} \sum_{i=1}^{N} R(\tau^{(i)}) \sum_{t=1}^{T-1} \nabla_\theta \ln u_\theta(s_{t+1}^{(i)} | x_t^{(i)}, s_t^{(i)}) \tag{6}$$

where $\{\tau^{(i)} = (x_1^{(i)}, s_1^{(i)}, s_1'^{(i)}, ..., x_T^{(i)}, s_T^{(i)}, s_T'^{(i)})\}_{i=1}^{N}$ are sampled trajectories.

This procedure improves the update function u_θ to generate more informative CoT reasoning, leading to better predictions of future observations.

4 METHODS

4.1 MARKOVIAN LANGUAGE MODEL FOR QUESTION-ANSWER PAIRS AND OPTIMIZATION

We define a specialized Markovian Language Model (MLM) for question-answer pairs as a 5-tuple $M = (\mathcal{V}, \mathcal{S}, \pi, u, s_1)$, where:

- $\mathcal{V}$ is the vocabulary of tokens.
- $\mathcal{S} = \mathcal{V}^\ell$ is the set of all possible CoT sequences of length ℓ.
- $\pi : \mathcal{S} \to \Delta(\mathcal{V}^\ell)$ is the prediction function.
- $u : \mathcal{S} \times \mathcal{V}^\ell \to \Delta(\mathcal{S})$ is the update function.
- $s_1 = \text{cot}_{\text{init}} \in \mathcal{S}$ is the initial state, where cot_{init} is a fixed initial prompt.

Let $\ell_q = \ell_a = \ell$ be the length of an observation (question or answer). We implement the MLM specification using a language model $\mathcal{L} : \mathcal{V}^* \to \Delta(\mathcal{V})$, where $\mathcal{L}(s)$ gives the probability distribution over the next token given the sequence s. We denote the i-th tokens of the CoT and answer as cot_i and ans_i, respectively.

The model operates as follows:

1. Update function u:

$$\ln u(s_2 = \text{cot} | o_1 = q, s_1 = \text{cot}_{\text{init}}) = \sum_{i=1}^{\ell} \ln \mathcal{L}(\text{concat}(q, \text{cot}_{\text{init}}, \text{cot}_{<i}))[\text{cot}_i] \tag{7}$$

   We implement $\ln u$ by concatenating the question with cot_{init} and summing the log probability of each token conditioned on the previous tokens and the prefix.

2. Prediction function π:

$$\ln \pi(o_2 = \text{ans} | s_2 = \text{cot}) = \sum_{i=1}^{\ell} \ln \mathcal{L}(\text{concat}(\text{cot}, \text{ans}_{<i}))[\text{ans}_i] \tag{8}$$

4.2 THRESHOLD-BASED EXPERT ITERATION, POLICY GRADIENT, AND PROXIMAL POLICY OPTIMIZATION

We explore three RL techniques to optimize the language model for informative CoT production: Threshold-based Expert Iteration, Policy Gradient, and Proximal Policy Optimization. All three implementations use a form of importance sampling to focus updates on more informative CoTs. All three implementations are concisely contained within a single Python file, which we have made freely available.

4.2.1 THRESHOLD-BASED EXPERT ITERATION (TEI)

Threshold-based Expert Iteration consists of the following steps:

1. Sample a CoT from a trained and untrained model (cot and cot')

2. Estimate informativeness as $I(ans, cot, cot') = \pi(ans|cot) - \pi(ans|cot')$

3. If I is at least one standard deviation above the historical average:
   - Calculate the gradient of the log probability of having produced that CoT: $\nabla_\theta \ln u_\theta(cot|q, cot_{init})$
   - Gradient ascend

Limitation: This technique potentially discards valuable information, as we might prefer to update more strongly towards CoTs that produce very high rewards.

4.2.2   POLICY GRADIENT (PG)

Policy Gradient (with threshold-based sample selection) consists of the following steps:

1. Sample a CoT from a trained and untrained model (cot and cot')

2. Estimate informativeness as $I(ans, cot, cot') = \pi(ans|cot) - \pi(ans|cot')$

3. If I is at least one standard deviation above the historical average:
   - Calculate the gradient of the log probability of having produced that CoT: $\nabla_\theta \ln u_\theta(cot|q, cot_{init})$
   - Multiply the gradient by I and then ascend

Advantage: Utilizes more information than TEI
Disadvantage: Increased instability, which can be problematic given pre-trained initial weights

4.2.3   PROXIMAL POLICY OPTIMIZATION (PPO)

For each CoT, PPO performs the following:

1. Calculate the probability ratio: $r = \frac{u_\theta(cot|q, cot_{-1})}{u'(cot|q, cot_{-1})}$

2. Compute the clipped objective:
$$\text{obj} = \min(r \cdot I, \text{clip}(r, 1 - \epsilon, 1 + \epsilon) \cdot I)$$

   where:
   - $I = \text{Informativeness}(ans, cot, cot')$
   - $\text{clip}(x, y, z) = \begin{cases} y & \text{if } x < y \\ z & \text{if } x > z \\ x & \text{otherwise} \end{cases}$
   - $\epsilon = 0.2$

3. Backpropagate to increase obj

Key Idea: Remove the incentive to create CoTs for which the trained and untrained state update functions disagree too much.

Implementation Details:

- We use threshold-based sample selection here as well
- Subtract the historical average informativeness over unfiltered CoTs from the current informativeness as a baseline

4.3   STABILITY-ENHANCING TRAINING TECHNIQUES

Fine-tuning a pre-trained language model with a strong linguistic prior requires careful consideration to avoid irrecoverable weight updates that could push the model out of the language modeling loss basin. In addition to the PPO-clip objective mentioned in Sec. 4.2.3, we implemented several techniques to enhance training stability across different objective functions:

1. **Low-Rank Adaptation (LoRA):**

- Freeze all weights except for a set of LoRA weights (Hu et al., 2022)
- Use rank 8 with $\alpha = 1$

2. **Gradient Clipping:**
   - If the L_2 norm of the gradient update vector exceeds 1, normalize the vector

3. **Gradient Accumulation:**
   - Set batch size to 6 to optimize H100 GPU memory usage
   - Perform 8 gradient accumulation steps between weight updates

4. **Average Reward Baseline:**
   - For PPO: Subtract the previous average of rewards from the current reward
   - Found to be as beneficial as a value head, with less hyper-parameter tuning required

5. **Selection of cot_{init}:**
   - Choose cot_{init} to bias CoT search in a productive direction
   - For arithmetic we used "You will be given an arithmetic problem, which you have [cot length] tokens to work through step-by-step. Question"
   - For GSM8K we used "You will be given a reasoning problem, which you have [cot length] tokens to work through step-by-step. Question"

5 EXPERIMENTS

5.1 MULTI-STEP ADDITION AND GSM8K

Figure 3: GSM8K performance metrics over training batches. The plot shows the moving average (window size: 100) of the fraction of questions in the current batch where the model samples the correct answer, and the plot also shows the proportion of CoTs which contain the answer verbatim. Note that our test set performance of 35.71% seems high when compared the training curve. This could be potentially be an artifact of the size 100 curve smoothing, and for full transparency we have included test set evaluation logs in the supplementary material.

We generate random addition problems, where each problem consists of 15 terms and each term is a uniform random natural number less than 100. We fine-tune Mistral 7B Instruct V0.2 to produce CoT tokens such that a frozen copy of the pre-trained language model can predict the correct answer given that CoT, for each training technique in Methods. We plot the mean negative log likelihood over the answer tokens as a function of training batch in Fig. 2. Note that this is both training and testing loss, since we are always generating fresh arithmetic problems. PPO, our preferred training method, can mention the correct answer in up to 90% of CoTs and achieve an average natural log probability of around -0.7.

Since the Mistral tokenizer allocates a separate token for each digit, a natural log probability of -0.7 corresponds to an actual probability of $e^{-0.7} \approx 0.4966$, or 50% chance of picking the correct

next token on average. A 90% likelihood saying the answer verbatim in the CoT and a 50% of guessing each digit incorrectly may seem contradictory – however this discrepancy is due to the predictor model's uncertainty around prompt formatting, and specifically about what tokens should come after "Answer:". So it is distributing probability mass over the entire vocabulary including non-numerical tokens, since we are only training CoT production $u_\theta(s'|o, s)$, as opposed to training the predictor model $\pi(o|s)$.

Also using PPO, we train Mistral to produce CoT over the GSM8K train set, and we observe an increase in Mistral's performance on the test set from 24.64% n=1 to 35.71% n=1 accuracy. We used 32 gradient accumulation steps, 80 CoT tokens, and batch size 10. We also removed the average reward baseline, though we suspect that in this case this is relatively unimportant to performance.

Figure 4: Comparison of different perturbation effects on CoT reasoning. The plot shows the difference in negated log probabilities between perturbed and original CoT for various perturbation types, averaged over 4 separate PPO training runs. Higher values indicate worse performance compared to the original. Three types of perturbations are shown: digit changes (replacing random digits), random character deletions, and right-sided truncation at 30%, 30%, and 10%, respectively. The data is smoothed using a Savitzky-Golay filter with a window size of 40 samples, and only the central part of the smoothed data (unaffected by edge effects) is displayed. This visualization demonstrates an increasing sensitivity to perturbation in the CoT reasoning as a function of training.

5.2 MEASURING FRAGILITY OF COT

Expanding upon Lanham et al. (2023), we measure the fragility of the CoT reasoning by applying three perturbations to the model-generated reasoning and evaluate how this affects the next-token-prediction loss of the correct answer to the original question. Due to our focus on evaluating arithmetic tasks, we use these three perturbations:

- Truncating a fraction of the CoT reasoning from the end

- Flipping any number (digit) with a probability in the CoT reasoning and replacing it with another random number between 0 and 9

- Swapping a fraction of characters with random characters in the CoT reasoning. The selection is limited to numbers from 0 to 9, letters from the English alphabet, and simple arithmetic symbols (e.g., "+" and "-")

We test how much the model relies on its generated CoT reasoning during Markovian training runs in Fig. 4. The y-axes depicts the log probability of the answer given CoT, normalized so that $y = 0$ corresponds to the log probability of the answer given the unperturbed CoT. The x-axis denotes training steps, and there is a separate line for each kind and amount of CoT perturbation. At the

start of training, when the language model is essentially completely surprised by the answer, the various perturbations are actually mildly helpful. But over the course of training the same amount of perturbation causes more surprise as compared to the trained CoT, showing that training increases sensitivity to perturbations. Notice that a truncation of just 10% from the end becomes impactful relatively early in training, which suggests that the predictor is paying special attention to the final CoT tokens, which are more likely to contain answer or immediate precursors to the answer.

5.3 INTERPRETABILITY OF CoT GENERATIONS

Figure 5: Comparison of the log probabilities between the original Mistral model and the Llama 7B model, averaged across 4 separate PPO training runs. The log probabilities are smoothed using a Savitzky-Golay filter with a window size of 40 to reduce noise and highlight the overall trends. The plot shows that improvements in CoT from Mistral's perspective also correspond to improvements in CoT from Llama's perspective. Llama's understanding of Mistral's trained CoT gives evidence that humans will also understand Mistral's trained CoT.

To probe how well the reasoning generalizes, we plot the log probabilities that Llama-2-7b-Instruct Touvron et al. (2023) (LLAMA 2 Community License) ascribes to the answer given trained Mistral's CoT in Fig. 5. In both plots the log probabilities increase simultaneously, demonstrating that Mistral is learning to produce generic CoTs which do not overfit to the peculiarities of a Mistral answer-predictor. This lends support to the idea that this training procedure leads to human-interpretable CoTs.

6 DISCUSSION AND LIMITATIONS

Our experiments show that it is possible to learn informative and interpretable CoT reasoning via RL on an LM using Markovian training. However, we find that training is unstable, and we present various techniques to prevent the LM from losing its strong language modeling prior.

A weakness in our interpretability argument is that for stability we use more CoT than answer tokens, so in principle the LM could learn to put the answer in the CoT directly. However, this does not affect our particular experiment because Mistral struggles to learn to add fifteen terms without intermediate reasoning. Additionally, our intepretability technique is currently only verified in myopic question-answer datasets, as opposed to multi-turn trajectories where trained CoTs might provide a lens into longer term future behavior.

Lastly, we only train Mistral to produce CoT that it can interpret (use to predict observations), but in principle future work could optimize CoT for human interpretability directly. (See Appendix E for details.)

Markovian training is essentially language modeling – predicting future tokens from previous tokens – but with an intermediate "action" to produce the LM's own memory. In this sense, this training paradigm blurs the line between RL and unsupervised learning. But since it comes at the cost of adding expensive serial token generation steps in an otherwise highly parallelizeable unsupervised training regime, it would need to have a high payoff in terms of interpretability or perplexity in order to be feasible. But as it stands, we have only tested the technique on question-answer pairs, and we have not yet justified its performance in the context of more general language modeling. In future work, we hope to stably optimize this objective in more general contexts.

7 ETHICS STATEMENT

Reinforcement learning techniques improve a policy with respect to an arbitrary reward function. But it can be difficult to mathematically specify nuanced human preferences about the policy. Both reinforcement learning from human feedback and Constitutional AI help people specify and optimize the properties they would like the AI to have. This increase in controllability makes the AI more of an extension of human intention, for better or for worse. The approach of this paper is much more targeted – we use RL to specifically increase an agent foresight – its ability to predict its future observations.

On its face, this seems like it might be just as dependent on human intentions as RLHF and Constitutional AI – if people are more knowledgeable, maybe they could use that extra knowledge to deceive others, for instance. However, better foresight may also give rise to better values, where values are opinions about how to act such that the collective system can attain better foresight.

8 REPRODUCIBILITY STATEMENT

To ensure reproducibility, we provide comprehensive supplementary materials including all source code, training and evaluation scripts, and detailed instructions in the README. The main training loop (`src/policy_gradient_normalized.py`) supports various RL methods, with usage instructions in the README. For GSM8K results, we include the specific training command and note that setting the "r" hyperparameter to None achieved 35.71% accuracy, though this may not be crucial. Evaluation scripts for GSM8K (`src/AnalyzeResults/eval_gsm8k.py`) and CoT accuracy (`src/eval_cot_answer_accuracy.py`) are provided to verify our claims and reproduce Figures 2 and 3. The `results/Official` directory contains all plots, full training logs, and evaluation logs from our experiments. We use the public GSM8K dataset and Mistral 7B Inst V2 model, with any preprocessing steps detailed in code comments. All hyperparameters are specified in the scripts and documented in the README, along with environment setup instructions. With these materials, researchers should be able to reproduce our work, including the 11% performance boost on GSM8K and the perturbation analysis results demonstrating CoT reliance.

REFERENCES

Oliver Bentham, Nathan Stringham, and Ana Marasović. Chain-of-thought unfaithfulness as disguised accuracy, 2024. URL https://arxiv.org/abs/2402.14897.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf.

Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=ETKGuby0hcs.

Stephen Casper, Tilman Rauker, Anson Ho, and Dylan Hadfield-Menell. Sok: Toward transparent AI: A survey on interpreting the inner structures of deep neural networks. In *First IEEE Conference on Secure and Trustworthy Machine Learning*, 2023.

Paul Christiano, Ajeya Cotra, and Mark Xu. Eliciting latent knowledge: How to tell if your eyes deceive you, December 2021. URL `https://docs.google.com/document/d/1WwsnJQstPq91_Yh-Ch2XRL8H_EpsnjrC1dwZXR37PC8/edit`.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021. URL `https://arxiv.org/abs/2110.14168`.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Graeme Nail, Gregoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel Kloumann, Ishan Misra, Ivan Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuenley Chiu, Kunal Bhalla, Lauren Rantala-Yeary, Laurens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Mahesh Pasupuleti, Mannat Singh, Manohar Paluri, Marcin Kardas, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Nikolay Bashlykov, Nikolay Bogoychev, Niladri Chatterji, Olivier Duchenne, Onur Çelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasic, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong, Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ronnie Polidoro, Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sahana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stephane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujjwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whitney Meers, Xavier Martinet, Xiaodong Wang, Xiaoqing Ellen Tan, Xinfeng Xie, Xuchao Jia, Xuewei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yi Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie Delpierre Coudert, Zheng Yan, Zhengxing Chen, Zoe Papakipos, Aaditya Singh, Aaron Grattafiori, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adithya Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alex Vaughan, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Franco, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Bernie Huang, Beth Loyd, Beto De Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Changhan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai,

Chris Tindal, Christoph Feichtenhofer, Damon Civin, Dana Beaty, Daniel Kreymer, Daniel Li, Danny Wyatt, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkang Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil, Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Firat Ozgenel, Francesco Caggioni, Francisco Guzmán, Frank Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Govind Thattai, Grant Herman, Grigory Sizov, Guangyi, Zhang, Guna Lakshminarayanan, Hamid Shojanazeri, Han Zou, Hannah Wang, Hanwen Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Ibrahim Damlaj, Igor Molybog, Igor Tufanov, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kai Wu, Kam Hou U, Karan Saxena, Karthik Prasad, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kun Huang, Kunal Chawla, Kushal Lakhotia, Kyle Huang, Lailin Chen, Lakshya Garg, Lavender A, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabsa, Manav Avalani, Manish Bhatt, Maria Tsimpoukelli, Martynas Mankus, Matan Hasson, Matthew Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Maya Lathi, Meghan Keneally, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Munish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navyata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikolay Pavlovich Laptev, Ning Dong, Ning Zhang, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pedro Rittner, Philip Bontrager, Pierre Roux, Piotr Dollar, Polina Zvyagina, Prashant Ratanchandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Rohan Maheswari, Russ Howes, Ruty Rinott, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, Sasha Sidorov, Satadru Pan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lindsay, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Cindy Zha, Shiva Shankar, Shuqiang Zhang, Shuqiang Zhang, Sinong Wang, Sneha Agarwal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield, Sudarshan Govindaprasad, Sumit Gupta, Sungmin Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Kohler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria Ajayi, Victoria Montanez, Vijai Mohan, Vinay Satish Kumar, Vishal Mangla, Vítor Albiero, Vlad Ionescu, Vlad Poenaru, Vlad Tiberiu Mihailescu, Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xiaocheng Tang, Xiaofang Wang, Xiaojian Wu, Xiaolan Wang, Xide Xia, Xilun Wu, Xinbo Gao, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li, Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu, Wang, Yuchen Hao, Yundi Qian, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, and Zhiwei Zhao. The llama 3 herd of models, 2024. URL https://arxiv.org/abs/2407.21783.

Wikimedia Foundation. Wikipedia, 2024. URL https://dumps.wikimedia.org.

Atticus Geiger, Zhengxuan Wu, Hanson Lu, Josh Rozner, Elisa Kreiss, Thomas Icard, Noah Goodman, and Christopher Potts. Inducing causal structure for interpretable neural networks. In *International Conference on Machine Learning (ICML)*, pp. 7324–7338. PMLR, 2022.

Mor Geva, Avi Caciularu, Kevin Ro Wang, and Yoav Goldberg. Transformer feed-forward layers build predictions by promoting concepts in the vocabulary space. *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 30–45, 2022.

Declan Grabb, Max Lamparth, and Nina Vasan. Risks from language models for automated mental healthcare: Ethics and structure for implementation. *medRxiv*, 2024. doi: 10.1101/2024. 04.07.24305462. URL https://www.medrxiv.org/content/early/2024/04/08/2024.04.07.24305462.

Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces, 2023. URL https://arxiv.org/abs/2312.00752.

Albert Gu, Isys Johnson, Karan Goel, Khaled Kamal Saab, Tri Dao, Atri Rudra, and Christopher Re. Combining recurrent, convolutional, and continuous-time models with linear state space layers. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, 2021. URL `https://openreview.net/forum?id=yWd42CWN3c`.

Albert Gu, Karan Goel, and Christopher Re. Efficiently modeling long sequences with structured state spaces. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=uYLFoz1vlAC`.

Wes Gurnee and Max Tegmark. Language models represent space and time. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=jE8xbmvFin`.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=nZeVKeeFYf9`.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mistral 7b, 2023. URL `https://arxiv.org/abs/2310.06825`. Version 1.

Nitish Joshi, Javier Rando, Abulhair Saparov, Najoung Kim, and He He. Personas as a way to model truthfulness in language models, 2024. URL `https://doi.org/10.48550/arXiv.2310.18168`. arXiv:2310.18168v5 [cs.CL].

Max Lamparth and Anka Reuel. Analyzing and editing inner mechanisms of backdoored language models, 2023. URL `https://arxiv.org/abs/2302.12461`.

Max Lamparth, Anthony Corso, Jacob Ganz, Oriana Skylar Mastro, Jacquelyn Schneider, and Harold Trinkunas. Human vs. machine: Language models and wargames, 2024. URL `https://arxiv.org/abs/2403.03407`.

Tamera Lanham, Anna Chen, Ansh Radhakrishnan, Benoit Steiner, Carson Denison, Danny Hernandez, Dustin Li, Esin Durmus, Evan Hubinger, Jackson Kernion, Kamilė Lukošiūtė, Karina Nguyen, Newton Cheng, Nicholas Joseph, Nicholas Schiefer, Oliver Rausch, Robin Larson, Sam McCandlish, Sandipan Kundu, Saurav Kadavath, Shannon Yang, Thomas Henighan, Timothy Maxwell, Timothy Telleen-Lawton, Tristan Hume, Zac Hatfield-Dodds, Jared Kaplan, Jan Brauner, Samuel R. Bowman, and Ethan Perez. Measuring faithfulness in chain-of-thought reasoning, 2023. URL `https://arxiv.org/abs/2307.13702`.

Stephanie Lin, Jacob Hilton, and Owain Evans. TruthfulQA: Measuring how models mimic human falsehoods. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics*, 2022. URL `https://arxiv.org/abs/2109.07958`. ACL 2022 (main conference).

Qing Lyu, Shreya Havaldar, Adam Stein, Li Zhang, Delip Rao, Eric Wong, Marianna Apidianaki, and Chris Callison-Burch. Faithful chain-of-thought reasoning, 2023. URL `https://arxiv.org/abs/2301.13379`.

Kevin Meng, David Bau, Alex J Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

Neel Nanda, Lawrence Chan, Tom Lieberum, Jess Smith, and Jacob Steinhardt. Progress measures for grokking via mechanistic interpretability. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=9XFSbDPmdW`.

Maxwell Nye, Anders Johan Andreassen, Guy Gur-Ari, Henryk Michalewski, Jacob Austin, David Bieber, David Dohan, Aitor Lewkowycz, Maarten Bosma, David Luan, Charles Sutton, and Augustus Odena. Show your work: Scratchpads for intermediate computation with language models, 2022. URL `https://openreview.net/forum?id=iedYJm92o0a`.

Leonardo Ranaldi and Andre Freitas. Aligning large and small language models via chain-of-thought reasoning. In Yvette Graham and Matthew Purver (eds.), *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1812–1827, St. Julian's, Malta, March 2024. Association for Computational Linguistics. URL https://aclanthology.org/2024.eacl-long.109.

Juan-Pablo Rivera, Gabriel Mukobi, Anka Reuel, Max Lamparth, Chandler Smith, and Jacquelyn Schneider. Escalation risks from language models in military and diplomatic decision-making, 2024. URL https://arxiv.org/abs/2401.03408.

D. Silver, A. Huang, C. Maddison, et al. Mastering the game of go with deep neural networks and tree search. *Nature*, 529:484–489, 2016.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, Timothy Lillicrap, Karen Simonyan, and Demis Hassabis. Mastering chess and shogi by self-play with a general reinforcement learning algorithm, 2017. URL https://doi.org/10.48550/arXiv.1712.01815. arXiv:1712.01815 [cs.AI].

Katherine Tian, Eric Mitchell, Huaxiu Yao, Christopher D. Manning, and Chelsea Finn. Fine-tuning language models for factuality, 2023. URL https://doi.org/10.48550/arXiv.2311.08401. arXiv:2311.08401 [cs.CL].

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023. URL https://arxiv.org/abs/2307.09288v2. Version 2.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=bzs4uPLXvi.

Kevin Ro Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. Interpretability in the wild: a circuit for indirect object identification in GPT-2 small. In *The Eleventh International Conference on Learning Representations*, 2022.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed H. Chi, Quoc V Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022. URL https://openreview.net/forum?id=_VjQlMeSB_J.

Zichao Yang, Phil Blunsom, Chris Dyer, and Wang Ling. Reference-aware language models. In Martha Palmer, Rebecca Hwa, and Sebastian Riedel (eds.), *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 1850–1859, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/D17-1197. URL https://aclanthology.org/D17-1197.

Eric Zelikman, Georges Harik, Yijia Shao, Varuna Jayasiri, Nick Haber, and Noah D. Goodman. Quiet-star: Language models can teach themselves to think before speaking, 2024. URL https://arxiv.org/abs/2403.09629.

A WIKIPEDIA EXPERIMENTS

While our primary results focus on mathematical reasoning, we also explored the application of our approach to more general language modeling using Wikipedia text. For each Wikipedia article, we condition on the first 200 tokens, produce 50 tokens of CoT, which is then used to predict the following 100 tokens of the article.

Our prompt template is:

> "You will need to predict the next 100 tokens which follow the provided passage. You can write 50 thinking tokens which will be your sole context for prediction. Feel free to be creative in your thinking strategy!\n\nOpening text:"

Figure 6: Four independent training runs, showing the difference in log probabilities of the answer ans given a trained CoT cot and the default cot' that a pre-trained model would produce — $\ln \pi(ans \mid cot) - \ln \pi(ans \mid cot')$. Unlike in 2, this is using Llama-3.1-8B-Instruct Dubey et al. (2024) instead of Mistral for π and u_θ, and the task is to produce text which helps predict the subsequent 100 tokens in a Wikipedia article (Foundation, 2024).

Results showed modest improvements in next-token prediction accuracy from 8.2% to 10.5% (Figure 6). However, this should be contextualized against Llama's typical 16.9% accuracy (estimated over 10,000 articles) on the 200th to 300th tokens of Wikipedia articles without any context. The lower baseline performance (8.2%) appears to be an artifact of our prompting setup.

Despite these limitations in absolute performance, we found that our key mechanistic findings about CoT reliability held up in this more general setting. Figure 7 demonstrates that perturbations to the CoT meaningfully impact performance, with the trained model showing greater sensitivity to perturbations than the baseline model. This suggests the model is genuinely using the generated reasoning rather than bypassing it.

Figure 8 shows that improvements in Mistral's CoT quality correspond to improvements in Llama's ability to use that CoT, indicating genuine generalization of the reasoning pattern rather than model-specific artifacts.

For the Wikipedia experiments, we made several modifications to our training approach. We introduced a KL penalty of 0.1 and replaced the PPO objective with policy gradient using a threshold of 2.2 standard deviations above the historical mean performance, and we increased the sampling temperature to 2.0. As with the other tasks, we replaced the immediate reward with an advantage function, where the estimated a value function is an exponentially decaying average of previous rewards and a decay factor of 0.9.

B TRUTHFULNESS AND ELICITING LATENT KNOWLEDGE

Existing methods seek to elicit truthfulness by having an LM cite external authorities (Yang et al., 2017), produce queries for an external solver such as Python (Lyu et al., 2023), or simulate a truthful

Figure 7: Impact of various perturbations on CoT effectiveness over the course of training. Each subplot shows a different perturbation type: character deletion, front truncation, back truncation, and random character replacement, with perturbation rates from 0% to 100%. For a perturbation function $pert$, letting $\pi(ans|cot)$ denote the log probability of the answer given a CoT, we plot $[\pi(ans|cot) - \pi(ans|pert(cot))] - [\pi(ans|cot') - \pi(ans|pert(cot'))]$, where cot' is the default CoT from the pre-trained model. Higher values indicate the trained model relies more heavily on precise CoT content than the baseline model. When $pert$ is a 100% perturbation rate (effectively a constant function k), this reduces to $[\pi(ans|cot) - k] - [\pi(ans|cot') - k] = \pi(ans|cot) - \pi(ans|cot') = I(ans, cot, cot')$, explaining why these curves align with the normalized reward from Figure 6. Smoothing window: 60.

Figure 8: Cross-model evaluation showing Llama-3.1-8B-Instruct's evaluation of Mistral's CoT quality throughout training on Wikipedia text prediction. The correlation between improvements in both models' evaluations suggests the learned reasoning patterns generalize across architectures rather than being model-specific artifacts. Each plot is averaged across 6 independent training runs. Smoothing window: 100.

persona (Joshi et al., 2024). Other methods include looking into model activations to discern a truth concept (Burns et al., 2023) or fine-tuning the LM for factuality (Tian et al., 2023).

One straightforward approach to measuring the truthfulness of an LM is to evaluate on datasets such as TruthfulQA (Lin et al., 2022) which focuses on popular human misconceptions. However, this technique will only continue to work so far as humans can tell which human beliefs are, indeed,

misconceptions. We would like to continue training a model for informativeness on questions that challenge human evaluators.

Reinforcement learning success stories such as AlphaGo (Silver et al., 2016) and AlphaZero (Silver et al., 2017) show that a top-ranking Go AI can continue to learn if we have an efficient way to compute the success criteria (such as a winning board state). However, many important success criteria are abstractions, and only exist within a person's ontology. This problem is discussed at length in Christiano et al. (2021), and we will use their example to illustrate the situation.

Suppose we were building a security system AI to watch over a vault containing a diamond. Suppose further that we have a camera pointed at the diamond, and that our security guard AI can competently predict future camera frames from past frames. How can we train it to classify camera sequences according to the ambiguous human concept of whether the diamond is still in the room, even in difficult scenarios when a person would not be able to provide a ground truth label (e.g., subtle camera tampering)? If we train the classifier based on scenarios when a person can provide ground truth labels, then the AI's video classifier has two valid generalization behaviors: (1) to say whether it thinks the diamond is still in the room and (2) to say whether the dataset-labeller would think the diamond is still in the room.

Our approach favors the second generalization behaviour by using RL to train the AI to produce messages such that the person can themselves predict future camera frames. This idea is based on the following three insights:

- Whereas truthfulness of an LM requires some internal information, *informativeness* can be measured using only input-output behavior.

- We can decompose the definition of informativeness into informativeness of a sender to a receiver, which can be an AI and a person, respectively.

- We can use reinforcement learning to push past the imitation learning regime, by continuing to train for this relative informativeness objective even when the AI is already the expert next-frame predictor.

C   QUALITATIVE ANALYSIS OF GENERATED COTS

Here is a (non-cherry picked) example of the CoT text generated by Mistral-7B-Instruct-V2, after and before Markovian training, respectively.

C.1   AFTER TRAINING

Batch Index 989

Previous Observation 6 + 89 + 38 + 36 + 42 + 98 + 85 + 95 + 49 + 24 + 47 + 95 + 60 + 20 + 40

Action Perform the given expression.

Next, calculate 6 + 89: 6 + 89 = 95

Next, calculate 95 + 38: 95 + 38 = 133

Next, calculate 133 + 36: 133 + 36 = 169

Next, calculate 169 + 42: 169 + 42 = 211

Next, calculate 211 + 98: 211 + 98 = 309

Next, calculate 309 + 85: 309 + 85 = 394

Next, calculate 394 + 95: 394 + 95 = 489

Next, calculate 489 + 49: 489 + 49 = 538

Next, calculate 538 + 24: 538 + 24 = 562

Next, calculate 562 + 47: 562 + 47 = 609

Next, calculate 609 + 95: 609 + 95 = 694

Next, calculate 694 + 60: 694 + 60 = 754

Next, calculate 754 + 20: 754 + 20 = 774

Next, calculate 774 + 40: 774 + 40 = 814

Hence, the result of

Observation 824

C.2   BEFORE TRAINING

Batch Index 35

Previous Observation 76 + 90 + 92 + 20 + 99 + 66 + 26 + 11 + 71 + 79 + 71 + 82 + 79 + 94 + 64

Action To add all the given numbers, you only need to follow the standard addition rule:
Sum = First Number + Second Number + ... + Last Number
Given numbers are 76, 90, 92, 20, 99, 66, 26, 11, 71, 79, 71, 82, 79, 94, 64
Addition process:
Sum = 76 + 90 + 92 + 20 + 99 + 66 + 26 + 11 + 71 + 79 + 71 + 82 + 79 + 94 + 64
Sum = 2314
So, the sum of all given numbers is 2314. Answer: 2314 .
Note: We use boxed numbers to represent answers and to distinguish them from the text.
We capitalize question numbers to help locate them easily.
Final answer: The sum is 2314.
Used and loved by 4 million people
Learn from a vibrant community of students and enthusiasts, just like you.
Your list looks good! Here's a clean version and a few suggestions.
1. Make sure each step in the calculation is clearly displayed. This can help make your cal-
culations (and your reasoning) more intuitive and easier to follow for others. For example:
Addition process:
Sum = 76 + 90 + 92 + 20 + 99 + 66 + 26 + 11 + 71 + 79 + 71 + 82 + 79 + 94

Observation 1020

D   ON BASELINES FOR FAITHFUL COT

The question of appropriate baselines for our method requires careful consideration, as there are three distinct interpretations of what could constitute a baseline in this context:

D.1   BASELINES FOR OPTIMIZING INFORMATIVENESS

For our specific informativeness objective, we compare against expert iteration with thresholding and policy gradient approaches in Figure 2. While PPO shows superior performance, the differences between these optimization techniques are relatively modest compared to the overall improvement over the pre-trained model.

D.2   BASELINES FOR FAITHFUL LANGUAGE MODEL REASONING

A more fundamental challenge lies in establishing baselines for the broader goal of generating CoTs that reflect a language model's underlying reasoning process. This requires first formalizing what we mean by "faithful" reasoning. Our approach takes the stance that a faithful CoT should have the property that perturbing it meaningfully impacts the model's predictive accuracy. We define this formally through our informativeness objective:

$$I(u, u', P) = \mathbb{E}_{\tau \sim P, u, u'}[R(\tau)] \tag{9}$$

where $R(\tau)$ measures how much more accurately the model predicts using the CoT compared to without it.

To our knowledge, there are no other formal definitions of faithfulness for language models that are sufficiently well-specified to serve as training objectives. If such alternatives existed, they would provide natural baselines for comparison.

D.3 BASELINES FOR CoT FRAGILITY

We can consider several potential approaches for generating CoTs that are fragile to perturbation:

1. **Formal Language CoTs:** One could generate CoTs in a precise language like Python, where the answer could be computed by executing the code. While such CoTs would be highly fragile to perturbation (due to syntax errors), this approach would not generalize to general language modeling tasks like Wikipedia text prediction where the "answer" cannot be computed deterministically.

2. **Question-CoT Pairs:** We could maintain the standard approach of keeping both question and CoT in context when predicting answers, measuring how perturbations to the CoT affect predictions. However, this makes it impossible to isolate whether the observed fragility stems from the CoT itself or from the interaction between question and CoT.

3. **Minimal Prompted CoTs:** We could prompt the model to produce minimal CoTs and measure their fragility to perturbation. This baseline is effectively represented at training step 0 in Figure 7, where we see minimal difference in log probability between perturbed and unperturbed CoTs from the pre-trained model.

Each of these potential baselines has significant limitations that prevent direct comparison with our approach. The formal language approach sacrifices generality, the question-CoT approach introduces confounding variables, and the minimal prompted approach is already captured as the starting point of our training process.

This analysis suggests that establishing meaningful baselines for faithful reasoning remains an open challenge in language model interpretability. Our approach provides one concrete formalization and optimization target, but we acknowledge there may be other valuable perspectives on what constitutes faithful reasoning that could lead to different baseline approaches in future work.

E STEGANOGRAPHY

If our goal is to generate *interpretable* CoT, a natural next question is "interpretable to whom?" For instance, one simple QA task is to copy the question. Then the optimal CoT would be a compression of the question, which can potentially be difficult for humans to decipher. So instead of informativeness of a CoT toward another language model, we might want to consider informativeness with respect to people (messages that allow the person to predict future observations). Of course, it may be prohibitive to have humans in the training loop, so the following are three potential (non-exclusive) approaches to address this issue: (1) Use a less competent predictor language model $\pi(o|s)$, (2) use a diversity of different $\pi(o|s)$ during training, so that $u_\theta(s|o,s)$ cannot anchor too much on the subtleties of any particular model, or (3) have the $\pi(o|s)$ mimic the target audience of the CoT, for instance by concatenating a fixed natural language prefix to s.

I'll help analyze these examples and write an appendix focusing on the contrasting strategies between the trained actor and untrained critic. Here's a proposed appendix:

F CASE STUDY OF WIKIPEDIA PREDICTION

To better understand Llama-3.1-8B-Instruct's behavior after Markovian training to predict Wikipedia text, let's examine a its behavior on the (randomly selected near the end of training) batch number 12500. The model was given the following Wikipedia article excerpt:

> Boones Mill is a town in Franklin County, Virginia, United States. The population was 239 in 2018, down from 285 at the 2000 census. It is part of the Roanoke Metropolitan Statistical Area.
> History
> Boones Mill was incorporated in 1927. It was previously known as "Boone Mill" and "Boon Mill". The town is named after Jacob Boon who operated a mill in the town.

The Boones Mill Norfolk & Western Railway Depot is listed on the National Register of Historic Places. https://www.townofboonesmill.org/history

Geography

Boones Mill is located in northern Franklin County at (37.115462, -79.953966), along U.S. Route 220 at the southern base of the Blue Ridge Mountains. US 220 leads north to Roanoke and south to Rocky Mount, the Franklin County seat.

According to the United States Census Bureau, the town has

Given this context ending with "According to the United States Census Bureau, the town has", we can compare the CoT generated by our trained versus an untrained model:

F.1 CoT after Training:

"The town of Boones Mill is located in Franklin County, Virginia, United States. US 220 leads north to Roanoke and south to Rocky Mount, the Franklin County seat. According to the United States Census Bureau, the town has"

F.2 CoT before Training:

"The town of Boones Mill is a small, rural community with a rich history and natural beauty. The town is surrounded by the Blue Ridge Mountains, offering scenic views and outdoor recreational opportunities. The town's economy is primarily based on agriculture and small"

F.3 Actual Continuation:

"a total area of , all of it land. The town is in the valley of Maggodee Creek, a southeast-flowing tributary of the Blackwater River, part of the Roanoke River watershed. Murray Knob, elevation , rises to the north on the crest of the Blue Ridge, and the eastern end of Cahas Mountain, at , is 2 miles to the west."

The trained CoT shows notably different characteristics from the untrained one. The trained CoT essentially copied the first and last two sentences from the context, making sure to line up the number of allotted tokens with the end of the last sentence. The untrained model seems to give fairly generic properties that the actual Boones Mill Wikipedia article does not mention, such as Boones Mill having an economy primarily based on agriculture. Also, the untrained CoT is not taking the token limit into account and is setting the evaluator model to be surprised when it glues the CoT to the answer and has to predict "agriculture and small a total area of , all of it land".

This example achieved a normalized reward of 0.3438 (in log probability), suggesting that the trained CoT strategy was indeed helpful for predicting the technical geographic description that followed.