Boosting Barely Robust Learners:
A New Perspective on Adversarial Robustness

Avrim Blum
avrim@ttic.edu
TTI Chicago

Omar Montasser
omar@ttic.edu
TTI Chicago

Greg Shakhnarovich
greg@ttic.edu
TTI Chicago

Hongyang Zhang
first.last@uwaterloo.ca
University of Waterloo

Abstract

We present an oracle-efficient algorithm for boosting the *adversarial robustness* of *barely robust* learners. Barely robust learning algorithms learn predictors that are adversarially robust only on a small fraction $\beta \ll 1$ of the data distribution. Our proposed notion of barely robust learning requires robustness with respect to a "larger" perturbation set; which we show is *necessary* for strongly robust learning, and that weaker relaxations are *not* sufficient for strongly robust learning. Our results reveal a qualitative and quantitative *equivalence* between two seemingly unrelated problems: strongly robust learning and barely robust learning.

1 Introduction

We consider the problem of learning predictors that are *robust* to adversarial examples at test time. That is, we would like to be robust against a perturbation set $\mathcal{U} : \mathcal{X} \to 2^{\mathcal{X}}$, where $\mathcal{U}(x) \subseteq \mathcal{X}$ is the set of allowed perturbations that an adversary might replace x with, e.g., $\mathcal{U}$ could be perturbations of bounded ℓ_p-norms [10]. The goal is to learn a predictor h with small *robust risk*:

$$\mathrm{R}_{\mathcal{U}}(h; \mathcal{D}) \triangleq \Pr_{(x,y)\sim\mathcal{D}} \left[\exists z \in \mathcal{U}(x) : h(z) \neq y \right]. \tag{1}$$

Adversarially robust learning has proven to be quite challenging in practice, where current adversarial learning methods typically learn predictors with low natural error but robust only on a small fraction of the data. For example, according to the RobustBench leaderboard [7], the highest achieved robust accuracy with respect to ℓ_∞ perturbations on CIFAR10 is $\approx 66\%$ and on ImageNet is $\approx 38\%$. Can we leverage existing methods and go beyond their limits? This motivates us to pursue the idea of *boosting* robustness, and study the following theoretical question:

Can we boost barely *robust learning algorithms to learn predictors with high* robust *accuracy?*

That is, given a *barely* robust learning algorithm $\mathbb{A}$ which can only learn predictors robust on say $\beta = 10\%$ fraction of the data distribution, we are asking whether it is possible to *boost* the robustness of $\mathbb{A}$ and learn predictors with high *robust* accuracy, say 90%. We want to emphasize that we are interested here in extreme situations when the robustness parameter $\beta \ll 1$. We are interested in generic boosting algorithms that take as input a black-box learner $\mathbb{A}$ and a specification of the perturbation set $\mathcal{U}$, and output a predictor with high robust accuracy by repeatedly calling $\mathbb{A}$.

In this work, by studying the question above, we offer a new perspective on adversarial robustness. Specifically, we discover a qualitative and quantitative *equivalence* between two seemingly unrelated problems: strongly robust learning and barely robust learning. We show that barely robust learning implies strongly robust learning through a novel algorithm for *boosting* robustness. As we elaborate below, our proposed notion of barely robust learning requires robustness with respect to a "larger" perturbation set. We also show that this is *necessary* for strongly robust learning, and that weaker relaxations of barely robust learning do not imply strongly robust learning.

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

1.1 Main contributions

When formally studying the problem of boosting robustness, an important question emerges which is: what notion of "barely robust" learning is required for boosting robustness? As we shall show, this is not immediately obvious. One of the main contributions of this work is the following key definition of *barely robust* learners:

Definition 1 (Barely Robust Learner). Learner $\mathbb{A}$ $(\beta, \epsilon, \delta)$-barely-robustly-learns a concept $c : \mathcal{X} \rightarrow \mathcal{Y}$ w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$ if $\exists m_{\mathbb{A}}(\beta, \epsilon, \delta) \in \mathbb{N}$ s.t. for any distribution D over $\mathcal{X}$ s.t. $\Pr_{x \sim D} \left[\exists z \in \mathcal{U}(x) : c(z) \neq c(x) \right] = 0$, with prob. at least $1 - \delta$ over $S = \{(x_i, c(x_i))\}_{i=1}^{m} \sim D_c$ and any internal randomness in the learner, $\mathbb{A}$ outputs a predictor $\hat{h} = \mathbb{A}(S)$ satisfying:

$$\Pr_{x \sim D} \left[\forall \tilde{x} \in \mathcal{U}^{-1}(\mathcal{U})(x) : \hat{h}(\tilde{x}) = \hat{h}(x) \right] \geq \beta \quad \text{and} \quad \Pr_{x \sim D} \left[\hat{h}(x) \neq c(x) \right] \leq \epsilon.$$

Notice that we require β-robustness with respect to a "larger" perturbation set $\mathcal{U}^{-1}(\mathcal{U})$. Specifically, $\mathcal{U}^{-1}(\mathcal{U})(x)$ is the set of all *natural* examples $\tilde{x}$ that share an adversarial perturbation z with x (see Equation 2). E.g., if $\mathcal{U}(x)$ is an ℓ_p-ball with radius γ, then $\mathcal{U}^{-1}(\mathcal{U})(x)$ is an ℓ_p-ball with radius 2γ.

On the other hand, (ϵ, δ)-robustly-learning a concept c with respect to $\mathcal{U}$ is concerned with learning a predictor $\hat{h}$ from samples S with small robust risk $R_{\mathcal{U}}(\hat{h}; D_c) \leq \epsilon$ with probability at least $1 - \delta$ over $S \sim D_c^m$ (see Equation 1 and Definition 2), where we are interested in robustness with respect to $\mathcal{U}$ and *not* $\mathcal{U}^{-1}(\mathcal{U})$. Despite this qualitative difference between *barely robust* learning and *strongly robust* learning, we provably show next that they are in fact *equivalent*.

Our main algorithmic result is β-RoBoost, an oracle-efficient boosting algorithm that boosts barely robust learners to strongly robust learners:

Theorem 1. *For any perturbation set $\mathcal{U}$, β-RoBoost (ϵ, δ)-robustly-learns any target concept $c : \mathcal{X} \rightarrow \mathcal{Y}$ w.r.t. $\mathcal{U}$ using $T = \frac{\ln(2/\epsilon)}{\beta}$ black-box oracle calls to any $(\beta, \frac{\beta\epsilon}{2}, \frac{\delta}{2T})$-barely-robust learner $\mathbb{A}$ for c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$, with sample complexity $\frac{4Tm_{\mathbb{A}}}{\epsilon}$, where $m_{\mathbb{A}}$ is the sample complexity of learner $\mathbb{A}$.*

The result above shows that barely robust learning is *sufficient* for strongly robust learning. An important question remains, however: is our proposed notion of barely robust learning *necessary* for strongly robust learning? In particular, our proposed notion of barely robust learning requires β-robustness with respect to a "larger" perturbation set $\mathcal{U}^{-1}(\mathcal{U})$, instead of the actual perturbation set $\mathcal{U}$ that we care about. We provably show next that this is *necessary*.

Theorem 4. *For any $\mathcal{U}$, learner $\mathbb{B}$, and $\epsilon \in (0, 1/4)$, if $\mathbb{B}$ (ϵ, δ)-robustly-learns some unknown target concept c w.r.t. $\mathcal{U}$, then there is a learner $\tilde{\mathbb{B}}$ that $(\frac{1-\epsilon}{2}, 2\epsilon, 2\delta)$-barely-robustly-learns c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$.*

This still does *not* rule out the possibility that boosting robustness is possible even with the weaker requirement of β-robustness with respect to $\mathcal{U}$. But we show next that, indeed, barely robust learning with respect to $\mathcal{U}$ is *not sufficient* for strongly robust learning with respect to $\mathcal{U}$:

Theorem 6. *There is a space $\mathcal{X}$, a perturbation set $\mathcal{U}$, and a class of concepts $\mathcal{C}$ s.t. $\mathcal{C}$ is $(\beta = \frac{1}{2}, \epsilon = 0, \delta)$-barely-robustly-learnable w.r.t $\mathcal{U}$, but $\mathcal{C}$ is not (ϵ, δ)-robustly-learnable w.r.t. $\mathcal{U}$ for any $\epsilon < 1/2$.*

Our results offer a new perspective on adversarially robust learning. We show that two seemingly unrelated problems: barely robust learning w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$ and strongly robust learning w.r.t. $\mathcal{U}$, are in fact *equivalent*. The following corollary follows from Theorem 1 and Theorem 4.

Corollary I. *For any class $\mathcal{C}$ and any perturbation set $\mathcal{U}$, $\mathcal{C}$ is strongly robustly learnable with respect to $\mathcal{U}$ if and only if $\mathcal{C}$ is barely robustly learnable with respect to $\mathcal{U}^{-1}(\mathcal{U})$.*

We would like to note that having a separate robustness parameter β and a natural error parameter ϵ allows us to consider regimes where $\beta < \frac{1}{2}$ and ϵ is small. This models typical scenarios in practice where learning algorithms are able to learn predictors with reasonably low natural error but the predictors are only barely robust. More generally, this allows us to explore the relationship between β and ϵ in terms of boosting robustness (see Section 5 for a more elaborate discussion).

Landscape of boosting robustness. Our results reveal an interesting landscape for boosting robustness when put in context of prior work. When the robustness parameter $\beta > \frac{1}{2}$, it is known from prior work that β-robustness with respect to $\mathcal{U}$ *suffices* for boosting robustness [see e.g., 15, 1], which

is witnessed by the α-Boost algorithm [18]. When the robustness parameter $\beta \leq \frac{1}{2}$, our results show that boosting is still *possible*, but β-robustness with respect to $\mathcal{U}^{-1}(\mathcal{U})$ is *necessary* and we *cannot* boost robustness with β-robustness with respect to $\mathcal{U}$.

In fact, by combining our algorithm β-RoBoost with α-Boost, we obtain an even *stronger* boosting result that only requires barely robust learners with a natural error parameter that does *not* scale with the targeted robust error. Beyond that, our results imply that we can even boost robustness with respect to $\mathcal{U}^{-1}(\mathcal{U})$. This is summarized in the following corollary which follows from Theorem 1, Lemma 8, and Theorem 4.

Corollary II (Landscape of Boosting Robustness). *Let $\mathcal{C}$ be a class of concepts. For fixed $\epsilon_0, \delta_0 = \left(\frac{1}{3}, \frac{1}{3}\right)$ and any target $\epsilon < \epsilon_0$ and $\delta > \delta_0$:*

1. *If $\mathcal{C}$ is $\left(\beta, \frac{\beta\epsilon_0}{2}, \frac{\beta\delta_0}{\ln(2/\epsilon_0)}\right)$-barely-robustly-learnable w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$, then $\mathcal{C}$ is (ϵ_0, δ_0)-robustly-learnable w.r.t. $\mathcal{U}$.*

2. *If $\mathcal{C}$ is (ϵ_0, δ_0)-robustly-learnable w.r.t. $\mathcal{U}$, then $\mathcal{C}$ is (ϵ, δ)-robustly learnable w.r.t. $\mathcal{U}$.*

3. *If $\mathcal{C}$ is (ϵ, δ)-robustly learnable w.r.t. $\mathcal{U}$, then $\mathcal{C}$ is $\left(\frac{1-\epsilon}{2}, 2\epsilon, 2\delta\right)$-barely-robustly-learnable w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$.*

In particular, $1 \Rightarrow 2 \Rightarrow 3$ reveals that we can also algorithmically boost robustness w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$.

Boosting robustness with unlabeled data. In Appendix A and Theorem 7, we show that a variant of our boosting algorithm, β-URoBoost, can boost robustness using *unlabeled* data when having access to a barely robust learner $\mathbb{A}$ that is tolerant to small noise in the labels. In Appendix E, we discuss an idea of obtaining robustness at different levels of granularity through our boosting algorithm. Specifically, when $\mathcal{U}(x)$ is a metric-ball around x with radius γ, we can learn a predictor $\hat{h}$ with different robustness levels: $\gamma, \frac{\gamma}{2}, \frac{\gamma}{4}, \ldots$, in different regions of the distribution.

1.2 Related work

To put our work in context, the classic and pioneering works of [12, 17, 8, 9] explored the question of boosting the *accuracy* of *weak* learning algorithms, from accuracy slightly better than $\frac{1}{2}$ to arbitrarily high accuracy in the realizable PAC learning setting. Later works have explored boosting the accuracy in the agnostic PAC setting [see e.g., 11].

In this work, we are interested in the problem of boosting *robustness* rather than accuracy. Specifically, boosting robustness of learners $\mathbb{A}$ that are highly accurate on *natural* examples drawn from the data distribution, but robust only on some β fraction of them. We consider this problem in the *robust realizable* setting, that is, when the unknown target concept c has zero robust risk $\mathrm{R}_{\mathcal{U}}(c; D_c) = 0$. For example, with linear classifiers and ℓ_2 perturbations, robust realizability is equivalent to linear separability with a margin, which is a setting that is studied extensively in the literature. Furthermore, for vision datasets in practice (e.g., CIFAR10 and ImageNet), it has been observed that the classes can be robustly separated with some non-negligible distance, indicating that robust classifiers for these datasets do exist, i.e., the robust realizability assumption holds [see Section 3 in 19].

We know from prior work [see e.g., 15, 1, 20] that if the robustness parameter $\beta > \frac{1}{2}$, then barely robust learning w.r.t. $\mathcal{U}$ implies strongly robust learning w.r.t. $\mathcal{U}$. In this case, we essentially have *weak* learners w.r.t. the robust risk $\mathrm{R}_{\mathcal{U}}$, and the original boosting algorithms such as the α-Boost algorithm [18, Section 6.4.2] can boost the robust risk. In this work, we focus on boosting *barely* robust learners, i.e., mainly when the robustness parameter $\beta \leq 1/2$, but our algorithm works for any $0 < \beta \leq 1$.

[15] studied the problem of adversarially robust learning (as in Definition 2). They showed that if a hypothesis class $\mathcal{C}$ is PAC learnable non-robustly (i.e., $\mathcal{C}$ has finite VC dimension), then $\mathcal{C}$ is adversarially robustly learnable. This result, however, is not constructive and the robust learning algorithm given does not directly use a black-box non-robust learner. Later on, [16] studied a more constructive version of the same question: reducing strongly robust learning to *non-robust* PAC learning when given access to black-box *non-robust* PAC learners. This is different from the question we study in this work. In particular, we explore the relationship between strongly robust learning and barely robust learning, and we present a boosting algorithm for learners that already have some non-trivial robustness guarantee $\beta > 0$.

2 Preliminaries

Let $\mathcal{X}$ denote the instance space and $\mathcal{Y}$ denote the label space. We would like to be robust with respect to a perturbation set $\mathcal{U} : \mathcal{X} \to 2^{\mathcal{X}}$, where $\mathcal{U}(x) \subseteq \mathcal{X}$ is the set of allowed adversarial perturbations that an adversary might replace x with at test time. Denote by $\mathcal{U}^{-1}$ the inverse image of $\mathcal{U}$, where for each $z \in \mathcal{X}$, $\mathcal{U}^{-1}(z) = \{x \in \mathcal{X} : z \in \mathcal{U}(x)\}$. Observe that for any $x, z \in \mathcal{X}$ it holds that $z \in \mathcal{U}(x) \Leftrightarrow x \in \mathcal{U}^{-1}(z)$. Furthermore, when $\mathcal{U}$ is symmetric, where for any $x, z \in \mathcal{X}, z \in \mathcal{U}(x) \Leftrightarrow x \in \mathcal{U}(z)$, it holds that $\mathcal{U} = \mathcal{U}^{-1}$. For each $x \in \mathcal{X}$, denote by $\mathcal{U}^{-1}(\mathcal{U})(x)$ the set of all *natural* examples $\tilde{x}$ that share some adversarial perturbation z with x, i.e.,

$$\mathcal{U}^{-1}(\mathcal{U})(x) = \cup_{z \in \mathcal{U}(x)} \mathcal{U}^{-1}(z) = \{\tilde{x} : \exists z \in \mathcal{U}(x) \cap \mathcal{U}(\tilde{x})\}. \tag{2}$$

For example, when $\mathcal{U}(x) = \mathrm{B}_{\gamma}(x) = \{z \in \mathcal{X} : \rho(x, z) \le \gamma\}$ where $\gamma > 0$ and ρ is some metric on $\mathcal{X}$ (e.g., ℓ_p-balls), then $\mathcal{U}^{-1}(\mathcal{U})(x) = \mathrm{B}_{2\gamma}(x)$. For any classifier $h : \mathcal{X} \to \mathcal{Y}$ and any $\mathcal{U}$, denote by $\mathrm{Rob}_{\mathcal{U}}(h)$ the *robust region* of h with respect to $\mathcal{U}$ defined as:

$$\mathrm{Rob}_{\mathcal{U}}(h) \triangleq \{x \in \mathcal{X} : \forall z \in \mathcal{U}(x), h(z) = h(x)\}. \tag{3}$$

Definition 2 (Strongly Robust Learner). Learner $\mathbb{B}$ (ϵ, δ)-robustly-learns a concept $c : \mathcal{X} \to \mathcal{Y}$ with respect to $\mathcal{U}$ if there exists $m(\epsilon, \delta) \in \mathbb{N}$ s.t. for any distribution D over $\mathcal{X}$ satisfying $\Pr_{x \sim D}[\exists z \in \mathcal{U}(x) : c(z) \ne c(x)] = 0$, with probability at least $1 - \delta$ over $S = \{(x_i, c(x_i))\}_{i=1}^{m} \sim D_c$, $\mathbb{B}$ outputs a predictor $\hat{h} = \mathbb{B}(S)$ satisfying:

$$\mathrm{R}_{\mathcal{U}}(\hat{h}; D_c) = \Pr_{x \sim D}\left[\exists z \in \mathcal{U}(x) : \hat{h}(z) \ne c(x)\right] \le \epsilon.$$

3 Boosting a barely robust Learner to a strongly robust learner

We present our main result in this section: β-RoBoost is an algorithm for *boosting* the *robustness* of *barely* robust learners. Specifically, in Theorem 1, we show that given a *barely* robust learner $\mathbb{A}$ for some unknown target concept c (according to Definition 1), it is *possible* to strongly robustly learn c with β-RoBoost by making black-box oracle calls to $\mathbb{A}$.

Algorithm 1: β-RoBoost — Boosting *barely* robust learners.

Input: Sampling oracle for distribution D_c, black-box $(\beta, \epsilon, \delta)$-barely-robust learner $\mathbb{A}$.

1 Set $T = \frac{\ln(2/\epsilon)}{\beta}$, and $m = \max\left\{m_{\mathbb{A}}(\beta, \frac{\beta\epsilon}{2}, \frac{\delta}{2T}), 4\ln\left(\frac{2T}{\delta}\right)\right\}$.

2 **while** $1 \le t \le T$ **do**

3   Call `RejectionSampling` on $h_1, \dots, h_{t-1}$ and m, and let $\tilde{S}_t$ be the returned dataset.

4   **If** $\tilde{S}_t \ne \emptyset$, **then** call learner $\mathbb{A}$ on $\tilde{S}_t$ and let $h_t = \mathbb{A}(\tilde{S}_t)$ be its output. **Otherwise**, break.

    Output: The cascade predictor defined as
$$\mathrm{CAS}(h_1, \dots, h_T)(z) \triangleq G_{h_s}(z) \text{ where } s = \min\{1 \le t \le T : G_{h_t}(z) \ne \perp\}, \text{ and}$$
$$\textit{selective classifiers} \quad G_{h_t}(z) \triangleq \begin{cases} y, & \text{if } (\exists y \in \mathcal{Y})\,(\forall \tilde{x} \in \mathcal{U}^{-1}(z)) : h(\tilde{x}) = y; \\ \perp, & \text{otherwise.} \end{cases}$$

5 `RejectionSampling`(*predictors* $h_1, \dots, h_t$, *and sample size* m):

6   **for** $1 \le i \le m$ **do**

7   Draw samples $(x, y) \sim D$ until sampling an (x_i, y_i) s.t.: $\forall_{t' \le t} \exists_{z \in \mathcal{U}(x_i)} G_{h_{t'}}(z) = \perp$.
                 `// sampling from the region of D where all predictors h_1,...,h_t are not robust.`

8   If this costs more than $\frac{4}{\epsilon}$ samples from D, abort and return an empty dataset $\tilde{S} = \emptyset$.
                 `// If the mass of the non-robust region is small, then we can safely terminate.`

9   Output dataset $\tilde{S} = \{(x_1, y_1), \dots, (x_m, y_m)\}$.

Theorem 1. *For any perturbation set $\mathcal{U}$, β-RoBoost (ϵ, δ)-robustly-learns any target concept c w.r.t. $\mathcal{U}$ using $T = \frac{\ln(2/\epsilon)}{\beta}$ black-box oracle calls to any $(\beta, \frac{\beta\epsilon}{2}, \frac{\delta}{2T})$-barely-robust learner $\mathbb{A}$ for c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$, with total sample complexity*

$$m(\epsilon, \delta) \le \frac{4T \max\left\{m_{\mathbb{A}}(\beta, \frac{\beta\epsilon}{2}, \frac{\delta}{2T}), 4\ln\left(\frac{2T}{\delta}\right)\right\}}{\epsilon}.$$

In fact, we present next an even stronger result for boosting $(\beta, \epsilon_0, \delta_0)$-barely-robust-learners with fixed error $\epsilon_0 = \frac{\beta}{6}$ and confidence $\delta_0 = \frac{\beta}{6\ln(6)}$. This is established by combining two boosting algorithms: β-RoBoost from Theorem 1 and α-Boost from earlier work [see e.g., 15, 18] which is presented in Appendix B for convenience. The main idea is to perform two layers of boosting. In the first layer, we use β-RoBoost to get a $(\frac{1}{3}, \frac{1}{3})$-robust-learner w.r.t. $\mathcal{U}$ from a $(\beta, \epsilon_0, \delta_0)$-barely-robust-learner $\mathbb{A}$ w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$. Then, in the second layer, we use α-Boost to boost β-RoBoost from a $(\frac{1}{3}, \frac{1}{3})$-robust-learner to an (ϵ, δ)-robust-learner w.r.t. $\mathcal{U}$.

Corollary 2 (Stronger Boosting Guarantee). *For any perturbation set $\mathcal{U}$, α-Boost combined with β-RoBoost (ϵ, δ)-robustly-learn any target concept c w.r.t. $\mathcal{U}$ using $T = O(\log(m)\,(\log(1/\delta) + \log\log m)) \cdot \frac{1}{\beta}$ black-box oracle calls to any $(\beta, \frac{\beta}{6}, \frac{\beta}{6\ln(6)})$-barely-robust-learner $\mathbb{A}$ for c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$, with total sample complexity*

$$ m(\epsilon, \delta) = O\left(\frac{m_0}{\beta\epsilon} \log^2\left(\frac{m_0}{\beta\epsilon}\right) + \frac{\log(1/\delta)}{\epsilon} \right), $$

where $m_0 = \max\left\{ m_{\mathbb{A}}\left(\beta, \frac{\beta}{6}, \frac{\beta}{6\ln(6)}\right), 4\ln\left(\frac{6\ln(6)}{\beta}\right) \right\}$.

We begin with describing the intuition behind β-RoBoost, and then we will prove Theorem 1. The proof of Corollary 2 is deferred to Appendix B.

High-level strategy. Let D_c be the unknown distribution we want to robustly learn. Since $\mathbb{A}$ is a *barely* robust learner for c, calling learner $\mathbb{A}$ on an i.i.d. sample S from D_c will return a predictor h_1, where h_1 is robust only on a region $R_1 \subseteq \mathcal{X}$ of small mass $\beta > 0$ under distribution D, $\Pr_{x\sim D}[x \in R_1] \geq \beta$. We can trust the predictions of h_1 in the region R_1, but not in the complement region $\bar{R}_1$ where it is not robust. For this reason, we will use a *selective* classifier G_{h_1} (see Equation 4) which makes predictions on *all* adversarial perturbations in region R_1, but *abstains* on adversarial perturbations not from R_1. In each round $t > 1$, the strategy is to focus on the region of distribution D where *all* predictors $h_1, \ldots, h_{t-1}$ returned by $\mathbb{A}$ so far are *not* robust. By *rejection sampling*, β-RoBoost gives barely robust learner $\mathbb{A}$ a sample $\tilde{S}_t$ from this non-robust region, and then $\mathbb{A}$ returns a predictor h_t with robustness at least β in this region. Thus, in each round, we shrink by a factor of β the mass of region D where the predictors learned so far are not robust. After T rounds, β-RoBoost outputs a *cascade* of *selective* classifiers $G_{h_1}, \ldots, G_{h_T}$ where roughly each selective classifier G_{h_t} is responsible for making predictions in the region where h_t is robust.

As mentioned above, one of the main components in our boosting algorithm is *selective classifiers* that essentially abstain from predicting in the region where they are *not* robust. Formally, for any classifier $h : \mathcal{X} \to \mathcal{Y}$ and any $\mathcal{U}$, denote by $G_h : \mathcal{X} \to \mathcal{Y} \cup \{\bot\}$ a *selective* classifier defined as:

$$ G_h(z) \triangleq \begin{cases} y, & \text{if } (\exists y \in \mathcal{Y})\left(\forall \tilde{x} \in \mathcal{U}^{-1}(z)\right) : h(\tilde{x}) = y; \\ \bot, & \text{otherwise.} \end{cases} \tag{4} $$

Before proceeding with the proof of Theorem 1, we prove the following key Lemma about *selective classifier* G_h which states that G_h will *not* abstain in the region where h is robust, and whenever G_h predicts a label for a perturbation z then we are guaranteed that this is the same label that h predicts on the corresponding natural example x where $z \in \mathcal{U}(x)$.

Lemma 3. *For any distribution D over $\mathcal{X}$, any $\mathcal{U}$, and any $\beta > 0$, given a classifier $h : \mathcal{X} \to \mathcal{Y}$ satisfying $\Pr_{x\sim D}\left[x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(h)\right] \geq \beta$, then the selective classifier $G_h : \mathcal{X} \to \mathcal{Y} \cup \{\bot\}$ (see Equation 4) satisfies:*

$$ \Pr_{x\sim D}\left[\forall z \in \mathcal{U}(x) : G_h(z) = h(x)\right] \geq \beta \text{ and } \Pr_{x\sim D}\left[\forall z \in \mathcal{U}(x) : G_h(z) = h(x) \vee G_h(z) = \bot\right] = 1. $$

Proof. Observe that, by the definition of the robust region of h w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$ (see Equation 3), for any $x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(h)$ the following holds:$(\forall z \in \mathcal{U}(x))\left(\forall \tilde{x} \in \mathcal{U}^{-1}(z)\right) : h(\tilde{x}) = h(x)$. By the definition of the *selective* classifier G_h (see Equation 4), this implies that: $\forall z \in \mathcal{U}(x), G_h(z) = h(x)$.

Since $\Pr_{x\sim D}\left[x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(h)\right] \geq \beta$, the above implies $\Pr_{x\sim D}\left[\forall z \in \mathcal{U}(x) : G_h(z) = h(x)\right] \geq \beta$. Furthermore, for any $x \in \mathcal{X}$ and any $z \in \mathcal{U}(x)$, by definition of $\mathcal{U}^{-1}$, $x \in \mathcal{U}^{-1}(z)$. Thus, by definition of G_h (see Equation 4), if $G_h(z) = y$ for some $y \in \mathcal{Y}$, then it holds that $h(x) = y$. Altogether, this implies that $\Pr_{x\sim D}\left[\forall z \in \mathcal{U}(x) : G_h(z) = h(x) \vee G_h(z) = \bot\right] = 1$. $\square$

We are now ready to proceed with the proof of Theorem 1.

Proof of Theorem 1. Let $\mathcal{U}$ be an arbitrary adversary, and $\mathbb{A}$ a $(\beta, \epsilon, \delta)$-barely-robust learner for some *unknown* target concept $c : \mathcal{X} \to \mathcal{Y}$ with respect to $\mathcal{U}^{-1}(\mathcal{U})$. We will show that β-RoBoost (ϵ, δ)-robustly-learns c with respect to $\mathcal{U}$. Let D be some unknown distribution over $\mathcal{X}$ such that $\Pr_{x \sim D} [\exists z \in \mathcal{U}(x) : c(z) \neq c(x)] = 0$. Let $\epsilon > 0$ be our target robust error, and ϵ' be the error guarantee of learner $\mathbb{A}$ (which we will set later to be $\frac{\beta \epsilon}{2}$).

Without loss of generality, suppose that β-RoBoost ran for $T = \frac{\ln(2/\epsilon)}{\beta}$ rounds (Step 4 takes care of the scenario where progress is made faster). Let $h_1 = \mathbb{A}(\tilde{S}_1), \ldots, h_T = \mathbb{A}(\tilde{S}_T)$ be the predictors returned by learner $\mathbb{A}$ on rounds $1 \leq t \leq T$. For any $1 \leq t \leq T$ and any $x \in \mathcal{X}$, denote by R_t the event that $x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(h_t)$, and by $\bar{R}_t$ the event that $x \notin \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(h_t)$ (as defined in Equation 3). Observe that by properties of $\mathbb{A}$ (see Definition 1), we are guaranteed that

$$\forall 1 \leq t \leq T : \Pr_{x \sim D_t} [R_t] \geq \beta \text{ and } \Pr_{x \sim D_t} [h_t(x) \neq c(x)] \leq \epsilon', \tag{5}$$

where D_t is the distribution from which $\tilde{S}_t$ is drawn. In words, distribution D_t is a conditional distribution focusing on the region of distribution D where all predictors $h_1, \ldots, h_{t-1}$ are *non-robust*. Specifically, for any $x \sim D$, in case $x \in R_1 \cup \cdots \cup R_{t-1}$ (i.e., there is a predictor among $h_1, \ldots, h_{t-1}$ that is robust on x), then Lemma 3 guarantees that one of the selective classifiers $G_{h_1}, \ldots, G_{h_{t-1}}$ will not abstain on any $z \in \mathcal{U}(x)$: $\exists t' \leq t - 1, \forall z \in \mathcal{U}(x), G_{h_{t'}}(z) \neq \perp$. In case $x \in \bar{R}_1 \cap \cdots \cap \bar{R}_{t-1}$, then, by definition of $\bar{R}_1, \ldots, \bar{R}_{t-1}$, each of the selective classifiers $G_{h_1}, \ldots, G_{h_{t-1}}$ can be forced to abstain: $\forall t' \leq t - 1, \exists z \in \mathcal{U}(x), G_{h_{t'}}(z) = \perp$. Thus, in Step 7 of β-RoBoost, *rejection sampling* guarantees that $\tilde{S}_t$ is a sample drawn from distribution D conditioned on the region $\bar{R}_{1:t-1} \triangleq \bar{R}_1 \cap \cdots \cap \bar{R}_{t-1}$. Formally, distribution D_t is defined such that for any measurable event E:

$$\Pr_{x \sim D_t} [E] \triangleq \Pr_{x \sim D} [E | \bar{R}_1 \cap \cdots \cap \bar{R}_{t-1}]. \tag{6}$$

Low error on natural examples. Lemma 3 guarantees that whenever any of the *selective* classifiers $G_{h_1}, \ldots, G_{h_T}$ (see Equation 4) chooses to classify an instance z at test-time their prediction will be correct with high probability. We consider two cases. First, in case of event R_t, $x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(h_t)$, and therefore, by Lemma 3, $\forall z \in \mathcal{U}(x) : G_{h_t}(z) = h_t(x)$. Thus, Equation 6 implies that $\forall 1 \leq t \leq T$:

$$\begin{aligned} &\Pr_{x \sim D} \left[R_t \wedge (\exists z \in \mathcal{U}(x) : (G_{h_t}(z) \neq \perp) \wedge (G_{h_t}(z) \neq c(x))) | \bar{R}_{1:t-1} \right] \\ &= \Pr_{x \sim D_t} [R_t \wedge (\exists z \in \mathcal{U}(x) : (G_{h_t}(z) \neq \perp) \wedge (G_{h_t}(z) \neq c(x)))] \\ &= \Pr_{x \sim D_t} [R_t \wedge (h_t(x) \neq c(x))]. \end{aligned} \tag{7}$$

Second, in case of the complement event $\bar{R}_t$, $x \notin \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(h_t)$. Therefore, by Lemma 3, $\forall z \in \mathcal{U}(x)$, we have $G_{h_t}(z) = \perp$ or $G_{h_t}(z) = h_t(x)$. Thus,

$$\begin{aligned} &\Pr_{x \sim D} \left[\bar{R}_t \wedge (\exists z \in \mathcal{U}(x) : (G_{h_t}(z) \neq \perp) \wedge (G_{h_t}(z) \neq c(x))) | \bar{R}_{1:t-1} \right] \\ &= \Pr_{x \sim D_t} [\bar{R}_t \wedge (\exists z \in \mathcal{U}(x) : (G_{h_t}(z) \neq \perp) \wedge (G_{h_t}(z) \neq c(x)))] \leq \Pr_{x \sim D_t} [\bar{R}_t \wedge (h_t(x) \neq c(x))]. \end{aligned} \tag{8}$$

By law of total probability Equation 7, Equation 8, and Equation 5,

$$\begin{aligned} &\Pr_{x \sim D} \left[(R_t \vee \bar{R}_t) \wedge (\exists z \in \mathcal{U}(x) : (G_{h_t}(z) \neq \perp) \wedge (G_{h_t}(z) \neq c(x))) | \bar{R}_{1:t-1} \right] \\ &\leq \Pr_{x \sim D_t} [R_t \wedge h_t(x) \neq c(x)] + \Pr_{x \sim D_t} [\bar{R}_t \wedge h_t(x) \neq c(x)] = \Pr_{x \sim D_t} [h_t(x) \neq c(x)] \leq \epsilon'. \end{aligned} \tag{9}$$

Boosted robustness. We claim that for each $1 \leq t \leq T : \Pr_{x \sim D} [\bar{R}_{1:t}] \leq (1 - \beta)^t$. We proceed by induction on the number of rounds $1 \leq t \leq T$. In the base case, when $t = 1$, $D_1 = D$ and by Equation 5, we have $\Pr_{x \sim D} [R_1] \geq \beta$ and therefore $\Pr_{x \sim D} [\bar{R}_1] \leq 1 - \beta$.

When $t > 1$, again by Equation 5, we have that $\Pr_{x \sim D_t}[R_t] \geq \beta$ and therefore, by Equation 6, $\Pr_{x \sim D}[\bar{R}_t | \bar{R}_{1:t-1}] = \Pr_{x \sim D_t}[\bar{R}_t] \leq 1 - \beta$. Finally, by the inductive hypothesis and Bayes' rule, we get

$$\Pr_{x \sim D}[\bar{R}_{1:t}] = \Pr_{x \sim D}[\bar{R}_t | \bar{R}_{1:t-1}] \Pr_{x \sim D}[\bar{R}_{1:t-1}] \leq (1-\beta)(1-\beta)^{t-1} = (1-\beta)^t. \quad (10)$$

Analysis of robust risk. For each $1 \leq t \leq T$, let

$$A_t = \left\{ x \in \bar{R}_t : \exists z \in \mathcal{U}(x) \text{ s.t. } G_{h_t(z)} \neq \perp \wedge \forall_{t' < t} G_{h_{t'}}(z) = \perp \right\}$$

denote the *non-robust* region of classifier h_t where the *selective* classifier G_{h_t} does not abstain but all selective classifiers $G_{h_1}, \ldots, G_{h_{t-1}}$ abstain. By the law of total probability, we can analyze the robust risk of the cascade predictor $\text{CAS}(h_1, \ldots, h_T)$ by partitioning the space into the *robust* and *non-robust* regions of $h_1, \ldots, h_T$. Specifically, by the structure of the cascade predictor $\text{CAS}(h_{1:T})$, each $x \sim D$ such that $\exists z \in \mathcal{U}(x)$ where $\text{CAS}(h_{1:T})(z) \neq c(x)$ satisfies the following condition:

$$\exists_{z \in \mathcal{U}(x)} : \text{CAS}(h_{1:T})(z) \neq c(x) \Rightarrow (\exists_{1 \leq t \leq T})(\exists_{z \in \mathcal{U}(x)}) : \forall_{t' < t} G_{h_{t'}}(z) = \perp \wedge G_{h_t}(z) \neq \perp \wedge G_{h_t}(z) \neq c(x).$$

Thus, each $x \sim D$ such that $\exists z \in \mathcal{U}(x)$ where $\text{CAS}(h_{1:T})(z) \neq c(x)$ can be mapped to one (or more) of the following regions:

$$\underbrace{R_1 \vee A_1}_{G_{h_1} \text{ does not abstain}} \mid \underbrace{\bar{R}_1 \wedge (R_2 \vee A_2)}_{G_{h_2} \text{ does not abstain}} \mid \bar{R}_{1:2} \wedge (R_3 \vee A_3) \mid \ldots \mid \underbrace{\bar{R}_{1:T-1} \wedge (R_T \vee A_T)}_{G_{h_T} \text{ does not abstain}} \mid \bar{R}_{1:T}.$$

We will now analyze the robust risk based on the above decomposition:

$$\Pr_{x \sim D}[\exists z \in \mathcal{U}(x) : \text{CAS}(h_{1:T})(z) \neq c(x)]$$

$$\leq \sum_{t=1}^{T+1} \Pr_{x \sim D}\left[\bar{R}_{1:t-1} \wedge (R_t \vee A_t) \wedge (\exists z \in \mathcal{U}(x) : \text{CAS}(h_{1:T})(z) \neq c(x))\right]$$

$$\leq \sum_{t=1}^{T} \Pr_{x \sim D}\left[\bar{R}_{1:t-1} \wedge (R_t \vee A_t) \wedge (\exists z \in \mathcal{U}(x) : \text{CAS}(h_{1:T})(z) \neq c(x))\right] + \Pr_{x \sim D}[\bar{R}_{1:T}]$$

$$\overset{(i)}{\leq} \sum_{t=1}^{T} \Pr_{x \sim D}\left[\bar{R}_{1:t-1} \wedge (R_t \vee A_t) \wedge (\exists z \in \mathcal{U}(x) : G_{h_t}(z) \neq \perp \wedge G_{h_t}(z) \neq c(x))\right] + \Pr_{x \sim D}[\bar{R}_{1:T}]$$

$$= \sum_{t=1}^{T} \Pr_{x \sim D}[\bar{R}_{1:t-1}] \Pr_{x \sim D}\left[(R_t \vee A_t) \wedge (\exists z \in \mathcal{U}(x) : G_{h_t}(z) \neq \perp \wedge G_{h_t}(z) \neq c(x)) | \bar{R}_{1:t-1}\right] + \Pr_{x \sim D}[\bar{R}_{1:T}]$$

$$\overset{(ii)}{\leq} \sum_{t=1}^{T} (1-\beta)^{t-1} \epsilon' + (1-\beta)^T = \epsilon' \sum_{t=1}^{T} (1-\beta)^{t-1} = \epsilon' \frac{1 - (1-\beta)^T}{1 - (1-\beta)} + (1-\beta)^T \leq \frac{\epsilon'}{\beta} + (1-\beta)^T,$$

$$(11)$$

where inequality (i) follows from the definitions of $\bar{R}_{1:t-1}$, R_t, and A_t, and inequality (ii) follows from Equation 10 and Equation 9. It remains to choose T and ϵ' such that the robust risk is at most ϵ.

Sample and oracle complexity. It suffices to choose $T = \frac{\ln(2/\epsilon)}{\beta}$ and $\epsilon' = \frac{\epsilon\beta}{2}$. We next analyze the sample complexity. Fix an arbitrary round $1 \leq t \leq T$. In order to obtain a *good* predictor h_t from learner $\mathbb{A}$ satisfying Equation 5, we need to draw $m_{\mathbb{A}}(\beta, \beta\epsilon/2, \delta/2T)$ samples from D_t. We do this by drawing samples from the original distribution D and doing rejection sampling. Specifically, let $m = \max\left\{m_{\mathbb{A}}(\beta, \frac{\epsilon\beta}{2}, \frac{\delta}{2T}), 4\ln\left(\frac{2T}{\delta}\right)\right\}$ (as defined in Step 1). Then, for each $1 \leq i \leq m$, let $X_{t,i}$ be a random variable counting the number of samples (x, y) drawn from D until a sample $(x, y) \in \bar{R}_{1:t-1}$ is obtained. Notice that $X_{t,i}$ is a geometric random variable with expectation $1/p_t$ where $p_t = \Pr_{x \sim D}[\bar{R}_{1:t}]$. Then, the expected number of samples drawn from D in round t is $\mathbb{E}[\sum_{i=1}^{m} X_{t,i}] = \frac{m}{p_t}$. By applying a standard concentration inequality for the sums of i.i.d. geometric random variables [4], we get

$$\Pr\left[\sum_{i=1}^{m} X_{t,i} > 2\frac{m}{p_t}\right] \leq e^{-\frac{2m(1-1/2)^2}{2}} = e^{-\frac{m}{4}} \leq \frac{\delta}{2T},$$

where the last inequality follows from our choice of m. By a standard union bound, we get that with probability at least $1 - \frac{\delta}{2}$, the total number of samples $\sum_{t=1}^{T} \sum_{i=1}^{m} X_{t,i} \leq \sum_{t=1}^{T} 2\frac{m}{p_t} = 2m \sum_{t=1}^{T} \frac{1}{p_t} \leq \frac{4mT}{\epsilon}$. $\qquad\square$

4 The Necessity of barely robust learning

We have established in Section 3 (Theorem 1) that our proposed notion of barely robust learning in Definition 1 *suffices* for strongly robust learning. But is our notion actually *necessary* for strongly robust learning? In particular, notice that in our proposed notion of barely robust learning in Definition 1, we require β-robustness with respect to a "larger" perturbation set $\mathcal{U}^{-1}(\mathcal{U})$, instead of the actual perturbation set $\mathcal{U}$ that we care about. Is this necessary? or can we perhaps boost robustness even with the weaker guarantee of β-robustness with respect to $\mathcal{U}$?

In this section, we answer this question in the negative. First, we provably show in Theorem 4 that strongly robust learning with respect to $\mathcal{U}$ implies barely robust learning with respect to $\mathcal{U}^{-1}(\mathcal{U})$. This indicates that our proposed notion of barely robust learning with respect to $\mathcal{U}^{-1}(\mathcal{U})$ (Definition 1) is *necessary* for strongly robust learning with respect to $\mathcal{U}$. Second, we provably show in Theorem 6 that barely robust learning with respect to $\mathcal{U}$ does *not* imply strongly robust learning with respect to $\mathcal{U}$ when the robustness parameter $\beta \leq \frac{1}{2}$ which is the main regime of interest that we study in this work.

Theorem 4. *For any $\mathcal{U}$, learner $\mathbb{B}$, and $\epsilon \in (0, 1/4)$, if $\mathbb{B}$ (ϵ, δ)-robustly learns some unknown target concept c w.r.t. $\mathcal{U}$, then there is a learner $\tilde{\mathbb{B}}$ that $(\frac{1-\epsilon}{2}, 2\epsilon, 2\delta)$-barely-robustly-learns c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$.*

We defer the proof of Theorem 4 to Appendix C, but we briefly describe the high-level strategy here. The main idea is to convert a strongly robust learner $\mathbb{B}$ with respect to $\mathcal{U}$ to a barely robust learner $\tilde{\mathbb{B}}$ with respect to $\mathcal{U}^{-1}(\mathcal{U})$. We do this with a simple *expansion* trick that modifies a predictor h robust with respect to $\mathcal{U}$ to a predictor g robust with respect to $\mathcal{U}^{-1}(\mathcal{U})$. For each label $y \in \mathcal{Y}$, we do this expansion conditional on the label to get a predictor g_y that is robust w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$ but only in the region of $\mathcal{X}$ where h predicts the label y robustly w.r.t. $\mathcal{U}$. This is described in the following key Lemma. We then use fresh samples to select predictor a g_y whose label y occurs more often.

Lemma 5. *For any distribution D over $\mathcal{X}$ and any concept $c : \mathcal{X} \to \{\pm 1\}$, given a predictor $\hat{h} : \mathcal{X} \to \{\pm 1\}$ such that $\mathrm{R}_{\mathcal{U}}(\hat{h}; D_c) \leq \epsilon$ for some $\epsilon \in (0, 1/4)$, then for each $y \in \{\pm 1\}$, the predictor g_y defined for each $x \in \mathcal{X}$ as*

$$g_y(x) \triangleq y \text{ iff } x \in \bigcup_{\tilde{x} \in \mathrm{Rob}_{\mathcal{U}}(\hat{h}) \wedge \hat{h}(\tilde{x}) = y} \mathcal{U}^{-1}(\mathcal{U}(\tilde{x})) \quad \text{satisfies}$$

$$\Pr_{x \sim D} [g_y(x) \neq c(x)] \leq 2\epsilon \text{ and } \Pr_{x \sim D} \left[x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(g_y) \right] \geq (1-\epsilon) \Pr_{x \sim D} \left[\hat{h}(x) = y \middle| x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h}) \right].$$

As mentioned earlier, Theorem 4 still leaves open the question of whether the *weaker* requirement of barely robust learning with respect to $\mathcal{U}$ suffices for strongly robust learning with respect to $\mathcal{U}$. We show next that this weaker requirement is *not* sufficient.

Theorem 6. *There is an instance space $\mathcal{X}$, a perturbation set $\mathcal{U}$, and a class $\mathcal{C}$ such that $\mathcal{C}$ is $(\beta = \frac{1}{2}, \epsilon = 0, \delta)$-barely-robustly-learnable with respect to $\mathcal{U}$, but $\mathcal{C}$ is not (ϵ, δ)-robustly-learnable with respect to $\mathcal{U}$ for any $\epsilon < 1/2$.*

We defer the proof of Theorem 6 to Appendix D, but we briefly sketch the high-level argument here. To show this impossibility result, we construct a collection of distributions that is *barely* robustly learnable w.r.t. $\mathcal{U}$ with robustness parameter $\beta = \frac{1}{2}$ and natural error $\epsilon = 0$ using a randomized predictor. We also show that it is not possible to robustly learn this collection with robust risk strictly smaller than $\frac{1}{2}$. The second part is shown by relying on a necessary condition for strongly robust learning proposed by [15] which is the finiteness of the robust shattering dimension.

5 Discussion

In this paper, we put forward a theory for *boosting* adversarial robustness. We discuss below practical implications and outstanding directions that remain to be addressed.

Practical implications. Our algorithm β-RoBoost is generic and can be used with any black-box barely robust learner $\mathbb{A}$. In the context of deep learning and ℓ_p robustness, our results suggest the following: for targeted robustness of radius γ, use an adversarial learning method [e.g., 13, 21, 6] to learn a neural net h_{NN}^1 predictor robust with radius 2γ, then filter the training examples to include *only* the ones on which h_{NN}^1 is *not* robust with radius 2γ, and repeat the training process on the filtered examples to learn a second neural net, and so on. Finally, use the cascade of neural nets $\mathrm{CAS}(h_{\mathrm{NN}}^1, h_{\mathrm{NN}}^2, \dots)$ as defined in β-RoBoost to predict.

It would be interesting to empirically explore whether adversarial learning methods [e.g., 13, 21, 6] satisfy the *barely* robust learning condition: on each round of boosting, the learning algorithm can shrink the fraction of the training examples on which the predictor from the previous round is not robust on. This is crucial for progress.

Multiclass. We would like to emphasize that our theory for boosting *barely robust* learners extends seamlessly to multiclass learning problems. In particular, when the label space $|\mathcal{Y}| > 2$, we obtain the same guarantees in Theorem 1 using the same algorithm β-RoBoost. The other direction of converting an (ϵ, δ)-robust-learner with respect to $\mathcal{U}$ to an $(\beta, 2\epsilon, 2\delta)$-barely-robust-learner with respect to $\mathcal{U}^{-1}(\mathcal{U})$ also holds, using the same technique in Theorem 4, but now we get $\beta = \frac{1-\epsilon}{|\mathcal{Y}|}$.

Relationship between robustness parameter β and error parameter ϵ. To achieve robust risk at most ϵ using a barely robust learner $\mathbb{A}$ with robustness parameter β, our algorithm β-RoBoost requires $\mathbb{A}$ to achieve a natural error of $\tilde{\epsilon} = \frac{\beta\epsilon_0}{2}$ for any constant $\epsilon_0 < \frac{1}{2}$ (say $\tilde{\epsilon} = \frac{\beta}{6}$) (see Corollary 2). It would be interesting to resolve whether requiring natural risk $\tilde{\epsilon}$ that depends on β is necessary, or whether it is possible to avoid dependence on β. Concretely, an open question here is: can we achieve robust risk at most ϵ using a $(\beta, O(\epsilon), \delta)$-barely-robust-learner instead of requiring $(\beta, O(\beta), \delta)$-barely-robust-learner? It actually suffices to answer the following: given a $(\beta, \frac{1}{3}, \delta)$-barely-robust-learner, is it possible to achieve *robust* risk at most $\frac{1}{3}$? A related question is whether it is possible to boost the error while maintaining robustness fixed at some level. For example, given a $(\beta, \frac{1}{3}, \delta)$-barely-robust-learner $\mathbb{A}$, is it possible to boost this to a $(\beta, \epsilon, \delta)$-barely-robust-learner $\mathbb{B}$?

Agnostic setting. We focused only on boosting robustness in the *realizable* setting, where the target unknown concept c and the unknown distribution D satisfy $\mathrm{R}_{\mathcal{U}}(c; D_c) = 0$, and we showed an equivalence between barely-robust-learning and strongly-robust-learning in this setting. In terms of obtaining stronger guarantees, we remark that an agnostic-to-realizable reduction described in [15, Theorem 8], implies, together with Theorem 1, that barely-robust-learning is equivalent to agnostic-robust-learning. The agnostic-to-realizable reduction in [15] is not oracle-efficient, however, so the interesting open question here is to explore oracle-efficient boosting algorithms in the agnostic setting. A key step in this direction is to identify reasonable definitions of *agnostic*-barely-robust learners that go beyond Definition 1.

Computational efficiency. Our algorithm β-RoBoost is guaranteed to terminate in at most $T = \frac{\ln(2/\epsilon)}{\beta}$ rounds of boosting (see Theorem 1), because our rejection sampling mechanism (Step 8) will safely terminate when the mass of the non-robust region becomes small (mass at most $\epsilon/2$). In each round $t > 1$ of boosting, rejection sampling (Step 7) in β-RoBoost needs to sample from the region of the distribution where all previous predictors $h_1, \dots, h_{t-1}$ are *non-robust*, and doing this computationally efficiently requires an efficient procedure to *certify* robustness of h_i on perturbation set $\mathcal{U}^{-1}(\mathcal{U})(x)$. Certifying robustness of predictors is an active area of research [e.g., randomized smoothing with ℓ_2 perturbations in 6], but is outside the scope of this work, since we make no assumptions on the form of the returned predictors h_i or the perturbation sets $\mathcal{U}$ and $\mathcal{U}^{-1}(\mathcal{U})$. In general, it's hard to imagine a world where efficient robust learning is possible without efficient certification of robustness. In other words, efficient certification of robustness seems to be a "necessary" condition for efficient robust learning, not just for our proposed boosting algorithm, but for any algorithm that is devised for robust learning. Without efficient certification of robustness, we can't even compute the robust loss, so how can we even learn.

Comparing $\mathcal{U}^{-1}(\mathcal{U})$ vs. $\mathcal{U}$. As mentioned earlier in the introduction, if $\mathcal{U}$ is a metric-ball of radius γ, then $\mathcal{U}^{-1}(\mathcal{U})$ is a metric-ball of radius 2γ. More generally, we think of robustness w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$ as being robust to "twice" the adversary's power (which is represented by $\mathcal{U}$). For example, for a

general vector space $\mathcal{X}$, if $\mathcal{U}(x) = x + B$, where B is some arbitrary symmetric set (i.e. $v \in B$ if and only if $-v \in B$), then $\mathcal{U}^{-1}(\mathcal{U})(x) = x + B + B$. We do not yet know of examples of $\mathcal{U}$ where $\mathcal{U}^{-1}(\mathcal{U})$ is much "larger" than $\mathcal{U}$, but this is an interesting direction to explore. More generally, it would be interesting to explore whether barely-robust-learning w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$ is *computationally* equivalent to strong-robust-learning w.r.t. $\mathcal{U}$.

6   Simple Experiments

We conduct simple experiments that illustrate the utility of our theoretical contribution for boosting robustness. These experiments demonstrate that our algorithm, β-RoBoost, can boost and improve the robustness of black-box learning algorithms. We describe the setup and the results below.

Datasets.   A synthetic binary classification dataset (`make_moons` from scikit-learn), and `MNIST` (rescaled by dividing by 255, and converted to binary classification of odd vs. even).

Perturbation set $\mathcal{U}$.   We consider ℓ_2 perturbations of some radius γ. In the respective datasets, we computed the minimum distance between examples from different classes and chose a radius γ that's smaller than this minimum distance.

Barely Robust Learner.   We use an off-the-shelve Linear SVM solver (from scikit-learn) as a barely-robust-learner. Using linear predictors and ℓ_2 perturbations simplifies the computation of the robust loss since it exactly corresponds to computing the margin loss [see Lemma 4.2 in 14]. Formally, for any linear predictor w and example (x, y),

$$\sup_{\|\delta\|_2 \le \gamma} \mathbb{1}[\text{sign}(\langle w, x + \delta \rangle) \neq y] = \mathbb{1}\left[y \left\langle \frac{w}{\|w\|_2}, x \right\rangle \le \gamma\right].$$

We ran our boosting algorithm, β-RoBoost, and compared it against the baseline of a single Linear SVM call. In our boosting algorithm, we run for as many rounds as possible until there are no more examples left in the training set to run LinearSVM on.

Results   On `make_moons` with perturbation radius $\gamma = 0.1$, the baseline Linear SVM achieves a robust accuracy of 84.78%, while β-RoBoost (with 2 rounds of boosting) achieves robust accuracy of 89.86%. On `MNIST` with perturbation radius $\gamma = 0.5$, the baseline Linear SVM achieves a robust accuracy of 73.9%, while β-RoBoost (with 2 rounds of boosting) achieves robust accuracy of 80.05%. Finally, on `MNIST` with a bigger perturbation radius $\gamma = 1.0$, the baseline Linear SVM achieves a robust accuracy of 48.1%, while β-RoBoost (with 2 rounds of boosting) achieves robust accuracy of 70.12%.

We observe that β-RoBoost improves the robustness of Linear SVM. Notice that even in the regime where the baseline Linear SVM archives robust-accuracy $< 50\%$ (MNIST with perturbation radius 1.0), β-RoBoost can actually improve the robust-accuracy beyond 50%.

We include code to reproduce our `MNIST` experiments with perturbation radius $\gamma = 1.0$ in Appendix F.

Acknowledgments and Disclosure of Funding

We would like to thank Steve Hanneke and Nathan Srebro for insightful discussions, and the anonymous reviewers for their detailed and valuable feedback. This work was supported in part by DARPA under cooperative agreement HR00112020003.[1] This work was supported in part by the National Science Foundation under grant CCF-1815011.

References

[1] J. D. Abernethy, P. Awasthi, and S. Kale. A multiclass boosting framework for achieving fast and provable adversarial robustness. *CoRR*, abs/2103.01276, 2021. 1.1, 1.2

---

[1]The views expressed in this work do not necessarily reflect the position or the policy of the Government and no official endorsement should be inferred. Approved for public release; distribution is unlimited.

[2] J. Alayrac, J. Uesato, P. Huang, A. Fawzi, R. Stanforth, and P. Kohli. Are labels required for improving adversarial robustness? In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, 8-14 December 2019, Vancouver, BC, Canada*, pages 12192–12202, 2019. A

[3] H. Ashtiani, V. Pathak, and R. Urner. Black-box certification and learning under adversarial perturbations. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 388–398. PMLR, 2020. A

[4] D. G. Brown. How i wasted too long finding a concentration inequality for sums of geometric variables. *Found at https://cs. uwaterloo. ca/~ browndg/negbin. pdf*, 8(4), 2011. 9, C

[5] Y. Carmon, A. Raghunathan, L. Schmidt, J. C. Duchi, and P. Liang. Unlabeled data improves adversarial robustness. In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, 8-14 December 2019, Vancouver, BC, Canada*, pages 11190–11201, 2019. A

[6] J. M. Cohen, E. Rosenfeld, and J. Z. Kolter. Certified adversarial robustness via randomized smoothing. In K. Chaudhuri and R. Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 1310–1320. PMLR, 2019. 5, 5

[7] F. Croce, M. Andriushchenko, V. Sehwag, E. Debenedetti, N. Flammarion, M. Chiang, P. Mittal, and M. Hein. Robustbench: a standardized adversarial robustness benchmark. *arXiv preprint arXiv:2010.09670*, 2020. 1

[8] Y. Freund. Boosting a weak learning algorithm by majority. In M. A. Fulk and J. Case, editors, *Proceedings of the Third Annual Workshop on Computational Learning Theory, COLT 1990, University of Rochester, Rochester, NY, USA, August 6-8, 1990*, pages 202–216. Morgan Kaufmann, 1990. 1.2

[9] Y. Freund and R. E. Schapire. A decision-theoretic generalization of on-line learning and an application to boosting. *J. Comput. Syst. Sci.*, 55(1):119–139, 1997. 1.2

[10] I. J. Goodfellow, J. Shlens, and C. Szegedy. Explaining and harnessing adversarial examples. In Y. Bengio and Y. LeCun, editors, *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. 1

[11] A. Kalai and V. Kanade. Potential-based agnostic boosting. In Y. Bengio, D. Schuurmans, J. D. Lafferty, C. K. I. Williams, and A. Culotta, editors, *Advances in Neural Information Processing Systems 22: 23rd Annual Conference on Neural Information Processing Systems 2009. Proceedings of a meeting held 7-10 December 2009, Vancouver, British Columbia, Canada*, pages 880–888. Curran Associates, Inc., 2009. 1.2

[12] M. Kearns. Thoughts on hypothesis boosting. Unpublished, Dec. 1988. 1.2

[13] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu. Towards deep learning models resistant to adversarial attacks. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. 5

[14] O. Montasser, S. Goel, I. Diakonikolas, and N. Srebro. Efficiently learning adversarially robust halfspaces with noise. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 7010–7021. PMLR, 2020. 6

[15] O. Montasser, S. Hanneke, and N. Srebro. VC classes are adversarially robustly learnable, but only improperly. In A. Beygelzimer and D. Hsu, editors, *Proceedings of the Thirty-Second Conference on Learning Theory*, volume 99 of *Proceedings of Machine Learning Research*, pages 2512–2530, Phoenix, USA, 25–28 Jun 2019. PMLR. 1.1, 1.2, 9, 4, 5, 8, 9, D, 10

[16] O. Montasser, S. Hanneke, and N. Srebro. Reducing adversarially robust learning to non-robust PAC learning. In H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. 1.2

[17] R. E. Schapire. The strength of weak learnability. *Mach. Learn.*, 5:197–227, 1990. 1.2

[18] R. E. Schapire and Y. Freund. *Boosting*. Adaptive Computation and Machine Learning. MIT Press, Cambridge, MA, 2012. 1.1, 1.2, 9, 5

[19] Y. Yang, C. Rashtchian, H. Zhang, R. Salakhutdinov, and K. Chaudhuri. A closer look at accuracy vs. robustness. In H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. 1.2

[20] D. Zhang, H. Zhang, A. Courville, Y. Bengio, P. Ravikumar, and A. S. Suggala. Building robust ensembles via margin boosting. In *International Conference on Machine Learning*, 2022. 1.2

[21] H. Zhang, Y. Yu, J. Jiao, E. P. Xing, L. E. Ghaoui, and M. I. Jordan. Theoretically principled trade-off between robustness and accuracy. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 7472–7482. PMLR, 2019. 5

A Boosting Robustness with Unlabeled Data

Prior work has shown that unlabeled data can improve adversarially robust generalization in practice [2, 5], and there is also theoretical work quantifying the benefit of unlabeled data for robust generalization [3]. In this section, we highlight yet another benefit of unlabeled data for adversarially robust learning. Specifically, we show that it is *possible* to boost robustness by relying only on *unlabeled* data.

We will start with some intuition first. For an unknown distribution D_c, imagine having access to a *non-robust* classifier h that makes no mistakes on natural examples, i.e., $\Pr_{x \sim D}[h(x) \neq c(x)] = 0$ but $\Pr_{x \sim D}[\exists z \in \mathcal{U}(x) : h(z) \neq h(x)] = 1$. Now, in order to learn a robust classifier, we can use β-RoBoost where in each round of boosting we sample unlabeled data from D (label it with h) and call a barely robust learner $\mathbb{A}$ on this *pseudo-labeled* dataset.

This highlights that perhaps robustness can be boosted using only unlabeled data if we have access to a good *pseudo-labeler* h that makes few mistakes on natural examples from D. But in case that $\Pr_{x \sim D}[h(x) \neq c(x)] = \epsilon$ for some small $\epsilon > 0$, it no longer suffices to use a barely robust learner $\mathbb{A}$ for c, but rather we need a more powerful learner that is tolerant to the noise in the labels introduced by h. Formally, we introduce the following noise-tolerant barely robust learner:

Definition 3 (Noise-Tolerant Barely Robust Learner). Learner $\mathbb{A}$ $(\eta, \beta, \epsilon, \delta)$-barely-robustly-learns a concept $c : \mathcal{X} \to \mathcal{Y}$ w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$ if there exists $m(\eta, \beta, \epsilon, \delta) \in \mathbb{N}$ such that for any distribution D over $\mathcal{X}$ satisfying $\Pr_{x \sim D}[\exists z \in \mathcal{U}(x) : c(z) \neq c(x)] = 0$ and any $h : \mathcal{X} \to \mathcal{Y}$ where $\Pr_{x \sim D}[h(x) \neq c(x)] \leq \eta$, w.p. at least $1 - \delta$ over $S \sim D_h^m$, $\mathbb{A}$ outputs a predictor $\hat{h} = \mathbb{A}(S)$ satisfying:

$$\Pr_{x \sim D}\left[x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(\hat{h})\right] \geq \beta \text{ and } \Pr_{x \sim D}\left[\hat{h}(x) \neq c(x)\right] \leq \Pr_{x \sim D}[h(x) \neq c(x)] + \epsilon \leq \eta + \epsilon.$$

In Theorem 7, we show that given a *noise-tolerant* barely robust learner $\mathbb{A}$ for some unknown target concept c (according to Definition 3), it is *possible* to strongly robustly learn c with β-URoBoost by making black-box oracle calls to $\mathbb{A}$.

Algorithm 2: β-URoBoost — Boosting Robustness with Unlabeled Data

Input: Sampling oracle for distribution D_c, black-box noise-tolerant barely-robust learner $\mathbb{A}$.
1 Draw $m = m_{\mathbb{A}}(\eta, \beta, \frac{\beta \epsilon}{4}, \frac{\delta}{2})$ labeled samples $S = \{(x_1, y_1), \ldots, (x_m, y_m)\} \sim D_c$.
2 Call learner $\mathbb{A}$ on S and let predictor $\hat{h} = \mathbb{A}(S)$ be its output.
3 Call β-RoBoost with access to labeled samples from $D_{\hat{h}}$ (i.e., $(x, \hat{h}(x)) \sim D_{\hat{h}}$), and
   black-box $(\eta, \beta, \frac{\epsilon \beta}{4}, \frac{\delta}{2T})$-noise-tolerant-barely-robust-learner $\mathbb{A}$.
Output: The cascade predictor $\mathrm{CAS}(h_1, \ldots, h_T)$.

Theorem 7. *For any perturbation set $\mathcal{U}$, β-URoBoost (ϵ, δ)-robustly-learns any target concept c w.r.t. $\mathcal{U}$ using $T + 1 \leq \frac{\ln(2/\epsilon)}{\beta} + 1$ black-box oracle calls to any $(\eta, \beta, \frac{\beta \epsilon}{4}, \frac{\delta}{2T})$-barely-robust learner $\mathbb{A}$ for c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$, with labeled sample complexity of $m_{\mathbb{A}}(\eta, \beta, \frac{\beta \epsilon}{4}, \frac{\delta}{2})$ and unlabeled sample complexity of at most*

$$\frac{4T \max\left\{m_{\mathbb{A}}(\eta, \beta, \frac{\beta \epsilon}{4}, \frac{\delta}{4T}), 4 \ln\left(\frac{4T}{\delta}\right)\right\}}{\epsilon}.$$

Proof. Let $\mathcal{U}$ be an arbitrary perturbation set, and $\mathbb{A}$ a $(\eta, \beta, \epsilon, \delta)$-barely-robust learner for some *unknown* target concept $c : \mathcal{X} \to \mathcal{Y}$ with respect to $\mathcal{U}^{-1}(\mathcal{U})$. We will show that β-URoBoost (ϵ, δ)-robustly-learns c with respect to $\mathcal{U}$. Let D be some unknown distribution over $\mathcal{X}$ such that $\Pr_{x \sim D}[\exists z \in \mathcal{U}(x) : c(z) \neq c(x)] = 0$.

By Step 1 and Step 2 and the guarantee of learner $\mathbb{A}$ (see Definition 3), with probability at least $1 - \frac{\delta}{2}$ over $S^m \sim D_c$, it holds that

$$\Pr_{x \sim D}\left[\hat{h}(x) \neq c(x)\right] \leq \frac{\beta \epsilon}{4}.$$

That is, with high probability, $\hat{h}$ is a predictor with low error on *natural* examples.

Pseudo labeling. In Step 3, β-URoBoost essentially runs β-RoBoost using unlabeled samples from D that are labeled with the predictor $\hat{h}$. Thus, we can view this as robustly learning the concept $\hat{h}$ which is only an approximation of the true concept c that we care about. Since the noise tolerance $\eta \geq \frac{\beta\epsilon}{4}$, it follows by the guarantees of learner $\mathbb{A}$ (see Definition 3) and Equation 11, that

$$\Pr_{x \sim D}\left[\exists z \in \mathcal{U}(x) : \mathrm{CAS}(h_{1:T})(z) \neq c(x)\right] \leq \frac{\Pr_{x \sim D}\left[\hat{h}(x) \neq c(x)\right]}{\beta} + \frac{\beta\epsilon}{4\beta} + (1-\beta)^T \leq \frac{\epsilon}{4} + \frac{\epsilon}{4} + \frac{\epsilon}{2} \leq \epsilon.$$

$\square$

B   Auxiliary Lemmas and Proofs for Corollary 2

Algorithm 3: α-Boost — Boosting *weakly* robust learners

Input: Training dataset $S = \{(x_1, y_1), \ldots, (x_m, y_m)\}$, black-box *weak* robust learner $\mathbb{B}$.

1 Set $m_0 = m_{\mathbb{B}}(1/3, 1/3)$.
2 Initialize D_1 to be uniform over S, and set $T = O(\log m)$.
3 **for** $1 \leq t \leq T$ **do**
4 $\quad$ Sample $S_t \sim D_t^{m_0}$, call learner $\mathbb{B}$ on S_t, and denote by h_t its output predictor. Repeat this step until $\mathrm{R}_{\mathcal{U}}(h_t; D_t) \leq 1/3$.
5 $\quad$ Compute a new distribution D_{t+1} by applying the following update for each $(x, y) \in S$:

$$D_{t+1}(\{(x,y)\}) = \frac{D_t(\{(x,y)\})}{Z_t} \times \begin{cases} e^{-2\alpha}, & \text{if } \mathbb{1}[\forall z \in \mathcal{U}(x) : h_{t-1}(z) = y] = 1; \\ 1, & \text{otherwise,} \end{cases}$$

$\quad$ where Z_t is a normalization factor and $\alpha = 1/8$.

Output: A majority-vote classifier $\mathrm{MAJ}(h_1, \ldots, h_T)$.

Before proceeding with the proof of Corollary 2, we state the following guarantee that α-Boost provides for boosting weakly robust learners.

Lemma 8 ([15])**.** *For any perturbation set $\mathcal{U}$, α-Boost (ϵ, δ)-robustly-learns any target concept c w.r.t. $\mathcal{U}$ using T black-box oracle calls to any $(\frac{1}{3}, \frac{1}{3})$-robust-learner $\mathbb{B}$ for c w.r.t. $\mathcal{U}$, with total sample complexity*

$$m(\epsilon, \delta) = O\left(\frac{m_{\mathbb{B}}(1/3, 1/3)}{\epsilon} \log^2\left(\frac{m_{\mathbb{B}}(1/3, 1/3)}{\epsilon}\right) + \frac{\log(1/\delta)}{\epsilon}\right),$$

and oracle calls $T = O(\log(m)(\log(1/\delta) + \log\log m))$.

Lemma 9 (Sample Compression Robust Generalization Guarantee – [15])**.** *For any $k \in \mathbb{N}$ and fixed function $\phi : (\mathcal{X} \times \mathcal{Y})^k \to \mathcal{Y}^{\mathcal{X}}$, for any distribution P over $\mathcal{X} \times \mathcal{Y}$ and any $m \in \mathbb{N}$, for $S = \{(x_1, y_1), \ldots, (x_m, y_m)\}$ i.i.d. P-distributed random variables, with probability at least $1 - \delta$, if $\exists i_1, \ldots, i_k \in \{1, \ldots, m\}$ s.t. $\hat{R}_{\mathcal{U}}(\phi((x_{i_1}, y_{i_1}), \ldots, (x_{i_k}, y_{i_k})); S) = 0$, then*

$$\mathrm{R}_{\mathcal{U}}(\phi((x_{i_1}, y_{i_1}), \ldots, (x_{i_k}, y_{i_k})); P) \leq \frac{1}{m - k}(k \ln(m) + \ln(1/\delta)).$$

Proof of Lemma 8. Let $\mathbb{B}$ be a *weak* robust learner with fixed parameters $(\epsilon_0, \delta_0) = (1/3, 1/3)$ for some *unknown* target concept c with respect to $\mathcal{U}$. Let D be some unknown distribution over $\mathcal{X}$ such that $\Pr_{x \sim D}[\exists z \in \mathcal{U}(x) : c(z) \neq c(x)] = 0$. By Definition 2, with fixed sample complexity $m_0 = m_{\mathbb{B}}(1/3, 1/3)$, for any distribution $\tilde{D}$ over $\mathcal{X}$ such that $\Pr_{x \sim \tilde{D}}[\exists z \in \mathcal{U}(x) : c(z) \neq c(x)] = 0$, with probability at least $1/3$ over $S \sim \tilde{D}_c^{m_0}$, $\mathrm{R}_{\mathcal{U}}(\mathbb{B}(S); \tilde{D}_c) \leq 1/3$.

We will now boost the confidence and robust error guarantee of the *weak* robust learner $\mathbb{B}$ by running boosting with respect to the *robust* loss (rather than the standard 0-1 loss). Specifically, fix $(\epsilon, \delta) \in (0, 1)$ and a sample size $m(\epsilon, \delta)$ that will be determined later. Let $S = \{(x_1, y_1), \ldots, (x_m, y_m)\}$ be an i.i.d. sample from D_c. Run the α-Boost algorithm on dataset S using $\mathbb{B}$ as the weak robust learner

for a number of rounds T that will be determined below. On each round t, α-Boost computes an empirical distribution D_t over S by applying the following update for each $(x, y) \in S$:

$$D_t(\{(x,y)\}) = \frac{D_{t-1}(\{(x,y)\})}{Z_{t-1}} \times \begin{cases} e^{-2\alpha}, & \text{if } \mathbb{1}[\forall z \in \mathcal{U}(x) : h_{t-1}(z) = y] = 1; \\ 1, & \text{otherwise,} \end{cases}$$

where Z_{t-1} is a normalization factor, α is a parameter that will be determined below, and h_{t-1} is the *weak* robust predictor outputted by $\mathbb{B}$ on round $t-1$ that satisfies $\mathrm{R}_\mathcal{U}(h_{t-1}; D_{t-1}) \leq 1/3$. Once D_t is computed, we sample m_0 examples from D_t and run *weak* robust learner $\mathbb{B}$ on these examples to produce a hypothesis h_t with robust error guarantee $\mathrm{R}_\mathcal{U}(h_t; D_t) \leq 1/3$. This step has failure probability at most $\delta_0 = 1/3$. We will repeat it for at most $\lceil \log(2T/\delta) \rceil$ times, until $\mathbb{B}$ succeeds in finding h_t with robust error guarantee $\mathrm{R}_\mathcal{U}(h_t; D_t) \leq 1/3$. By a union bound argument, we are guaranteed that with probability at least $1 - \delta/2$, for each $1 \leq t \leq T$, $\mathrm{R}_\mathcal{U}(h_t; D_t) \leq 1/3$. Following the argument from [18, Section 6.4.2], after T rounds we are guaranteed

$$\min_{(x,y)\in S} \frac{1}{T} \sum_{t=1}^{T} \mathbb{1}[\forall z \in \mathcal{U}(x) : h_t(z) = y] \geq \frac{2}{3} - \frac{2}{3}\alpha - \frac{\ln(|S|)}{2\alpha T},$$

so we will plan on running until round $T = 1 + 48\ln(|S|)$ with value $\alpha = 1/8$ to guarantee

$$\min_{(x,y)\in S} \frac{1}{T} \sum_{t=1}^{T} \mathbb{1}[\forall z \in \mathcal{U}(x) : h_t(z) = y] > \frac{1}{2},$$

so that the majority-vote classifier $\mathrm{MAJ}(h_1, \ldots, h_T)$ achieves *zero* robust loss on the empirical dataset S, $\mathrm{R}_\mathcal{U}(\mathrm{MAJ}(h_1, \ldots, h_L); S) = 0$.

Note that each of these classifiers h_t is equal to $\mathbb{B}(S_t')$ for some $S_t' \subseteq S$ with $|S_t'| = m_0$. Thus, the classifier $\mathrm{MAJ}(h_1, \ldots, h_T)$ is representable as the value of an (order-dependent) reconstruction function ϕ with a compression set size $m_0 T = m_0 O(\log m)$. Now, invoking Lemma 9, with probability at least $1 - \delta/2$,

$$\mathrm{R}_\mathcal{U}(\mathrm{MAJ}(h_1, \ldots, h_T); \mathcal{D}) \leq O\left(\frac{m_0 \log^2 m}{m} + \frac{\log(2/\delta)}{m}\right),$$

and setting this less than ϵ and solving for a sufficient size of m yields the stated sample complexity bound. □

We are now ready to proceed with the proof of Corollary 2.

Proof of Corollary 2. The main idea is to perform two layers of boosting. In the first layer, we use β-RoBoost to get a *weak* robust learner for c w.r.t. $\mathcal{U}$ from a *barely* robust learner $\mathbb{A}$ for c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$. Then, in the second layer, we use α-Boost to boost β-RoBoost from a *weak* robust learner to a *strong* robust learner for c w.r.t. $\mathcal{U}$.

Let $\mathbb{A}$ be a $(\beta, \frac{\beta}{6}, \frac{\beta}{6\ln(6)})$-barely-robust-learner $\mathbb{A}$ for c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$. Let $(\epsilon_0, \delta_0, T_0) = (\frac{1}{3}, \frac{1}{3}, \frac{\ln(6)}{\beta})$, and observe that $\mathbb{A}$ is a $(\beta, \frac{\beta\epsilon_0}{2}, \frac{\delta_0}{2T_0})$-barely-robust-learner for c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$. By Theorem 1, β-RoBoost (ϵ_0, δ_0)-robustly-learns c w.r.t. $\mathcal{U}$ using T_0 black-box oracle calls to $\mathbb{A}$, with sample complexity $m_0 = O\left(\frac{\max\{m_\mathbb{A}, 4\ln\left(\frac{6\ln(6)}{\beta}\right)\}}{\beta}\right)$. Finally, by Lemma 8, α-Boost (ϵ, δ)-robustly-learns c w.r.t. $\mathcal{U}$ using $m(\epsilon, \delta) = O\left(\frac{m_0}{\epsilon}\log\left(\frac{m_0}{\epsilon}\right) + \frac{\log(1/\delta)}{\epsilon}\right)$ samples, and $O(\log m)$ black-box oracle calls to β-RoBoost. □

C Proof of Theorem 4

Proof of Lemma 5. Without loss of generality, let $y = +1$. Let $x \in \mathrm{supp}(D)$ such that $x \in \mathrm{Rob}_\mathcal{U}(\hat{h})$. In case $\hat{h}(x) = +1$, then by definition of g_+, since $x \in \mathcal{U}^{-1}(\mathcal{U}(x))$, it holds that $g_+(x) = +1$. In case $\hat{h}(x) = -1$, then $\neg \exists \tilde{x} \in \mathrm{Rob}_\mathcal{U}(\hat{h})$ such that $\hat{h}(\tilde{x}) = +1$ and $\mathcal{U}(\tilde{x}) \cap \mathcal{U}(x) \neq \emptyset$, which implies that $x \notin \bigcup_{\tilde{x} \in \mathrm{Rob}_\mathcal{U}(\hat{h}) \wedge \hat{h}(\tilde{x}) = +1} \mathcal{U}^{-1}(\mathcal{U}(\tilde{x}))$, and therefore, $g_+(x) = -1$. This establishes that in the

robust region of $\hat{h}$, $\mathrm{Rob}_{\mathcal{U}}(\hat{h})$, the predictions of g_+ on *natural* examples $x \sim D$ are equal to the predictions of $\hat{h}$. We will use this observation, in addition to the fact that the robust risk of $\hat{h}$ is small $\left(\mathrm{Pr}_{x \sim D}\left[\exists z \in \mathcal{U}(x) : \hat{h}(z) \neq c(x)\right] \leq \epsilon\right)$ to show that the error of g_+ on natural examples is small. Specifically, by law of total probability,

$$
\begin{aligned}
\Pr_{x \sim D}\left[g_+(x) \neq c(x)\right] &= \Pr_{x \sim D}\left[g_+(x) \neq c(x) \wedge x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] + \Pr_{x \sim D}\left[g_+(x) \neq c(x) \wedge x \notin \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] \\
&= \Pr_{x \sim D}\left[\hat{h}(x) \neq c(x) \wedge x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] + \Pr_{x \sim D}\left[g_+(x) \neq c(x) \wedge x \notin \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] \\
&\leq \Pr_{x \sim D}\left[\hat{h}(x) \neq c(x) \wedge x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] + \Pr_{x \sim D}\left[x \notin \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] \leq \epsilon + \epsilon = 2\epsilon.
\end{aligned}
$$

Finally, observe that for any $x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})$ such that $\hat{h}(x) = +1$, by definition of g_+, it holds that $x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(g_+)$, thus

$$
\begin{aligned}
\Pr_{x \sim D}\left[x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(g_+)\right] &\geq \Pr_{x \sim D}\left[x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h}) \wedge \hat{h}(x) = +1\right] \\
&= \Pr_{x \sim D}\left[x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] \Pr_{x \sim D}\left[\hat{h}(x) = +1 \big| x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] \\
&\geq (1 - \epsilon) \Pr_{x \sim D}\left[\hat{h}(x) = +1 \big| x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right].
\end{aligned}
$$

$\square$

Proof of Theorem 4. Let $\mathcal{U}$ be an arbitrary perturbation set, and $\mathbb{B}$ an (ϵ, δ)-robust learner for some *unknown* target concept $c : \mathcal{X} \to \mathcal{Y}$ with respect to $\mathcal{U}$. We will construct another learner $\tilde{\mathbb{B}}$ that $(\beta, 2\epsilon, 2\delta)$-barely-robustly-learns c with respect to $\mathcal{U}^{-1}(\mathcal{U})$, with $\beta = (1 - \epsilon)/2$. Let D be some unknown distribution over $\mathcal{X}$ that is robustly realizable: $\Pr_{x \sim D}\left[\exists z \in \mathcal{U}(x) : c(z) \neq c(x)\right] = 0$.

Description of $\tilde{\mathbb{B}}$. Sample $S \sim D_c^{m_{\mathbb{B}}(\epsilon, \delta)}$, and run learner $\mathbb{B}$ on S. Let $\hat{h} = \mathbb{B}(S)$ be the predictor returned by $\mathbb{B}$. Let $\tilde{m} \geq \frac{64}{9} \ln(1/\delta)$. For each $1 \leq i \leq \tilde{m}$, consider the following process: draw an example $(x, y) \sim D_c$. If $x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})$ terminate, otherwise repeat the process again. Let $\tilde{S} = \{(x_1, y_1), \ldots, (x_{\tilde{m}}, y_{\tilde{m}})\}$ be the sample resulting from this process. Calculate $M_+ = \frac{1}{|\tilde{S}|} \sum_{x \in \tilde{S}} \mathbb{1}[\hat{h}(x) = +1]$. If $M_+ \geq 1/2$, output g_+, otherwise output g_- (as defined in Lemma 5).

Analysis. With probability at least $1 - \delta$ over $S \sim D_c^m$, $\hat{h}$ has small robust risk: $\mathrm{R}_{\mathcal{U}}(\hat{h}; D_c) \leq \epsilon$. Lemma 5 implies then that for each $y \in \{\pm 1\}$, g_y satisfies:

$$
\Pr_{x \sim D}\left[g_y(x) \neq c(x)\right] \leq 2\epsilon \quad \text{and} \quad \Pr_{x \sim D}\left[x \in \mathrm{Rob}_{\mathcal{U}^{-1}(\mathcal{U})}(g_y)\right] \geq (1 - \epsilon) \Pr_{x \sim D}\left[\hat{h}(x) = y \big| x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right].
$$

It remains to show that with probability at least $1 - \delta$ over $\tilde{S} \sim D^{\tilde{m}}$, for $g_{\hat{y}}$ returned by $\tilde{\mathbb{B}}$:

$$
\Pr_{x \sim D}\left[\hat{h}(x) = \hat{y} \big| x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] \geq \frac{1}{2}.
$$

Observe that by the rejection sampling mechanism of $\tilde{\mathbb{B}}$, $\tilde{S}$ is a sample from the region of distribution D where $\hat{h}$ is robust. Furthermore, we know that

$$
\max\left\{ \Pr_{x \sim D}\left[\hat{h}(x) = +1 \big| x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right], \Pr_{x \sim D}\left[\hat{h}(x) = -1 \big| x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right]\right\} \geq \frac{1}{2}.
$$

Without loss of generality, suppose that $p = \Pr_{x \sim D}\left[\hat{h}(x) = +1 \big| x \in \mathrm{Rob}_{\mathcal{U}}(\hat{h})\right] \geq 1/2$. Then, the failure event is that $\tilde{\mathbb{B}}$ outputs g_-, i.e. the event that $M_+ < \frac{1}{2}$. By a standard application of the Chernoff bound, we get that

$$
\Pr_{\tilde{S}}\left[M_+ < \frac{1}{2}\right] \leq e^{\frac{-\tilde{m} p \frac{1}{4}\left(\frac{1}{2} - \frac{1}{p}\right)^2}{2}} \leq e^{-\frac{9\tilde{m}}{64}} \leq \delta,
$$

where the last inequality follows from the choice of $\tilde{m}$ in the description of $\tilde{\mathbb{B}}$.

Finally, to conclude, observe that the sample complexity of learner $\tilde{\mathbb{B}}$ is equal to $m_{\mathbb{B}}(\epsilon, \delta)$ plus the number of samples drawn from D to construct $\tilde{S}$. For each $1 \le i \le \tilde{m}$, let X_i be the number of samples drawn from D until a sample from the robust region $\mathrm{Rob}_{\mathcal{U}}(\hat{h})$ was observed. Note that X_i is a geometric random variable with mean at most $1/(1 - \epsilon)$. By a standard concentration inequality for the sums of i.i.d. geometric random variables [4],

$$\Pr\left[\sum_{i=1}^{\tilde{m}} X_i > 2\frac{\tilde{m}}{1 - \epsilon}\right] \le e^{-\frac{\tilde{m}}{4}} \le \delta,$$

where the last inequality follows from the choice of $\tilde{m}$ in the description of $\tilde{\mathbb{B}}$. Thus, with probability at least $1 - \delta$, the total sample complexity is $m_{\mathbb{B}}(\epsilon, \delta) + \frac{2\tilde{m}}{1 - \epsilon}$. This concludes that learner $\tilde{\mathbb{B}}$ $(\beta, 2\epsilon, 2\delta)$-barely-robustly-learns c w.r.t. $\mathcal{U}^{-1}(\mathcal{U})$, where $\beta = (1 - \epsilon)/2$. $\qquad\square$

D Proof of Theorem 6

Definition 4 (Robust Shattering Dimension). A sequence $z_1, \ldots, z_k \in \mathcal{X}$ is said to be $\mathcal{U}$-robustly shattered by $\mathcal{C}$ if $\exists x_1^+, x_1^-, \ldots, x_k^+, x_k^- \in \mathcal{X}$ such that $\forall i \in [k], z_i \in \mathcal{U}(x_i^+) \cap \mathcal{U}(x_i^-)$ and $\forall y_1, \ldots, y_k \in \{\pm 1\} : \exists h \in \mathcal{C}$ such that $h(z') = y_i \forall z' \in \mathcal{U}(x_i^{y_i}), \forall 1 \le i \le k$. The $\mathcal{U}$-robust shattering dimension $\dim_{\mathcal{U}}(\mathcal{C})$ is defined as the largest k for which there exist k points $\mathcal{U}$-robustly shattered by $\mathcal{C}$.

The following lemma due to [15] states that finite robust shattering dimension $\dim_{\mathcal{U}}(\mathcal{C})$ is *necessary* for strongly robustly learning $\mathcal{C}$ with respect to $\mathcal{U}$.

Lemma 10 ([15]). *For any class $\mathcal{C}$ and any perturbation set $\mathcal{U}$, $\mathcal{C}$ is (ϵ, δ)-robustly-learnable with respect to $\mathcal{U}$ only if $\dim_{\mathcal{U}}(\mathcal{C})$ is finite.*

We are now ready to proceed with the proof of Theorem 6.

Proof of Theorem 6. Pick three infinite unique sequences $(x_n^+)_{n \in \mathbb{N}}$, $(x_n^-)_{n \in \mathbb{N}}$, and $(z_n)_{n \in \mathbb{N}}$ from $\mathbb{R}^2$ such that for each $n \in \mathbb{N} : x_n^+ = (n, 1), x_n^- = (n, -1), z_n = (n, 0)$, and let $\mathcal{X} = \cup_{n \in \mathbb{N}}\{x_n^+, x_n^-, z_n\}$. We now describe the construction of the perturbation set $\mathcal{U}$. For each $n \in \mathbb{N}$, let $\mathcal{U}(x_n^+) = \{x_n^+, z_n\}, \mathcal{U}(x_n^-) = \{x_n^-, z_n\}$, and $\mathcal{U}(z_n) = \{z_n, x_n^+, x_n^-\}$.

We now describe the construction of the concept class $\mathcal{C}$. For each $\boldsymbol{y} \in \{\pm 1\}^{\mathbb{N}}$ define $h_{\boldsymbol{y}} : \mathcal{X} \to \mathcal{Y}$ to be:
$$\forall n \in \mathbb{N} : h_{\boldsymbol{y}}(z_n) = y_n \wedge h_{\boldsymbol{y}}(x_n^+) = +1 \wedge h_{\boldsymbol{y}}(x_n^-) = -1. \tag{12}$$

Let $\mathcal{C} = \left\{h_{\boldsymbol{y}} : \boldsymbol{y} \in \{\pm 1\}^{\mathbb{N}}\right\}$. Observe that by construction of $\mathcal{U}$ and $\mathcal{C}$, $\mathcal{C}$ robustly shatters the sequence $(z_n)_{n \in \mathbb{N}}$ with respect to $\mathcal{U}$ (see Definition 4), and therefore, the robust shattering dimension of $\mathcal{C}$ with respect to $\mathcal{U}$, $\dim_{\mathcal{U}}(\mathcal{C})$, is infinite. Thus, Lemma 10 implies that $\mathcal{C}$ is not (ϵ, δ)-*strongly-robustly-learnable* with respect to $\mathcal{U}$.

We will now show that there is a simple learner $\mathbb{A}$ that $(\beta, \epsilon, \delta)$-*barely*-robustly-learns $\mathcal{C}$ with respect to $\mathcal{U}$, with robustness parameter $\beta = \frac{1}{2}$ and natural error $\epsilon = 0$. Specifically, $\mathbb{A}$ samples a bitstring $\tilde{\boldsymbol{y}} \in \{\pm 1\}^{\mathbb{N}}$ uniformly at random, and outputs the classifier $h_{\tilde{\boldsymbol{y}}}$. Learner $\mathbb{A}$ will not require any data as input.

We now proceed with analyzing the performance of learner $\mathbb{A}$. Let $h_{\boldsymbol{y}} \in \mathcal{C}$ be some unknown target concept and D be some unknown distribution over $\mathcal{X}$ that is robustly realizable: $\Pr_{x \sim D}[\exists z \in \mathcal{U}(x) : h_{\boldsymbol{y}}(z) \ne y] = 0$. Since D is robustly realizable, by construction of $\mathcal{U}$ and $\mathcal{C}$, this implies that
$$\forall n \in \mathbb{N} : D(z_n) = 0 \text{ and } D(x_n^{-y_n}) = 0. \tag{13}$$
This is because $\mathcal{U}(z_n) = \{z_n, x_n^+, x_n^-\}$ and Equation 12 implies that $h_{\boldsymbol{y}}$ is not robust on z_n since $h_{\boldsymbol{y}}(x_n^+) \ne h_{\boldsymbol{y}}(x_n^-)$, also $\mathcal{U}(x_n^+) \cap \mathcal{U}(x_n^-) = \{z_n\}$ and since $h_{\boldsymbol{y}}(z_n) = y_n$ this implies that $h_{\boldsymbol{y}}$ is not robust on $x_n^{-y_n}$. Equation 13 and Equation 12 together imply that the random classifier $h_{\tilde{\boldsymbol{y}}} \in \mathcal{C}$ selected by learner $\mathbb{A}$ has *zero* error on *natural* examples: with probability 1 over $\tilde{\boldsymbol{y}}$, $\Pr_{x \sim D}[h_{\tilde{\boldsymbol{y}}}(x) \ne h_{\boldsymbol{y}}(x)] = 0$.

We now turn to analyzing the *robust* risk of learner $\mathbb{A}$,

$$
\begin{aligned}
\mathbb{E}_{\tilde{\boldsymbol{y}}}\left[\mathbb{E}_{x\sim D}\left[\mathbb{1}\left\{\exists z\in\mathcal{U}(x):h_{\tilde{\boldsymbol{y}}}(z)\neq h_{\boldsymbol{y}}(x)\right\}\right]\right] &= \mathbb{E}_{x\sim D}\left[\mathbb{E}_{\tilde{\boldsymbol{y}}}\left[\mathbb{1}\left\{\exists z\in\mathcal{U}(x):h_{\tilde{\boldsymbol{y}}}(z)\neq h_{\boldsymbol{y}}(x)\right\}\right]\right] \\
&= \sum_{n\in\mathbb{N}} D(x_n^{y_n})\mathbb{E}_{\tilde{\boldsymbol{y}}}\left[\mathbb{1}\left\{\exists z\in\mathcal{U}(x_n^{y_n}):h_{\tilde{\boldsymbol{y}}}(z)\neq h_{\boldsymbol{y}}(x_n^{y_n})\right\}\right] \\
&= \sum_{n\in\mathbb{N}} D(x_n^{y_n})\mathbb{E}_{\tilde{\boldsymbol{y}}}\left[\mathbb{1}\left\{h_{\tilde{\boldsymbol{y}}}(z_n)\neq h_{\boldsymbol{y}}(x_n^{y_n})\right\}\right] \\
&= \sum_{n\in\mathbb{N}} D(x_n^{y_n})\mathbb{E}_{\tilde{\boldsymbol{y}}}\left[\mathbb{1}\left\{\tilde{y}_n\neq y_n\right\}\right] = \sum_{n\in\mathbb{N}} D(x_n^{y_n})\frac{1}{2} = \frac{1}{2}.
\end{aligned}
$$

This implies that in expectation over randomness of learner $\mathbb{A}$, it will be robust on half the mass of distribution D: $\mathbb{E}_{\tilde{\boldsymbol{y}}}\mathbb{E}_{x\sim D}\mathbb{1}[x\in\mathrm{Rob}_{\mathcal{U}}(h_{\tilde{\boldsymbol{y}}})] = \frac{1}{2}$. $\qquad\square$

E Robustness at Different Levels of Granularity

For concreteness, throughout the rest of this section, we consider robustness with respect to metric balls $\mathrm{B}_\gamma(x) = \{z\in\mathcal{X}:\rho(x,z)\leq\gamma\}$ where ρ is some metric on $\mathcal{X}$ (e.g., ℓ_∞ metric), and $\gamma>0$ is the perturbation radius. Achieving small robust risk with respect to a *fixed* perturbation set B_γ is the common goal studied in adversarially robust learning. What we studied so far in this work is learning a predictor $\hat{h}$ robust to $\mathcal{U}=\mathrm{B}_\gamma$ perturbations as measured by the robust risk: $\Pr_{(x,y)\sim D}\left[\exists z\in\mathrm{B}_\gamma(x):\hat{h}(z)\neq y\right]$, when given access to a learner $\mathbb{A}$ barely robust with respect to $\mathcal{U}^{-1}(\mathcal{U})=\mathrm{B}_{2\gamma}$.

Our original approach to boosting robustness naturally leads us to an alternate interesting idea: learning a cascade of robust predictors with different levels of granularity. This might be desirable in situations where it is difficult to robustly learn a distribution D_c over $\mathcal{X}\times\mathcal{Y}$ with robustness granularity γ everywhere, and thus, we settle for a weaker goal which is first learning a robust predictor h_1 with granularity γ on say β mass of D, and then recursing on the conditional distribution of D where h_1 is not γ-robust and learning a robust predictor h_2 with granularity $\gamma/2$, and so on. That is, we are adaptively learning a sequence of predictors $h_1,\ldots,h_T$ where each predictor h_t is robust with granularity $\frac{\gamma}{2^t}$. Furthermore, if we are guaranteed that in each round we make progress on some β mass then it follows that

$$
\Pr\left[\cup_{t=1}^T\mathrm{Rob}_{\gamma/2^{t-1}}(h_t)\right] = 1 - \Pr\left[\cap_{t=1}^T\overline{\mathrm{Rob}}_{\gamma/2^{t-1}}(h_t)\right] \geq 1 - (1-\beta)^T,
$$

and the cascade predictor $\mathrm{CAS}(h_{1:T})$ has the following robust risk guarantee

$$
\sum_{t=1}^T\Pr\left[\bar{R}_{1:t-1}\wedge\left(\exists z\in\mathrm{B}_{\gamma/2^t}(x):\forall_{t'<t}G_{h_{t'}}(z)=\perp\wedge G_{h_t}(z)=1-c(x)\right)\right]+\Pr\left[\bar{R}_{1:T}\right] \leq \frac{\epsilon}{\beta}+(1-\beta)^T.
$$

In words, the cascade predictor $\mathrm{CAS}(h_{1:T})$ offers robustness at different granularities. That is, for $x\sim D$ such that $x\in R_1$, $\mathrm{CAS}(h_{1:T})$ is guaranteed to be robust on x with granularity γ, and for $x\sim D$ such that $x\in\bar{R}_1\cap R_2$, $\mathrm{CAS}(h_{1:T})$ is guaranteed to be robust on x with granularity $\gamma/2$, and so on.

Applications. We give a few examples where this can be useful. Consider using SVMs as barely robust learners. SVMs are known to be margin maximizing learning algorithms, which is equivalent to learning linear predictors robust to ℓ_2 perturbations. In our context, by combining SVMs with our boosting algorithm, we can learn a cascade of linear predictors each with a maximal margin on the conditional distribution.

F   Python Code

```python
# MNIST odd vs. even
from torchvision import datasets, transforms
from sklearn.preprocessing import StandardScaler
from sklearn.pipeline import make_pipeline
from sklearn.svm import LinearSVC

def flatten(X):
    return X.reshape(X.shape[0], -1)

train_set = datasets.MNIST('./', train=True, download=True, transform
    = transforms.Compose([transforms.ToTensor()]))
test_set = datasets.MNIST('./', train=False, download=True, transform
    = transforms.Compose([transforms.ToTensor()]))

X_train = train_set.train_data.numpy()
y_train = train_set.train_labels.numpy()
X_test = test_set.test_data.numpy()
y_test = test_set.test_labels.numpy()
# Convert to binary labels
y_train_binary = 2*np.array([y % 2 for y in y_train])-1
y_test_binary = 2*np.array([y % 2 for y in y_test])-1

#flatten data
f_X_tr = flatten(X_train) / 255.0
f_X_te = flatten(X_test) / 255.0

# sample size, and robustness radius
m, gamma, T = 10000, 1.0, 2

# fit a linear classifier
print('====================================================')
print('Baseline Linear Classifier:')
base_clf = LinearSVC(C=10e-7, fit_intercept=False, loss='hinge', tol=1
    e-5)
base_clf.fit(f_X_tr, y_train_binary)
print("0-1 Accuracy - Testing:", 100*base_clf.score(f_X_te,
    y_test_binary))

# robust accuracy
y_margin = y_test_binary*(base_clf.decision_function(f_X_te) / np.
    linalg.norm(base_clf.coef_))
robust_accuracy = len(y_margin[y_margin >= gamma]) / len(y_margin)
print('Robust Accuracy - Test:', 100*robust_accuracy)

y_margin = y_train_binary*(base_clf.decision_function(f_X_tr) / np.
    linalg.norm(base_clf.coef_))
robust_accuracy = len(y_margin[y_margin >= gamma]) / len(y_margin)
print('====================================================')

# boosting rounds
print('\nBoosting Robustness')
clf = []
for t in range(1,T+1):
    print("round ", t)
    # SVM
    lin_clf = LinearSVC(C=10e-7, fit_intercept=False, loss='hinge',
        tol=1e-5)
    lin_clf.fit(f_X_tr, y_train_binary)
    clf.append(lin_clf)

    if t < T:
        # Compute margin on fresh sample
```

```python
        margin = lin_clf.decision_function(f_X_tr) / np.linalg.norm(
            lin_clf.coef_)
        amargin = abs(margin)
        print("Fraction of Training Data with Robustness at least 2
            gamma: ", 100*float(len(amargin[amargin >= 2*gamma])/len(
            amargin)))
        print(len(amargin[amargin < 2*gamma]), " samples with small
            margin")

        # Update / Filter training data
        f_X_tr = f_X_tr[amargin < 2*gamma]
        y_train_binary = y_train_binary[amargin < 2*gamma]

# Evaluation
print('\nEvaluation - Test')
print('number of test samples', len(y_test_binary))
adv_mistake = 0
total = len(y_test_binary)
for t in range(0,T):
    print('round ', t)
    amargin = abs(clf[t].decision_function(f_X_te) / np.linalg.norm(
        clf[t].coef_))
    y_margin = y_test_binary*(clf[t].decision_function(f_X_te) / np.
        linalg.norm(clf[t].coef_))
    adv_mistake += len(y_test_binary[y_margin < -1*gamma])
    print('adversarial mistakes', len(y_test_binary[y_margin < -1*
        gamma]))

    f_X_te = f_X_te[(y_margin < 2*gamma) & (y_margin >= -1*gamma)]
    y_test_binary = y_test_binary[(y_margin < 2*gamma) & (y_margin >=
        -1*gamma)]
    print('abstained on data', len(y_test_binary), len(f_X_te))

    # last round
    if t == T-1 and len(f_X_te)>0:
        y_margin = y_test_binary*(clf[t].decision_function(f_X_te) /
            np.linalg.norm(clf[t].coef_))
        print('classifications in final round', len(y_margin))
        ee = len(y_test_binary[(y_margin < gamma)])
        print('extra mistakes', ee)
        adv_mistake += ee

print('total number of adv. mistakes', adv_mistake)
print('==================================================')
print('Cascade Robust Accuracy:', 100*float((total - adv_mistake)/
    total) )
print('==================================================')
```