A quantitative analysis of semantic information in deep representations of text and images

Abstract

It was recently observed that the representations of different models that process identical or semantically related inputs tend to align. We analyze this phenomenon using the Information Imbalance, an asymmetric rank-based measure that quantifies the capability of a representation to predict another, providing a proxy of the cross-entropy which can be computed efficiently in high-dimensional spaces. By measuring the Information Imbalance between representations generated by DeepSeek-V3 processing translations, we find that semantic information is spread across many tokens, and that semantic predictability is strongest in a set of central layers of the network, robust across six language pairs. We measure clear information asymmetries: English representations are systematically more predictive than those of other languages, and DeepSeek-V3 representations are more predictive of those in a smaller model such as Llama3-8b than the opposite. In the visual domain, we observe that semantic information concentrates in middle layers for autoregressive models and in final layers for encoder models, and these same layers yield the strongest cross-modal predictability with textual representations of image captions. Notably, two independently trained models (DeepSeek-V3 and DinoV2) achieve stronger cross-modal predictability than the jointly trained CLIP model, suggesting that model scale may outweigh explicit multimodal training. Our results support the hypothesis of semantic convergence across languages, modalities, and architectures, while showing that directed predictability between representations varies strongly with layer-depth, model scale, and language.

1 Introduction

Large transformers encode information in high-dimensional spaces, transforming representations across layers to perform a task. The Platonic Representation Hypothesis (Huh et al., 2024) suggests that–at large model sizes–representations of semantically related inputs converge to similar neighboring structures regardless of (i) the task of the model and (ii) the specific encoding of the information. The statistical bias driving the convergence of neighborhood is, plausibly, the *meaning* which is shared between related inputs, with models loosely acting as mappings from data-specific representations to a hidden manifold, shared between different data modalities, in which semantically similar concepts are close to each other.

One can cast the convergence to a universal representation as a mutual information problem. If one models the representations of related inputs, say an image and its caption, as random variables x and y with a joint probability distribution $p(x, y)$, one can measure the information lost by replacing the joint distribution with the product of the marginals $p(x)p(y)$. If the distributions are independent, observing the caption is not informative of the image. If representations converge, a caption will be highly informative about the respective image, and the joint distribution is not approximated well by the marginals. Mutual information alone, however, is not sufficient to compare different models. In the deep layers, the distributions $p(x)$ and $p(y)$ loosely span a common underlying manifold, which is hypothesized to be associated with shared semantic information. The support of the different distributions does not reduce to this manifold, but spans other directions, orthogonal to the shared manifold, which are data- and architecture-specific. To quantify the relative information of x and y we need a statistical measure that is asymmetric, as there may be a partial order relation between models and representations induced by model size, model quality, different

data-specific subspaces, etc. The cross-entropy is a measure of how difficult it is to encode an event from a distribution into another distribution, and it would be the ideal choice, but estimating it is computationally difficult due to the dimension of the representations, which are of order of thousands. To overcome this limitation, we employ here the Information Imbalance (Glielmo et al., 2022), a statistical measure which is a proxy of the cross-entropy, but which can be computed efficiently even in high-dimensional spaces. This statistics has already been successfully used to perform feature selection(Wild et al., 2025) and to detect the presence of causal links (Del Tatto et al., 2024; Allione et al., 2025). The Information Imbalance between representation x and representation y is proportional to the average rank in representation y of the the data points which are nearest neighbors in representation x. If representation x predicts representation y, this average will be small, since the nearest neighbors of in x are also nearest neighbors y. If, instead, x does not predict y well, the average rank will be high, since the nearest neighbors in x are not necessarily close also in y. Note that the measure is asymmetric, as the nearest neighbors in one space could be near neighbors in the other space even if the reverse does not hold (Glielmo et al., 2022).

In this work, we first show on synthetic datasets that the Information Imbalance can be used to assess quantitatively the information provided by a representation on another representation, and we compare its properties to those of other statistics used in the literature for similar purposes. We then focus on DeepSeek-V3, the largest publicly available LLM, and measure, layer by layer, the relative information content between representations of sentence pairs that are translations of each other. This reveals a region of the network, robust across language pairs, that consistently encodes shared semantic content. We find clear information asymmetry effects, such that English-sentence representations tend to be better predictors of their translation than the other way around, and DeepSeek-V3 better predicts the smaller Llama3 models than the reverse. We also compare different methods for representing a sentence, considering the concatenation of the token activations, the mean of token activations, and the last token alone. We find that the convergence of representations is better revealed by utilizing several tokens, suggesting that in deep layers semantic information is spread across many tokens. Furthermore, averaged representations give better predictability scores than concatenated ones, probably due to the ablation of semantically irrelevant positional information. We finally identify semantic layers in vision transformers by processing pairs of images that share the same class. These semantic layers are also the most informative about DeepSeek-V3 representations of descriptive image captions, where we observe significant information asymmetries between image and text representations.

1.1 Related work

Representation alignment and convergence. A growing body of work suggests that deep networks develop similar representational structure across architectures and modalities (Kornblith et al., 2019a; Sorscher et al., 2022; Maniparambil et al., 2024; Sucholutsky et al., 2024). This is formalized by the *Platonic representation hypothesis* (Huh et al., 2024), which postulates that, as model quality improves, representations converge to a shared structure. Evidence for this includes the finding that models can be stitched together (Lenc & Vedaldi, 2019; Bansal et al., 2021; Moschella et al., 2023) across architectures. However, these works largely treat representations as monolithic objects, without asking *where* in the network shared structure emerges, or *how much* information one representation carries about another.

Multilingual representations. The related question of whether multilingual LLMs develop language-independent representations was partially studied by searching for a linear transformation between simple concepts expressed in different languages (Peng & Søgaard, 2024) and by using Sparse Autoencoders (Brinkmann et al., 2025). Another complementary line of research studied the role of English acting as an internal pivot language using logit lens (Wendler et al., 2024) and neuron importance scores (Zhao et al., 2024), to try to explain the observed representation similarities across languages. Cheng et al. (2025) study LLM representations layer by layer using, among other tools, the Information Imbalance, focusing solely on last-token representations of the same text across models.

This work. By measuring the Information Imbalance across different models, layers and token aggregations, we observe that semantic information is spread across many tokens of deep internal representations, and we quantify the *directed* predictability between representations of translations, images sharing a class, and image-caption pairs, unifying and extending recently observed results.

2 Methods

2.1 Representation choice

Text. LLMs encode sentences (or other text units) as a sequence of tokens. What we refer to as the semantic content (or meaning) of a sentence should be a global property emerging from the interaction of all the tokens present in it, encoded in the respective representations. However, in deep layers, the attention mechanism can move information across tokens, and eventually concentrate it in a specific token, as indeed happens to some extent in the last token of autoregressive LLMs. Thus, it is natural to ask how the choice of token representation aggregation affects the observed representation alignments. In Sec. 3.1.1, we consider using the last token representation as a proxy for the whole sentence as in, for example Cheng et al. (2025) and Yin et al. (2024), and compare it to two different ways of aggregating token sequences: their average, a standard pooling technique used in, for example, Huh et al. (2024) and Valeriani et al. (2023), and their concatenation. Concatenating tokens is computationally expensive and thus is only feasible for moderate sentence lengths. Its main property is to preserve positional information, and it was used in Joshi et al. (2020) to predict spans of masked tokens using the concatenation of their left and right boundary tokens. Given that the averaged representation provided the best alignment scores between translations, we used it in all subsequent experiments.

2.2 Data and models

Translations. We use samples from Opus Books (Tiedemann, 2012), with pairs of sentences with lengths between 40 and 80 tokens, extracted from different novels. We excluded the last two tokens of each sentence from the analysis, as they consistently correspond to punctuation marks (e.g., a period or a period followed by a quotation mark), which introduce trivial similarities in the representations. We consider between 1000 and 3000 pairs of sentences where one of the languages is English, and the other is one of Spanish, Italian, German, French, Dutch, or Hungarian. This set was chosen based on their presence in the repository with more than a thousand samples after filtering, support by the language models we use, and our ability to manually check translation quality. For text representations, we focus on DeepSeek-V3, a MoE model with 671B total parameters (DeepSeek-AI et al., 2025); to compare it with a widely used family of smaller models, we also use LLama3 (Meta, 2024) with 1, 3 and 8 billion parameters.

Images. We use the ImageNet-1k dataset (Deng et al., 2009), sampling 1,000 same-class pairs without replacement (to ensure we have no duplicates in the data), as a proxy for semantically related content. Thus, in this dataset, each pair is given by two different instances of the same ImageNet-1k category. We process the data with image-gpt-large (Chen et al., 2020) and DinoV2-large (Oquab et al., 2024). These models use fundamentally different training objectives. Image-gpt performs next-token prediction after down-scaling, row-wise unrolling, and color quantization of the input image, closely mimicking the autoregressive strategy of LLMs; previous work suggests that its semantic representations peak in the middle of the network (Chen et al., 2020). DinoV2 trains a student network to match a teacher on different augmentations of the same image, producing representations whose final layer is designed as the input to downstream tasks such as depth estimation and image segmentation.

Image-caption pairs. We use the Flickr30k dataset (Young et al., 2014), in which each image is paired with five human-generated captions that we concatenate into a single description. Images are processed with image-gpt-large and DinoV2-large; captions are encoded with DeepSeek-V3. We additionally include the ViT-L/14 visual encoder for images and the masked self-attention transformer for captions of CLIP (Radford et al., 2021) and three DinoV2 variants (small, base, large) to probe the effect of joint text-image contrastive training and vision model scale, respectively.

2.3 Quantifying the relative information content between representations

Our analysis is focused on the quantification of the relative information content of deep representations of translations of the same sentences, images of same-category objects, and image-caption pairs. We perform this analysis using the Information Imbalance (Glielmo et al., 2022; Del Tatto et al., 2024), a statistics

Figure 1: **a)** Information Imbalance (II) $\Delta(X\to Y)$ and $\Delta(Y\to X)$, CKA, and Neighborhood Overlap (NO) for a synthetic Gaussian construction in which each index r generates a pair (X_r, Y_r) via $Y_r = B_r X_r + \varepsilon$, with $X_r \sim \mathcal{N}(0, I)$, $\varepsilon \sim \mathcal{N}(0, \sigma^2 I)$, in $p = 10$ dimensions. The matrices $B_r \in \mathbb{R}^{p\times p}$ have monotonically increasing rank, from one at $r=1$ to full rank at the final index. Note that *smaller* II means more predictivity, whereas *higher* CKA and NO mean higher similarity. The Information Imbalance is the only measure able to reveal that X is more informative than its noisy transform Y. **b), c)** Statistical-power benchmark on a high-dimensional Gaussian vector with $p = 10^2$ and $p = 10^4$ components. We compute II, CKA, and NO with respect to a smaller vector with only a fraction of the p features, ranging from small subsets to the full vector. In all panels, shaded bands show the standard error over ten jackknife repetitions; the sample size is 2500.

which (qualitatively) measures the capability of a representation to predict another representation. Before discussing our main results, we present II measurements on synthetic data distributions. For a comparison, we analyze the same data with other standard statistics used to compare different representations, in particular the Central Kernel Alignment (CKA) (Kornblith et al., 2019b) and the Neighborhood Overlap (Huh et al., 2024).

The Information Imbalance compares the neighborhood structures of two representation spaces X and Y. Given representations $\{\mathbf{z}_i^X\}_{i=1}^N$ and $\{\mathbf{z}_i^Y\}_{i=1}^N$, we compute all pairwise distances and rank points $j \neq i$ in each space by increasing distance, obtaining ranks $r_{i,j}^X$ and $r_{i,j}^Y$. The Information Imbalance from X to Y is the normalized average rank in Y of the nearest neighbor of i in X:

$$\Delta(X \to Y) = \frac{2}{N-1} \frac{1}{N} \sum_{i,j:r_{ij}^X=1} r_{i,j}^Y,$$

where the sum is taken over pairs of indices i, j such that j is the first neighbor of i in space X, i.e., $r_{ij}^X = 1$. If neighborhoods in X predict neighborhoods in Y, these ranks are small and $\Delta(X \to Y)$ is close to zero; if X carries no information about Y, the expected rank is uniform and $\Delta(X \to Y) \approx 1$. The asymmetry $\Delta(X \to Y) \neq \Delta(Y \to X)$ quantifies directional predictability across models or modalities (Glielmo et al., 2022).

We first compute the Information Imbalance, the CKA (Kornblith et al., 2019b) and the Neighborhood Overlap from Huh et al. (2024) for a synthetic Gaussian construction in which each index r generates a pair (X_r, Y_r) via $Y_r = B_r X_r + \varepsilon$, with $X_r \sim \mathcal{N}(0, I)$ and $\varepsilon \sim \mathcal{N}(0, \sigma^2 I)$, in $p = 10$ dimensions. The B_r matrices are defined by first choosing a target rank $r \in \{1, \ldots, D\}$ and then sampling independent Gaussian factors $U_r \sim \mathcal{N}(0, 1)^{D\times r}$ and $V_r \sim \mathcal{N}(0, 1)^{r\times D}$, with the linear map given by $B_r = U_r V_r$, which enforces a transformation of rank r. High–rank settings preserve most of the structure in X_r, whereas low–rank settings collapse information into a low-dimensional, noisy subspace. In Fig. 1-a), we show that the Information Imbalance captures both the strength and the direction of the relative information across layers in this controlled synthetic setting. In particular, the Information-Imbalance shows that the predictivity between X and Y is *directional*. Indeed, $\Delta(X\to Y)$ is significantly lower than $\Delta(Y\to X)$. For comparison, we also report CKA and the Neighborhood Overlap, which track the overall loss of alignment between X_r and Y_r but, being symmetric, cannot reveal the asymmetry captured by Information Imbalance.

Figure 2: **Representation choice.** Information Imbalance from English to Italian tranlsations in DeepSeek-V3 when tokens are a) averaged or b) concatenated. The (hardly visible) shaded colored areas correspond to the standard deviation obtained by subsampling half of the samples five times.

A complementary benchmark is shown in Figs. 1-b) and 1-c), where we compute the Information Imbalance between a Gaussian vector with p components and a smaller dimensional vector containing only a given fraction of them, for cases $p = 10^2$ and $p = 10^4$, respectively. For a 10^4-dimensional Gaussian, CKA saturates close to 1 even when only a small fraction of the components is observed, while the Information Imbalance and the Neighborhood Overlap retain discriminative resolution up to a much larger fraction of shared features. This illustrative example echoes the findings of Huh et al. (2024), that observed their Neighborhood Overlap was preferable to CKA in high dimensions. We highlight that in Figs. 1-b) and 1-c) the Information Imbalance is more sensitive in the regime of small fraction of shared features (weak signal) than the Neighborhood Overlap, and in a complementary way, the opposite happens in the regime of large fraction of shared features. In both panels, the information asymmetry between representations is captured by the small gap between Information Imbalance curves, which becomes small when the dimensionality is large.

We remark that the example presented in Fig. 1-b) and provides a heuristic interpretation for the value of the II between two representations. Namely, if one measures an II between two representations of, say, 0.2, it can be interpreted as them sharing roughly 25 percent of their features. In these conditions, even if the dimension of the space is large, a small but statistically significant gap would open between the two II curves in each direction.

3 Results

3.1 Comparing translation representations

We now present results of a set of analyses performed using the Information Imbalance (II) on deep representations of data points that qualitatively convey approximately the same information to a human. We start by considering translations of the same sentence in different languages.

3.1.1 Representation choice: Last token, concatenated tokens or averaged tokens?

Fig. 2-a) shows the II between English and Italian translations from the Opus Books parallel corpus collection, using three different representations: (i) The last token, (ii) the concatenation of the last T tokens, or (iii) their average. Note that -under the Platonic representation hypothesis- for an ideal dataset of translations, an ideal network separately processing the sentence pairs should generate equivalent representations, namely, somewhere in the network, the II from one language to the other should be close to zero. Thus, we

Figure 3: **Comparison with other languages and models.** Panel a): Information Imbalance from English to several languages, computed on representations generated by DeepSeek-V3. Panel b): Information Imbalance from English to Italian, computed on representations generated by Llama3 models with 1,3, and 8 billion parameters, and by DeepSeek-V3 for comparison. In both panels we used the average of the last 20 tokens to represent sentences, and the (hardly visible) shaded areas correspond to the standard deviation obtained by subsampling half of the samples five times.

expect better abstract representations to have a lower Information Imbalance. In all three cases, the II is minimum in central layers, that were independently found to be related to an abstraction phase(Cheng et al., 2025), simultaneously far away from the encoding ($l = 0$) and decoding ($l = L$) layers, which necessarily contain more language-specific information. We highlight that the predictability between representation significantly increases from single-token to many-token representations. Given that the observed neighborhood predictability seems driven by semantic correspondences, this result suggests that semantic information is spread across many tokens, and not concentrated in, say, only the last token.

Among the two considered aggregation methods, i.e., concatenation and average of the last T tokens, we note three main differences. In initial layers, the average of an increasing number of tokens increases predictability (reducing II) between representations with respect to the last token alone, whereas this does not happen for the concatenated representation. This is consistent with the fact that the meaning of sentences, which drives predictability of the representations, does not rely on precise positional information and it will be typically distributed across different tokens in a sentence and its translation. Furthermore, we observe that, in deep layers, the average of a larger number of tokens in the representation monotonically improves predictability (whereas this does not happen for the concatenated representations) and, most importantly, gives the "best" (i.e., lowest) predictability score. Consequently, in what follows we focus on token-averaged representations.

For all curves, predictability is still larger at the last layer than at the first. This is plausibly due to the fact that the representation of the last layer must still contain some of the semantic information computed in the central layers, which must be at least partially used for next-token prediction. As a null hypothesis, we show in Appendix A that performing batch-shuffling on any of the datasets leads to completely uninformative representations (Information Imbalance gives 1 at every layer), since the semantic correspondence between translations is destroyed. Appendix C shows that the results obtained in Fig. 2 qualitatively agree with those given by CKA and Neighborhood Overlap, highlighting some limitations of these metrics.

Figure 4: **Information asymmetries.** Panel a): Information Imbalance (II) from English to Italian and from Italian to English, computed on representations generated by DeepSeek-V3. Panel b): II Asymmetry $\mathcal{A} = II(English \rightarrow other) - II(other \rightarrow English)$ between English and other languages, computed on representations generated by DeepSeek-V3. Note that, under this definition of asymmetry, a negative value implies that English is more informative than the other language. Panel c): Information Imbalance between representations generated by DeepSeek-V3 and Llama3-8b on the same English text, as a function of comparable relative depth in both models. The shaded area corresponds to one standard deviation, computed with a Jackknife procedure by subsampling five times half of the samples. In all three panels, we used the average of the last 20 tokens.

3.1.2 Information Imbalance between different languages and different models

Fig. 3-a) shows that the II profiles across layers for Spanish, Dutch, German and French translations are in very good agreement with the Italian one. Hungarian, which is simultaneously the tested language with the smallest amount of resources available on the internet[1] and the only non-Indo-European language in the set, shares the same qualitative II profile, but with larger II values (smaller predictability). Fig. 3-b) shows instead that the II layer profile for English-Italian translations is similar for the Llama3 family of models with 1, 3 and 8 billion parameters. DeepSeek-V3 results from Fig. 2-a) are also shown for direct comparison. Notably, and in accordance with the Platonic representation hypothesis, increasing model size reduces the II, predominantly in the inner layers. The position of the global II minimum also shifts slightly towards earlier layers for the larger models. We highlight that, qualitatively, the II profiles of all models are very similar, and DeepSeek-V3's global minimum is deeper than for the other models.

3.1.3 Information asymmetries

Given that English is the dominant language in terms of training resources and performance (Zhu et al., 2024), one could expect English representations to be more informative than those generated processing other languages. Fig. 4-a) shows that this asymmetry is indeed observed, most notably in the last quarter of the network, for the specific case of English-Italian translations. Nonetheless, the II asymmetry profile is far from trivial. Notably, both representations are equally predictive of each other where predictability is maximal, around the middle of the network. This is in line with the hypothesis that the middle layers store semantic information that might be largely language-independent. Moving towards earlier layers, at around 0.2 relative depth, we see that a small gap opens between the two II curves, where again English is the most informative, whereas in the very first layers we observe a small inverted asymmetry. Fig. 4-b) shows the II asymmetry $\mathcal{A} = II(English \rightarrow other) - II(other \rightarrow English)$ across the layers of DeepSeek-V3. Note that, under this definition, a negative asymmetry corresponds to the case in which English representations are more informative than representations in the other language. We observe that the asymmetry profile across layers is robust across translations in five different languages, with the same overall trend: the representations of English sentences are asymmetrically more informative in the early and late layers. The very first layers show

---

[1] https://en.wikipedia.org/wiki/Languages_used_on_the_Internet

a consistent positive asymmetry, where English tokens are less predictive than those in the other language, which could be an effect of the tokenization, and is left for a better understanding in future work.

Fig. 8 in Appendix B shows that the corresponding asymmetry profiles across the layers of Llama3-8b also are positive in the very early layers, approaching zero in middle layers, and negative in the last quarter of the network, with the exception of the last layer, in which the asymmetry is roughly zero.

One can also wonder if the representations of a huge model such as DeepSeek-V3 are more informative than those generated by a smaller Llama3 model. For identical English inputs, Fig. 4-c) shows the II between DeepSeek-V3 and Llama3-8b representations at comparable relative depths. In contrast to the II profile between translations in Fig. 2, in Fig. 4-c) the II in the very first layers is very small, suggesting that the word embeddings of the two models are very similar. The II has then a small peak at roughly 0.1 relative depth, plausibly related to some difference in input processing between the two networks. Afterwards, at intermediate depths, we observe a region of maximal mutual predictability (lowest II) without information asymmetries up until roughly half of the networks. Again, this is plausibly related to the fact that the middle layers are those that contain the most "universal" semantic information. In the second part of the network, we observe a massive gap between the curves, where DeepSeek-V3 representations are far more predictive than those from Llama3-8b.

3.1.4 Token-token Information Imbalance

We have used representations constructed out of the average of several tokens to measure mutual predictability between translations (Figures 2 and 3) and to quantify information asymmetries between English and other languages and between different LLMs (Fig. 4). In this section, we zoom-in on two languages and look at the correlation structure between tokens, trying to gain further qualitative insights.

Fig. 5 shows the II between the last token and a previous token at distance τ from it, for English and Italian representations generated by both DeepSeek-V3 and Llama3-8b. For DeepSeek-V3, in the very first layers, the last token is, on average, already not informative about a previous token at distance $\tau \approx 5$. In deeper layers, tokens become more and more informative about each other. The layers with strongest correlations (lowest II) are those with relative depth roughly between 0.6 and 0.9, which approximately coincides with the broad region with very low II between translations in Fig. 2, right after the global minimum. The token-token predictability in these deep layers is much larger in DeepSeek-V3 (Figs. 5-a) and 5-b)) than in Llama3-8b (Figs. 5-c) and 5-d)). This analysis is to be compared with the one of Fig. 3-b), where DeepSeek-V3's II between translations is lower (higher predictability) than the II computed on any of the Llama3 models. Furthermore, by comparing Fig. 5-a) and Fig. 5-b), we see that the token-token II in very deep layers of DeepSeek-V3 is also much lower in English than in Italian, and the same happens for Llama3-8b between panels c) and d). Thus, we qualitatively observe that representations that are more predictive across languages are also those in which the information is more consistent across many tokens, similarly to the observed information asymmetries from Fig. 4, and to Hosseini & Fedorenko (2023), who showed that better performing models tend to display linear correlations across longer spans of tokens, giving straighter token trajectories.

3.2 Comparing image and image-text representations

3.2.1 Convergence in representations of same-class images

We first compare representations for pairs of images that share the same ImageNet-1k class, but depict different instances. For example, one pair might consist of images of two *black widows*, another of two *accordion* pictures. The representations of these image pairs should be close in layers that capture semantic information. We use mean-token activations to represent each image, consistently with previous work by Valeriani et al. (2023). Since the assignment of the two images to the two representation spaces is arbitrary, the Information Imbalance is symmetric, except for statistical errors. Therefore, we report its average between the two directions. Results are shown in Fig. 6 a). For DinoV2, the Information Imbalance decreases monotonically and reaches values close to 0.35 around its last layer. For image-gpt-large, the minimum (≈ 0.65) is attained around 42% relative depth, after which the Information Imbalance rises again, reaching

Figure 5: **Token-token Information Imbalance.** Information Imbalance from the last token to a previous token at distance τ, as a function of τ. Panels a) and b) correspond to DeepSeek-V3 representations of English and Italian text, whereas panels c) and d) correspond to Llama3-8b representations of English and Italian. The (hardly visible) shaded area corresponds to one standard deviation, computed with a Jackknife procedure by subsampling five times half of the samples.

Figure 6: **a)** Within-model Information Imbalance for 1,000 same-class image pairs from ImageNet-1k, using mean-token activations. For each model, we compare the representations of two distinct images of the same class at the same layer, and plot the result as a function of relative depth. DinoV2 reaches its minimum at the last layer; ImageGPT at $\approx 42\%$ relative depth. **b)** Cross-modal Information Imbalance on Flickr30k image–caption pairs. One model is held at a fixed layer (DeepSeek-V3 at $\approx 60\%$ relative depth, or CLIP-Image at its last layer) while all layers of the partner model are swept. Solid lines show the Information Imbalance in the $A \rightarrow B$ direction; dashed lines show the reverse direction ($B \rightarrow A$), keeping the same model fixed at the same layer.

≈ 0.85 at the last layer. This is consistent with the respective training objectives. DinoV2 is trained so that its final-layer representations serve as input to downstream tasks such as depth estimation and segmentation, which should lead to rich semantic content being encoded at the output. Image-gpt-large, an autoregressive model, concentrates instead semantic content in the middle of the network, and probably reverts to lower-level, pixel-predictive features near the output. The contrasting profiles of DinoV2 and image-gpt-large suggest that the training objective is shaping where in the network semantic information is most concentrated, with autoregressive models (such as the textual transformers and image-gpt-large) placing it in intermediate layers, and encoder models pushing it toward the final layers.

3.2.2 Images and captions: multimodal data sharing semantic content

Image-caption pairs convey approximately the same meaning in different modalities, similarly to translations of the same sentence in different languages. The within-model image–image analysis of Fig. 6 a) identifies, for each vision model, the layers where semantic information is most concentrated. We expect these same layers to yield the strongest cross-modal alignment with textual representations of the corresponding captions. In Fig. 6 b), we test this by fixing DeepSeek-V3 at $\approx 60\%$ relative depth (in the region that minimizes the Information Imbalance in the translation analysis of Fig. 2) and sweeping all layers of each vision model on the Flickr30k dataset. We compute the Information Imbalance in both directions: the gap between the two reveals how asymmetric the cross-modal relationship is, serving as a measure of how much richer one representation is relative to the other. To verify that the results are not sensitive to this particular choice, Fig. 10 c) of Appendix D shows the Information Imbalance from representative layers of the vision models against all DeepSeek-V3 layers, showcasing how the values stabilize after 60% relative depth.

For DinoV2, the minimum Information Imbalance (DeepSeek-V3 $\rightarrow$ DinoV2) is ≈ 0.20, attained at the final layer; in the reverse direction (DinoV2 $\rightarrow$ DeepSeek-V3), the minimum is ≈ 0.30. For image-gpt-large, the minimum Information Imbalance from DeepSeek-V3 is ≈ 0.40 (at $\approx 40\%$ relative depth), while in the reverse direction it reaches ≈ 0.60. The substantially higher values compared to DinoV2 indicate weaker cross-modal alignment. Note that both the curve profiles and the absolute Information Imbalance values are largely compatible with the image–image results (Fig. 6 a). This suggests that the nature and quality of semantic processing by the visual transformers is the dominating factor in determining image–text convergence. Note, moreover, an asymmetry in favor of DeepSeek-V3 being more predictive of the visual models than the opposite (dashed lines above solid lines in the plot).

To test whether joint text-image training facilitates cross-modal alignment, we also include in Fig. 6 b) the ViT-L/14 visual encoder ($\approx$303M parameters) of the multimodal CLIP system (Radford et al., 2021), paired with its autoregressive text encoder ($\approx$123M parameters). Note that both CLIP encoders are orders of magnitude smaller than DeepSeek-V3 (671B parameters), while DinoV2-large ($\approx$300M parameters) is comparable in size to the CLIP visual encoder. The CLIP pair reaches a minimum Information Imbalance of ≈ 0.30, noticeably higher than the DeepSeek-V3 $\rightarrow$ DinoV2 value of ≈ 0.20. Remarkably, two independently trained models (DeepSeek-V3 and DinoV2) thus achieve stronger cross-modal alignment than a pair explicitly trained to align image and text representations, suggesting that explicit multimodal training is neither necessary nor sufficient to maximize cross-modal predictability; model scale may be the dominant factor. Two further differences stand out. First, multimodal training produces more uniform alignment across layers: the CLIP curves remain flatter than those of the non-aligned pairs, indicating that contrastive training encourages cross-modal predictability throughout the network rather than concentrating it in a narrow depth range. Second, the CLIP pair exhibits a more symmetric Information Imbalance between the two directions than the DeepSeek-V3/vision transformer pairs, which may reflect the explicit CLIP alignment objective. That two very different cross-modal comparisons, namely (i) a large independently trained LLM–ViT pair and (ii) a much smaller jointly trained pair, both reach minimum Information Imbalance values in the range 0.2–0.3 raises the intriguing question of whether this threshold approaches an intrinsic ceiling in text-image alignment. We leave the exploration of this question to future work.

Finally, to probe the dependence of the observed cross-modal alignment on the scale of the vision model, we repeat the DeepSeek-V3–DinoV2 analysis with three DinoV2 variants (large, base, and small); see Fig. 10 b) of Appendix D. The minimum Information Imbalance is 0.20 for DinoV2-large, 0.20 for DinoV2-base, and 0.25 for DinoV2-small. All three profiles reach their minimum at the last layer, confirming that this semantic region is robustly identified regardless of vision model size. Moreover, similarly to what we observe with the results on translations of Fig. 3, we see that bigger model sizes produce lower values of Information Imbalance. For these vision models, the small gap between the large and base variants suggests that the quality of cross-modal alignment may saturate once the vision model reaches a sufficient capacity. We repeat the analysis with a smaller LLama3.1-8B model, confirming the same qualitative results we obtain for the larger DeepSeek-V3 model. We report the results in Appendix D.

4 Conclusion

The recent observations on representation alignment by Huh et al. (2024) call for thorough analyses determining how different metrics affect their results (Gröger et al., 2026), and more generally, how presumably universal semantic information is encoded in deep neural networks. We contributed to this research line by measuring the relative information content between representations generated by deep neural networks processing inputs in different languages and modalities that carry approximately the same meaning. For these purposes, we used the Information Imbalance (II), an *asymmetric* measure based on neighborhood ranks. First, we showed on synthetic data sets how this metric provides an insight that cannot be captured with standard similarity metrics such as Central Kernel Alignment and Neighborhood Overlap, which are symmetric. Then, using translated sentences, we explicitly characterized the layer dependence of the II inside a LLM with state-of-the-art performance, DeepSeek-V3. Consistently with recent experiments on cross-language retrieval (Liu & Niehues, 2025), and with semantic probing experiments (Cheng et al., 2025; Skean et al., 2025), we found that central layers representations for each language are most predictive about each other. Using the II, we were able to estimate the asymmetric information content of representations. We found that the only layers in which mutual predictability across languages is symmetric are the central ones, while asymmetries arise in early and late layers. We explored how representation choice affects the observed predictabilities by comparing the II between (i) last-token representations, (ii) average, and (iii) concatenation of the last T tokens. We found that averaged representations give the best scores (lowest II), probably because they partially remove positional information that is irrelevant for semantics, and that semantic information is spread across many tokens, instead of concentrated only in, say, the last token.

We found that English sentence representations are systematically more informative than those generated by processing other, less resource-rich languages, and that DeepSeek-V3 representations are more informative than those generated by the smaller Llama3-8b. At a qualitative level, we observed that such asymmetries also arise in token-token correlation structure, suggesting that long-range correlations could be a hallmark of representation quality, as also suggested by Hosseini & Fedorenko (2023).

In the visual domain, we observed that the autoregressive image-gpt-large model, when processing semantically-related images, produces a qualitatively similar II profile as autoregressive LLMs processing translations, where central layers are the most predictive. Instead, an encoder model such as Dino-V2 develops representations that are maximally predictive towards the last layers. We also observed that the layers with the highest relative information content for semantically-related images are also those where we observe the largest cross-modal convergence with DeepSeek-V3 textual representations.

Taken together, our results support the hypothesis of semantic convergence across languages, modalities and models, and establish a more nuanced picture of it. In particular, they suggest that convergence is a property of specific intermediate processing stages, that can differ from model to model (e.g., central vs. late layers), and even when different representations of semantically related inputs do converge, there might be significant asymmetries in their relative information content, which might depend on factors such as model size, training resources and objective, and modality.

Having shown these basic results, in future work we would like, on the one hand, to more clearly disentangle the factors leading to asymmetric semantic content. We plan to investigate, for example, if the lower convergence observed when vision models are involved is due to model size, training regime, or intrinsic properties of linguistic vs. visual inputs. On the other hand, we believe that the ultimate question to be answered pertains to the *nature* of the semantic features that are shared across representational systems. For example, Tamkin et al. (2020) showed that linguistic information at different scales (word-level, sentence-level, document-level) is better decoded by classification probes using different frequency modes along the token axis. The fact that we achieved the best scores for alignment between translations by using mean token representations, which correspond to the zero-frequency mode, suggests that semantic information might be predominantly encoded in low frequency frequency modes. We hope that our contribution, by highlighting specific patterns of semantic convergence, lays the foundation for this kind of future explorations.

References

Matteo Allione, Vittorio Del Tatto, and Alessandro Laio. Linear scaling causal discovery from high-dimensional time series by dynamical community detection. *Phys. Rev. Lett.*, 135:047401, Jul 2025. doi: 10.1103/kd73-93cg. URL `https://link.aps.org/doi/10.1103/kd73-93cg`.

Yamini Bansal, Preetum Nakkiran, and Boaz Barak. Revisiting model stitching to compare neural representations. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 225–236. Curran Associates, Inc., 2021. URL `https://proceedings.neurips.cc/paper_files/paper/2021/file/01ded4259d101feb739b06c399e9cd9c-Paper.pdf`.

Jannik Brinkmann, Chris Wendler, Christian Bartelt, and Aaron Mueller. Large language models share representations of latent grammatical concepts across typologically diverse languages, 2025.

Mark Chen, Alec Radford, Rewon Child, Jeffrey Wu, Heewoo Jun, David Luan, and Ilya Sutskever. Generative pretraining from pixels. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 1691–1703. PMLR, 13–18 Jul 2020. URL `https://proceedings.mlr.press/v119/chen20s.html`.

Emily Cheng, Diego Doimo, Corentin Kervadec, Iuri Macocco, Lei Yu, Alessandro Laio, and Marco Baroni. Emergence of a high-dimensional abstraction phase in language transformers. In *The Thirteenth International Conference on Learning Representations*, 2025. URL `https://openreview.net/forum?id=0fD3iIBhlV`.

DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, Fuli Luo, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Han Bao, Hanwei Xu, Haocheng Wang, Haowei Zhang, Honghui Ding, Huajian Xin, Huazuo Gao, Hui Li, Hui Qu, J. L. Cai, Jian Liang, Jianzhong Guo, Jiaqi Ni, Jiashi Li, Jiawei Wang, Jin Chen, Jingchang Chen, Jingyang Yuan, Junjie Qiu, Junlong Li, Junxiao Song, Kai Dong, Kai Hu, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, Lean Wang, Lecong Zhang, Lei Xu, Leyi Xia, Liang Zhao, Litong Wang, Liyue Zhang, Meng Li, Miaojun Wang, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Mingming Li, Ning Tian, Panpan Huang, Peiyi Wang, Peng Zhang, Qiancheng Wang, Qihao Zhu, Qinyu Chen, Qiushi Du, R. J. Chen, R. L. Jin, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, Runxin Xu, Ruoyu Zhang, Ruyi Chen, S. S. Li, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shaoqing Wu, Shengfeng Ye, Shengfeng Ye, Shirong Ma, Shiyu Wang, Shuang Zhou, Shuiping Yu, Shunfeng Zhou, Shuting Pan, T. Wang, Tao Yun, Tian Pei, Tianyu Sun, W. L. Xiao, Wangding Zeng, Wanjia Zhao, Wei An, Wen Liu, Wenfeng Liang, Wenjun Gao, Wenqin Yu, Wentao Zhang, X. Q. Li, Xiangyue Jin, Xianzu Wang, Xiao Bi, Xiaodong Liu, Xiaohan Wang, Xiaojin Shen, Xiaokang Chen, Xiaokang Zhang, Xiaosha Chen, Xiaotao Nie, Xiaowen Sun, Xiaoxiang Wang, Xin Cheng, Xin Liu, Xin Xie, Xingchao Liu, Xingkai Yu, Xinnan Song, Xinxia Shan, Xinyi Zhou, Xinyu Yang, Xinyuan Li, Xuecheng Su, Xuheng Lin, Y. K. Li, Y. Q. Wang, Y. X. Wei, Y. X. Zhu, Yang Zhang, Yanhong Xu, Yanhong Xu, Yanping Huang, Yao Li, Yao Zhao, Yaofeng Sun, Yaohui Li, Yaohui Wang, Yi Yu, Yi Zheng, Yichao Zhang, Yifan Shi, Yiliang Xiong, Ying He, Ying Tang, Yishi Piao, Yisong Wang, Yixuan Tan, Yiyang Ma, Yiyuan Liu, Yongqiang Guo, Yu Wu, Yuan Ou, Yuchen Zhu, Yuduan Wang, Yue Gong, Yuheng Zou, Yujia He, Yukun Zha, Yunfan Xiong, Yunxian Ma, Yuting Yan, Yuxiang Luo, Yuxiang You, Yuxuan Liu, Yuyang Zhou, Z. F. Wu, Z. Z. Ren, Zehui Ren, Zhangli Sha, Zhe Fu, Zhean Xu, Zhen Huang, Zhen Zhang, Zhenda Xie, Zhengyan Zhang, Zhewen Hao, Zhibin Gou, Zhicheng Ma, Zhigang Yan, Zhihong Shao, Zhipeng Xu, Zhiyu Wu, Zhongyu Zhang, Zhuoshu Li, Zihui Gu, Zijia Zhu, Zijun Liu, Zilin Li, Ziwei Xie, Ziyang Song, Ziyi Gao, and Zizheng Pan. Deepseek-v3 technical report, 2025.

Vittorio Del Tatto, Gianfranco Fortunato, Domenica Bueti, and Alessandro Laio. Robust inference of causality in high-dimensional dynamical processes from the information imbalance of distance ranks. *Proceedings of the National Academy of Sciences*, 121(19):e2317256121, 2024.

Jia Deng, Wei Dong, Richard Socher, Lia-Ji Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Proceedings of CVPR*, pp. 248–255, Miami Beach, FL, 2009.

Aldo Glielmo, Claudio Zeni, Bingqing Cheng, Gábor Csányi, and Alessandro Laio. Ranking the information content of distance measures. *PNAS Nexus*, 1(2):pgac039, 04 2022. ISSN 2752-6542. doi: 10.1093/pnasnexus/pgac039.

Fabian Gröger, Shuo Wen, and Maria Brbić. Revisiting the platonic representation hypothesis: An aristotelian view, 2026. URL `https://arxiv.org/abs/2602.14486`.

Eghbal Hosseini and Evelina Fedorenko. Large language models implicitly learn to straighten neural sentence trajectories to construct a predictive representation of natural language. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 43918–43930. Curran Associates, Inc., 2023. URL `https://proceedings.neurips.cc/paper_files/paper/2023/file/88dddaf430b5bc38ab8228902bb61821-Paper-Conference.pdf`.

Minyoung Huh, Brian Cheung, Tongzhou Wang, and Phillip Isola. Position: The platonic representation hypothesis. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 20617–20642. PMLR, 21–27 Jul 2024. URL `https://proceedings.mlr.press/v235/huh24a.html`.

Mandar Joshi, Danqi Chen, Yinhan Liu, Daniel S. Weld, Luke Zettlemoyer, and Omer Levy. SpanBERT: Improving pre-training by representing and predicting spans. *Transactions of the Association for Computational Linguistics*, 8:64–77, 2020. doi: 10.1162/tacl_a_00300. URL `https://aclanthology.org/2020.tacl-1.5/`.

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *Proceedings of ICML*, pp. 3519–3529, Long Beach, CA, 2019a.

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey E. Hinton. Similarity of neural network representations revisited. *ArXiv*, abs/1905.00414, 2019b. URL `https://api.semanticscholar.org/CorpusID:141460329`.

Karel Lenc and Andrea Vedaldi. Understanding image representations by measuring their equivariance and equivalence. *International Journal of Computer Vision*, 127, 05 2019. doi: 10.1007/s11263-018-1098-y.

Danni Liu and Jan Niehues. Middle-layer representation alignment for cross-lingual transfer in fine-tuned LLMs. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15979–15996, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.778. URL `https://aclanthology.org/2025.acl-long.778/`.

Mayug Maniparambil, Raiymbek Akshulakov, Yasser Abdelaziz Dahou Djilali, Sanath Narayan, Mohamed El Amine Seddik, Karttikeya Mangalam, and Noel O'Connor. Do vision and language encoders represent the world similarly? In *Proceedings of CVPR*, pp. 14334–14343, Seattle, WA, 2024.

Meta. Introducing Meta Llama 3: The most capable openly available LLM to date, 2024. URL `https://ai.meta.com/blog/meta-llama-3/`.

Luca Moschella, Valentino Maiorca, Marco Fumero, Antonio Norelli, Francesco Locatello, and Emanuele Rodolà. Relative representations enable zero-shot latent space communication. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=SrC-nwieGJ`.

Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, Mahmoud Assran, Nicolas Ballas, Wojciech Galuba, Russell Howes, Po-Yao Huang, Shang-Wen Li, Ishan Misra, Michael Rabbat, Vasu Sharma, Gabriel Synnaeve, Hu Xu, Hervé Jegou, Julien Mairal, Patrick Labatut, Armand Joulin, and Piotr Bojanowski. DINOv2: Learning Robust Visual Features without Supervision, February 2024.

Qiwei Peng and Anders Søgaard. Concept space alignment in multilingual llms, 2024.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PmLR, 2021.

Oscar Skean, Md Rifat Arefin, Dan Zhao, Niket Nikul Patel, Jalal Naghiyev, Yann LeCun, and Ravid Shwartz-Ziv. Layer by layer: Uncovering hidden representations in language models. In *Forty-second International Conference on Machine Learning*, 2025. URL `https://openreview.net/forum?id=WGXb7UdvTX`.

Ben Sorscher, Surya Ganguli, and Haim Sompolinsky. Neural representational geometry underlies few-shot concept learning. *Proceedings of the National Academy of Sciences*, 119(43):e2200800119, 2022.

Ilia Sucholutsky, Lukas Muttenthaler, Adrian Weller, Andi Peng, Andreea Bobu, Been Kim, Bradley C. Love, Christopher J. Cueva, Erin Grant, Iris Groen, Jascha Achterberg, Joshua B. Tenenbaum, Katherine M. Collins, Katherine L. Hermann, Kerem Oktar, Klaus Greff, Martin N. Hebart, Nathan Cloos, Nikolaus Kriegeskorte, Nori Jacoby, Qiuyi Zhang, Raja Marjieh, Robert Geirhos, Sherol Chen, Simon Kornblith, Sunayana Rane, Talia Konkle, Thomas P. O'Connell, Thomas Unterthiner, Andrew K. Lampinen, Klaus-Robert Müller, Mariya Toneva, and Thomas L. Griffiths. Getting aligned on representational alignment, 2024.

Alex Tamkin, Dan Jurafsky, and Noah D. Goodman. Language through a prism: A spectral approach for multiscale language representations. *ArXiv*, abs/2011.04823, 2020. URL `https://api.semanticscholar.org/CorpusID:226290128`.

Jörg Tiedemann. Parallel data, tools and interfaces in OPUS. In Nicoletta Calzolari, Khalid Choukri, Thierry Declerck, Mehmet Uğur Doğan, Bente Maegaard, Joseph Mariani, Asuncion Moreno, Jan Odijk, and Stelios Piperidis (eds.), *Proceedings of the Eighth International Conference on Language Resources and Evaluation (LREC'12)*, pp. 2214–2218, Istanbul, Turkey, May 2012. European Language Resources Association (ELRA). URL `http://www.lrec-conf.org/proceedings/lrec2012/pdf/463_Paper.pdf`.

Lucrezia Valeriani, Diego Doimo, Francesca Cuturello, Alessandro Laio, Alessio Ansuini, and Alberto Cazzaniga. The geometry of hidden representations of large transformer models. *Advances in Neural Information Processing Systems*, 36:51234–51252, 2023.

Chris Wendler, Veniamin Veselovsky, Giovanni Monea, and Robert West. Do llamas work in English? on the latent language of multilingual transformers. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15366–15394, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.820. URL `https://aclanthology.org/2024.acl-long.820/`.

Romina Wild, Felix Wodaczek, Vittorio Del Tatto, Bingqing Cheng, and Alessandro Laio. Automatic feature selection and weighting in molecular systems using differentiable information imbalance. *Nature Communications*, 16(1):270, January 2025. ISSN 2041-1723. doi: 10.1038/s41467-024-55449-7.

Fan Yin, Jayanth Srinivasa, and Kai-Wei Chang. Characterizing truthfulness in large language model generations with local intrinsic dimension. In Ruslan Salakhutdinov, Zico Kolter, Katherine Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 57069–57084. PMLR, 21–27 Jul 2024. URL `https://proceedings.mlr.press/v235/yin24c.html`.

Peter Young, Alice Lai, Micah Hodosh, and Julia Hockenmaier. From image descriptions to visual denotations: New similarity metrics for semantic inference over event descriptions. *Transactions of the Association for Computational Linguistics*, 2:67–78, December 2014. ISSN 2307-387X. doi: 10.1162/tacl_a_00166.

Figure 7: Information Imbalance between English (en) and Spanish (es) representations generated by DeepSeek-V3 and Llama3.1-8b, for the non-informative case, namely a misaligned dataset in which we batch-shuffle the Spanish translations. The (hardly visible) shaded area corresponds to one standard deviation, computed with a Jackknife procedure by subsampling five times half of the samples.

Yiran Zhao, Wenxuan Zhang, Guizhen Chen, Kenji Kawaguchi, and Lidong Bing. How do large language models handle multilingualism? In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (eds.), *Advances in Neural Information Processing Systems*, volume 37, pp. 15296–15319. Curran Associates, Inc., 2024. URL `https://proceedings.neurips.cc/paper_files/paper/2024/file/1bd359b32ab8b2a6bbafa1ed2856cf40-Paper-Conference.pdf`.

Shaolin Zhu, Supryadi, Shaoyang Xu, Haoran Sun, Leiyu Pan, Menglong Cui, Jiangcun Du, Renren Jin, António Branco, and Deyi Xiong. Multilingual large language models: A systematic survey. `https://arxiv.org/abs/2411.11072`, 2024.

A   Misalignment of translations erases semantic similarity

As a consistency check, Fig 7 shows the Information Imbalance for DeepSeek-V3 and Llama3.1-8b representations using misaligned translations, namely performing a batch-shuffle in one of the datasets. Since the semantic correspondence between sentences is destroyed, the representations are not informative about each other, and thus the Information Imbalance is close to one, for all layers. The same occurs with misaligned image pairs and image-caption pairs (tested, but not reported here).

B   Information Asymmetry in translations processed by Llama3

Fig. 8 shows the Information Imbalance asymmetry $\mathcal{A}$ between English and other languages across layers. We see some similarities and some differences with respect to DeepSeek-V3's results from Fig. 4-b). As for DeepSeek-V3, Llama3-8b's II asymmetry is positive for the very first layers, roughly zero in middle layers, and negative around the third quarter of its relative depth. Contrary to Fig. 4, the last layer of Llama3-8b presents roughly zero asymmetry, and there is no negative local minimum of $\mathcal{A}$ in between the very first layers and the central layers.

C   CKA and Neighborhood Overlap comparison on translations

Fig. 9 compares the II curves between English and Italian translations as a function of DeepSeek-V3's relative depth with CKA and Neighborhood Overlap (NO) computed on the same data, using a) the last token, b) the average of the last 20 tokens, and c) their concatenation.

Figure 8: II Asymmetry $\mathcal{A} = II(English \rightarrow other) - II(other \rightarrow English)$ between English and other languages, computed on representations generated by Llama3-8b. Note that, under this definition of asymmetry, a negative value implies that English is more informative than the other language.

First, we highlight that, for all three representational choices, the three metrics concurrently achieve their maximum score (lowest II, maximum CKA and NO, respectively). This confirms the robustness of the result we report in the main text about the presence of a central phase where representations are most clearly encoding shared semantic information.

However, there are several nuances to note. Starting with the Neighborhood Overlap, we note that it only reaches maximum values of roughly 0.1, 0.4 and 0.2 in panels a), b) and c), respectively, far from its theoretical maximum of 1, suggesting it is underestimating representational convergence. The last-layer Neighborhood Overlap is barely above zero for last-token and concatenated representations, with values of 0.031 ± 0.002 and 0.035 ± 0.003, respectively. Small alignment values were also observed and even highlighted as a limitation of the convergence of representations in Huh et al. (2024), although the authors do not provide arguments to understand the reasons behind this effect. We note that, if the k-th neighbor of representation A is instead the $k+1$ neighbor of representation B, automatically that point counts as *outside* the k-neighborhood, even if it is extremely close, rendering NO alignment values very low. This does not affect Information Imbalance, which, instead of evaluating whether k neighbors are shared, measures what is the *rank* in space B of k neighbors in space A, and vice-versa.

CKA displays much larger alignment values than NO in all three panels, with the exception of the last layer of panel a), where CKA = 0.059 ± 0.001, as the measure struggles to capture the weak signal provided by last-token representations. Moreover, while the CKA similarity profiles are compatible with those computed with II and NO in panels a) and b), we observe that CKA estimates very high similarity in the initial layers of panel c), in complete contrast with the other two metrics. We hypothesize this to be a spurious artifact of working in extremely high dimensions (20 concatenated tokens, each embedded in the 7,168 dimensions of DeepSeek-V3), that is avoided by the metrics based on neighborhood ranks.

D   Image-Captions

We report additional image–caption analyses that complement the main results of Sec. 3. Fig. 10 a) repeats the cross-modal experiment of Fig. 6 b) using LLama3.1-8B (fixed at $\approx 59\%$ relative depth, in the minimum identified by Fig. 2) instead of DeepSeek-V3 as the text encoder. The qualitative picture is unchanged: DinoV2 achieves stronger cross-modal alignment than image-gpt-large, and the same information asymmetry in favour of the LLM is observed, confirming that the results are not specific to DeepSeek-V3.

Figure 9: **Central Kernel Alignment (CKA) and Neighborhood Overlap (NO) comparison on translations.** Information Imbalance (II) from English to Italian and from Italian to English, together with CKA and Neighborhood Overlap computed on the same activations, using a) the last token, b) the average of the last 20 tokens, and c) the concatenation of the last 20 tokens. Note that for II, *lower* values cue higher alignment, whereas for CKA and NO *higher* values cue higher alighnment.

Figure 10: **a)** Cross-modal Information Imbalance on Flickr30k image–caption pairs with LLama3.1-8B ($\approx 59\%$ relative depth) as the text encoder, swept against DinoV2-large and image-gpt-large. **b)** DinoV2 model-size comparison: DeepSeek-V3 ($\approx 60\%$ relative depth) swept against DinoV2-large, DinoV2-base, and DinoV2-small. **c)** Information Imbalance from DinoV2 (last layer) and image-gpt-large ($\approx 42\%$ relative depth) against DeepSeek-V3. Solid lines show the Information Imbalance in the $A \rightarrow B$ direction; dashed lines show the reverse direction ($B \rightarrow A$), keeping the same model fixed at the same layer.

Fig. 10 b) probes the effect of vision-model scale by comparing DeepSeek-V3 (fixed at $\approx 60\%$ relative depth) against three DinoV2 variants (large, base, and small). All three profiles reach their minimum at the last layer, and larger models yield lower Information Imbalance, consistent with the Platonic representation hypothesis.

Fig. 10 c) verifies that the choice of fixed LLM layer does not qualitatively affect the results. We sweep all DeepSeek-V3 layers while fixing DinoV2 at its last layer and image-gpt-large at $\approx 42\%$ relative depth. The Information Imbalance stabilizes after roughly 60% relative depth in DeepSeek-V3, confirming that the fixed-layer results reported in the main text are robust.