Multi-Armed Bandits with Bounded Arm-Memory: Near-Optimal Guarantees for Best-Arm Identification and Regret Minimization

Abstract

We study the Stochastic Multi-armed Bandit problem under bounded arm-memory. In this setting, the arms arrive in a stream, and the number of arms that can be stored in the memory at any time, is bounded. The decision-maker can only pull arms that are present in the memory. We address the problem from the perspective of two standard objectives: 1) regret minimization, and 2) best-arm identification. For *regret minimization*, we settle an important open question by showing an almost tight guarantee. We show $\Omega(T^{2/3})$ cumulative regret in expectation for single-pass algorithms for arm-memory size of $(n-1)$, where n is the number of arms. For *best-arm identification*, we provide an (ε, δ)-PAC algorithm with $O(\log^* n)$ space complexity and $O(\frac{n}{\varepsilon^2} \cdot \log(\frac{1}{\delta}))$ optimal sample complexity.

1 Introduction

The Stochastic Multi-armed Bandit (MAB) problem is a classical framework used to capture decision-making in uncertain environments. In this model, a decision-maker is faced with n choices (called *arms*) and has to sequentially choose one of the n arms (referred to as *pulling* an arm). Based on the pulled arm, the decision-maker gets a reward drawn from a corresponding reward distribution unknown to the decision-maker. Starting with the seminal work of Robbins [23], MAB has been extensively studied with one of the following two goals: *regret minimization* and *best-arm identification*. See, e.g. [6] for a textbook treatment of the area. In addition to being theoretically interesting, MAB also finds numerous practical applications in diverse areas, including online advertising [28], crowd-sourcing [29], and clinical trials [8]. Hence, the study of MAB and its variants is of paramount interest in multiple fields, including online learning and reinforcement learning.

In many applications of the MAB problem, the number of arms (set of advertisements, crowd-workers, etc.) could be huge. Thus, the MAB problem with a large set of arms has received significant attention in recent years. Starting with the formative work of Berry et al. [5] and Herschkorn et al. [15] which studied the MAB problem with infinitely many arms, to the more recent work of Kleinberg et al. [17] which studies the MAB problem where the set of arms form a metric space, this variant has remained an active and prominent area of research. Large number of arms may enforce a constraint that the algorithm may not be able to store all the arms in the memory simultaneously. Additionally, as is common in these applications, the arms could arrive online, i.e., the algorithm may not have access to the entire set of arms at the beginning.

The streaming model, first formalized in the pioneering work of Alon et al. [2], has been developed to handle data streams where a huge amount of data arrives online and an algorithm has access to only a limited amount of memory. We refer the readers to [20, 1] for a detailed survey of streaming algorithms. With the ever-increasing amount of data available to any machine learning

(ML) algorithm, several salient areas of ML are being studied under streaming constraints; e.g., active learning [32, 26], lifelong learning [30], and identifying correlations in multivariate data [11] (see the recent survey by [14] for further discussions).

In this work, we study the classical stochastic MAB problem under streaming constraints. This model has recently been studied in [24, 18, 3]. In particular, we study a setting where we are given a set of n arms arriving one-by-one, and an algorithm can store only a fixed number of arms $m < n$ in the memory. The set of arms stored in the memory is known as arm-memory. Here, m, the upper bound on the number of arms that can be stored in the memory at any time step, is called the space (arm-memory) complexity of the algorithm. In this model, at any time step an arm not in the current arm-memory can not be pulled. Further, for any arm currently not in the arm-memory, we assume we do not know anything about the reward statistics corresponding to that arm until that arm is read into arm-memory and subsequently pulled. Note that the classical MAB algorithms such as UCB1 [4] and Thompson Sampling [27] for regret minimization, and Median-Elimination [12] for best-arm identification are not suited for this streaming setting as they require all arms to be present in the arm-memory at the start of the algorithm. Our goal is to study the interplay between *space complexity* vs. *expected regret* and *space complexity* vs. *sample complexity*, respectively.

An algorithm for our setting works as follows: at any time step t, the algorithm can only pull an arm that is currently in arm-memory and update its reward statistics. Then, the algorithm may choose to discard some of the arms that are currently in the arm-memory and read new arms into the arm-memory before proceeding to the next time-step to pull an arm from the arm-memory. In streaming terminology, algorithms that can not read back an arm into the arm-memory that was previously discarded from the arm-memory, are called *single-pass* or *one-pass* algorithms. On the other hand, algorithms that are allowed to read back an arm into the arm-memory that was previously discarded from the arm-memory, are called *multi-pass* algorithms. We note that our algorithms are designed for the more challenging single-pass setting, which has also been the focus of other prominent areas in machine learning, for example, Rai et al. [22] focus on designing one-pass SVMs when the data arrives in a stream, whereas Carvalho and Cohen [7] design single-pass algorithms for online learning.

1.1 Our Contribution

We study MAB under *bounded arm-memory*, where n arms arrive in a stream and at most $m < n$ arms can be stored in the arm-memory at any time. We study the trade-off between space (arm-memory) complexity vs. expected regret, and space complexity vs. sample complexity.

Regret minimization: Our first result, in Section 3, settles an open question stated in both [18] and [24] pertaining to the lower bound on the expected cumulative regret in this model. Using information-theoretic machinery related to KL-divergence, we show that any single-pass algorithm in this model will incur an expected regret of $\Omega\big(n^{1/3} \cdot T^{2/3}/m^{7/3}\big)$. Interestingly, this result holds for any $m < n$, which shows that even if the algorithm is allowed to store $n-1$ arms in the arm-memory at any time, we cannot hope to obtain a better regret guarantee in terms of T. This lower bound almost matches with the $\tilde{O}(n^{1/3}T^{2/3})$ bound on the expected cumulative regret, obtained by the standard uniform-exploration algorithm where we store $m = 2$ arms. As this is already optimal for the single-pass setting, we cannot hope to get a better regret guarantee in terms of T, even if we store $n-1$ arms in the memory. This shows an interesting dichotomy for $T \gg n$, as one can obtain expected cumulative regret of $\tilde{O}\big(\sqrt{nT}\big)$ by standard UCB1 algorithm [4], where we are allowed to store n arms. Our lower bound holds even when the arms arrive in a uniformly random sequence.

Best-arm identification: In Section 4, we propose an (ε, δ)-PAC streaming algorithm that takes r as input and stores $r + 1$ arms in the arm-memory at any time and has sample complexity $O(\frac{n}{\varepsilon^2} \cdot (\texttt{ilog}^{(r)}(n) + \ln(\frac{1}{\delta})))$ [1]. In particular, when $r = \log^* n$, our algorithm achieves the optimal worst-case sample complexity $O\big(\frac{n}{\varepsilon^2}\log(\frac{1}{\delta})\big)$ for any best-arm identification algorithm [12].

This problem was also studied in recent STOC'20 paper by Assadi and Wang [3] where they proposed an (ε, δ)-PAC algorithm with optimal sample complexity and $O(\log^* n)$ space complexity. However, we show that due to an error in their analysis, their claim is incorrect and their algorithm is *not* (ε, δ)-PAC. In Appendix E, we construct a family of input instances for which their algorithm will

---

[1] Here $\texttt{ilog}^{(r)}$ is iterated logarithm of order r (see Section 1.3).

output a non-ε-best arm with probability significantly larger than δ. In Section 4, we show that the special case of our algorithm (when $r = \log^* n$) indeed provides the guarantee claimed in [3].

1.2 Related Work

In one of the earliest works on MAB with bounded arm-memory, Herschkorn et al. [15] study the infinite-armed MAB problem where only a single arm is stored in the arm-memory at any time step and an arm that is once discarded from the arm-memory cannot be recalled. On the other hand, Cover [10] studied a different variant of bounded memory where the algorithm can remember the rewards of only a finite number of samples for each arm in a two-armed bandit model. The work of Lu and Lu [19] also studies this variant of bounded memory in the learning from experts setting, where the constraint is on the number of time steps for which the rewards can be stored by the algorithm and not on the number of arms. In our work, we focus on the finite-armed MAB problem with bounded arm-memory. Recently, the MAB problem where arms arrive in a stream and arm-memory is bounded, has been studied in both regret minimization and best-arm identification frameworks.

For the regret minimization problem in the stochastic MAB setting, Peköz [21] showed that when $m = 1$, a single-pass algorithm can have linear regret unless the reward distributions of arms satisfy some additional conditions. Liau et al. [18] and RoyChaudhuri and Kalyanakrishnan [24] study the stochastic MAB problem with bounded arm-memory with the goal of minimizing the expected cumulative regret over T time steps. The algorithms in both these works are multi-pass algorithms whereas our work focusses on single-pass algorithms. Liau et al. [18] propose an upper-confidence bound based algorithm with $O(1)$ space complexity, which achieves an expected cumulative regret bound of $O\left(\sum_{i \neq i^*} \log\left(\frac{\Delta_i}{\Delta}\right)\frac{\log T}{\Delta_i}\right)$, which is within $\log\left(\frac{\Delta_i}{\Delta}\right)$ factor of the UCB1 regret bound [4]. Here Δ is the gap parameter, i.e., the difference in the expected rewards of the best and the second-best arms, and Δ_i is the difference in the expected rewards of the best arm and the i'th arm. They do not provide a worst-case regret bound for their algorithm, and hence, depending on the instance the regret of this algorithm can become very high. RoyChaudhuri and Kalyanakrishnan [24] propose an algorithmic framework, which is given m as input and uses a MAB algorithm as a black-box. When the MAB algorithm used is UCB1, their algorithm achieves an expected regret of $O(nm + n^{3/2}m\sqrt{T \log(T/nm)})$ using $\Omega(\log T)$ passes. The recent work of Xu and Zhao [31] also studies the regret minimization problem with bounded arm-memory constraints. However, they consider the setting with adversarial rewards and is different from the stochastic MAB setting studied in our paper.

Recently, Assadi and Wang [3] studied the best-arm identification variant of this problem. First, they propose an algorithm for the best-coin identification problem (equivalent to MAB with Bernoulli reward distributions), which keeps exactly one extra coin in the memory at any time and has optimal sample complexity. They further extend their algorithm to the top-k coins identification problem, which stores k coins in the memory and has optimal sample complexity. Crucially though, both algorithms assume that the gap parameter Δ is known. Throughout our work, we deal with the case when Δ is not known to the algorithm. Falahatgar et al. [13] also study the best-arm identification problem with bounded arm-memory and provide an algorithm with $O(1)$ space complexity. However, they only provide a high probability guarantee on the sample complexity while additionally assuming that the arms arrive in a uniformly random sequence. Note that unlike [13], the sample complexity of our algorithm is independent of the rewards observed during the sampling, and we do not require the assumption that the arms need to arrive in a uniformly random sequence.

1.3 Notation

Let $[k]$ (where $k \in \mathbb{N}$) denote the set $\{1, 2, \ldots, k\}$. Let $\log$ denote the binary logarithm. For integers $r \geq 0$, and $a \geq 1$, $\mathtt{ilog}^{(r)}(\cdot)$ denotes the iterated logarithm of order r, i.e., $\mathtt{ilog}^{(r)}(a) = \max\{\log(\mathtt{ilog}^{(r-1)}(a)), 1\}$ and $\mathtt{ilog}^{(0)}(a) = a$. Hence, $\mathtt{ilog}^{(\log^* n)}(n) = 1$. Let $\mathbb{P}, \mathbb{E}$ denote probability and expectation, respectively.

2 Model and Problem Definition

An instance of the MAB problem is defined as the tuple $\langle n, (\mu_i)_{i \in [n]} \rangle$, where n is the number of arms. A pull of $\mathtt{arm}_i$ gives a reward in $[0, 1]$ drawn from a distribution with mean $\mu_i \in [0, 1]$ that is

unknown to the decision-maker beforehand. We study MAB under *bounded arm-memory* setting where the arms arrive in a stream, and at any time-step, the algorithm can store only $m < n$ arms (and their reward statistics, i.e., mean and the number of pulls so far) in the memory. We consider the standard "word RAM" model [9, 24], where *word* is the unit of space and each input value takes $O(1)$ word space. We use standard assumption that the total time period $T \gg n$ and we assume each word to have $O(\log T)$ bits. Therefore, total admissible space complexity is $O(m)$ words or $O(m \log(nT))$ bits.

In a single-pass algorithm, every arm arrives only once and it can't be read back into the arm-memory after it is discarded from the arm-memory. When an arm is read into the arm-memory, its reward statistics get initialized to zero and are updated whenever the arm is pulled until it is discarded from the arm-memory. As we consider single-pass algorithms, our results hold even for a more general model where we do not enforce any restriction on the number of arms for which we can store the arm-statistics. We only impose a condition that at any time step the pulled arm can only be chosen from the set of m arms present in the arm-memory. We cannot pull an arm if the arm is not present in the arm-memory. Next, we formalize the notions of regret minimization and best-arm identification.

The regret of a MAB algorithm can be thought of as the loss suffered by it due to not knowing the reward distributions of the arms beforehand. Let $i^* = \arg\max_{i \in [n]} \mu_i$. Then $\texttt{arm}_{i^*}$ is the best arm and let $\mu^* = \mu_{i^*}$. The cumulative regret (also called the *pseudo-regret*) of an algorithm over T time-steps is defined as follows:

Definition 1 (Cumulative Regret)**.** *Given an instance $\langle n, (\mu_i)_{i \in [n]} \rangle$ of the MAB problem, the cumulative regret of an algorithm after T rounds is defined as $R(T) = \mu^* \cdot T - \sum_{t=1}^{T} \mu_{i_t}$, where $\texttt{arm}_{i_t}$ is the arm pulled by the algorithm at time $t \in [T]$, and $\mu^* = \max_{i \in [n]} \mu_i$.*

The expected cumulative regret of an algorithm is defined as $\mathbb{E}[R(T)] = \mu^* \cdot T - \sum_{t=1}^{T} \mathbb{E}[\mu_{i_t}]$, where the expectation is over the randomness in the algorithm and the distribution of rewards. In the model with bounded arm-memory, the goal is to minimize expected cumulative regret while storing at most $m \ (< n)$ arms in arm-memory at any time-step. Note that, popular algorithms such as UCB1 [4] and Thompson sampling [27] store all n arms in memory, i.e., they have space complexity $\Omega(n)$.

For best-arm identification, the goal of a decision-maker is to output the best arm $\texttt{arm}_{i^*}$ using the minimum number of arm pulls. In practice, a relaxed goal is to find an arm which is close to the best arm in terms of the expected reward. We formalize this notion below.

Definition 2 (ε-best arm)**.** *Given a parameter $\varepsilon \in (0, 1)$, $\texttt{arm}_i$ with mean reward μ_i is said to be an ε-best arm if $\mu_i \geq \mu^* - \varepsilon$. Otherwise we call the arm $\texttt{arm}_i$ to be a non-ε-best arm.*

Definition 3 ((ε, δ)-PAC Algorithm)**.** *Given an approximation parameter $\varepsilon \in [0, 1)$ and a confidence parameter $\delta \in [0, 1/2)$, an algorithm $\mathcal{A}$ is an (ε, δ)-PAC algorithm if it outputs an ε-best arm with probability at least $1 - \delta$.*

Traditionally, the goal in the best-arm identification is to design an (ε, δ)-PAC algorithm minimizing the total number of arm pulls. The goal under streaming setup is to find an (ε, δ)-PAC algorithm that minimizes the total number of arm pulls while storing at most m arms in the arm-memory at any time.

3   Regret Minimization

In this section, we study limitations of bounded arm-memory for regret minimization. An adaptation of uniform-exploration algorithm (see [25]) achieves expected cumulative regret of $\tilde{O}(n^{1/3} T^{2/3})$ with an arm-memory of two. The algorithm keeps in the arm-memory one arm $\texttt{arm}^*$, called the king, with the best empirical mean $\widehat{\mu}_{\texttt{arm}^*}$ among the arms seen so far. Whenever a new arm $\texttt{arm}_i$ arrives, $\texttt{arm}_i$ is sampled $(T/n)^{2/3} O(\log T)^{1/3}$ times to obtain its empirical mean $\widehat{\mu}_i$. Then, $\widehat{\mu}_i$ is compared with $\widehat{\mu}_{\texttt{arm}^*}$. If $\widehat{\mu}_{\texttt{arm}^*} < \widehat{\mu}_i$, then $\texttt{arm}_i$ becomes the new king, replacing $\texttt{arm}^*$. Otherwise, $\texttt{arm}^*$ continues to be the king. After the algorithm tries out all the arms, it returns the king as the best-arm and continues to sample it for the rest of the time horizon.

An important question left open in [24] is to provide a lower bound on the expected cumulative regret of an algorithm with bounded arm-memory. We settle the question by showing that any single-pass algorithm for such a setting incurs at least $\Omega\left(n^{1/3} \cdot T^{2/3} / m^{7/3}\right)$ regret.

189 Now we state some fundamental properties of KL-divergence that will be needed in this section.

190 **Theorem 1** (Slivkins [25]). KL-*divergence satisfies the following properties:*

191   • Pinsker's inequality: *For any event $A \subset \Omega$, we have $2(p(A) - q(A))^2 \leq \mathtt{KL}(p, q)$.*

192   • Chain rule for product distributions: *Let the sample space be a product $\Omega = \Omega_1 \times \Omega_2 \times \ldots \times \Omega_t$.*
193   *Let p, q be two distributions on Ω such that $p = p_1 \times p_2 \times \cdots \times p_t$ and $q = q_1 \times q_2 \times \cdots \times q_t$,*
194   *where p_j, q_j are distributions on Ω_j, for each $j \in [t]$. Then $\mathtt{KL}(p, q) = \sum_{j=1}^{t} \mathtt{KL}(p_j, q_j)$.*

195   • Random coins: *Let $\mathtt{B}_\varepsilon$ denote a Bernoulli distribution with mean $(1 + \varepsilon)/2$. Then*
196        $\mathtt{KL}(\mathtt{B}_\varepsilon, \mathtt{B}_0) \leq 2\varepsilon^2$ *and* $\mathtt{KL}(\mathtt{B}_0, \mathtt{B}_\varepsilon) \leq \varepsilon^2$, *for all $\varepsilon \in (0, 1/2)$.*

197 For simplicity of presentation, we first discuss a weaker version of our main result in the following
198 theorem.

199 **Theorem 2.** *In the* MAB *setting, fix the number of arms n and the time horizon T. For any single-*
200 *pass streaming MAB algorithm, if we are allowed to store at most $m < n$ arms, then there exists a*
201 *problem instance such that $\mathbb{E}[R(T)] \geq \Omega(T^{2/3}/m^2)$*

202 *Proof.* We consider 0-1 rewards and the following family of problem instances $\{\mathcal{I}_j : j \in$
203 $\{0, \ldots, m\}\}$ each containing n arms, with parameter $\varepsilon > 0$ (where $\varepsilon = 1/T^{1/3}$):

$$\mathcal{I}_0 = \begin{cases} \mu_i &= 1/2, & \text{for } i \neq n; \\ \mu_i &= 1, & \text{for } i = n. \end{cases}$$

$$\forall j \in [m],\ \mathcal{I}_j = \begin{cases} \mu_i &= (1 + \varepsilon)/2, & \text{for } i = j; \\ \mu_i &= 1/2, & \text{for } i \neq j. \end{cases}$$

204 In the above instances, μ_i denotes the expected reward of $\mathtt{arm}_i$, the i-th arm to arrive in the stream.

205 Before delving into the formal proof, we present an intuitive idea behind the proof. Consider the first
206 m arms that are loaded in the arm-memory. If these arms are not sampled for a sufficient number of
207 times, then the probability of discarding the best-arm from the arm-memory is large enough to lead
208 to a large regret in one of the instances in $\{(\mathcal{I}_j)_{j \in [m]}\}$. Instead, if these arms are sampled a greater
209 number of times, we accumulate a large regret in the problem instance $\mathcal{I}_0$. Appropriately choosing
210 the number of samplings to be done and balancing the regrets in these different cases leads to the
211 lower bound on the regret.

212 Note that a deterministic algorithm that directly stores the first m arms in the arm-memory and has the
213 least expected regret among all such deterministic algorithms, cannot have a worse regret compared
214 to any other algorithm that processes the first m arms in some different manner. This is because the
215 processing of any such algorithm can be replicated by an algorithm which directly stores the first m
216 arms. In other words, an algorithm that discards some of the first m arms without storing them, can
217 be replicated by an algorithm that first stores these arms in memory and then discards them without
218 sampling. Thus, w.l.o.g. we consider a deterministic algorithm $\mathcal{A}$ which directly stores the first m
219 arms in the arm-memory.

220 We next set up the sample space. Let $L = 1/(4m^2\varepsilon^2)$. Further, let $(r_s(i) : i \in [m], s \in [L])$ be
221 a tuple of mutually independent Bernoulli random variables where $r_s(i)$ has expectation μ_i. We
222 interpret $r_s(i)$ as the reward obtained when $\mathtt{arm}_i$ is pulled for the s-th time and the tuple is called
223 the *rewards table*. The sample space is then expressed as $\Omega = \{0, 1\}^{m \times L}$. Then, any $\omega \in \Omega$ can be
224 interpreted as a realization of the rewards table.

225 Each instance $\mathcal{I}_j$, where $j \in \{0, \ldots, m\}$, defines a distribution P_j on Ω as follows:

$$P_j(A) = \mathbb{P}[A \mid \mathcal{I}_j], \quad \text{for each } A \subseteq \Omega.$$

226 Given an instance $\mathcal{I}_j$ where $j \in \{0, \ldots, m\}$, let $P_j^{i,s}$ be the distribution of $r_s(i)$ under this instance.
227 Then, we have that $P_j = \prod_{i \in [m], s \in [L]} P_j^{i,s}$.

228 Let $S_t \subseteq \{\mathtt{arm}_1, \mathtt{arm}_2, \ldots, \mathtt{arm}_m\}$ denote the subset of first m arms which are discarded from
229 the arm-memory till (and including) time step t by the algorithm $\mathcal{A}$. If $\mathtt{arm}_i$ is discarded before
230 the algorithm begins pulling arms, call this time step 0, then we include $\mathtt{arm}_i$ in the set S_0 where

$i \in [m]$. As time horizon T is fixed, and we will eventually discard all arms at the end of time horizon, we can assume that $S_T = \{\texttt{arm}_1, \texttt{arm}_2, \ldots, \texttt{arm}_m\}$. For all $\omega \in \Omega$, let $T'_\omega = \arg\min_{0 \leq t \leq T}\{t : S_t \neq \emptyset\}$, i.e., T'_ω is the number of time steps since the beginning of the algorithm $\mathcal{A}$ when some arm in $\{\texttt{arm}_1, \texttt{arm}_2, \ldots, \texttt{arm}_m\}$ is discarded from the arm-memory for the first time. Let $A_1 = \{\omega \in \Omega : T'_\omega \leq L\}$ be the set of reward realizations for which $T'_\omega \leq L$. Now, fix some arm $i \in \{\texttt{arm}_1, \texttt{arm}_2, \ldots, \texttt{arm}_m\}$. Define $A_2^i = \{\omega \in \Omega : \texttt{arm}_i \in S_{T'_\omega}\}$ to be the event that the $\texttt{arm}_i$ belongs to $S_{T'_\omega}$. Now, let $A^i = A_1 \cap A_2^i$ be the set of reward realizations such that $\forall \omega \in A^i$, $T'_\omega \leq L$ and $\texttt{arm}_i$ is discarded from the arm-memory at the time step T'_ω. Also, for any event $A \subseteq \Omega$, let $\overline{A} = \Omega \setminus A$.

Now we have the following observation for instance $\mathcal{I}_0$.

Observation 1. *If $\omega \in \overline{A_1}$, then the algorithm $\mathcal{A}$ would incur regret of at least $L/2 = T^{2/3}/(8m^2)$ on instance $\mathcal{I}_0$.*

Let $i' = \arg\max_{i \in [m]} P_0(A^i)$. We get the next observation as the best arm $\texttt{arm}_{i'}$ is sampled at most L times.

Observation 2. *For all $\omega \in A^{i'}$, the regret on instance $\mathcal{I}_{i'}$ is at least $\varepsilon(T - L)/2 \geq T^{2/3}/4$.*

Now we will prove the following inequality, which will be useful in our analysis.

$$m \cdot P_{i'}(A^{i'}) + P_0(\overline{A_1}) \geq 1/4. \tag{1}$$

The above inequality intuitively shows that the probability of "bad" events that incur large regret, is significant. This inequality is trivially true if $P_0(\overline{A_1}) \geq 1/4$. Therefore, let us assume $P_0(\overline{A_1}) \leq 1/4$, i.e., $P_0(A_1) \geq 3/4$. Then $P_0(A^{i'}) \geq 3/(4m)$, by averaging argument. Using Theorem 1 for distributions P_0 and $P_{i'}$, we obtain:

$$2(P_0(A^{i'}) - P_{i'}(A^{i'}))^2$$

$$\leq \texttt{KL}(P_0, P_{i'}) = \sum_{i \in [m]} \sum_{t=1}^{L} \texttt{KL}(P_0^{i,t}, P_{i'}^{i,t}) \qquad \text{(by Pinsker's inequality and chain rule)}$$

$$= \sum_{i \in [m] \setminus \{i'\}} \sum_{t=1}^{L} \texttt{KL}(P_0^{i,t}, P_{i'}^{i,t}) + \sum_{t=1}^{L} \texttt{KL}(P_0^{i',t}, P_{i'}^{i',t}) \leq 0 + L \cdot 2\varepsilon^2.$$

In the last inequality, the first term of the summation is zero because all arms $\texttt{arm}_i$, where $i \in [m] \setminus \{i'\}$, have identical reward distributions under instances $\mathcal{I}_0$ and $\mathcal{I}_{i'}$. To bound the second term in the summation, we use the last property from Theorem 1. Thus, we have, $P_0(A^{i'}) - P_{i'}(A^{i'}) \leq \varepsilon\sqrt{L}$. Hence, $P_{i'}(A^{i'}) \geq P_0(A^{i'}) - \varepsilon\sqrt{L} \geq (3/(4m)) - (1/(2m)) = 1/(4m)$. Here, we use $P_0(A^{i'}) \geq 3/(4m)$ and $L = 1/(4m^2\varepsilon^2)$. Hence, if $P_0(\overline{A_1}) \leq 1/4$ then $m \cdot P_{i'}(A^{i'}) \geq 1/4$. This proves Inequality (1).

Now suppose that we choose an instance $\mathcal{I}$ in such a way that we have $\mathbb{P}[\mathcal{I} = \mathcal{I}_j] = 1/(2m)$ for any $j \in [m]$ and $\mathbb{P}[\mathcal{I} = \mathcal{I}_0] = 1/2$. Then,

$$\mathbb{E}[R(T)] \geq \mathbb{P}[\mathcal{I} = \mathcal{I}_{i'}] \cdot P_{i'}(A^{i'}) \cdot T^{2/3}/4 + \mathbb{P}[\mathcal{I} = \mathcal{I}_0] \cdot P_0(\overline{A_1}) \cdot T^{2/3}/(8m^2)$$

$$\geq \frac{1}{2m} \cdot (m \cdot P_{i'}(A^{i'})) \cdot T^{2/3}/(4m) + \frac{1}{2} \cdot P_0(\overline{A_1}) \cdot T^{2/3}/(8m^2)$$

$$\geq \left(m \cdot P_{i'}(A^{i'}) + P_0(\overline{A_1})\right) \cdot T^{2/3}/(16m^2) \geq T^{2/3}/(64m^2)$$

The first inequality follows from Observations 1 and 2. In the last equality, we have used Inequality (1). Note that the expectation is taken over the choice of input instance and randomness in reward. $\square$

Since a randomized algorithm is a distribution over deterministic algorithms, the above result also holds for any randomized algorithm. Now, by slight modification to the above family of instances and using more sophisticated techniques and involved analysis, we can improve the lower bound on the expected cumulative regret and obtain the following main result (see Appendix A for details):

Theorem 3. *In the* MAB *setting, fix the number of arms n and the time horizon T. For any single-pass streaming* MAB *algorithm, if we are allowed to store at most $m < n$ arms, then there exists a problem instance such that $\mathbb{E}[R(T)] \geq \Omega(\frac{n^{1/3}T^{2/3}}{m^{7/3}})$.*

In the above result, the arms can arrive in any order, known as adversarial-order arrival. Our hardness results can also be extended to random-order arrival of arms, which we define next. Let $\langle n, (\mu_i)_{i \in [n]} \rangle$ be an instance of the MAB problem. Let, $\sigma : [n] \to [n]$ be a permutation and let $(\texttt{arm}_{\sigma(i)})_{i \in [n]}$ be the ordering of $(\texttt{arm}_i)_{i \in [n]}$ under σ. Define $\mathcal{S}_n = \{\sigma : \sigma \text{ is a permutation of } [n]\}$. Under the random-order arrival model, we assume that the arrival order of the arms in the stream is determined by a permutation $\sigma \in \mathcal{S}_n$, which is drawn uniformly at random from the set $\mathcal{S}_n$. The arms arrive in the order in which they appear in the tuple $(\texttt{arm}_{\sigma(i)})_{i \in [n]}$, i.e., the first arm to arrive in the stream is $\texttt{arm}_{\sigma(1)}$, followed by $\texttt{arm}_{\sigma(2)}$, and so on. Random-order arrival is a well-studied model in optimization under uncertainty due to its connection with the secretary problem and optimal stopping theory [16]. The algorithm of RoyChaudhuri and Kalyanakrishnan [24] also uses an analogous random shuffling of arms. We show that even such random shuffling of arms does not beat $\Omega(T^{2/3})$ for the single-pass case. For random-order arrival, we obtain the following result (see Appendix B for details):

Theorem 4. *In the* MAB *setting, fix the number of arms n and the time horizon T. For any single-pass streaming* MAB *algorithm, if we are allowed to store at most $m < n$ arms, then in the setting of random order arrival there exists an input instance such that $\mathbb{E}[R(T)] \geq \Omega(\frac{n^{1/3}T^{2/3}}{m^{7/3}})$.*

4   Best-arm Identification

In this section, we design an (ε, δ)-PAC algorithm (Algorithm 1) which minimizes the total number of arm pulls while storing at most $m < n$ arms in the arm-memory. Let $r := m - 1$.

Intuitively, our algorithm maintains r levels and in each level we maintain a running best-arm candidate (denoted as $\texttt{arm}_i^*$ for the arm in level i) in the arm-memory. Every new arm first arrives at the level 1. When an arm $\texttt{arm}'$ arrives at level i, we sample $\texttt{arm}'$ (s_i number of times at level i) and compare its empirical mean with the empirical mean of $\texttt{arm}_i^*$. If it is better than $\texttt{arm}_i^*$ then $\texttt{arm}'$ is stored in $\texttt{arm}_i^*$ by replacing the previous arm in it, otherwise we drop $\texttt{arm}'$. Once we see a *sufficient* number ($= c_i$ for level i) of arms in a level, we send $\texttt{arm}_i^*$ to the next level $(i + 1)$. At each level i, only one out of every c_i arms is sent to level $i + 1$. As the level index i increases, value of c_i and s_i increases. Intuitively, for higher level indices, the number of arms reaching that level decreases rapidly. Hence, in higher levels each arm can be sampled more number of times for a more refined comparison without affecting the sample complexity. At the end of the stream, the algorithm returns the arm left in the highest level.

For $r = \log^* n$, our algorithm is related to the recent work by Assadi and Wang [3]. They propose an (ε, δ)-PAC algorithm (Algorithm 3 in [3]) for the above setting, which has optimal sample complexity and stores at most $\log^* n$ arms in the arm-memory at any time step. However, their analysis is erroneous, due to which their algorithm will output a non-ε-best arm with probability much greater than δ for some input sequences. This implies that the (ε, δ)-PAC guarantee in Lemma 6.2 of [3] does not hold. Here, we intuitively describe the problem in their analysis and show how our algorithm overcomes it.

The algorithm by [3] has a similar framework as that of our algorithm. It maintains $\log^* n$ levels and in each level they also maintain a running best-arm candidate (denoted as $\texttt{arm}_i^*$ for level i) in the arm-memory. However, their algorithm samples both $\texttt{arm}_\ell^*$ and the arriving arm $\texttt{arm}_i$ s_ℓ number of times whereas our algorithm only samples the arriving arm $\texttt{arm}_i$ s_ℓ number of times and reuses the stored empirical mean of $\texttt{arm}_\ell^*$ for the comparison. This seemingly simple but critical difference renders their claim erroneous. We briefly explain the intuition behind this with the help of an example. Let the first three arms to arrive in the stream be $\texttt{arm}_1, \texttt{arm}_2, \texttt{arm}_3$ with means $0.5, 0.45, 0.40$, respectively. After sampling the first two arms, let us assume that $\texttt{arm}_2$ defeats $\texttt{arm}_1$, which can happen with sufficiently large probability as their means are close. Now, if we only sample $\texttt{arm}_3$ and use the previous empirical mean of $\texttt{arm}_2$, then $\texttt{arm}_3$ can defeat $\texttt{arm}_2$ if its empirical mean exceeds the empirical mean of $\texttt{arm}_2$ which in turn is greater than that of $\texttt{arm}_1$. This is unlikely as the means of $\texttt{arm}_3$ and $\texttt{arm}_1$ are far apart. On other hand, $\texttt{arm}_3$ has a good chance of defeating $\texttt{arm}_2$ if $\texttt{arm}_2$ is resampled since the empirical mean of $\texttt{arm}_2$ after resampling can be lower than the empirical

---

Algorithm 1 (ε, δ)-PAC algorithm for Best-arm indentification

---

1: $\{\varepsilon_\ell\}_{\ell=1}^r : \varepsilon_\ell \leftarrow \varepsilon/2^{\ell+1}$. //Intermediate gap parameter in level ℓ.
2: $\{\beta_\ell\}_{\ell=1}^r : \beta_\ell \leftarrow 1/\varepsilon_\ell^2$.
3: $\{s_\ell\}_{\ell=1}^r : s_\ell \leftarrow \lceil 2\beta_\ell\big(\texttt{ilog}^{(r+1-\ell)}(n) + \log(\frac{2^{\ell+2}}{\delta})\big)\rceil$. //Samples per arm in level ℓ.
4: $\{c_\ell\}_{\ell=1}^r : c_\ell \leftarrow \lceil \texttt{ilog}^{(r-\ell)}(n)\rceil$. //Number of arms in level ℓ.
5: Counters: $C_1, C_2, \ldots, C_r$, initialized to 0.
6: Stored arms: $\texttt{arm}', \texttt{arm}_1^*, \texttt{arm}_2^*, \ldots, \texttt{arm}_r^*$, where $\texttt{arm}_\ell^*$ is a running best-arm candidate at the ℓ-th level, initialized to NULL.
7: Stored empirical means: $\mu_1^*, \mu_2^*, \ldots, \mu_r^*$, where μ_ℓ^* is the highest empirical mean of ℓ-th level, initialized to 0.
   //Modified Selective Promotion (Steps 8-18).
8: **while** a new arm $\texttt{arm}_i$ arrives in the stream **do**
9:   $\texttt{arm}' \leftarrow \texttt{arm}_i$ and $\ell \leftarrow 0$.
10:   **while** $\ell = 0$ **or** $C_\ell = c_\ell$ **do**
11:     If $\ell \neq 0$, then $C_\ell \leftarrow 0$, $\mu_\ell^* \leftarrow 0$, $\texttt{arm}' \leftarrow \texttt{arm}_\ell^*$, and $\texttt{arm}_\ell^* \leftarrow$ NULL.
12:     $\ell \leftarrow \ell + 1$. //Promoting $\texttt{arm}'$ to next level
13:     Sample $\texttt{arm}'$ for s_ℓ times and compare its empirical mean $\widehat{\mu}_{\texttt{arm}'}$ with μ_ℓ^*.
14:     If $\widehat{\mu}_{\texttt{arm}'} < \mu_\ell^*$, drop $\texttt{arm}'$ from the memory. Otherwise, $\texttt{arm}_\ell^* \leftarrow \texttt{arm}'$ and $\mu_\ell^* \leftarrow \widehat{\mu}_{\texttt{arm}'}$.
15:     $C_\ell \leftarrow C_\ell + 1$.
16:     If $C_\ell = c_\ell$ and $r = 1$, **return** $\texttt{arm}_1^*$ as the selected arm and terminate the Algorithm.
17:   **end while**
18: **end while**
19: If there is any arm which is stored in a level below r, then promote it to level r and sample it for s_r times. Let $\texttt{arm}_{\ell'}^*$ be the arm with the highest empirical mean $\widehat{\mu}_{\ell'}$ among the arms which were sampled in this step, where $\ell' \in [r-1]$. If $\mu_r^* \leq \widehat{\mu}_{\ell'}$ then $\texttt{arm}_r^* \leftarrow \texttt{arm}_{\ell'}^*$.
   //Post-processing step done at the end of the stream to send any arm
   present in intermediate levels to the final level for sampling.
20: **return** $\texttt{arm}_r^*$.

---

mean of $\texttt{arm}_3$ with sufficiently large probability. Extending this example to a stream of n arms would imply that an arm with significantly low mean can get selected by the Algorithm in [3] with high probability. For a detailed discussion on this, we refer the reader to Appendix E.

We now proceed towards the detailed analysis of Algorithm 1. For simplicity of presentation, we ignore the *ceiling* function in the expression of s_ℓ and c_ℓ.

Theorem 5. *Algorithm 1 is an (ε, δ)-PAC algorithm with worst-case sample complexity* $O\big(\frac{n}{\varepsilon^2} \cdot (\texttt{ilog}^{(r)}(n) + \log(\frac{1}{\delta}))\big)$ *and $O(r)$ space complexity, where $1 \leq r \leq \log^*(n)$.*

Proof. We prove this theorem using the following lemmas. Lemma 7 shows that the sample complexity of our algorithm is $O\big(\frac{n}{\varepsilon^2} \cdot (\texttt{ilog}^{(r)}(n) + \ln(\frac{1}{\delta}))\big)$. Lemma 9 gives the proof of correctness that the algorithm is (ε, δ)-PAC. Further, at each of the r levels we store a single arm along with its empirical mean, implying the space complexity of our algorithm. $\square$

Corollary 6. *Algorithm 1 is an (ε, δ)-PAC algorithm with worst-case sample complexity* $O\big(\frac{n}{\varepsilon^2} \cdot \log(\frac{1}{\delta})\big)$ *and $O(\log^* n)$ space complexity, when $r = \log^* n$.*

The following lemma establishes the worst sample complexity of Algorithm 1 (see Appendix D for the detailed proof of the lemma).

Lemma 7. *The worst case sample complexity of the algorithm is $O\big(\frac{n}{\varepsilon^2} \cdot (\texttt{ilog}^{(r)}(n) + \ln(\frac{1}{\delta}))\big)$ and it does not depend on the arms' rewards or gap parameter or the order in which the arms arrive.*

We use the following lemma which follows from the Hoeffding's inequality, to prove the correctness of our algorithm (see Appendix D for the detailed proof).

Lemma 8. *Let $\texttt{arm}_1$ and $\texttt{arm}_2$ be two different arms with means μ_1 and μ_2. Suppose $\mu_1 - \mu_2 \geq \theta$ and we sample each arm $\frac{K}{\theta^2}$ times to obtain empirical means $\widehat{\mu}_1$ and $\widehat{\mu}_2$. Then,*

$$\mathbb{P}(\widehat{\mu}_1 \leq \widehat{\mu}_2) \leq 2 \cdot e^{(-K/2)}$$

We now proceed to show that our algorithm is an (ε, δ)-PAC algorithm.

Claim 1. *For any level $\ell < r$, let $\mathtt{arm}'_\ell$ be the best arm to ever reach this level. Then, with probability at least $1 - \frac{\delta}{2^{\ell+1}}$, an arm with reward gap at most ε_ℓ from $\mathtt{arm}'_\ell$ is sent to level $\ell + 1$ or is sampled in Step 19.*

Proof. Let us consider some level ℓ and a set of arms $\mathtt{arm}_{\ell_1}, \mathtt{arm}_{\ell_2}, \ldots, \mathtt{arm}_{\ell c_\ell}$, which increases the counter C_ℓ from 0 to c_ℓ. Denote the best arm among them as $\mathtt{arm}'_\ell$ and let $\mathtt{arm}^*_\ell$ be the empirically best arm seen so far since the arrival of $\mathtt{arm}_{\ell_1}$. Our algorithm works as follows: once an arm arrives at level ℓ, it is pulled s_ℓ number of times. Next, we compare its empirical mean with that of $\mathtt{arm}^*_\ell$, which was computed when the arm corresponding to $\mathtt{arm}^*_\ell$ arrived at level ℓ. The arm with the greater empirical mean is maintained as $\mathtt{arm}^*_\ell$ and its empirical mean is stored for future comparisons. Once $C_\ell = c_\ell$, $\mathtt{arm}^*_\ell$ is sent to level $\ell + 1$. Note that this is equivalent to simultaneously pulling each of the c_ℓ arms s_ℓ number of times, and then sending the empirically best arm to level $\ell + 1$. Also note that if $0 < C_\ell < c_\ell$, and the condition in Step 8 is not satisfied then we will sample $\mathtt{arm}^*_\ell$ in the Step 19.

Using Lemma 8, we can show that at any level ℓ, if two arms have reward gap $\mu_i - \mu_j \geq \varepsilon_\ell$ then $\mathbb{P}[\widehat{\mu}_i < \widehat{\mu}_j] \leq \frac{\delta}{2^{\ell+1} \cdot c_\ell}$. Since at most c_ℓ arms arrive at level ℓ before the counter C_ℓ reaches c_ℓ or the condition in Step 8 is not satisfied, taking union bound we have that the probability that an arm with reward gap $\leq \varepsilon_\ell$ with respect to $\mathtt{arm}'_\ell$ is either sent to level $\ell + 1$ or is sampled in the Step 19 is at least $1 - \frac{\delta}{2^{\ell+1} \cdot c_\ell} \cdot c_\ell = 1 - \frac{\delta}{2^{\ell+1}}$. $\qquad\square$

Claim 2. *Let $\mathtt{arm}'_r$ be the best arm among the arms which reached level r including the arms which were sampled in Step 19 of Algorithm 1. Then, with probability at least $1 - \frac{\delta}{2^{r+1}}$, an arm with reward gap at most ε_r from $\mathtt{arm}'_r$ is returned by the Algorithm.*

Proof. Using Lemma 8, we can show that among the arms that are being considered here, if two arms have reward gap $\mu_i - \mu_j \geq \varepsilon_r$ then $\mathbb{P}[\widehat{\mu}_i < \widehat{\mu}_j] \leq \frac{\delta}{2^{r+1} \cdot c_r}$. As $c_r = n$, by taking union bound we get that with probability at least $1 - \frac{\delta}{2^{r+1}}$, an arm with reward gap at most ε_r from $\mathtt{arm}'_r$ is returned by the Algorithm. $\qquad\square$

Lemma 9. *With probability at least $1 - \delta$, the arm selected by the algorithm is an ε-best arm.*

Proof. Let the best arm be $\mathtt{arm}^*$. By union bound and Claim 1, the probability that an arm with reward gap at most $\sum_{i=1}^{r-1} \varepsilon_i$ from $\mathtt{arm}^*$ neither reaches level r via Modified Selective Promotion nor is sampled in Step 19 is upper bounded by $\sum_{\ell=1}^{r-1} \delta/2^{\ell+1}$. Given this upper bound and Claim 2, the probability that an arm with reward gap at most $\sum_{i=1}^{r} \varepsilon_i$ from $\mathtt{arm}^*$ is not returned by the Algorithm is upper bounded by: $\sum_{\ell=1}^{r} \delta/2^{\ell+1} \leq \delta \cdot \sum_{\ell=1}^{\infty} 1/2^{\ell+1} = \delta/2 < \delta$.

Thus with probability at least $1 - \delta$, an arm with reward gap at most: $\sum_{\ell=1}^{r} \varepsilon_\ell = \sum_{\ell=1}^{r} \varepsilon/2^{\ell+1} \leq \varepsilon/2 < \varepsilon$ from $\mathtt{arm}^*$ is returned by the algorithm. This concludes the proof. $\qquad\square$

5   Conclusion

In this paper, we studied the MAB problem with bounded arm-memory under regret minimization and best-arm identification. First we showed a lower bound of $\Omega(n^{1/3} \cdot T^{2/3}/m^{7/3})$ on the expected cumulative regret for single-pass MAB algorithms with bounded arm-memory. Next we proposed (ε, δ)-PAC streaming algorithm with $O(r)$ space complexity ($r \in [\log^* n]$) which has optimal sample complexity when $r = \log^* n$. A future research direction is to obtain instance-dependent lower bounds on the expected cumulative regret for single-pass MAB algorithms with bounded arm-memory. Another direction would be to obtain an (ε, δ)-PAC streaming algorithm with $O(1)$ space complexity and optimal sample complexity.

References

[1] Charu C Aggarwal. *Data streams: models and algorithms*, volume 31. Springer Science & Business Media, 2007.

[2] Noga Alon, Yossi Matias, and Mario Szegedy. The space complexity of approximating the frequency moments. In *Proceedings of the twenty-eighth annual ACM symposium on Theory of Computing*, pages 20–29, 1996.

[3] Sepehr Assadi and Chen Wang. Exploration with limited memory: streaming algorithms for coin tossing, noisy comparisons, and multi-armed bandits. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, pages 1237–1250, 2020.

[4] Peter Auer, Nicolò Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2-3):235–256, 2002.

[5] Donald A Berry, Robert W Chen, Alan Zame, David C Heath, and Larry A Shepp. Bandit problems with infinitely many arms. *The Annals of Statistics*, pages 2103–2116, 1997.

[6] Sébastien Bubeck and Nicolo Cesa-Bianchi. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *Foundations and Trends® in Machine Learning*, 5(1):1–122, 2012.

[7] Vitor R Carvalho and William W Cohen. Single-pass online learning: Performance, voting schemes and online feature selection. In *Proceedings of the 12th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 548–553, 2006.

[8] Jhelum Chakravorty and Aditya Mahajan. Multi-armed bandits, gittins index, and its calculation. *Methods and applications of statistics in clinical trials: Planning, analysis, and inferential methods*, 2(416-435):455, 2014.

[9] Thomas H Cormen, Charles E Leiserson, Ronald L Rivest, and Clifford Stein. *Introduction to algorithms*. MIT press, 2009.

[10] Thomas M Cover. A note on the two-armed bandit problem with finite memory. *Information and Control*, 12(5):371–377, 1968.

[11] Yuval Dagan and Ohad Shamir. Detecting correlations with little memory and communication. In *Conference On Learning Theory*, pages 1145–1198, 2018.

[12] Eyal Even-Dar, Shie Mannor, and Yishay Mansour. Pac bounds for multi-armed bandit and markov decision processes. In *International Conference on Computational Learning Theory*, pages 255–270. Springer, 2002.

[13] Moein Falahatgar, Alon Orlitsky, and Venkatadheeraj Pichapati. Optimal sequential maximization: One interview is enough! In *International Conference on Machine Learning*, pages 2975–2984. PMLR, 2020.

[14] Heitor Murilo Gomes, Jesse Read, Albert Bifet, Jean Paul Barddal, and João Gama. Machine learning for streaming data: state of the art, challenges, and opportunities. *ACM SIGKDD Explorations Newsletter*, 21(2):6–22, 2019.

[15] Stephen J Herschkorn, Erol Pekoez, and Sheldon M Ross. Policies without memory for the infinite-armed bernoulli bandit under the average-reward criterion. *Probability in the Engineering and Informational Sciences*, 10:21–28, 1996.

[16] Anna Karlin and Eric Lei. On a competitive secretary problem. In *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence*, pages 944–950, 2015.

[17] Robert Kleinberg, Aleksandrs Slivkins, and Eli Upfal. Bandits and experts in metric spaces. *Journal of the ACM (JACM)*, 66(4):1–77, 2019.

[18] David Liau, Zhao Song, Eric Price, and Ger Yang. Stochastic multi-armed bandits in constant space. In *International Conference on Artificial Intelligence and Statistics*, pages 386–394, 2018.

[19] Chi-Jen Lu and Wei-Fu Lu. Making online decisions with bounded memory. In *International Conference on Algorithmic Learning Theory*, pages 249–261. Springer, 2011.

[20] Shanmugavelayutham Muthukrishnan. *Data streams: Algorithms and applications*. Now Publishers Inc, 2005.

[21] Erol A Peköz. Some memoryless bandit policies. *Journal of applied probability*, pages 250–256, 2003.

[22] Piyush Rai, Hal Daumé, and Suresh Venkatasubramanian. Streamed learning: one-pass svms. In *Proceedings of the 21st international jont conference on Artifical intelligence*, pages 1211–1216, 2009.

[23] Herbert Robbins. Some aspects of the sequential design of experiments. *Bulletin of the American Mathematical Society*, 58(5):527–535, 1952.

[24] Arghya RoyChaudhuri and Shivaram Kalyanakrishnan. Regret minimisation in multi-armed bandits using bounded arm memory. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020*, pages 10085–10092. AAAI Press, 2020.

[25] Aleksandrs Slivkins. Introduction to multi-armed bandits. *Found. Trends Mach. Learn.*, 12 (1-2):1–286, 2019.

[26] Linqi Song, Jie Xu, and Congduan Li. Active learning for streaming data in a contextual bandit framework. In *Proceedings of the 2019 5th International Conference on Computing and Data Engineering*, pages 29–35, 2019.

[27] William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.

[28] Long Tran-Thanh, Lampros Stavrogiannis, Victor Naroditskiy, Valentin Robu, Nicholas R Jennings, and Peter Key. Efficient regret bounds for online bid optimisation in budget-limited sponsored search auctions. *Uncertainty in Artificial Intelligence*, pages 809–818, 2014.

[29] Long Tran-Thanh, Sebastian Stein, Alex Rogers, and Nicholas R Jennings. Efficient crowd-sourcing of unknown experts using bounded multi-armed bandits. *Artificial Intelligence*, 214: 89–111, 2014.

[30] Zirui Wang, Sanket Vaibhav Mehta, Barnabas Poczos, and Jaime G Carbonell. Efficient meta lifelong-learning with limited memory. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 535–548, 2020.

[31] Xiao Xu and Qing Zhao. Memory-constrained no-regret learning in adversarial bandits. *arXiv preprint arXiv:2002.11804*, 2020.

[32] Indrė Žliobaitė, Albert Bifet, Bernhard Pfahringer, and Geoffrey Holmes. Active learning with drifting streaming data. *IEEE transactions on neural networks and learning systems*, 25(1): 27–39, 2013.