Depth is More Powerful than Width in Deep Forest

Abstract

Random Forest (RF) is an ensemble learning algorithm proposed by Breiman [2001] that constructs a large number of randomized decision trees individually and aggregates their predictions by naive averaging. Zhou and Feng [2019] further propose Deep Forest (DF) algorithm with multi-layer feature transformation, which significantly outperforms single-layer random forest in various application fields. Despite its great successes, little is known about the mathematical properties of the cascade structure. In this paper, we analyze the influence of depth and width on the consistency of cascade forest. Especially when the individual tree is inconsistent (as in practice, the individual tree is often set to be fully grown, i.e., there is only one sample at each leaf node), we find that the convergence rate of two-layer DF *w.r.t.* the number of trees M can reach $\mathcal{O}(1/M^2)$ under some mild conditions, while the convergence rate of single-layer RF is $\mathcal{O}(1/M)$. Therefore, learning decision trees in the "deep" layer will be more powerful than learning in the "shallow" layer. Experiments further confirm the theoretical advantages.

1 Introduction

Random forest (RF) [Breiman, 2001] is a state-of-art classification and regression algorithm that constructs a number of randomized individual decision trees during a parallel training phase and predicts by naive averaging the results. Recently, Zhou and Feng [2019] propose Deep Forest (DF) algorithm with multi-layer feature transformation to investigate the possibility of tree-based representation learning. Benefiting from the layer-by-layer feature transformation in cascade structure (depth), DF outperforms various single-layer forest algorithms [Breiman, 2001, Friedman, 2001, Geurts et al., 2006, Chen and Guestrin, 2016] in empirical study, and have been involved in real applications such as medicine [Su et al., 2019], computer vision [Zhou et al., 2019], remote sensing [Boualleg et al., 2019], financial fraud detection [Zhang et al., 2019], etc. Numerous variants have been extended to various tasks and meet with remarkable success in Utkin and Ryabinin [2018, 2019], Yang et al. [2020], Wang et al. [2020]. There are also variants aiming at improving performance and reducing computational cost [Pang et al., 2020, Chen et al., 2021].

Empirical successes have attracted attention to the theoretical analysis of DF. Since its cascade structure transforms features layer by layer, and each layer consists of complex non-parametric random forest estimators, analyzing the impact of the new features extracted from these estimators on generalization performance is important. To start theoretical analysis on DF, Lyu et al. [2019] prove a margin-based generalization bound for additive new features in DF. Then, Pang et al. [2020] prove an upper bound on the sample efficiency and inspire an efficient improvement for reducing computational cost of DF. In the direction of consistency, Arnould et al. [2021] provide tight lower and upper bounds on the excess risk of a shallow centered random tree network, which leverages the new features to improve the performance of a single centered random tree. Assuming that the original and new features are separated and independently used in two stages, Lyu et al. [2022] prove

that the new features based on prediction are easy to cause overfitting risk, and propose to use the interaction of decision rules to alleviate it.

However, previous theoretical studies often choose to ignore the impact of the new features on the forest generation. For example, Lyu et al. [2019, 2022], Pang et al. [2020] assume that the forest estimator in each layer is a black-box model and Arnould et al. [2021] simplify that there is only a single centered random tree in each layer. Such strong assumptions are in favor of theoretical analysis, but widen the gap between the theoretical results and practical deep forest architecture. The difficulty in properly analyzing DF can be explained by the subtle combination of different techniques. Among the complex architecture in DF, both prediction concatenation (PreConc) [Lyu et al., 2019] and the classification and regression trees (CART)-split criterion [Breiman et al., 1984] play a critical role. Therefore, in order to open the black box of DF, we need to analyze the properties of the new feature and study how CART generates and utilizes it.

Contributions. In this paper, we try to narrow the gap between theoretical and empirical studies on DF. We compare the advantages of depth (cascade structure with PreConc in deep forest) over width (bagging of trees in random forest) in the scope of $\mathbb{L}_2^2$-consistency, based on the assumptions of the additive regression functions and uniform distribution over input space. The main contributions can be summarized as follows:

- We are the first to establish a theoretical analysis of the priority of the new feature under the CART-split criterion in DF, which means the trees in the second layer and beyond tend to primarily choose the new feature to split. We further prove that the degree of this priority depends on the error of the first-layer forest estimator.

- We prove the universal consistency of CART, random forest and deep forest when the total number of leaves of individual trees is chosen properly. Although in this setting, neither depth nor width will affect the consistency, experiments show that such trees have poor performance in practice.

- In the practical setting, when the individual trees are fully grown, we prove that the convergence rate of two-layer deep forest reach $\mathcal{O}(1/M^2)$ *w.r.t.* the increasing number of trees M, while that of single-layer random forest is $\mathcal{O}(1/M)$. This result reflects that depth is more powerful than width.

Agenda. The rest of this work is organized as follows: Section 3 shows the setting and notations related to tree-based estimators in this work. Section 4 recall the original deep forest architecture and simplify it into a two-layer deep forest. Section 5 contains the properties of cascade structure with prediction concatenation. Section 6 proves the main result that depth is more powerful than width in deep forest architecture in the scope of consistency. Section 7 is devoted to the empirical studies of deep forest by verifying the theoretical results above. Section 8 concludes with future work. Detailed proofs for theorems and propositions are given in the supplementary material due to page limitation.

2 Related work

Despite the widespread use and remarkable success of random forest in real world applications, the theoretical properties of it are still not fully understood [Biau, 2012, Denil et al., 2014]. Breiman [2001] offers an upper bound on the generalization error of random forest in terms of correlation and accuracy of the individual trees. Lin and Jeon [2006] establish a connection between random forest and a particular class of nearest neighbor predictors, which are further studied by Biau and Devroye [2010]. Meinshausen [2006] studies the consistency of the quantile random forest for regression. In recent years, various theoretical works [Biau, 2012, Biau et al., 2008, Ishwaran and Kogalur, 2010, Genuer, 2012, Zhu et al., 2015] have been performed, analyzing the consistency of various simplified forests, and moving ever closer to practice. Denil et al. [2014] narrows the gap between theory and practice of random forests for regression. Scornet et al. [2015] prove the first $\mathbb{L}_2^2$-consistency of Breiman's original random forest with CART-split criterion based on the assumptions of the additive regression functions and uniform distribution over input space. Scornet [2016] prove that infinite forest consistency implies finite forest consistency. Gao and Zhou [2020] then present the convergence rate of purely randomized trees and a simplified variant of Breiman's original CART trees. In addition, another research route is the theory analysis of feature importance [Strobl et al., 2007, Louppe et al., 2013, Arnould et al., 2022]. Recently, Li et al. [2019] derive non-asymptotic lower and upper bounds on the expected bias of MDI importance for random forests. Sutera et al. [2021] establish a connection between MDI importance of pure random forest and Shapley values.

3 Setting and notations

We first describe the setting and notations related to tree-based estimators in this work. For the sake of conciseness, we consider the regression setting.

Setting. We consider a regression framework, where the training set $S_n = \{(\boldsymbol{x}_1, y_1), \ldots, (\boldsymbol{x}_n, y_n)\}$ of $[0,1]^d \times \mathbb{R}$-valued independent random variables distributed as the prototype sample $(\boldsymbol{x}, y)$ with $\mathbb{E}[y^2] < \infty$. This underlying distribution, characterized by the marginal distribution $\mathcal{D}_{\mathcal{X}}$ on $[0,1]^d$ and by the conditional distribution $\mathcal{D}_{\mathcal{Y}|\mathcal{X}}$, can be written as

$$y = f(\boldsymbol{x}) + \epsilon, \tag{1}$$

where $f(\boldsymbol{x}) = \mathbb{E}[y|\boldsymbol{x}]$ is the conditional expectation of y given $\boldsymbol{x}$, and ϵ is a noise satisfying $\mathbb{E}[\epsilon] = 0$ and $\mathrm{Var}[\epsilon] < \sigma^2$. The task considered in this paper is to output a randomized estimator $h_n(\cdot, \Theta, S_n) \colon [0,1]^d \to \mathbb{R}$ where Θ is a random variable that accounts for the randomization procedure and independent of the training set S_n. To simplify notation, we denote $h_n(\boldsymbol{x}, \Theta) = h_n(\boldsymbol{x}, \Theta, S_n)$. The quality of a randomized estimator h_n is measured by its $\mathbb{L}_2$ risk

$$R(h_n) = \mathbb{E}\left[(h_n(\boldsymbol{x}, \Theta) - f(\boldsymbol{x}))^2 \right], \tag{2}$$

where the expectation is taken with respect to $(\boldsymbol{x}, \Theta)$, conditionally on S_n. As the training data size n increases, we get a sequence of estimators $\{h_1, h_2, \ldots, h_n, \ldots\}$. A sequence of estimators $\{h_n\}_{n=1}^{\infty}$ is said to be consistent if $R(h_n) \to 0$ as $n \to \infty$.

Trees and forests. A random forest estimator $h_{M,n}(\boldsymbol{x}, \Theta)$ outputs the average prediction over M individual randomized trees $h_n(\boldsymbol{x}, \Theta_j)$, $\forall j \in [M]$. Here, $[M] = \{1, 2, \ldots, M\}$ denotes the indexes of all individual randomized trees, where $\Theta_1, \ldots, \Theta_M$ are distributed identically and independently and denoted by a generic random variable Θ. The random variable Θ can be used to sample the training set or select the candidate dimensions or positions for splitting. Specifically, a recursive partition Π of $[0,1]^d$ is built by performing successive axis-aligned splits according to Θ:

$$h_n(\boldsymbol{x}, \Theta) = \sum_{i=1}^{n} \frac{y_i \cdot \mathbb{1}(\boldsymbol{x}_i \in C_{\Pi,n}(\boldsymbol{x}))}{N_n(C_{\Pi,n}(\boldsymbol{x}))}, \tag{3}$$

where $C_{\Pi,n}(\boldsymbol{x})$ is the cell of the tree partition containing $\boldsymbol{x}$ and $N_n(C_{\Pi,n}(\boldsymbol{x}))$ is the number of training samples falling into $C_{\Pi,n}(\boldsymbol{x})$ with convention that the estimation equals to zero if the cell $C_{\Pi,n}(\boldsymbol{x})$ is empty. These trees are combined to form a finite forest estimation:

$$h_{M,n}(\boldsymbol{x}, \Theta) = h_{M,n}(\boldsymbol{x}, \Theta_1, \ldots, \Theta_M) = \frac{1}{M} \sum_{i=1}^{M} h_n(\boldsymbol{x}, \Theta_i). \tag{4}$$

By the law of large numbers, for any fixed $\boldsymbol{x}$, conditionally on $\mathcal{D}_n$, the finite forest estimation converges to the infinite forest estimation:

$$h_{\infty,n}(\boldsymbol{x}) = \lim_{M \to \infty} h_{M,n}(\boldsymbol{x}, \Theta) = \mathbb{E}_{\Theta}[h_n(\boldsymbol{x}, \Theta)]. \tag{5}$$

When the number of samples tends to ∞, we denote by $h_{\infty}(\boldsymbol{x}, \Theta)$ the randomized tree with infinite samples and $h_{M,\infty}(\boldsymbol{x}, \Theta)$ the random forest with M trees and infinite samples.

4 Deep forest

We recall the original deep forest algorithm in Section 4.1, and describe the simplified two-layer deep forest algorithm in Section 4.2.

4.1 Original deep forest

Deep forest [Zhou and Feng, 2019] is a tree-based deep model made up of non-differentiable forest modules without back-propagation. Each layer of DF is composed of two Breiman's random forest (RF) and two Completely-Random Forest (CRF). The RF is composed of CARTs and CRF

Figure 1: Deep forest architecture (the scheme is taken from Zhou and Feng [2019]).

is composed of pure random trees. In the regression setting, each forest of each layer outputs a prediction for any query point $\boldsymbol{x}$, corresponding to the average response in the leaf node (cell) containing $\boldsymbol{x}$. At a given layer, the predictions of all forests of this layer are concatenated together with raw features. This prediction concatenation process is called PreConc, which is repeated for each layer until the best layer and construct a deep forest. For an overview of the architecture of deep forest, we refer readers to the work [Zhou and Feng, 2017, 2019].

4.2 Simplified two-layer deep forest

In order to narrow the gap between theoretical and empirical studies of deep forest, we retain CART-split criterion and PreConc when simplifying the model. We define a simplified two-layer deep forest, each layer of it is composed of one Breiman's random forest. We denote by $h^{(1)}_{M,n}(\boldsymbol{x}, \Theta, S_n)$ the first-layer forest estimator and $h^{(2)}_{M,n}([\boldsymbol{x}, h], \Theta, S_n)$ the second-layer forest estimator, where $[\boldsymbol{x}, h]$ is the concatenation of the raw features $\boldsymbol{x}$ and the new feature h. Then we can define the two-layer deep forest as follows:

$$\bar{h}_{2M,n}(\boldsymbol{x}, \Theta, S_n) = h^{(2)}_{M,n} \circ h^{(1)}_{M,n}(\boldsymbol{x}, \Theta, S_n). \tag{6}$$

The complete algorithm is shown in Algorithm 1. This algorithm has three parameters: $m_{\text{try}} \in \{1, \ldots, d\}$ is the number of pre-selected directions for splitting, $a_n \in \{1, \ldots, n\}$ is the number of samples in each tree, $t_n \in \{1, \ldots, a_n\}$ is the number of leaves in each tree. In the default procedure, the parameters are set as follows: m_{try} is set to d. a_n is set to n/k, where k is the k-fold cross-validation in the Zhou and Feng [2019]'s deep forest. $t_n = a_n$ means we use fully grown CART which is inconsistent in practice. Notice that k can control the subsampling rate $a_n/n = 1/k$, which is proved by Scornet et al. [2015] to be the key component for imposing tree diversity.

Given the above parameters, the most basic part of Algorithm 1 is the training process of each CART. Let C be a cell and $N_n(C)$ be the number of data points falling in C. A split in C is a pair (j, z), where j is a dimension in $\{1, \ldots, d\}$ and z is the position of the split along the j-th dimension in cell C. Let $\mathcal{S}_C$ be the set of all possible splits in C. The CART-split criterion [Breiman et al., 1984] takes the form

$$\begin{aligned}
\hat{L}_n(j, z) = &\frac{1}{N_n(C)} \sum_{i: \boldsymbol{x}_i \in C} (y_i - \mu_n(C))^2 \\
&- \frac{1}{N_n(C_L)} \sum_{i: \boldsymbol{x}_i \in C_L} (y_i - \mu_n(C_L))^2 - \frac{1}{N_n(C_R)} \sum_{i: \boldsymbol{x}_i \in C_R} (y_i - \mu_n(C_R))^2
\end{aligned} \tag{7}$$

where $C_L = \{\boldsymbol{x} \in C : \boldsymbol{x}^{(j)} < z\}$, $C_R = \{\boldsymbol{x} \in C : \boldsymbol{x}^{(j)} \geq z\}$, and $\mu_n(C) = \frac{1}{N_n(C)} \sum_{i: \boldsymbol{x} \in A} y_i$ denotes the average response in any cell C (resp. $\mu_n(C_L), \mu_n(C_R)$), with the convention $0/0 = 0$. At each cell C, the best split (j_n^*, z_n^*) is selected by maximizing $\hat{L}_n(j, z)$ over $\mathcal{M}_{\text{try}}$ and $\mathcal{S}_C$, that is,

$$(j_n^*, z_n^*) \in \underset{\substack{(j^*, z^*) \in \mathcal{S}_C \\ j \in \mathcal{M}_{try}}}{\arg\max} \; \hat{L}_n(j, z). \tag{8}$$

Algorithm 1: A simplified variant of Zhou's original deep forest

---
Require: A training set $S_n = \{(\boldsymbol{x}_1, y_1), \ldots, (\boldsymbol{x}_n, y_n)\}$, the number of trees $2M$,
$\quad m_{\text{try}} \in \{1, \ldots, d\}$, $a_n \in \{1, \ldots, n\}$, $t_n \in \{1, \ldots, a_n\}$ and the query point $\boldsymbol{x} \in [0, 1]^d$.

Ensure: Two-layer deep forest $\bar{h}_{2M,n}(\cdot) = h_{M,n}^{(2)} \circ h_{M,n}^{(1)}(\cdot)$ and the prediction of $\boldsymbol{x}$.

1: **for** layer ℓ in $\{1, 2\}$ **do**
2:   **if** $\ell = 2$ **then**
3:     $S_n \leftarrow \{([\boldsymbol{x}_1, h_{M,n}^{(1)}(\boldsymbol{x}_1)], y_1), \ldots, ([\boldsymbol{x}_n, h_{M,n}^{(1)}(\boldsymbol{x}_n)], y_n)\}$.   ▷ *Prediction concatenation.*
4:   **end if**
5:   **for** tree $j \in \{1, 2, \ldots, M\}$ **do**
6:     Select a_n data points, without replacement, uniformly in S_n.
7:     Set $\Pi_0 = \{[0, 1]^d\}$ the partition associated with the root of the tree.
8:     For all $1 \leq i \leq a_n$, set $\Pi_i = \emptyset$.
9:     Set $n_{\text{nodes}} = 1$ and level $= 0$.
10:     **while** $n_{\text{nodes}} < t_n$ **do**
11:      **if** $\Pi_{\text{level}} = \emptyset$ **then**
12:       level $=$ level $+ 1$.
13:      **else**
14:       Let C be the first element in Π_{level}.
15:       **if** C contains exactly one point **then**
16:        $\Pi_{\text{level}} \leftarrow \Pi_{\text{level}} \setminus \{C\}$.
17:        $\Pi_{\text{level}+1} \leftarrow \Pi_{\text{level}+1} \cup \{C\}$.
18:       **else**
19:        Select the best split (j_n^*, z_n^*) in C by optimizing the CART-split criterion along the
         dimension D in $\{1, \ldots, d\}$.   ▷ *See details in Eq.* (7).
20:        Split cell C along D according to the best split. Call C_L and C_R.
21:        $\Pi_{\text{level}} \leftarrow \Pi_{\text{level}} \setminus \{C\}$.
22:        $\Pi_{\text{level}+1} \leftarrow \Pi_{\text{level}+1} \cup \{C_L\} \cup \{C_R\}$.
23:        $n_{\text{nodes}} \leftarrow n_{\text{nodes}} + 1$.
24:       **end if**
25:      **end if**
26:     **end while**
27:     Compute the predicted value $h_n^{(\ell)}(\boldsymbol{x}, \Theta_j, S_n)$ at the query point $\boldsymbol{x}$ equal to the average of
     the Y_i's falling in the cell of $\boldsymbol{x}$ in partition $\Pi_{\text{level}} \cup \Pi_{\text{level}+1}$.
28:   **end for**
29:   Compute the random forest estimation $h_{M,n}^{(\ell)}(\boldsymbol{x}, \Theta, S_n)$ at the query point $\boldsymbol{x}$ according to
   Eq. (4).
30: **end for**
31: Compute the two-layer deep forest estimation $\bar{h}_{2M,n}(\boldsymbol{x}, \Theta, S_n)$ at the query point $\boldsymbol{x}$ according
  to Eq. (6).

---

5   Properties of cascade structure

In this section we show that the properties of the simplified deep forest enable us to analyze the influence of the concatenated new feature in deep forest and the local variation related to the empirical CART-split criterion.

We consider an additive regression model satisfying the following assumption:

Assumption 1. *The response y follows*

$$y = \sum_{j=1}^{d} f_j(x^{(j)}) + \epsilon, \tag{9}$$

where $\boldsymbol{x} = \left(x^{(1)}, \ldots, x^{(d)}\right)$ is uniformly distributed over $[0, 1]^d$, ϵ is an independent centered Gaussian noise with finite variance $\sigma^2 > 0$ and each component f_j is continuous.

Stone [1985], Hastie and Tibshirani [1987] popularize these models, which decompose the regression function as a sum of univariate functions. Especially, Scornet et al. [2015] prove the consistency of

Breiman's original random forest under this assumption. On this basis, we study the impact of the new feature generated in the deep forest.

To start with, we analyze the priority of the new features generated by the previous layer in the selection of splitting features under the CART-split criterion, in both infinite sample regime and finite sample regime respectively.

Proposition 1 (Priority of the new feature). *Assume the data set follows Assumption 1 and the first-layer forest is consistent. The following results hold for any CART in the second-layer forest.*

1. *In the infinite sample regime ($n = \infty$), we consider a single second-layer CART $h_\infty^{(2)}(\cdot, \Theta)$. All splits in this CART are performed along the new feature only.*

2. *In the finite sample regime ($n < \infty$), we consider a single second-layer CART $h_n^{(2)}(\cdot, \Theta)$. Fix $k \in \mathbb{N}^*$ and $\xi, \rho > 0$. Then, with probability $\geq 1 - \rho$, for all n large enough, we have, the error of the first-layer forest is bound by ξ. As a consequence, the first k splits $(j_{q,n}(\boldsymbol{x}), 1 \leq q \leq k)$ in this CART are performed along the new feature only.*

Proof sketch. **(P1.1).** In the infinite sample regime, the random forest estimation of the first layer has zero error. Therefore, the new feature of the second layer is the target function $h_{M,\infty}^{(1)}(\boldsymbol{x}) = f(\boldsymbol{x})$. Obviously, the new feature is the most informative dimension. Therefore, when splitting in any cell, CART algorithm will select the new feature as the splitting dimension. **(P1.2).** In the finite sample regime, the random forest estimation of the first layer is not precise. Therefore, there is an error related to n between the new feature and the target function. Firstly, we prove that the distance between the theoretical ($n = \infty$) and empirical ($n < \infty$) first k splits of the CART algorithm is bounded by $c\xi$ with probability $\geq 1 - \rho$, when n is large enough. Connecting with the result of theoretical split above, the proof is completed. $\square$

Remark 1. Proposition 1 shows that the trees in the second layer primarily choose the new feature to split and the degree of this priority depends on the error of the first-layer forest estimator. This also reveals that the advantages of deep forest depend on the performance of the first layer. If the forest of the first layer does not return an estimation with noise reduction, the performance of deep forest cannot be further improved through cascade structure. This is consistent with the empirical results in previous work [Zhou and Feng, 2019, Arnould et al., 2021].

In order to control the risk of deep forest, we need study the local variation property of the empirical CART-split criterion. For any cell C, the variation of regression function $f(\boldsymbol{x})$ within C is defined as

$$\Delta(f, C) = \sup_{\boldsymbol{x}, \boldsymbol{x}' \in C} |f(\boldsymbol{x}) - f(\boldsymbol{x}')|. \tag{10}$$

Proposition 2 (Variation of f in the empirical cell). *Assume that Assumption 1 holds and the first-layer forest is consistent. The following results hold for any CART in the second-layer forest $h_n^{(2)}(\cdot, \Theta)$. After splitting along the new feature, the CART will estimate the residual of the first-layer forest estimation. Then for all $\rho, \xi > 0$, there exists $N \in \mathbb{N}^*$ such that, for all $n > N$,*

$$\Pr\left[\Delta\left(f, C_{\Pi,n}(\boldsymbol{x}, \Theta)\right) \leq \xi\right] \geq 1 - \rho. \tag{11}$$

Proof sketch. Firstly, we prove the variation of $f(\boldsymbol{x})$ within the cell obtained by the theoretical CART-split criterion converges to zero. Secondly, we prove that the distance between the theoretical and empirical first k splits of the CART convergence to zero. Finally, we prove that the variation of $f(\boldsymbol{x})$ within the empirical cell is close to the theoretical cell. $\square$

Proposition 2 shows that the variation of the regression function $f(\boldsymbol{x})$ within a cell of a random tree $C_{\Pi,n}$ is small provided n is large enough, thereby forcing the approximation error of DF to asymptotically approach zero.

6 Depth is more powerful than width

Our first result considers the $t_n < a_n$ regime, where the number of samples in each leaf node tends to ∞ as $t_n \to \infty$ and $a_n \to \infty$. We prove that controlling the depth of the trees through the number of leaves t_n is sufficient to achieve consistency of deep forest.

Theorem 3 (Universal consistency). *Let $M \geq 1$. Consider two-layer deep forest $\bar{h}_{2M,n}$ given by Eq. (6) and Breiman's random forest $h_{M,n}$ given by Eq. (4) for the random CARTs satisfying $a_n \to \infty, t_n \to \infty$ and $t_n (\log a_n)^9 / a_n \to 0$. Then under the setting described in Section 3 and assume the data set follows Assumption 1,*

> *1. [Scornet et al., 2015, Theorem 1] the Breiman's random forest $h_{2M,n}$ is consistent for any $M \geq 1$,*
>
> *2. the two-layer deep forest $\bar{h}_{M,n}$ is consistent for any $M \geq 1$.*

Proof sketch. **(T3.1).** The universal consistency of Breiman's random forest is proved by Scornet et al. [2015]. **(T3.2).** Firstly, we already know that the variation of the target regression function $f(\boldsymbol{x})$ within a cell of a randomized CART in the second-layer forest is small when n is large enough via Proposition 2. Similar as Scornet et al. [2015], we utilize Proposition 2 to control the approximation error of the two-layer deep forest. And the parameter t_n allows us to control the size of the leaves of CART, which allows us to have enough samples in each leaf node to smooth the impact of noise, so as to control the estimation error. Connecting the approximation and estimation error, the consistency of a CART of second-layer deep forest is proved. The universal consistency can be proved via Biau et al. [2008, Proposition 1], which guarantees that the error of forest estimator is no more than twice that of individual randomized CART. □

Remark 2. Notice that under this setting, random forest and even deep forest have no obvious advantages over single CART in theory. When we use forests in practical, we do not choose to control the depth of the trees. Empirical studies in Section 7.2 show that the forest with $t_n = a_n$ always outperforms the forest with $t_n < a_n$. Actually, the fully grown trees $t_n = a_n$ is the setting close to practical forest algorithm.

In order to deal with the $t_n = a_n$ regime, we need to introduce an assumption first proposed by Scornet et al. [2015]. We denote by $Z_i = \mathbb{1}(\boldsymbol{x}_i \in C_{\Pi,n}(\boldsymbol{x}))$ the indicator that $\boldsymbol{x}_i$ falls into the same cell as $\boldsymbol{x}$ in the random tree designed with $\mathcal{D}_n$ and the random parameter Θ. $Z'_j = \mathbb{1}(\boldsymbol{x}_i \in C_{\Pi'}(\boldsymbol{x}))$ is another independent indicator. Then, we define the correlation between these two indicators conditionally on y_i, y_j or not, respectively

$$\phi_{i,j}(y_i, y_j) = \mathbb{E}[Z_i, Z'_j | \boldsymbol{x}, \boldsymbol{x}_1, \ldots, \boldsymbol{x}_n, y_i, y_j] \quad \text{and} \quad \phi_{i,j} = \mathbb{E}[Z_i, Z'_j | \boldsymbol{x}, \boldsymbol{x}_1, \ldots, \boldsymbol{x}_n]. \quad (12)$$

Assumption 2. *Let $Z_{i,j} = (Z_i, Z_j)$. Then one of the following two conditions holds:*

> *1. One has*
> $$\lim_{n \to \infty} (\log a_n)^{2d-2} (\log n)^2 \mathbb{E}\left[\max_{i \neq j} |\phi_{i,j}(y_i, y_j) - \phi_{i,j}|\right]^2 = 0. \quad (13)$$

> *2. There exists a constant $C > 0$ and a sequence $(\gamma_n)_n \to 0$ such that, almost surely,*
> $$\max_{\ell_1, \ell_2 = 0,1} \frac{|\text{Cor}\left[(y_i - f(\boldsymbol{x}_i)), \mathbb{1}(Z_{i,j} = (\ell_1, \ell_2) | \boldsymbol{x}_i, \boldsymbol{x}_j, y_j)]\right|}{\text{Pr}^{1/2}[Z_{i,j} = (\ell_1, \ell_2) | \boldsymbol{x}_i, \boldsymbol{x}_j, y_j]} \leq \gamma_n, \quad (14)$$
> *and*
> $$\max_{\ell_1 = 0,1} \frac{\left|\text{Cor}\left[(y_i - f(\boldsymbol{x}_i))^2, \mathbb{1}(Z_i = \ell_1 | \boldsymbol{x}_i)]\right|\right|}{\text{Pr}^{1/2}[Z_i = \ell_1 | \boldsymbol{x}_i]} \leq C. \quad (15)$$

(A2.1.) means that the influence of two labels y_i, y_j on the probability of connection of two couples of random points converge to zero as $n \to \infty$. **(A2.2.)** means that the correlation between the noise and the probability of connection of two couples of random points vanishes quickly enough, as $n \to \infty$. However, this assumption is too strong for the Breiman's original random forest [Breiman, 2001]. Scornet et al. [2015] emphasize that they cannot know whether or not Assumption 2 is satisfied in random forest. In this paper, we recall this assumption and state that this assumption is mild for the second-layer forest estimation in deep forest algorithm.

Since deep forest concatenates the prediction with the raw features as the input for the next layer, the label information is encoded into the new feature of second layer. In this way, the influence of two labels on the connection probability of this pair of samples tends to zero, so **(A2.1.)** is mild for the second-layer forest estimation. From another point of view, Proposition 1, the priority of new feature also shows that the partition can be independent of labels, and the information of new feature is enough to obtain appropriate partition results, so **(A2.2.)** is mild too.

Theorem 4 (Depth is more powerful than width). *Let $M \geq 1$. Consider two-layer deep forest $\bar{h}_{2M,n}$ given by Eq. (6) and Breiman's random forest $h_{M,n}$ given by Eq. (4) for the random CARTs satisfying $a_n \to \infty, t_n \to \infty, t_n = a_n$ and $a_n \log n / n \to 0$. Then under the setting described in Section 3 and assume the data set follows Assumption 1 and 2, the following results hold*

1. *[Scornet et al., 2015, Theorem 2] [Scornet, 2016, Theorem 3] The Breiman's random forest $h_{\infty,n}$ is consistent, and for all $M, n \in \mathbb{N}$,*

$$0 \leq R(h_{2M,n}) - R(h_{\infty,n}) \leq \frac{8\|f\|_\infty^2 + 8\sigma^2(1 + 4\log n)}{M}. \tag{16}$$

2. *The two-layer deep forest $\bar{h}_{\infty,n}$ is consistent, and for all $M, n \in \mathbb{N}$, if $\Delta(f, C_{\Pi,n}(\boldsymbol{x}, \Theta))$ is small enough, then*

$$0 \leq R(\bar{h}_{2M,n}) - R(\bar{h}_{\infty,n}) \leq \frac{64\|f\|_\infty^2 + 64\sigma^2(1 + 4\log n)}{M^2}. \tag{17}$$

Proof sketch. **(T4.1).** The consistency of the infinite Breiman's random forest is proved by Scornet et al. [2015]. And the convergence rate of the finite random forest with the number of trees M is proved by Scornet [2016]. **(T4.2).** Similar as Scornet et al. [2015], we recall Proposition 2 to control the approximation error of the two-layer deep forest. Then the estimation error is controlled by forcing the subsampling rate a_n/n to be $o(1/\log n)$. Different from the bagging-style mechanism in random forest, the residual-style mechanism shown in Proposition 2 makes the second-layer forest in DF can reuse the first-layer estimation and focus on the residual learning. $\square$

Remark 3. In the $t_n = a_n$ setting, Scornet et al. [2015] show that the sub-sampling rate a_n/n is the key component in random forest. Because the small rate ensures that query point $\boldsymbol{x}$ is connected with enough different data points through different trees, the convergence rate of RF is $\mathcal{O}(1/M)$, *w.r.t.* the number of trees M. Theorem 4 proves that, if the first layer forest can encode the regression function $f(\boldsymbol{x})$ into the new feature with noise reduction, the cascade structure in DF can further accelerate the convergence. Because the second-layer forest estimates the residual of the first layer, the trees in each layer of forest are more different. As a result, the convergence rate of deep forest will be improved to $\mathcal{O}(1/M^2)$. This reflects that depth is more powerful than width.

7 Simulation experiments

7.1 Priority of the new feature

This experiment aims to verify the priority of the new feature in choosing which feature to split as suggested in Proposition 1. We focus on a second layer decision tree built upon the first layer random forest. Since a regression forest has only one output dimension, there's only one new feature for the second layer tree. More specifically, we count the maximum consecutive levels from root node that uses the new feature to split, which we call *effective depth* for short.

The synthetic data set is generated as $y = f(\boldsymbol{x}) + \epsilon$, where

$$f(\boldsymbol{x}) = \frac{1}{5} \sum_{1 \leq j \leq 5} x_j, \tag{18}$$

$\boldsymbol{x}$ is uniformly distributed over $[0,1]^5$, $\epsilon \sim \mathcal{N}(0, \sigma^2)$ where $\sigma = 0.02$. We vary the number of training samples and the number of trees in the first layer of forest, and report the average effective depth of 5 runs in Figure 2(a). It is easy to observe that no matter what the first layer's setting is, the effective depth of new feature is at least 2.4. That is to say, at the beginning of the growing of the second layer tree, CART will always choose the new feature to split. And we can see that with the increase of trees in the first layer and training samples, the CART's preference of new feature extend to deeper layers. Figure 2(b) further plots the effective depth against the predictive error of the first layer measured by root mean square error (RMSE), showing that the better the first layer's predictive performance, the more the new features are preferred in splitting.

(a) Heatmap of the effective depth of new feature under different settings of the first layer forest.

(b) Effective depth of new feature against the predictive error of the first layer.

Figure 2: Illustrations of the effective depth of the new feature (the consecutive levels from root node that split on the new feature only). The larger the effective depth, the higher priority the new feature takes in being chosen as the split feature under the CART-split criterion.

(a) Consistent trees ($t_n < a_n$).

(b) Inconsistent trees ($t_n = a_n$).

Figure 3: Root mean square error with the increasing of trees.

7.2 Convergence rate *w.r.t.* the number of trees

To study the convergence rate of predictive error with respect to the number of trees in the whole model, we fix the number of training samples to be 50,000. We compare a 2-layer deep forest (DF) with M trees each layer to a random forest (RF) with $2M$ trees, and we adopt 3-fold split in training both DF and RF to ensure fairness. The performance is measured by RMSE with respect to the noise-free version of data generating function. Since the training data are with noise, a fully grown tree is inconsistent. In Figure 3(a), we set the minimum leaf size of the trees to be $\sqrt{n}$, i.e., 233 in the case when training data size is 50,000. In Figure 3(b) the trees are fully grown with only one sample in each leaf. We plot the average RMSE of 5 runs against the increasing number of trees, with the colored band indicating the standard deviation. Theorem 3 reveals that when the component trees are consistent, random forest and deep forest are all consistent. However, the consistency analysis result cannot guarantee the finite sample performance in practice. Comparing Figure 3(a) and Figure 3(b), we can see that even though the training set is as large as 50,000, the performance of RF and DF using consistent trees is still much worse than using inconsistent trees. This observation confirms the efficacy of the default experimental setting of using fully grown trees in RF and DF. Figure 3(b) shows that DF enjoys a faster improvement in RMSE with the increasing of M. More specifically, DF with $M = 20$ outperforms RF with $M = 500$. This experimental result matches our theoretical analysis in Theorem 4 that DF has a faster convergence rate *w.r.t.* the number of trees M.

8 Conclusion

In this paper, we analysis DF with its individual trees using CART-split criterion, narrowing the gap between theoretical and empirical studies on DF. Theoretically, when the individual trees are consistent, the corresponding deep forest is universal consistent like RF, but practically, we often set the trees to be fully grown, which leads to successful applications of deep forests. We further analyze deep forest when the individual trees are inconsistent, and prove that a two-layer deep forest has a faster convergence rate *w.r.t.* the number of component trees M than random forest. Our theoretical and empirical results illustrate the effectiveness of the cascade forest structure in deep forest, showing that depth is more powerful than width.

References

Leo Breiman. Random forests. *Machine learning*, 45(1):5–32, 2001.

Zhi-Hua Zhou and Ji Feng. Deep forest. *National Science Review*, 6(1):74–86, 2019.

Jerome H. Friedman. Greedy function approximation: A gradient boosting machine. *The Annals of Statistics*, 29(5):1189–1232, 2001.

Pierre Geurts, Damien Ernst, and Louis Wehenkel. Extremely randomized trees. *Machine Learning*, 63(1):3–42, 2006.

Tianqi Chen and Carlos Guestrin. XGboost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 785–794, 2016.

Ran Su, Xinyi Liu, Leyi Wei, and Quan Zou. Deep-resp-forest: A deep forest model to predict anti-cancer drug response. *Methods*, 166:91–102, 2019.

Meng Zhou, Xianhua Zeng, and Aozhu Chen. Deep forest hashing for image retrieval. *Pattern Recognition*, 95:114–127, 2019.

Yaakoub Boualleg, Mohamed Farah, and Imed Riadh Farah. Remote sensing scene classification using convolutional features and deep forest classifier. *IEEE Geoscience and Remote Sensing Letters*, 16(12):1944–1948, 2019.

Ya-Lin Zhang, Jun Zhou, Wenhao Zheng, Ji Feng, Longfei Li, Ziqi Liu, Ming Li, Zhiqiang Zhang, Chaochao Chen, Xiaolong Li, Yuan (Alan) Qi, and Zhi-Hua Zhou. Distributed deep forest and its application to automatic detection of cash-out fraud. *ACM Transactions on Intelligent Systems and Technology*, 10(5):55:1–55:19, 2019.

Lev V. Utkin and Mikhail A. Ryabinin. A siamese deep forest. *Knowledge-Based Systems*, 139: 13–22, 2018.

Lev V. Utkin and Mikhail A. Ryabinin. Discriminative metric learning with deep forest. *International Journal on Artificial Intelligence Tools*, 28(2):1950007:1–1950007:19, 2019.

Liang Yang, Xi-Zhu Wu, Yuan Jiang, and Zhi-Hua Zhou. Multi-label learning with deep forest. In *Proceedings of the 24th European Conference on Artificial Intelligence*, volume 325, pages 1634–1641, 2020.

Qian-Wei Wang, Liang Yang, and Yu-Feng Li. Learning from weak-label data: A deep forest expedition. In *Proceedings of the 34th AAAI Conference on Artificial Intelligence*, volume 34, pages 6251–6258, 2020.

Ming Pang, Kai-Ming Ting, Peng Zhao, and Zhi-Hua Zhou. Improving deep forest by confidence screening. *IEEE Transactions on Knowledge and Data Engineering*, 2020. doi: 10.1109/TKDE. 2020.3038799.

Yi-He Chen, Shen-Huan Lyu, and Yuan Jiang. Improving deep forest by exploiting high-order interactions. In *IEEE International Conference on Data Mining*, pages 1030–1035, 2021.

Shen-Huan Lyu, Liang Yang, and Zhi-Hua Zhou. A refined margin distribution analysis for forest representation learning. In *Advances in Neural Information Processing Systems 32*, pages 5531–5541, 2019.

Ludovic Arnould, Claire Boyer, and Erwan Scornet. Analyzing the tree-layer structure of deep forests. In *Proccedings of the 37th International Conference on Machine Learning*, pages 342–350, 2021.

Shen-Huan Lyu, Yi-He Chen, and Zhi-Hua Zhou. A region-based analysis of deep forest. *arXiv preprint arXiv:2202.03688*, 2022.

Leo Breiman, Jerome Friedman, Charles J Stone, and Richard A Olshen. *Classification and Regression Trees*. CRC press, 1984.

Gérard Biau. Analysis of a random forests model. *The Journal of Machine Learning Research*, 13(1): 1063–1095, 2012.

Misha Denil, David Matheson, and Nando De Freitas. Narrowing the gap: Random forests in theory and in practice. In *Proccedings of the 30th International conference on machine learning*, pages 665–673, 2014.

Yi Lin and Yongho Jeon. Random forests and adaptive nearest neighbors. *Journal of the American Statistical Association*, 101(474):578–590, 2006.

Gérard Biau and Luc Devroye. On the layered nearest neighbour estimate, the bagged nearest neighbour estimate and the random forest method in regression and classification. *Journal of Multivariate Analysis*, 101(10):2499–2518, 2010.

Nicolai Meinshausen. Quantile regression forests. *Journal of Machine Learning Research*, 7:983–999, 2006.

Gérard Biau, Luc Devroye, and Gäbor Lugosi. Consistency of random forests and other averaging classifiers. *Journal of Machine Learning Research*, 9(9), 2008.

Hemant Ishwaran and Udaya B Kogalur. Consistency of random survival forests. *Statistics & probability letters*, 80(13-14):1056–1064, 2010.

Robin Genuer. Variance reduction in purely random forests. *Journal of Nonparametric Statistics*, 24 (3):543–562, 2012.

Ruoqing Zhu, Donglin Zeng, and Michael R Kosorok. Reinforcement learning trees. *Journal of the American Statistical Association*, 110(512):1770–1784, 2015.

Erwan Scornet, Gérard Biau, and Jean-Philippe Vert. Consistency of random forests. *The Annals of Statistics*, 43(4):1716–1741, 2015.

Erwan Scornet. On the asymptotics of random forests. *Journal of Multivariate Analysis*, 146:72–83, 2016.

Wei Gao and Zhi-Hua Zhou. Towards convergence rate analysis of random forests for classification. In *Advances in Neural Information Processing Systems 33*, pages 9300–9311, 2020.

Carolin Strobl, Anne-Laure Boulesteix, Achim Zeileis, and Torsten Hothorn. Bias in random forest variable importance measures: Illustrations, sources and a solution. *BMC Bioinformation*, 8, 2007.

Gilles Louppe, Louis Wehenkel, Antonio Sutera, and Pierre Geurts. Understanding variable importances in forests of randomized trees. In *Advances in Neural Information Processing Systems 26*, pages 431–439, 2013.

Ludovic Arnould, Claire Boyer, and Erwan Scornet. Is interpolation benign for random forests? *arXiv preprint arXiv:2202.03688*, 2022.

Xiao Li, Yu Wang, Sumanta Basu, Karl Kumbier, and Bin Yu. A debiased MDI feature importance measure for random forests. In *Advances in Neural Information Processing Systems 32*, pages 8047–8057, 2019.

Antonio Sutera, Gilles Louppe, Vân Anh Huynh-Thu, Louis Wehenkel, and Pierre Geurts. From global to local MDI variable importances for random forests and when they are shapley values. In *Advances in Neural Information Processing Systems 34*, pages 3533–3543, 2021.

Zhi-Hua Zhou and Ji Feng. Deep forest: Towards an alternative to deep neural networks. In *Proceedings of the 26th International Joint Conference on Artificial Intelligence*, pages 3553–3559, 2017.

Charles J Stone. Additive regression and other nonparametric models. *The annals of Statistics*, 13(2): 689–705, 1985.

Trevor Hastie and Robert Tibshirani. Generalized additive models: some applications. *Journal of the American Statistical Association*, 82(398):371–386, 1987.

Ronen Eldan and Ohad Shamir. The power of depth for feedforward neural networks. In *Proceedings of the 29th Conference on Learning Theory*, pages 907–940, 2016.

Matus Telgarsky. Benefits of depth in neural networks. In *Proceedings of the 29th Conference on Learning Theory*, pages 1517–1539, 2016.

Itay Safran and Ohad Shamir. Depth-width tradeoffs in approximating natural functions with neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, pages 2979–2987, 2017.

Eran Malach and Shai Shalev-Shwartz. Is deeper better only when shallow is good? In *Advances in Neural Information Processing Systems 32*, pages 6426–6435, 2019.

Amit Daniely and Eran Malach. Learning parities with neural networks. In *Advances in Neural Information Processing Systems 33*, 2020.

László Györfi, Michael Kohler, Adam Krzyzak, Harro Walk, et al. *A Distribution-Free Theory of Nonparametric Regression*, volume 1. Springer, 2002.

Pengfei Ma, Youxi Wu, Yan Li, Lei Guo, He Jiang, Xingquan Zhu, and Xindong Wu. Hw-forest: Deep forest with hashing screening and window screening. *ACM Trans. Knowl. Discov. Data*, 2022. doi: 10.1145/3532193.

Misha Denil, David Matheson, and Nando Freitas. Consistency of online random forests. In *Proccedings of the 31st International conference on machine learning*, pages 1256–1264, 2013.

Shai Shalev-Shwartz and Shai Ben-David. *Understanding Machine Learning: From Theory to Algorithms*. Cambridge university press, 2014.

Luc Devroye, László Györfi, and Gábor Lugosi. *A Probabilistic Theory of Pattern Recognition*, volume 31. Springer Science & Business Media, 2013.

Luc Devroye. A note on the height of binary search trees. *Journal of the ACM*, 33(3):489–498, 1986.

Sumanta Basu, Karl Kumbier, James B. Brown, and Bin Yu. Iterative random forests to discover predictive and stable high-order interactions. *Proceedings of the National Academy of Sciences*, 115(8):1943–1948, 2018.

Zhi-Hua Zhou. Why over-parameterization of deep neural networks does not overfit? *Science China Information Sciences*, 64(1):1–3, 2021.

Gérard Biau and Erwan Scornet. A random forest guided tour. *Test*, 25(2):197–227, 2016.