Federated Learning for Appearance-based Gaze Estimation in the Wild

Abstract

Gaze estimation methods have significantly matured in recent years but the large number of eye images required to train deep learning models poses significant privacy risks. In addition, the heterogeneous data distribution across different users can significantly hinder the training process. In this work, we propose the first federated learning approach for gaze estimation to preserve the privacy of gaze data. We further employ pseudo-gradients optimisation to adapt our federated learning approach to the divergent model updates to address the heterogeneous nature of in-the-wild gaze data in collaborative setups. We evaluate our approach on a real-world dataset (MPIIGaze dataset) and show that our work enhances the privacy guarantees of conventional appearance-based gaze estimation methods, handles the convergence issues of gaze estimators, and significantly outperforms vanilla federated learning by 15.8% (from a mean error of 10.63 degrees to 8.95 degrees). As such, our work paves the way to develop privacy-aware collaborative learning setups for gaze estimation while maintaining the model's performance.

1 Introduction

Human eye gaze is a crucial non-verbal cue used in a wide variety of applications, such as gaze-contingent rendering in virtual reality [1, 2, 3], gaze-based interaction [4, 5], gaze-assisted collaboration [6, 7], as well as eye movement-based task recognition [8, 9]. Given the importance of eye gaze, many researchers have focused on the problem of gaze estimation [10, 11, 12, 13], i.e. estimating gaze position or direction from eye images. However, the collection of large amounts of eye images required to train deep learning models or their exchange across networks can pose significant privacy risks. In addition, the heterogeneous data distribution across different users in real-world settings (in-the-wild settings) can significantly hinder the training process of gaze estimation methods [14]. Therefore, preserving privacy and maintaining high performance for heterogeneous data become two main challenges for gaze estimation.

To address these challenges, recent works have developed privacy-preserving approaches for gaze estimation. Nonetheless, they either only handle specific attacks and data vulnerabilities [15, 16, 17], or mainly focus on enhancing the data privacy on the sacrifice of model performance [18, 15, 19, 16].

In this work, we propose the first federated learning (FL) approach [20] for gaze estimation to preserve the privacy of gaze data. Federated learning is a machine learning paradigm that enables training algorithms across multiple local datasets without exchanging data samples to alleviate the data sharing privacy risks. In addition, we employ pseudo-gradients optimisation to adapt our federated learning approach to the divergent model updates caused by the heterogeneous gaze data distribution among users. We evaluate our approach on the MPIIGaze dataset [21] where the privacy-sensitive nature, as well as the heterogeneous distribution of in-the-wild gaze data, is prominent. Our experimental results show that our work enhances the privacy concerns of conventional gaze estimation approaches about

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

data sharing. It also reduces the model updates divergence in collaborative setups while significantly outperforming vanilla federated learning by 15.8% (from a mean error of 10.63 degrees to 8.95 degrees). Finally, we discuss our method's impact on users' privacy and data heterogeneity in terms of fairness and robustness.

In summary, the main contributions of our work are as follows:

- We propose the first federated learning approach for gaze estimation to preserve the privacy of gaze data.

- We employ pseudo-gradients optimisation to adapt our federated learning approach to the divergent model updates to handle the heterogeneous data distribution in collaborative setups.

- We show that our approach enhances the privacy guarantees of conventional methods, handles the convergence of gaze estimation models, and significantly outperforms vanilla federated learning.

2 Related Work

Gaze Estimation Methods Gaze estimation methods can be generally categorised as either model-based or appearance-based [21]. Model-based methods employ features detected from eye images to estimate gaze direction and can hardly obtain good performance in real-word settings because accurate eye feature detection relies on high-resolution images and homogeneous illumination [21]. In contrast, appearance-based approaches directly regress gaze direction from eye images [10, 11, 12, 13] and can handle low-resolution images and long distances. However, appearance-based methods require a larger number of training eye images than model-based approaches to cover the significant variability in eye appearance [21], which poses serious privacy risks since eye images contain ample personal information, such as gender [22], identity [23], and personality traits [24]. Moreover, the heterogeneous data distribution across different users in real-world settings, which is caused by many factors including the differences in gaze ranges, head pose, illumination conditions, and personal appearance [21], can significantly hinder the training process of appearance-based gaze estimation methods.

Recent works [18, 15, 17, 19, 16, 25] have developed privacy-preserving approaches for gaze estimation. These works mainly focus on differential privacy solutions where the model's performance is decreased through noise addition [18, 15, 19, 16], are dataset-dependent [15, 16], i.e. customising the added noise to the properties of the dataset, or solely reduce adversarial attacks [17]. In contrast, our work focused on developing a privacy-preserving gaze estimator that maintains high estimation performance.

Federated Learning Federated learning [20] is a machine learning setting where multiple decentralised edge devices (a.k.a. clients) or servers collaborate in solving a machine learning problem. Each client owns a local training dataset which is never exchanged nor transferred to the server; instead, focused updates intended for immediate aggregation are used to achieve the learning objective. These updates are ephemeral and cannot contain more information compared to the raw data according to the data processing inequality principle. In addition, focused collection and data minimisation principles [26] are applied.

FL architectures [27] can be categorised into centralised (a.k.a. client-server) or decentralised (a.k.a. peer-to-peer) training. FL can also be classified according to the type of clients. In cross-silo FL, participants are multiple organisations (e.g., medical, financial, or geo-distributed data centres) that train on siloed data while in cross-device FL, participants consist of a large number of mobile or IoT devices. FL can be further classified according to how data is partitioned among the clients in the feature and sample spaces. Horizontal FL applies to the scenario where the clients share overlapping data features but they differ in data samples, in contrast to vertical FL. In this work, we train our gaze estimator under a cross-device centralised horizontal federated learning setting.

The federated optimisation problem [28] is different from typical distributed optimisation problems in terms of data heterogeneity, formally the non-Independent and Identical Distribution (non-IID) of the data among clients, the unbalance of the size of the local training sets, the limited and expensive communication, the computing capabilities, and clients' availability. To effectively address these heterogeneity challenges, multi-model FL approaches were introduced [29, 27]. Multi-model learning approaches in FL can be summarised into multi-task learning [30] (i.e. considering each client's local

problem as an independent task), local fine-tuning [27] (performing local training steps locally on the final model), and meta-learning [31, 32, 33] (exploiting the metadata) solutions. Furthermore, solving local updates as pseudo-gradients was first proposed for speech tasks [34], while adaptive learning was introduced in [35] with the goal of incorporating knowledge from previous iterations for better-informed optimisation. In consequence, Reddi et al. [35] proposed FedOpt and showed that as the nature of federated learning allows optimising the model on two levels, the user and server sides. In our work, we mainly focus on FedOpt, as, unlike multi-task learning, it does not require stateful updates which makes it suitable for cross-device setups. It also empirically outperforms meta-learning approaches [36], and can be fine-tuned. Overall, FL holds the promise of increasing usability by training gaze estimation models on large and diverse datasets at different participants while preserving data privacy.

3   Methodology

In this work, we propose a federated learning approach for gaze estimation that allows model training to adapt to the divergence of participants' heterogeneous data while enhancing users' privacy.

3.1   Gaze Data Distribution

Previous works show that gaze estimation error is significantly affected by many factors including glasses due to the caused distortions, reflections, and thick frames, illumination conditions between indoor and outdoor environments, personal appearance change during the long-term recording, differ-ent times of the day, a varying amount of data samples per user, gender, race and age differences [21]. Earlier works [37, 14, 38, 39, 21] tried to overcome these challenges by improving user-specific and user-independent metrics However, they rarely consider the associated privacy risks of data-sharing and only offer one global dataset-specific model for all participants.

Formally, for a better understanding of data heterogeneity, gaze estimation represents a supervised task with features x and labels y. The dataset contains N participants with their respective datasets $\{D_i\}_{i=1}^N$. Each participant i is sampled from the distribution Q over all available participants. Then, a data sample (x, y) is sampled from the participant's local data distribution $P_i(x, y)$.

The differences between the data distribution $P_i(x, y)$ and $P_j(x, y)$ for different participants i and j is referred to as non-IID. The joined probability $P_i(x, y)$ can be formulated as $P_i(y \mid x)P_i(x)$ or $P_i(x \mid y)P_i(y)$. Hence, decoupling this joint distribution allows defining the distribution skews as:

1. **Non-identical distribution**

   - **Feature distribution skew (covariate shift):** The marginal distributions $P_i(x)$ differs across participants, even if $P_i(y \mid x) = P_j(y \mid x)$ for all participants i and j. In other words, each participant stores features that have different statistical distributions compared to other participants (e.g. different lightning conditions and personal appearance).
   - **Label distribution skew (prior probability shift):** The marginal distributions $P_i(y)$ differ across participants, even if $P_i(y \mid x) = P_j(y \mid x)$ for all participants i and j. Each participant owns labels that have different statistical distributions compared to other participants (e.g. some gaze targets are more frequent than others).
   - **Same label, different features (concept shift):** The conditional distributions $P_i(x \mid y)$ differ across participants, even if $P_i(y) = P_j(y)$ for all participants i and j. This means that different participants may have the same labels corresponding to different features at each participant (e.g. the same gaze target location can be mapped to different data samples).
   - **Same features, different label (concept shift):** The conditional distributions $P_i(y \mid x)$ may differ across participants, even if $P_i(y) = P_j(y)$ for all participants i and j. This means that different participants may have the same features corresponding to different labels at each participant (e.g. the data is collected from different laptops with different cameras and screen sizes).

2. **Violation of independence** Violations of independence can appear whenever the distribution Q varies during the data collection or its simulation during the training process. In practice, devices should typically satisfy eligibility requirements (e.g., devices should be idle, connected to an un-metered wi-fi connection, charged, and at night local time) in order to participate in the training

process. Hence, patterns in device availability and local timing introduce strong bias in the data source. In the used datasets, the different screen times and the number of days used for data collection significantly differ across participants.

3. **Quantity unbalance** Different participants hold significantly different dataset sizes due to the heavier use of devices.

Therefore, since the heterogeneity of data distribution is prominent in gaze estimation tasks, we take into consideration the above challenges to improve the gaze estimator performance across participants in collaborative setups.

3.2 Gaze Estimation Model

Based on Zhang et al. [14], a multi-modal convolutional neural network (CNN) is implemented for gaze estimation. The CNN regresses the pre-processed dataset input $x = (e, h)$, where e and h denote the 60x36 eye image and 1x2 head angle, respectively, to the gaze angles $\hat{g}$ in the normalised space. The final output g consists of the yaw $\hat{g}_\phi$ and pitch $\hat{g}_\theta$ angles. The loss function between the predicted $\hat{g}$ and ground-truth g angle vectors is calculated by the sum of the individual $L1$ losses.

In this paper, we mainly focus on the CNN optimiser that minimises the loss function and updates the model parameters θ. For CNN training, stochastic gradient descent (SGD) is used with a learning rate η of 10^{-5}. A momentum term γ of 0.9 is added to stabilize the optimization, speed convergence, and reduce oscillations. Finally, a Nesterov accelerated gradient (NAG) is added for a better anticipatory gradient update, as shown in Equation 1.

$$\theta = \theta - v_t \quad : \quad v_t = \gamma v_{t-1} + \eta \nabla_\theta J(\theta - \gamma v_{t-1}) \tag{1}$$

3.3 Federated Learning

Federated learning [20] is an approach to train deep learning models on large and diverse datasets while preserving participants' privacy. We specifically study a cross-device centralised, horizontal FL setup. This setup is characterised by the fact that the data distribution is massively parallel and can include a large number of devices. It also builds on a client-server architecture since a central server is needed to orchestrate the exchange and aggregation of model updates. Finally, the setup is horizontal as participants share overlapping data features as they all train on similar modalities and they differ in data samples with every participant having his/her own data. Formally, $X_{p_i} = X_{p_j}, Y_{p_i} = Y_{p_j}, I_{p_i} \neq I_{p_j}, \forall D_{p_i}, D_{p_j}, p_i \neq p_j$ where X denotes the data feature space, Y denotes the label space, and D denotes the dataset. Both spaces pair (X_{p_i}, Y_{p_i}) and (X_{p_j}, Y_{p_j}) are assumed to be the same, whereas the user identifiers I_{p_i} and I_{p_j} are assumed to be different.

During model training, as shown in Figure 1, each participant p_i in a set of participants trains a model without exchanging their local data. The server initialises the model's hyper-parameters, weights, and biases along with the number of communication rounds and local epochs. Thus, at each communication round t, the server selects a random cohort of participants C for the training. In this work, $C = 0.8$ to reduce the communication traffic and to mitigate the straggler effect introduced by the computational heterogeneity of the participants. The central server sends the current model parameters to the selected participants. Each selected participant samples a batch of samples D_i^t from its local dataset D_i. The batch size is denoted by $|D_i^t|$. To train the local gaze estimation model, we minimize the non-convex objective function f_i:

$$\min_{w \in R^d} f(w) = \frac{1}{N} \sum_{i=1}^{N} f_i(w) \tag{2}$$

In the supervised learning setting, f_i is the expected loss over the data distribution of participants N: $f_i(w) = E_{(x,y) \sim P_i}[l_i(w; x, y)]$ where $l_i(w; x, y)$ denotes the error of model w in predicting the true gaze target $y \in Y_i$ given the input $x \in X_i$, and P_i is the distribution over $X_i \times Y_i$ (the set of indexes of data samples in D_i) with $n_i = |P_i|$.

Since the data is non-IID, P_i represents the empirical distribution of the participant's data samples. Therefore, $f_i(w) = \sum_{(x,y) \in D_i} P_i(x, y) l_i(w; x, y)$ where $P_i(x, y)$ is the probability that participant

Figure 1: Cross-device centralised horizontal FL

185 i selects a particular sample (x, y). Therefore, we can rewrite Equation 2 as: $\min_{w \in R^d} f(w) =$
186 $\frac{1}{N} \sum_{i=1}^{N} \frac{n_i}{N} F_i(w)$ where, $F_i(w) = \frac{1}{n_i} \sum_{i=1}^{n_i} f_i(w)$.

187 Each participant trains a model using their respective data and sends the model weight updates to the
188 central server. The server then combines the model updates received from all participants, typically
189 by computing the average (a.k.a. FedAvg [20]) and sends the aggregated model updates back to the
190 participants. This cycle is repeated until the maximum number of rounds is reached. Furthermore,
191 conventional FL optimisation techniques (e.g. SGD) often require high communication costs. As a
192 solution, multiple local client updates are used [20].

193 Nonetheless, due to the non-IID distribution, participants tend to drift towards the minima of the
194 local objective functions and, consequently, model updates become significantly different across
195 participants hindering model convergence. In addition, previous works [40, 41] have shown that there
196 exists an error term that monotonically increases with each local step and exacerbates with non-IID
197 data. This error can be negligible when the learning rate decays. As learning rate decay (lr-decay)
198 skips spurious local minima by starting from an initial large learning rate, it benefits convergence
199 by avoiding oscillation with the decayed learning rates. Thus, an lr-decay of 0.1 was added to our
200 scheduler.

3.4 Adaptive Federated Learning for Gaze Estimation

202 Due to the heterogeneity of in-the-wild gaze data, training a single global model across users is known
203 to result in lower performance due to having different local updates across participants. Therefore,
204 simply averaging the updates (i.e. FedAvg [20]) leads to increasing the error rate even with learning
205 rates or lr-decay. Alternatively, the expectation of the aggregated local updates should follow the
206 global objective.

207 In this work, for each communication round t, the model is optimised on two levels. While the
208 participant optimiser aims to minimise Equation 2 according to the local data of each participant, the
209 server optimiser aims to optimise it globally on the aggregated model. In other words, the participant's
210 updates are treated as pseudo-gradients to aggregate the model at the server side while adapting to the
211 heterogeneous local updates resulting from the heterogeneous distribution by incorporating knowledge
212 from previous iterations for better-informed optimisation, as shown in algorithm 1 (lines 18-23).
213 Specifically, the server gathers the local differences ∇_i^t, averages them into the pseudo-gradient ∇_t,
214 and updates the aggregated model using the Adam optimiser.

215 Although adaptive optimisation methods (e.g. Adam [42, 43]) have proven their effectiveness in
216 training deep neural networks, improving the performance of SGD, and guaranteeing convergence,
217 especially for gaze estimation tasks [37, 39, 21], SGD maintains the same computation and communi-
218 cation costs on the participant side and does not depend on the participant sampling ratio. Here, the

participant and server optimisers are SGD and Adam, respectively. This combination of optimisers has been proven to be effective both theoretically and empirically [28].

Additionally, for robustness, we investigate the performance of our approach against more heterogeneous setups (e.g. poisoning attacks, outliers...). As a simulation, Gaussian noise was added with a standard deviation of 0.5 to the participants' training data, according to Mills et al. [36].

Algorithm 1 Adaptive FL Algorithm

1: **The central server:**
2: Initialises model parameters w_0 and broadcasts them to all participants.

3: **for** each global model update round $t = 1, 2, ..., T$ **do**
4:     The server determines C_t, which is the set of randomly selected participants.
5:     **for** each participant $i \in C_t$ **in parallel do**
6:         Obtain the latest model parameters from the server, i.e., set $w_i^{t,0} = w_t$
7:         **for** each local epoch $e = 1, 2, ..., E$ **do**
8:             batches $\leftarrow$ randomly divides dataset D_i into batches of size M.
9:             Obtain the local model parameters from last epoch, i.e., set $w_i^{t,e} = w_i^{B,e-1}$
10:             **for** batch index $b = 1, 2, ..., B = \frac{n_i}{M}$ **do**
11:                 Computes the batch gradient g_i^b using the participant optimizer in 1.
12:                 Updates model parameters locally: $w_i^{b+1,e} \leftarrow w_i^{b,e} - \mu g_i^b$.
13:             **end for**
14:         **end for**
15:         Sends the updated model $\nabla_i^t = w_{i,E}^t - w_t$ to the central server.
16:     **end for**

17:     **Server optimiser:**
18:     The central server aggregates the received model weights
19:     $\nabla_t = \frac{1}{|C|} \sum_{i \in C} \nabla_i^t$
20:     The central server optimizes the model with its learning rate β
21:     $a_t = \beta a_{t-1} + (1 - \beta)\nabla_t$
22:     $v_t = \beta v_{t-1} + (1 - \beta)\nabla_t^2$ (Adam)
23:     $w_{t+1} = w_t + \eta \frac{a_t}{\sqrt{v_t} + \tau}$ where τ is the degree of adaptivity

24:     The central server checks if the maximum number of rounds is reached to break.
25:     The central server broadcasts the aggregated model parameters to all the participants.
26: **end for**

---

4   Results

As the participants' population can rapidly evolve in gaze estimation applications, non-IID distribution shifts arise and in-the-wild gaze challenges intensify. Thus, for a better understanding of the model robustness and the heterogeneous updates across participants, we first evaluate our approach and the baselines under person-specific and person-independent evaluation schemes. The former holds out a fraction of the data at each participant for validation to ensure that the validation set is representative and to measure the local performance while the latter leaves one participant out of the training set for evaluation of the global model generalisation capability. We perform our evaluations on the MPIIGaze dataset [21] in terms of the mean angle error, i.e. the difference between the predicted gaze angles and the dataset ground truth.

Dataset   The MPIIGaze dataset contains 15 participants with 213,659 annotated data samples collected over 9 days to 3 months with varying head poses, gaze targets, and illumination conditions. The number of images collected by each participant varies between 1,498 and 34,745. Consequently, the dataset was chosen due to its daily real-life representation of different users, environments, and cameras, emphasising the heterogeneous in-the-wild data distribution among different participants.

Baselines We compare our method against three baselines: An individual learning, a data centre learning scheme, and a conventional federated learning approach.

- **Individual Learning:** Each participant p_i trains the model locally on their local dataset D_i. The data is neither shared with other participants nor a central server. However, the model is only exposed to a relatively small amount of samples which, consequently, yields a poor generalisation performance on out-of-the-training-set samples, lacks robustness and, therefore cannot be deployed to other participants due to the non-IID data distribution.

- **Data centre Learning:** Since the availability of a large number of training samples is a stepping stone for model training, data centre learning collects data samples from all participants and trains the model on one central dataset. Therefore, the model robustness increases but participants' data is shared with the central server and privacy leakage risks arise.

- **Federated Average (FedAvg):** we compare our approach with the conventional federated learning setting, FedAvg, where the server aggregates the model updates by simply averaging them.

Person-Independent Performance For individual learning, the results in Figure 2 show that the gaze estimator yields a poor generalisation performance on out-of-the-training-set samples (person-independent), lacks robustness and, therefore cannot be deployed to other participants due to the non-IID data distribution. For data centre learning, despite the increase in the model robustness shown in Figure 3, participants' data is shared with the central server and privacy leakage risks arise. Finally, for federated learning, we employ the same number of communication rounds and computations to our adaptive framework and vanilla FL (FedAvg) for a fair comparison. Instead of performing a number of steps in FedAvg, we perform a fixed number of epochs for each participant to accommodate the data unbalance of the local datasets and avoid training on the same data sample repeatedly. Figure 3 shows that, in FedAvg, convergence issues occur. As shown in Figure 3 and Figure 4, in user-independent setups, our adaptive FL approach outperforms FedAvg 15.8% (from a mean error of 10.63 degrees to 8.95 degrees) and achieves convergence while maintaining the same communication cost as FedAvg. It also outperforms individual training (from a mean error of 9.10 degrees to 8.95 degrees) and can potentially improve with more participants in practical setups. Finally, the performance gap between our approach and the data centre training comes at the cost of privacy and scale (section 5) and can potentially be bridged in practice with more participants and training rounds over time.

Person-Specific Performance The local model performance is essential for the adaptivity of the gaze estimator to the divergent model updates, as well as fairness by correcting the unintended behaviors exhibited by the gaze estimator in heterogeneous collaborative setups.

In the FL literature, fairness is measured by the minimum performance metric across all clients. As shown in Figure 3, FedAvg resulted in a mean angle error of 9.3 degrees and 12.2 degrees for the minimum and maximum participant performance, respectively, while our approach resulted in 7.5 degrees and 10.2 degrees.

Robustness Due to the open nature of FL and the involvement of a large number of participants, the training process can be vulnerable to failures (e.g. distribution shifts and data poisoning). As distinguishing heterogeneous distributions from poisoning attacks can be challenging, we test our model on noisy participants to check the model's robustness, i.e. the ability of the gaze estimator to function correctly in the presence of such problems. Results, in Figure 4, show that the model is robust to $\geq 70\%$ of noisy participants and it is important to mention that the effective rate of malicious activity or outliers can be extremely small in cross-device settings, where thousands of participants are involved [28].

5 Discussion

Our work paves the way to develop privacy-preserving collaborative learning setups for gaze estimation while maintaining the utility of the model. FL extends prior non-federated gaze estimation directions along with other unique approaches to address privacy, fairness, and robustness.

Figure 2: Person-specific (diagonal) and person-independent mean angle error for individual training

Figure 3: Mean angle error for person-specific evaluation for each participant (left) and the average person-independent evaluation (right)

Privacy of Gaze Data   Our FL approach is able to enhance data privacy via data minimisation. It focuses on reducing the attack surface on gaze data by sending the model minimal focused updates needed for the gaze estimation task instead of the raw data while maintaining a better model performance than FedAvg. It also yields a minor loss performance to the non-private data centre training since the model is no longer directly trained on the entire dataset but instead, the individual model updates are combined by the aggregation function, as shown in Figure 3.

In addition, our work presents a privacy-preserving solution that does not interfere with the user experience as it requires the same computation and communication costs as FedAvg on the user side.

Gaze Data Heterogeneity   Deep learning models for gaze estimation often exhibit unintended behaviours that lead to undesirable performance due to human, environmental, and device differences resulting in data heterogeneity. Fairness concerns about gaze estimation models can be exacerbated in FL settings due to data heterogeneity. We evaluated the adaptivity of our work under person-specific, person-independent, and fairness metrics. Our results show that our approach indeed adapts the model updates to the participants' data distribution resulting in better performance, as shown in Figure 3. In this paper, we investigated the model robustness against random noise, as shown in Figure 4. Nonetheless, attacks on gaze estimation models can be further studied.

Limitations and Future Work   Apart from the privacy guarantees presented in this paper, a limitation of our work reside in the fact that FL does not provide formal privacy guarantees. Thus, a direction for further research can be to combine FL with formal privacy technologies (e.g. differential privacy and secure aggregation [44]). In addition, as we introduce additional communication through

Figure 4: The training and test losses and mean angular errors for FedAvg (first row), our approach (second row), and robustness to noisy participants (third row)

FL in comparison to conventional gaze estimation approaches, allowing participants to join the federation when they are idle (i.e., charged and connected to Wi-Fi, or during local nighttime) can potentially enhance the user experience in practical settings. In addition, applying these techniques for high-dimensional and large-scale gaze estimation applications under in-the-wild non-IID distributions and developing better evaluation metrics that cover both the user-specific and user-independent performance for federated learning local and global models remain open research directions.

Lastly, finding the right balance between fairness, robustness, and privacy is a challenging task. While fairness ensures that the model performs well for participants with different data distributions, robustness ensures that the outliers do not affect the model performance, and privacy ensures that the model does not retain information about outlier participants' data. However, adaptive learning and personalisation techniques are believed to balance this interplay [45, 46].

6   Conclusion

In this paper, we presented a federated learning approach for gaze estimation that allows model training to adapt to the divergence of participants' heterogeneous data while alleviating privacy concerns of data sharing. To the best of our knowledge, this is the first work that integrates federated learning with gaze estimation tasks. We showed that our approach enhances the privacy guarantees of conventional methods, handles the convergence of gaze estimators, and significantly outperforms the performance of vanilla federated learning. We believe that our work paves the way to develop privacy-preserving collaborative learning setups for gaze estimation tasks while maintaining a good model performance.

References

[1]   Zhiming Hu et al. "SGaze: a data-driven eye-head coordination model for realtime gaze prediction". In: *IEEE Transactions on Visualization and Computer Graphics* 25.5 (2019), pp. 2002–2010.

[2] Zhiming Hu et al. "DGaze: CNN-based gaze prediction in dynamic scenes". In: *IEEE Transactions on Visualization and Computer Graphics* 26.5 (2020), pp. 1902–1911.

[3] Zhiming Hu et al. "FixationNet: forecasting eye fixations in task-oriented virtual environments". In: *IEEE Transactions on Visualization and Computer Graphics* 27.5 (2021), pp. 2681–2690.

[4] Diako Mardanbegi et al. "EyeSeeThrough: unifying tool selection and application in virtual environments". In: *Proceedings of the 2019 IEEE Conference on Virtual Reality and 3D User Interfaces*. 2019, pp. 474–483.

[5] Thammathip Piumsomboon et al. "Exploring natural eye-gaze-based interaction for immersive virtual reality". In: *Proceedings of the 2017 IEEE Symposium on 3D User Interfaces*. IEEE. 2017, pp. 36–39.

[6] Keita Higuch, Ryo Yonetani, and Yoichi Sato. "Can eye help you? Effects of visualizing eye fixations on remote collaboration scenarios for physical tasks". In: *Proceedings of the 2016 CHI Conference on Human Factors in Computing Systems*. 2016, pp. 5180–5190.

[7] Yanxia Zhang et al. "Look together: using gaze for assisting co-located collaborative search". In: *Personal and Ubiquitous Computing* 21.1 (2017), pp. 173–186.

[8] Zhiming Hu et al. "EHTask: recognizing user tasks from eye and head movements in immersive virtual reality". In: *IEEE Transactions on Visualization and Computer Graphics* (2022).

[9] Antoine Coutrot, Janet H Hsiao, and Antoni B Chan. "Scanpath modeling and classification with hidden Markov models". In: *Behavior Research Methods* 50.1 (2018), pp. 362–379.

[10] Shumeet Baluja and Dean Pomerleau. "Non-intrusive gaze tracking using artificial neural networks". In: *Advances in Neural Information Processing Systems* 6 (1993).

[11] Ke Liang et al. "Appearance-based gaze tracking with spectral clustering and semi-supervised gaussian process regression". In: *Proceedings of the 2013 Conference on Eye Tracking South Africa*. 2013, pp. 17–23.

[12] Jinsoo Choi et al. "Appearance-based gaze estimation using kinect". In: *2013 10th International Conference on Ubiquitous Robots and Ambient Intelligence*. IEEE. 2013, pp. 260–261.

[13] Feng Lu et al. "Learning gaze biases with head motion for head pose-free gaze estimation". In: *Image and Vision Computing* 32.3 (2014), pp. 169–179.

[14] Xucong Zhang et al. "Appearance-based gaze estimation in the wild". In: *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*. 2015, pp. 4511–4520.

[15] Efe Bozkir et al. "Differential privacy for eye tracking with temporal correlations". In: *Plos one* 16.8 (2021), e0255979.

[16] Julian Steil et al. "Privacy-aware eye tracking using differential privacy". In: *ACM Symposium on Eye Tracking Research & Applications*. 2019, pp. 1–9.

[17] Inken Hagestedt, Michael Backes, and Andreas Bulling. "Adversarial attacks on classifiers for eye-based user modelling". In: *ACM Symposium on Eye Tracking Research and Applications*. 2020, pp. 1–3.

[18] Jingjie Li et al. "{Kalεido}:{Real-Time} Privacy Control for {Eye-Tracking} Systems". In: *30th USENIX Security Symposium*. 2021, pp. 1793–1810.

[19] Ao Liu et al. "Differential privacy for eye-tracking data". In: *ACM Symposium on Eye Tracking Research & Applications*. 2019, pp. 1–10.

[20] Brendan McMahan et al. "Communication-efficient learning of deep networks from decentralized data". In: *Artificial intelligence and statistics*. PMLR. 2017, pp. 1273–1282.

[21] Xucong Zhang et al. "Mpiigaze: Real-world dataset and deep appearance-based gaze estimation". In: *IEEE transactions on Pattern Analysis and Machine Intelligence* 41.1 (2017), pp. 162–175.

[22] Negar Sammaknejad et al. "Gender classification based on eye movements: A processing effect during passive face viewing". In: *Advances in Cognitive Psychology* 13.3 (2017), p. 232.

[23] Virginio Cantoni et al. "GANT: Gaze analysis technique for human identification". In: *Pattern Recognition* 48.4 (2015), pp. 1027–1038.

[24] Sabrina Hoppe et al. "Eye movements during everyday behavior predict personality traits". In: *Frontiers in Human Neuroscience* (2018), p. 105.

[25] Mingjie Xu et al. "Vulnerability of Appearance-based Gaze Estimation". In: *arXiv preprint arXiv:2103.13134* (2021).

[26] *White house report. consumer data privacy in a networked world: A framework for protecting privacy and promoting innovation in the global digital economy*. 2012.

[27] Peter Kairouz et al. "Advances and open problems in federated learning". In: *Foundations and Trends® in Machine Learning* 14.1–2 (2021), pp. 1–210.

[28] Jianyu Wang et al. "A field guide to federated optimization". In: *arXiv preprint arXiv:2107.06917* (2021).

[29] Viraj Kulkarni, Milind Kulkarni, and Aniruddha Pant. "Survey of personalization techniques for federated learning". In: *ArXiv Preprint* (2020).

[30] Yu Zhang and Qiang Yang. "A survey on multi-task learning". In: *CoRR* abs/1707.08114 (2017).

[31] Jonathan Baxter. "A model of inductive bias learning". In: *Journal of Artificial Intelligence Research* (2000), pp. 149–198.

[32] Alireza Fallah, Aryan Mokhtari, and Asuman Ozdaglar. "Personalized federated learning: a meta-learning approach". In: *arXiv preprint arXiv:2002.07948* (2020).

[33] Canh T Dinh, Nguyen Tran, and Josh Nguyen. "Personalized federated learning with moreau envelopes". In: *Advances in Neural Information Processing Systems* 33 (2020), pp. 21394–21405.

[34] Kai Chen and Qiang Huo. "Scalable training of deep learning machines by incremental block training with intra-block parallel optimization and blockwise model-update filtering". In: *IEEE International Conference on Acoustics, Speech and Signal Processing*. IEEE. 2016, pp. 5880–5884.

[35] Sashank Reddi et al. "Adaptive federated optimization". In: *arXiv preprint arXiv:2003.00295* (2020).

[36] Jed Mills, Jia Hu, and Geyong Min. "Multi-task federated learning for personalised deep neural networks in edge computing". In: *IEEE Transactions on Parallel and Distributed Systems* 33.3 (2021), pp. 630–641.

[37] Dan Witzner Hansen and Qiang Ji. "In the eye of the beholder: A survey of models for eyes and gaze". In: *IEEE transactions on pattern analysis and machine intelligence* 32.3 (2009), pp. 478–500.

[38] Kenneth Alberto Funes Mora and Jean-Marc Odobez. "Person independent 3d gaze estimation from remote rgb-d cameras". In: *2013 IEEE International Conference on Image Processing*. IEEE. 2013, pp. 2787–2791.

[39] Xucong Zhang et al. "It's written all over your face: Full-face appearance-based gaze estimation". In: *IEEE Conference on Computer Vision and Pattern Recognition workshops*. 2017, pp. 51–60.

[40] Sebastian U Stich. "Local SGD converges fast and communicates little". In: *arXiv preprint arXiv:1805.09767* (2018).

[41] Jianyu Wang and Gauri Joshi. "Cooperative SGD: a unified framework for the design and analysis of communication-efficient SGD algorithms". In: *arXiv preprint arXiv:1808.07576* (2018).

[42] Diederik P Kingma and Jimmy Ba. "Adam: A method for stochastic optimization". In: *arXiv preprint arXiv:1412.6980* (2014).

[43] Manzil Zaheer et al. "Adaptive methods for nonconvex optimization". In: *Advances in Neural Information Processing Systems* 31 (2018).

[44] Keith Bonawitz et al. "Practical secure aggregation for privacy-preserving machine learning". In: *ACM SIGSAC Conference on Computer and Communications Security*. 2017, pp. 1175–1191.

[45] Yihan Jiang et al. "Improving federated learning personalization via model agnostic meta learning". In: *arXiv preprint arXiv:1909.12488* (2019).

[46] Kangkang Wang et al. "Federated evaluation of on-device personalization". In: *arXiv preprint arXiv:1910.10252* (2019).