Federated Hypergradient Descent

Abstract

In this work, we explore combining automatic hyperparameter tuning and opti-
mization for federated learning (FL) in an online, one-shot procedure. We apply
a principled approach on a method for adaptive client learning rate, number of
local steps, and batch size. In our federated learning applications, our primary
motivations are minimizing communication budget as well as local computational
resources in the training pipeline. Conventionally, hyperparameter tuning meth-
ods involve at least some degree of trial-and-error, which is known to be sample
inefficient. In order to address our motivations, we propose FATHOM (Feder-
ated AuTomatic Hyperparameter OptiMization) as a one-shot online procedure.
We investigate the challenges and solutions of deriving analytical gradients with
respect to the hyperparameters of interest. Our approach is inspired by the fact
that all components involved in our training process are open-boxed, and this
fact can be exploited in our algorithm impactfully. We show that FATHOM is
more communication efficient than Federated Averaging (FedAvg) with optimized,
static valued hyperparameters, and is also more computationally efficient overall.
As a communication efficient, one-shot online procedure, FATHOM solves the
bottleneck of costly communication and limited local computation, by eliminat-
ing a potentially wasteful tuning process, and by optimizing the hyperparamters
adaptively throughout the training procedure without trial-and-error. We show
our numerical results through extensive empirical experiments with the Federated
EMNIST-62 (FEMNIST) and Federated Stack Overflow (FSO) datasets, using
FedJAX as our baseline framework.

1 Introduction

Federated learning (FL) for on-device applications has its obvious social implications, due to its
inherent privacy-protection feature. It opens up a broad range of opportunities to allow a massive
number of devices to collaborate in developing a shared model by retaining private data on the
devices. The ubiquity of machine learning (ML) on consumer data, coupled with the growth of
privacy concerns, has pushed researchers and developers to look for new ways to protect and benefit
end-users. In order for FL to deliver its promise in deployed applications, there are still many open
challenges remained to be solved. We are especially interested in the overall communication efficiency
of the FL pipeline for it to be realistically deployed in a unique communication environment over
expensive links. To begin, consider a typical step in a machine learning (ML) pipeline: hyperparameter
tuning. Whether it is in a centralized, distributed or federated setting, it is an essential step to achieve
an optimal operation for the training process. At the heart of a ML training process is the optimization
algorithm. In particular, we are interested in using Federated Averaging (FedAvg) as our baseline

federated optimization algorithm for our work. This is because, despite all the recent innovations in FL since its introduction in 2016 by McMahan et al. [2016], FedAvg remains the de facto standard in federated optimization for both research and for practice, due to its simplicity and empirical effectiveness. In order for FedAvg to operate effectively, it requires properly tuned hyperparameter values.

Our work focuses specifically on hyperparameter optimization of: 1) client learning rate, 2) number of local steps, as well as 3) batch size, for FedAvg. We propose FATHOM (Federated AuTomatic Hyperparameter OptiMization), which is an online algorithm that operates as a one-shot procedure. Conventionally, in offline tuning, hyperparameter tuning is de-coupled from model training. When hyperparameter tuning is done in an online-manner, the two steps are combined and done in a single procedure. FATHOM is an online method, and when integrated with FedAvg, it minimizes the loss function by applying gradients with respect to both the parameters and the hyperparameters in every communication round. A performance gain from FATHOM in comparison to FedAvg with already optimally tuned, static hyperparameters, is a step closer to eliminating the tuning step. However, we need to determine if the procedure makes any undesirable trade-off for the gain in communication efficiency. As an example, from worst case bounds in Wang et al. [2021], Gorbunov et al. [2020] and Woodworth et al. [2020], FedAvg can reach optimal ($\mathcal{O}(T^{-1/3})$) asymptotic performance when the number of local steps is sufficiently large, where the price may be increased local computation, which is not always a desirable trade-off. We will explore how FATHOM can address the above concerns. These benefits are shown empirically in our numerical results in our FEMNIST and FSO experiments, justify its utility in a FL pipeline over any offline approach involving static valued FedAvg, such as the ones used in Holly et al. [2021].

In the rest of this paper, we will go through a few notable recent state-of-the-art works on this topic, and make justifications for our new approach. Then we will derive a few key steps for our algorithm, followed by a theoretical convergence bound for adaptive learning rate and number of local steps in the non-convex regime. Lastly, we present numerical results on our empirical experiments with neural networks on the FEMNIST and FSO datasets.

Our contributions are as follows:

- We derive gradients with respect to client learning rate and number of local steps for FedAvg, for an online optimization procedure. We propose FATHOM, a practical one-shot procedure for joint-optimization of hyperparameters and model parameters, for the federated learning setting.

- We derive a new convergence upper-bound with a relaxed condition, to highlight the benefits from the extra degree-of-freedom that FATHOM delivers for performance gains.

- We present empirical results that show state-of-the-art performance. To our knowledge, we are the first to show gain from an online hyperparameter optimization procedure over a well-tuned equivalent procedure with fixed hyperparameter values.

2   Related Work and Justifications for FATHOM

We explore the question whether the FATHOM approach is justified over the more recent, state-of-the-art methods that are designed for the same goal: a single-shot online hyperparamter optimization procedure for FL, but approached from different principles. A few notable works have produced methods belonging in this category of algorithms. Khodak et al. [2021] draws inspiration from weight-sharing in Neural Architectural Search (Pham et al. [2018], Cai et al. [2019]), and proposed FedEx, which is an online hyperparameter tuning algorithm that uses exponentiated gradients to update hyperparameters. On the other hand, Mostafa [2019]'s RMAH and Guo et al. [2022]'s Auto-FedRL both use REINFORCE (Williams [1992]) in their reinforcement learning (RL) agents to update hyperparameters in an online manner, by using relative loss as their trial rewards. One basic assumption among these methods is that at least some of the gradients with respect to the hyperparameters are non-differentiable and unavailable directly. A generalized technique is used to estimate these quantities by Monte-Carlo sampling, followed by an evaluation step with held-out data, and finally backpropagation by using the re-parametrization trick (Kingma and Welling [2013]). One key benefit with this technique, which is common to the above cited methods, is its generalizability for a wide range of different hyperparameters. On the other hand, we identify a few areas with these

methods that we would like to improve on. One, information about the internals of the procedure can and should be exploited. Two, communication overhead becomes a concern, since sufficient Monte-Carlo sampling is required for the re-parametrization trick to converge (Kingma and Welling [2013]). From initial observations of their empirical results, while these methods are successful in hyperparameter tuning and reaching target model accuracy as shown in these works, these goals are achieved in unspecified numbers of total communication rounds from works based on RL approaches such as Mostafa [2019] and Guo et al. [2022]. Similarly, performance numbers of FedEX from Khodak et al. [2021] in their online-tuning experiments on the FEMNIST dataset are subpar in their global model test error after 2000 rounds (roughly 20% test error), in comparison to the result after 1500 rounds from the same experiment in Reddi et al. [2020] conducted with tuned hyperparameters from brute-force grid search (roughly 15% test error).

The above observations justify exploring our problem differently from previous approaches. We explore a method that exploits our open-box knowledge of the training process, and a method that does not require sufficient trials at potential expense of communication budget. Inspired by the hypergradient descent techniques developed by Baydin et al. [2017] and Amid et al. [2022] for centralized optimization learning rate, we develop FATHOM by directing deriving analytical gradients with respect to the hyperparameters of interest. Our work is based on the motivation that we assume direct access to gradient information with respect to the hyperparameters. The result is a sample efficient method, FATHOM, which offers both improvements in communication efficiency and reduced local computation in a single-shot online optimization procedure. Meanwhile, FATHOM is not as flexibly applicable in optimizing a wide range of hyperparameters, since, as a open-box approach, each gradient needs to be derived separately. We believe this approach is a performance advantage, at the expense of its flexibility.

There are other notable works that are related to ours and are worth mentioning. Charles and Konečný [2020] and Li et al. [2019] proved that reducing the client learning rate during training is necessary to reach the true objective. Yet, a line of interesting works (Dai et al. [2020] and Holly et al. [2021]) applies Bayesian Optimization on federated hyperparamter tuning, by treating it as a closed-box optimization problem. However, they do not consider adaptive hyperparameters. Yet, another work (Wang and Joshi [2018]) shares similarity to our approach of optimally adapting the number of local steps, with their adaptive communication strategy, AdaComm, in the distributed setting. However, their main interest is reducing wall-clock time.

3 Methodology

In this section we formalize the problem of hyperparameter optimization for FL. We also review FedAvg, a de facto standard of federated optimization methods for research baseline and in practice. We also present our method for online-tuning of its hyperparameters, specifically client learning rate, number of local steps, and batch size. We call our method FATHOM (Federated AuTomatic Hyperparameter OptiMization).

3.1 Problem Definition

In this paper, we consider the empirical risk minimization (ERM) across all the client data, as an unconstrained optimization problem:

$$f^* := \min_{x \in \mathcal{R}^d} \left[f(x) := \frac{1}{m} \sum_{i=1}^{m} f_i(x) \right] \tag{1}$$

where $f_i : \mathcal{R}^d \to \mathcal{R}$ is the loss function for data stored in local client index i with d being the dimension of the parameters x, m is number of clients, and $f^* = f(x_*)$ where x_* is a stationary solution to the ERM problem in eq(1).

To facilitate some of the discussions that follow, it helps to define a few assumptions:

Assumption 1. *(Unbiased Local Gradient Estimator) Let $g_i(x)$ be the unbiased, local gradient estimator of $\nabla f_i(x)$, i.e., $\mathbb{E}[g_i(x)] = \nabla f_i(x)$, $\forall x$, and $i \in [m]$.*

Assumption 2. *(Convexity with respect to η_L and K) Base on the upper-bound of $f(x_t)$ derived in eq(36) being convex with respect to η_L and K, we assume also that $\mathbb{E}_t(f(x_t))$ is also convex with respect to η_L and K.*

3.2 Federated Optimization and Tuning of Hyperparameters

Federated Averaging (FedAvg) We describe the operations of FedAvg from McMahan et al. [2016], as follows. At any round t, each of the m clients takes a total of K_i local SGD steps, where $K_i = \lfloor E\nu_i/B \rfloor$, and where ν_i is the number of data samples from client index i, B is batch size, with epoch number $E = 1$ being a common baseline. In this version of FedAvg, heterogeneous data size is accommodated across clients, and the number of local steps can be manipulated via E and B as hyperparameters. Each local SGD step updates the local model parameters of each client i as follows: $x_{t,k+1}^i = x_{t,k}^i - \eta_L g_i(x_{t,k}^i)$, where η_L is the local learning rate and $k \in [K]$ is the local step index. To conclude each round, these clients return the local parameters x_{t,K_i}^i to the server where it updates its global model, with $x_{t+1} = \sum_i \nu_i x_{t,K}^i/\nu$ where $\nu = \sum_i \nu_i$. To facilitate some of the discussions that follow, we define the following quantities:

$$\overline{\Delta}_t \triangleq x_{t+1} - x_t = \sum_{i=1}^{m} \frac{\nu_i}{\nu} \Delta_t^i \quad \text{where} \quad \Delta_t^i \triangleq - \sum_{k=0}^{K_i-1} \eta_{L,t} g_i(x_t^{i,k}) \tag{2}$$

Offline Hyperparameter Tuning Offline tuning is best to be summarized as follows. We first define $A = \{a \in \mathcal{R} \mid a \geq 0\}$ with $\eta_L \in A$, and $B = \{b \in \mathcal{I} \mid b \geq 1\}$ with $K \in B$. We also define $C = A \times B$, and $c = (\eta_L, K)$, where $c \in C$. Offline tuning would have the following objective: $\min_{c \in C} f_{\text{valid}}(x, c)$ s.t. $x = \arg\min_{z \in \mathcal{R}^d} f_{\text{train}}(z, c)$. With abuse of notation, we use f_{valid} for the objective function calculated from a validation dataset which is usually held-out before the procedure, and f_{train} for the objective from training data which usually is just local client data. We also use notations such as $f(x, c)$ to remind us that its solution, x^*, depends on the optimization algorithm. With these clarifications, a few notable offline tuning methods are as follows. Global grid-search from Holly et al. [2021] is an example of offline tuning, for example, that iterates over the entire search grid defined as C, completing an optimization process for each grid point and evaluating the result with a held-out validation set. Global Bayesian Optimization from Holly et al. [2021] is another similar example of offline tuning that follows the same template and objective. Instead of brute-force grid-search, c is sampled from a distribution $\mathcal{D}_C$ over C, i.e. $c \sim \mathcal{D}_C$, that updates after every iteration.

Online Hyperparameter Optimization We are interested in an online procedure that combines hyperparameter optimization and model parameter optimization, with the following objective:

$$\min_{\substack{x \in \mathcal{R}^d \\ c \in C}} f_{\text{train}}(x, c) \tag{3}$$

This formulation is the objective of our method, FATHOM, which we will discuss shortly in detail. It has the advantage of joint optimization in a one-shot procedure. It does not assume the availability of a validation dataset. However, when a validation dataset is required in the joint optimization process, such as methods proposed in Khodak et al. [2021] and Mostafa [2019], then the objective becomes : $\min_{\substack{x \in \mathcal{R}^d \\ c \in C}} f_{\text{train}}(x, c) + f_{\text{valid}}(x, c)$.

3.3 Our Method: FATHOM

In this subsection we will introduce our method, FATHOM (Federated AuTomatic Hyperparameter OptiMization), and discuss it in detail. Recall from our joint objective, eq(3), that both the model parameters, x, and hyperparameters of the optimization algorithm, c, are optimized jointly to minimize our objective function. An alternative view is to treat c as part of the parameters being optimized in a classic formulation, i.e. $min_y f(y)$ with $y = (x, c)$. As previously mentioned, our method is inspired by hypergradient descent from Baydin et al. [2017] and by exponentiated gradient from Amid et al. [2022], both proposed for centralized learning rate optimization. We will present how FATHOM exploits our knowledge of analytical gradients to update client learning rate, number of local steps, as well as batch size, for an online, one-shot optimization procedure.

3.3.1 Hypergradient for Client Learning Rate

In this section, we derive the hypergradient for client learning rate in a similar fashion as Baydin et al. [2017], with the difference being that they are mainly concerned with the centralized optimization

problem, and that we are concerned with the distributed setting where clients take local steps. We derive the following hypergradient of the objective function as defined in eq(1), taken with respect to the learning rate $\eta_{L,t-1}$ such that it can be updated to obtain $\eta_{L,t}$:

$$H_t = \frac{\partial f(x_t)}{\partial \eta_{L,t-1}} = \frac{\partial f(x_t)}{\partial x_t} \cdot \frac{\partial(x_{t-1} + \overline{\Delta}_{t-1})}{\partial \eta_{L,t-1}} = \nabla f(x_t) \cdot \frac{\partial \overline{\Delta}_{t-1}}{\partial \eta_{L,t-1}} \tag{4}$$

$$\overline{H}_t = \frac{\nabla f(x_t)}{\|\nabla f(x_t)\|} \cdot \Big(\frac{\partial \overline{\Delta}_{t-1}}{\partial \eta_{L,t-1}} \Big/ \Big\| \frac{\partial \overline{\Delta}_{t-1}}{\partial \eta_{L,t-1}} \Big\| \Big) \approx -\frac{\overline{\Delta}_t}{\|\overline{\Delta}_t\|} \cdot \frac{\overline{\Delta}_{t-1}}{\|\overline{\Delta}_{t-1}\|} \tag{5}$$

where $\overline{\Delta}_t$ is the update step for the global model as defined in eq(2), and $\overline{H}_t$ is the normalized update similar to Amid et al. [2022]. We also make the approximation: $\nabla f(x_t) = \sum_{i=1}^{m} \frac{\nu_i}{\nu} \nabla f_i(x_t) \approx \sum_{i=1}^{m} \frac{\nu_i}{\nu} \sum_{k=0}^{K-1} g_i(x_t^{i,k})$, to reduce communication and local memory requirements, since $\overline{\Delta}_t$ is already part of the original FedAvg algorithm and is readily available. The resulting hypergradient is a scalar, as expected, and can be used efficiently as part of the update rule for η_L, which we will see in Section 3.3.4. The implementation is communication efficient, since in each round, each client needs one extra scalar to send back to the server, and likewise the server needs to broadcast one extra scalar back to the clients.

3.3.2 Hypergradient for Number of Local Steps

Since the number of local steps is an integer, i.e. $K = \{k \in \mathcal{I} \mid k \geq 1\}$, this means $f(x_t)$ does not exist for non-integer values of K. We formulate a subgradient as a surrogate of the hypergradient $\partial f(x_t)/\partial K$, as follows. We will call this a hyper-subgradient.

Theorem 1. *When a piecewise function L_t is defined for every value of $K_0 \in [K]$ on l, such that $0.0 \leq l < 1.0$, we claim the following is a subgradient of $f(x_t)$ at $K_t = K_0$:*

$$\frac{\partial L_t}{\partial l} = \nabla f(x_t) \cdot \Big(-\eta_{L,t} \sum_{i=1}^{m} g_i(x_{t-1}^{i,K_t-1}) \frac{\nu_i}{\nu} \Big) \tag{6}$$

where l represents the marginal fraction of local steps beyond K_0. We leave the proof in the Appendix section beginning in eq(20).

The result from Theorem 1 is not sufficiently communication-efficient for implementing an update rule for K. This is because it would require the quantity $g_i(x_{t-1}^{i,K_t-1})$ to be communicated from each client i to the server. To save communication, let us reuse what the server has in memory: $\overline{\Delta}_t = \big(-\eta_L \sum_{i=1}^{m} \frac{\nu_i}{\nu} \sum_{k=0}^{K_t-1} g_i(x_t^{i,k}) \big)$. If we let:

$$S_t = \nabla f(x_t) \cdot \Big(-\eta_{L,t} \sum_{i=1}^{m} \frac{\nu_i}{\nu} \sum_{k=0}^{K_t-1} g_i(x_{t-1}^{i,k}) \Big) l \tag{7}$$

$$N_t = \frac{\partial S_t}{\partial l} = \nabla f(x_t) \cdot \Big(-\eta_{L,t} \sum_{i=1}^{m} \frac{\nu_i}{\nu} \sum_{k=0}^{K_t-1} g_i(x_{t-1}^{i,k}) \Big) = \nabla f(x_t) \cdot \overline{\Delta}_{t-1} \tag{8}$$

$$\overline{N}_t = \frac{\nabla f(x_t)}{\|\nabla f(x_t)\|} \cdot \frac{\overline{\Delta}_{t-1}}{\|\overline{\Delta}_{t-1}\|} \approx -\frac{\overline{\Delta}_t}{\|\overline{\Delta}_t\|} \cdot \frac{\overline{\Delta}_{t-1}}{\|\overline{\Delta}_{t-1}\|} \tag{9}$$

where eq(9) is the normalized update as in Amid et al. [2022]. We claim that eq(8) is a positively-biased version of eq(6), which has its practical importance due to the fact that the last term in eq(6) from Theorem 1 results in zero-mean, noisy gradients, when the local functions are nearing their local solutions, when in fact, this is the area where more local work is not needed. Thus, a positive bias is desirable to drive the number of local steps down. This result is also useful from a communication efficiency perspective in its implementation, because the server has all the components to calculate this quantity, and would not require additional communication.

3.3.3 Regularization for Number of Local Steps

One of the goals for FATHOM is savings in local computation. To avoid excessive number of local steps, we further develop a regularization term for local computation against excessive K, which is a proxy for the hypergradient of the local client functions at the end of each round : $\partial f_i(x_t^{i,K})/\partial K$.

Theorem 2. *When a piecewise function J_t is defined for every value of $K_0 \in [K]$ on l, such that $0.0 \leq l < 1.0$, we claim the following is a subgradient of $\sum_{i=1}^{m} f_i(x_t^{i,K_t})$ at $K_t = K_0$:*

$$\frac{\partial J_t}{\partial l} = -\eta_{L,t} \sum_{i=1}^{m} \frac{\nu_i}{\nu} \mathbb{E}\big[g_i(x_t^{i,K_0-1})\big] \cdot g_i(x_t^{i,K_t}) \approx -\eta_{L,t} \sum_{i=1}^{m} \frac{\nu_i}{\nu} \sum_{k=0}^{K_t-1} g_i(x_t^{i,k}) \cdot g_i(x_t^{i,K_t}) \quad (10)$$

where l represents the marginal fraction of local steps beyond K_0. We leave the proof in the Appendix section beginning in eq(24).

In our algorithm, we use the normalized update based on the following biased proxy, since eq(10) tends to be noisy from $g_i(x_t^{i,K_t})$.

$$G_t = -\eta_{L,t} \sum_{i=1}^{m} \frac{\nu_i}{\nu} \min_{K \leq K_t} \Big(\sum_{k=0}^{K-1} g_i(x_t^{i,k}) \cdot g_i(x_t^{i,K}) \Big) \quad (11)$$

$$\overline{G}_t = -\eta_{L,t} \sum_{i=1}^{m} \frac{\nu_i}{\nu} \min_{K \leq K_t} \left(\frac{\sum_{k=0}^{K-1} g_i(x_t^{i,k})}{\big\| \sum_{k=0}^{K-1} g_i(x_t^{i,k}) \big\|} \cdot \frac{g_i(x_t^{i,K})}{\|g_i(x_t^{i,K})\|} \right) \quad (12)$$

where $\overline{G}_t$ is the normalized update. The proxy yields a bias towards smaller number of local steps, which is desirable for reducing local computation. We use this biased proxy against using a more typical regularization such as L2 on K to avoid tuning an extra hyperparameter.

3.3.4 Normalized Exponentiated Gradient Updates

For the update rules of the hyperparameters η_L (client learning rate) and K (number of client local steps), we use the normalized exponentiated gradient descent method (EGN) with no momentum, rather than a conventional linear update method such as the additive update of hypergradient descent proposed in Baydin et al. [2017]. It is reasonable to use exponentiated gradient (EG) methods for updates of hyperparameters that are strictly positive in value. EG methods also enjoy significantly faster convergence properties when only a small subset of the dimensions are relevant, according to Amid et al. [2022].

EG methods have been proposed in previous works for a variety of applications (Khodak et al. [2021], Amid et al. [2022], Li et al. [2020]), and analyzed in depth (Ghai et al. [2019]), where its convergence has been studied and validated (Li and Cevher [2018]). Recently, Amid et al. [2022] showed that EGN is the same as the multiplicative update for hypergradient descent proposed in Baydin et al. [2017], when the approximation $exp(\cdot) \approx 1 + \cdot$ is made. From our observations, we believe that momentum is not needed for the effectiveness of EGN in our application, as validated in our numerical results. We also opted-out of adding further complexity such as extra weights and activation functions to model the relationships between $\eta_{L,t}$ and K_t, because it would require more samples to optimize and because FATHOM is a one-shot procedure. Furthermore, due to the non-stationary nature of these values, we opt for a simpler scheme for faster performance.

Hence, for the update rule of client learning rate, η_L, we have:

$$\eta_{L,t+1} = \eta_{L,t} \exp\big(-\gamma_\eta \overline{H}_t\big) \quad (13)$$

where $\overline{H}_t$ is as defined in eq(5). For local steps K, we observe that it is related to batch size B as follows. To accommodate heterogeneity of local dataset sizes among clients, we have number of local data samples from client i to be ν_i. Then we have $K_i = \lfloor \nu_i E/B \rfloor$, where E is number of epochs, with $E = 1$ meaning the entire local dataset for each client to be processed once per round. We derive update rules for E and B globally, without having to make any changes to our theoretical analysis to accommodate the heterogeneity of local dataset sizes:

$$E_{t+1} = E_t \exp\big(-\gamma_E\big(\overline{N}_t + \overline{G}_t\big)\big) \quad (14)$$

and

$$B_{t+1} = B_t \exp\big(-\gamma_B\big(-\overline{G}_t\big)\big) \quad (15)$$

where N_t and G_t are defined in eq(9) and eq(12), respectively.

Algorithm 1: FATHOM : $g_i(x)$ is defined in Assumptions 1, and m is the number of clients.

Input: Server initializes global model $x_{t=1}$, T as the end communication round, and:

$$\overline{\Delta}_{t=0,sm} = 0 \; ; \; \alpha = 0.5 \; ; \; \gamma_\eta = 0.01 \; ; \; \gamma_E = 0.01 \; ; \; \gamma_B = 0.1$$

Output: x_T, as well as $\eta_{L,t}$, E_t and B_t for all $t \in [T]$

for $t = 1, \ldots, T$ **do**

    Sample client set S_t out of m clients.

    For each client $i \in S_t$, initialize: $x_t^{i,k=0} = x_t$ and $K_{t,i} = \lfloor \nu_i E_t / B_t \rfloor$.

    Set $\Delta_i = 0$, and $\phi_i = +\infty$.

    for $k = 0, \ldots, K_{t,i} - 1$ **do**

        For each client i, compute in parallel an unbiased stochastic gradient $g_i(x_t^{i,k})$.

        For each client i, calculate $\phi_i = \min(\phi_i, g_i(x_t^{i,k}) \cdot \Delta_i)$ where $\Delta_i = x_t^{i,k} - x_t$

        For each client i, update in parallel its local solution: $x_t^{i,k+1} = x_t^{i,k} - \eta_{L,t} g_i(x_t^{i,k})$

    end

    Server calcualtes $\nu = \sum_{i \in S_t} \nu_i$, where ν_i is the size of client i dataset.

    Server calculates $\overline{\Delta}_t = \sum_{i \in S_t} \Delta_i(\nu_i/\nu)$; see eq(2)

    Server updates global model $x_{t+1} = x_t - \overline{\Delta}_t$

    Server calculates $\overline{H}_t = \overline{N}_t = -\frac{\overline{\Delta}_t}{\|\overline{\Delta}_t\|} \cdot \frac{\overline{\Delta}_{t-1,sm}}{\|\overline{\Delta}_{t-1,sm}\|}$, modified from eq(5) and eq(9)

    Server calculates $\overline{G}_t$; see eq(12

    Server updates client learning rate $\eta_{L,t+1}$, epochs, E_{t+1}, and batch size B_{t+1} for the next round; see eq(13), eq(14), and eq(15).

    Server updates $\overline{\Delta}_{t,sm} = (1 - \alpha)\overline{\Delta}_t + \alpha\overline{\Delta}_{t-1,sm}$ for the next round

end

3.3.5 Client Sampling

We present our method, FATHOM, as shown in Algorithm 1. One practical factor we have not considered in our discussions is partial client sampling. For our implementation to handle the stochastic nature of client sampling, the metric $\overline{\Delta}_{t-1}$ for calculating $\overline{H}_t$ in eq(5) and $\overline{N}_t$ in eq(9) is modified by a smoothing function for noise filtering, i.e. $\overline{\Delta}_{t,sm} = \alpha\overline{\Delta}_{t-1,sm} + (1-\alpha)\overline{\Delta}_t$, which is a single-pole infinite impulse response filter (Oppenheim and Schafer [2009]Oppenheimer et al. [2009]) with no bias compensation. We use the notation "sm" for smoothed, and after many experiments, we decide to use $\alpha = 0.5$ for all of our numerical results.

4 Theoretical Convergence

A standard approach to theoretical analysis of an online convex optimization method such as ours (see Assumption 2), is through analyzing the regret bound (Zinkevich [2003], Khodak et al. [2019], Kingma and Ba [2014], and Mokhtari et al. [2016]). Nonetheless, this approach does not tell us the impact on communication efficiency by the online updates introduced from FATHOM. Therefore, we take an alternative approach by extending the guarantees of FedAvg performance (Wang et al. [2021], Reddi et al. [2020], Gorbunov et al. [2020], Yang et al. [2021], Li et al. [2019], etc) to include both adaptive learning rate and adaptive number of local steps. We highlight the degree-of-freedom aspect of our result offered by the new relaxed conditions in eq(17), for not imposing any constraint, e.g. a decay function such as that done by Li et al. [2019] on learning rate, over the course of the process. We assume the special case in our analysis to have full client participation. We prove that adaptive learning rate and adaptive number of local steps does not impact asymptotic convergence, despite the given relaxed conditions. Furthermore, the relaxed conditions allow strategies that emphasize different performance metrics in various stages of the optimization process, such as the classic acceleration in earlier rounds followed by reduced local computation towards the asymptote.

4.1 Assumptions

Assumption 3. *(L-Lipschitz Continuous Gradient) There exists a constant $L > 0$, such that* $\|\nabla f_i(x) - \nabla f_i(y)\| \le L\|x - y\|$, $\forall x, y \in \mathcal{R}^d$, *and* $i \in [m]$.

Assumption 4. *(Bounded Local Variance) There exist a constant $\sigma_L > 0$, such that the variance of each local gradient estimator is bounded by $\mathbb{E}\|\nabla f_i(x) - g_i(x)\|^2 \leq \sigma_L^2$, $\forall x$, and $i \in [m]$.*

Assumption 5. *(Bounded Second Moment) There exists a constant $G > 0$, such that $\mathbb{E}_t\|\nabla f_i(x_t)\| \leq G$, $i \in [m]$, $\forall x_t$.*

4.2 Convergence Results

Theorem 3. *Under Assumptions 1-5 and with full client participation, when FATHOM as shown in Algorithm 1 is used to find a solution x_* to the unconstrained problem defined in eq(1), the sequence of outputs $\{x_t\}$ satisfies the following upper-bound, where, with slight abuse of notation, $\mathcal{E} = \min_{t \in [T]} \mathbb{E}_t\|\nabla f(x_t)\|_2^2$:*

$$\mathcal{E}_{fathom} = \mathcal{O}\left(\sqrt{\frac{\sigma_L^2 + G^2}{m\overline{K}T}} + \sqrt[3]{\frac{\sigma_L^2}{\overline{K}T^2}} + \sqrt[3]{\frac{G^2}{T^2}} \right) \tag{16}$$

with the following conditions: $\overline{\eta}_L = \min\left(\sqrt{\frac{2\beta_0 mD}{\beta_1 \overline{K}LT(\sigma_L^2 + G^2)}}, \sqrt[3]{\frac{\beta_0 D}{2.5\beta_2 \overline{K}^2 L^2 \sigma_L^2 T}}, \sqrt[3]{\frac{\beta_0 D}{2.5\beta_3 \overline{K}^3 L^2 G^2 T}} \right)$

and $\eta_{L,t} \leq 1/L$ for all t, where

$$\overline{\eta}_L \triangleq \frac{1}{T}\sum_{t=1}^{T}\eta_{L,t} \qquad and \qquad \overline{K} \triangleq \frac{1}{T}\sum_{t=1}^{T}K_t \tag{17}$$

and where

$$\beta_0 = \frac{\sum_t \eta_{L,t}K_t}{T\left[\frac{1}{T}\sum_t \eta_{L,t}\right]\left[\frac{1}{T}\sum_t K_t\right]} \ , \ \ \beta_1 = \frac{\sum_t \eta_{L,t}K_t\left[\frac{1}{T}\sum_t \eta_{L,t}\right]}{\sum_t \eta_{L,t}^2 K_t} \tag{18}$$

$$\beta_2 = \frac{\sum_t \eta_{L,t}K_t\left[\frac{1}{T}\sum_t \eta_{L,t}\right]^2\left[\frac{1}{T}\sum_t K_t\right]}{\sum_t \eta_{L,t}^3 K_t^2} \ , \ \ \beta_3 = \frac{\sum_t \eta_{L,t}K_t\left[\frac{1}{T}\sum_t \eta_{L,t}\right]^2\left[\frac{1}{T}\sum_t K_t\right]^2}{\sum_t \eta_{L,t}^3 K_t^3} \tag{19}$$

We leave the proof in the Appendix beginning in eq(29).

The values of β_0, β_1, β_2, β_3, and β_4 are dependent on the relative changes over the adaptive process of these components, according to Chebyshev's Sum Inequalities (Hardy et al. [1988]). A special case is when these quantities equal to 1 when both $\eta_{L,t}$ and K_t are constant, which recovers the standard upperbound for FedAvg from eq(16).

Figure 1: Test Accuracy Performance with various values of initial client learning rate (LR_0), initial batch size (BatchSize_0), and number of clients per round (NumClients). Baseline values for FEMNIST: LR_0=0.1, BatchSize_0=20, NumClients=10. Baseline values for FSO: LR_0=0.32, BatchSize_0=16, NumClients=50.

5 Empirical Evaluation and Numerical Results

We present an empirical evaluation of FATHOM proposed in Section 3 and outlined in Algorithm 1. We conduct extensive simulations of federated learning in character recognition on the federated EMNIST-62 dataset (FEMNIST) (Cohen et al. [2017]) with a CNN, and in natural language next-word prediction on the federated Stack Overflow dataset (FSO) (TensorFlow-Federated-Authors [2019]) with a RNN. For completeness, we defer most of the details of the experiment setup in Appendix Section C.1. Our choice of datasets, tasks and models, are exactly the same as the "EMNIST CR" task and the "SO NWP" task from Reddi et al. [2020]. See Figure 1 and Table 1 and their captions for details of the experiment results.

The underlying principle behind these experiments is evaluating the robustness of FATHOM versus FedAvg under various initial settings, to mirror realistic usage scenarios where the optimal hyperparameter values are unknown. For FATHOM, we start with the same initial hyperparameter values as FedAvg. The test accuracy progress with respect to communication rounds is shown in Figure 1 from these experiments. We also pick test accuracy targets for the two tasks. For FEMNIST CR we use 86% and for FSO NWP we use 23%. Table 1 shows a table of resource utilization metrics with respect to reaching these targets in our experiments, highlighting the communication efficiency as well as reduction in local computation from FATHOM in comparison to FedAvg. To our knowledge, we are the first to show gain from an online hyperparameter optimization procedure over a well-tuned equivalent procedure with fixed hyperparameter values.

The federated learning simulation framework on which we build our algorithms for our experiments is FedJAX (Ro et al. [2021]) which is under the Apache License. The server that runs the experiments is equipped with Nvidia Tesla V100 SXM2 GPUs.

Table 1: Resource utilization in communication and local computation to reach specified test accuracy target for each task. All evelutions are run for ten trials. Bold numbers highlight better performance. NA means target was not reached within 1500 rounds for FSO NWP and 2000 rounds for FEMNIST CR, in any of our trials. LR_0 is initial client learning rate, BS_0 is initial batch size, and NCPR is number of clients per round. All experiments use baseline initial values except where indicated. For clarification, M is used in place for "million", and K for "thousand".
Baseline_fso : (LR_0 = 0.32, BS_0 = 16, NCPR = 50)
Baseline_femnist : (LR_0 = 0.10, BS_0 = 20, NCPR = 10)

Tasks	Experiments	Number of Rounds To Reach Target Test Accuracy		Local Gradients Calculated To Reach Target Test Accuracy	
		FATHOM	FedAvg	FATHOM	FedAvg
FSO NWP Target@23%	Baseline_fso	562 ± 12	971 ± 11	$85M \pm 1.2M$	$124M \pm 1.3M$
	LR_0 = 0.05	871 ± 7	NA	$138M \pm 3.2M$	NA
	BS_0 = 4	758 ± 43	580 ± 18	$93M \pm 2.8M$	$74M \pm 2.5M$
	BS_0 = 256	801 ± 28	NA	$174M \pm 18M$	NA
	NCPR = 25	970 ± 49	1283 ± 33	$63M \pm 2.7M$	$82M \pm 3.8M$
	NCPR = 200	396 ± 17	684 ± 26	$280M \pm 45M$	$350M \pm 13M$
FEMNIST CR Target@86%	Baseline_femnist	739 ± 24	1098 ± 15	$1.5M \pm 36K$	$2.2M \pm 64K$
	LR_0 = 0.05	905 ± 21	1574 ± 19	$1.7M \pm 28K$	$3.1M \pm 28K$
	BS_0 = 4	708 ± 17	885 ± 41	$1.2M \pm 28K$	$1.7M \pm 88K$
	BS_0 = 256	736 ± 20	NA	$2.0M \pm 44K$	NA
	NCPR = 100	777 ± 16	1436 ± 18	$22M \pm 0.27M$	$28M \pm 0.39K$
	NCPR = 200	790 ± 16	1481 ± 33	$57M \pm 1.0M$	$59M \pm 1.3M$

6 Conclusion and Future Work

In this work, we propose FATHOM for adaptive hyperparameters in federated optimization, specifically for FedAvg. We analyze theoretically and evaluate empirically its potential benefits in convergence behavior as measured in test accuracy, and in reduction of local computations, by automatically adapting the three main hyperparameters of FedAvg: client learning rate, and number of local steps via epochs and batch size. Server learning rate online optimization is an area that has not been addressed by our method and therefore is a limitation of FATHOM. However, this area will be considered for our future work, perhaps by using FATHOM in conjunction with methods such as those from Reddi et al. [2020] that specifically address this topic.

References

E. Amid, R. Anil, C. Fifty, and M. K. Warmuth. Step-size adaptation using exponentiated gradient updates, 2022.

A. G. Baydin, R. Cornish, D. M. Rubio, M. Schmidt, and F. Wood. Online learning rate adaptation with hypergradient descent, 2017.

H. Cai, L. Zhu, and S. Han. ProxylessNAS: Direct neural architecture search on target task and hardware. In *International Conference on Learning Representations*, 2019. URL https://arxiv.org/pdf/1812.00332.pdf.

Z. Charles and J. Konečný. On the outsized importance of learning rates in local update methods, 2020.

G. Cohen, S. Afshar, J. Tapson, and A. Van Schaik. Emnist: Extending mnist to handwritten letters. In *2017 international joint conference on neural networks (IJCNN)*, pages 2921–2926. IEEE, 2017.

Z. Dai, K. H. Low, and P. Jaillet. Federated bayesian optimization via thompson sampling, 2020.

U. Ghai, E. Hazan, and Y. Singer. Exponentiated gradient meets gradient descent, 2019.

E. Gorbunov, F. Hanzely, and P. Richtárik. Local sgd: Unified theory and new efficient methods, 2020.

P. Guo, D. Yang, A. Hatamizadeh, A. Xu, Z. Xu, W. Li, C. Zhao, D. Xu, S. Harmon, E. Turkbey, et al. Auto-fedrl: Federated hyperparameter optimization for multi-institutional medical image segmentation. *arXiv preprint arXiv:2203.06338*, 2022.

G. Hardy, J. Littlewood, and G. Pólya. *Inequalities*. Cambridge Mathematical Library. Cambridge University Press, 1988. ISBN 9781107647398. URL https://books.google.com/books?id=EfvZAQAAQBAJ.

S. Holly, T. Hiessl, S. R. Lakani, D. Schall, C. Heitzinger, and J. Kemnitz. Evaluation of hyperparameter-optimization approaches in an industrial federated learning system, 2021.

M. Khodak, M.-F. Balcan, and A. Talwalkar. Adaptive gradient-based meta-learning methods, 2019.

M. Khodak, R. Tu, T. Li, L. Li, N. Balcan, V. Smith, and A. Talwalkar. Federated hyperparameter tuning: Challenges, baselines, and connections to weight-sharing. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=p99rWde9fVJ.

D. P. Kingma and J. Ba. Adam: A method for stochastic optimization, 2014.

D. P. Kingma and M. Welling. Auto-encoding variational bayes, 2013.

L. Li, M. Khodak, M.-F. Balcan, and A. Talwalkar. Geometry-aware gradient algorithms for neural architecture search, 2020.

X. Li, K. Huang, W. Yang, S. Wang, and Z. Zhang. On the convergence of fedavg on non-iid data, 2019.

Y.-H. Li and V. Cevher. Convergence of the exponentiated gradient method with armijo line search. *Journal of Optimization Theory and Applications*, 181(2):588–607, Dec 2018. ISSN 1573-2878. doi: 10.1007/s10957-018-1428-9. URL http://dx.doi.org/10.1007/s10957-018-1428-9.

H. B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas. Communication-efficient learning of deep networks from decentralized data, 2016.

A. Mokhtari, S. Shahrampour, A. Jadbabaie, and A. Ribeiro. Online optimization in dynamic environments: Improved regret rates for strongly convex problems. *2016 IEEE 55th Conference on Decision and Control (CDC)*, Dec 2016. doi: 10.1109/cdc.2016.7799379. URL http://dx.doi.org/10.1109/cdc.2016.7799379.

H. Mostafa. Robust federated learning through representation matching and adaptive hyper-parameters, 2019.

A. V. Oppenheim and R. W. Schafer. *Discrete-Time Signal Processing*. Prentice Hall Press, USA, 3rd edition, 2009. ISBN 0131988425.

H. Pham, M. Guan, B. Zoph, Q. Le, and J. Dean. Efficient neural architecture search via parameters sharing. In J. Dy and A. Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 4095–4104. PMLR, 10–15 Jul 2018. URL https://proceedings.mlr.press/v80/pham18a.html.

S. Reddi, Z. Charles, M. Zaheer, Z. Garrett, K. Rush, J. Konečný, S. Kumar, and H. B. McMahan. Adaptive federated optimization, 2020.

J. H. Ro, A. T. Suresh, and K. Wu. Fedjax: Federated learning simulation with jax. *arXiv preprint arXiv:2108.02117*, 2021.

TensorFlow-Federated-Authors. Tensorflow federated stack overflow dataset, 2019. URL `https://www.tensorflow.org/federated/api_docs/python/tff/simulation/datasets/stackoverflow`.

J. Wang and G. Joshi. Adaptive communication strategies to achieve the best error-runtime trade-off in local-update sgd, 2018.

J. Wang, Z. Charles, Z. Xu, G. Joshi, H. B. McMahan, B. A. y Arcas, M. Al-Shedivat, G. Andrew, S. Avestimehr, K. Daly, D. Data, S. Diggavi, H. Eichner, A. Gadhikar, Z. Garrett, A. M. Girgis, F. Hanzely, A. Hard, C. He, S. Horvath, Z. Huo, A. Ingerman, M. Jaggi, T. Javidi, P. Kairouz, S. Kale, S. P. Karimireddy, J. Konecny, S. Koyejo, T. Li, L. Liu, M. Mohri, H. Qi, S. J. Reddi, P. Richtarik, K. Singhal, V. Smith, M. Soltanolkotabi, W. Song, A. T. Suresh, S. U. Stich, A. Talwalkar, H. Wang, B. Woodworth, S. Wu, F. X. Yu, H. Yuan, M. Zaheer, M. Zhang, T. Zhang, C. Zheng, C. Zhu, and W. Zhu. A field guide to federated optimization, 2021.

R. J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Mach. Learn.*, 8(3–4):229–256, may 1992. ISSN 0885-6125. doi: 10.1007/BF00992696. URL `https://doi.org/10.1007/BF00992696`.

B. Woodworth, K. K. Patel, S. U. Stich, Z. Dai, B. Bullins, H. B. McMahan, O. Shamir, and N. Srebro. Is local sgd better than minibatch sgd?, 2020.

H. Yang, M. Fang, and J. Liu. Achieving linear speedup with partial worker participation in non-iid federated learning, 2021.

M. Zinkevich. Online convex programming and generalized infinitesimal gradient ascent. In *Proceedings of the Twentieth International Conference on International Conference on Machine Learning*, ICML'03, page 928–935. AAAI Press, 2003. ISBN 1577351894.