Improved Bounds on Neural Complexity for Representing Piecewise Linear Functions

Abstract

A deep neural network using rectified linear units represents a continuous piecewise linear (CPWL) function and vice versa. Recent results in the literature estimated that the number of neurons needed to exactly represent any CPWL function grows exponentially with the number of pieces or exponentially in terms of the factorial of the number of distinct linear components. Moreover, such growth is amplified linearly with the input dimension. These existing results seem to indicate that the cost of representing a CPWL function is expensive. In this paper, we propose much tighter bounds and establish an algorithm to find a network satisfying these bounds for any given CPWL function. We prove that the number of hidden neurons required to exactly represent any CPWL function is at most a quadratic function of the number of pieces. More importantly, in contrast to all previous results, this upper bound is invariant to the input dimension. Besides the number of pieces, we also study the number of distinct linear components in CPWL functions. When such a number is also given, we prove that the quadratic complexity turns into bilinear, which implies a lower neural complexity because the number of distinct linear components is always not greater than the minimum number of pieces in a CPWL function. When the number of pieces is unknown, we prove that, in terms of the number of distinct linear components, the neural complexity of any CPWL function is at most polynomial growth for low-dimensional inputs and a factorial growth for the worst-case scenario, which are significantly better than existing results in the literature.

1 Introduction

The rectified linear unit (ReLU) [Fukushima, 1980, Nair and Hinton, 2010] activation has been by far the most widely used nonlinearity and successful building block in deep neural networks (DNNs). Numerous architectures based on ReLU DNNs have achieved remarkable performance or state-of-the-art accuracy in speech processing [Zeiler et al., 2013, Maas et al., 2013], computer vision [Krizhevsky et al., 2012, Simonyan and Zisserman, 2015, He et al., 2016], medical image segmentation [Ronneberger et al., 2015], game playing [Mnih et al., 2015, Silver et al., 2016], and natural language processing [Vaswani et al., 2017], just to name a few. Besides such unprecedented empirical success, ReLU DNNs are also probably the most understandable nonlinear deep learning models due to their ability to be "un-rectified" [Hwang and Heinecke, 2019].

The ability to demystify ReLU DNNs via "un-rectifying ReLUs" dates back to a seminal work by Pascanu et al. in 2014. Because each of ReLUs in a hidden layer divides the space of the preceding layer's output into two half spaces whose ReLU response is affine in one half space and exactly zero in the other, the layer of ReLUs can be replaced by an input-dependent diagonal matrix whose diagonal elements are ones for firing ReLUs and zeros for non-firing ReLUs. Based on this

Figure 1: Any CPWL function $\mathbb{R}^n \to \mathbb{R}$ with q pieces or k distinct linear components can be exactly represented by a ReLU network with at most h hidden neurons. In Theorem 1 and 3, $h = 0$ when $q = 1$ or $k = 1$. The figure on the right-hand side uses $n = 1$ (see Figure 2 for different n). (5) is used to infer the bounds based on the depth and width given by Hertrich et al. [2021]. The upper bounds given by Theorem 1 and 3 are substantially lower than existing bounds in the literature, implying that any CPWL function can be exactly realized by a ReLU network at a potentially much lower cost.

rationale, Pascanu et al. [2014] proved that a neural network using ReLUs divides the input space into many linear regions such that the network itself is an affine function within every region. Two excellent visualizations are shown in Figure 2 in [Hanin and Rolnick, 2019a] and [Hanin and Rolnick, 2019b]. At this point, it is quite evident that any ReLU network exactly represents a CPWL function. Pascanu et al. also proved that the maximum number of linear regions for any ReLU network with a single hidden layer is equivalent to the number of connected components induced by arrangements of hyperplanes in general position where each hyperplane corresponds to a ReLU in the hidden layer. Such a number can be computed in a closed form by Zaslavsky's Theorem [Zaslavsky, 1975]. Furthermore, they showed that the maximum number of linear regions can be bounded from below by exponential growth in terms of the number of hidden layers, leading to a conclusion that ReLU DNNs can generate more linear regions than their shallow counterparts. In the same year, Montúfar et al. improved such a lower bound and gave the first upper bound for the maximum number of linear regions. These bounds and their assumptions were later improved by [Montúfar, 2017, Raghu et al., 2017, Arora et al., 2018, Serra et al., 2018, Hinz and van de Geer, 2019], just to name a few. We refer readers to Hinz's doctoral thesis for a thorough discussion on the upper bound of the number of linear regions. Because a CPWL function with more pieces can better approximate any given continuous function and a ReLU DNN exactly represents a CPWL [Arora et al., 2018], a ReLU DNN with more linear regions in general exhibits stronger expressivity. In summary, this "un-rectifying" perspective provides us a new angle to understand ReLU DNNs, and the results in some ways align with the advance in approximation theory demonstrating the expressivity. [1]

Despite these advancements in linear regions, the complexity of a ReLU DNN that exactly represents a given CPWL function remains largely unexplored. One can find that this question is the opposite direction of the above-mentioned line of research. Although Arora et al. [2018] proved that any CPWL function can be exactly represented by a ReLU DNN with a bounded depth, any estimates regarding the width or number of neurons of such a network were not given. The resources required for a ReLU neural network to exactly represent a CPWL function remained unknown until He et al. [2020] first gave an estimate to the complexity of a ReLU network that realizes any given CPWL function. They proved that the number of neurons is bounded from above by exponential growth in terms of the product between number of pieces and the number of distinct linear components of a given CPWL function. Such an exponential bound also grows linearly with the input dimension. Because the number of pieces is an upper bound of the number of distinct linear components for any CPWL function [Tarela and Martinez, 1999, He et al., 2020], the bound grows exponentially with the

---

[1]The approximation viewpoint is not the focus of this paper. The literature on approximation is vast and we refer readers to [Vardi et al., 2021, Lu et al., 2017, Eldan and Shamir, 2016, Telgarsky, 2016, Hornik et al., 1989, Cybenko, 1989], just to name a few.

quadratic number of pieces, which seems to imply that the cost for representing a CPWL function by a ReLU DNN is exceedingly high.

The most recent upper bound can be inferred from a recent work by Hertrich et al. [2021] although the number of hidden neurons was not directly given. Hertrich et al. [2021] proved the first width bound in terms of the number of pieces under the same depth used by Arora et al. [2018] and He et al. [2020]. In particular, they proved that the width of a ReLU network that represents any given CPWL function can be polynomially bounded from above in terms of the number of pieces. However, the order of such a polynomial is a quadratic function of the input dimension, which can be immensely large for a small number of pieces if the input dimension is large. This bound grows larger with the input dimension even though the underlying CPWL function is just a one-hidden-layer ReLU network using only one ReLU.

In this paper, we provide improved bounds showing that any CPWL function can be represented by a ReLU DNN whose neural complexity is bounded from above by functions with much slower growth (see Figure 1). Our results imply that one can exactly realize any given CPWL function by a ReLU network at a much lower cost. Moreover, in addition to guarantee the existence, we also give an algorithm to exactly find a network satisfying our bounds. To the best of our knowledge, our results regarding the computational resource for a ReLU network, i.e., the number of hidden neurons, are the lowest upper bounds in the existing literature and the algorithm is the first tailored procedure to find a network representation from any given CPWL function. Key results and main contributions of this paper are highlighted below.

1.1 Key results and contributions

Quadratic bounds.   We prove that any CPWL function with q pieces can be represented by a ReLU network whose total number of hidden neurons is bounded from above by a quadratic function of q. We also give the corresponding upper bounds for the maximum width, i.e., the maximum number of neurons per hidden layer, and the number of layers for such a network. The maximum width is bounded from above by $\mathcal{O}(q^2)$ and the number of layers is bounded from above by a logarithmic function of q, i.e., $\mathcal{O}(\log_2 q)$. *These bounds are invariant to the input dimension.* For any affine function, the upper bounds for the maximum width and the number of hidden neurons are zero.

Further improvements on neural complexity.   When the number of distinct linear components k of any CPWL function is given along with the number of pieces q, the quadratic bounds $\mathcal{O}(q^2)$ for the number of hidden neurons and the maximum width turn into *bilinear* bounds of k and q, i.e., $\mathcal{O}(kq)$. Such a change reduces the neural complexity because q is always not less than k and usually much larger with a high dimensional input. Still, these bounds are independent of the input dimension.

Finding a network satisfying bilinear bounds.   We establish an algorithm (see Algorithm 1) that finds a ReLU network representing any given CPWL function. The network found by the algorithm satisfies the bilinear bounds on the number of hidden neurons and the maximum width, and the logarithmic bound on the number of layers. Note that such an algorithm also guarantees that one can always reverse-engineer at least one ReLU network from the function it computes. Compared to the general-purpose reverse-engineering algorithm proposed by Rolnick and Kording [2020], our algorithm specializes in the situation when the CPWL is given.

Improved bounds from a perspective of linear components.   When the number of pieces of a CPWL function is unknown and only the number of linear components k is available, we prove that the number of hidden neurons and maximum width are bounded from above by factorial growth. More precisely, $\mathcal{O}\left(k \cdot k!\right)$. The number of layers is bounded from above by linearithmic growth, or $\mathcal{O}(k \log_2 k)$. However, if the the input dimension n grows sufficiently slower than k, e.g., $\mathcal{O}\left(\sqrt{k}\right)$, then bounds for the number of hidden neurons and maximum width reduce to *polynomial* growth functions of order $2n + 1$; and the linearithmic growth reduces to $\mathcal{O}\left(n \log_2 k\right)$ for the depth.

A new approach to choosing depth.   Instead of scaling the depth of a ReLU network with the input dimension [Arora et al., 2018, He et al., 2020, Hertrich et al., 2021], we reveal that constructing a ReLU network whose depth is scaled with the number of pieces of the given CPWL function is more advantageous. Such a scaling turns out to be the key to derive better upper bounds. This insight

is provided by the max-min representation of CPWL functions [Tarela et al., 1990]. The importance of this scaling on the depth in ReLU networks has not been well recognized by existing bounds in the literature. We discuss implications of different representations in Section 4.

2 Preliminaries

Notation and definitions used in this paper are set up and clarified in this section. The set $\{1, 2, \cdots, m\}$ is denoted by $[m]$. $\mathbb{I}\left[condition\right]$ is an indicator function that gives 1 if the *condition* is true, and 0 otherwise. The CPWL function is defined by Definition 1 below.

Definition 1. *A function $p\colon \mathbb{R}^n \to \mathbb{R}$ is said to be CPWL if there exists a finite number of closed subsets of $\mathbb{R}^n$, say $\{\mathcal{X}_i\}_{i\in[m]}$, such that (a) $\mathbb{R}^n = \bigcup_{i\in[m]} \mathcal{X}_i$; (b) p is affine on $\mathcal{X}_i, \forall i \in [m]$.*

A family of closed *convex* subsets of $\mathbb{R}^n$ satisfying Definition 1 are also referred to as convex regions, affine pieces or simply *pieces* for a CPWL function in this paper. Definition 1 follows the definition of CPWL functions by Ovchinnikov [2002]. Notice that there are different definitions in the literature. For example, Chua and Deng [1988] and Arora et al. [2018] defined a CPWL function on a finite number of polyhedral regions. However, their definitions are essentially the same as Definition 1 because any family of closed subsets satisfying Definition 1 can be decomposed into polyhedral regions. It is possible that some of the closed subsets satisfying Definition 1 are non-convex even though the number of them reaches the minimum (see Figure 2 in [Wang and Sun, 2005]). The continuity is implied by Definition 1 due to the subsets being closed.

Because the goal of this paper is to bound the complexity of a ReLU DNN that exactly represents any given CPWL function, it is necessary to be able to measure the complexity of a CPWL function. The complexity of a CPWL function can be described using two quite different perspectives. One is the number of pieces q, which is the number of closed convex subsets satisfying Definition 1. Because this number has a minimum and any finite number above the minimum can be a valid m in Definition 1, the bounds become obviously loose when the number of pieces is not the minimum. Without loss of generality, we are interested in the number q when it is the minimum. The other is the number of distinct linear components k. A linear component of a CPWL function is defined in Definition 2.

Definition 2. *An affine function f is said to be a linear component of a CPWL function p if there exists a nonempty subset $\mathcal{M} \subseteq [m]$ such that $f(\mathbf{x}) = p(\mathbf{x}), \forall \mathbf{x} \in \bigcup_{i\in\mathcal{M}} \mathcal{X}_i$ where $\{\mathcal{X}_i\}_{i\in[m]}$ is a family of minimum number of closed subsets satisfying Definition 1.*

A greater q or k gives a CPWL function more degrees of freedom because a CPWL function allowed to use $q + 1$ pieces or $k + 1$ arbitrary linear components can represent any CPWL function with q pieces or k distinct linear components and still have a flexibility to modify existing affine maps or increase the number of distinct affine maps of the CPWL function. Although increasing them both leads to a CPWL function with a higher flexibility, the speed of upgrading degrees of freedom is different from each other. Note that a CPWL function with q pieces can never have more than q distinct linear components and a CPWL function with k distinct linear components can easily have more than k minimum number of pieces. Such a difference in an 1-dimensional case can be clearly observed from Figure 1 in [Tarela and Martinez, 1999]. Note that it is possible for two disjoint subsets from a minimum number of closed subsets satisfying Definition 1 to share the same linear component. In other words, a linear component can be reused by multiple pieces. Hence, increasing k gives much faster growth than increasing q for the complexity and expressivity of CPWL functions.

We define the ReLU activation function in Definition 3 and the ReLU network in Definition 4. Definition 5 defines the corresponding number of hidden neurons, depth, and the maximum width.

Definition 3. *The rectified linear unit (ReLU) activation function σ is defined as $\sigma(x) = \max(0, x)$. The ReLU layer or vector-valued rectified linear activation function σ_k is defined as $\sigma_k(\mathbf{x}) = \begin{bmatrix} \sigma(x_1) & \sigma(x_2) & \cdots & \sigma(x_k) \end{bmatrix}^{\mathsf{T}}$ where $\mathbf{x} = \begin{bmatrix} x_1 & x_2 & \cdots & x_k \end{bmatrix}^{\mathsf{T}}$.*

Definition 4. *Let l be any positive integer. A function $g\colon \mathbb{R}^{k_0} \to \mathbb{R}^{k_l}$ is said to be an l-layer ReLU network if there exist weights $\mathbf{W}_i \in \mathbb{R}^{k_i \times k_{i-1}}$ and $\mathbf{b}_i \in \mathbb{R}^{k_i}$ for $i \in [l]$ such that the input-output relationship of the network satisfies $g(\mathbf{x}) = h_l(\mathbf{x})$ where $h_1(\mathbf{x}) = \mathbf{W}_1 \mathbf{x} + \mathbf{b}_1$ and $h_i(\mathbf{x}) = \mathbf{W}_i \sigma_{k_{i-1}} \left(h_{i-1}(\mathbf{x}) \right) + \mathbf{b}_i$ for every $i \in [l] \setminus [1]$.*

Definition 5. *The sum $\sum_{l=1}^{L-1} k_l$ and the maximum $\max_{l\in[L-1]} k_l$ for $L > 1$ are referred to as the number of hidden neurons and the maximum width of an L-layer ReLU network, respectively. Any*

172 *1-layer ReLU network is said to have* 0 *hidden neurons and a maximum width of* 0. *An l-layer ReLU*
173 *network is said to have depth* l *and* $l - 1$ *hidden layers.*

3 Upper bounds on neural complexity for representing CPWL functions

175 The correspondence between CPWL functions and ReLU networks was first clearly confirmed by
176 Theorem 2.1 in [Arora et al., 2018] although a weaker version of the correspondence can be inferred
177 from Proposition 4.1 in [Goodfellow et al., 2013]. Arora et al. [2018] proved that every ReLU
178 network $\mathbb{R}^n \to \mathbb{R}$ exactly represents a CPWL function, and the converse is also true, i.e., every
179 CPWL function can be exactly represented by a ReLU network. One of the key steps used by Arora
180 et al. [2018] to construct a ReLU network from any given CPWL function relies on an important
181 representation result by Wang and Sun [2005], stating that any CPWL function can be represented by
182 a sum of a finite number of *max-η-affine* functions [Magnani and Boyd, 2009] whose sign may be
183 flipped and η is bounded from above by $n + 1$. The implication of using this representation is later
184 discussed in Section 4.1. The bound $\eta \le n + 1$ in the representation allowed Arora et al. [2018] to
185 further prove that there exists a ReLU DNN with at most

$$\lceil \log_2(n + 1) \rceil \tag{1}$$

186 hidden layers to exactly realize any given CPWL function. However, the computational resource
187 required for a ReLU network to exactly represent any CPWL function had not been available in the
188 literature until the work by He et al. [2020].

3.1 Upper bounds in prior work

190 He et al. [2020] proved that a CPWL function $\mathbb{R}^n \to \mathbb{R}$ with q pieces and k linear components can
191 be represented by a ReLU network whose number of neurons is given by

$$\mathcal{O}\left(n2^{kq+(n+1)(k-n-1)}\right) \tag{2}$$

192 for $k \ge n + 1$ and

$$\mathcal{O}\left(n2^{kq}\right) \tag{3}$$

193 for $k < n + 1$. The number of hidden layers in such a ReLU DNN is also bounded from above
194 by $\lceil \log_2(n + 1) \rceil$, the same as the bound derived by Arora et al. [2018]. One of their significant
195 contributions in our view is that they utilize the number of pieces and linear components of a CPWL
196 function to bound the complexity of the equivalent ReLU network. In general, the number of pieces
197 q is much larger than the number of linear components k for a CPWL function. He et al. [2020] also
198 proved the relationship

$$k \le q \le k! \tag{4}$$

199 for any CPWL function. Note that the bounds in (4) on the number of pieces q and linear components k
200 were first mentioned by Tarela and Martinez [1999] who developed the lattice representation of CPWL
201 function. Asymptotically, the bounds in (2) and (3) are amplified linearly with the input dimension n
202 for any fixed k. Due to (4), they can be further bounded from above by $\mathcal{O}\left(n2^{q^2+(n+1)(q-n-1)}\right)$ and
203 $\mathcal{O}\left(n2^{q^2}\right)$ in terms of q and n. On the other hand, in terms of k and n, they can be further bounded
204 from above by $\mathcal{O}\left(n2^{k \cdot k!+(n+1)(k-n-1)}\right)$ and $\mathcal{O}\left(n2^{k \cdot k!}\right)$. Because these bounds grow much faster
205 than exponential growth, they seems to suggest that the cost of computing a CPWL function via a
206 ReLU network is exceptionally high.

207 Hertrich et al. [2021] proved that any CPWL function $\mathbb{R}^n \to \mathbb{R}$ with q pieces can be represented by a
208 ReLU network whose maximum width is $\mathcal{O}\left(q^{2n^2+3n+1}\right)$ under the same number of hidden layers
209 $\lceil \log_2(n + 1) \rceil$. Hence, the number of hidden neurons must be bounded from above by

$$\mathcal{O}\left(q^{2n^2+3n+1} \log_2(n + 1)\right). \tag{5}$$

210 Note that we infer this bound by taking the product of the depth and the maximum width. The
211 bound given by (5) can grow slower than $\mathcal{O}\left(n2^{q^2}\right)$, but it grows faster than $\mathcal{O}\left(n2^{q^2}\right)$ if the input
212 dimension n grows sufficiently faster than the number of pieces q. Bounds expressed in terms of the
213 number of distinct linear components were not given in [Hertrich et al., 2021].

3.2 Improved upper bounds

We show that any CPWL function can be represented by a ReLU network whose number of hidden neurons is bounded by much slower growth functions. We state our main results in Theorem 1, 2 and 3, and focus on their impact in this subsection. Each one of them is tailored to a specific complexity measure of the CPWL function. Their proof sketches are deferred to Section 4.2. We first focus on the case when the number of linear components is unknown and the complexity of the CPWL is only measured by the number of pieces, a scenario used in [Hertrich et al., 2021].

Theorem 1. *Any CPWL function* $p\colon \mathbb{R}^n \to \mathbb{R}$ *with* q *pieces can be represented by a ReLU network whose number of layers* l, *maximum width* w, *and number of hidden neurons* h *satisfy*

$$l \leq 2 \lceil \log_2 q \rceil + 1, \tag{6}$$

$$w \leq \mathbb{I}\left[q > 1\right] \left\lceil \frac{3q}{2} \right\rceil q, \tag{7}$$

and

$$h \leq \left(3 \cdot 2^{\lceil \log_2 q \rceil} + 2 \lceil \log_2 q \rceil - 3\right) q + 3 \cdot 2^{\lceil \log_2 q \rceil} - 2 \lceil \log_2 q \rceil - 3. \tag{8}$$

Furthermore, Algorithm 1 finds such a network.

Algorithm 1 Find a ReLU network that computes a given continuous piecewise linear function

---

Input: A continuous piecewise linear function p with pieces $\{\mathcal{X}_i\}_{i \in [q]}$ of $\mathbb{R}^n$ satisfying Definition 1.
Output: A ReLU network g computing $g(\mathbf{x}) = p(\mathbf{x}), \forall \mathbf{x} \in \mathbb{R}^n$.
1: $f_1, f_2, \cdots, f_m \leftarrow$ Find all distinct linear components of p
2: **for** $i = 1, 2, \cdots, q$ **do**
3:     $\mathcal{A}_i \leftarrow \emptyset$
4:     **for** $j = 1, 2 \cdots, m$ **do**
5:         **if** $f_j(\mathbf{x}) \geq p(\mathbf{x}), \forall \mathbf{x} \in \mathcal{X}_i$ **then**
6:             $\mathcal{A}_i \leftarrow \mathcal{A}_i \bigcup \{j\}$
7:         **end if**
8:     **end for**
9:     $v_i \leftarrow$ run Algorithm 2 with $\{f_k\}_{k \in \mathcal{A}_i}$ using the minimum type
10: **end for**
11: $v \leftarrow$ run Algorithm 3 with $v_1, v_2, \cdots, v_q$ ▷ Combine q ReLU networks in parallel
12: $u \leftarrow$ run Algorithm 2 with $\left\{\begin{bmatrix} s_1 & s_2 & \cdots & s_q \end{bmatrix}^{\mathsf{T}} \mapsto s_k\right\}_{k \in [q]}$ using the maximum type
13: $g \leftarrow$ run Algorithm 4 with v and u ▷ Find a ReLU network for the composition $u \circ v$

The proof of Theorem 1 is deferred to Appendix B.4 in the supplementary material. Algorithm 4, 2 and 3 used by Algorithm 1 are deferred to Appendix C in the supplementary material and will be discussed later. Because $2^{\lceil \log_2 q \rceil} < 2q$, the upper bound in (8) can be further bounded from above by $6q^2 + 2 \lceil \log_2 q \rceil q + 3q - 2 \lceil \log_2 q \rceil - 3$, leading to the asymptotic bounds $l = \mathcal{O}(\log_2 q)$, $w = \mathcal{O}(q^2)$, and $h = \mathcal{O}(q^2)$. Since the bound given by Theorem 5.2 in He et al. [2020] can be lower bounded by $\mathcal{O}\left(n2^{q^2}\right)$, it grows exponentially faster than our bound of h given in Theorem 1. On the other hand, the upper bound given by (5) is at least polynomially larger than our bound of h and the order of this polynomial grows quadratically with the input dimension n. Note that such a polynomial becomes an exponential when the growth in n is not slower than q. Such differences are illustrated by the figure on the left-hand side of Figure 1. The bounds in Theorem 1 are independent of the input dimension n. Hence, one can realize any given CPWL function using a relatively small ReLU network even though the input dimension n is huge.

In terms of the maximum width, the upper bound given by (7) is at least polynomially smaller than the one given by Hertrich et al. [2021]. In contrast to the bound for the number of layers in [Arora et al., 2018, He et al., 2020, Hertrich et al., 2021] that grows logarithmically with the input dimension n, our bound in Theorem 1 grows logarithmically with the number of pieces q. Therefore, the ReLU network found by Algorithm 1 in general becomes deeper when the CPWL becomes more complex for a fixed

Figure 2: Left: The upper bound of h in Theorem 3 grows much slower when n grows sufficiently slower than k, leading to a much better upper bound compared to the worst-case asymptotic bound $\mathcal{O}\left(k \cdot k!\right)$ in Theorem 3. Middle: the bound in (5) inferred from [Hertrich et al., 2021] using the bound $\phi(n, k)$ for q. Right: Theorem 5.2 in [He et al., 2020].

input dimension. On the other hand, the network remains the same depth even for arbitrarily larger n as long as q is fixed. Taking an affine function for example, an 1-layer ReLU network with 0 hidden neurons is the solution given by Theorem 1. However, the bound given by [Arora et al., 2018, He et al., 2020, Hertrich et al., 2021] keeps increasing the depth for a larger n.

Algorithm 1 directly follows from the proof of Theorem 2. Notice that the distinct linear components $f_1, f_2, \cdots, f_m$ and a family of index sets $\{\mathcal{A}_i\}_{i \in [q]}$ in Algorithm 1 are important information allowing us to be able to construct a ReLU network satisfying the bounds in Theorem 1 (and Theorem 2 as well). Each one of distinct linear components can be easily found by solving a least square problem when the pieces $\{\mathcal{X}_i\}_{i \in [q]}$ are given. Every least square problem here has a unique solution because the the interior of each of pieces is nonempty. The nonemptyness is guaranteed by Lemma 15 in Appendix A in the supplementary material. Algorithm 2 finds a ReLU network that computes a *max-affine* or *min-affine* function [Magnani and Boyd, 2009]. Algorithm 3 concatenates two given ReLU networks in parallel and returns another ReLU network computing the concatenation of two outputs. Algorithm 4 finds a ReLU network that represents a composition of two given ReLU networks. These algorithms are basic manipulations of ReLU networks required in Algorithm 1.

Theorem 2 discusses the case when the number of linear components and pieces are both known.

Theorem 2. *Any CPWL function $p \colon \mathbb{R}^n \to \mathbb{R}$ with k linear components and q pieces can be represented by a ReLU network whose number of layers l, maximum width w, and number of hidden neurons h satisfy $l \leq \lceil \log_2 q \rceil + \lceil \log_2 k \rceil + 1$, $w \leq \mathbb{I}\left[k > 1\right] \left\lceil \frac{3k}{2} \right\rceil q$, and*

$$h \leq \left(3 \cdot 2^{\lceil \log_2 k \rceil} + 2\lceil \log_2 k \rceil - 3\right) q + 3 \cdot 2^{\lceil \log_2 q \rceil} - 2\lceil \log_2 k \rceil - 3. \tag{9}$$

Furthermore, Algorithm 1 finds such a network.

The proof of Theorem 2 is deferred to Appendix B.3 in the supplementary material. The bounds in Theorem 2 are in general tighter and always no worse than those in Theorem 1 because q is never less than k but can be much larger than k. Asymptotically, $l = \mathcal{O}(\log_2 q)$, $w = \mathcal{O}(kq)$, and $h = \mathcal{O}(kq)$. The bound given by Theorem 5.2 in He et al. [2020] increases exponentially faster than the bound of h in Theorem 2.

When the number of linear components is the only complexity measure of the CPWL function, we resort to Theorem 3 below.

Theorem 3. *Any CPWL function $p \colon \mathbb{R}^n \to \mathbb{R}$ with k linear components can be represented by a ReLU network whose number of layers l, maximum width w, and number of hidden neurons h satisfy $l \leq \lceil \log_2 \phi(n, k) \rceil + \lceil \log_2 k \rceil + 1$, $w \leq \mathbb{I}\left[k > 1\right] \left\lceil \frac{3k}{2} \right\rceil \phi(n, k)$,*

$$h \leq \left(3 \cdot 2^{\lceil \log_2 k \rceil} + 2\lceil \log_2 k \rceil - 3\right) \phi(n, k) + 3 \cdot 2^{\lceil \log_2 \phi(n, k) \rceil} - 2\lceil \log_2 k \rceil - 3, \tag{10}$$

and

$$\phi(n, k) = \min\left(\sum_{i=0}^{n} \binom{\frac{k^2 - k}{2}}{i}, k!\right). \tag{11}$$

The proof of Theorem 3 is deferred to Appendix B.5 in the supplementary material. Because $\phi(n,k) \leq k!$, the worst-case asymptotic bounds for l, w and h are $l = \mathcal{O}(k \log_2 k)$, $w = \mathcal{O}(k \cdot k!)$, and $h = \mathcal{O}(k \cdot k!)$, respectively. However, it holds that $\sum_{i=0}^{n} \binom{\frac{k^2-k}{2}}{i} \leq k^{2n}$, so the asymptotic bounds are $l = \mathcal{O}(n \log_2 k)$, $w = \mathcal{O}(k^{2n+1})$, and $h = \mathcal{O}(k^{2n+1})$ when n grows sufficiently slower than k. For example, $n = \mathcal{O}(\sqrt{k})$. In this case, w and h are bounded from above by a polynomial of order $2\sqrt{k} + 1$, which grows slower than factorial growth. Such an advantage for small n is illustrated by the figure on the left-hand side of Figure 2.

Since the bound given by Theorem 5.2 in [He et al., 2020] can be bounded from below by $\mathcal{O}(n2^{k \cdot k!})$, it at the minimum grows exponentially larger than the upper bound of h in Theorem 3. For sufficiently small n, the relative order of growth is even larger. The figure on the right-hand side of Figure 2 illustrates such a large difference. For $k = 5$, $n2^{k \cdot k!} \approx 7.92 \times 10^{28}$ if $n = 1$, while our bound of h is less than 3.7×10^3 for any n. The difference is extremely large even though k is small under $n = 1$. The middle plot in Figure 2 shows that (5) increases much faster when n becomes larger. The upper bound of h in Theorem 3 is better than (5) for any n, which can be clearly seen from Figure 2.

Lemma 1. *Let $\mathcal{P}_{n,k}$ be the set of all CPWL functions with exactly k distinct linear components such that $p \colon \mathbb{R}^n \to \mathbb{R}, \forall p \in \mathcal{P}_{n,k}$. Let $\mathcal{C}_{n,k}(p)$ be the collection of all families of closed convex subsets satisfying Definition 1 for any $p \in \mathcal{P}_{n,k}$. Then, $k \leq \min_{\mathcal{Q} \in \mathcal{C}_{n,k}(p)} |\mathcal{Q}| \leq \phi(n,k)$.*

The proof of Lemma 1 is deferred to Appendix B.1 in the supplementary material. Clearly, $\phi(n,k)$ is a better upper bound of q compared to the bound $q \leq k!$ given by He et al. [2020]. When n grows sufficiently slower than k, the bound $\phi(n,k)$ can be exponentially smaller than $k!$.

Although the upper bounds in our main results are much better, it is still possible to find a ReLU network whose hidden neurons are fewer than the bounds in Theorem 2 to exactly represent a given CPWL function. Tight bounds for the case when $n = 1$ was first given by Theorem 2.2 in [Arora et al., 2018]. However, it seems more difficult to bound the size of a network from below for a high dimensional input. To the best of our knowledge, we are not aware of any tight bounds in the literature for the exact ReLU network representation of general CPWL functions using an arbitrary n.

4 Representations of CPWL functions have different implications on depth

We reveal implications of using different representations of CPWL functions and their impact on constructing ReLU networks. We first discuss the popular representation used by prior work and the implicit constraint imposed by such a representation.

4.1 Constrained depth

Arora et al. [2018], He et al. [2020], and Hertrich et al. [2021] proved the same bound for the number of layers and the work relies on the following representation of CPWL function:

$$p(\mathbf{x}) = \sum_{j=1}^{J} \sigma_j \max_{i \in \eta(j)} f_i(\mathbf{x}) \tag{12}$$

where $\sigma_j \in \{+1, -1\}$ and $\eta(j)$ is a subset of $[J]$ such that $|\eta(j)| \leq n + 1$ for all $j \in [J]$. That is, a sum of a finite number of *max-η-affine* functions whose sign may be flipped. (12) was established by Theorem 1 in Wang and Sun [2005] which is essentially the same as Theorem 1 in Wang [2004] that emphasizes on the difference of two convex piecewise linear functions. This result was also used by Goodfellow et al. [2013] for the maxout network (Proposition 4.1).

The depth given by (1) does not scale with the complexity of the CPWL function. This feature directly comes from using a ReLU network to realize each of *max-η-affine* functions in (12) and concatenating all of them together. Because the size of $\eta(j)$ is bounded from above by $n + 1$, the depth can be made to depend solely on n. Such a treatment seems to be the only way if one considers a CPWL function represented by (12). As a result, the ReLU network is forced to use a depth constrained by the input dimension to represent the given CPWL function, which in turn requires more hidden neurons. Because we do not use (12), our networks are not limited by such an implication.

4.2 Proof sketch for unconstrained depth

We give a proof sketch in this subsection for our main results. By using a different representation, the depth of a ReLU network is able to be scaled with the complexity measure, i.e., number of pieces, of any given CPWL function to accommodate the high expressivity.

By Theorem 4.2 in [Tarela and Martinez, 1999], any CPWL function p can be represented as

$$p(\mathbf{x}) = \max_{\mathcal{X} \in \mathcal{Q}} \min_{i \in \mathcal{A}(\mathcal{X})} f_i(\mathbf{x}) \tag{13}$$

for all $\mathbf{x} \in \mathbb{R}^n$ where $\mathcal{A}(\mathcal{X}) = \left\{ i \in [k] \,|\, f_i(\mathbf{x}) \geq p(\mathbf{x}), \forall \mathbf{x} \in \mathcal{X} \right\}$ is the set of indices of linear components that have values greater than or equal to $p(\mathbf{x})$ for all $\mathbf{x} \in \mathcal{X}$, and $\mathcal{Q}$ is any family of closed convex subsets of $\mathbb{R}^n$ satisfying Definition 1. We have used $f_1, f_2, \cdots, f_k$ to denote the k distinct linear components of p. Notice that Theorem 4.2 in [Tarela and Martinez, 1999] was first stated by Theorem 7 in [Tarela et al., 1990]. Both are essentially the same, but Theorem 4.2 in [Tarela and Martinez, 1999] emphasizes the convexity of each of regions in the domain. Both theorems are also fundamentally equivalent to Theorem 2.1 in [Ovchinnikov, 2002]. Notice that one of the concluding remarks in [Ovchinnikov, 2002] pointed out that the convexity of the input space is an essential assumption. The entire space $\mathbb{R}^n$ satisfies such an assumption. In addition, Ovchinnikov pointed out that the max-min representation also holds for vector-valued CPWL functions. Hence, it is possible to generalize the bounds in our results to vector-valued CPWL functions.

Using the representation in (13) and Lemma 2 below, we are able to prove Theorem 2 by bounding the size of $\mathcal{Q}$ and $\mathcal{A}(\mathcal{X})$. Theorem 1 and 3 can be proved by applying Lemma 1 to Theorem 2. Note that the size $|\mathcal{Q}|$ in (13) is the key for the depth of a ReLU network to be able to scale with q.

Lemma 2. *Let m be any positive integer. Define $l(m) = \lceil \log_2 m \rceil + 1$, $w(m) = \mathbb{I}\left[m > 1\right]\left\lceil \frac{3m}{2} \right\rceil$, and the following sequence for any positive integer k,*

$$r(k) = \begin{cases} 0, & \text{if } k = 1 \\ \frac{3k}{2} + r\left(\frac{k}{2}\right), & \text{if } k \text{ is even} \\ 2 + \frac{3(k-1)}{2} + r\left(\frac{k+1}{2}\right), & \text{if } k \neq 1 \text{ and } k \text{ is odd} \end{cases} \tag{14}$$

Then, there exists an $l(m)$-layer ReLU network $g \colon \mathbb{R}^n \to \mathbb{R}$ with $r(m)$ hidden neurons and a maximum width of $w(m)$ such that g computes the extremum of $f_1(\mathbf{x}), f_2(\mathbf{x}), \cdots, f_m(\mathbf{x})$, i.e., $g(\mathbf{x}) = \max_{i \in [m]} f_i(\mathbf{x})$ or $g(\mathbf{x}) = \min_{i \in [m]} f_i(\mathbf{x})$ for all $\mathbf{x} \in \mathbb{R}^n$ under any m scalar-valued affine functions $f_1, f_2, \cdots, f_m$. Furthermore, Algorithm 2 finds such a network.

The proof of Lemma 2 is deferred to Appendix B.2 in the supplementary material. One can also view $l(m)$, $w(m)$, and $r(m)$ as upper bounds for the number of layers, maximum width, and the number of hidden neurons. Because $r(m) < 6m - 3$ by Lemma 6, the bound for the number of hidden neurons $r(m)$ is tighter than the bound $8m - 4$ given by Lemma D.3 in [Arora et al., 2018] or Lemma 5.4 in [He et al., 2020] (these two lemmas are essentially the same). The bound for the number of layers remains the same as the one given by Lemma D.3 in [Arora et al., 2018]. By combining Lemma 2 with Lemma 3, Lemma 4, and Lemma 8, we can easily perform the same job on computing the extremum of multiple scalar-valued ReLU networks as Lemma D.3 does in [Arora et al., 2018]. Lemma 6, 3, 4, and 8 are given in Appendix A in the supplementary material.

5 Broader impact

Our results guarantee that any CPWL function can be exactly computed by a ReLU neural network at a more manageable cost. This assurance is crucial because CPWL functions are important tools in many applications. Such an assurance also relates DNNs closer to CPWL functions and allows researchers and engineers to understand the expressivity of DNNs from a different perspective. We focus on ReLU networks in this paper, but it is possible to derive bounds with similar asymptotic growth rates for other neural network architectures such as maxout networks [Goodfellow et al., 2013], residual networks [He et al., 2016], densely connected networks [Huang et al., 2017], and other nonlinear networks [Chen et al., 2021]. Our contributions advance the fundamental understanding of the link between ReLU networks and CPWL functions.

References

R. Arora, A. Basu, P. Mianjy, and A. Mukherjee. Understanding deep neural networks with rectified linear units. In *International Conference on Learning Representations*, 2018.

K.-L. Chen, C.-H. Lee, H. Garudadri, and B. D. Rao. ResNEsts and DenseNEsts: Block-based DNN models with improved representation guarantees. In *Advances in Neural Information Processing Systems*, pages 3413–3424, 2021.

L. O. Chua and A.-C. Deng. Canonical piecewise-linear representation. *IEEE Transactions on Circuits and Systems*, 35(1):101–111, 1988.

G. Cybenko. Approximation by superpositions of a sigmoidal function. *Mathematics of Control, Signals and Systems*, 2(4):303–314, 1989.

R. Eldan and O. Shamir. The power of depth for feedforward neural networks. In *Conference on Learning Theory*, pages 907–940. PMLR, 2016.

K. Fukushima. Neocognitron: A self-organizing neural network model for a mechanism of pattern recognition unaffected by shift in position. *Biological Cybernetics*, 36(4):193–202, 1980.

I. Goodfellow, D. Warde-Farley, M. Mirza, A. Courville, and Y. Bengio. Maxout networks. In *International Conference on Machine Learning*, pages 1319–1327. PMLR, 2013.

B. Hanin and D. Rolnick. Complexity of linear regions in deep networks. In *International Conference on Machine Learning*, pages 2596–2604. PMLR, 2019a.

B. Hanin and D. Rolnick. Deep ReLU networks have surprisingly few activation patterns. In *Advances in Neural Information Processing Systems*, 2019b.

J. He, L. Li, J. Xu, and C. Zheng. ReLU deep neural networks and linear finite elements. *Journal of Computational Mathematics*, 38(3):502–527, 2020.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Conference on Computer Vision and Pattern Recognition*, pages 770–778. IEEE, 2016.

C. Hertrich, A. Basu, M. Di Summa, and M. Skutella. Towards lower bounds on the depth of ReLU neural networks. In *Advances in Neural Information Processing Systems*, 2021.

P. Hinz. *An analysis of the piece-wise affine structure of ReLU feed-forward neural networks*. PhD thesis, ETH Zurich, 2021.

P. Hinz and S. van de Geer. A framework for the construction of upper bounds on the number of affine linear regions of relu feed-forward neural networks. *IEEE Transactions on Information Theory*, 65(11):7304–7324, 2019.

K. Hornik, M. Stinchcombe, and H. White. Multilayer feedforward networks are universal approximators. *Neural Networks*, 2(5):359–366, 1989.

G. Huang, Z. Liu, L. Van Der Maaten, and K. Q. Weinberger. Densely connected convolutional networks. In *Conference on Computer Vision and Pattern Recognition*, pages 4700–4708. IEEE, 2017.

W.-L. Hwang and A. Heinecke. Un-rectifying non-linear networks for signal representation. *IEEE Transactions on Signal Processing*, 68:196–210, 2019.

A. Krizhevsky, I. Sutskever, and G. E. Hinton. ImageNet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems*, pages 1097–1105, 2012.

Z. Lu, H. Pu, F. Wang, Z. Hu, and L. Wang. The expressive power of neural networks: A view from the width. In *Advances in Neural Information Processing Systems*, 2017.

A. L. Maas, A. Y. Hannun, and A. Y. Ng. Rectifier nonlinearities improve neural network acoustic models. In *International Conference on Machine Learning*, volume 30, page 3, 2013.

A. Magnani and S. P. Boyd. Convex piecewise-linear fitting. *Optimization and Engineering*, 10(1): 1–17, 2009.

V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

G. Montúfar. Notes on the number of linear regions of deep neural networks. In *International Conference on Sampling Theory and Applications*, 2017.

G. Montúfar, R. Pascanu, K. Cho, and Y. Bengio. On the number of linear regions of deep neural networks. In *Advances in Neural Information Processing Systems*, pages 2924–2932, 2014.

V. Nair and G. E. Hinton. Rectified linear units improve restricted boltzmann machines. In *International Conference on Machine Learning*, pages 807–814, 2010.

S. Ovchinnikov. Max-min representation of piecewise linear functions. *Contributions to Algebra and Geometry*, 43(1):297–302, 2002.

R. Pascanu, G. Montúfar, and Y. Bengio. On the number of response regions of deep feed forward networks with piece-wise linear activations. *International Conference on Learning Representations*, 2014.

M. Raghu, B. Poole, J. Kleinberg, S. Ganguli, and J. Sohl-Dickstein. On the expressive power of deep neural networks. In *International Conference on Machine Learning*, pages 2847–2854. PMLR, 2017.

D. Rolnick and K. Kording. Reverse-engineering deep ReLU networks. In *International Conference on Machine Learning*, pages 8178–8187. PMLR, 2020.

O. Ronneberger, P. Fischer, and T. Brox. U-Net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

T. Serra, C. Tjandraatmadja, and S. Ramalingam. Bounding and counting linear regions of deep neural networks. In *International Conference on Machine Learning*, pages 4558–4566. PMLR, 2018.

D. Silver, A. Huang, C. J. Maddison, A. Guez, L. Sifre, G. Van Den Driessche, J. Schrittwieser, I. Antonoglou, V. Panneershelvam, M. Lanctot, S. Dieleman, D. Grewe, J. Nham, N. Kalchbrenner, I. Sutskever, T. Lillicrap, M. Leach, K. Kavukcuoglu, T. Graepel, and D. Hassabis. Mastering the game of Go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016.

K. Simonyan and A. Zisserman. Very deep convolutional networks for large-scale image recognition. In *International Conference on Learning Representations*, 2015.

J. Tarela and M. Martinez. Region configurations for realizability of lattice piecewise-linear models. *Mathematical and Computer Modelling*, 30(11-12):17–27, 1999.

J. Tarela, E. Alonso, and M. Martinez. A representation method for PWL functions oriented to parallel processing. *Mathematical and Computer Modelling*, 13(10):75–83, 1990.

M. Telgarsky. Benefits of depth in neural networks. In *Conference on learning theory*, pages 1517–1539. PMLR, 2016.

G. Vardi, D. Reichman, T. Pitassi, and O. Shamir. Size and depth separation in approximating benign functions with neural networks. In *Conference on Learning Theory*, pages 4195–4223. PMLR, 2021.

A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

S. Wang. General constructive representations for continuous piecewise-linear functions. *IEEE Transactions on Circuits and Systems I: Regular Papers*, 51(9):1889–1896, 2004.

S. Wang and X. Sun. Generalization of hinging hyperplanes. *IEEE Transactions on Information Theory*, 51(12):4425–4431, 2005.

T. Zaslavsky. *Facing up to arrangements: Face-count formulas for partitions of space by hyperplanes*, volume 154. American Mathematical Society, 1975.

M. D. Zeiler, M. Ranzato, R. Monga, M. Mao, K. Yang, Q. V. Le, P. Nguyen, A. Senior, V. Vanhoucke, J. Dean, et al. On rectified linear units for speech processing. In *International Conference on Acoustics, Speech and Signal Processing*, pages 3517–3521. IEEE, 2013.