PROVABLY ROBUST CLASSIFICATION OF ADVERSARIAL EXAMPLES WITH DETECTION

ABSTRACT

Adversarial attacks against deep networks can be defended against either by building robust classifiers or, by creating classifiers that can *detect* the presence of adversarial perturbations. Although it may intuitively seem easier to simply detect attacks rather than build a robust classifier, this has not bourne out in practice even empirically, as most detection methods have subsequently been broken by adaptive attacks, thus necessitating *verifiable* performance for detection mechanisms. In this paper, we propose a new method for jointly training a provably robust classifier and detector. Specifically, we show that by introducing an additional "abstain/detection" into a classifier, we can modify existing certified defense mechanisms to allow the classifier to either robustly classify *or* detect adversarial attacks. We extend the common interval bound propagation (IBP) method for certified robustness under ℓ_∞ perturbations to account for our new robust objective, and show that the method outperforms traditional IBP used in isolation, especially for large perturbation sizes. Specifically, tests on MNIST and CIFAR-10 datasets exhibit promising results, for example with provable robust error less than 63.63% and 67.92%, for 55.6% and 66.37% natural error, for $\epsilon = 8/255$ and $16/255$ on the CIFAR-10 dataset, respectively.

1 INTRODUCTION

Despite popularity and success of deep neural networks in many applications, their performance declines sharply in adversarial settings. Small adversarial perturbations are shown to greatly deteriorate the performance of neural network classifiers, which creates a growing concern for utilizing them in safety critical application where robust performance is key. In adversarial training, different methods with varying levels of computational complexity aim at robustifying the network by finding such *adversarial examples* at each training steps and adding them to the training dataset. While such methods exhibit empirical robustness, they lack verifiable guarantees as it is not provable that a more rigorous adversary, e.g., one that does brute-force enumeration to compute adversarial perturbations, will not be able to cause the classifier to misclassify.

It is thus desirable to provably verify the performance of robust classifiers without restricting the adversarial perturbations by inexact solvers, while restraining perturbations to a class of admissible set, e.g., within an ℓ_∞ norm-bounded ball. Progress has been made by 'complete methods' that use Satisfiability Modulo Theory (SMT) or Mixed-Integer Programming (MIP) to provide exact robustness bounds, however, such approaches are expensive, and difficult to scale to large networks as exhaustive enumeration in the worst case is required (Tjeng et al., 2017; Ehlers, 2017; Xiao et al., 2018). 'Incomplete methods' on the other hand, proceed by computing a differential upper bound on the worst-case adversarial loss, and similarly for the verification violations, with lower computational complexity and improved scalability. Such upper bounds, if easy to compute, can be utilized during the training, and yield provably robust networks with tight bounds. In particular, bound propagation via various methods such as differentiable geometric abstractions (Mirman et al., 2018), convex polytope relaxation (Wong & Kolter, 2018), and more recently in (Salman et al., 2019; Balunovic & Vechev, 2020; Gowal et al., 2018; Zhang et al., 2020), together with other techniques such as semi-definite relaxation, (Fazlyab et al., 2019; Raghunathan et al., 2018), and dual solutions via additional verifier networks (Dvijotham et al., 2018) fall within this category. In particular, recent successful use of Interval Bound Propagation (IBP) as a simple layer-by-layer bound propagation mechanism was shown to be very effective in Gowal et al. (2018), which despite its light computational com-

plexity exhibits SOTA robustness verification. Additionally, combining IBP in a forward bounding pass with linear relaxation based backward bounding pass (CROWN) Zhang et al. (2020) leads to improved robustness, although it can be up to 3-10 times slower.

Alternative to robust classification, detection of adversarial examples can also provide robustness against adversarial attacks, where suspicious inputs will be flagged and the classifier "rejects/abstains" from assigning a label. The situation in the literature on the detection of adversarial examples is quite different from above. Most techniques that attempt to detect adversarial examples, either by training explicit classifiers to do so or by simply formulating "hand-tuned" detectors, still largely look to identify and exploit statistical properties of adversarial examples that appear in practice Smith & Gal (2018); Roth et al. (2019). However, to provide a fair evaluation, a defense must be evaluated under attackers that attempt to fool both the classifier *and* the detector, while addressing particular characteristics of a given defense, e.g., gradient obfuscation, non-differentiability, randomization, and simplifying the attacker's objective for increased efficiency. A non-exhaustive list of recent detection methods entails randomization and sparsity-based defenses (Xiao et al., 2019; Roth et al., 2019; Pang et al., 2019b), confidence and uncertainty-based detection (Smith & Gal, 2018; Stutz et al., 2020), transformation-based defenses (Bafna et al., 2018; Yang et al., 2019), ensemble methods (Verma & Swami, 2019; Pang et al., 2019a), generative adversarial training Yin et al. (2020), and many more. Unfortunately, existing defenses have largely proven to have poor performance against adaptive attacks (Athalye et al., 2018; Tramer et al., 2020), necessitating provable performance guarantees on detectors as well. Recently Laidlaw & Feizi (2019) have proposed joint training of classifier and detector, however this work also does not provided any provable guarantees.

Our contribution. In this work, we propose a new method for jointly training a provably robust classifier and detector. Specifically, by introducing an additional "abstain/detection" into a classifier, we show that the existing certified defense mechanisms can be modified, and by building on the detection capability of the network, classifier can effectively *choose* to either robustly classify *or* detect adversarial attacks. We extend the light-weight Interval Bound Propagation (IBP) method to account for our new robust objective, enabling verification of the network for provable performance guarantees. Our proposed robust training objective is also effectively upper bounded, enabling its incorporation into the training procedure leading to tight provably robust performance. While tightening of the bound propagation may be additionally possible for tighter verification, to the best of our knowledge, our approach is the first method to extend certification techniques by considering *detection* while providing *provable* verification. By stabilizing the training, as also used in similar IBP-based methods, experiments on MNIST and CIFAR-10 empirically show that the proposed method can successfully leverage its detection capability, and improves traditional IBP used in isolation, especially for large perturbation sizes.

2 BACKGROUND AND RELATED WORK

Let us consider an L-layer feed-forward neural network, trained for a K-class classification task. Given input $\mathbf{x}$, it will pass through a sequential model, with h_l denoting the mapping at layer l, recursively parameterized by

$$\mathbf{z}_l = h_l(\mathbf{z}_{l-1}) = \sigma_l(\mathbf{W}_l^\top \mathbf{z}_{l-1} + \mathbf{b}_l), \ l = 1, \cdots, L \quad \mathbf{W}_l \in \mathbb{R}^{n_{l-1} \times n_l}, \quad \mathbf{b}_l \in \mathbb{R}^{n_l} \tag{1}$$

where $\sigma_l(.)$ is a monotonic activation function, $\mathbf{z}_0$ denotes the input, and $\mathbf{z}_L \in \mathbb{R}^K$ is the pre-activation unnormalized K-dimensional output vector ($n_L = K$ and $\sigma_L(.)$ as identity operator), referred to as the logits. Robust classifiers can be obtained by minimizing the worst-case (adversarial) classification loss, formally trained by the following min-max optimization Madry et al. (2017)

$$\underset{\theta}{\text{minimize}} \quad \underset{(\mathbf{x},y) \sim \mathcal{D}}{\mathbb{E}} \left[\underset{\boldsymbol{\delta} \in \Delta_\epsilon}{\max} \ \ell(f_\theta(\mathbf{x} + \boldsymbol{\delta}), y) \right]. \tag{2}$$

where θ denotes network parameters, vector $f_\theta(\mathbf{x}) = \mathbf{z}_L$ is the logit output for input $\mathbf{x}$, $\ell(.)$ is the misclassification loss, e.g., cross-entropy loss, and Δ_ϵ denotes the set of permissible perturbations, e.g., for ℓ_∞-norm ball of radius ϵ giving $\Delta_\epsilon := \{\boldsymbol{\delta} \mid \|\boldsymbol{\delta}\|_\infty \leq \epsilon\}$. Although augmenting the training set with adversarial inputs, obtained by approximately solving the inner maximization in equation 2, empirically leads to improved adversarial robustness Madry et al. (2017); Shafahi et al. (2019); Wong et al. (2019); Zhang et al. (2019), inexact solution of the inner maximization prevents such methods from providing provable guarantees. In critical applications however, provable verification of classification accuracy against a given threat model is crucial.

2.1 PERFORMANCE VERIFICATION AND NETWORK RELAXATION

Given input $(\mathbf{x}, y)$, a classification network is considered verifiably robust if all of its perturbed variations, that is $\mathbf{x} + \boldsymbol{\delta}$ for $\forall \boldsymbol{\delta} \in \Delta_\epsilon$, are correctly classified as class y. Such verification can be effectively obtained by

$$p_i^* = \min_{\mathbf{z}_L \in \mathcal{Z}_L} \mathbf{c}_{y,i}^\top \mathbf{z}_L \quad \text{where}, \quad \mathcal{Z}_L := \{\mathbf{z}_L | \mathbf{z}_l = h_l(\mathbf{z}_{l-1}), \ l = 1, ..., L, \ \mathbf{z}_0 = \mathbf{x} + \boldsymbol{\delta}, \ \forall \boldsymbol{\delta} \in \Delta_\epsilon\}$$

where $\mathbf{c}_{y,i} = \mathbf{e}_y - \mathbf{e}_i$ for $i = 1, 2, .., K, i \neq y$, and $\mathbf{e}_i$ is the standard i^{th} canonical basis vector. If $p_i^* > 0 \ \forall i \neq y$, then the classifier is verifiably robust at point $(\mathbf{x}, y)$ as this guarantees that $z_i \leq z_y \ \forall i \neq y$ for all admissible perturbations $\boldsymbol{\delta} \in \Delta_\epsilon$.

The feasible set $\mathcal{Z}_L$ is generally nonconvex, rendering obtaining p_i^* intractable. Any convex relaxation of $\mathcal{Z}_L$ however, will provide a lower bound on p_i^*, and can be alternatively used for verification. As outlined in Section 1, various relaxation techniques have been proposed in the literature. Specifically, IBP in (Mirman et al., 2018; Gowal et al., 2018) proceeds by bounding the activation $\mathbf{z}_l$ of each layer by propagating an element-wise bounding box using interval arithmetic for networks with monotonic activation functions. Despite its simplicity and relatively small computational complexity (computational requirements for bound propagation for a given input using IBP is equal to two forward passes of the input), it can provide tight bounds once the network is trained accordingly.

Specifically, starting from the input layer $\mathbf{z}_0$, it can be bounded for the perturbation class $\boldsymbol{\delta} \in \Delta_\epsilon$ as $\underline{\mathbf{z}}_0 = \mathbf{x} - \epsilon \mathbf{1}$ and $\overline{\mathbf{z}}_0 = \mathbf{x} + \epsilon \mathbf{1}$, and $\mathbf{z}_l$ for the following layers can be bounded as

$$\underline{\mathbf{z}}_l = \sigma_l(\mathbf{W}_l^\top \frac{\overline{\mathbf{z}}_{l-1} + \underline{\mathbf{z}}_{l-1}}{2} - |\mathbf{W}_l^\top| \frac{\overline{\mathbf{z}}_{l-1} + \underline{\mathbf{z}}_{l-1}}{2}), \overline{\mathbf{z}}_l = \sigma_l(\mathbf{W}_l^\top \frac{\overline{\mathbf{z}}_{l-1} + \underline{\mathbf{z}}_{l-1}}{2} + |\mathbf{W}_l^\top| \frac{\overline{\mathbf{z}}_{l-1} + \underline{\mathbf{z}}_{l-1}}{2}), \tag{3}$$

where $|.|$ is the element-wise absolute-value operator. The verification problem over the relaxed feasible set $\hat{\mathcal{Z}}_L := \{\mathbf{z}_L \mid \underline{z}_{L,i} \leq z_{L,i} \leq \overline{z}_{L,i}\}$, where $\mathcal{Z}_L \subseteq \hat{\mathcal{Z}}_L$ is then easily solved as

$$p_i^* = \min_{\mathbf{z}_L \in \mathcal{Z}_L} \mathbf{c}_{y,i}^\top \mathbf{z}_L \geq \min_{\mathbf{z}_L \in \hat{\mathcal{Z}}_L} \mathbf{c}_{y,i}^\top \mathbf{z}_L = \underline{z}_{L,y} - \overline{z}_{L,i}. \tag{4}$$

2.2 ROBUST TRAINING OF VERIFIABLE NETWORKS

It has been shown that convex relaxation of $\mathcal{Z}_L$ can also provide a tractable upper bound on the inner maximization in equation 2 for the cross-entropy loss. While this holds for various relaxation techniques, focusing on the IBP let us define

$$\mathbf{J}_{\epsilon,\theta}^{\text{IBP}}(\mathbf{x}, y) := [J_1^{\text{IBP}}, J_2^{\text{IBP}}, ..., J_K^{\text{IBP}}] \quad \text{where} \quad J_i^{\text{IBP}} := \min_{\mathbf{z}_L \in \hat{\mathcal{Z}}_L} \mathbf{c}_{y,i}^\top \mathbf{z}_L \tag{5}$$

with (θ, ϵ) implicitly influencing $\hat{\mathcal{Z}}_L$ and dropped for brevity, and upperbound the inner-max in equation 2

$$\max_{\boldsymbol{\delta} \in \Delta_\epsilon} \ell_{\text{xent}}(f_\theta(\mathbf{x} + \boldsymbol{\delta}), y) \leq \ell_{\text{xent}}(-\mathbf{J}_{\epsilon,\theta}^{\text{IBP}}(\mathbf{x}, y), y). \tag{6}$$

By using this tractable upper bound of the robust optimization, network can now be trained by

$$\underset{\theta}{\text{minimize}} \sum_{(\mathbf{x}, y) \in \mathcal{D}} \kappa \ell_{\text{xent}}(f_\theta(\mathbf{x}), y) + (1 - \kappa) \ell_{\text{xent}}(-\mathbf{J}_{\epsilon,\theta}^{\text{IBP}}(\mathbf{x}, y), y), \tag{7}$$

where κ trades natural versus robust accuracy, and is scheduled through a ramp-down process to stabilize the training and facilitate tightening of IBP Gowal et al. (2018).

3 VERIFIABLE CLASSIFICATION WITH DETECTION

In this paper, we propose a new method for jointly training a provably robust classifier and detector. Specifically, let us augment the classifier by introducing an additional "abstain/detection". This can be readily done by extending the K-class classification task to a $(K+1)$-class classification, with the $(K+1)$-th class dedicated to the detection task. The classifier is then trained such that adversarial examples, or *ideally any other example that the network would misclassify*, are classified in this abstain class, denoted by a, thus preventing incorrect classification.

Formally, the classifier can be denoted as in equation 1, with the only difference that the final output is $K + 1$ dimensional, i.e., $\mathbf{z}_L \in \mathbb{R}^{K+1}$; simply by substituting the last fully-connected weight matrix $\mathbf{W}_L$ of dimension $n_L \times K$ with that of dimension $n_L \times (K + 1)$, and similarly for $\mathbf{b}_L$.

3.1 VERIFICATION PROBLEM FOR CLASSIFICATION WITH ABSTAIN/DETECTION

It is desirable to provably verify performance of the joint classification/detection. In contrast to existing robust classifiers, however, on a perturbed image $\mathbf{x} + \boldsymbol{\delta}$, the classification/detection task is considered successful if the input is classified either as the correct class y, *or* as the abstain class a; as both cases prevent misclassification of the adversarially perturbed input as a wrong class. On clean natural images however, classification/detection is considered successful *only* if it is classified as the correct class y, and abstaining is considered misclassification.

In order to certify performance in adversarial settings, it is now sufficient to verify that the network satisfies the following for a given input pair $(\mathbf{x}, y)$ and perturbation $\boldsymbol{\delta} \in \Delta_\epsilon$:

$$\max\{\mathbf{c}_{y,i}^\top \mathbf{z}, \mathbf{c}_{a,i}^\top \mathbf{z}\} \geq 0 \qquad \forall \mathbf{z} \in \mathcal{Z}_L := \{\mathbf{z}_L | \mathbf{z}_l = h_l(\mathbf{z}_{l-1})\ l = 1, ..., L,\ \mathbf{z}_0 = \mathbf{x} + \boldsymbol{\delta},\ \forall \boldsymbol{\delta} \in \Delta_\epsilon\} \tag{8}$$

where $\mathbf{c}_y := \mathbf{e}_y - \mathbf{e}_i$ and $\mathbf{c}_a := \mathbf{e}_a - \mathbf{e}_i$, a denotes the "abstain" class, and the dependence of $\mathcal{Z}_L$ on $(\mathbf{x}, y, \epsilon, \theta)$ is omitted for brevity. Verification can be done effectively by seeking a counterexample

$$\pi_i^* := \min_{\mathbf{z} \in \mathcal{Z}_L} \quad \max\{\mathbf{c}_{y,i}^\top \mathbf{z}, \mathbf{c}_{a,i}^\top \mathbf{z}\}. \tag{9}$$

If $\pi_i^* \geq 0\ \forall i \neq y$, the specification is then satisfied and the performance is verified.

Similar to previous verification methods, to overcome the non-convexity of the optimization in equation 9, one can lower bound the problem by expanding the feasible set $\mathcal{Z}_L \subseteq \hat{\mathcal{Z}}_L$, where $\hat{\mathcal{Z}}_L$ is convex, as stated in Theorem 1, and proved in Appendix A.1.

Theorem 1: *For any convex $\hat{\mathcal{Z}}_L$ s.t. $\mathcal{Z}_L \subseteq \hat{\mathcal{Z}}_L$, equation 9 can be bounded by the convex relaxation*

$$\max_{0 \leq \eta \leq 1} \min_{\mathbf{z} \in \hat{\mathcal{Z}}_L} \quad \left(\eta\, \mathbf{c}_{a,i} + (1 - \eta)\, \mathbf{c}_{y,i}\right)^\top \mathbf{z} \leq \min_{\mathbf{z} \in \mathcal{Z}_L} \quad \max\{\mathbf{c}_{y,i}^\top \mathbf{z}, \mathbf{c}_{a,i}^\top \mathbf{z}\}. \tag{10}$$

Although Theorem 1 holds for any convex relaxation of $\mathcal{Z}_L$, for IBP relaxation in Gowal et al. (2018) it can be further simplified by substituting $\mathbf{z} = \mathbf{W}_L^\top \mathbf{z}_{L-1} + \mathbf{b}_L$, expressed in terms of convex relaxation of $\mathcal{Z}_{L-1}$ for tighter bounding, and solved analytically as follows.

Theorem 2: *The optimization in equation 9 can be lower-bounded by the convex optimization*

$$J_i(\mathbf{x}, y) = \max_{0 \leq \eta \leq 1} \min_{\mathbf{z}_{L-1} \in \hat{\mathcal{Z}}_{L-1}} \quad (\boldsymbol{\omega}_1 + \eta \boldsymbol{\omega}_2)^\top \mathbf{z}_{L-1} \quad \leq \min_{\mathbf{z} \in \mathcal{Z}_L} \max\{\mathbf{c}_{y,i}^\top \mathbf{z}, \mathbf{c}_{a,i}^\top \mathbf{z}\} \tag{11}$$

in which $\boldsymbol{\omega}_1 := \mathbf{W}_L^\top \mathbf{c}_{y,i}$, $\boldsymbol{\omega}_2 := \mathbf{W}_L^\top (\mathbf{c}_{a,i} - \mathbf{c}_{y,i})$, and convex set $\hat{\mathcal{Z}}_{L-1}$ is a convex relaxation of $\mathcal{Z}_{L-1}$ on the hidden values at $L - 1$. Furthermore, $J_i(\mathbf{x}, y)$ can be analytically obtained with complexity $\mathcal{O}(n_{L-1} \log(n_{L-1}))$ as outlined in Alg. 1

Algorithm 1 Solution for $J_i(\mathbf{x}, y)$ in Theorem 2

1: **Input.** Bounds on layer $L - 1$: $\underline{\mathbf{z}}_{L-1}, \bar{\mathbf{z}}_{L-1}$, and weight matrix $\mathbf{W}_L$
2: $\boldsymbol{\zeta} = [\zeta_1, ..., \zeta_{n_L}] := -\boldsymbol{\omega}_1/\boldsymbol{\omega}_2$ and vector of indices $\mathbf{s}$ that sorts $\boldsymbol{\zeta}$, i.e., $\zeta_{s_1} \leq \cdots \leq \zeta_{s_{n_{L-1}}}$
3: $\boldsymbol{\omega}_1 = \mathbf{W}_L \mathbf{c}_{y,i}$ and $\boldsymbol{\omega}_2 = \mathbf{W}_L (\mathbf{c}_{a,i} - \mathbf{c}_{y,i})$
4: $\underline{\mathbf{u}}_1 = \Pi_\mathbf{s}(\boldsymbol{\omega}_1 \circ \underline{\mathbf{z}}_{L-1})$, $\bar{\mathbf{u}}_1 := \Pi_\mathbf{s}(\boldsymbol{\omega}_1 \circ \bar{\mathbf{z}}_{L-1})$, $\underline{\mathbf{u}}_2 := \Pi_\mathbf{s}(\boldsymbol{\omega}_2 \circ \underline{\mathbf{z}}_{L-1})$, $\bar{\mathbf{u}}_2 := \Pi_\mathbf{s}(\boldsymbol{\omega}_2 \circ \bar{\mathbf{z}}_{L-1})$.
5: $m = \min_{\zeta_{s_j} \geq 0} j$, and $M = \max_{\zeta_{s_j} \leq 1} j$ for $j = 1, ..., n_L$
6: $\alpha_m := \sum_{i=1}^m \underline{u}_{1,i} + \sum_{i=m+1}^{n_{L-1}} \bar{u}_{1,i}$
7: $q_m = \sum_{i=1}^m \underline{u}_{2,i} + \sum_{i=m+1}^{n_{L-1}} \bar{u}_{2,i}$, $\quad \beta_m = \left(\tilde{\zeta}_\nu 1_{\{q_\nu \leq 0\}} + \tilde{\zeta}_{\nu+1} 1_{\{q_\nu > 0\}}\right) \times q_\nu$
8: **for** $\nu = m + 1, ..., M - 1$ **do**
9: $\quad \alpha_\nu = \alpha_{\nu-1} + \underline{u}_{1,\nu} - \bar{u}_{1,\nu}$
10: $\quad q_\nu = q_{\nu-1} + \underline{u}_{2,\nu} - \bar{u}_{2,\nu}$
11: $\quad \beta_\nu = q_\nu \left(\zeta_{s_\nu} 1_{\{q_\nu \leq 0\}} + \zeta_{s_{\nu+1}} 1_{\{q_\nu > 0\}},\right)$
12: **return** $\max_{\nu = m, ..., M-1} \alpha_\nu + \beta_\nu$

Note that since η is the dual variable, any selection within the feasible set would serve as a (looser but valid) lower bound, while the maximization makes the bound tight; see App. A.2 for proof. Similar to other convex relaxation-based verification methods, in order for a trained networks to provide tight verifiable performance, one needs to incorporate bound propagation during training.

4 TRAINING A VERIFIABLE ROBUST CLASSIFICATION WITH DETECTION

In order to train a robust classifier with detection, let us start by formalizing the objective of an adversarial attacker. Naturally, an adaptive attacker's objective is to craft perturbation $\boldsymbol{\delta}$ such that it simultaneously evades detection and causes misclassification. Formally, this can be tackled by seeking $\boldsymbol{\delta}$ such that loss corresponding to the winner of the two classes y and a (higher logit leading to smaller cross-entropy loss) is maximized, i.e.,

$$\max_{\boldsymbol{\delta} \in \Delta} \min \left\{ \ell_{\text{xent}}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), y), \ell_{\text{xent}}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), a) \right\}, \quad \ell_{\text{xent}}(\mathbf{z}, c) := -\log \left(\frac{\exp(z_c)}{\sum_{i \in \mathcal{I}} \exp(z_i)} \right). \quad (12)$$

where $\ell_{\text{xent}}(\mathbf{z}, c)$ denotes the cross-entropy loss for class $c = y$ and $c = a$, and $\mathcal{I} = \{1, 2, ..., K, a\}$ denotes the class index set with $K + 1$ elements.

Let us now define

$$L_{\text{robust}}^{\text{abstain}}(\mathbf{x}, y; \theta) := \max_{\boldsymbol{\delta} \in \Delta} \min \left\{ \ell_{\text{xent}\backslash a}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), y), \ell_{\text{xent}\backslash y}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), a) \right\} \quad (13)$$

in which the inner maximization is closely related to that of the adversarial objective in equation 12 with a small difference: loss terms $\ell_{\text{xent}\backslash a}$ and $\ell_{\text{xent}\backslash y}$ are defined as

$$\ell_{\text{xent}\backslash a}(\mathbf{z}, y) := -\log \left(\frac{\exp(z_y)}{\sum_{i \in \mathcal{I}\backslash\{a\}} \exp(z_i)} \right), \text{ and } \ell_{\text{xent}\backslash y}(\mathbf{x}, a) := -\log \left(\frac{\exp(z_a)}{\sum_{i \in \mathcal{I}\backslash\{y\}} \exp(z_i)} \right).$$

This small alteration to the cost, while not changing the minimization "winner" between the true class y and rejection class a in equation 12 and 13, i.e.,

$$\begin{cases} z_a \leq z_y \Rightarrow & \ell_{\text{xent}}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), y) \leq \ell_{\text{xent}}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), a) \text{ and } \ell_{\text{xent}\backslash a}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), y) \leq \ell_{\text{xent}\backslash y}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), a) \\ z_y \leq z_a \Rightarrow & \ell_{\text{xent}}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), a) \leq \ell_{\text{xent}}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), y) \text{ and } \ell_{\text{xent}\backslash y}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), a) \leq \ell_{\text{xent}\backslash a}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), y) \end{cases}$$

favorably influences the training process. That is so since, for $\boldsymbol{\delta}$ such that, for instance $z_a < z_y$, minimizing $L_{\text{robust}}^{\text{abstain}}(\mathbf{x}, y; \theta)$ during training reduces to minimizing $\ell_{\text{xent}}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), y)$ which in turn leads to further increasing z_y while *decreasing* the logit value z_a; and similarly, increasing z_y while *decreasing* z_y if $z_y < z_a$. Intuitively however, the true objective of the *classifier augmented with detection* on adversarial examples is to increase both z_y and z_a while reducing z_j, $\forall j \neq a, y$; thus preventing any *gap* in between the boundary of the classes a and y, which can potentially lead to successful *adaptive* attacks. Hence, minimizing equation 12 would be in contrast with the true underlying objective, and equation 13 simply prevents the raised issue.

Upon defining $L_{\text{natural}}(\mathbf{x}, y; \theta) := \ell_{\text{xent}}(f_\theta(\mathbf{x}), y)$ and $L_{\text{robust}}(\mathbf{x}, y; \theta) := \max_{\boldsymbol{\delta} \in \Delta} \ell_{\text{xent}}(f_\theta(\mathbf{x}+\boldsymbol{\delta}), y)$, we then define the overall training loss as

$$L = L_{\text{robust}}(\mathbf{x}, y; \theta) + \lambda_1 L_{\text{robust}}^{\text{abstain}}(\mathbf{x}, y; \theta) + \lambda_2 L_{\text{natural}}(\mathbf{x}, y; \theta), \quad (14)$$

where $L_{\text{natural}}(\mathbf{x}, y; \theta)$ captures the misclassification loss of the natural (clean) examples, and $L_{\text{robust}}(\mathbf{x}, y; \theta)$ denotes that of adversarial examples without considering the rejection class, i.e., similar to that of Gowal et al. (2018), and parameters (λ_1, λ_2) trade-off clean and adversarial accuracy. To train a robust classifier, we proceed by minimizing the overall loss equation 14, by first upperbounding $L_{\text{robust}}(\mathbf{x}, y; \theta)$ and $L_{\text{robust}}^{\text{abstain}}(\mathbf{x}, y; \theta)$.

4.1 UPPERBOUNDING THE TRAINING LOSS

Using Theorem 2, and restricting $0 < \underline{\eta} \leq \eta \leq \bar{\eta} < 1$, let us now define $J_i^{\underline{\eta}, \bar{\eta}}(\mathbf{x}, y)$, where trivially

$$J_i^{\underline{\eta}, \bar{\eta}}(\mathbf{x}, y) := \max_{0 \leq \underline{\eta} \leq \eta \leq \bar{\eta} \leq 1} (\boldsymbol{\omega}_1 + \eta \boldsymbol{\omega}_2)^\top \hat{\mathbf{z}}_{L-1} \leq \max_{0 \leq \eta \leq 1} (\boldsymbol{\omega}_1 + \eta \boldsymbol{\omega}_2)^\top \hat{\mathbf{z}}_{L-1} = J_i(\mathbf{x}, y) \quad (15)$$

and can also be solved analytically similar to Theorem 2. By generalizing the findings in Wong & Kolter (2018); Mirman et al. (2018), we can upper bound the robust optimization problem using our dual problem in equation 15, according to the following Theorem, which we prove in Appendix A.3.

Theorem 3: *For any data point* $(\mathbf{x}, y)$, *and* $\epsilon > 0$, *and for any* $0 \leq \underline{\eta} \leq \bar{\eta} \leq 1$, *the adversarial loss* $L_{robust}^{abstain}(\mathbf{x}, y; \theta)$ *in equation 13 can be upper bounded by*

$$L_{\text{robust}}^{\text{abstain}}(\mathbf{x}, y; \theta) \leq \bar{L}_{\text{robust}}^{\text{abstain}}(\mathbf{x}, y; \theta) := \ell_{xent\backslash a}(-\mathbf{J}_{\epsilon, \theta}(\mathbf{x}, y), y) = \ell_{xent\backslash y}(-\mathbf{J}_{\epsilon, \theta}(\mathbf{x}, y), a) \quad (16)$$

where $\mathbf{J}_{\epsilon,\theta}(\mathbf{x}, y)$ is a $(K+1)$-dimensional vector, valued at index i as $[\mathbf{J}_{\epsilon,\theta}(\mathbf{x}, y)]_i = J_i^{\eta,\bar{\eta}}(\mathbf{x}, y)$.

Note that maximization over η for obtaining $J_i^{\eta,\bar{\eta}}(\mathbf{x}, y)$ can be done either by bisection (concave maximization) or by following Alg. 1 and substituting $m = \min_{\zeta_{s_\nu} \geq \underline{\eta}} \nu$, and $M = \max_{\zeta_{s_\nu} \leq \bar{\eta}} \nu$

Remark 2. Setting $\underline{\eta} = \bar{\eta} = 0$ forces $\eta = 0$ which reduces $J_i^{\eta,\bar{\eta}}(\mathbf{x}, y)$ in equation 15 to that in equation 5, .i.e, $J_i^{\text{IBP}}(\mathbf{x}, y) = J_i^{\eta,\bar{\eta}}(\mathbf{x}, y)|_{\underline{\eta}=\bar{\eta}=0}$, also bounding loss term $L_{\text{natural}}(\mathbf{x}, y; \theta)$ as

$$L_{\text{robust}}(\mathbf{x}, y; \theta) \leq \bar{L}_{\text{robust}}(\mathbf{x}, y; \theta) := \ell_{xent}(-\mathbf{J}_{\epsilon,\theta}^{\text{IBP}}(\mathbf{x}, y), y). \tag{17}$$

Remark 3. While setting $\underline{\eta} = 0$ and $\bar{\eta} = 1$ gives tighter bounds, (and is thus used for the verification counterpart in Theorem 2), strictly setting $0 < \underline{\eta} \leq \bar{\eta} < 1$ empirically yields better generalization of the network. This can be intuitively understood by rewriting $\boldsymbol{\omega}_1 + \eta\boldsymbol{\omega}_2 = \mathbf{W}_L^\top(\eta\mathbf{c}_{a,i} + (1-\eta)\mathbf{c}_{y,i})$ which is a convex combination of the verification constraints for the correct and the abstain class. Thus $\eta \neq 0 \neq 1$ will lead to minimizing a combination of both terms, preventing gaps in between the two classes. Also, higher values of η increase the influence of the term corresponding to the abstain case, and vice versa, whose tuning can promote abstaining by considering how desirable such outcome is (or is not).

Utilizing upperbounds in equation 16 and equation 17, we can proceed to training the network by minimizing the tractable upperbound on the overall loss

$$\min_\theta L \leq \min_\theta \ell_{xent}(-\mathbf{J}_{\epsilon,\theta}^{\text{IBP}}(\mathbf{x}, y), y) + \lambda_1 \ell_{xent\backslash y}(-\mathbf{J}_{\epsilon,\theta}(\mathbf{x}, y), a) + \lambda_2 \ell_{\text{natural}}(f_\theta(\mathbf{x}), y) \tag{18}$$

Note that setting $\lambda_1 = 0$ reduces the training to that of Gowal et al. (2018) without detection.

Complexity. Since given IBP bounds on $\mathbf{z}_{L-1}$, the solution to equation 16 is analytically available (that is after sorting whose complexity is negligible in comparison with forward pass), computing equation 18 imposes the same computational complexity as in IBP, which is twice the normal training procedure, as it requires propagating the upper and lower bounds via forward pass.

5 EXPERIMENTS

Empirical performance of the proposed robust classification with detection on MNIST-10 and CIFAR-10 datasets is reported in this section, and is compared with the state-of-the-art alternatives. The training procedure is stabilized as detailed next.

5.1 STABILIZING THE TRAINING PROCEDURE

We incorporate the following mechanisms to stabilize the training procedure in our tests, where the first two have been previously used in (Gowal et al., 2018) and (Zhang et al., 2020) as well.

Ramp down of κ: To stabilize the trade-off between nominal and verified accuracy, let us introduce parameter κ in the overall loss by trading the natural and robust loss as

$$L = (1-\kappa)\underbrace{\left(\bar{L}_{\text{robust}}(\mathbf{x}, y; \theta) + \lambda_1 \bar{L}_{\text{robust}}^{\text{abstain}}(\mathbf{x}, y; \theta)\right)}_{\text{Robust loss}} + \kappa\underbrace{\lambda_2 L_{\text{natural}}(\mathbf{x}, y; \theta)}_{\text{Natural loss}} \tag{19}$$

Setting $\kappa = 0.5$ renders the optimization identical to that in eq. 18. During the training however, we incorporate a ramp down procedure where κ starts at value $\kappa_{\text{start}} = 1$, thus training the model to fit the natural data, and slowly decreasing it to value $\kappa_{\text{end}} = 0.5$, similar to that in Gowal et al. (2018).

Ramp up of ϵ: It is very important during the training process to start at $\epsilon = 0$ and gradually increase it to ϵ_{train}, while also setting ϵ_{train} larger than ϵ_{test} can improve generalization.

Ramp down of $\underline{\eta}$ and $\bar{\eta}$: Setting $0 < \underline{\eta}$ and $\bar{\eta} < 1$ helps with better generalization. Furthermore, setting large $\underline{\eta}$ and $\bar{\eta}$ promotes the abstain class in loss term $\bar{L}_{\text{robust}}^{\text{abstain}}$ by increasing the weight of $\boldsymbol{\omega}_2$ in equation 15. Thus, we can further stabilize the training process through a ramp down procedure where these parameters start at $\underline{\eta} = \underline{\eta}_{\text{start}}$ and $\bar{\eta} = \bar{\eta}_{\text{start}}$, and are gradually reduced to $\underline{\eta} = \underline{\eta}_{\text{end}}$ and $\bar{\eta} = \bar{\eta}_{\text{end}}$, with $\underline{\eta}_{\text{end}} < \underline{\eta}_{\text{start}}$ and $\bar{\eta}_{\text{end}} < \bar{\eta}_{\text{start}}$.

dataset	attack	method	standard err	verified err	pgd-attack-success
MNIST	$\epsilon_{\text{test}} = 0.3$ $\epsilon_{\text{train}} = 0.4$	IBP	2.12	8.47	6.78
		IBP w/ detection	4.34	**5.98**	**4.15**
		Best recorded in literature			
		IBP (Gowal et al., 2018)	1.66	8.21	6.12
		IBP-CROWN (Zhang et al., 2020)	1.82	7.02	6.05
		Xiao et al. (2018)	2.67	19.32	7.95
		Wong & Kolter (2018)	14.87	43.10	–
	$\epsilon_{\text{test}} = 0.4$ $\epsilon_{\text{train}} = 0.4$	IBP	2.74	14.80	11.14
		IBP w/ detection	4.79	**11.29**	**7.55**
		Best recorded in literature			
		IBP (Gowal et al., 2018)	1.66	15.01	10.34
		IBP-CROWN (Zhang et al., 2020)	2.17	12.06	9.47
CIFAR-10	$\epsilon_{\text{test}} = 2/255$ $\epsilon_{\text{train}} = 2.2/255$	IBP	38.54	55.21	49.72
		IBP w/ detection	34.66	57.9	47.2
		Best recorded in literature			
		IBP (Gowal et al., 2018)	29.84	55.88	49.98
		IBP-CROWN (Zhang et al., 2020)	28.48	**46.03**	**40.28**
		Mirman et al. (2018)	38.0	47.8	
		Wong & Kolter (2018)	31.72	46.11	
		Xiao et al. (2018)	38.88	54.07	50.08
	$\epsilon_{\text{test}} = 8/255$ $\epsilon_{\text{train}} = 8.8/255$	IBP	53.69	69.92	65.17
		IBP w/ detection	55.60	**63.63**	**49.22**
		Best recorded in literature			
		IBP (Gowal et al., 2018)	50.51	68.44+	65.23
		IBP-CROWN (Zhang et al., 2020)	54.02	66.94	65.42
		Xiao et al. (2018)	59.55	79.73	73.22
		Wong & Kolter (2018)	71.33	78.22	–
	$\epsilon_{\text{test}} = 16/255$ $\epsilon_{\text{train}} = 16.7/255$	IBP	68.97	78.12	76.66
		IBP w/ detection	66.37	**67.92**	**58.20**
		Best recorded in literature			
		IBP-CROWN (Zhang et al., 2020)	66.06	76.80	75.23

Table 1: The verified, standard (clean), and PGD attack errors for models trained on MNIST and CIFAR-10. IBP with detection is to be compared with IBP (without detection capability) to emphasize the successful utilization of the detection capability of the network in increasing its verifiable as well as empirical performance. For a more detailed decomposition of the standard and robust error terms see Fig. 1.

+ As reported in Zhang et al. (2020), achieving the 68.44% IBP verified error requires extra PGD adversarial training loss, without which the verified error is 72.91% (LP/MIP verified) or 73.52% (IBP verified), thus our result should be compared to 73.52%.

* Best reported numbers for IBP are computed using mixed integer programming (MIP), which are strictly smaller than IBP veified error rates, see table 3 and 4 in Gowal et al. (2018). For fair comparison, we report IBP verified error rates from table 3 therein.

** Best reported results from the literature may use different network architectures, and empirical PGD error rate may have been computed under different settings, e.g., number of steps and restarts.

*** Number in the IBP rows in this table are the best between (Zhang et al., 2020) and our experiments, while results from (Gowal et al., 2018) are reported under best literature record for IBP.

Furthermore, although the term $\bar{L}_{\text{robust}}(\mathbf{x}, y; \theta)$ could in theory be excluded from the training process, as the term $L_{\text{natural}}(\mathbf{x}, y; \theta)$ prevents the degenerate solution of always classifying all images in the abstain class, it's inclusion empirically helps the stability of the training process.

5.2 Empirical results on MNIST and CIFAR10

The classification networks are identical to the large network in Gowal et al. (2018), also detailed in Table 2, trained by minimizing the loss in equation 18 with the above stabilizing schemes. Selection of parameters for each datasets is detailed in Appendix B. Since most recent detector networks have shown very low performance against adaptive attacks, and lack provable performance Tramer et al. (2020), we only compare the performance with other provable robust classification methods, while focusing on the different decomposition in the reported natural and robust accuracy among these two. As numbers in Table 1 suggest, the proposed detection/classification network shows improved robustness against other methods, including IBP in isolation (without the detection capability), specially against larger perturbations in the CIFAR-10 dataset, which intuitively is pleasing: as larger perturbations are naturally more distinguishable, the detection capability of the network is successfully leveraged for improving the adversarial robustness. Let us now take a closer look at the performance by focusing on the detection capability.

(a) Accuracy on natural (clean) images

(b) Verified accuracy on adversarial images

Figure 1: Decomposition of accuracy and verified accuracy on CIFAR-10 dataste: the detection capability of the network can increase robust by adaptively abstaining on adversarial inputs while also abstaining on some natural images rather than misclassifying them.

Effectiveness of the detection class. By nature, the proposed classification "adaptively chooses" between (robust) correct classification and detection of *adversarial* or *difficult* inputs during the training. This gives rise to two phenomena:

(1) In verifiably robust methods, natural image accuracy declines as robustness improves. In the proposed approach however, a considerable number of misclassified natural inputs are in fact *abstained on*, which in certain applications is more favorable than assigning them to a wrong class, as classifiers without detection capability would: compare 30.5% abstain and 25.6% 'wrong-class misclassification' (other than abstain and the correct class) in IBP-with-detection, with that of 53.7% 'wrong-class' misclassification in IBP on natural CIFAR-10 images in networks trained for $\epsilon = 8/255$.

(2) Regardless of the training procedure, the proposed classifier with detection can still be verified using verification in equation 4 to obtain its guaranteed robustness with only considering the correct class. Thus, comparing this verification percentage with that of equation 11 highlights the effectiveness of the abstain class in detecting perturbed images and increasing robustness: for instance, using our method 76.07% maximum robust error successfully decreases to 63.63% by considering the detection capability, on CIFAR-10 trained for $\epsilon = 8/255$, compared to 69.92% in IBP without detection.

See Fig. 1 for decomposition of the performance metrics of the proposed network over CIFAR-10 dataset, demonstrating the effectiveness of the abstain class in detecting "difficult" natural images while also increasing the robustness certificate over adversarial inputs.

Natural-vs-robust error tradeoff.

Reporting a single set point in the Pareto frontier as reported in Table 1 gives limited understanding on how different methods trade off natural versus robust error. To address this, performance of IBP-based robust classification without and with detection is plotted in 2 versus natural error to demonstrate the trade-off. As seen, IBP-with-detection is effectively utilizing its detection capability to adaptively trade natural and robust performance, leading to improved certified robustness. It is important to note that IBP w/detection allows us to obtain *additional regions* on this Pareto frontier that traditional-robust-classifiers without detection cannot obtain. For completeness, similar plots for other ϵ values in CIFAR-10 and MNIST are also provided in Appendix B.1 along with parameter details.

Figure 2: Robust vs. natural error tradeoff for CIFAR-10 with $\epsilon = 8/255$. Lower curve is better.

6 CONCLUSION

We proposed a new method for jointly training a provably robust classifier and detector. By introducing an additional "abstain/detection" into a classifier, we have proposed a verification scheme for classifiers with detection under adversarial settings, and shown that such networks can be efficiently trained be extending the common IBP relaxation techniques. The effectiveness of the proposed detection scheme with provable guarantees versus SOTA robust verifiable classification methods is corroborated by empirical tests on MNIST and CIFAR-10, specially against large perturbations.

REFERENCES

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. Proceedings of Machine Learning Research, pp. 274–283. PMLR, 10–15 Jul 2018.

Mitali Bafna, Jack Murtagh, and Nikhil Vyas. Thwarting adversarial examples: An l_0-robust sparse fourier transform. In *Advances in Neural Information Processing Systems*, pp. 10075–10085, 2018.

Mislav Balunovic and Martin Vechev. Adversarial training and provable defenses: Bridging the gap. In *International Conference on Learning Representations*, 2020.

Krishnamurthy Dvijotham, Robert Stanforth, Sven Gowal, Timothy A Mann, and Pushmeet Kohli. A dual approach to scalable verification of deep networks. In *UAI*, volume 1, pp. 550–559, 2018.

Ruediger Ehlers. Formal verification of piece-wise linear feed-forward neural networks. In *International Symposium on Automated Technology for Verification and Analysis*, pp. 269–286. Springer, 2017.

Mahyar Fazlyab, Alexander Robey, Hamed Hassani, Manfred Morari, and George Pappas. Efficient and accurate estimation of lipschitz constants for deep neural networks. In *Advances in Neural Information Processing Systems 32*, pp. 11427–11438. 2019.

Sven Gowal, Krishnamurthy Dvijotham, Robert Stanforth, Rudy Bunel, Chongli Qin, Jonathan Uesato, Relja Arandjelovic, Timothy Mann, and Pushmeet Kohli. On the effectiveness of interval bound propagation for training verifiably robust models. *arXiv preprint arXiv:1810.12715*, 2018.

Cassidy Laidlaw and Soheil Feizi. Playing it safe: Adversarial robustness with an abstain option. *arXiv preprint arXiv:1911.11253*, 2019.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *ICLR*, 2017.

Matthew Mirman, Timon Gehr, and Martin Vechev. Differentiable abstract interpretation for provably robust neural networks. In *International Conference on Machine Learning*, pp. 3578–3586, 2018.

Tianyu Pang, Kun Xu, Chao Du, Ning Chen, and Jun Zhu. Improving adversarial robustness via promoting ensemble diversity. In *International Conference on Machine Learning*, pp. 4970–4979, 2019a.

Tianyu Pang, Kun Xu, and Jun Zhu. Mixup inference: Better exploiting mixup to defend adversarial attacks. In *International Conference on Learning Representations*, 2019b.

Aditi Raghunathan, Jacob Steinhardt, and Percy Liang. Certified defenses against adversarial examples. *ICLR*, 2018.

Kevin Roth, Yannic Kilcher, and Thomas Hofmann. The odds are odd: A statistical test for detecting adversarial examples. In *International Conference on Machine Learning*, pp. 5498–5507, 2019.

Hadi Salman, Greg Yang, Huan Zhang, Cho-Jui Hsieh, and Pengchuan Zhang. A convex relaxation barrier to tight robustness verification of neural networks. In *Advances in Neural Information Processing Systems 32*, pp. 9835–9846. 2019.

Ali Shafahi, Mahyar Najibi, Mohammad Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! In *Advances in Neural Information Processing Systems*, pp. 3358–3369, 2019.

Lewis Smith and Yarin Gal. Understanding measures of uncertainty for adversarial example detection. *arXiv preprint arXiv:1803.08533*, 2018.

David Stutz, Matthias Hein, and Bernt Schiele. Confidence-calibrated adversarial training: Generalizing to unseen attacks. In *International Conference on Machine Learning*, 2020.

Vincent Tjeng, Kai Xiao, and Russ Tedrake. Evaluating robustness of neural networks with mixed integer programming. *ICLR*, 2017.

Florian Tramer, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses. *arXiv preprint arXiv:2002.08347*, 2020.

Gunjan Verma and Ananthram Swami. Error correcting output codes improve probability estimation and adversarial robustness of deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 8643–8653, 2019.

Eric Wong and Zico Kolter. Provable defenses against adversarial examples via the convex outer adversarial polytope. volume 80 of *Proceedings of Machine Learning Research*, pp. 5286–5295. PMLR, 10–15 Jul 2018.

Eric Wong, Leslie Rice, and J Zico Kolter. Fast is better than free: Revisiting adversarial training. In *International Conference on Learning Representations*, 2019.

Chang Xiao, Peilin Zhong, and Changxi Zheng. Resisting adversarial attacks by k-winners-take-all. *arXiv preprint arXiv:1905.10510*, 2019.

Kai Y Xiao, Vincent Tjeng, Nur Muhammad Mahi Shafiullah, and Aleksander Madry. Training for faster adversarial robustness verification via inducing relu stability. In *International Conference on Learning Representations*, 2018.

Yuzhe Yang, Guo Zhang, Dina Katabi, and Zhi Xu. Me-net: Towards effective adversarial robustness with matrix estimation. In *International Conference on Machine Learning*, pp. 7025–7034, 2019.

Xuwang Yin, Soheil Kolouri, and Gustavo K Rohde. Gat: Generative adversarial training for adversarial example detection and robust classification. In *International Conference on Learning Representations*, 2020.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael I Jordan. Theoretically principled trade-off between robustness and accuracy. In *ICML*, 2019.

Huan Zhang, Hongge Chen, Chaowei Xiao, Sven Gowal, Robert Stanforth, Bo Li, Duane Boning, and Cho-Jui Hsieh. Towards stable and efficient training of verifiably robust neural networks. In *International Conference on Learning Representations*, 2020.