INVESTIGATING MULTI-TASK PRETRAINING AND GENERALIZATION IN REINFORCEMENT LEARNING

ABSTRACT

Deep reinforcement learning (RL) has achieved remarkable successes in complex single-task settings. However, designing RL agents that can learn multiple tasks and leverage prior experience to quickly adapt to a related new task remains challenging. Despite previous attempts to improve on these areas, our understanding of multi-task training and generalization in RL remains limited. To fill this gap, we investigate the generalization capabilities of a popular actor-critic method, IMPALA (Espeholt et al., 2018). Specifically, we build on previous work that has advocated for the use of modes and difficulties of Atari 2600 games as a challenging benchmark for transfer learning in RL (Farebrother et al., 2018; Rusu et al., 2022). We do so by pretraining an agent on multiple *variants* of the same Atari game before fine-tuning on the remaining *never-before-seen* variants. This protocol simplifies the multi-task pretraining phase by limiting negative interference between tasks and allows us to better understand the dynamics of multi-task training and generalization. We find that, given a fixed amount of pretraining data, agents trained with more variations are able to generalize better. Surprisingly, we observe that this advantage can be more pronounced after fine-tuning for 200M environment frames than when doing zero-shot transfer. This highlights the potential effect of a good learned representation and that performance after fine-tuning might be more appropriate to evaluate generalization in RL. We also find that, even though small networks have remained popular to solve Atari 2600 games, increasing the capacity of the value and policy network is critical to achieve good performance as we increase the number of pretraining modes and difficulties. Overall, our findings emphasize key points that are essential for efficient multi-task training and generalization in reinforcement learning.

1 INTRODUCTION

Deep RL has achieved remarkable results in recent years, from surpassing human-level performance on challenging games (Silver et al., 2017; Berner et al., 2019; Vinyals et al., 2019) to learning complex control policies that can be deployed in the real world (Levine et al., 2016; Bellemare et al., 2020). However, these successes were attained with specialized agents trained to solve a single task and with every new task requiring a new policy trained from scratch. On the other hand, *high-capacity* models trained on large amounts of data have remarkable generalization abilities in other deep learning domains such as vision and NLP (Brown et al., 2020; He et al., 2022). Such models can solve multiple tasks simultaneously (Chowdhery et al., 2022), show emergent capabilities (Srivastava et al., 2022), and quickly adapt to unseen but related tasks by leveraging previously acquired knowledge (Brown et al., 2020). While recent work has succeeded in learning such broadly generalizing policies using supervised learning (Reed et al., 2022; Lee et al., 2022), despite many attempts, deep RL agents have not been able to achieve the same kind of broad generalization.

RL policies pretrained on multiple tasks are often unable to leverage information about previous tasks to accelerate learning on related tasks (Kirk et al., 2021). Furthermore, multi-task agents are reported to perform worse on individual tasks than a single-task agent trained on that task (Espeholt et al., 2018). The limited performance of multi-task policies is believed to be due to negative interference between tasks (Schaul et al., 2019). Recent work has tried to address this issue, Hessel et al. (2019) proposes a reward rescaling scheme that normalizes the effect of each task on the learning dynamics. Similarly Guo et al. (2020) introduces a self-supervised learning objective to improve representation

learning during multi-task training. Other works have shown that multi-task pretraining can lead to better representations that are useful for downstream tasks when the policy only needs to generalize to a new reward (Borsa et al., 2016; Yang et al., 2020; Sodhani et al., 2021). Nevertheless, in complex multi-task problems, such as the Arcade Learning Environment (ALE; Bellemare et al., 2013), generalization of pretrained policies to unseen tasks remains an unsolved problem.

In this paper, we propose to take a closer look at multi-task RL pretraining and generalization on the ALE, one of the most widely used deep RL benchmark. Though, one might hope that an agent could benefit from multi-task training to learn some high level concepts such as affordances (Khetarpal et al., 2020) or contingency awareness (Bellemare et al., 2012), the lack of common ground between tasks makes joint training on multiple Atari games a difficult problem. To circumvent these issues, we make use of the *modes* and *difficulties* of Atari 2600 games (Figure 1), which we call *variants* (Machado et al., 2018). These *variants* were developed by game designers to make each game progressively more challenging for human players. Previous work has advocated for their use to study generalization in reinforcement learning (Farebrother et al., 2018; Rusu et al., 2022), though these works did not go beyond pretraining on a single task. Notably, Farebrother et al. (2018) argued that the representation learned by a DQN agent (Mnih et al., 2013) after pretraining is brittle and is not able transfer well to *variants* of the same game. They find that during pretraining, the representation tends to overfit to the task it is being trained on, decreasing its generalization capabilities.

Our goal in this work is to revisit these results under a new light, leveraging advances in algorithms, architectures and computation that have happened since. We use a more efficient algorithm, IMPALA (Espeholt et al., 2018) instead of DQN, much larger networks than the decade old 3-layer convolutional neural networks used by DQN (Mnih et al., 2013) and pretrain our agents using multiple *variants* of a game as opposed to just a single one. By limiting the pretraining tasks to different *variants* of the same game, we facilitate multi-task transfer between variants, which in-turn allows us to study under what conditions RL algorithms are able to generalize better when training on multiple tasks. Our contribution are as follow:

- We find that pretrained policies have limited zero-shot transfer learning performance. However, if we fine-tune these polices using interactions in the unseen variant, the fine-tuned policies generalize quite well and learn significantly faster than a randomly initialized policy.

- We observe that a good representation can be learned using pretraining on a relatively small number of modes. Fine-tuning performance from these representations improve as we increase the amount of the pretraining data, as opposed to overfitting on pretraining tasks.

- Finally, we demonstrate that it is possible to train high capacity networks such as residual networks (He et al., 2016), with tens of millions of parameters, using online RL. We find that increased representation capabilities from such networks are essential to reach peak performance in the multi-task regime.

2 BACKGROUND

Reinforcement learning: We consider a Markov decision process (MDP) (Puterman, 2014) M represented by a tuple $\langle \mathcal{S}, \mathcal{A}, P, r, \gamma, \rho \rangle$ with $\mathcal{S}$ the state space, $\mathcal{A}$ the finite set of actions, $P : \mathcal{S} \times A \to [0, 1]^{\mathcal{S}}$ the transition probability distribution, $r : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}$ the reward function, $\gamma \in [0, 1]$ the discount factor and ρ the initial state distribution. At each timestep t the agent observe the current state s_t, then its chooses an action sampled according to its policy $\pi : \mathcal{S} \times \mathcal{A} \to [0, 1]$ before it can receive a reward r_t and observe the subsequent state s_{t+1}. Given a policy π, we define the value function at time t to be the discounted sum of expected rewards to be collected from the current state when following policy π: $V(s_t) := \mathbb{E}\left[\sum_{i=0}^{+\infty} \gamma^i r_{t+i} | s_t, a_t \sim \pi(s_t) \right]$. The agent's goal is to find a policy that maximizes its value in each state.

Transfer learning / Generalization: In transfer learning, we are interested in designing learning methods that are able to leverage previous interactions with a task / environment to solve new tasks more efficiently. There are many possible ways to quantify transfer in reinforcement learning. The first one we study is zero-shot where performance is evaluated on the target tasks without any adaptation (*e.g.,* Cobbe et al., 2020a; Agarwal et al., 2021a; Zhang et al., 2021). We also evaluate performance after the agent is allowed to interact with the target environment for a fixed number of

Space Invaders	Asteroids	Breakout	Bank Heist

Figure 1: Examples of **game *variants*** of Atari 2600 games. Each column represents two different variants of a game. In SPACE INVADERS shields move from static to mobile, in ASTEROIDS the shape of the spaceship changes, in BREAKOUT the ball becomes steerable by the paddle, in BANK HEIST banks appear at different locations. While there are only subtle changes in the visual observations or agent embodiments, such changes are crucial for determining the optimal behavior, which makes generalization on these *variants* difficult.

online environment interactions. We refer the reader to Zhu et al. (2020); Kirk et al. (2021) for a in-depth overview on transfer and generalization in deep reinforcement learning.

Arcade Learning Environment The Arcade Learning Environment (Bellemare et al., 2013) provides an interface to Atari 2600 games and was first proposed as a platform to evaluate the abilities of reinforcement learning agents across a wide variety of environments. It has since become a cornerstone of reinforcement learning research. Practitioners have focused mostly on training agents individually on each game to achieve the highest possible reward and current techniques far exceed human performance (Mnih et al., 2015; Van Hasselt et al., 2016; Bellemare et al., 2017; Kapturowski et al., 2018; Badia et al., 2020). Recent work has also looked at the ALE in the context of generalization, transfer learning and continual learning (Farebrother et al., 2018; Rusu et al., 2022). The major benefit of the ALE compared to other generalization benchmarks (Nichol et al., 2018; Yu et al., 2020) is that it proposes a diverse set of games that is free of researcher bias, as these games were designed to be challenging for human players, rather than for improving deep RL agents. The latest version of the ALE (Machado et al., 2018) introduces different modes and difficulties for Atari 2600 games. These flavours were part of the original titles and were designed to offer players a more entertaining experience by offering variations of the default game. Each variant offers a different alteration of the base game across some discrete modifications while most of the game remains the same (see Figure 1). Because the underlying dynamics of the environment do not change much we can expect that playing some modes can lead to faster learning on others. Farebrother et al. (2018) and Rusu et al. (2022) have both previously investigated the transfer and generalization capabilities of value based agents using modes and difficulties of Atari 2600 games. Our work goes further by looking at the impact of pretraining on multiple variants to improve generalization.

3 EMPIRICAL METHODOLOGY

Environment Protocol: We follow the latest ALE recommendations (Machado et al., 2018) and use sticky actions to make the environment stochastic. The agent also does not receive a signal when a life is lost within the game. Even when not all actions are available, agents must act with the full set of 18 possible actions. We use the default pre-processing (Mnih et al., 2015) for environment frames.

ALE Games & Variants: We will be using four Atari games, SPACE INVADERS, ASTEROIDS, BREAKOUT and BANK HEIST. We chose them because of their relatively large number of game *variants*, 32 for SPACE INVADERS, 66 for ASTEROIDS, 24 for BREAKOUT and 32 for BANK HEIST (see the Appendix for a detailed overview of each game). For each game we split the available *variants* into a train and a test set, where the test set contains 3 unseen *variants*. This split is done

randomly, except for SPACE INVADERS where we reuse the test set introduced by Farebrother et al. (2018).

Pre-training Agent: All our experiments use IMPALA (Espeholt et al., 2018), a model-free actor-critic method. IMPALA introduces V-traces, an off-policy learning algorithm that corrects updates that become off-policy due to the lag between actors and a learner in a distributed setup. Prior work using IMPALA in the multi-task regime always had to use an individual value function for each task. Here, we use *a single policy and value network* to play every flavour of a game. By restricting the different tasks variants of the same game we observe less negative interference between tasks which allows us to share parameters between the policy and value function. For experiments that analyze the impact of network capacity, we also use large ResNets (Espeholt et al., 2018). Further details regarding hyperparameters and the training procedure may be found in the Appendix.

Reporting & Evaluation: Given that human scores are not available for Atari 2600 game modes and difficulties, we cannot report human-normalized scores. Instead, we provide results using an *IMPALA-Normalized* score, where we assign a normalized score of 1 to the average score obtained by an IMPALA agent trained for 200 million frames and a normalized score of 0 to the random agent. For reliable evaluation, we report aggregate metrics and performance profiles, with 90% stratified bootstrap confidence intervals (Agarwal et al., 2021b). In particular, we use the interquartile mean (IQM) recommended by Agarwal et al. (2021b), which computes the mean of normalized scores over the middle 50% of the runs, combined across all the test *variants*. IQM is more robust to outliers than mean and results in smaller CIs than median.

Pre-training procedure: Unless otherwise specified, the amount of pretraining data is kept fixed for each agent at 15 billion environment frames. As a result, each agent interacts with each mode and difficulty for at least 250 million frames. The different tasks are split among multiple actors and the agent must play all variants of a game in the training set at the same time. The agent is not provided the mode and difficulty identities with the observation. Though passing this information may improve training performance, it would negatively impact generalization to unseen *variants*.

Fine-tuning on unseen *variants*: A common way to use a learned representation is to reuse its parameters as initialization to solve a subsequent task. We follow this procedure and use pretrained models to initialize the policy and value network of a new IMPALA agent to play the test set games. Previous work has usually limited the length of the fine-tuning process to 10 million frames, here we choose the standard limit of 200 million frames to quantify the impact of the learned initialization using the standard amount of online interactions used by ALE agents (Machado et al., 2018). Every fine-tuning experiment is run using 5 seeds.

4 EXPERIMENTS

Using the above methodology, we now present our results on multi-task pretraining and generalization using the game variants in ALE.

4.1 PRETRAINING ON MULTIPLE VARIANTS

RL agents are often trained from scratch, starting from a randomly initialized policy, as it is unclear whether they can leverage their experience during pretraining to generalize well on subsequent tasks. To understand this behavior we are interested in quantifying the impact of pretraining and number of pretraining variants on the transfer and generalization capabilities of an IMPALA agent (Espeholt et al., 2018). We first compare agents pretrained on subsets containing different numbers of variants of a game using the same budget of 15B environment frames. We evaluate zero-shot transfer by using a pretrained policy directly on a target variant. We also analyze fine-tuning performance by allowing the pretrained policy to interact with the test variant for 200 million environment frames. Given the large number of variants for selected games, it precludes pretraining on all possible subsets of variants as this number grows exponentially with the number of variants. Instead, we randomly subsample multiple subsets of different sizes and require that each subset be a superset of previously picked smaller subsets. This was necessary to limit the effect of particular variants that might have a larger impact on generalization due to their relatively higher similarity with unseen variants (Rusu et al., 2022).

Figure 2: **Zero-shot *vs.* Fine-tuning** performance on unseen modes using interquartile mean (IQM) scores. Error bars show 90% bootstrap confidence intervals. Notably, increasing the number of modes for pre-training does not significantly impact zero-shot performance but consistently improves fine-tuning performance after 200M frames of online interactions for most games. These results indicate that the pre-trained representations learn relevant features for the unseen modes but need to be fine-tuned to show any benefits.

4.1.1 ZERO-SHOT

Zero-shot generalization is the most desirable but also most difficult kind of generalization to achieve as it does not allow for any interaction with the target environment. In the context of RL generalization benchmarks with procedurally generated environments, such as Procgen (Cobbe et al., 2020a), zero-shot transfer only emerges after interacting with hundreds of training environments. Here, we assess the zero-shot performance of pretrained models on the test game variants after pretraining on a relatively much smaller number of environments. Results are shown in Figure 2 (orange). We observe contrasting results: on ASTEROIDS and BANK HEIST pretraining is highly beneficial. Pretrained agents are able to reach half of the performance achieved by the IMPALA trained from scratch for 200 million frames, on BANK HEIST policies pretrained with more modes perform better and they almost match the performance of IMPALA. On the other hand, on BREAKOUT and SPACE INVADERS, the impact of pretraining on zero-shot performance is limited, pretrained policies can reach a score higher than a random agent but not by much. Overall, we see that zero-shot generalization remains challenging for current RL agents in the context of the ALE.

4.1.2 FINE-TUNING

Zero-shot transfer is difficult to achieve, the policy and learned representation have limited margin for error given how small mistakes can compound over the duration of an evaluation episode. An easier task is to fine-tune a pretrained model on the test variant, giving time for the policy to adapt to the new task. In this section we focus on quantifying the performance of fine-tuning models after pretraining with different numbers of variants.

We report results in Figure 3 and 4. We observe that pretraining is valuable for every game. On BREAKOUT and BANK HEIST the final score achieved by pretrained and non-pretrained models is similar. However, the pretrained models are much more sample efficient: they only require 25 million

Figure 3: **Fine-tuning performance on unseen modes** after 200M frames. On all games except BREAKOUT, pretrained policies significantly outperform the baseline that was randomly initialized (0 modes). On BREAKOUT, we observe a huge boost in sample efficiency from pretraining but final performance saturates for all agents. **Left**. Aggregate IQM as a function of pretraining modes. Crosses show performance on the 3 individual variants, where each color corresponds to a specific variant. **Right**. Performance profiles are quite useful for qualitative summarization: Higher is better. Area under the profiles correspond to the mean performance, the median can be read by the intersection of the profile curves with the horizontal line at $y = 0.5$. Similarly, we can easily check how many runs score above a certain score threshold τ using the intersections of the curves with the vertical line $x = \tau$. Shaded region shows 90% stratified bootstrap CIs.

Figure 4: **Sample efficiency** IQM curves for IMPALA with no pretraining (0 modes), a small number of pretraining modes and a large number of pretraining modes. Shaded regions show 90% bootstrap confidence intervals. Pretrained agents go through an *adaptation phase* over the first 10 million frames where performance quickly rises after acclimating to the test environment.

frames to get close to their final performance. On ASTEROIDS and SPACE INVADERS, fine-tuned models significantly outperform our IMPALA baseline and reach scores three times higher.

Our result corroborates previous results demonstrating the benefits of pretraining and fine-tuning, in particular, with domain randomization (Tobin et al., 2017; Cobbe et al., 2020b). What is surprising is that, in our setup, these effects are largely captured with a relatively small number of pretraining modes and difficulties, possibly due to the fact that these variants may be sufficient to cover most factors of variations present in the test set. We see little additional improvements when increasing the number of pretraining modes. On the other hand, domain randomization will often generate hundreds of thousands of variations of an environment; Cobbe et al. (2020b)'s experiments required thousands of levels to see an improvement in terms of zero-shot generalization. These results indicate that few-shot transfer is much more difficult to achieve and requires a large amount of diversity in the pretraining data. Nonetheless, representations learned with a few modes can be useful for transfer but they will require an *adaptation phase* – which happens in the first 10 million frames in our experiments – where performance will increase rapidly to tailor the representation to the new task at hand. Somewhat surprisingly, the pretrained agents can significantly outperform the same agent trained from scratch (0 modes) even after 200 million frames whereas we could have imagined that the effect of initialization had been washed away by now. This is in line with recent work (Igl et al., 2020; Nikishin et al., 2022) highlighting the lasting effects of initialization in deep RL.

4.2 INFLUENCE OF PRETRAINING DATA

Farebrother et al. (2018)'s experiments showed that the limited generalization capabilities of the DQN agent they studied is in part due to an overfitting phenomenon. Their agent is pretrained on a single task and learns a specialized representation for this task that does not generalize well. They show that the zero shot performance of a DQN agent can increase then decrease during pretraining as the representation becomes more specialized. This is highly undesirable and shows how fragile the representation learned by a reinforcement learning agent can be. In this section we investigate whether representations learned using large amounts of pretraining data still overfit to variants encountered during pretraining. To do so we use intermediate checkpoints of the previous pretrained IMPALA models saved at 850M, 1.9B, 2.8B, 3.75B and 7.5B frames. They are then fine-tuned for 200 million frames on the test set variants. Results are shown in Figure 5. We observe that fine-tuning performance

Figure 5: **Impact of pretraining data on fine-tuning performance** on unseen variants. Error bars show 90% bootstrap CIs. Increasing the number of environment interactions during pretraining is beneficial to fine-tuning performance.

improves with more pretraining data and we do not observe the overfitting phenomenon. This is likely due to the fact that joint pretraining on several variants acts as a regularizer on the representation and prevents over specialization. This is akin to how training on large amounts of diverse data from multiple tasks in supervised learning leads to representations that generalize broadly.

4.3 SCALING MODEL SIZE

Our results so far hold for the network introduced with the IMPALA algorithm (Espeholt et al., 2018). Though it is an improvement over the DQN network architecture, the IMPALA network has only 15 layers and less than 2 millions parameters. This is relatively small in comparison with models used in vision and NLP where large networks trained on large datasets have been shown to be superior and display impressive generalization capabilities. Additionally, larger capacity models in single-task deep RL settings often lead to instabilities or performance degradation (Van Hasselt et al., 2018; Ota et al., 2021; Bjorck et al., 2021), making it unclear whether multi-task RL can leverage such high-capacity models. We may wonder if increasing the network size is beneficial in the multi-task setting, where there is diversity in the training data and hence more to learn.

In this section we investigate this idea and take a closer look at the generalization capabilities of the IMPALA algorithm combined with larger networks from the ResNet family (He et al., 2016). In our experiments we use ResNet-18, ResNet-34, ResNet-50 and ResNet-101 (respectively 11.4, 21.5, 23.9 and 42.8 millions parameters). As before, we pretrain these architectures for 15B frames with varying numbers of game variants before fine-tuning on the test flavours for 200 million frames. Due to the huge computational cost of these experiments we limit our results to ASTEROIDS and SPACE INVADERS. Results are displayed in Figure 6. When training only on test environments, increasing the network size noticeably degrades performance in both games. This result is aligned with prior findings and may explain the dearth of reported results using very large networks in the RL literature. Inversely, pretraining on multiple variants unlocks the potential of larger networks in deep

Figure 6: **Impact of network capacity** on fine-tuning performance on unseen modes. 0 modes corresponds to no pretraining. When networks are randomly initialized, ResNets underperform the IMPALA architecture and performance decreases as the network capacity is increased. With pretraining ResNets significantly outperform the IMPALA architecture.

RL. As such, we observe a significant increase in performance (note the logarithmic scale) and these architectures achieve a score 3-4× higher than the IMPALA network trained in the same conditions. Moreover, most of these benefits are attained with ResNet-18, with small benefits in performance when we further increase model capacity. Altogether, it is unexpected to see that pretraining can have such a dramatic impact on the performance of larger networks. In recent years, researchers have attempted to train multi-task policies on all Atari games using slight variations of the IMPALA architecture (Hessel et al., 2019; Guo et al., 2020). Our results indicate that these approaches would likely benefit from higher capacity networks.

5 CONCLUSION

Deep reinforcement learning has made a lot of strides in recent years, yet real world applications remain seldom. Better generalization in reinforcement learning could be one of the missing pieces to unlock real-world reinforcement learning. Having access to generalist agents that can perform multiple tasks and are capable of leveraging their prior knowledge to learn new tasks efficiently would take RL to new heights. Nevertheless, prior work has shown that RL remains far from achieving such ambitions and that generalization in RL should not be relied upon. Yet our work offers a glimmer of hope: in our controlled setup, RL agents pre-trained on a small number of game variants generalize to *never-before-seen* variants and considerably improve sample efficiency. Overall, our work calls for using more diverse data and bigger networks in reinforcement learning, which is now a given in other machine learning communities. Though there remains a lot of work to be done to fully take advantage of these two elements, our work offers a glimpse at the potential of large scale multi-task RL. Finally, in line with Agarwal et al. (2022), we would open-source our pretrained models to allow researchers to reproduce our findings as well as study zero-shot generalization and fine-tuning in RL, without the excessive cost of multi-task pretraining from scratch.

REFERENCES

Rishabh Agarwal, Marlos C Machado, Pablo Samuel Castro, and Marc G Bellemare. Contrastive behavioral similarity embeddings for generalization in reinforcement learning. 2021a.

Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron C Courville, and Marc Bellemare. Deep reinforcement learning at the edge of the statistical precipice. *Advances in neural information processing systems*, 34:29304–29320, 2021b.

Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron Courville, and Marc G Bellemare. Beyond tabula rasa: Reincarnating reinforcement learning. *Advances in neural information processing systems*, 2022.

Adrià Puigdomènech Badia, Bilal Piot, Steven Kapturowski, Pablo Sprechmann, Alex Vitvitskyi, Zhaohan Daniel Guo, and Charles Blundell. Agent57: Outperforming the atari human benchmark. In *International Conference on Machine Learning*, pp. 507–517. PMLR, 2020.

Marc G Bellemare, Joel Veness, and Michael Bowling. Investigating contingency awareness using atari 2600 games. In *Twenty-Sixth AAAI Conference on Artificial Intelligence*, 2012.

Marc G. Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47: 253–279, 2013.

Marc G. Bellemare, Will Dabney, and Remi Munos. A distributional perspective on reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 449–458, 2017.

Marc G Bellemare, Salvatore Candido, Pablo Samuel Castro, Jun Gong, Marlos C Machado, Subhodeep Moitra, Sameera S Ponda, and Ziyu Wang. Autonomous navigation of stratospheric balloons using reinforcement learning. *Nature*, 588(7836):77–82, 2020.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Debiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

Johan Bjorck, Carla P Gomes, and Kilian Q Weinberger. Towards deeper deep reinforcement learning. *arXiv preprint arXiv:2106.01151*, 2021.

Diana Borsa, Thore Graepel, and John Shawe-Taylor. Learning shared representations in multi-task reinforcement learning. *arXiv preprint arXiv:1603.02041*, 2016.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Johan Samir Obando Ceron and Pablo Samuel Castro. Revisiting rainbow: Promoting more insightful and inclusive deep reinforcement learning research. In *International Conference on Machine Learning*, pp. 1373–1383. PMLR, 2021.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.

Karl Cobbe, Chris Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *International conference on machine learning*, pp. 2048–2056. PMLR, 2020a.

Karl Cobbe, Chris Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 2048–2056. PMLR, 13–18 Jul 2020b.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Vlad Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *International Conference on Machine Learning*, pp. 1407–1416. PMLR, 2018.

Lasse Espeholt, Raphaël Marinier, Piotr Stanczyk, Ke Wang, and Marcin Michalski. Seed rl: Scalable and efficient deep-rl with accelerated central inference. *arXiv preprint arXiv:1910.06591*, 2019.

Jesse Farebrother, Marlos C Machado, and Michael Bowling. Generalization and regularization in dqn. *arXiv preprint arXiv:1810.00123*, 2018.

Zhaohan Daniel Guo, Bernardo Avila Pires, Bilal Piot, Jean-Bastien Grill, Florent Altché, Rémi Munos, and Mohammad Gheshlaghi Azar. Bootstrap latent-predictive representations for multitask reinforcement learning. In *International Conference on Machine Learning*, pp. 3875–3886. PMLR, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16000–16009, 2022.

Matteo Hessel, Hubert Soyer, Lasse Espeholt, Wojciech Czarnecki, Simon Schmitt, and Hado van Hasselt. Multi-task deep reinforcement learning with popart. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 3796–3803, 2019.

Matteo Hessel, Manuel Kroiss, Aidan Clark, Iurii Kemaev, John Quan, Thomas Keck, Fabio Viola, and Hado van Hasselt. Podracer architectures for scalable reinforcement learning. *arXiv preprint arXiv:2104.06272*, 2021.

Maximilian Igl, Gregory Farquhar, Jelena Luketina, Wendelin Boehmer, and Shimon Whiteson. Transient non-stationarity and generalisation in deep reinforcement learning. *arXiv preprint arXiv:2006.05826*, 2020.

Steven Kapturowski, Georg Ostrovski, John Quan, Remi Munos, and Will Dabney. Recurrent experience replay in distributed reinforcement learning. In *International conference on learning representations*, 2018.

Khimya Khetarpal, Zafarali Ahmed, Gheorghe Comanici, David Abel, and Doina Precup. What can i do here? a theory of affordances in reinforcement learning. In *International Conference on Machine Learning*, pp. 5243–5253. PMLR, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Robert Kirk, Amy Zhang, Edward Grefenstette, and Tim Rocktäschel. A survey of generalisation in deep reinforcement learning. *arXiv preprint arXiv:2111.09794*, 2021.

Kuang-Huei Lee, Ofir Nachum, Mengjiao Yang, Lisa Lee, Daniel Freeman, Winnie Xu, Sergio Guadarrama, Ian Fischer, Eric Jang, Henryk Michalewski, et al. Multi-game decision transformers. *arXiv preprint arXiv:2205.15241*, 2022.

Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.

Marlos C. Machado, Marc G. Bellemare, Erik Talvitie, Joel Veness, Matthew Hausknecht, and Michael Bowling. Revisiting the arcade learning environment: Evaluation protocols and open problems for general agents. *Journal of Artificial Intelligence Research*, 61:523–562, 2018.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

Alex Nichol, Vicki Pfau, Christopher Hesse, Oleg Klimov, and John Schulman. Gotta learn fast: A new benchmark for generalization in rl. *arXiv preprint arXiv:1804.03720*, 2018.

Evgenii Nikishin, Max Schwarzer, Pierluca D'Oro, Pierre-Luc Bacon, and Aaron Courville. The primacy bias in deep reinforcement learning. In *International Conference on Machine Learning*, pp. 16828–16847. PMLR, 2022.

Kei Ota, Devesh K Jha, and Asako Kanezaki. Training larger networks for deep reinforcement learning. *arXiv preprint arXiv:2102.07920*, 2021.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Scott Reed, Konrad Zolna, Emilio Parisotto, Sergio Gomez Colmenarejo, Alexander Novikov, Gabriel Barth-Maron, Mai Gimenez, Yury Sulsky, Jackie Kay, Jost Tobias Springenberg, et al. A generalist agent. *arXiv preprint arXiv:2205.06175*, 2022.

Andrei Rusu, Sebastian Flennerhaga, Dushyant Rao, Razvan Pascanu, and Raia Hadsell. Probing transfer in deep reinforcement learning without task engineering. In *Conference on Lifelong Learning Agents*, 2022.

Tom Schaul, Diana Borsa, Joseph Modayil, and Razvan Pascanu. Ray interference: a source of plateaus in deep reinforcement learning. *arXiv preprint arXiv:1904.11455*, 2019.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *Nature*, 550(7676):354, 2017.

Shagun Sodhani, Amy Zhang, and Joelle Pineau. Multi-task reinforcement learning with context-based representations. In *International Conference on Machine Learning*, pp. 9767–9779. PMLR, 2021.

Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *arXiv preprint arXiv:2206.04615*, 2022.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pp. 23–30. IEEE, 2017.

Hado Van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 30, 2016.

Hado Van Hasselt, Yotam Doron, Florian Strub, Matteo Hessel, Nicolas Sonnerat, and Joseph Modayil. Deep reinforcement learning and the deadly triad. *arXiv preprint arXiv:1812.02648*, 2018.

Oriol Vinyals, Igor Babuschkin, Junyoung Chung, Michael Mathieu, Max Jaderberg, Wojtek Czarnecki, Andrew Dudzik, Aja Huang, Petko Georgiev, Richard Powell, Timo Ewalds, Dan Horgan, Manuel Kroiss, Ivo Danihelka, John Agapiou, Junhyuk Oh, Valentin Dalibard, David Choi, Laurent Sifre, Yury Sulsky, Sasha Vezhnevets, James Molloy, Trevor Cai, David Budden, Tom Paine, Caglar Gulcehre, Ziyu Wang, Tobias Pfaff, Toby Pohlen, Dani Yogatama, Julia Cohen, Katrina McKinney, Oliver Smith, Tom Schaul, Timothy Lillicrap, Chris Apps, Koray Kavukcuoglu, Demis Hassabis, and David Silver. AlphaStar: Mastering the Real-Time Strategy Game StarCraft II. https://deepmind.com/blog/alphastar-mastering-real-time-strategy-game-starcraft-ii/, 2019.

Ruihan Yang, Huazhe Xu, Yi Wu, and Xiaolong Wang. Multi-task reinforcement learning with soft modularization. *Advances in Neural Information Processing Systems*, 33:4767–4777, 2020.

Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on robot learning*, pp. 1094–1100. PMLR, 2020.

Amy Zhang, Rowan McAllister, Roberto Calandra, Yarin Gal, and Sergey Levine. Learning invariant representations for reinforcement learning without reconstruction. 2021.

Zhuangdi Zhu, Kaixiang Lin, and Jiayu Zhou. Transfer learning in deep reinforcement learning: A survey. *arXiv preprint arXiv:2009.07888*, 2020.

A PARAMETERS

In this section, the specific parameter settings that are used throughout our experiments are given in detail. We kept all the original IMPALA hyperparameters fixed except the optimizer where we used Adam (Kingma & Ba, 2014) instead of RMSProp as it was shown to be superior in the context of reinforcement learning (Ceron & Castro, 2021). We did not do any hyperparameter tuning.

Parameter	Value
Image Width	84
Image Height	84
Grayscaling	Yes
Action Repetitions	4
Max-pool over last N action repeat frames	2
Frame Stacking	4
End of episode when life lost	No
Sticky actions	Yes
Action set	Full (18 actions)
Reward Clipping	[-1, 1]
Unroll Length (n)	19
Batch size	128
Discount (γ)	0.99
Baseline loss scaling	0.5
Entropy Regularizer	0.01
Adam β_1	0.9
Adam β_2	0.999
Adam ϵ	1e-8
Learning rate	3e-4
Clip global gradient norm	40

Table 1: Hyperparameters for Atari experiments.

We use an efficient implementation of IMPALA (Espeholt et al., 2019; Hessel et al., 2021) that runs on TPUs. Experiment specific hyperparameters are as follow

- The pretraining phase is carried on 32 TPU v3 cores using 3200 actors.

- Fine-tuning is done 8 TPU v2 cores using 900 actors.

B ATARI VARIANTS: GAME MODES AND DIFFICULTIES

We quickly review the modes and difficulties of Atari games used throughout the main paper. (Rusu et al., 2022) provides a more in detailed presentation of modes and difficulties for the games BREAKOUT and SPACE INVADERS. To identify individual flavours we use the notation $mXdY$ where X refers to the game mode setting and Y to the difficulty setting:

- **Space Invaders** is a shooting game where the player moves a laser cannon across the bottom of the screen and fires at aliens. The aliens begin on the upper half of the screen and move left and right as a group. The players wins by eliminating all the aliens. There are two difficulty switches and sixteen different game modes leading to a total of 32 flavours. We keep $m1d0$, $m1d1$ and $m9d0$ for the test set and keep the other modes for training.

- **Breakout** is a game where rows of bricks are layered at the top half of the screen. Using a single ball the player must hit the bricks using the paddle it controls at the bottom of the screen. However if the player let the ball fall below the bottom of the screen it looses a life. There are two difficulty switches and twelve game modes for a total of 24 flavours. We use $m12d0$, $m28d1$, $m36d1$ for the test set and use the remaining modes for training.

- **Asteroids**, in this game the player controls a ship in space that must destroy asteroids. The ship must avoid getting hit by asteroids, saucers will also appear regularly and try to shoot the ship. There are two difficulty switches and 33 game modes for a total of 63 flavours. $m4d0$, $m18d3$, $m27d3$ are saved for the test set while the remaining modes are part of the training set.

- **Bank Heist** is a maze game similar to Pac-Man where the objective is to rob as many banks as possible while avoiding police cars that appear everytime a bank is robbed. For this game there are four difficulty switches and eight game modes for a total of 32 different flavours. The training set contains all the flavours except $m8d3$, $m20d1$, $m24d0$ that are used for the test set.