SHUFFLED TRANSFORMERS FOR BLIND TRAINING

ABSTRACT

Conventional split learning faces the challenge of preserving training data and model privacy as a part of the training is beyond the data owner's control. We tackle this problem by introducing *blind training*, i.e., training without being aware of the data or the model, realized by shuffled Transformers. This is attributed to our intriguing findings that the inputs and the model weights of the Transformer encoder blocks, the backbone of Transformer, can be shuffled without degrading the model performance. We not only have proven the shuffling invariance property in theory, but also design a privacy-preserving split learning framework following the property, with little modification to the original Transformer architecture. We carry out verification of the properties through experiments, and also show our proposed framework successfully defends privacy attacks to split learning with superiority.

1 INTRODUCTION

Recent years have witnessed remarkable growth in deep learning applications, as deep neural networks (DNNs) have grown deeper and larger. It poses a dilemma for the thin edge device: on one hand, it lacks the computational power to individually train the models; on the other, data privacy would be violated if it sends all data to an untrusted party, *e.g.,* the cloud, to process. A paradigm called split learning (Gupta & Raskar, 2018) emerges to be a potential solution: without sharing its raw data, the edge transmits intermediate features to the cloud while offloading partial computation.

Typically, the private inputs are transformed into intermediate features by feeding through the first few layers of the DNN. The vanilla split learning still faces privacy leakages as an adversary could infer the input from the feature (Erdogan et al., 2021; Isola et al., 2017). Hence many works have proposed to remove the sensitive information from the features, such as encryption (Lee et al., 2022), adversarial learning (Xiao et al., 2020), differential privacy (Dong et al., 2019), etc. However, these works mostly sacrifice accuracy or efficiency for privacy guarantee. More importantly, the privacy threat of the model weights trained on the cloud is left to be an open problem — the trained weights reveal the privacy of the training data (Fredrikson et al., 2015; Carlini et al., 2019; Zhang et al., 2020), and should be proprietary to the data owner, *i.e.,* the edge.

We propose a novel *blind training* framework on the Transformer (Steiner et al., 2021), a state-of-the-art DNN achieving impressive accuracy performance on a wide range of tasks. Blind training means that the cloud conducts its part of computation 'in blind' — being unaware of the data or the model it trains, yet executing valid computation to assist the edge. The framework resembles the homomorphic encryption where the edge encrypts training data with its key, and feeds to the encrypted DNN hosted in the cloud. The cloud trains the DNN in ciphertext, without knowing the input or the model. Different from the cryptographic tool, our framework is built all in plaintext, and thus avoiding the hassle of encryption.

The key is to exploit the shuffle invariance property of Transformers. We discovered that Transformers have an intriguing property that its data can be randomly shuffled to feed through the network, equivalent to that without shuffling. Despite that the previous work (Naseer et al., 2021) has recognized similar properties through experiments, we for first time establish its theoretical foundation. By regarding the shuffling order as a 'key,' the edge feeds shuffled training data to the cloud which performs natural training. Another interesting property we found is that, by training on the shuffled data, we inherently obtain a Transformer encoder block with shuffled weights, which only yields valid results on inputs permuted by the 'key.' Hence the Transformer is 'encrypted' to train on the

shuffled data. More importantly, the shuffled model can be 'decrypted' to obtain an equivalent plain network to which normal data can be fed.

Highlights of our contributions are: we discovered the intriguing shuffle invariance property of Transformers (and other models with Transformer encoder blocks as backbone), and built a privacy-preserving split learning framework on it. The framework provides shuffling-based privacy guarantees for training data, testing data, as well as the model weights. A variety of experiments are implemented to verify the properties, and demonstrate the superior performance of our scheme in terms of accuracy, privacy and efficiency.

2 BACKGROUND AND RELATED WORKS

Transformer-based models are the state-of-the-art deep neural networks and have attracted great attention in both areas of computer vision and natural language processing. Models including transformer encoder blocks as their backbone, such as Bert (Devlin et al., 2018), ViT (Dosovitskiy et al., 2020), T2T-ViT (Yuan et al., 2021), ViTGAN (Hirose et al., 2021), BEiT (Wang et al., 2022) and CoCa (Yu et al., 2022), have been achieving exceeding performance in a great many tasks.

Transformer encoder blocks, as shown in Fig. 1, mainly contain two critical components: Multi-head Scaled-dot-product self-attention and a feed-forward network (MLP). Inputs are fed in the form of patches, which are usually embedding vectors for words in Bert, or for fractions of images in ViT. The relative position of patches are learned by position embeddings (Vaswani et al., 2017), which are injected into the model. Recent studies have found that by removing the position embeddings, ViT merely loses 4% accuracy on ImageNet (Russakovsky et al., 2015). And the work further reports the shuffling invariance property of ViT through experiments.

Figure 1: Transformer Encoder Block

Split learning. As deep neural networks are growing deeper and wider, it is hardly fit for the edge which lacks the computational power but owns abundant data. Hence split learning (Gupta & Raskar, 2018) proposes to let the cloud server shoulder partial computation without accessing the data. To achieve this, a model is split into two parts, deployed on the edge and the cloud, respectively. The edge processes the first few layers and sends the intermediate features to the cloud which holds the main body of the model. If the cloud does not own the corresponding labels, it returns the prediction to the edge for computing the loss. In the backward propagation, error gradients are passed between the edge and the cloud instead of the features.

Studies have revealed that the untrusted cloud can reconstruct the private data with the intermediate features (Erdogan et al., 2021; Isola et al., 2017). Additionally, split learning allows the cloud to directly touch the model weights, which is also a threat to the privacy of training data at the edge.

Privacy-preserving split learning. Many efforts have been made to preserve data privacy in split learning but most have been devoted to inference data, rather than training data or model protection. Almost no lightweight protection scheme is feasible for trained model weights, which should be proprietary to the edge, and not be taken advantage of by the cloud. Traditional methods include cryptographic ones such as secure multi-party computation and homomorphic encryption. But these methods typically involve significant overhead in encryption, decryption, computation, and communication. Lee et al. (2022) implemented a polynomial approximation over nonlinear functions and encrypted the training process with FHE, but it demands 10 to 1000 times more computation power compared to plain split learning. The approximation computation also results in accuracy losses. Xiao et al. (2020) adversarially trained the edge sub-module to produce features not containing any private information, but sufficient to complete the learning task. However, the method only works when the learning converges and thus suffers potential leakage at the early stage of training. Dong et al. (2019) inserted Gaussian noise to the features following the convention of differential privacy. Ryoo et al. (2018) adjusted the image resolution to seek a sweetspot in the tradeoff between utility

and privacy. These works have to sacrifice considerable model accuracy performance to meet the privacy requirement.

Matrix Multiplication Computation (MMC) is a fundamental mathematical operation, and works (Lei et al., 2014; Liu et al., 2021) propose random permutation as an encryption scheme to the out-sourced MMC tasks. To enhance the security, the recent work (Liu et al., 2021) introduces additive perturbation besides the multiplicative one; but their works are mostly theoretical and should be viewed as complementary to ours. We investigate the privacy guarantee in a more challenging scene — deep neural networks, and propose a practical protection scheme.

3   PROBLEM FORMULATION

We formally formulate our problem in the setting of split learning. The edge holds a private data set $\mathbb{D}_{train} = \{X, Y\}$, where $X \in \mathbb{R}^d$ is the private data and $Y = \{y_1, \cdots, y_n\}$ are k-class labels. The edge aims at training a model with the assistance of the cloud, yet without revealing any private input or the model weights to the cloud. The cloud possesses powerful computing power but is curious about the private data of the edge and the model it trains. The edge selects a model and splits it into two parts, F and F', to deploy on the edge and the cloud, respectively. Referring to the loss function as L_{task} and the local privacy-preserving method as M, the ultimate goal of the edge is to train F and F' jointly to

$$\underset{F, F'}{\text{minimize}} \ L_{task}(F'(F(X)), Y), \tag{1}$$

without revealing X or F' to the cloud or any other third party. Although the cloud does not directly access the input, it is possible to invert X from $F(X)$ by the following attacks.

We assume the cloud server is honest-but-curious, meaning that it obeys the protocol and performs the learning task accordingly, but is curious about the private data. Depending on whether the edge model is accessible to the attacker, we divide the attacks into two categories:

Black-box attacks. The attacker is able to obtain the auxiliary data set X_{aux} and the corresponding features $F(X_{aux})$, which may be collected over multiple training rounds. It trains an inversion model G over $(X_{aux}, F(X_{aux}))$ to invert the raw input from features. The attack goal can be

$$\underset{G}{\text{minimize}} \ L_{attack}(G(M(F^1(X_{aux})), \cdots, M^e(F^e(X_{aux}))), X_{aux}). \tag{2}$$

The superscript e denotes the number of trained iterations for the features. The loss L_{attack} can be the mean square error (MSE) between the reconstructed input $\tilde{X}_{aux}$ and X_{aux}. At convergence, G works as a decoder to invert features into inputs.

White-box attacks. The attacker has full access to the edge model and the protection mechanism M, and performs gradient descent over $M(F(X))$ and its guess $M(F(\tilde{X}))$ by

$$\underset{\tilde{X}}{\text{minimize}} \ L_{attack}(M(F(X)), M(F(\tilde{X}))). \tag{3}$$

Figure 2: The structure of our privacy-preserving split learning over shuffled Transformers.

4 METHODOLOGY

We present how training data, inference data, and the model weights can be protected in our privacy-preserving split learning framework, and then introduce their privacy indications.

4.1 SHUFFLED TRANSFORMERS

The overall scheme of our method is shown in Fig. 2. We split a typical Transformer-based model into three stubs: the part from input layer to patch embeddings residing at the edge, the transformer encoder blocks at the cloud, and the MLP and loss layer at the edge, since the edge owns the data and labels. Position embeddings are removed from the model in training since they potentially compromise the training data privacy, but are kept in the inference stage for better accuracy. Being transmitted between the edge and the cloud, the smashed data in the forward loop and backward loop are referred to as features and error gradients, respectively.

Our method runs at the edge, processing the smashed data transmitted back and forth between the two entities. We introduce four basic operations: row shuffle and unshuffle, column shuffle and unshuffle. All *shuffling orders are secret* of the edge. We perform row and column shuffle to the features sent from the edge to the cloud. The features $\boldsymbol{Z} = F(X)$ are expressed by a (p, d) (*e.g.,* $(197, 768)$) matrix, where p denotes the number of patches and d the dimension of each patch. We shuffle the patches to be sent and unshuffle the received features by

$$\text{Shuffle: } M_{\boldsymbol{Z}}(\boldsymbol{Z}) = \boldsymbol{P}_R \boldsymbol{Z} \boldsymbol{P}_C^{-1}, \tag{4}$$

$$\text{Unshuffle: } M_{\boldsymbol{Z}}^{-1}(F'_{(P)}(M_{\boldsymbol{Z}}(\boldsymbol{Z}))) = \boldsymbol{P}_R^{-1} F'_{(P)}(M_{\boldsymbol{Z}}(\boldsymbol{Z})) \boldsymbol{P}_C, \tag{5}$$

where $\boldsymbol{P}_R \in \{0, 1\}^{p \times p}$ and $\boldsymbol{P}_C \in \{0, 1\}^{d \times d}$ are row and column permutation matrices, respectively, represented by permutations of the identity matrix. The row and column shuffle are jointly denoted as mechanism $M_{\boldsymbol{Z}}$. $\boldsymbol{P}_R$ can be chosen randomly for each $\boldsymbol{Z}$, while $\boldsymbol{P}_C$ is randomly chosen once for the model. The model stub $F'_{(P)}$ on the cloud is trained as the usual network, and the output of the transformer encoder block is sent to the edge for unshuffle by Eq. 5. The backward loop is no different from the normal backward propagation.

Privacy for training data is preserved by $M_{\boldsymbol{Z}}$, as each input is randomly row-shuffled by $\boldsymbol{P}_R$ and column-shuffled by $\boldsymbol{P}_C$ before being sent to the cloud. Note that since no particular patch size is specified, all patch size would work but the finest granularity is recommended for privacy concerns. We will give the formal guarantee in Sec. 4.2.

Privacy for model weights is also guaranteed as the model stub trained on $M_{\boldsymbol{Z}}$ has the following unique property. Letting $F'_{(P)} = \{\boldsymbol{W}_{(P)}, b_{(P)}, \gamma_{(P)}\}$ and $F' = \{\boldsymbol{W}, b, \gamma\}$ denote the {weight matrix, bias, layer normalization parameter} of the cloud model trained on $M_{\boldsymbol{Z}}(\boldsymbol{Z})$ and the normal $\boldsymbol{Z}$, respectively, we have:

$$\boldsymbol{W}_{(P)} = \boldsymbol{P}_C \boldsymbol{W} \boldsymbol{P}_C^{-1} \triangleq M_{\boldsymbol{W}}(\boldsymbol{W}), \ \ b_{(P)} = b \boldsymbol{P}_C^{-1}, \ \ \gamma_{(P)} = \gamma \boldsymbol{P}_C^{-1}. \tag{6}$$

Note that Eq. 6 demands the weight matrix to be a square one, which requires minor modification to the cloud model as we will elaborate on later. It is an interesting fact that if the model is trained on the shuffled patches $M_{\boldsymbol{Z}}(\boldsymbol{Z})$, the randomly initialized weight $\boldsymbol{W}_0$ learns to become $\boldsymbol{W}_{(P)}$ instead of $\boldsymbol{W}$, and thus the true model weights are unknown to the cloud. More importantly, the cloud cannot take advantage of the trained $F'_{(P)}$, as any party except for the edge would yield invalid output on $F'_{(P)}$, as specified below.

Protection of the inference data. Obviously, if the shuffle (Eq. 4) and unshuffle (Eq. 5) procedures give legitimate training results, the testing data can be legally inferred by the same in a single forward loop. Since the data sent to the cloud is shuffled, its privacy is preserved. In addition, only the entity who holds $\boldsymbol{P}_C^{-1}$ would produce valid inference results on $F'_{(P)}$:

$$F'_{(P)}(\boldsymbol{Z}) = \bot, \ \ F'_{(P)}(M_{\boldsymbol{Z}}(\boldsymbol{Z})) = M_{\boldsymbol{Z}}(F'(\boldsymbol{Z})). \tag{7}$$

Re-encrypting the model is also available with our method. The edge may pre-train a secret Transformer body with a secret $\boldsymbol{P}_C$, and later can obtain the unencrypted weights $\boldsymbol{W} = \boldsymbol{P}_C^{-1} \boldsymbol{W}_{(P)} \boldsymbol{P}_C$,

or re-encrypt the model to authorize other party to use it: $\boldsymbol{W}_{(P')} = \boldsymbol{P}_{C'}\boldsymbol{W}\boldsymbol{P}_{C'}^{-1}$. Other parties who hold $\boldsymbol{P}_{C'}$ can further perform privacy-preserving transfer learning or fine-tuning on the model.

Model structure modification. Our method requires all the weight matrices in the Transformer encoder blocks and the MLP layer to be square ones. For example, the multi-head attention in the classical ViT-Base (Dosovitskiy et al., 2020) introduces non-square weight matrices, and its MLP has an input/output dimension of 768 but a hidden layer of dimension 3072. To implement shuffled transformers, each head has to be square: weights of the linear projection layers of Q, K, V are reshaped to $(768 \times no.\_of\_heads, 768)$, so that each head has a shape of $(768, 768)$. Instead of concatenating them, we calculate their average to keep the square shape of the weight matrices, which mildly increases the computational overhead but no accuracy decline. Or one can simply choose to use single-head attention to replace the multi-head one, which also has limited impact to the model performance. The MLP layer is reshaped with 768-hidden units, which keeps the weight matrices square.

4.2 DEFINITION OF PRIVACY

The purpose of shuffling is to prevent the attacker from reconstructing input X given the feature $M_{\boldsymbol{Z}}(\boldsymbol{Z})$. In this work, we consider recovering $\boldsymbol{Z}$ to be the same with reconstructing X, as a black-box or white-box attacker can easily invert X from $\boldsymbol{Z}$. To quantize the likelihood that an adversary rebuilds $\boldsymbol{Z}$ from $M_{\boldsymbol{Z}}(\boldsymbol{Z})$, we first define neighboring permutations as:

Definition 1. *(Neighboring Permutations.) For feature matrix $\boldsymbol{Z} \in \mathbb{R}^{p \times d}$, all row-column permutation orders of $\boldsymbol{Z}$ constitute $\mathbb{S}$. Any two permutations $\sigma, \sigma' \in \mathbb{S}$ are neighboring permutations.*

Our privacy definition based on shuffling is as follows.

Definition 2. *(σ-privacy.) Given the private feature $\boldsymbol{Z}$ and permutation set $\mathbb{S}$, a randomized shuffling mechanism $M : M(\boldsymbol{Z}) \mapsto \boldsymbol{Z}' \in \mathbb{S}$ is σ-private if for all $\boldsymbol{Z}, \boldsymbol{Z}'$, and any neighbouring permutations σ, σ', we have*

$$\Pr[M(\sigma(\boldsymbol{Z})) = \boldsymbol{Z}'] = \Pr[M(\sigma'(\boldsymbol{Z})) = \boldsymbol{Z}'].\tag{8}$$

σ-privacy suggests that shuffling mechanism M is agnostic of the relative order of patches. Thus any adversary is incapable of telling the original order from its neighboring permutations, given the perturbed feature $\boldsymbol{Z}'$. This definition shares some similarities with d_σ-privacy in (Meehan et al., 2021) but ours removes α in d_σ-privacy as permutations are sampled from a uniform distribution rather than Mallows model. With the definition, we can calculate that if all row-column permutations are equally likely for an input, our $M_{\boldsymbol{Z}}(\boldsymbol{Z})$ has the probability of $\frac{1}{p!d!}$ to reveal the true $\boldsymbol{Z}$, which is negligible. Similarly for weights shuffling, $M_{\boldsymbol{W}}(\boldsymbol{W})$ and $M_{\boldsymbol{W}}(\boldsymbol{P}\boldsymbol{W}\boldsymbol{P}^{-1})$ (where $\boldsymbol{P}$ is a random permutation matrix) have the same probability to yield $\boldsymbol{W}'$, which has $\frac{1}{d!}$ probability to be the true $\boldsymbol{W}$. Hence the mechanism prevents any adversary from recovering the true weights. Hereby we have

Proposition 1. *Input shuffling $M_{\boldsymbol{Z}}(\cdot)$ is σ-private with $\mathbb{S}$ being the set for all possible $\boldsymbol{P}_R, \boldsymbol{P}_C^{-1}$ permutations.*

Proposition 2. *Weights shuffling $M_{\boldsymbol{W}}(\cdot)$ is σ-private with $\mathbb{S}$ being the set for all possible $\boldsymbol{P}_C, \boldsymbol{P}_C^{-1}$ permutations.*

5 ANALYSIS

In this section, we show why shuffled Transformer works through theoretical analysis. Fig. 3 offers a clear overview for the important properties discussed, and the detailed proofs can be found in Appendix A.

Denoting the Transformer encoder as Enc, we have the following theorem:

Theorem 1. *Transformer encoder blocks are **row-permutation-equivalent**:*

$$Enc(\boldsymbol{P}_R\boldsymbol{Z}) = \boldsymbol{P}_R Enc(\boldsymbol{Z})\tag{9}$$

As shown in Fig. 3a, the row permutation $\boldsymbol{P}_R$ can 'pass through' the encoder so that a reverse operation can be performed at the output of the encoder to return the original output: $\boldsymbol{P}_R^{-1}\text{Enc}(\boldsymbol{P}_R\boldsymbol{Z}) =$

(a) Training the cloud model on $\boldsymbol{Z}$ or $\{\boldsymbol{P}_{Ri}\boldsymbol{Z}_i\}$ yields the same $\boldsymbol{W}$.

(b) Training the cloud model on $\{\boldsymbol{Z}_i\boldsymbol{P}_C^{-1}\}$ or $\{\boldsymbol{P}_{Ri}\boldsymbol{Z}\boldsymbol{P}_C^{-1}\}$ returns $\boldsymbol{W}_{(P)} = \boldsymbol{P}_C\boldsymbol{W}\boldsymbol{P}_C^{-1}$.

(c) Decryption and re-encryption of trained model can be implemented by matrix multiplication.

Figure 3: Properties of shuffled Transformers. White blocks denote initialized models, gray blocks mean the naturally trained models, and red ones indicates 'encrypted' model $\text{Enc}_{(P)}$. $\boldsymbol{O}$ represents the original outputs. R_i suggests the order of row shuffle can vary for each input.

$\text{Enc}(\boldsymbol{Z})$. More interestingly, the gradients of Transformer encoder blocks in the backward propagation are invariant to row shuffle:

Theorem 2. *The gradients of Transformer encoder blocks w.r.t. the loss l are **row-permutation-invariant**:*

$$\frac{\partial l}{\partial \boldsymbol{W}_{(R)}} = \frac{\partial l}{\partial \boldsymbol{W}}. \tag{10}$$

In Eq. 10, $\boldsymbol{W}$ generally refers to the weights learned naturally in the multi-head attention or the MLP. $\boldsymbol{W}_{(R)}$ is the corresponding weights learned on $\boldsymbol{P}_R\boldsymbol{Z}$. Hence indicating by Fig. 3a, the learned weights are the same with or without row shuffle on $\boldsymbol{Z}$. Rigorously speaking, it is not the same $\boldsymbol{W}$ learned since the weights are initialized differently; it can be considered the row shuffle is transparent to the Transformer encoder blocks, either in training or inference.

Theorem 3. *If the Transformer encoder is permuted as $\text{Enc}_{(P)} = \boldsymbol{P}_C\text{Enc}\boldsymbol{P}_C^{-1}$, $\text{Enc}_{(P)}$ is row-column-shuffle-equivalent:*

$$\text{Enc}_{(P)}(\boldsymbol{P}_R\boldsymbol{Z}\boldsymbol{P}_C^{-1}) = \boldsymbol{P}_R\text{Enc}(\boldsymbol{Z})\boldsymbol{P}_C^{-1}. \tag{11}$$

And the outputs can be reversed by $\boldsymbol{P}_R^{-1}\text{Enc}_{(P)}(\boldsymbol{P}_R\boldsymbol{Z}\boldsymbol{P}_C^{-1})\boldsymbol{P}_C = \text{Enc}(\boldsymbol{Z})$. More intriguingly, we have

Theorem 4. *The gradients of Transformer encoder blocks $\text{Enc}_{(P)}$ w.r.t. the loss l is **column-permutation-equivalent**:*

$$\frac{\partial l}{\partial \boldsymbol{W}_{(P)}} = \boldsymbol{P}_C\frac{\partial l}{\partial \boldsymbol{W}}\boldsymbol{P}_C^{-1}. \tag{12}$$

By induction, we prove that if one shuffles the normally trained Enc, it would obtain an equivalent $\text{Enc}_{(P)}$ trained on the shuffled data. Specifically, letting the weights of the normally trained model be $\boldsymbol{W}$, the weights of the model trained on $\boldsymbol{P}_R\boldsymbol{Z}\boldsymbol{P}_C^{-1}$ are $\boldsymbol{P}_C\boldsymbol{W}\boldsymbol{P}_C^{-1}$, as shown in Fig. 3b. If the 'encrypted' model $\text{Enc}_{(P)}$ is deployed in the cloud, the cloud would have no clue about the model weights or the inputs, but train the model 'blindly' for the edge. Compared to cryptographic tools like fully homomorphic encryption (Lee et al., 2022), our 'encryption' method realizes a similar idea but with far less computation overhead.

Similar to the 'encryption' process, 'decryption' is feasible by reverse shuffling, as in Fig. 3c. Re-encryption is also viable by matrix multiplication, suggesting that Enc can be 'encrypted' not only by training on shuffled data, but also by permuting the trained weights.

To sum up, the row shuffle is transparent to the Transformer encoder blocks. The row-and-column-shuffle serves in a similar way to homomorphic encryption, in that the weights of $\text{Enc}_{(P)}$ are not known, while $\text{Enc}_{(P)}$ is only capable of processing shuffled $\boldsymbol{Z}$. Either by training on shuffled data or by matrix multiplication, can the weights of $\text{Enc}_{(P)}$ be obtained. The entire process does not incur additional computational burden, or sacrifice accuracy performance.

6   EXPERIMENTS AND EVALUATIONS

We first verify the properties of the shuffled Transformer by experiments, and show its defence capability against attacks.

Setup: Our implementation is built on `Pytorch` and `Torchvision`. We use Cifar10 (Krizhevsky et al., 2009) consisting of 60,000 natural images in 10 classes, and CelebA (Liu et al., 2015) containing 2,022,599 faces from 10,177 celebrities. On CelebA, we adopt `timm`[1] model vit_base_patch16_224 (ViT-Base) pre-trained on ImageNet to transfer to a 40-binary-attribute classification task. We adopt a single-head ViT-Base according to the modification stated in Sec. 4.1 with the following structure: 12 layers, image size=224, patch size=16, embedding_dim=768, mlp_hidden_dim=768 and one head. The model is referred to as single-head ViT for CelebA later. A SGD optimizer is used with a cosine scheduler, for which the (initial, final) learning rate are set to $(0.05, 2 \times 10^{-4})$ and $(5 \times 10^{-4}, 2 \times 10^{-6})$ for the MLP and the encoder blocks, respectively.

On Cifar10, we use a smaller ViT with the structure: 6 layers, image size=32, patch size=4, embedding_dim=512, mlp_hidden_dim=512, 1 head in the row-column-shuffle case and 6 heads in others. The models are called the single-head and the multi-head ViT for Cifar10, respectively. These ViTs are trained from scratch on Cifar10, and thus it provides satisfying but inferior accuracy to the pre-trained one. An Adam optimizer and a cosine scheduler with learning rate 10^{-4} are used.

Baselines: We compare our method with a set of existing privacy-preserving methods. Conventional cryptographic tools are not included for unbearable computational and communication costs. Baselines include unprotected split learning (**SL**), adversarial learning (**adv**) (Xiao et al., 2020), methods based on **Transform** containing adding Gaussian noise $\sim \mathcal{N}(0, 4)$ (**GN**) (Dong et al., 2019) and **Blur** (Ryoo et al., 2018).

Metrics: We evaluate model performance from the accuracy, privacy, and efficiency aspects. The average classification accuracy of 40 attributes, and the 10-class classification accuracy are reported for CelebA and Cifar10, respectively. Privacy is gauged by the attackers' capability in reconstructing inputs. We select popular metrics such as Structural Similarity (SSIM), Peak Signal to Noise Ratio (PSNR) (Hore & Ziou, 2010), and F-SIM. For F-SIM, We feed the original and reconstructed inputs into a third-party network and compare the cosine similarity between the features. The third-party network for CelebA is InceptionResNetV1 of FaceNet (Schroff et al., 2015), pre-trained on VggFace2 (Cao et al., 2018), and that for Cifar10 is ResNet18 pre-trained on ImageNet.

6.1   VERIFYING PROPERTIES

We experimentally verify the properties of shuffled Transformers by their accuracy performance.

Row-permutation-equivalence: To verify Thm. 1 and Thm. 2, we train and test models with or without row-shuffled (RS) inputs. No model modification are needed for row shuffle and thus the original model structures are used. Testing accuracies are reported in Tab. 1. Despite being shuffled or not, the testing data reach approximately the same accuracy for each dataset, verifying the row shuffle is indeed transparent to the Transformer encoder blocks. The model trained on row-shuffled data has an equivalent performance to the model normally trained, verifying their training processes are equivalent. On CelebA, removing the position embedding from the model merely leads to an 0.506% accuracy drop compared to the benchmark (91.908%).

Row-column-shuffle-equivalence: To verify Thm. 3 and Thm. 4, we train and test on natural or row-column-shuffled (RCS) data, and report the testing accuracies in Tab. 1. Particularly for CelebA, we pre-train the single-head ViT on RCS (natrual) ImageNet data, and transfer the weights of the 20^{th} epoch to CelebA. 'Training with RCS' suggests both pre-training and fine-tuning are on

---

[1]https://github.com/rwightman/pytorch-image-models

Table 1: Accuracies(%) on row-shuffled and row-column-shuffled data. Shuffle methods of the testing data correspond to that of the training data.

| Train
Test	ViT Cifar10		ViT-Base CelebA		multi-head ViT Cifar10		single-head ViT CelebA	
	w/ RS	w/o RS	w/ RS	w/o RS	w/ RCS	w/o RCS	w/ RCS	w/o RCS
w/ Shuffle	78.35	78.38	91.40	91.61	80.76	10.38	91.30	79.76
w/o Shuffle	79.08	78.40	91.62	91.52	7.50	80.98	71.50	91.51

RCS data. Note that due to the imbalanced data distribution, the average accuracy reported for the 40 attributes of CelebA is around $66 - 73\%$ for random guesses. And the benchmark of CelebA on pre-trained ImageNet is around 91%. It is clear that if the model is trained on normal data but test on shuffled data, or vice versa, its performance is close to random guesses. Otherwise, the shuffled Transformer almost achieves no accuracy loss.

Table 2: Accuracies(%) of decrypted/re-encrypted models.

	Encrypted	Decrypted
single-head ViT Cifar10	79.55	79.01
multi-head ViT Cifar10	80.96	80.67
single-head ViT CelebA	91.51	91.30

(a) Normal Transformer   (b) Shuffled Transformer

Figure 4: Cosine similarity between every two patches.

Decryption and Re-encryption: We also verify decrypting and re-encrypting the weight matrices are feasible with Eq. 6. For each model, we 'encrypt' the naturally trained model by multiplying a random permutation matrix and have it tested on the shuffled test data. And we also 'decrypt' the model trained on row-column-shuffled data and test it on plain data. All the testing accuracies are reported in Tab. 2, and the results are almost no different from the benchmarks.

Privacy guarantee. One may argue that the original patch embeddings may be correlated in space and thus each permutation may not be equally likely to occur. Hence we draw the cosine similarity of the position embeddings between every pair of patches at the final epoch, on models trained normally and with RCS, respectively, on CelebA. By Fig. 4, the learned position embedding of the latter appear to be random while the former clearly marks relative position of the patch in the input (one observes the sketch of a face). Hence we consider the position information is discarded during training with shuffled Transformers. More discussion on the position embedding can be found in Appendix B.4.

6.2 DEFENCE AGAINST ATTACKS

We focus on the privacy performance of our method against attacks in Sec. 3, in comparison to the baselines.

Defence in inference. The train set of CelebA is adopted as X_{aux} and the test set is used as the private inference data. All defence methods are applied to the same edge model F, a fixed patch_embedding layer.

In inference, the black-box attacker can only acquire smashed data once, and thus we fix weights of the edge model and train the attacker model to minimize the loss of Eq. 2 where $e = 1$. We implement the attacker with an MAE decoder G, pre-trained on ImageNet with an additional position embedding layer at the head of the decoder and a Tanh activation layer at the rear. We report the inference accuracy and attack performance in Tab. 3. It is observed that adv and Blur fails to maintain a privacy guarantee. GN successfully prevents the attacker from reconstructing the private inputs but degrades the accuracy considerably. Our methods achieve satisfying privacy performance across all metrics while sharing a close accuracy to SL.

Table 3: Accuracy and privacy on the inference data, CelebA. ↓ means desirable direction.

	Utility	Privacy in Black-Box			Privacy in White-Box		
	Accuracy↑	SSIM↓	PSNR↓	F-SIM↓	SSIM↓	PSNR↓	F-SIM↓
unprotected SL	91.91%	0.645	16.247	0.933	0.173	12.411	0.738
adv	91.82%	0.539	12.123	0.767	0.173	12.411	0.738
Blur	89.84%	0.501	14.233	0.501	0.079	10.729	0.124
GN	82.40%	0.290	13.052	0.361	0.078	9.968	0.127
Our RS	91.83%	0.243	10.395	0.299	0.315	10.519	0.139
Our RCS	91.58%	0.270	10.629	0.345	0.160	10.464	0.107

Original   Black: SL   Black: adv   Black: blur   Black: RCS   White: SL   White: RCS   e=10: SL   e=10: RCS

Figure 5: The visualization effect of input reconstruction on CelebA under black-box attacks (Black), white-box attacks (White) and attacks to training (e = 10).

The white-box attack follows Eq. 3 with 100,000 optimization iterations. As we can tell from Tab. 3, the transform-based methods successfully defends against the white-box attack for introducing randomness, so as our method, but their methods suffer great accuracy losses. This is also verified in the visualization results of Fig. 5, and further results on Cifar10 are left to Appendix B.3.

Defence in training. We launch an adaptive black-box attack on features collected over 10 rounds ($e = 10$ in Eq. 2). The final testing accuracy and privacy performance is reported in Tab. 4. It can be found that our RCS is strong in preserving the privacy of the training data without little loss of accuracy.

Table 4: Results of black-box attack to the training process.

	Utility	Privacy		
	Accuracy↑	SSIM↓	PSNR↓	F-SIM↑
blur	89.84%	0.34	13.60	0.39
Our RS	91.40%	0.27	10.81	0.39
Our RCS	89.92%	0.09	10.46	0.34

Figure 6: The computational overhead, memory cost, and convergence curves of the normal split learning and our method. PE stands for position embedding.

Efficiency. To see if our method incurs additional overhead to the normal split learning framework, we evaluate its efficiency by MAC operation counts (Macc, recording the number of multiplication and addition operations) on the edge, the memory consumption, and the convergence curve of pre-training ImageNet. The ImageNet image of size 224×224 is adopted with a batch size 256. Results of Fig. 6 can be concluded that our methods are almost as efficient as the normal SL.

7 CONCLUSION

We propose a blind training method to realize privacy-preserving split learning, where the cloud trains over unknown data and model for the edge. The method is founded on the shuffle invariance property we discovered on Transformers, and other Transformer-based models. Theoretical proofs, property verification, and real-world performance resisting attacks are provided. Our method successfully defends black-box, and white-box attacks without degrading accuracy and efficiency.

REFERENCES

Qiong Cao, Li Shen, Weidi Xie, Omkar M Parkhi, and Andrew Zisserman. Vggface2: A dataset for recognising faces across pose and age. In *2018 13th IEEE international conference on automatic face & gesture recognition (FG 2018)*, pp. 67–74. IEEE, 2018.

Nicholas Carlini, Chang Liu, Úlfar Erlingsson, Jernej Kos, and Dawn Song. The secret sharer: Evaluating and testing unintended memorization in neural networks. In Nadia Heninger and Patrick Traynor (eds.), *28th USENIX Security Symposium, USENIX Security 2019, Santa Clara, CA, USA, August 14-16, 2019*, pp. 267–284. USENIX Association, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Jinshuo Dong, Aaron Roth, and Weijie J Su. Gaussian differential privacy. *arXiv preprint arXiv:1905.02383*, 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Ege Erdogan, Alptekin Kupcu, and A Ercument Cicek. Unsplit: Data-oblivious model inversion, model stealing, and label inference attacks against split learning. *arXiv preprint arXiv:2108.09033*, 2021.

Matt Fredrikson, Somesh Jha, and Thomas Ristenpart. Model inversion attacks that exploit confidence information and basic countermeasures. In *Proceedings of the 22nd ACM SIGSAC conference on computer and communications security*, pp. 1322–1333, 2015.

Otkrist Gupta and Ramesh Raskar. Distributed learning of deep neural network over multiple agents. *Journal of Network and Computer Applications*, 116:1–8, 2018.

Shota Hirose, Naoki Wada, Jiro Katto, and Heming Sun. Vit-gan: Using vision transformer as discriminator with adaptive data augmentation. In *2021 3rd International Conference on Computer Communication and the Internet (ICCCI)*, pp. 185–189. IEEE, 2021.

Alain Hore and Djemel Ziou. Image quality metrics: Psnr vs. ssim. In *2010 20th international conference on pattern recognition (ICPR)*, pp. 2366–2369. IEEE, 2010.

Phillip Isola, Jun-Yan Zhu, Tinghui Zhou, and Alexei A Efros. Image-to-image translation with conditional adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition (CVPR)*, pp. 1125–1134, 2017.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Joon-Woo Lee, HyungChul Kang, Yongwoo Lee, Woosuk Choi, Jieun Eom, Maxim Deryabin, Eunsang Lee, Junghyun Lee, Donghoon Yoo, Young-Sik Kim, et al. Privacy-preserving machine learning with fully homomorphic encryption for deep neural network. *IEEE Access*, 10:30039–30054, 2022.

Xinyu Lei, Xiaofeng Liao, Tingwen Huang, and Feno Heriniaina. Achieving security, robust cheating resistance, and high-efficiency for outsourcing large matrix multiplication computation to a malicious cloud. *Information sciences*, 280:205–217, 2014.

Chun Liu, Xuexian Hu, Xiaofeng Chen, Jianghong Wei, and Wenfen Liu. An efficient matrix multiplication with enhanced privacy protection in cloud computing and its applications. *arXiv preprint arXiv:2105.05525*, 2021.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of the IEEE international conference on computer vision*, pp. 3730–3738, 2015.

Casey Meehan, Amrita Roy Chowdhury, Kamalika Chaudhuri, and Somesh Jha. Privacy implications of shuffling. In *International Conference on Learning Representations (ICLR)*, 2021.

Muhammad Muzammal Naseer, Kanchana Ranasinghe, Salman H Khan, Munawar Hayat, Fahad Shahbaz Khan, and Ming-Hsuan Yang. Intriguing properties of vision transformers. *Advances in Neural Information Processing Systems*, 34:23296–23308, 2021.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision (IJCV)*, 115(3):211–252, 2015.

Michael Ryoo, Kiyoon Kim, and Hyun Yang. Extreme low resolution activity recognition with multi-siamese embedding learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.

Florian Schroff, Dmitry Kalenichenko, and James Philbin. Facenet: A unified embedding for face recognition and clustering. In *Proceedings of the IEEE conference on computer vision and pattern recognition (CVPR)*, pp. 815–823, 2015.

Andreas Steiner, Alexander Kolesnikov, Xiaohua Zhai, Ross Wightman, Jakob Uszkoreit, and Lucas Beyer. How to train your vit? data, augmentation, and regularization in vision transformers. 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Wenhui Wang, Hangbo Bao, Li Dong, Johan Bjorck, Zhiliang Peng, Qiang Liu, Kriti Aggarwal, Owais Khan Mohammed, Saksham Singhal, Subhojit Som, et al. Image as a foreign language: Beit pretraining for all vision and vision-language tasks. *arXiv preprint arXiv:2208.10442*, 2022.

Taihong Xiao, Yi-Hsuan Tsai, Kihyuk Sohn, Manmohan Chandraker, and Ming-Hsuan Yang. Adversarial learning of privacy-preserving and task-oriented representations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 12434–12441, 2020.

Jiahui Yu, Zirui Wang, Vijay Vasudevan, Legg Yeung, Mojtaba Seyedhosseini, and Yonghui Wu. Coca: Contrastive captioners are image-text foundation models, 2022.

Li Yuan, Yunpeng Chen, Tao Wang, Weihao Yu, Yujun Shi, Zi-Hang Jiang, Francis EH Tay, Jiashi Feng, and Shuicheng Yan. Tokens-to-token vit: Training vision transformers from scratch on imagenet. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 558–567, 2021.

Yuheng Zhang, Ruoxi Jia, Hengzhi Pei, Wenxiao Wang, Bo Li, and Dawn Song. The secret revealer: Generative model-inversion attacks against deep neural networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition (CVPR)*, pp. 253–261, 2020.

A PROOF OF THEORIES

We show the theorems in Sec. 5 hold for Transformer encoder blocks.

A.1 NOTATIONS AND LEMMAS

The Transformer encoder block is denoted as Enc and the loss is ℓ. The patch embedding of a single input $\boldsymbol{X}$ is expressed as $\boldsymbol{Z}$ of shape (p, d). The first layer in the self-attention contains three parallel linear layers projecting $\boldsymbol{Z}$ to Q, K, V as

$$\boldsymbol{Z}\boldsymbol{W}_Q^T = \boldsymbol{Q}, \tag{13}$$

$$\boldsymbol{Z}\boldsymbol{W}_K^T = \boldsymbol{K}, \tag{14}$$

$$\boldsymbol{Z}\boldsymbol{W}_V^T = \boldsymbol{V}. \tag{15}$$

Q, K, V are fed to the following attention operation

$$\boldsymbol{S} = Softmax(\frac{\boldsymbol{Q}\boldsymbol{K}^T}{\sqrt{d}}), \tag{16}$$

$$\boldsymbol{A} = \boldsymbol{S}\boldsymbol{V}, \tag{17}$$

where $\boldsymbol{S}$ and $\boldsymbol{A}$ are the softmax output, and the attention output, respectively.

The part following the attention layer is the MLP layer:

$$\boldsymbol{A}_1 = \boldsymbol{A}\boldsymbol{W}_1^T, \tag{18}$$

$$\boldsymbol{H} = a(\boldsymbol{A}_1), \tag{19}$$

$$\boldsymbol{A}_2 = \boldsymbol{H}\boldsymbol{W}_2^T \tag{20}$$

where $\boldsymbol{A}_1, \boldsymbol{A}_2$ are the outputs of the linear layers with weights $\boldsymbol{W}_1, \boldsymbol{W}_2$, respectively, and $\boldsymbol{H}$ is the output of the element-wise activation function a, being ReLu or Tanh.

Element-wise operators including shortcut, Hadamard product, matrix addition/subtraction and other element-wise functions are permutation-equivalent:

Lemma 1. *Element-wise operators are permutation-equivalent:*

$$(\boldsymbol{P}_1\boldsymbol{A}\boldsymbol{P}_2) \odot (\boldsymbol{P}_1\boldsymbol{B}\boldsymbol{P}_2) = \boldsymbol{P}_1(\boldsymbol{A} \odot \boldsymbol{B})\boldsymbol{P}_2. \tag{21}$$

On the left hand-side of the equation, a_{ij} in $\boldsymbol{A}$ and b_{ij} in $\boldsymbol{B}$ are permuted to the same position before being performed the operation. On the right hand-side, a_{ij} and b_{ij} are performed the operation of which the results are permuted. The two are obviously equivalent. Importantly,

Lemma 2. *Softmax is permutation-equivalent:*

$$Softmax(\boldsymbol{P}_1\boldsymbol{A}\boldsymbol{P}_2) = \boldsymbol{P}_1 Softmax(\boldsymbol{A})\boldsymbol{P}_2. \tag{22}$$

This is because an element is always normalized with the same group of elements, which are not changed in permutations. Thus Softmax is permutation-equivalent.

A.2 PROOF OF THEOREM 1

Proof. We prove the row-permutation equivalence of Transformer encoder blocks in forward propagation (Eq. 10). We denote the row-permutation matrix as $\boldsymbol{P}_R$. Features are permuted as $\boldsymbol{Z}_{(R)} = \boldsymbol{P}_R\boldsymbol{Z}$. It is worth noting that

$$\boldsymbol{P}_R^T\boldsymbol{P}_R = \boldsymbol{E}$$

holds for permutation matrix $\boldsymbol{P}_R$. $\boldsymbol{E}$ is the identity matrix.

We first prove the permutation equivalence of attention.

$$\begin{aligned}
\boldsymbol{A}_{(R)} &= Softmax(\frac{\boldsymbol{Q}_{(R)}\boldsymbol{K}_{(R)}^T}{\sqrt{d}})\boldsymbol{V}_{(R)} \\
&= Softmax(\frac{\boldsymbol{Z}_{(R)}\boldsymbol{W}_Q^T\boldsymbol{W}_K\boldsymbol{Z}_{(R)}^T}{\sqrt{d}})\boldsymbol{Z}_{(R)}\boldsymbol{W}_V^T \\
&= Softmax(\frac{\boldsymbol{P}_R\boldsymbol{Z}\boldsymbol{W}_Q^T\boldsymbol{W}_K\boldsymbol{Z}^T\boldsymbol{P}_R^T}{\sqrt{d}})\boldsymbol{P}_R\boldsymbol{Z}\boldsymbol{W}_V^T \\
&= \boldsymbol{P}_R Softmax(\frac{\boldsymbol{Z}\boldsymbol{W}_Q^T\boldsymbol{W}_K\boldsymbol{Z}^T}{\sqrt{d}})\boldsymbol{P}_R^T\boldsymbol{P}_R\boldsymbol{Z}\boldsymbol{W}_V^T \\
&= \boldsymbol{P}_R Softmax(\frac{\boldsymbol{Z}\boldsymbol{W}_Q^T\boldsymbol{W}_K\boldsymbol{Z}^T}{\sqrt{d}})\boldsymbol{Z}\boldsymbol{W}_V^T \\
&= \boldsymbol{P}_R Softmax(\frac{\boldsymbol{Q}\boldsymbol{K}^T}{\sqrt{d}})\boldsymbol{V} \\
&= \boldsymbol{P}_R\boldsymbol{A},
\end{aligned}$$

and thus

$$Attention(\boldsymbol{P}_R \boldsymbol{Z}) = \boldsymbol{P}_R Attention(\boldsymbol{Z}). \tag{23}$$

By Lemma 2, the softmax layer following the attention is permutation-equivalent. And the subsequent is the MLP layer which satisfies:

$$\begin{aligned}
\boldsymbol{A}_{2(R)} &= a(\boldsymbol{A}_{(R)} \boldsymbol{W}_1^T) \boldsymbol{W}_2^T \\
&= a(\boldsymbol{P}_R \boldsymbol{A} \boldsymbol{W}_1^T) \boldsymbol{W}_2^T \\
&= \boldsymbol{P}_R a(\boldsymbol{A} \boldsymbol{W}_1^T) \boldsymbol{W}_2^T \\
&= \boldsymbol{P}_R \boldsymbol{A}_2,
\end{aligned}$$

meaning

$$MLP(\boldsymbol{P}_R \boldsymbol{A}) = \boldsymbol{P}_R MLP(\boldsymbol{A}). \tag{24}$$

Hence we have proved the transformer encoder block is row-permutation-equivalent:

$$Enc(\boldsymbol{P}_R \boldsymbol{Z}) = \boldsymbol{P}_R Enc(\boldsymbol{Z}). \tag{25}$$

$\square$

A.3   PROOF OF THEOREM 2

Proof. To prove the gradients are the same when the inputs are row-shuffled, we first calculate the all the gradients from the final layer back to the first. Gradients are expressed as

$$\begin{aligned}
\mathrm{d}l &= \mathrm{tr}(\frac{\partial l}{\partial \boldsymbol{A}_2}^T \mathrm{d}\boldsymbol{A}_2) \\
&= \mathrm{tr}(\frac{\partial l}{\partial \boldsymbol{A}_2}^T (\mathrm{d}\boldsymbol{H})\boldsymbol{W}_2^T) + \mathrm{tr}(\frac{\partial l}{\partial \boldsymbol{A}_2}^T \boldsymbol{H}\mathrm{d}(\boldsymbol{W}_2^T)).
\end{aligned}$$

Let's study $\boldsymbol{H}$ first:

$$\begin{aligned}
\mathrm{d}l_1 &\triangleq \mathrm{tr}(\frac{\partial l}{\partial \boldsymbol{A}_2}^T (\mathrm{d}\boldsymbol{H})\boldsymbol{W}_2^T) \\
&= \mathrm{tr}(\boldsymbol{W}_2^T \frac{\partial l}{\partial \boldsymbol{A}_2}^T \mathrm{d}\boldsymbol{H}) \\
&= \mathrm{tr}((\frac{\partial l}{\partial \boldsymbol{A}_2}\boldsymbol{W}_2)^T \mathrm{d}\boldsymbol{H}),
\end{aligned}$$

indicating

$$\frac{\partial l}{\partial \boldsymbol{H}} = \frac{\partial l}{\partial \boldsymbol{A}_2}\boldsymbol{W}_2. \tag{26}$$

For $\boldsymbol{W}_2$,

$$\begin{aligned}
\mathrm{d}l_2 &\triangleq \mathrm{tr}(\frac{\partial l}{\partial \boldsymbol{A}_2}^T \boldsymbol{H}\mathrm{d}(\boldsymbol{W}_2^T)) \\
&= \mathrm{tr}(\mathrm{d}\boldsymbol{W}_2 \boldsymbol{H}^T \frac{\partial l}{\partial \boldsymbol{A}_2}) \\
&= \mathrm{tr}((\frac{\partial l}{\partial \boldsymbol{A}_2}^T \boldsymbol{H})^T \mathrm{d}\boldsymbol{W}_2),
\end{aligned}$$

and

$$\frac{\partial l}{\partial \boldsymbol{W}_2} = \frac{\partial l}{\partial \boldsymbol{A}_2}^T \boldsymbol{H}. \tag{27}$$

For $\boldsymbol{A}_1$:

$$dl_1 = \text{tr}((\frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{W}_2)^T d\boldsymbol{H})$$

$$= \text{tr}(\frac{\partial l}{\partial \boldsymbol{H}}^T d(a(\boldsymbol{A}_1)))$$

$$= \text{tr}(\frac{\partial l}{\partial \boldsymbol{H}}^T a'(\boldsymbol{A}_1) \odot d\boldsymbol{A}_1))$$

$$= \text{tr}((\frac{\partial l}{\partial \boldsymbol{H}} \odot a'(\boldsymbol{A}_1))^T d\boldsymbol{A}_1),$$

and

$$\frac{\partial l}{\partial \boldsymbol{A}_1} = \frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{W}_2 \odot a'(\boldsymbol{A}_1). \tag{28}$$

Similarly, we calculate the gradients of $\boldsymbol{A}$ and $\boldsymbol{W}_1$:

$$\frac{\partial l}{\partial \boldsymbol{A}} = \frac{\partial l}{\partial \boldsymbol{A}_1} \boldsymbol{W}_1, \tag{29}$$

$$\frac{\partial l}{\partial \boldsymbol{W}_1} = \frac{\partial l}{\partial \boldsymbol{A}_1}^T \boldsymbol{A}. \tag{30}$$

In the attention operation:

$$dl_3 \triangleq \text{tr}(\frac{\partial l}{\partial \boldsymbol{A}}^T d\boldsymbol{A})$$

$$= \text{tr}(\frac{\partial l}{\partial \boldsymbol{A}}^T (d\boldsymbol{S})\boldsymbol{V}) + \text{tr}(\frac{\partial l}{\partial \boldsymbol{A}}^T \boldsymbol{S}d\boldsymbol{V})$$

$$= \text{tr}((\frac{\partial l}{\partial \boldsymbol{A}} \boldsymbol{V}^T)^T d\boldsymbol{S}) + \text{tr}((\boldsymbol{S}^T \frac{\partial l}{\partial \boldsymbol{A}})^T d\boldsymbol{V}),$$

and

$$\frac{\partial l}{\partial \boldsymbol{S}} = \frac{\partial l}{\partial \boldsymbol{A}} \boldsymbol{V}^T, \tag{31}$$

$$\frac{\partial l}{\partial \boldsymbol{V}} = \boldsymbol{S}^T \frac{\partial l}{\partial \boldsymbol{A}}. \tag{32}$$

First, for $\boldsymbol{V} = \boldsymbol{Z}\boldsymbol{W}_V^T$:

$$dl_4 \triangleq \text{tr}(\frac{\partial l}{\partial \boldsymbol{V}}^T d\boldsymbol{V})$$

$$= \text{tr}(\frac{\partial l}{\partial \boldsymbol{V}}^T (d\boldsymbol{Z})\boldsymbol{W}_V^T) + \text{tr}(\frac{\partial l}{\partial \boldsymbol{V}}^T \boldsymbol{Z}d\boldsymbol{W}_V^T).$$

Similarly, the gradients of $\boldsymbol{Z}$ and $\boldsymbol{W}_V$ are:

$$\frac{\partial l}{\partial \boldsymbol{Z}} = \frac{\partial l}{\partial \boldsymbol{V}} \boldsymbol{W}_V, \tag{33}$$

$$\frac{\partial l}{\partial \boldsymbol{W}_V} = \frac{\partial l}{\partial \boldsymbol{V}}^T \boldsymbol{Z}. \tag{34}$$

Now we focus on $\boldsymbol{S} = Softmax(\frac{\boldsymbol{Q}\boldsymbol{K}^T}{\sqrt{d}})$:

$$dl_5 \triangleq \text{tr}(\frac{\partial l}{\partial \boldsymbol{S}}^T d\boldsymbol{S})$$

$$= \text{tr}(\frac{\partial l}{\partial \boldsymbol{S}}^T (diag(\boldsymbol{S}) - \boldsymbol{S}^T \boldsymbol{S})d(\frac{\boldsymbol{Q}\boldsymbol{K}^T}{\sqrt{d}}))$$

$$= \text{tr}(((diag(\boldsymbol{S}) - \boldsymbol{S}^T \boldsymbol{S})^T \frac{\partial l}{\partial \boldsymbol{S}})^T d(\frac{\boldsymbol{Q}\boldsymbol{K}^T}{\sqrt{d}})),$$

and thus

$$\frac{\partial l}{\partial \boldsymbol{Q}} = \frac{1}{\sqrt{d}}((diag(\boldsymbol{S}) - \boldsymbol{S}^T \boldsymbol{S})^T \frac{\partial l}{\partial \boldsymbol{S}})\boldsymbol{K}, \tag{35}$$

$$\frac{\partial l}{\partial \boldsymbol{K}} = \frac{1}{\sqrt{d}}((diag(\boldsymbol{S}) - \boldsymbol{S}^T \boldsymbol{S})^T \frac{\partial l}{\partial \boldsymbol{S}})^T \boldsymbol{Q}. \tag{36}$$

And similarly the gradients of $\boldsymbol{W}_Q$ and $\boldsymbol{W}_K$ are:

$$\frac{\partial l}{\partial \boldsymbol{W}_Q} = \frac{\partial l}{\partial \boldsymbol{Q}}^T \boldsymbol{Z}, \tag{37}$$

$$\frac{\partial l}{\partial \boldsymbol{W}_K} = \frac{\partial l}{\partial \boldsymbol{K}}^T \boldsymbol{Z}. \tag{38}$$

What happens in backward propagation with RS: First, let us take a black-box view of the Transformer encoder blocks. In our scheme, the input of Enc is the shuffled smashed data $\boldsymbol{P}_R \boldsymbol{Z}$ and the output is $\boldsymbol{P}_R \boldsymbol{A}_2$. The edge client obtains $\boldsymbol{P}_R \boldsymbol{A}_2$ and reverse the shuffling order to get $\boldsymbol{A}_{3(R)} = \boldsymbol{P}_R^T \boldsymbol{A}_{2(R)}$. In the following, we denote all variables involved with our RS method with subscript (R), and variables in vanilla split learning are without the subscript. According to Eq. 1,

$$\boldsymbol{A}_{3(R)} = \boldsymbol{P}_R^T \boldsymbol{A}_{2(R)} = \boldsymbol{P}_R^T \boldsymbol{P}_R \boldsymbol{A}_2 = \boldsymbol{A}_2. \tag{39}$$

We have $\boldsymbol{A}_3 = \boldsymbol{A}_2$ in plain SL, and thus

$$\frac{\partial l}{\partial \boldsymbol{A}_{3(R)}} = \frac{\partial l}{\partial \boldsymbol{A}_3} = \frac{\partial l}{\partial \boldsymbol{A}_2}. \tag{40}$$

Then we focus on the relationship between $\frac{\partial l}{\partial \boldsymbol{A}_{2(R)}}$ and $\frac{\partial l}{\partial \boldsymbol{A}_2}$.

$$\mathrm{d}l = \mathrm{tr}(\frac{\partial l}{\partial \boldsymbol{A}_{3(R)}}^T \boldsymbol{P}_R^T \mathrm{d}\boldsymbol{A}_{2(R)})$$

$$= \mathrm{tr}((\boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_3})^T \mathrm{d}\boldsymbol{A}_{2(R)}),$$

and thus

$$\frac{\partial l}{\partial \boldsymbol{A}_{2(R)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_3} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_2}. \tag{41}$$

It is quite an interesting conclusion, and we will soon find it important to the permutation-invariance of gradients of the weight matrix. By substituting Eq. 41 into Eq. 27, we obtain:

$$\frac{\partial l}{\partial \boldsymbol{W}_{2(R)}} = \frac{\partial l}{\partial \boldsymbol{A}_{2(R)}}^T \boldsymbol{H}_{(R)} \tag{42}$$

$$= \frac{\partial l}{\partial \boldsymbol{A}_2}^T \boldsymbol{P}_R^T \boldsymbol{P}_R \boldsymbol{H} \tag{43}$$

$$= \frac{\partial l}{\partial \boldsymbol{A}_2}^T \boldsymbol{H} \tag{44}$$

$$= \frac{\partial l}{\partial \boldsymbol{W}_2}. \tag{45}$$

Eq. 45 reveals that the gradients of the weight matrix in our RS scheme would be the same as the gradients in vanilla SL. In fact, each gradient of the weight matrix is 'permutation-invariant', i.e., satisfying Eq. 45, whereas each gradient of the intermediate feature is 'permutation-equivalent,' meeting Eq. 41. Properties of Eq. 45 and Eq. 41 are transductive, carrying from the final layer backward to the first layer. Hence by Eq. 26,

$$\frac{\partial l}{\partial \boldsymbol{H}_{(R)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{H}}, \tag{46}$$

and by Eq. 28,

$$\frac{\partial l}{\partial \boldsymbol{A}_{1(R)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{W}_2 \odot \boldsymbol{P}_R a'(\boldsymbol{A}_1)$$

$$= \boldsymbol{P}_R(\frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{W}_2 \odot a'(\boldsymbol{A}_1)).$$

Thus,

$$\frac{\partial l}{\partial \boldsymbol{A}_{1(R)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_1}, \tag{47}$$

and by Eq. 30,

$$\frac{\partial l}{\partial \boldsymbol{W}_{1(R)}} = \frac{\partial l}{\partial \boldsymbol{W}_1}. \tag{48}$$

By Eq. 29, we have:

$$\frac{\partial l}{\partial \boldsymbol{A}_{(R)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}} \tag{49}$$

which passes the property to $\boldsymbol{S}$. But $\boldsymbol{S}$ is a tricky one since in the derivation of Eq. 23, we notice that $\boldsymbol{S}_{(R)} = \boldsymbol{P}_R \boldsymbol{S} \boldsymbol{P}_R^T$. According to Eq. 31,

$$\frac{\partial l}{\partial \boldsymbol{S}_{(R)}} = \frac{\partial l}{\partial \boldsymbol{A}_{(R)}} \boldsymbol{V}_{(R)}^T$$

$$= \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}} \boldsymbol{V}^T \boldsymbol{P}_R^T,$$

which interestingly leads to

$$\frac{\partial l}{\partial \boldsymbol{S}_{(R)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{S}} \boldsymbol{P}_R^T. \tag{50}$$

This is consistent with the $\boldsymbol{S}_{(R)}$'s permutation form, which passes the elegant properties down to $\boldsymbol{Q}, \boldsymbol{K}$:

$$\frac{\partial l}{\partial \boldsymbol{Q}_{(R)}} = \frac{1}{\sqrt{d}}((diag(\boldsymbol{S}_{(R)}) - \boldsymbol{S}_{(R)}^T \boldsymbol{S}_{(R)})^T \frac{\partial l}{\partial \boldsymbol{S}_{(R)}}) \boldsymbol{K}_{(R)}$$

$$= \frac{1}{\sqrt{d}}((\boldsymbol{P}_R diag(\boldsymbol{S}) \boldsymbol{P}_R^T - \boldsymbol{P}_R \boldsymbol{S}^T \boldsymbol{P}_R^T \boldsymbol{P}_R \boldsymbol{S} \boldsymbol{P}_R^T)^T \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{S}} \boldsymbol{P}_R^T) \boldsymbol{P}_R \boldsymbol{K}$$

$$= \frac{1}{\sqrt{d}}(\boldsymbol{P}_R(diag(\boldsymbol{S}) - \boldsymbol{S}^T \boldsymbol{S})^T \boldsymbol{P}_R^T \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{S}} \boldsymbol{P}_R^T) \boldsymbol{P}_R \boldsymbol{K}$$

$$= \boldsymbol{P}_R \frac{1}{\sqrt{d}}((diag(\boldsymbol{S}) - \boldsymbol{S}^T S)^T \frac{\partial l}{\partial \boldsymbol{S}}) \boldsymbol{K},$$

and hence

$$\frac{\partial l}{\partial \boldsymbol{Q}_{(R)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{Q}}. \tag{51}$$

Similarly,

$$\frac{\partial l}{\partial \boldsymbol{K}_{(R)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{K}}. \tag{52}$$

By Eq. 37,

$$\frac{\partial l}{\partial \boldsymbol{W}_{Q(R)}} = \frac{\partial l}{\partial \boldsymbol{Q}_{(R)}}^T \boldsymbol{Z}_{(R)} \tag{53}$$

$$= \frac{\partial l}{\partial \boldsymbol{Q}}^T \boldsymbol{P}_R^T \boldsymbol{P}_R \boldsymbol{Z} = \frac{\partial l}{\partial \boldsymbol{W}_Q}. \tag{54}$$

Similarly,

$$\frac{\partial l}{\partial \boldsymbol{W}_{K(R)}} = \frac{\partial l}{\partial \boldsymbol{W}_K}. \tag{55}$$

For now, we have proved that the gradients of weights in our RS scheme are exactly the same as the gradients of weights in vanilla split learning, and by induction, we can conclude that the learned Enc with RS method is no different from the learned Enc without. It is worth mentioning that if the attention is cut to multi-head, the property remains because cutting the second dimension (column) does not affect the permutation of the first dimension (row). □

A.4 PROOF OF THEOREM 3

Proof. We denote variables involved in our RCS method with subscript (P). Row shuffling is included as a special case of RCS.

First and foremost, we 'encrypt' all the weight matrices by Eq. 6:
$$\boldsymbol{W}_{i(p)} = \boldsymbol{P}_C \boldsymbol{W}_i \boldsymbol{P}_C^T,$$
where $\boldsymbol{P}_C$ is the column permutation matrix, $\boldsymbol{W}_i$ is the weight of a normal Enc, and $i \in \{1, 2, Q, K, V\}$. We denote the Transformer encoder block with such 'encryption' as $Enc_{(P)}$. Note that this operation requires $\boldsymbol{W}_i$ to be a square one. We have proposed two ways to achieve this with little modification to the original model without performance loss.

For $\boldsymbol{Q}$:
$$\boldsymbol{Q}_{(P)} = \boldsymbol{Z}_{(P)} \boldsymbol{W}_{\boldsymbol{Q}(P)}^T \tag{56}$$
$$= \boldsymbol{P}_R \boldsymbol{Z} \boldsymbol{P}_C^T \cdot \boldsymbol{P}_C \boldsymbol{W}_{\boldsymbol{Q}}^T \boldsymbol{P}_C^T \tag{57}$$
$$= \boldsymbol{P}_R \boldsymbol{Z} \boldsymbol{W}_{\boldsymbol{Q}}^T \boldsymbol{P}_C^T \tag{58}$$
$$= \boldsymbol{P}_R \boldsymbol{Q} \boldsymbol{P}_C^T. \tag{59}$$
Similarly for $\boldsymbol{K}, \boldsymbol{V}$:
$$\boldsymbol{K}_{(P)} = \boldsymbol{P}_R \boldsymbol{K} \boldsymbol{P}_C^T, \tag{60}$$
$$\boldsymbol{V}_{(P)} = \boldsymbol{P}_R \boldsymbol{V} \boldsymbol{P}_C^T. \tag{61}$$

For $\boldsymbol{S} = Softmax(\frac{\boldsymbol{Q}\boldsymbol{K}^T}{\sqrt{d}})$:
$$\boldsymbol{S}_{(P)} = Softmax(\frac{\boldsymbol{Q}_{(P)}\boldsymbol{K}_{(P)}^T}{\sqrt{d}}) \tag{62}$$
$$= Softmax(\frac{\boldsymbol{P}_R \boldsymbol{Q} \boldsymbol{P}_C^T \cdot \boldsymbol{P}_C \boldsymbol{K}^T \boldsymbol{P}_R^T}{\sqrt{d}}) \tag{63}$$
$$= Softmax(\frac{\boldsymbol{P}_R \boldsymbol{Q} \boldsymbol{K}^T \boldsymbol{P}_R^T}{\sqrt{d}}) \tag{64}$$
$$= \boldsymbol{P}_R Softmax(\frac{\boldsymbol{Q}\boldsymbol{K}^T}{\sqrt{d}}) \boldsymbol{P}_R^T \tag{65}$$
$$= \boldsymbol{P}_R \boldsymbol{S} \boldsymbol{P}_R^T. \tag{66}$$

So for $\boldsymbol{A}$:
$$\boldsymbol{A}_{(P)} = \boldsymbol{S}_{(P)} \boldsymbol{V}_{(P)} \tag{67}$$
$$= \boldsymbol{P}_R \boldsymbol{S} \boldsymbol{P}_R^T \cdot \boldsymbol{P}_R \boldsymbol{V} \boldsymbol{P}_C^T \tag{68}$$
$$= \boldsymbol{P}_R \boldsymbol{S} \boldsymbol{V} \boldsymbol{P}_C^T \tag{69}$$
$$= \boldsymbol{P}_R \boldsymbol{A} \boldsymbol{P}_C^T. \tag{70}$$

Following the attention layer, $\boldsymbol{A}$ is fed to the MLP layer:
$$\boldsymbol{A}_{1(P)} = \boldsymbol{A}_{(P)} \boldsymbol{W}_{1(P)}^T \tag{71}$$
$$= \boldsymbol{P}_R \boldsymbol{A} \boldsymbol{P}_C^T \cdot \boldsymbol{P}_C \boldsymbol{W}_1 \boldsymbol{P}_C^T \tag{72}$$
$$= \boldsymbol{P}_R \boldsymbol{A} \boldsymbol{W}_1 \boldsymbol{P}_C^T \tag{73}$$
$$= \boldsymbol{P}_R \boldsymbol{A}_1 \boldsymbol{P}_C^T. \tag{74}$$

Similarly for $\boldsymbol{A}_2$,

$$\boldsymbol{A}_{2(P)} = \boldsymbol{P}_R \boldsymbol{A}_2 \boldsymbol{P}_C^T. \tag{75}$$

As for the activation in the middle, the element-wise activation function is permutation-equivalent:

$$\boldsymbol{H}_{(P)} = \boldsymbol{P}_R \boldsymbol{H} \boldsymbol{P}_C^T. \tag{76}$$

Overall, we have proved Thm. 3. □

A.5 PROOF OF THEOREM 4

Proof. By row and column unshuffle, the computation of the part of forward propagation and backward propagation on the edge is no different with or without our RCS method. Hence we only focus on the propagation of the Transformer encoder blocks.

Similarly to the proof on RS, we denote $\boldsymbol{A}_{3(P)}$ as the reversed intermediate feature that the edge receives:

$$\boldsymbol{A}_{3(P)} = \boldsymbol{P}_R^T \boldsymbol{A}_{2(P)} \boldsymbol{P}_C. \tag{77}$$

By Thm. 3, we have

$$\boldsymbol{A}_3 = \boldsymbol{A}_2,$$
$$\boldsymbol{A}_3 = \boldsymbol{A}_{3(P)}.$$

First we fouces on MLP:

$$\begin{aligned}
\mathrm{d}l &= \mathrm{tr}(\frac{\partial l}{\partial \boldsymbol{A}_3}^T \boldsymbol{P}_R^T \mathrm{d}(\boldsymbol{A}_{2(P)}) \boldsymbol{P}_C) \\
&= \mathrm{tr}(\boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{A}_3}^T \boldsymbol{P}_R^T \mathrm{d}\boldsymbol{A}_{2(P)}) \\
&= \mathrm{tr}((\boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_3} \boldsymbol{P}_C^T)^T \mathrm{d}\boldsymbol{A}_{2(P)}),
\end{aligned}$$

that is:

$$\frac{\partial l}{\partial \boldsymbol{A}_{2(P)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{P}_C^T. \tag{78}$$

With $\boldsymbol{H}_{(P)} = \boldsymbol{P}_R \boldsymbol{H} \boldsymbol{P}_C^T$ and the gradient:

$$\begin{aligned}
\frac{\partial l}{\partial \boldsymbol{W}_{2(P)}} &= \frac{\partial l}{\partial \boldsymbol{A}_{2(P)}}^T \boldsymbol{H}_{(P)} \\
&= \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{P}_R^T \cdot \boldsymbol{P}_R \boldsymbol{H} \boldsymbol{P}_C^T \\
&= \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{H} \boldsymbol{P}_C^T \\
&= \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{W}_2} \boldsymbol{P}_C^T,
\end{aligned}$$

that is:

$$\frac{\partial l}{\partial \boldsymbol{W}_{2(P)}} = \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{W}_2} \boldsymbol{P}_C^T. \tag{79}$$

And:

$$\frac{\partial l}{\partial \boldsymbol{A}_{1(P)}} = \frac{\partial l}{\partial \boldsymbol{A}_{2(P)}} \boldsymbol{W}_{2(P)} \odot a'(\boldsymbol{A}_{1(P)})$$

$$= [\boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{P}_C^T \cdot \boldsymbol{P}_C \boldsymbol{W} \boldsymbol{P}_C^T] \odot [\boldsymbol{P}_R a'(\boldsymbol{A}_1) \boldsymbol{P}_C^T]$$

$$= [\boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{W} \boldsymbol{P}_C^T] \odot [\boldsymbol{P}_R a'(\boldsymbol{A}_1) \boldsymbol{P}_C^T]$$

$$= \boldsymbol{P}_R [\frac{\partial l}{\partial \boldsymbol{A}_2} \boldsymbol{W}_2 \odot a'(\boldsymbol{A}_1)] \boldsymbol{P}_C^T$$

$$= \boldsymbol{P}_R \frac{\partial l}{\partial_1} \boldsymbol{P}_C^T,$$

that is:

$$\frac{\partial l}{\partial \boldsymbol{A}_{1(P)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_1} \boldsymbol{P}_C^T. \tag{80}$$

The last weight in MLP:

$$\frac{\partial l}{\partial \boldsymbol{W}_{1(P)}} = \frac{\partial l}{\partial \boldsymbol{A}_{1(P)}}^T \boldsymbol{A}_{(P)}$$

$$= \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{A}_1}^T \boldsymbol{P}_R^T \cdot \boldsymbol{P}_R \boldsymbol{A} \boldsymbol{P}_C^T$$

$$= \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{W}_1} \boldsymbol{P}_C^T,$$

that is:

$$\frac{\partial l}{\partial \boldsymbol{W}_{1(P)}} = \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{W}_1} \boldsymbol{P}_C^T. \tag{81}$$

And we come to the attention operation:

$$\frac{\partial l}{\partial \boldsymbol{A}_{(P)}} = \frac{\partial l}{\partial \boldsymbol{A}_{1(P)}} \boldsymbol{W}_{1(P)}$$

$$= \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_1} \boldsymbol{P}_C^T \cdot \boldsymbol{P}_C \boldsymbol{W}_1 \boldsymbol{P}_C^T$$

$$= \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}_1} \boldsymbol{W}_1 \boldsymbol{P}_C^T$$

$$= \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}} \boldsymbol{P}_C^T,$$

that is:

$$\frac{\partial l}{\partial \boldsymbol{A}_{(P)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}} \boldsymbol{P}_C^T. \tag{82}$$

and for S:

$$\frac{\partial l}{\partial \boldsymbol{S}_{(P)}} = \frac{\partial l}{\partial \boldsymbol{A}_{(P)}} \boldsymbol{V}_{(P)}^T$$

$$= \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}} \boldsymbol{P}_C^T \cdot \boldsymbol{P}_C \boldsymbol{V}^T \boldsymbol{P}_R^T$$

$$= \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}} \boldsymbol{V}^T \boldsymbol{P}_R^T$$

$$= \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{S}} \boldsymbol{P}_R^T,$$

that is:

$$\frac{\partial l}{\partial \boldsymbol{S}_{(P)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{S}} \boldsymbol{P}_R^T. \tag{83}$$

And:

$$
\begin{aligned}
\frac{\partial l}{\partial \boldsymbol{Q}_{(P)}} &= \frac{1}{\sqrt{d}}[(diag(\boldsymbol{S}_{(P)}) - \boldsymbol{S}_{(P)}^T \boldsymbol{S}_{(P)})\frac{\partial l}{\partial \boldsymbol{S}_{(P)}}]\boldsymbol{K}_{(P)} \\
&= \frac{1}{\sqrt{d}}[(\boldsymbol{P}_R diag(\boldsymbol{S})\boldsymbol{P}_R^T - \boldsymbol{P}_R \boldsymbol{S}^T \boldsymbol{P}_R^T \cdot \boldsymbol{P}_R \boldsymbol{S}\boldsymbol{P}_R^T)\boldsymbol{P}_R\frac{\partial l}{\partial \boldsymbol{S}}\boldsymbol{P}_R^T]\boldsymbol{P}_R \boldsymbol{K}\boldsymbol{P}_C^T \\
&= \frac{1}{\sqrt{d}}[(\boldsymbol{P}_R diag(\boldsymbol{S})\boldsymbol{P}_R^T - \boldsymbol{P}_R \boldsymbol{S}^T \boldsymbol{S}\boldsymbol{P}_R^T)\boldsymbol{P}_R\frac{\partial l}{\partial \boldsymbol{S}}\boldsymbol{P}_R^T]\boldsymbol{P}_R \boldsymbol{K}\boldsymbol{P}_C^T \\
&= \frac{1}{\sqrt{d}}[\boldsymbol{P}_R(diag(\boldsymbol{S}) - \boldsymbol{S}^T \boldsymbol{S})\boldsymbol{P}_R^T \cdot \boldsymbol{P}_R\frac{\partial l}{\partial \boldsymbol{S}}\boldsymbol{P}_R^T]\boldsymbol{P}_R \boldsymbol{K}\boldsymbol{P}_C^T \\
&= \frac{1}{\sqrt{d}}[\boldsymbol{P}_R(diag(\boldsymbol{S}) - \boldsymbol{S}^T \boldsymbol{S})\frac{\partial l}{\partial \boldsymbol{S}}\boldsymbol{P}_R^T]\boldsymbol{P}_R \boldsymbol{K}\boldsymbol{P}_C^T \\
&= \frac{1}{\sqrt{d}}\boldsymbol{P}_R(diag(\boldsymbol{S}) - \boldsymbol{S}^T \boldsymbol{S})\frac{\partial l}{\partial \boldsymbol{S}}\boldsymbol{P}_R^T \cdot \boldsymbol{P}_R \boldsymbol{K}\boldsymbol{P}_C^T \\
&= \boldsymbol{P}_R \frac{1}{\sqrt{d}}(diag(\boldsymbol{S}) - \boldsymbol{S}^T \boldsymbol{S})\frac{\partial l}{\partial \boldsymbol{S}}\boldsymbol{K}\boldsymbol{P}_C^T \\
&= \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{Q}}\boldsymbol{P}_C^T,
\end{aligned}
$$

and with similar process on $\boldsymbol{K}$ we reach:

$$
\frac{\partial l}{\partial \boldsymbol{Q}_{(P)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{Q}}\boldsymbol{P}_C^T \tag{84}
$$

$$
\frac{\partial l}{\partial \boldsymbol{K}_{(P)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{K}}\boldsymbol{P}_C^T. \tag{85}
$$

Between $\boldsymbol{Q}, \boldsymbol{K}$ and $\boldsymbol{W}_Q, \boldsymbol{W}_K$ is just linear layer. Hence, similar with proof in MLP:

$$
\frac{\partial l}{\partial \boldsymbol{W}_{Q(P)}} = \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{W}_Q}\boldsymbol{P}_C^T \tag{86}
$$

$$
\frac{\partial l}{\partial \boldsymbol{W}_{K(P)}} = \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{W}_K}\boldsymbol{P}_C^T. \tag{87}
$$

And last one is $\boldsymbol{V}$:

$$
\begin{aligned}
\frac{\partial l}{\partial \boldsymbol{V}_{(P)}} &= \boldsymbol{S}_{(P)}^T \frac{\partial l}{\partial \boldsymbol{A}_{(P)}} \\
&= \boldsymbol{P}_R \boldsymbol{S}\boldsymbol{P}_R^T \cdot \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{A}}\boldsymbol{P}_C^T \\
&= \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{V}}\boldsymbol{P}_C^T,
\end{aligned}
$$

that is:

$$
\frac{\partial l}{\partial \boldsymbol{V}_{(P)}} = \boldsymbol{P}_R \frac{\partial l}{\partial \boldsymbol{V}}\boldsymbol{P}_C^T \tag{88}
$$

$$
\frac{\partial l}{\partial \boldsymbol{W}_{V(P)}} = \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{W}_V}\boldsymbol{P}_C^T. \tag{89}
$$

So far we have proved that for every single gradient of weight matrix there is:

$$
\frac{\partial l}{\partial \boldsymbol{W}_{i(P)}} = \boldsymbol{P}_C \frac{\partial l}{\partial \boldsymbol{W}_i}\boldsymbol{P}_C^T, \tag{90}
$$

where $\boldsymbol{W}_{i(P)}$ is the weight in $Enc_{(P)}$ while $\boldsymbol{W}_i$ is the weight in Enc. With certain straightforward induction we can reach the conclusion that if a Transformer encoder blocks is randomly initialized and trained with $\boldsymbol{Z}_{(P)}$, finally it will learn to become $Enc_{(P)}$, the same as the one directly encrypted via matrix multiplication. □

B SUPPLEMENTARY EXPERIMENTS

B.1 VERIFYING THE PROPERTIES ON BIAS AND LAYER NORM

We do not mention bias and γ, the weight in layer normalization, in the proofs in Appendix A. Here is some intuition about why they are encrypted in the way shown in Eq. 6:

$$b_{(P)} = b\boldsymbol{P}_C^{-1}, \ \ \gamma_{(P)} = \gamma\boldsymbol{P}_C^{-1}.$$

Both bias and γ are 1-D vector, and each element only interrelates with the corresponding column of $\boldsymbol{Z}$ in both forward and backward propagation. So if the columns are permuted, bias and γ should be permuted in the same way. During the experiments we find that the encryption/decryption of bias and γ hardly affect the model performance on Cifar10. But on CelebA, if most weight matrices are encrypted by $M_{\boldsymbol{W}}$ while bias and γ are not, the accuracy would be greatly affected, which is merely 79.056%. But if the encryption is strictly performed as Eq. 6, the relative accuracy difference between a normally trained model (tested with $\boldsymbol{Z}$) and an encrypted model (tested with $\boldsymbol{Z}\boldsymbol{P}_C^T$) is merely 0.00013% (91.50991% and 91.50979% respectively).

B.2 VERIFYING ON ORDER-DEPENDENT TASKS

We consider the classification task weak order-dependent, i.e., the model may not need much information on the order of the pieces of the picture. To prove the feasibility of our method on strong order-dependent tasks, we designed a simple tasks that strongly depends on the input order – to discriminate the correctness of order. We label the shuffled picture in CelebA as 1 and original picture as 0 and train a ViT-Base on the those from scratch to complete the task. Within one epoch, the accuracy of ViT-Base reaches around 97%. And we conduct similar experiment in the former section, and all the results are as expected: RS is transparent to the encoder, and encrypted model can only process encrypted data. It demonstrates the shuffled Transformer also works on tasks strongly associated with the input patch order.

B.3 ATTACK RESULTS TO CIFAR10

(a) Original Cifar10 Picture

(b) Black-box (e=1): RCS

(c) Black-box (e=10): RCS

Figure 7: The black-box attack result of inference process

Additionally, we also conduct the black-box attack in Sec. 3 on the object dataset, Cifar10, and the result is presented in Tab. 5. Due to the spares distribution, the defense results are more successful than the attack on CelebA, the face dataset. As shown in Fig. 7, the attacker fails to reconstruct the main object in the picture when our RCS method is used.

Table 5: Results of black-box attack to Cifar10. ↓ means desirable direction.

	SSIM↓	PSNR↓	F-SIM↓
unprotected SL	0.360	2.761	0.644
Our RS (inference)	0.075	0.987	0.464
Our RCS (inference)	0.094	0.984	0.421
Our RS (training)	0.275	10.812	0.390
Our RCS (training)	0.264	10.460	0.336

(a) Normally Learned (b) Before Shuffle (c) After Shuffle

Figure 8: Cosine similarity between every two patches of position embeddings learned in different ways.

B.4 EXPERIMENTS ON POSITION EMBEDDINGS

Position embedding and accuracy.   To further verify that our method does not affect network parameters on edge, we study the position embedding in Fig. 2. We visualized the cosine similarity of position embeddings learned at different places of the model on the CelebA classification tasks. Interestingly, trained from scratch on a face dataset, the learned position embedding is like a human face. As shown in Fig. 8, the position embedding learned before shuffle, as shown in Fig. 2, is quite similar to the normally learned one, which further verifies that our method has no influence on the model stub on the edge.

It is worth noting that, we find that the removal of positional embedding does not influence much when the Transformer is trained on a large dataset, or when the model is previously pre-trained on a large dataset. If the ViT without position embedding is trained from scratch on Cifar10, the accuracy drops by around 10% (around 80%if position embedding is added and around 70% if not). This does not matter in practice since the random initialized Transformer based models are not expected to be used when only a small private dataset is available. Normally Transformer based model should be pre-trained on a large dataset before being transferred to a smaller dataset.

We also find that if the position embedding is not added in training, it does not improve test accuracy if a fixed position embedding is added in testing. Instead, the accuracy drops a little.

Position embedding and privacy.   In the privacy guarantee experiment in Sec. 6.1, we place the position embedding at the rear of row-column shuffle, and it learns to become similar, random, and meaningless, thus we consider position information is discarded during training with shuffled Transformers.

Noting that placing the position embedding at the rear of the shuffle does not make any sense in practice, our experiments are aimed to study whether the cloud is able to learn the position information. In the inference-only scenario, the position embedding should be added in the front of the shuffle.