MMVAE+: Enhancing the Generative Quality of Multimodal VAEs without Compromises

Abstract

Multimodal VAEs have recently gained attention as efficient models for weakly-supervised generative learning with multiple modalities. However, all existing variants of multimodal VAEs are affected by a non-trivial trade-off between generative quality and generative coherence. In particular mixture-based models achieve good coherence only at the expense of sample diversity and a resulting lack of generative quality. We present a novel variant of the mixture-of-experts multimodal variational autoencoder that improves its generative quality, while maintaining high semantic coherence. We model shared and modality-specific information in separate latent subspaces, proposing an objective that overcomes certain dependencies on hyperparameters that arise for existing approaches with the same latent space structure. Compared to these existing approaches, we show increased robustness with respect to changes in the design of the latent space, in terms of the capacity allocated to modality-specific subspaces. We show that our model achieves both good generative coherence and high generative quality in challenging experiments, including more complex multimodal datasets than those used in previous works.

1 Introduction

Multimodal VAEs are a promising class of models for weakly-supervised generative learning. Different from initially proposed models in this class (Suzuki et al., 2016; Vedantam et al., 2018), more recent approaches (Wu & Goodman, 2018; Shi et al., 2019; 2021; Sutter et al., 2020; 2021) can efficiently scale to a large number of modalities. These methodological advances enabled applications in multi-omics data integration (Lee & van der Schaar, 2021; Minoura et al., 2021) and tumor segmentation from multiple image modalities (Dorent et al., 2019).

Several variants of scalable multimodal VAEs have been proposed (Wu & Goodman, 2018; Shi et al., 2019; 2021; Sutter et al., 2021) and their performance is measured in terms of generative quality and generative coherence. While generative quality measures how well a model approximates the data distribution, generative coherence measures the semantic coherence of generated samples across modalities (e.g., see Shi et al., 2019). High generative quality requires generated samples being similar to the test data, while high generative coherence requires generated samples to agree in their semantic content across modalities. For instance, in a dataset of image/caption pairs, conditional generation from the text modality should produce images where the depicted object matches the description in the given caption (e.g. matching color). Ideally, an effective multimodal generative model should fulfill both of these performance aspects. Still, recent work (Daunhawer et al., 2022) shows that the predominant approaches exhibit a non-trivial trade-off between the two criteria, which limits their utility for complex real-world applications.

In this work we focus on mixture-based multimodal VAEs, which show high generative coherence only at the expense of a lack of generative quality, a fact that undermines their performance in realistic settings. Results for models in this class are promising for capturing *shared* information, i.e. information that is communal across modalities on the underlying concept being described, while exhibit a lack of modelling of *private* variation, i.e. modality-specific information for single modalities (see Shi et al., 2019; Sutter et al., 2021; Daunhawer et al., 2022). In an attempt to enhance modelling of private information, recent work (Sutter et al., 2020) has suggested introducing modality-specific latent spaces in addition to a shared subspace for mixture-based multimodal VAEs. However, we

revise such proposed extension and find that an improvement in terms of generative quality comes again at the expense of reduced generative coherence. Most importantly we uncover a relevant short-coming of existing approaches with separate subspaces, in that we find generative coherence to be overly sensitive to hyperparameters controlling the capacity of private latent subspaces, which in practice calls for expensive model selection procedures to achieve adequate performance.

Incorporating the idea of modelling the latent space as a combination of shared and modality-specific encodings, we propose the MMVAE+, a variant of the mixture-of-experts multimodal VAE (MM-VAE, Shi et al. (2019)) with a novel ELBO, that significantly improves the diversity of the generated samples, without sacrificing semantic coherence. Compared to previously proposed models, our method achieves *both* convincing generative quality *and* generative coherence (Section 4.1). Notably, its performance in terms of both criteria is robust with respect to hyperparameters controlling latent dimensionality, compared to previous methods with separate shared and private latent subspaces. (Section 4.2) Finally, we show our proposed model can successfully tackle a challenging multimodal dataset of image and text pairs (Section 4.3), that was shown to be too complex for existing multimodal VAEs (Daunhawer et al., 2022).

2 RELATED WORK

Multimodal generative models are promising approaches for learning from co-occurring data sources without explicit supervision, by exploiting the pairing between modalities as a form of weak-supervision. Previous work has achieved outstanding results for multimodal generative tasks such as image-to-image translation (Zhu et al., 2017; Choi et al., 2018) or text-to-image synthesis (Reed et al., 2016). While these models are designed for specialized tasks limited to a fixed number of modalities, in a lot of real-world settings there is a need for general methods that can leverage large datasets of many heterogeneous modalities. A prominent example is the field of healthcare, where personalised medicine requires learning from large-scale multimodal datasets comprised of medical images, genomics tests, and clinical measurements. Multimodal VAEs (Suzuki et al., 2016; Wu & Goodman, 2018; Shi et al., 2019; 2021; Sutter et al., 2020; 2021) are a promising model class for such applications, showing encouraging results towards efficient learning from multimodal datasets with multiple heterogeneous modalities.

Multimodal VAEs extend the popular variational autoencoder (VAE, Kingma & Welling, 2014) to multiple data modalities. Initially proposed approaches (Suzuki et al., 2016; Vedantam et al., 2018) lack scalability in the number of modalities, requiring an additional encoder network per possible subset of modalities, to enable inference from the given subset. Other proposed methods require explicit supervision (Tsai et al., 2019), which demands prior expensive data labelling processes. In contrast, recent methodological advances enable learning from a large number of modalities efficiently and without explicit supervision, by using a joint encoder that decomposes in terms of unimodal encoders. Previous work proposed three different formulations for the joint encoder: the product-of-experts (MVAE, Wu & Goodman 2018), mixture-of-experts (MMVAE, Shi et al. 2019), and mixture-of-product-of-experts (MoPoE-VAE, Sutter et al. 2021).

Recent work (Daunhawer et al., 2022) shows that existing multimodal VAEs exhibit a tradeoff between two desired performance criteria for multimodal generation, namely generative quality and generative coherence. While generative quality assesses the generative performance of the model for each modality, generative coherence (Shi et al., 2019) examines the learning of shared information by estimating the consistency in the semantic content between modalities in both conditional and unconditional generation. Daunhawer et al. (2022) show that existing product-based models exhibit low generative coherence, while mixture-based models exhibit a lack of sample diversity, which negatively affects generative quality (cp. Wolff et al., 2021).

Based on the three mentioned formulations of multimodal VAEs, subsequent work introduced additional regularization terms (Sutter et al., 2020; Hwang et al., 2021) and hierarchical latent spaces (Sutter & Vogt, 2021; Vasco et al., 2022; Wolff et al., 2022). Recent work has also explored the possibility of assuming separate modality-specific latent subspaces in addition to a shared subspace (Sutter et al., 2020; Lee & Pavlovic, 2021), or leveraging mutual supervision (Joy et al., 2022). Yet, it is not clear whether these extensions overcome the fundamental tradeoff between generative quality and coherence. For instance, for existing approaches to employ additional modality-specific latent subspaces with mixture-based models, we observe an overly high sensitivity to hyperparame-

ters (Section 4.2), which raises fundamental questions with regard to model selection. Notably, we show that our proposed method—also in the class of multimodal VAEs with modality-specific latent subspaces—is significantly more robust to changes in the same hyperparameter values.

3 METHOD

3.1 PRELIMINARIES: MMVAE

Given a set of M modalities $\boldsymbol{X} := \boldsymbol{x}_1, \ldots, \boldsymbol{x}_M$, multimodal VAEs learn a latent-variable generative model of the form $p_\Theta(\boldsymbol{X}, \boldsymbol{z}) = p(\boldsymbol{z}) \prod_{m=1}^{M} p_{\theta_m}(\boldsymbol{x}_m | \boldsymbol{z})$, by using neural networks to approximate the intractable evidence $p_\Theta(\boldsymbol{X})$. Analogous to the VAE (Kingma & Welling, 2014), multimodal VAEs optimise a lower bound of the log-evidence by maximizing the following objective:

$$\mathcal{L}_{\text{VAE}}(\boldsymbol{x}_{1:M}) = \mathbb{E}_{q_\Phi(\boldsymbol{z}|\boldsymbol{X})} \left[\log \frac{p_\Theta(\boldsymbol{X}, \boldsymbol{z})}{q_\Phi(\boldsymbol{z}|\boldsymbol{X})} \right] \tag{1}$$

where $q_\Phi(\boldsymbol{z}|\boldsymbol{X})$ denotes the approximate posterior, a neural network that is parameterized by Φ. In the above form, the objective does not scale to a large number of modalities (e.g., see Wu & Goodman, 2018; Sutter et al., 2021) and additional assumptions are required for the joint encoder to be computed efficiently in terms of the unimodal encoders. Different formulations of the joint encoder have been proposed (Wu & Goodman, 2018; Shi et al., 2019; Sutter et al., 2021), but here we focus on the decomposition used by the MMVAE (Shi et al., 2019), formulating the joint encoder as a mixture-of-experts of unimodal encoders $q_\Phi(\boldsymbol{z}|\boldsymbol{X}) = \frac{1}{M} \sum_{m=1}^{M} q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)$. When a mixture distribution for the joint encoder is assumed, the expression in eqn. (1) is evaluated by computing the expectation with respect to each component of the mixture distribution, and averaging over the results. As in this case we assume a mixture-of-experts encoder, the MMVAE (Shi et al., 2019) objective is a sum indexed by the M unimodal encoders

$$\mathcal{L}_{\text{MMVAE}}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)} \left[\log \frac{p_\Theta(\boldsymbol{X}, \boldsymbol{z})}{q_\Phi(\boldsymbol{z}|\boldsymbol{X})} \right] \tag{2}$$

where

$$\mathbb{E}_{q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)} \left[\log \frac{p_\Theta(\boldsymbol{X}, \boldsymbol{z})}{q_\Phi(\boldsymbol{z}|\boldsymbol{X})} \right] \propto \mathbb{E}_{q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)} \left[\log p_{\theta_m}(\boldsymbol{x}_m | \boldsymbol{z}) \right] + \sum_{\substack{m=1 \\ n \neq m}}^{M} \mathbb{E}_{q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)} \left[\log p_{\theta_n}(\boldsymbol{x}_n | \boldsymbol{z}) \right]$$

$$\tag{3}$$

For each term in the sum, the encoding $\boldsymbol{z} \sim q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)$ is sampled from a unimodal encoder, but it is used for the reconstruction of *all* modalities: the likelihood term encompasses the reconstruction of the modality m, i.e. self-reconstruction $\mathbb{E}_{q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)}[\log p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z})]$, as well as the reconstruction *across* modalities, i.e. cross-modal reconstruction $\sum_{m=1, n\neq m}^{M} \mathbb{E}_{q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)} \left[\log p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z}) \right]$. Maximizing reconstruction likelihood of modalities not observed for inference encourages the latent code to contain information common across modalities, and can explain improved semantic coherence compared to previously proposed product-based approaches (see qualitative results in Shi et al. (2019) and section 4.1). However it has also been recently been shown that the optimization of cross-modal reconstructions given a unimodal encoding can lead to a lack of modelled diversity in private information for generation across modalities (Wolff et al., 2021; Daunhawer et al., 2022), which manifests in average-looking samples with low generative quality (see section 4.1).

3.2 PRELIMINARIES: ADDITIONAL MODALITY-SPECIFIC SUBSPACES

In an attempt to enhance modelling of private information and improve performance, recent work on multimodal VAEs (Sutter et al. (2020)) has proposed to model the latent space for mixture-based models including modality-specific latent subspaces, in addition to a shared subspace (Bouchacourt et al., 2018; Tsai et al., 2019) . Formally, each modality $\boldsymbol{x}_m$ is modelled to have its own modality-specific latent code $\boldsymbol{w}_m$, in addition to a latent code $\boldsymbol{z}$ shared between all modalities. The assumed

generative model is then of the form $p_\Theta(\boldsymbol{X}, \boldsymbol{z}, \boldsymbol{W}) = p(\boldsymbol{z}) \prod_{m=1}^{M} p_{\theta_m}(\boldsymbol{x}_m | \boldsymbol{z}, \boldsymbol{w}_m) p(\boldsymbol{w}_m)$, where the shared latent code $\boldsymbol{z}$ and all the modality-specific codes $\boldsymbol{w}_1, \dots \boldsymbol{w}_M =: \boldsymbol{W}$ are assumed to be independent. A variational encoder $q_\Phi(\boldsymbol{z}, \boldsymbol{W} | \boldsymbol{X})$ is introduced to approximate posterior inference, and is modelled in line with the assumptions on the generative process, assuming conditional independence given $\boldsymbol{X}$

$$q_\Phi(\boldsymbol{z}, \boldsymbol{W} | \boldsymbol{X}) = q_{\Phi_{\boldsymbol{z}}}(\boldsymbol{z} | \boldsymbol{X}) q_{\Phi_{\boldsymbol{W}}}(\boldsymbol{W} | \boldsymbol{X}) = q_{\Phi_{\boldsymbol{z}}}(\boldsymbol{z} | \boldsymbol{X}) \prod_{m=1}^{M} q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m | \boldsymbol{x}_m)$$

Again, achieving scalability in the number of modalities requires additional assumption for the joint encoder $q_{\Phi_{\boldsymbol{z}}}(\boldsymbol{z} | \boldsymbol{X})$ of the shared latent code $\boldsymbol{z}$. In particular assuming a mixture-of-experts joint encoder $q_{\Phi_{\boldsymbol{z}}}(\boldsymbol{z} | \boldsymbol{X}) = \frac{1}{M} \sum_{m=1}^{M} q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z} | \boldsymbol{x}_m)$ one obtains a variant of the MMVAE with factorized latent space into shared and private subspaces

$$\mathcal{L}_{\text{MMVAE}}^{f}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{\substack{q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z} | \boldsymbol{x}_m) \\ q_{\Phi_{\boldsymbol{W}}}(\boldsymbol{W} | \boldsymbol{X})}} \left[\log \frac{p_\Theta(\boldsymbol{X}, \boldsymbol{z}, \boldsymbol{W})}{q_{\Phi_{\boldsymbol{z}}}(\boldsymbol{z} | \boldsymbol{X}) q_{\Phi_{\boldsymbol{W}}}(\boldsymbol{W} | \boldsymbol{X})} \right] \tag{4}$$

where

$$\mathbb{E}_{\substack{q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z} | \boldsymbol{x}_m) \\ q_{\Phi_{\boldsymbol{W}}}(\boldsymbol{W} | \boldsymbol{X})}} \left[\log \frac{p_\Theta(\boldsymbol{X}, \boldsymbol{z}, \boldsymbol{W})}{q_{\Phi_{\boldsymbol{z}}}(\boldsymbol{z} | \boldsymbol{x}_m) q_{\Phi_{\boldsymbol{W}}}(\boldsymbol{W} | \boldsymbol{X})} \right] \propto \mathbb{E}_{\substack{q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z} | \boldsymbol{x}_m) \\ q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m | \boldsymbol{x}_m)}} \left[\log p_{\theta_m}(\boldsymbol{x}_m | \boldsymbol{z}, \boldsymbol{w}_m) \right] +$$

$$\sum_{\substack{m=1 \\ n \neq m}}^{M} \mathbb{E}_{\substack{q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z} | \boldsymbol{x}_m) \\ q_{\phi_{\boldsymbol{w}_n}}(\boldsymbol{w}_n | \boldsymbol{x}_n)}} \left[\log p_{\theta_n}(\boldsymbol{x}_n | \boldsymbol{z}, \boldsymbol{w}_n) \right]$$

Existing mixture-based multimodal VAEs with a factorized latent space are based on this objective Sutter et al. (2020). Note that both self-reconstruction likelihood and cross-modal reconstruction likelihood terms are computed given the modality-specific encoding from the *target* modality. This can seemingly be an advantage, given these additional latent encodings can provide the modality-specific information for reconstruction that is not modelled in the shared latent code. In particular, for cross-modal reconstruction no private information about the target modality can be present in the $\boldsymbol{z}$ encoding from the starting modality.

Figure 1: Shortcut problem for the objective in 4: generative coherence as a function of of private latent capacity. The percentages on the x-axis indicate the relative size of any private subspace with respect to the shared subspace.

However, we find that with such an approach model performance is heavily dependent on hyperparameters controlling private latent dimensionality. In fact, when modality-specific latent subspaces are given enough capacity, in terms of number of dimensions, the modality-specific encoding can contain *all* information for the given modality (i.e., both shared and modality-specific features), while the shared subspace is ignored by the decoders. We show here that this can lead to a degenerate solution—a *shortcut* where all information flows through the modality-specific subspaces and no shared subspace is learned for generation across modalities. As a consequence, to achieve sufficient generative coherence it is necessary to heavily constrain the size of private subspaces (see figure 1). Note however that this in turn negatively impacts generative quality, being detrimental to modelling modality-specific variation, which was our motivation to employ additional private subspaces in the first place (see section 4.2). Therefore, assuming modality-specific latent subspaces seems to not be sufficient to overcome the trade-off between generative quality and generative coherence, and most importantly results in instabilities with respect to hyperparameters controlling private latent space capacity, which calls for expensive model selection procedures in practical settings.

3.3 THE MMVAE+ OBJECTIVE

To enhance generative quality without compromising semantic coherence, we introduce the MM-VAE+ model, a novel variant of the MMVAE. Our model incorporates the idea of using factorized

shared and modality-specific latent representations, and therefore makes the assumptions on the generative process and the variational approximation function presented in section 3.2. In order to ensure learning of a shared subspace while not incurring in a shortcut, auxiliary distributions for private features are used to facilitate the estimation of cross-modal reconstructions. The optimized objective is

$$\mathcal{L}_{\text{MMVAE+}}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{\substack{q_{\phi_{\boldsymbol{z}m}}(\boldsymbol{z}|\boldsymbol{x}_m) \\ q_{\phi_{\boldsymbol{w}m}}(\boldsymbol{w}_m|\boldsymbol{x}_m) \\ \{r_n(\boldsymbol{w}_n)\}_{n \neq m}}} \log \left(\frac{p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z}, \boldsymbol{w}_m)p(\boldsymbol{z})p(\boldsymbol{w}_m)}{q_{\Phi}(\boldsymbol{z}|\boldsymbol{X})q_{\phi_m^w}(\phi_{\boldsymbol{w}_m}|\boldsymbol{x}_m)} \prod_{n \neq m} p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z}, \boldsymbol{w}_n) \right)$$

(5)

where $r_1(\boldsymbol{w}_1), \ldots, r_M(\boldsymbol{w}_M)$ are auxiliary prior distributions on modality-specific features for each modality. [1]

Comparing with the objective in 4, the inferred modality-specific encoding is used *only* for self-reconstruction, and *not* for cross-modal reconstruction, for which the modality-specific code is sampled from the auxiliary prior. This crucial feature avoids the creation of a shortcut in the presence of modality-specific latent subspaces. In fact, cross-modal reconstructions are computed conditioning on a non-informative value for the modality-specific encoding, which forces the decoder to rely on the shared encoding $\boldsymbol{z}$ to reconstruct unobserved modalities. As a consquence, $\boldsymbol{z}$ encodes information useful to maximize reconstruction across modalities, i.e. shared information. Still, modality-specific subspaces can serve the purpose of modelling private variation, as private encoders are used for computing modality-specific codes for self-reconstruction.

The following lemma, for which we provide a proof in Appendix A, proves that MMVAE+ optimizes a valid ELBO and therefore belongs to the family of multimodal VAEs.

Lemma 1. *The MMVAE+ objective (Equation 5) is a valid lower bound on* $\log p_{\Theta}(\boldsymbol{x}_{1:M})$.

Note that while we obtain a valid ELBO for an arbitrary choice of auxiliary priors, we discuss our specific design choices in Appendix B. As in Shi et al. (2019), a multi-sample version of the objective can provide a tighter bound on the log-evidence. In Appendix C we discuss the details of the tighter version of the objective, along with the possibility to include a β hyperparameter (Higgins et al., 2017) to weight latent space regularization.

(a) MMVAE

(b) MMVAE+ (ours)

Figure 2: Graphical models for comparison of MMVAE (left) and MMVAE+ (right). Note that for MMVAE+ cross-modal reconstruction does not depend on inferred modality-specific information, thereby relying on the shared latent space $\boldsymbol{z}$ to encode information useful across modalities, i.e. shared information. At the same time, maximizing self-reconstruction of each modality m given the modality-specific $\boldsymbol{w}_m$ code, encourages private variation to be encoded in modality-specific subspaces.

---

[1] Note that we refer to these as priors in the sense that they are not conditional on the data, but are effectively surrogate non-informative inference distributions for private features, which do not depend on the observed data samples, and are different from the prior distributions for private information in the assumed generative process $p_1(\boldsymbol{w}_1), \ldots, p(\boldsymbol{w}_M)$.

4 EXPERIMENTS

We report experimental results for two challenging datasets introduced in previous work, namely PolyMNIST (Sutter et al., 2021) and Caltech Birds (CUB) Image-Captions (Shi et al., 2019; Wah et al., 2011). PolyMNIST is a synthetic dataset consisting of five modalities, depicting MNIST digits sharing the digit label, patched on random crops from five different background images, one for each modality. Each datapoint consists of five images, one per modality, where all the images share the digit label, but not the style of the handwriting, as MNIST samples are shuffled prior to the pairing. Shared information between modalities is therefore the digit label, while modality-specific information includes the style of the handwriting and the specific background image. The Caltech Birds (CUB) Image-Captions dataset consists of images of birds paired with matching linguistic descriptions. What makes this a challenging experiment is the large amount of modality-specific information for each modality, due to the different nature of the information sources. While previous work (Shi et al., 2019; 2021; Joy et al., 2022) has tackled a simplified version of this experiment by using pretrained ResNet-features, we train the models on actual images—a more realistic setting that was shown to be challenging for the predominant approaches (Daunhawer et al., 2022). All quantitative results are averaged over three independent seeds and we report standard deviations. Technical details on the experiments and additional results are available in Appendices E and F.

4.1 ENHANCED GENERATIVE QUALITY FOR SEMANTICALLY COHERENT GENERATION

This section shows our results on the PolyMNIST dataset comparing MMVAE+ to the predominant approaches, namely MMVAE (Shi et al., 2019), MVAE (Wu & Goodman, 2018) and MoPoE-VAE (Sutter et al., 2021). For completeness, we also compare with two recently proposed variations of MVAE and MMVAE, namely the MTCVAE (Hwang et al., 2021) and the mmJSD (Sutter et al., 2020), which both introduce additional regularization terms to the respective objectives. Qualitative results for conditional generation in Figure 3 illustrate the shortcomings of the existing approaches. The MVAE exhibits a lack of generative coherence, whereas the MMVAE and MoPoE-VAE both show a lack of sample diversity, resulting in poor generative quality. Even in this relatively simple setting, modality-specific information—such as the background details or the style of handwriting—tends to collapse to expected values for cross-modal generation. In contrast, the MMVAE+ shows a significantly better generative quality with an improved sample diversity and high semantic coherence. Comparing directly with the MMVAE, the results validate that our approach achieves enhanced generative quality without compromising semantic coherence.

For a quantitative comparison, we measure the performance in terms of generative coherence (Shi et al., 2019) and generative quality. The latter is estimated in terms of FID score (Heusel et al., 2017), a standard metric to evaluate sample quality for generative models in image domains. The scatter-plots in Figure 4 show that only the MMVAE+ reaches high generative quality *and* high semantic coherence consistently over a large range of hyperparameter values, while other models underperform in one of the two performance criteria. Note that while MTCVAE and mmJSD both show some improvement over the predominant approaches they are based on, e.g. MTCVAE markedly improves generative coherence over the MVAE, they still exhibit poor performance in either conditional or unconditional genenration. Notably, the advantage of MMVAE+ persists for both unconditional and conditional generation.

4.2 COMPARING WITH ALTERNATIVE APPROACHES WITH SEPARATE LATENT SUBSPACES

In this section, we compare MMVAE+ with alternative variants of multimodal VAE objectives that adopt a latent space that factorizes in separate shared and modality-specific subspaces. In particular, we compare with the factorized MMVAE objective in 4, as well as with its alternative version proposed in Sutter et al. (2020), which extends the single-space mmJSD model to a factorized latent space. Crucially, we find that both approaches exhibit a non-trivial problem: to improve generative coherence, they require strong constraining of modality-specific latent capacity, to avoid incurring in a shortcut where all information used by decoders is encoded independently in modality-specific subspaces.

In figure 5a we report an ablation for generative coherence for the compared models, varying the relative size of the modality-specific subspace for each modality with respect to the shared subspace.

| (a) MVAE | (b) MTCVAE | (c) mmJSD | (d) MoPoE-VAE | (e) MMVAE | (f) MMVAE+ |

Figure 3: Qualitative results for conditional generation on the PolyMNIST dataset. The input sample from the first modality is shown in the top row, and below are four conditionally generated samples for each of the remaining modalities.

Figure 4: Comparison of generative quality (in terms of FID, lower is better) and generative coherence (higher is better). The left scatterplot evaluates conditional (cross-modal) generation and the right subplot quantifies unconditional generation performance. For each model, we show the results for a range of representative β values (see Appendix E). An optimal model would lie in the top-right area of each scatterplot.

Adopting the factorized version of either the MMVAE or the mmJSD objective, generative coherence quickly deteriorates as more capacity is allocated to private subspaces, reaching values close to random when private and shared subspaces have equal size. This behaviour can arise from the fact that the encoding from each modality-specific subspace is used to compute both self- and cross-modal reconstructions of the given modalities (see section 3.2). Therefore, with enough capacity, the modality-specific encoder can learn all information for the given modality (i.e., both shared and private features), which creates a shortcut where all information flows through the modality-specific subspaces and the shared subspace is ignored by the decoder. As additional evidence for this phenomenon, we report in Figure 5b the amount of shared information present in private subspaces, in terms of latent classification accuracy (see Appendix D.2), when varying private latent capacity. As expected, as the number of dimensions for modality-specific latent subspaces is augmented, an increasing amount of shared information is present in the corresponding encodings.

It is evident from these results that current approaches achieve sufficient coherence across generated modalities, at the expense of carefully constraining the size of modality-specicic subspaces. This

(a) Generative coherence (higher is better)

(b) Latent classification accuracy from modality-specific encodings (lower is better)

(c) Generative quality (in terms of FID score, lower is better)

Figure 5: Ablation for generative coherence and latent classification accuracy, based on the modality-specific encodings, as a function of private latent dimensionality. The percentages on the x-axis indicate the relative size of any private subspace with respect to the shared subspace.

however has two undesirable effects. On one hand it inevitably limits modelling capacity for private information, which hampers generative quality, as showcased in figure 5c. On the other hand, and more importantly, achieving an adequate balance between the two performance criteria heavily depends on hyperparameter tuning, which calls for expensive model selection procedures in practical settings.

In contrast to the alternative approaches, the MMVAE+ proves to be significantly more robust with respect to hyperparameter values controlling the size of the modality-specific subspaces. In particular, our approach does not incur in a shortcut, and strikes the optimal balance between generative quality and generative coherence when shared and private latent subspaces for each modality have comparable capacities. Combining these results with the ones from the previous section, it is evident how our approach successfully exploits having additional modality-specific latent codes to enhance generative quality, without compromising semantic coherence.

4.3 CUB IMAGE-CAPTIONS

In this section, we test the MMVAE+ on the CUB Image-Captions (Shi et al., 2019; Netzer et al., 2011) dataset, and compare its performance with existing approaches in terms of conditional and unconditional generation, in order to validate our approach and test its impact on a complex real-world dataset. For the conditional caption-to-image generation (Figure 6), we again observe that modality-specific information tends to collapse to average values for mixture-based models, namely MMVAE, MoPoE-VAE and mmJSD, whereas MVAE and MTCVAE show convincing generative quality but a severe lack of coherence (cp. Daunhawer et al., 2022). Similar conclusions can be drawn for conditional image-to-caption generation (Figure 7). In contrast, MMVAE+ shows significantly better results for both caption-to-image and image-to-caption generation. Specifically, our model achieves high sample diversity for both the image and text modality. Hence, we demonstrate the effectiveness of our approach for more complex real-world data, where there is a sizeable amount of modality-specific information and significant heterogeneity across modalities.

	Conditional coherence	Conditional FID
MVAE	$0.271_{(\pm 0.007)}$	$172.21_{(\pm 39.61)}$
MTCVAE	$0.221_{(\pm 0.007)}$	$208.43_{(\pm 1.10)}$
mmJSD	$0.556_{(\pm 0.158)}$	$262.80_{(\pm 6.93)}$
MMVAE	$0.713_{(\pm 0.057)}$	$232.20_{(\pm 2.14)}$
MoPoE-VAE	$0.579_{(\pm 0.158)}$	$265.55_{(\pm 4.01)}$
MMVAE+ (ours)	$0.721_{(\pm 0.090)}$	$164.94_{(\pm 1.50)}$

Table 1: Comparison of generative quality (in terms of FID, lower is better) and generative coherence (higher is better) for conditional caption-to-image generation on the CUB Image-Captions dataset.

Figure 6: Conditional image-to-caption generation on the CUB Image-Caption dataset.

Figure 7: Conditional caption-to-image generation on the CUB Image-Caption dataset. For each model, the input caption is used to conditionally generate four images.

To quantitatively evaluate coherence, we design a new coherence proxy for the CUB Image-Captions dataset. While for the PolyMNIST dataset, the information shared between modalities always consists of the digit label, for the CUB Image-Captions dataset we do not have annotation for the shared content between modalities. Further, the ResNet-feature evaluation used in previous works (Shi et al., 2019; 2021) is not suitable to evaluate models that were trained on real images. Therefore, we design a coherence proxy for conditional caption-to-image generation based on the color of the described bird (see D.2 for details). Based on this metric, Table 1 provides a quantitative comparison of the models in for caption-to-image generation in terms of generative coherence and generative quality. We again quantify visual quality of the produced images using the FID score. The quantitative results suggest that the MMVAE+ can model complex real-world datasets, where the predominant models fail to achieve satisfying results in at least one of the two performance criteria.

5 CONCLUSION

This work introduced MMVAE+, a new model in the family of multimodal VAEs, which derives from the MMVAE and considerably improves its generative quality without compromising semantic coherence. The proposed model uses separate shared and modality-specific subspaces and leverages auxiliary priors to facilitate the estimation of cross-modal reconstructions. We show that the model optimizes a valid multimodal ELBO and that it effectively encodes shared and modality-specific information in the respective subspaces. Our approach can be generalized and extended to other types of decompositions of the joint encoder, such as the mixture-of-products of experts. We leave this as a possibility for future work. On both synthetic and real-world data, we demonstrate the effectiveness of our approach for enhancing generative quality without compromising semantic coherence. Compared to previous approaches with separate latent spaces, MMVAE+ is significantly more robust to hyperparameters values controlling the capacity of modality-specific subspaces. As such, MMVAE+ takes an important step towards the applicability of multimodal VAEs to complex, real-world multimodal datasets.

ETHICS STATEMENT

Given the nature of the experiments, and the datasets used we see no ethical concerns regarding this work.

REPRODUCIBILITY STATEMENT

We provide details about datasets, metrics, hyperparameters and architectures in the Appendix, which can aid reproducibility of our method along with the provided code.

REFERENCES

Diane Bouchacourt, Ryota Tomioka, and Sebastian Nowozin. Multi-level variational autoencoder: Learning disentangled representations from grouped observations. *Proceedings of the AAAI Conference on Artificial Intelligence*, 2018.

Yunjey Choi, Minje Choi, Munyoung Kim, Jung-Woo Ha, Sunghun Kim, and Jaegul Choo. Stargan: Unified generative adversarial networks for multi-domain image-to-image translation. In *Conference on Computer Vision and Pattern Recognition*, 2018.

Imant Daunhawer, Thomas M. Sutter, Kieran Chin-Cheong, Emanuele Palumbo, and Julia E Vogt. On the limitations of multimodal VAEs. In *International Conference on Learning Representations*, 2022.

Reuben Dorent, Samuel Joutard, Marc Modat, Sébastien Ourselin, and Tom Vercauteren. Heteromodal variational encoder-decoder for joint modality completion and segmentation. *Medical Image Computing and Computer Assisted Intervention*, 2019.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems*, 2017.

Irina Higgins, Loïc Matthey, Arca Pal, Christopher P. Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, 2017.

HyeongJoo Hwang, Geon-Hyeong Kim, Seunghoon Hong, and Kee-Eung Kim. Multi-view representation learning via total correlation objective. In *Advances in Neural Information Processing Systems*, 2021.

Tom Joy, Yuge Shi, Philip Torr, Tom Rainforth, Sebastian M Schmon, and Siddharth N. Learning multimodal VAEs through mutual supervision. In *International Conference on Learning Representations*, 2022.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2014.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *International Conference on Learning Representations*, 2014.

Changhee Lee and Mihaela van der Schaar. A variational information bottleneck approach to multiomics data integration. In *International Conference on Artificial Intelligence and Statistics*, 2021.

Mihee Lee and Vladimir Pavlovic. Private-shared disentangled multimodal vae for learning of latent representations. In *CVPR Workshop on Multimodal Learning and Applications*, 2021.

Kodai Minoura, Ko Abe, Hyunha Nam, Hiroyoshi Nishikawa, and Teppei Shimamura. A mixtureof-experts deep generative model for integrated analysis of single-cell multiomics data. *Cell Reports Methods*, 2021.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NeurIPS Workshop on Deep Learning and Unsupervised Feature Learning*, 2011.

Scott Reed, Zeynep Akata, Xinchen Yan, Lajanugen Logeswaran, Bernt Schiele, and Honglak Lee. Generative adversarial text to image synthesis. In *International Conference on Machine Learning*, 2016.

Maximilian Seitzer. pytorch-fid: FID Score for PyTorch. `https://github.com/mseitzer/pytorch-fid`, August 2020. Version 0.2.1.

Yuge Shi, N. Siddharth, Brooks Paige, and Philip Torr. Variational mixture-of-experts autoencoders for multi-modal deep generative models. In *Advances in Neural Information Processing Systems*, 2019.

Yuge Shi, Brooks Paige, Philip Torr, and N. Siddharth. Relating by contrasting: A data-efficient framework for multimodal generative models. In *International Conference on Learning Representations*, 2021.

Thomas M. Sutter and Julia E. Vogt. Multimodal relational VAE. In *NeurIPS Workshop on Bayesian Deep Learning*, 2021.

Thomas M. Sutter, Imant Daunhawer, and Julia E. Vogt. Multimodal generative learning utilizing jensen-shannon-divergence. In *Advances in Neural Information Processing Systems*, 2020.

Thomas M. Sutter, Imant Daunhawer, and Julia E Vogt. Generalized multimodal ELBO. In *International Conference on Learning Representations*, 2021.

Masahiro Suzuki, Kotaro Nakayama, and Yutaka Matsuo. Joint multimodal learning with deep generative models. *arXiv preprint arXiv:1611.01891.*, 2016.

Yao-Hung Hubert Tsai, Paul Pu Liang, Amir Zadeh, Louis-Philippe Morency, and Ruslan Salakhutdinov. Learning factorized multimodal representations. In *International Conference on Learning Representations*, 2019.

George Tucker, Dieterich Lawson, Shixiang Gu, and Chris J. Maddison. Doubly reparameterized gradient estimators for monte carlo objectives. In *International Conference on Learning Representations*, 2019.

Miguel Vasco, Hang Yin, Francisco S. Melo, and Ana Paiva. Leveraging hierarchy in multimodal generative models for effective cross-modality inference. *Neural Networks*, 2022.

Ramakrishna Vedantam, Ian Fischer, Jonathan Huang, and Kevin Murphy. Generative models of visually grounded imagination. In *International Conference on Learning Representations*, 2018.

Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The Caltech-UCSD Birds-200-2011 Dataset. Technical report, California Institute of Technology, 2011.

Jannik Wolff, Tassilo Klein, Moin Nabi, Rahul G Krishnan, and Shinichi Nakajima. Mixture-of-experts vaes can disregard variation in surjective multimodal data. In *NeurIPS Workshop on Bayesian Deep Learning*, 2021.

Jannik Wolff, Rahul G Krishnan, Lukas Ruff, Jan Nikolas Morshuis, Tassilo Klein, Shinichi Nakajima, and Moin Nabi. Hierarchical multimodal variational autoencoders, 2022.

Mike Wu and Noah Goodman. Multimodal generative models for scalable weakly-supervised learning. In *Advances in Neural Information Processing Systems*, 2018.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A. Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *International Conference on Computer Vision*, 2017.

A   PROOFS

Lemma 1. *The MMVAE+ objective (Equation 5) is a valid lower bound on* $\log p_\Theta(\boldsymbol{x}_{1:M})$.

Proof. We assume the data generative process

$$p_\Theta(\boldsymbol{X}, \boldsymbol{z}, \boldsymbol{W}) = p(\boldsymbol{z}) \prod_{m=1}^{M} p_{\theta_m}(\boldsymbol{x}_m | \boldsymbol{z}, \boldsymbol{w}_m) p(\boldsymbol{w}_m),$$

where $\boldsymbol{z}$ encodes the shared content between modalities, and each $\boldsymbol{w}_m$ encodes modality-specific information for modality m. Note that shared latent information in $\boldsymbol{z}$ and modality-specific information for each modality $\boldsymbol{w}_1, \ldots, \boldsymbol{w}_M =: \boldsymbol{W}$ are assumed to be independent. We start by approximating posterior inference for the shared latent space with a mixture-of-experts variational encoder $q_{\Phi_{\boldsymbol{z}}}(\boldsymbol{z}|\boldsymbol{X}) = \frac{1}{M} \sum_{m=1}^{M} q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z}|\boldsymbol{x}_m)$. With our assumptions the objective

$$\mathcal{L}_{\text{MMVAE}}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z}|\boldsymbol{x}_m)} \left[\log \frac{p(\boldsymbol{z}) p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z}) \prod_{n \neq m} p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z})}{q_\Phi(\boldsymbol{z}|\boldsymbol{X})} \right]. \tag{6}$$

is a valid lower bound on the log-evidence $\log p_\Theta(\boldsymbol{X})$.

Note that this is the MMVAE objective (Shi et al., 2019), where for each term in the sum the encoding $\boldsymbol{z} \sim q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z}|\boldsymbol{x}_m)$ is sampled from a unimodal encoder, and used to compute the conditional likelihood of all M modalities: in particular both self-reconstruction likelihood $\log p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z})$ and cross-modal reconstruction likelihoods $\log p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z})$ for $n \neq m$ are evaluated. We derive the MMVAE+ objective by adopting different estimators for the two kinds of likelihood terms. In detail, we estimate $\log p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z})$ using a variational encoder $q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m|\boldsymbol{x}_m)$ for modality-specific information and deriving the lower bound

$$\log p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z}) \geq \mathbb{E}_{q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m|\boldsymbol{x}_m)} \left[\log \frac{p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{w}_m, \boldsymbol{z}) p(\boldsymbol{w}_m)}{q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m|\boldsymbol{x}_m)} \right] \tag{7}$$

In contrast for cross-modal reconstruction likelihoods we propose the estimator

$$\log p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z}) = \log \mathbb{E}_{r_n(\boldsymbol{w}_n)} p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z}, \boldsymbol{w}_n) \geq \mathbb{E}_{r_n(\boldsymbol{w}_n)} \log p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z}, \boldsymbol{w}_n) \tag{8}$$

using an auxiliary prior distribution $r(\boldsymbol{w}_n)$ specific to each target modality. Note the first step holds by definition of conditional expectation, while the second step follows from Jensen's inequality.

Plugging the derived expressions in 7 and 8 in equation 6, we recover the MMVAE+ objective

$$\mathcal{L}_{\text{MMVAE+}}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{\substack{q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z}|\boldsymbol{x}_m) \\ q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m|\boldsymbol{x}_m) \\ \{r_n(\boldsymbol{w}_n)\}_{n \neq m}}} \log \left(\frac{p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z}, \boldsymbol{w}_m) p(\boldsymbol{z}) p(\boldsymbol{w}_m)}{q_{\Phi_{\boldsymbol{z}}}(\boldsymbol{z}|\boldsymbol{X}) q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m|\boldsymbol{x}_m)} \prod_{n \neq m} p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z}, \boldsymbol{w}_n) \right) \tag{9}$$

From the fact that equation 6 is an ELBO, and the fact that the derived expressions in 7 and 8 are lower bounds, we conclude that the MMVAE+ objective is an ELBO. $\square$

B   CHOICES OF AUXILIARY PRIORS

In this section we elaborate on the role of auxiliary prior distributions $r_1(\boldsymbol{w}_1), ..., r_M(\boldsymbol{w}_M)$ in our proposed objective, and the specific design choices for such distributions.

In our experiments, as auxiliary priors we choose zero-mean distributions with a variance parameter that is learnt at training time. Notably, the learnt variance is a separate parameter vector (for each private subspace) that does not affect the encoders. Moreover, the variance parameter, and hence the $r_1(\boldsymbol{w}_1), ..., r_M(\boldsymbol{w}_M)$ distributions are not computed conditioning on any specific data sample. Therefore having a variance parameter does not affect our results from lemma 1.

Having a learnt variance is a key component as it allows the auxiliary priors to adapt the effective value range of the private encoding for cross-modal reconstructions. Specifically, the prior can adapt the value range to serve as an indicator that informs the decoder about self-reconstructions versus cross-modal reconstructions. Empirically, we find support for this hypothesis, as each auxiliary prior tends to become a sharp distribution (i.e., approximately a delta function) in the course of training.

C INCLUDING A MULTI-SAMPLE ESTIMATOR AND A β HYPERPARAMETER IN THE MMVAE AND MMVAE+ OBJECTIVES

C.1 MULTI-SAMPLE MMVAE AND MMVAE+ OBJECTIVES

To tighten the bound on the log-evidence in 6, Shi et al. (2019) propose to use a multi-sample estimator. In fact the K-sample objective

$$\mathcal{L}_{\text{MMVAE}_\beta}^{ms}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{\boldsymbol{z}^{1:K} \sim q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)} \left[\log \frac{1}{K} \sum_{k=1}^{K} \frac{p_\Theta(\boldsymbol{X}, \boldsymbol{z}^k)}{q_\Phi(\boldsymbol{z}^k|\boldsymbol{X})} \right]$$

is a tighter ELBO compared to (6) for $K > 1$, as it can be shown with Jensen's inequality. However, as multi-sample estimators can lead to undesirably high variance, Tucker et al. (2019) have proposed a doubly-reparameterized gradient estimator (DReG) to reduce the variance in estimated gradients for latent-variable models with multi-sample objectives. Shi et al. (2019) resort to this estimator in computing gradients for the multi-sample version of the MMVAE objective.

Analogously for the MMVAE+ objective, a tighter bound on the log-evidence can be enforced if one uses a multi-sample estimator. In fact the K-sample version of the objective in (5)

$$\mathcal{L}_{\text{MMVAE+}}^{ms}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{\substack{\boldsymbol{z}_m^{1:K} \sim q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z}|\boldsymbol{x}_m) \\ \boldsymbol{w}_m^{1:K} q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m|\boldsymbol{x}_m) \\ \{\boldsymbol{w}_n^{1:K} \sim r_n(\boldsymbol{w}_n)\}_{n \neq m}}} \log \sum_{k=1}^{K} C_{\Phi,\Theta}(\boldsymbol{X}, \boldsymbol{z}^k, \boldsymbol{w}_1^k, \dots \boldsymbol{w}_M^k) \tag{10}$$

with

$$C_{\Phi,\Theta}(\boldsymbol{X}, \boldsymbol{z}^k, \boldsymbol{w}_1^k, \dots \boldsymbol{w}_M^k) = \frac{p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z}^k, \boldsymbol{w}_m^k) p(\boldsymbol{z}^k) p(\boldsymbol{w}_m^k)}{q_\Phi(\boldsymbol{z}^k|\boldsymbol{X}) q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m^k|\boldsymbol{x}_m)} \prod_{n \neq m} p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z}^k, \boldsymbol{w}_n^k)$$

is a tighter ELBO compared to (5) for $K > 1$, as it can be shown with Jensen's inequality.

C.2 BALANCING RECONSTRUCTION AND REGULARIZATION WITH A β HYPERPARAMETER

As common practice in the VAE literature, the objective in (1) can be rewritten as a sum of a reconstruction term and a KL-divergence term

$$\mathcal{L}_{\text{VAE}_\beta}(\boldsymbol{x}_{1:M}) = \mathbb{E}_{q_\Phi(\boldsymbol{z}|\boldsymbol{X})} \big[\log p_\Theta(\boldsymbol{X}|\boldsymbol{z}) \big] - \beta D_{KL}(q_\Phi(\boldsymbol{z}|\boldsymbol{X}) \, \| \, p(\boldsymbol{z}))$$

$$\tag{11}$$

where a β hyperparameter weighting the latter term is introduced to control smoothness of the latent space (Higgins et al., 2017). With the assumption of a mixture-of-experts joint encoder, one can in the same way rewrite the MMVAE objective as the sum of a reconstruction and a KL-divergence term, weighted with a β hyperparameter

$$\mathcal{L}_{\text{MMVAE}_\beta}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{q_{\phi_m}(\boldsymbol{z}|\boldsymbol{X})} \left[\log p_\Theta(\boldsymbol{X}|\boldsymbol{z}) \right] - \beta D_{KL}(q_\Phi(\boldsymbol{z}|\boldsymbol{X}) \, \| \, p(\boldsymbol{z}))$$

$$= \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)} \left[\log \frac{p_\Theta(\boldsymbol{X}|\boldsymbol{z})(p(\boldsymbol{z}))^\beta}{(q_\Phi(\boldsymbol{z}|\boldsymbol{X}))^\beta} \right] \tag{12}$$

From the last expression, one can derive a multi-sample version of the MMVAE objective

$$\mathcal{L}_{\text{MMVAE}_\beta}^{ms}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{\boldsymbol{z}^{1:K} \sim q_{\phi_m}(\boldsymbol{z}|\boldsymbol{x}_m)} \left[\log \frac{1}{K} \sum_{k=1}^{K} \frac{p_\Theta(\boldsymbol{X}|\boldsymbol{z}^k)(p(\boldsymbol{z}^k))^\beta}{(q_\Phi(\boldsymbol{z}^k|\boldsymbol{X}))^\beta} \right] \tag{13}$$

where the β hyperparameter is introduced. Note that Jensen's inequality proves (13) is a tighter bound on the log-evidence compared to (12) for $K > 1$ and any fixed value of $\beta \geq 1$.

Analogously, we can derive a β-weighted version of the K-sample MMVAE+ objective

$$\mathcal{L}_{\text{MMVAE+}_\beta}(\boldsymbol{x}_{1:M}) = \frac{1}{M} \sum_{m=1}^{M} \mathbb{E}_{\substack{q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z}|\boldsymbol{x}_m) \\ q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m|\boldsymbol{x}_m) \\ \{r_n(\boldsymbol{w}_n)\}_{n \neq m}}} \log \left(\frac{p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z}, \boldsymbol{w}_m)(p(\boldsymbol{z})p(\boldsymbol{w}_m))^\beta}{(q_\Phi(\boldsymbol{z}|\boldsymbol{X})q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m|\boldsymbol{x}_m))^\beta} \prod_{n \neq m} p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z}, \boldsymbol{w}_n) \right)$$

and the corresponding K-sample objective

$$\mathcal{L}^{ms}_{\text{MMVAE}+\beta}(\boldsymbol{x}_{1:M}) = \frac{1}{M}\sum_{m=1}^{M}\mathbb{E}_{\substack{\boldsymbol{z}_m^{1:K}\sim q_{\phi_{\boldsymbol{z}_m}}(\boldsymbol{z}|\boldsymbol{x}_m)\\ \boldsymbol{w}_m^{1:K}q_{\phi_{\boldsymbol{w}_m}}(\boldsymbol{w}_m|\boldsymbol{x}_m)\\ \{\boldsymbol{w}_n^{1:K}\sim r_n(\boldsymbol{w}_n)\}_{n\neq m}}}\log\sum_{k=1}^{K}D^{\beta}_{\Phi,\Theta}(\boldsymbol{X},\boldsymbol{z}^k,\boldsymbol{w}_1^k,\ldots\boldsymbol{w}_M^k)$$

with

$$D^{\beta}_{\Phi,\Theta}(\boldsymbol{X},\boldsymbol{z}^k,\boldsymbol{w}_1^k,\ldots\boldsymbol{w}_M^k) = \frac{p_{\theta_m}(\boldsymbol{x}_m|\boldsymbol{z}^k,\boldsymbol{w}_m^k)(p(\boldsymbol{z}^k)p(\boldsymbol{w}_m^k))^{\beta}}{(q_{\Phi}(\boldsymbol{z}^k|\boldsymbol{X})q_{\boldsymbol{w}_m}(\boldsymbol{w}_m^k|\boldsymbol{x}_m))^{\beta}}\prod_{n\neq m}p_{\theta_n}(\boldsymbol{x}_n|\boldsymbol{z}^k,\boldsymbol{w}_n^k)$$

Note that in our experiments, when training the MMVAE and the MMVAE+ with the respective K-sample β-weighted objectives we make use of the DReG estimator (Tucker et al., 2019).

D TECHNICAL DETAILS FOR DATASETS AND METRICS

D.1 DATASETS

In this work, we report experimental results on two multimodal datasets introduced in previous works, namely PolyMNIST (Sutter et al., 2021) and CUB Image-Captions (Shi et al., 2019; Netzer et al., 2011).

PolyMNIST is a synthetic dataset consisting of five image modalities. Each datapoint consists of five images depicting MNIST samples sharing the digit label, patched on random crops from five different background images, one for each modality. Shared information between modalities is the digit label, while private information comprises the background and the style of the handwriting, since MNIST digits are shuffled prior to the pairing.

The Caltech Birds (CUB) Image-Captions dataset consists of images of birds paired with matching linguistic descriptions. Making this experiment ambitious is the high amount of modality-specific information for each modality, due to the different nature of the information sources. Moreover, while for PolyMNIST the amount of shared information for each sample is fixed, always consisting of the digit label, here the amount of shared information present can vary from datapoint to datapoint. In fact, descriptions can be more or less detailed, leading to more or less shared information between modalities. This dataset presents a lot of challenges typical of a realistic experiment, which makes it a relevant setting to benchmark existing approaches.

Figure 8: Illustrative samples from PolyMNIST (left) and CUB Image-Captions (right) respectively. Images taken from Shi et al. (2019) and Daunhawer et al. (2022).

D.2 METRICS

FID score   In our experiments, to evaluate generative quality for image modalities we adopt the FID score (Heusel et al., 2017), a state-of-the-art metric to quantify visual sample quality for generative models in image domains, which has been shown to correlate well with human judgement. To compute FID scores we use the implementation from Seitzer (2020).

Generative coherence: PolyMNIST   To compute generative coherence in the PolyMNIST experiment, as done in previous works (Shi et al., 2019; Sutter et al., 2021; Daunhawer et al., 2022), we use the training samples for each single modality to train a classifier for the digit label. The resulting classifiers are then used to obtain a quantitative measure for conditional and unconditional

white	yellow	blue	red	
$[0, 0, 120]$	$[25, 50, 70]$	$[90, 50, 70]$	$[0, 50, 70]$	$[159, 50, 70]$
$[180, 18, 255]$	$[35, 255, 255]$	$[158, 255, 255]$	$[15, 255, 255]$	$[180, 255, 255]$
green	gray	brown	black	
$[36, 50, 70]$	$[0, 0, 50]$	$[24, 255, 255]$	$[0, 0, 0]$	
$[89, 255, 255]$	$[180, 18, 120]$	$[16, 50, 70]$	$[180, 255, 50]$	

Table 2: HSV (Hue, Saturation, Value) color ranges used to classify pixels in color classes. Each pixel in HSV color coding is represented by three values. Lower and upper limit(s) for each color class range(s) are reported below each color class label. Note that to include all tonalities of *red* one has to consider two distinct ranges.

generative coherence. To measure conditional generative coherence from a given input modality m to a given target modality n, we feed the conditionally generated sample to the classifier for the target modality n, then compare the predicted digit label with the true digit label. The matching rate for the whole test set measures conditional generative coherence from modality m to modality n. To obtain a single representative metric for PolyMNIST, we compute the average coherence for each target modality, and then average the five obtained results. For unconditional generation, coherence is measured by feeding jointly-generated samples for each modality to the corresponding trained classifier. Then the measure for coherence is the rate with which all classifiers output the same predicted digit label for N generations, where N is equal to the length of the test set, for compatibility with the sample size used to compute conditional coherence.

Generative coherence: CUB Image-Captions To have a quantitative assessment of semantic coherence in the CUB Image-Captions experiment we design a novel generative coherence metric for caption-to-image generation. In detail, we construct eight captions of the form *this bird is completely [color]*, where [color] takes values in the set {*white, yellow, red, blue, green, grey, brown, black*}. We divide the HSV color coding range according to these eight color classes (see Table 2). Then, for each of the starting captions we generate ten images. For each generated image we count the pixels belonging to each color class. We label an image as *coherent* if the color for the starting caption is among the two color classes with the highest pixel count in the image. We take into account the *two* color classes with the highest count, as the highest count for some images might be the background color rather than the color of the depicted bird. Finally, the ratio of *coherent* images over the total number of generated images is our coherence metric.

Latent classification accuracy In the PolyMNIST setting, where we have annotations for the shared information between modalities, i.e. the digit label, we use latent classification accuracy (Sutter et al., 2021; Daunhawer et al., 2022; Shi et al., 2019) as a proxy for the amount of shared information encoded in a given latent subspace. To compute this metric, a digit-classifier is trained on the latent embeddings and its accuracy on the test set is a proxy for how much information about the shared digit content is encoded in the latent code. For our results in section 4.2, where we aim to have a measure of how much shared information is present in modality-specific subspaces, we train a digit classifier on each of the five modality-specific latent embeddings, and then average the test accuracies of the five classifiers to obtain a single metric.

E   TECHNICAL DETAILS FOR THE EXPERIMENTS

PolyMNIST (results in Section 4.1 **and Appendix** F**)** Following the suggestions by the authors in Shi et al. (2019) to reach best performance on image-to-image datasets, we train the MMVAE assuming Laplace priors, likelihoods and posteriors, constraining their scaling across the D dimensions to sum to D. For compatibility, we use the same settings for the MMVAE+. In our experiments we set the size of the shared latent subspace for MMVAE+ to 32 dimensions. In order not to induct any bias, and have equal shared and private latent capacity for each modality, we also set the size of each modality-specific latent subspace to 32 dimensions. For a fair comparison with the MMVAE, we set the size of the latent space to be equal to the total latent capacity of MMVAE+, namely 160 dimensions. When training both models with a multi-sample estimator in the objective, we reduce the size of the latent space of MMVAE to 64 dimensions, due to main memory constraints. MM-

VAE and MMVAE+ are trained for 50 epochs when trained the K-sample version of the respective objectives, using $K = 10$ samples, while they are trained for 150 epochs when trained without multi-sample estimators. We train the mmJSD model again using a latent space of 160 dimensions, and for 150 epochs.

For MVAE, MoPoE-VAE, and MTCVAE, we use the settings in the work of Daunhawer et al. (2022) and Hwang et al. (2021), in order to obtain best performance in this experimental setting. We assume Laplace likelihoods and resort to Gaussian priors and posteriors which enable to compute product distributions in closed form. We train both MVAE and MoPoE-VAE for 500 epochs with a latent space of size 512, while MTCVAE (Hwang et al., 2021) is trained for 300 epochs, with the same latent space size.

We compare all models for a range of representative values of the regularization hyperparameter $\beta \in \{1.0, 2.5, 5.0\}$. Due to numerical instabilities the MVAE could not be trained with $\beta = 5.0$, and therefore for this model we set $\beta = 3.0$ as the last value of the regularization hyperparameter. Finally, for all compared models we use the same ResNet encoder and decoder networks for each modality.

PolyMNIST (results in Section 4.2**)** For a fair comparison between the models, we train the MM-VAE using the objective in 4, the mmJSD with the objective assuming factorized latent space (Sutter et al., 2020), and the MMVAE+, using the same ResNet encoder and decoder networks for each modality, assuming Laplace likelihoods, and training all models for 150 epochs, without resorting to multi-sample estimators for any of the models. Note that the size of the shared latent subspace is always fixed to 32 dimensions.

CUB Image-Captions On this experiment, for all compared models, we assume Laplace and one-hot categorical likelihood distributions for images and captions respectively, with Gaussian priors and posteriors, and set the latent space capacity to 64 dimensions. The size of private latent subspaces for MMVAE+ is chosen so that, for both modalities, summing the size of the private subspace and the shared subspace also amounts to 64 dimensions. We train MVAE, MoPoE-VAE, MTCVAE and mmJSD on this experiment for 150 epochs, with the settings to replicate best performance used in Daunhawer et al. (2022). In particular, ResNet encoder and decoder networks are used for both image and text modalities. MMVAE and MMVAE+ are trained for 50 epochs with the K-sample version of the respective objectives and $K = 10$, using the DReG estimator. Both models use Resnet network architectures for the image modality and CNNs for the text modality.

General specifics for the experiments All models are trained using the Adam optimizer (Kingma & Ba, 2014). We choose a learning rate of 5e-4 for MVAE and MoPoE-VAE, following Daunhawer et al. (2022), while for MMVAE and MMVAE+ we choose 1e-3. mmJSD, and MTCVAE are also trained with learning rate 1e-3, as suggested in the respective implementations by the authors. All quantitative results are averaged over three seeds, and reported with standard deviations.

F   ADDITIONAL RESULTS

F.1   POLYMNIST

Detailed quantitative model comparison In Table 3 we report the numerical values for each metric in the quantitative comparison in Section 4.1. These results show that only the MMVAE+ reaches high generative quality *and* high semantic coherence consistently over the considered β values, for both conditional and unconditional generation. Alternative models instead markedly underperform in one of the two criteria, or achieve convincing scores only for conditional *or* unconditional generation. The latter is the case with MTCVAE. In fact, while being an important improvement over the MVAE for conditional generation with greatly superior coherence, its performance markedly drops for unconditional generation, with extremely low values for coherence.

Conditional generation In figures 10 and 9 we report additional and more extensive qualitative results for the comparison between MMVAE+, MMVAE, MVAE, MTCVAE, mmJSD and MoPoE-VAE in section 4.1 for conditional generation.

Latent classification accuracy While conditional generation results showcased in Section 4.1 already offer sufficient evidence in this regard, here we show yet other results supporting the validity

of our modelling assumptions where the shared latent subspace and the private latent subspace contain disentangled shared and modality-specific information respectively for each modality. In detail, we use latent classification accuracy (see Appendix D.2) to prove that the MMVAE+ achieves factorization between shared information in z and private information in $w_1, \ldots, w_M$. For an ablation, similarly to section 4.2, we vary the proportion of latent dimensions allocated to the shared and the private subspace: with the shared subspace fixed to 32 dimensions, we vary the number of dimensions for each private subspace between $4, 8, 16, 24, 32$. Hence we go from having 12.5% of the shared latent capacity allocated to the w_m subspace for each modality m, to up to the two subspaces having the same size. The showcased results in Figure 11 indicate that the z subspace successfully encodes shared content across modalities, consistently throughout the ablation, which validates our modelling assumptions for MMVAE+, showing they are robust to variation in hyperparameters. The accuracies obtained with classifiers trained on private embeddings are, as expected, markedly low. These results offer additional empirical evidence demonstrating that MMVAE+ learns representations that factorize into shared and private subspaces consistently with respect to changes in hyperparameters.

Figure 9: Conditional generation qualitative results for MMVAE and MMVAE+ on the PolyMNIST dataset. For each different starting modality, we show input samples in the top row, and four instances of conditional generation for the remaining target modalities.

Figure 10: Conditional generation qualitative results for MVAE, MTCVAE, mmJSD and MoPoE-VAE on the PolyMNIST dataset. For each different starting modality, we show input samples in the top row, and four instances of conditional generation for the remaining target modalities.

Figure 11: MMVAE+: latent classification accuracy computed on the shared latent embedding z and the modality-specific latent embeddings $W = w_1, \ldots, w_M$, as a function of relative capacity of modality-specific subspaces. Note that this result validates our approach, which consistently encodes shared information across modalities in z, while this information is not present in W.

$\beta = 1.0$	Unconditional		Conditional	
	FID	Coherence	FID	Coherence
MVAE	$50.65 _{(\pm 0.72)}$	$0.007 _{(\pm 0.001)}$	$82.59 _{(\pm 6.22)}$	$0.093 _{(\pm 0.009)}$
MTCVAE	$110.85 _{(\pm 2.61)}$	$0.000 _{(\pm 0.000)}$	$58.98 _{(\pm 0.62)}$	$0,509 _{(\pm 0.006)}$
mmJSD	$179.76 _{(\pm 3.20)}$	$0.630 _{(\pm 0.004)}$	$209.98 _{(\pm 1.26)}$	$0.785 _{(\pm 0.023)}$
MoPoE-VAE	$98.56 _{(\pm 1.32)}$	$0.037 _{(\pm 0.002)}$	$160.29 _{(\pm 4.12)}$	$0.723 _{(\pm 0.006)}$
MMVAE	$165.17 _{(\pm 4.62)}$	$0.222 _{(\pm 0.019)}$	$152.11 _{(\pm 4.11)}$	$0.837 _{(\pm 0.004)}$
MMVAE(K=10)	$158.95 _{(\pm 1.79)}$	$0.292 _{(\pm 0.015)}$	$196.62 _{(\pm 1.99)}$	$0.865 _{(\pm 0.006)}$
MMVAE+	$86.12 _{(\pm 0.59)}$	$0.162 _{(\pm 0.23)}$	$81.24 _{(\pm 0.68)}$	$0.788 _{(\pm 0.074)}$
MMVAE+ (K=10)	$95.81 _{(\pm 5.52)}$	$0.316 _{(\pm 0.010)}$	$96.11 _{(\pm 5.36)}$	$0.859 _{(\pm 0.012)}$

$\beta = 2.5$	Unconditional		Conditional	
	FID	Coherence	FID	Coherence
MVAE	$58.53 _{(\pm 0.12)}$	$0.080 _{(\pm 0.006)}$	$85.23 _{(\pm 9.37)}$	$0.298 _{(\pm 0.044)}$
MTCVAE	$87.07 _{(\pm 0.89)}$	$0.003 _{(\pm 0.000)}$	$62.55 _{(\pm 1.30)}$	$0.591 _{(\pm 0.005)}$
mmJSD	$180.55 _{(\pm 6.66)}$	$0.630 _{(\pm 0.006)}$	$22.09 _{(\pm 5.34)}$	$0.778 _{(\pm 0.003)}$
MoPoE-VAE	$107.11 _{(\pm 0.780)}$	$0.141 _{(\pm 0.005)}$	$178.27 _{(\pm 2.01)}$	$0.720 _{(\pm 0.008)}$
MMVAE	$164.71 _{(\pm 4.38)}$	$0.232 _{(\pm 0.010)}$	$150.83 _{(\pm 2.69)}$	$0.844 _{(\pm 0.001)}$
MMVAE (K=10)	$164.64 _{(\pm 2.84)}$	$0.379 _{(\pm 0.034)}$	$197.24 _{(\pm 1.87)}$	$0.853 _{(\pm 0.007)}$
MMVAE+	$94.83 _{(\pm 2.34)}$	$0.341 _{(\pm 0.018)}$	$92.58 _{(\pm 1.50)}$	$0.864 _{(\pm 0.013)}$
MMVAE+ (K=10)	$103.67 _{(\pm 2.76)}$	$0.475 _{(\pm 0.014)}$	$102.60 _{(\pm 2.17)}$	$0.900 _{(\pm 0.002)}$

$\beta = 5.0$	Unconditional		Conditional	
	FID	Coherence	FID	Coherence
MVAE	$61.25 _{(\pm 0.40)}$	$0.112 _{(\pm 0.010)}$	$90.37 _{(\pm 3.20)}$	$0.301 _{(\pm 0.024)}$
MTCVAE	$85.43 _{(\pm 2.80)}$	$0.029 _{(\pm 0.001)}$	$74.61 _{(\pm 3.41)}$	$0.604 _{(\pm 0,004)}$
mmJSD	$186.49 _{(\pm 3.40)}$	$0.629 _{(\pm 0.005)}$	$226.20 _{(\pm 2.90)}$	$0.784 _{(\pm 0.029)}$
MoPoE-VAE	$122.68 _{(\pm 1.96)}$	$0.238 _{(\pm 0.001)}$	$182.99 _{(\pm 1.96)}$	$0.673 _{(\pm 0.002)}$
MMVAE	$164.29 _{(\pm 4.03)}$	$0.229 _{(\pm 0.017)}$	$152.11 _{(\pm 3.18)}$	$0.839 _{(\pm 0.010)}$
MMVAE (K=10)	$176.79 _{(\pm 1.32)}$	$0.407 _{(\pm 0.022)}$	$193.79 _{(\pm 2.83)}$	$0.817 _{(\pm 0.016)}$
MMVAE+	$109.29 _{(\pm 0.34)}$	$0.397 _{(\pm 0.226)}$	$106.95 _{(\pm 1.78)}$	$0.8318 _{(\pm 0.016)}$
MMVAE+ (K=10)	$115.57 _{(\pm 2.19)}$	$0.504 _{(\pm 0.018)}$	$118.30 _{(\pm 1.42)}$	$0.868 _{(\pm 0.005)}$

Table 3: Comparison of model performance for generative quality (in terms of FID, lower is better) and generative coherence (higher is better). Both conditional (cross-modal) generation and unconditional generation performance are evaluated. Each table shows the results for the compared models for a different β value. Note that values in the table relative to $\beta = 5.0$ for MVAE are actually computed with $\beta = 3.0$ due to numerical instabilities.

F.2 CUB IMAGE-CAPTIONS

Image quality for generation In figures 12 and 14 we report unconditional and conditional image generation results for the compared models on the CUB Image-Captions dataset. Image generation results for MMVAE, mmJSD, and MoPoE-VAE in this complex experiment are characterized by the presence a considerable number of generated samples for which modality-specific features are collapsed to average values, resulting in blurred images. MMVAE+ results on the contrary do not exhibit signs of this pattern, which indicates good modelling of modality-specific information even in this complex setting, compared to the other mixture-based approaches. For the MVAE and MTC-VAE, product-based approaches, we witness instead the presence of significant variation in produced images, but a total absence of generative coherence comparing with our approach. In figure 15 we also show the generated samples resulting from our computation of the coherence score for this experiment, as described in appendix D.2.

Image-to-caption generation In figure 13 we showcase conditional image-to-caption results for the compared models, showing the MMVAE+ is the only approach achieving high quality for the produced sentences, which are also fairly coherent in attributes such as the set color present in the bird.

Figure 12: Qualitative results for MVAE, MMVAE, MoPoE-VAE and MMVAE+ for the caption-to-image generation procedure used for an estimation of generative coherence in Section 4.3

Figure 13: Qualitative results for MVAE, MMVAE, MoPoE-VAE and MMVAE+ for the caption-to-image generation procedure used for an estimation of generative coherence in Section 4.3

Figure 14: Qualitative results for MVAE, MMVAE, MoPoE-VAE and MMVAE+ for the caption-to-image generation procedure used for an estimation of generative coherence in Section 4.3

Figure 15: Qualitative results for the compared models for the caption-to-image generation procedure used for an estimation of generative coherence as described in appendix D.2