Towards Flexible and Controllable Unknown Rejection

Abstract

Reliable prediction is an essential requirement for deep neural models that are deployed in open environments, where both covariate and semantic out-of-distribution (OOD) data arise naturally. Recent studies have formulated and pursued two problems named OOD generalization and detection independently, where the former aims to correctly recognize covariate shifts while the latter focuses on rejecting semantic shifts. However, existing methods are misaligned with real-world applications in two aspects. First, in practice, to make safe decisions, a reliable model should accept correctly recognized inputs while rejecting both those misclassified covariate-shifted and semantic-shifted examples. Second, considering the potential existing trade-off between rejecting different failure cases, more convenient, controllable, and flexible unknown rejection approaches are needed. To meet the above requirements, we propose a novel and elegantly simple unknown rejection framework to unify and facilitate classification with rejection under both covariate and semantic shifts. Our key insight is that by separating and consolidating failure-specific reliability knowledge with low-rank adapters and then integrating them, we can enhance the unknown rejection ability effectively and flexibly. Extensive experiments demonstrate the superiority of our framework.

1 Introduction

Deep neural models have achieved remarkable performance in closed-world scenarios, assuming that train and test sets come from the same distribution. However, in practice, out-of-distribution (OOD) data naturally arises during the deployment (Nguyen et al., 2015), which mainly includes two types named *covariate shifts* and *semantic shifts* (Bai et al., 2023). Specifically, as depicted in Fig. 1, a model trained on in-distribution (ID) data may encounter covariate shifts such as conditions with snowy night (Sakaridis et al., 2021) or corrupted inputs resulting from camera noise and sensor degradation (Hendrycks & Dietterich, 2018). Unfortunately, the model often suffers significant performance deterioration when deployed in those scenarios. To ensure safety, it is expected to reject wrong predictions instead of accepting them blindly. Alternatively, unknown categories with semantic shifts may also emerge (Hendrycks & Gimpel, 2016; Hendrycks et al., 2018). In this case, the model must reject to make incorrect decisions by detecting semantic-shifted examples.

In recent years, both covariate and semantic shifts have received extensive attention, and have been formulated as OOD generalization (Hendrycks et al., 2021; Yi et al., 2021; Liu et al., 2021; Schneider et al., 2020) and detection (Hendrycks et al., 2018; Zheng et al., 2024; Liu et al., 2020; Basart et al., 2022) problems, respectively. Concretely, the former focuses on recognizing inputs with covariate shifts while the latter focuses on rejecting inputs with semantic shifts. Instead of pursuing those two problems independently, Bai et al. (2023) handles OOD generalization and detection simultaneously by leveraging unlabeled wild data consisting of both covariate and semantic shifts during training. However, the aforementioned efforts still have primary limitations. First, for OOD generalization, there is no rejection option involved, and accepting misclassified covariate-shifted inputs could lead to catastrophic issues. Second, for OOD detection, the performance of prevalent methods drops a lot when inputs of known classes suffer from covariate shifts, and rejecting semantic-shifted samples while accepting all covariate-shifted samples may also lead to serious safety issues.

In addition, the trade-off between the rejection of different failure sources further complicates the problem. Recent studies (Jaeger et al., 2022; Kim et al., 2023b; Narasimhan et al., 2024)

Figure 1: (a) Unknown rejection rejects both the (✗) misclassified covariate-shifted and all semantic-shifted OOD samples, and accepts the (✓) correct prediction. (b) Illustration of three types of common failure cases in the natural open environment.

have observed that prevalent OOD detection methods proposed in the literature often sacrifice the performance when detecting incorrect predictions of ID samples. There are a few studies (Zhu et al., 2024a; Cen et al., 2023; Zhu et al., 2023a; Li et al., 2024) focused on developing reliable models that can reject both misclassified ID and semantic-shifted OOD data. Nevertheless, they typically overlook covariate-shifted samples, and it is hard to distinguish correct covariate-shifted samples from semantic-shifted ones. Besides, they typically train a deep model from scratch or fully fine-tune one, which is computationally heavy and inefficient. In practical scenarios, *different failure sources are not always predefined and can emerge continually*. For instance, an autonomous driving system performs classification with misclassification rejection on ID data under a normal environment (e.g., clean inputs on a sunny day), and switches to more challenging unknown rejection under covariate shifts when facing sensory degeneration or bad weather (Fig. 1 (b, Middle)). Moreover, when a car drives into the countryside, it may encounter unexpected novel objects such as sheep and deer (Fig. 1 (b, Right)), where the model should perform OOD detection and make a warning. In more common situations, a model is expected to have good rejection ability on various failure cases in the wild without reliability disparity. From a multi-objective optimization perspective, we could simultaneously optimize the model with existing methods dealing with covariate and semantic shifts. However, it is often hard or impossible (Kendall et al., 2018; Boyd & Vandenberghe, 2004) to find a single optimal solution that can optimize the performance on different failure sources simultaneously. Moreover, a single prefixed, static solution lacks the flexibility to explore and calibrate the trade-off among different requirements. Therefore, there is a demand for developing *flexible* and *controllable* unknown rejection methods.

The goal of this paper is to show that the above-mentioned limitations and requirements can be considerably addressed. For one thing, we aim to predict and accept correctly classified covariate-shifted examples while rejecting those misclassified ones and all unknown samples with semantic shifts. As illustrated in Fig. 1 (a), unlike the OOD detection problem that defines "positive" and "negative" with regard to the label space, unknown rejection directly specifies the distinction by the correctness of model's predictions, which is more reasonable and aligned with the requirement in practical applications. For another, considering the trade-off between rejecting different failure sources, we aim to develop a more flexible method that enables us to easily separate, consolidate, and incorporate different reliable knowledge regarding surrounding environments.

Contributions. (1) We study the unknown rejection problem under both covariate and semantic shifts, and call for flexible and controllable methods for reliability enhancement. (2) We propose a reliability arithmetic framework with low-rank adapters to compress and consolidate reliability knowledge effectively and flexibly. To the best of our knowledge, this work is the first to separate and compress reliability knowledge via low-rank adapters. Further, a random projection strategy is proposed for rank adaptation to enhance the tuning efficiency. (3) Comprehensive experiments demonstrating the strong performance of our method, as well as the flexibility of reliability edition.

2 PROBLEM FORMULATION

Training on in-distribution data. We focus on the multi-class classification setting. Let $\mathcal{X} \subset \mathbb{R}^d$ be an input space, $\mathcal{Y} = [K] = \{1, ..., K\}$ denotes the label space and $\mathcal{P}_{\text{in}}$ be the underlying in-distribution (ID) over $\mathcal{X} \times \mathcal{Y}$. Given a labeled training set $\mathcal{D}_{\text{in}}^{\text{train}} = \{(\mathbf{x}_i, y_i)\}_{i=1}^{N}$ comprising N

samples drawn *i.i.d.* from the joint data distribution $\mathcal{P}_{\text{in}}$, multi-class classification aims to learn a classifier $h : \mathcal{X} \rightarrow \mathcal{Y}$ with low misclassification error. Typically, we learn a function $f : \mathcal{X} \rightarrow \mathbb{R}^K$ that yields the posterior distributions of a given input by minimizing an empirical surrogate risk, e.g., cross-entropy (CE) loss, on $\mathcal{D}_{\text{in}}^{\text{train}}$, and then $h(\mathbf{x}) = \arg\max_{y \in [K]} f_y(\mathbf{x})$.

Inference in open environments with wild data. Trained on the ID data, a classifier f deployed in open environments can encounter various out-of-distribution (OOD) shifts, as shown in Figure 1(a). Typically, the OOD data can be grouped into covariate and semantic shifts (Yang et al., 2021):

- Covariate OOD $\mathcal{P}_{\text{out}}^{\text{covariate}}$ has the same label space $\mathcal{Y}$ as the training data, but the input space $\mathcal{X}^{\text{covariate}} \subset \mathbb{R}^d$ undergoes shifting and therefore is different from $\mathcal{X}$.
- Semantic OOD $\mathcal{P}_{\text{out}}^{\text{semantic}}$ represents new-class shifted samples that do not belong to any known classes, i.e., $y \notin \mathcal{Y}$. We further assume that the input space $\mathcal{X}^{\text{semantic}}$ and $\mathcal{X}$ are also in different subsets of $\mathbb{R}^d$, which makes OOD detection possible.

For inference with covariate shifts, existing literature formulates the OOD generalization problem (Hendrycks et al., 2021; Yi et al., 2021; Liu et al., 2021; Schneider et al., 2020) which aims to improve the classification accuracy of covariate-shifted samples. For inference with semantic shifts, prior studies formulate the OOD detection problem (Hendrycks et al., 2018; Zheng et al., 2024; Liu et al., 2020; Basart et al., 2022) which focuses on separating ID and semantic OOD.

Formulation of unknown rejection in the wild. In practice, one is likely to encounter both types of samples during classifier deployment. To this end, unknown rejection allows for abstention on both misclassified covariate-shifted and semantic-shifted data, while only accepting correctly classified inputs from known classes ($y = h(\mathbf{x})$ and $y \in \mathcal{Y}$). Formally, considering all possible distributions that a model may encounter in practice, we suppose the test distribution $\mathcal{P}^{\text{test}}$ is a mixture of data from in-distribution, covariate-shifted and semantic-shifted distributions:

$$\mathcal{P}^{\text{test}} = (1 - \pi_{\text{c}} - \pi_{\text{s}})\mathcal{P}_{\text{in}} + \pi_{\text{c}}\mathcal{P}_{\text{out}}^{\text{covariate}} + \pi_{\text{s}}\mathcal{P}_{\text{out}}^{\text{sematic}}, \tag{1}$$

where $\pi_{\text{c}}, \pi_{\text{s}}, \pi_{\text{c}} + \pi_{\text{s}} \in [0, 1]$. The goal of unknown rejection is to learn the classifier h and design a rejector $r : \mathbb{R}^d \rightarrow \{0, 1\}$, where an ideal rejector can ensure to make safe decisions by separating correctly classified samples from misclassified ones or semantic OOD data as follows:

$$r(\mathbf{x}) = \begin{cases} 1 & \text{if } \mathbf{x} \in \mathcal{P}_{\text{in}}(y \neq h(\mathbf{x})) \cup \mathcal{P}_{\text{out}}^{\text{covariate}}(y \neq h(\mathbf{x})) \cup \mathcal{P}_{\text{out}}^{\text{semantic}} \\ 0 & \text{if } \mathbf{x} \in \mathcal{P}_{\text{in}}(y = h(\mathbf{x})) \cup \mathcal{P}_{\text{out}}^{\text{covariate}}(y = h(\mathbf{x})) \end{cases}. \tag{2}$$

Here we emphasize the distinction between those three problems introduced above. OOD generalization only focuses on classification accuracy and has ***no rejection option***; OOD detection ***only rejects*** semantic-shifted samples from unknown classes ($y \notin \mathcal{Y}$), and blindly accepts misclassified samples from known classes ($y \neq h(\mathbf{x})$ and $y \in \mathcal{Y}$). Besides, misclassification detection (MisD) focuses on known classes and rejects misclassified ones. Unknown rejection provides a unified classification with rejection framework that satisfies the practical requirements.

Figure 2: Covariate shifts remarkably complicate the problem of unknown rejection.

Unknown rejection in the wild is quite challenging. Prior works (Hendrycks & Gimpel, 2016; Hendrycks et al., 2018; Liu et al., 2020; Cen et al., 2023) often study the rejection ability of a model without considering covariate shifts that will be anticipated at inference time. Actually, unknown rejection under covariate shifts is quite difficult. As shown in Fig. 2 (ResNet-18 (He et al., 2016) trained on CIFAR-10): (1) Within known classes, covariate shifts make it much harder to separate misclassified examples from correct ones. When increasing the corruption severity, the performance of MisD continually drops. (2) Considering OOD detection performance, the model struggles to

distinguish between known and unseen classes when the samples of known classes undergo covariate shifts. (3) From (1)-(2), we know that $\mathcal{P}_{\text{out}}^{\text{covariate}}(y \neq h(\mathbf{x}))$ and $\mathcal{P}_{\text{out}}^{\text{covariate}}(y = h(\mathbf{x}))$ are hard to be separated, and the confidence distributions of $\mathcal{P}_{\text{out}}^{\text{covariate}}$ and $\mathcal{P}_{\text{out}}^{\text{semantic}}$ are also mixed. Therefore, it is quite challenging to achieve the goal of unknown rejection in Eq. (2).

3 THE PROPOSED FRAMEWORK: TRUSTLORA

3.1 MOTIVATION AND OVERVIEW

Limitation of failure-specific full training. It is acknowledged that rejecting incorrect predictions is essential for reliable learning. However, the failure sources are rich in uncontrolled environments, including incorrect predictions of ID or corrupt-shifted samples, and also inputs from unknown new categories. Current methodologies predominantly focus solely on rejecting one specific failure case, e.g., OOD detection only rejects data with semantic shifts while accepting all other samples. This paradigm, however, has evident limitations: **(1)** *Unrecoverable.* Enhancing the ability of rejection on one specific failure may lead to unrecoverable damage on other aspects of the model, since it has been empirically revealed that trade-off existed when rejecting different failure sources (Jaeger et al., 2022; Kim et al., 2023b). This is undesirable in practice: an autonomous car can not return to its "standard" mode for normal environment after full tuning in OOD environment. **(2)** *Inflexible.* Full training with failure-specific optimization objectives often leads to a static solution. Considering the complexity of open environments, it is beneficial to have convenient ways that can flexibly adjust the trade-off at inference time without full retraining. **(3)** *Inefficient.* When facing new failure cases, full training a model is computationally intensive and time-consuming. In practice, to avoid catastrophic consequences, we expect the model to handle novel failure sources with minimal overhead in latency.

Reliability knowledge separation and integration. With the above limitations in mind, we propose to develop unknown rejection framework with separable and combinable reliability knowledge, which is different remarkably from the prior efforts. As demonstrated by Gueta et al. (2023), knowledge can be represented by a region in weight space. Our high-level idea is to compress reliability knowledge regarding different failure cases and then selectively integrate them based on real-world requirements. To this end, two important questions arise: how to get failure-specific knowledge and how to compress it. **(1)** *Acquire reliability.* Many methods have been developed in recent years for reliable prediction, and they often excel at one specific failure case. Those methods form a rich and diverse toolbox, which can be interpreted as encapsulating the specific reliability knowledge naturally. **(2)** *Compress reliability.* Common strategies to compress knowledge such as pruning (Tanaka et al., 2020) and knowledge distillation (Hinton et al., 2015) often suffer from the heavy computation issue, which conflicts with the efficient principle. Therefore, we hope to compress knowledge to a small set of parameters, enabling cheap computation and lightweight integration.

Based on the above discussion, we propose a novel **TrustLoRA** framework to acquire and integrate trustworthy knowledge, which is illustrated in Fig. 3 and detailed below.

3.2 RELIABILITY KNOWLEDGE SEPARATION WITH LOW-RANK ADAPTATION

LoRA-adapted reliability acquiring. To acquire and compress specific reliable knowledge related to covariate shits, we propose to fine-tune the model in specific low-rank subspace. Concretely, we leverage parameter efficient tuning technique with an auxiliary low-rank adapter (LoRA) (Hu et al., 2021). As illustrated in Fig. 3, LoRA composes of two rank decomposition matrices $\mathbf{B} \in \mathbb{R}^{u \times r}$ and $\mathbf{A} \in \mathbb{R}^{r \times v}$ where $r \in \mathbb{N}$ is the rank and $r \ll \min(u, v)$. v and u are the dimensionality of the input $\hat{\mathbf{x}} \in \mathbb{R}^v$ for current layer and hidden features, respectively. Therefore, $\mathbf{BA} \in \mathbb{R}^{u \times v}$ has the same size as the parameters, i.e., $\mathbf{W} \in \mathbb{R}^{u \times v}$, of the corresponding fully-connected layer in the feature extractor. The modified forward pass with LoRA becomes:

$$\mathbf{z} = (\mathbf{W} + \mathbf{BA})\hat{\mathbf{x}} = \mathbf{W}\hat{\mathbf{x}} + \mathbf{BA}\hat{\mathbf{x}}, \tag{3}$$

where $\mathbf{z} \in \mathbb{R}^u$ is the output, which will be the input of the next layer after passing non-linear activation. During the training stage, the original parameters $\mathbf{W}$ remain frozen, while only $\mathbf{A}$ and $\mathbf{B}$ are trainable, which is low-cost and parameter efficient.

To acquire and separate reliable knowledge in dynamic open environments, we propose to optimize the failure-specific objectives via the LoRA branch as follows. In this work, we follow most of

Figure 3: Illustration of the proposed reliability arithmetic framework. (Left) We freeze the pre-trained backbone and add a LoRA module to acquire failure-specific knowledge. (Right) The LoRAs are stored in the memory, and will be merged via arithmetic for unified unknown rejection in the wild.

existing studies that assume the real OOD data is unavailable. For covariate shifts, we leverage AugMix (Hendrycks et al., 2019b), which is a simple augmentation method with the following learning objective:

$$\mathcal{L}_{\text{LoRA,cov}} = \mathcal{L}_{\text{CE}}(f(\mathbf{x}), y) + \lambda \text{JS}\left(f(\mathbf{x}); f(\mathbf{x}_{\text{augmix1}}); f(\mathbf{x}_{\text{augmix2}})\right). \tag{4}$$

Denote $\overline{f} = \left(f(\mathbf{x}) + f(\mathbf{x}_{\text{augmix1}}) + f(\mathbf{x}_{\text{augmix2}})\right)/3$ the averaged posterior distributions of $\mathbf{x}$ and its augmented variants, and then the JS loss is: $\text{JS}\left(f(\mathbf{x}); f(\mathbf{x}_{\text{augmix1}}); f(\mathbf{x}_{\text{augmix2}})\right) = \frac{\lambda}{3}\left(\mathcal{L}_{\text{KL}}(f(\mathbf{x}), \overline{f}) + \mathcal{L}_{\text{KL}}(f(\mathbf{x}_{\text{augmix1}}), \overline{f}) + \mathcal{L}_{\text{KL}}(f(\mathbf{x}_{\text{augmix2}}), \overline{f})\right)$. For semantic shifts, we use OE (Hendrycks et al., 2018), which helps the model acquire the knowledge of unknown classes by introducing auxiliary outliers $\mathcal{D}_{\text{aux}}$. Specifically, we minimize the following objective:

$$\mathcal{L}_{\text{LoRA,sem}} = \mathcal{L}_{\text{CE}}(f(\mathbf{x}), y) + \lambda \cdot \mathcal{L}_{\text{KL}}\left(f(\mathbf{x}_{\text{aux}}), \mathcal{U}([K])\right), \tag{5}$$

where $\lambda > 0$ is a scalar, $\mathcal{U}([K])$ represents the uniform distribution over the training label space $\mathcal{Y} = [K]$. $\{\mathbf{A}, \mathbf{B}\}$ denotes all trainable parameters. Since the pre-trained backbone is frozen, the newly added LoRA captures the residual knowledge regarding the specific learning objectives.

Remark. We would like to clarify that we do not propose novel failure-specific learning objectives in this paper. Instead, we focus on designing a unified framework to integrate different sources of reliability knowledge in a flexible and parameter-efficient manner.

LoRA with random projection. For the initialization of LoRA, the common way is to initialize $\mathbf{B}$ with an all-zero matrix, while initialize $\mathbf{A}$ with a normal distribution. Specifically, each element in $\mathbf{A}$ is independently sampled from a standard Gaussian distribution. In other words, LoRA first projects the input $\hat{\mathbf{x}}$ into a low-rank space via random projection, and then decodes it to the original space. For random projection, the Johnson-Lindenstrauss (Dasgupta & Gupta, 2003) states that the pairwise relation between any two data points can be preserved in an appropriate lower-rank space. Therefore, we further fix the parameters of $\mathbf{A}$ once initialized and only optimize $\mathbf{B}$ in a LoRA module during the training stage, which is much more efficient than learning the original LoRA. Besides, we can store the random seed that generates the random projection of $\mathbf{A}$, requiring much less memory than storing the full matrix, as shown in Fig. 3. We empirically verify that LoRA only introduces a quite small amount of extra trainable parameters that are less than 1% of the original parameters.

3.3 RELIABILITY KNOWLEDGE CONSOLIDATION WITH LoRA ARITHMETIC

Let $\theta_{\text{pre}} \in \mathbb{R}^M$ be the parameters of a given pre-trained model, where M is the number of parameters. In order to deal with unknown rejection in the wild, we freeze θ_{pre} and learn an additional LoRA module with a loss function related to a specific emerged failure at phase t (e.g., OE loss for semantic shifts). Let $\theta_{\text{LoRA},t-1} \in \mathbb{R}^m$ be the weights of the LoRA before fine-tuning, $\theta_{\text{LoRA},t} \in \mathbb{R}^m$ be the corresponding weights after fine-tuning and $m \ll M$. The LoRA vector $\tau_{\text{LoRA},t}$ is given by the element-wise difference between $\{\theta_{\text{pre}}, \theta_{\text{LoRA},t}\}$ and $\{\theta_{\text{pre}}, \theta_{\text{LoRA},t-1}\}$ as follow:

$$\tau_{\text{LoRA},t} = \{\theta_{\text{pre}}, \theta_{\text{LoRA},t}\} - \{\theta_{\text{pre}}, \theta_{\text{LoRA},t-1}\} = \theta_{\text{LoRA},t} - \theta_{\text{LoRA},t-1}. \tag{6}$$

The intuition behind LoRA vector is to encapsulate crucial directions in which the model's parameters move when learning with a loss function (Ilharco et al., 2022) dealing with a specific failure source.

As illustrated in Fig. 3 (Right), after fine-tuning each LoRA module with its respective learning objective, we can perform reliability enhancement or reduction easily and flexibly via element-wise addition or negation with a scaling term $\alpha \in [0, 1]$ as follows:

- **LoRA addition**. The sum of the LoRA vectors $\tau = \sum_t \alpha_t \tau_{\text{LoRA},t}$ is added to a pre-trained model θ_{pre} to produce a model that performs unknown rejection on different failure sources. In our cases, we focus on model reliability under both covariate and semantic shifts, and we can get a model $\{\theta_{\text{pre}}, \tau\}$ with unified unknown rejection ability by merging the two LoRA vectors trained using AugMix and OE easily, in which

$$\tau = (1 - \alpha) \cdot \tau_{\text{LoRA,cov}} + \alpha \cdot \tau_{\text{LoRA,sem}}. \tag{7}$$

- **LoRA negation**. We can reduce the ability of rejecting specific failure while retaining performance in other cases by subtracting the LoRA vector from the given LoRA-augmented model. For example, we can get a model $\{\theta_{\text{pre}}, \tau\}$, whose OOD detection ability is weaken with $\tau = -\alpha \cdot \tau_{\text{LoRA,sem}}$.

The LoRA arithmetic is simple and effective to address the challenging unified unknown rejection. Specifically, in our case, we get LoRA vectors regarding covariate and semantic shits via learning objectives presented in Eq. (4) and Eq. (5), respectively. Then we perform LoRA addition to consolidate those two aspects of reliability. The proposed LoRA arithmetic has the following advantages: **(1)** *Flexible.* the scaling term α provides the possibility and flexibility to control the strength of reliability edition, easily adjusting the trade-off without full retraining. **(2)** *Efficient.* When facing new failure cases, we only fine-tune the LoRA, which is lightweight and computationally efficient with minimal latency compared with full training. **(3)** *Recoverable.* We can easily recover the model to the default setting without losing the original knowledge by removing the LoRA module.

Theoretical analysis. The investigated problem involves dealing with multiple failure cases, which can be formulated as a multi-objective learning problem. Recently, it has been proved that a linear combination of multiple base models can lead to a pareto-optimal solution with diverse preferences (Dimitriadis et al., 2023). In our work, we build on a pre-trained base model with parameters and introduce LoRA vectors to capture and compress the failure-specific reliable knowledge. Based on the Theorem in Dimitriadis et al. (2023), we can state the approximation power of the proposed LoRA arithmetic as the following Proposition, which states that TrustLoRA can flexibly find a model with a controllable solution for any scaling term $\alpha \in [0, 1]$. The proof can be found in the Appendix.

Proposition 3.1. *Given a compact $\mathcal{X} \subseteq \mathbb{R}^D$ and a family of continuous mappings $f_n : \mathcal{X} \to \mathbb{R}^{D'}$, $n = 1, \ldots, N$, there exists a ReLU multi-layer perceptron f with base parameters θ_{pre} and two low-rank vectors $\tau_{\text{LoRA,cov}}$ and $\tau_{\text{LoRA,sem}}$, such that for any $\epsilon > 0$ and all n, there exists an $\alpha \in [0, 1]$ satisfying $\|f_n(x) - f(x; \theta_{pre} + (1 - \alpha) \cdot \tau_{\text{LoRA,cov}} + \alpha \cdot \tau_{\text{LoRA,sem}})\| \le \epsilon$ for all $x \in \mathcal{X}$.*

4 EXPERIMENTS

Datasets and implementation. Following the common setup in literature, we assume that the real distribution of OOD data remains unknown during training. For covariate-shifted data, we use CIFAR-10/100-C (Hendrycks & Dietterich, 2018) consists of 15 diverse corruption types; for semantic-shifted data, we use natural image datasets including SVHN (Netzer et al., 2011), Textures (Cimpoi et al., 2014), Places (Zhou et al., 2018), LSUN-Crop (Xu et al., 2015), LSUN-Resize (Yu et al., 2015), and iSUN (Xu et al., 2015). To focus on the unknown rejection ability on distribution shifts, we first evaluate the performance with a mixture of covariate-shifted and semantic-shifted data at the inference stage and generally keep equal numbers of misclassified covariate-shifted data $\mathcal{P}_{\text{out}}^{\text{covariate}}(y \neq h(\mathbf{x}))$ and semantic OOD data $\mathcal{P}_{\text{out}}^{\text{semantic}}$, which are two kinds of failure sources we want to reject. Then, we provide the unified unknown rejection results evaluated on both clean ID and distribution-shifted data. We use the ResNet-18 (He et al., 2016) and optimize it with SGD optimizer for 200 epochs to get the standard pre-trained model. Then it is fine-tuned for 10 epochs to acquire different aspects of reliability. For LoRA, we simply set $r = 4$. More implementation details are provided in Appendix.

Metrics and comparison methods. We leverage AURC (‰) (Geifman & El-Yaniv, 2017; Jaeger et al., 2022), FPR95 (%) and AUC (%) (Hendrycks & Gimpel, 2016) to evaluate the performance of unknown rejection. Besides, we also introduce the F-AUC (%) (defined in Appendix). We compare TrustLoRA with various methods including CE (MSP) (Hendrycks & Gimpel, 2016), RegMixUp

Table 1: Unknown rejection performance under mixture of covariate and semantic shifts on CIFAR-10 with ResNet-18. Methods with * train from scratch, methods with + fully fine-tune the pretrained model, while others only fine-tune the LoRA.

Method	Severity-1				Severity-2				Severity-3			
	AURC	FPR95	AUC	F-AUC	**AURC**	FPR95	AUC	F-AUC	**AURC**	FPR95	AUC	F-AUC
CE*	56.04	37.53	89.49	87.41	89.05	44.23	86.93	84.19	122.75	48.93	84.63	81.17
RegMixUp*	57.05	50.60	88.56	86.86	89.13	55.62	86.30	83.89	124.50	58.52	84.05	80.99
CRL*	50.25	32.06	90.35	88.12	81.56	38.47	87.98	84.93	115.06	44.28	85.58	81.59
LogitNorm*	48.15	32.56	91.92	90.88	76.79	38.44	90.01	88.53	107.45	43.63	88.25	86.25
OE*	51.24	33.30	91.73	90.37	82.77	39.12	89.76	87.51	120.52	44.37	87.46	84.20
OpenMix*	29.46	28.13	92.45	91.08	46.90	32.61	90.95	89.12	66.86	36.94	89.18	86.83
SURE*	31.25	27.39	92.67	91.26	48.13	31.19	91.02	89.51	68.31	36.60	89.55	86.27
RCL+	58.01	35.92	89.53	87.47	93.19	43.11	86.95	84.17	132.03	48.36	84.57	81.12
SCONE+	44.01	26.99	93.13	92.08	71.28	32.75	91.17	89.37	104.06	38.91	88.83	86.15
RegMixUp	62.17	53.63	87.97	86.11	94.89	57.20	85.73	83.23	130.78	61.87	83.37	80.32
CRL	56.28	38.40	89.36	87.37	88.87	44.57	86.97	84.27	125.28	50.16	84.45	81.09
LogitNorm	59.05	36.71	89.41	87.22	94.15	42.89	86.84	83.85	133.41	48.76	84.26	80.62
OE	43.63	26.01	93.51	92.47	70.04	30.86	92.56	90.69	100.99	36.04	90.91	87.96
AugMix	36.62	36.09	90.72	89.16	51.73	39.06	89.61	87.71	67.82	41.97	88.51	86.20
MaxLogit	40.58	45.39	89.30	88.08	55.32	46.52	88.57	87.06	71.02	48.31	87.74	85.90
Energy	43.50	49.19	88.03	86.84	58.75	50.10	87.33	85.94	74.90	51.51	86.48	84.86
KNN	43.87	42.53	87.20	86.00	61.94	45.98	85.71	84.27	82.10	48.63	84.02	82.35
FS-KNN	47.54	55.75	87.29	86.01	62.36	55.35	86.79	85.30	80.36	57.86	85.52	83.74
NNGuide	51.77	63.95	85.25	84.05	68.17	63.28	84.65	83.32	84.80	63.49	84.01	82.40
Relation	58.98	59.52	80.85	79.74	77.10	60.19	80.17	78.85	97.12	61.66	79.04	77.57
GEN	41.30	46.00	88.78	87.62	56.34	47.31	88.00	86.61	72.20	48.94	87.18	85.48
ASH	41.10	45.87	89.11	87.89	55.97	47.28	88.31	86.83	72.08	49.31	87.44	85.66
TrustLoRA	**28.68**	**23.80**	**93.67**	**92.53**	**41.64**	**27.43**	**92.67**	**91.18**	**56.64**	**30.62**	**91.55**	**89.65**

(Pinto et al., 2022), CRL (Moon et al., 2020), LogitNorm (Wei et al., 2022), OE (Hendrycks et al., 2018), OpenMix (Zhu et al., 2023a), SURE (Li et al., 2024), RCL (Zhu et al., 2024a), AugMix (Hendrycks et al., 2019b), MaxLogit (Hendrycks et al., 2022), Energy (Liu et al., 2020), KNN (Sun et al., 2022), FS-KNN (Cen et al., 2023), NNGuide (Park et al., 2023), Relation (Kim et al., 2023a), GEN (Liu et al., 2023) and ASH (Djurisic et al., 2022). For training-time methods, we report the results of both training from scratch and LoRA fine-tuning. Score-based methods are applied to LoRA-augmented model tuning with AugMix. TrustLoRA leverages the simple MSP score (Hendrycks & Gimpel, 2016).

4.1 RESULTS AND DISCUSSION

To fully reflect the unknown rejection performance under both covariate and semantic shifts, we combine each of 15 corruptions under three different severity with six semantic OOD sets, resulting in 90 wild data mixtures in total. We report the average performance on those 90 evaluations.

Trade-off between the two unknown rejection tasks. Fig. 4 shows the performance change when fine-tuning the pre-trained model. Cov-MisD denotes the ability to reject misclassified covariate-shifted (e.g., `Gaussian noise`) examples. Unknown rejection denotes the ability to reject both misclassified covariate-shifted data and semantic-shifted data jointly. We can clearly observe that when fine-tuning with OE (after the dotted line) to acquire OOD detection ability, it is harder to detect misclassi-

Figure 4: Change of rejection ability when fine-tuning the pre-trained ResNet-18 on CIFAR-100.

fied corrupted samples, e.g., AURC (↓) of Cov-MisD increases dramatically. As a result, the unified unknown rejection performance becomes worse.

Our method achieves strong performance. The main results in Table 1 and 2 verify that TrustLoRA establishes overall strong performance, especially on *AURC ↓, which has been considered as the most important metric for unknown rejection evaluation* (Jaeger et al., 2022; Moon et al., 2020). In particular, we consider two groups of baselines: training the model from scratch (denotes with *) and fine-tuning the pre-trained model. We highlight a few observations: (1) TrustLoRA

Table 2: Unknown rejection under mixture of covariate and semantic shifts on CIFAR-100.

Method	Severity-1				Severity-2				Severity-3			
	AURC	FPR95	AUC	F-AUC	**AURC**	FPR95	AUC	F-AUC	**AURC**	FPR95	AUC	F-AUC
CE*	163.66	54.88	82.95	76.33	218.26	61.90	79.53	71.53	279.10	67.12	76.65	68.06
RegMixUp*	154.87	54.34	83.12	76.72	198.08	60.46	80.25	72.64	249.93	65.33	77.43	69.25
CRL*	152.20	53.03	83.94	77.67	195.12	59.43	81.07	73.37	244.45	64.10	78.74	70.00
LogitNorm*	166.34	56.51	82.91	77.24	217.56	62.15	80.21	73.37	273.87	66.38	77.78	70.37
OE*	149.02	45.48	87.09	83.17	194.97	51.69	85.26	80.21	246.45	56.24	83.31	77.18
OpenMix*	134.18	46.46	86.57	81.84	164.32	51.49	84.47	78.78	203.87	56.18	82.29	76.10
SURE*	137.62	48.35	86.04	82.26	172.45	51.76	83.95	78.41	205.71	56.62	82.18	76.54
RCL+	155.85	52.89	84.29	78.73	202.39	59.20	81.61	74.88	256.47	64.10	79.11	71.83
SCONE+	148.50	47.65	86.50	81.69	201.73	53.92	83.57	77.37	264.59	59.29	80.74	74.03
RegMixUp	155.58	53.51	83.81	77.99	203.97	59.66	80.70	73.83	261.76	64.50	77.96	70.71
CRL	153.48	52.10	84.27	78.57	204.13	58.43	81.24	74.25	262.74	63.65	78.31	71.19
LogitNorm	155.08	52.55	84.14	78.38	207.23	58.92	81.07	74.10	267.35	63.96	78.16	71.06
OE	147.40	46.57	87.21	83.04	197.74	52.09	84.73	79.32	259.43	57.08	82.12	76.15
AugMix	141.23	51.24	84.69	79.69	158.07	54.44	83.47	77.63	177.71	57.12	82.26	75.69
MaxLogit	150.37	57.84	83.33	78.72	166.31	59.89	82.35	76.96	185.83	61.91	81.20	75.10
Energy	158.37	60.62	81.52	77.58	175.02	62.48	80.47	75.90	194.12	64.27	79.40	74.28
KNN	168.58	66.07	80.55	77.54	184.77	67.07	79.41	75.79	204.44	68.17	78.22	74.09
FS-KNN	143.83	56.08	84.71	81.69	167.36	58.13	83.03	79.74	183.17	59.21	82.26	77.12
NNGuide	180.32	66.12	76.27	72.23	197.55	67.51	75.21	70.47	215.89	68.58	74.39	69.10
Relation	171.64	67.49	80.28	76.20	186.00	67.95	79.49	74.63	204.07	68.98	78.58	73.07
GEN	157.47	60.25	81.68	77.69	174.32	62.19	80.57	75.99	193.63	64.04	79.50	74.32
ASH	150.38	57.78	83.22	78.77	167.33	59.93	82.09	76.90	185.92	61.75	81.05	75.13
TrustLoRA	**129.64**	**46.46**	**87.29**	**83.73**	**149.14**	**50.12**	**85.77**	**81.40**	**172.35**	**53.32**	**84.41**	**79.28**

Figure 5: Flexibility of controlling the strength of reliability edition on CIFAR-100.

outperforms strong training methods like LogitNorm (Wei et al., 2022), CRL (Moon et al., 2020) and RegMixUp (Pinto et al., 2022) in both training from scratch and fine-tuning scenarios. (2) TrustLoRA outperforms competitive post-hoc OOD detection methods, which are applied to the same model fine-tuned with AugMix and hence they have the same classification accuracy. (3) The proposed reliability arithmetic framework excels in detecting both misclassified covariate-shifted and semantic-shifted data, achieving the best performance among all compared methods.

Flexibility of controlling the strength of reliability edition. We separate reliability knowledge with LoRAs and merge them to get a unified failure detector. One of the primary advantages of our method is to control the strength of each kind of reliability flexibly based on end-user preference without training the model again or affecting the original model. In Fig. 5 (Left), we show that the scaling α in Eq. (7) can easily control the preference between MisD under covariate shits and OOD detection. In Fig. 5 (Middle and Right), we observe that an overall

Figure 6: Accurate forgetting of OOD detection ability while keeping the MisD ability on clean ID (Left) and covariate-shifted data (Right).

strong unified unknown rejection performance can be achieved with $\alpha \in [0.4, 0.6]$, and we simply set $\alpha = 0.5$ for all experiments.

Selective reliability forgetting with LoRA negation. Besides LoRA addition for unified unknown rejection, here we explore accurate reliability forgetting. We apply the OOD detection vector $\tau = -\alpha \cdot \tau_{\text{LoRA,sem}}$ (learned with OE) to a given model (e.g., LoRA tuning with AugMix). The experiments on CIFAR-100 in Fig. 6 show that we can enable the model to forget OOD detection

Table 3: Unknown rejection performance on CIFAR-100 with ViT.

Method	Severity-1				Severity-2				Severity-3			
	AURC	**FPR95**	**AUC**	**F-AUC**	**AURC**	**FPR95**	**AUC**	**F-AUC**	**AURC**	**FPR95**	**AUC**	**F-AUC**
Full-FT	49.17	33.80	91.07	89.09	69.78	37.67	89.77	87.08	92.46	41.43	88.39	84.81
Linear	98.88	37.34	90.03	87.23	116.38	40.22	88.94	85.33	134.55	43.36	87.70	83.20
CE	51.68	33.77	91.30	89.61	73.33	36.91	90.14	87.88	93.37	40.73	88.87	85.95
RegMixUp	50.54	37.70	90.83	89.21	74.42	44.21	88.97	86.78	97.86	49.19	87.35	84.41
CRL	54.48	34.01	91.23	89.44	76.32	37.63	90.01	87.65	95.83	40.86	88.74	85.70
LogitNorm	59.66	49.24	88.70	87.39	81.65	50.18	88.16	86.44	101.24	51.96	87.25	85.03
AugMix	46.13	34.27	91.12	89.37	65.15	37.65	90.06	87.75	85.36	41.12	88.83	85.89
MaxLogit	52.22	43.66	89.35	88.08	70.65	45.35	88.76	87.11	89.95	47.21	87.93	85.79
Energy	55.52	48.50	88.24	87.00	74.24	49.68	87.76	86.18	93.74	51.18	87.02	85.07
KNN	58.91	53.46	86.82	85.46	78.90	54.02	86.11	84.51	99.20	54.78	85.32	83.38
NNGuide	53.86	46.97	88.53	87.28	72.53	48.36	87.96	86.40	92.06	50.20	87.17	85.23
GEN	54.15	46.31	88.59	87.36	73.01	47.82	88.00	86.48	92.40	49.49	87.25	85.28
TrustLoRA	**43.40**	**31.25**	**92.13**	**90.78**	**63.01**	**34.08**	**91.22**	**89.36**	**83.37**	**37.91**	**89.90**	**87.56**

ability, while with little deterioration of MisD ability on clean ID (Left) and covariate-shifted data (Right). This demonstrates that our method can enable flexible reliability knowledge edition.

Experiments with ViT. We also conduct experiments on pre-trained ViT backbone (ViT-B16) (Dosovitskiy et al., 2020), and perform full fine-tuning, linear prob and LoRA tuning. Detailed implementation can be found in Appendix. Despite the strong performance of pre-trained ViT-B16, results in Table 3 reveal that our method yields notable improvement, especially on AURC.

Large scale experiments on ImageNet. We provide additional large-scale results on the ImageNet-200/500 benchmark with ResNet-50. The classes were randomly sampled from 1K, and we also sampled another set of classes (with equal numbers) as outliers for OE. At inference stage, we use a mixture of covariate and semantic OOD data. Specifically, for semantic shifts, we use the fixed ImageNet OOD dataset proposed in (Bitterwolf et al., 2023), which includes truly OOD versions of 11 popular OOD datasets with in total of 2715 OOD samples; for covari-

Table 4: Experimental results on ImageNet.

Method	ImageNet-200		ImageNet-500	
	AURC	**AUC**	**AURC**	**AUC**
Baseline[*]	188.37	92.55	268.42	89.08
MaxLogit[*]	198.44	90.11	286.90	85.03
Energy[*]	203.02	89.28	295.91	83.71
AugMix (LoRA)	166.53	93.25	236.25	89.95
OE (LoRA)	180.18	92.78	265.11	89.50
MaxLogit (AugMixLoRA)	187.54	91.97	259.65	87.82
Energy (AugMixLoRA)	197.60	91.63	266.37	86.65
TrustLoRA	**159.67**	**93.91**	**229.92**	**90.15**

ate shifts, we use the corruption type `Frost` with severity-1. Results in Table 4 suggest that our method yields strong unknown rejection performance compared with competitive baselines.

TrustLoRA outperforms the multi-task learning. We further compare our method with more baselines: (1) Two new methods named SIRC (Xia & Bouganis, 2024) and FMFP (Zhu et al., 2023b) (FlatLoRA in our comparison). (2) Multi-task tuning with combined OE and Aug-Mix learning objectives. The results in Table 5 verify that our method outperforms SIRC and FlatLoRA consistently. In particular, our LoRA arithmetic outperforms the multi-task learning,

Table 5: Comparison with more baselines and multi-task learning on CIFAR-100, severity-1.

Method	**AURC**	**FPR95**	**AUC**	**F-AUC**
SIRC[*] (MSP, $z1$)	160.26	52.17	83.75	76.65
FlatLoRA	152.94	51.97	84.40	78.74
SIRC (AugMixLoRA)	139.86	50.53	85.50	80.04
AugMix (Full FT)	133.68	49.79	85.05	80.48
AugMix+OE (Full FT)	138.92	50.26	85.40	81.44
TrustLoRA	**129.64**	**46.46**	**87.29**	**83.73**

i.e., AugMix+OE (Full FT) in Table 5. *Intuitively*, this is because when optimizing both two objectives in a multi-task learning (MTL) manner, there exist remarkable conflicts between pulling covariate-shifted samples close to class centers while pushing semantic-shifted samples away from class centers since those two types of shifted samples are often overlapping. *Theoretically*, the Bayes-optimal reject rule for MisD is based on maximum class-posterior probability $\max_{y \in \mathcal{Y}} \mathbb{P}(y|\mathbf{x})$, while OOD detection rejects samples with small density ratio $p(\mathbf{x}|\text{in})/p(\mathbf{x}|\text{out})$ (Zhu et al., 2023b; Narasimhan et al., 2024). OOD detection methods such as OE and Energy score often perform density estimation explicitly or implicitly. However, to separate samples from known classes and unknown semantic-shifted unknown classes, binary discrimination would compress the confidence distribution of correct and incorrect covariate-shifted samples. As a result, MTL of the two objectives would be unstable. Differently, our proposed LoRA arithmetic overcomes the above limitation with reliability knowledge separation and consolidation.

Table 6: Robustness to different auxiliary data when acquiring OOD detection ability.

Auxiliary Data	Severity-1				Severity-2				Severity-3			
	AURC	FPR95	AUC	F-AUC	AURC	FPR95	AUC	F-AUC	AURC	FPR95	AUC	F-AUC
TIN597	130.45	45.26	87.41	83.19	152.50	49.63	85.81	80.83	178.82	52.73	84.30	78.66
RandomImage	129.64	46.46	87.29	83.73	149.14	50.12	85.77	81.40	172.35	53.32	84.41	79.28

Robustness to different auxiliary data. In this paper, the proposed TrustLoRA acquires OOD detection via OE technique, which requires access to auxiliary outlier data. For CIFAR benchmark, the `RandomImage` is used as auxiliary outliers following existing work. In Table 6 (CIFAR-100), we show that Trust-LoRA is robust to other auxiliary outliers like TIN597 (Zhang et al., 2023b).

Figure 7: MisD ability on clean ID.

Unified unknown rejection on clean ID and distribution-shifted data. In above experiments, to *clearly reflect the unknown rejection ability under covariate and semantic shits*, we do not include clean ID data at inference time. With integrated LoRAs of covariate and semantic shifts, the MisD performance on the original clean set can be well preserved on CIFAR-10 while suffering from a slight drop on CIFAR-100. As shown in Fig. 7 (Left), TrustLoRA can further recover and integrate

Table 7: Comparison of unified unknown rejection ability evaluated on both clean ID and distribution-shifted data.

Method	CIFAR-10				CIFAR-100			
	AURC	FPR95	AUC	F-AUC	AURC	FPR95	AUC	F-AUC
CE	32.62	31.56	91.59	89.98	134.19	48.70	85.47	79.71
RegMixUp	34.82	44.92	90.56	89.27	133.88	49.25	84.96	79.35
CRL	30.37	26.24	92.30	90.54	129.75	47.73	85.97	80.47
LogitNorm	27.11	26.10	93.76	92.97	138.73	51.38	85.22	80.20
AugMix	27.47	31.75	91.85	90.45	133.73	49.50	85.34	80.70
MaxLogit	32.53	46.17	89.95	88.86	142.31	56.11	84.00	79.74
Energy	35.48	50.48	88.52	87.49	149.95	58.96	82.23	78.55
GEN	33.33	46.73	89.31	88.31	149.52	58.66	82.30	78.59
ASH	33.09	46.95	89.67	88.61	142.67	56.05	83.87	79.75
TrustLoRA	**20.86**	**20.86**	**94.42**	**93.47**	**121.90**	**44.44**	**87.75**	**84.35**

MisD knowledge on clean set by merging an additional LoRA fine-tuned with flat minima loss Zhu et al. (2023b), and we denote the model "LoRA-3". Fig.7 (Right) compares the MisD on clean ID data, where our method successfully achieves comparable MisD performance with the original model, and outperforms other methods. Table 7 further reports the results on full spectrum of test set including clean ID, covariate and semantic OOD data. As can be observed, our method still achieves strong performance and outperforms other methods.

Computational costs. Table 8 reports the number of parameters of the base model and all LoRA modules, where our method has much smaller parameters than the base model. Note that we further fix the parameters of **A** once initialized and only optimize **B** in LoRA during the training stage, which is much more efficient than learning the original LoRA.

Table 8: Comparison of the computational costs.

Model	ResNet-20	ResNet-18	ViT (B16)
BaseModel	$0.2871M$	$10.91M$	$81.89M$
TrustLoRA	**$0.0275M$**	**$0.25M$**	**$0.21M$**

5 CONCLUSION

In this work, we present a novel reliability arithmetic framework to address the unknown rejection under both covariate and semantic shifts. For the first time, we introduce low-rank adaptation to separate and compress reliability knowledge. The proposed framework is a powerful tool to easily achieve unified, flexible and controllable reliability towards different failure sources. Extensive experiments and analysis show the superiority of our method over existing approaches for unknown rejection under both covariate and semantic shifts. We hope this work can inspire the community to investigate the trade-off among different failure sources, and further develop flexible and controllable methods for reliable prediction in real-world applications.

REFERENCES

Haoyue Bai, Gregory Canal, Xuefeng Du, Jeongyeol Kwon, Robert D Nowak, and Yixuan Li. Feed two birds with one scone: Exploiting wild data for both out-of-distribution generalization and detection. In *International Conference on Machine Learning*, pp. 1454–1471. PMLR, 2023.

Steven Basart, Mazeika Mantas, Mostajabi Mohammadreza, Steinhardt Jacob, and Song Dawn. Scaling out-of-distribution detection for real-world settings. In *International Conference on Machine Learning*, 2022.

Julian Bitterwolf, Maximilian Müller, and Matthias Hein. In or out? fixing imagenet out-of-distribution detection evaluation. In *Proceedings of the 40th International Conference on Machine Learning*, pp. 2471–2506, 2023.

Stephen P Boyd and Lieven Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

Jun Cen, Di Luan, Shiwei Zhang, Yixuan Pei, Yingya Zhang, Deli Zhao, Shaojie Shen, and Qifeng Chen. The devil is in the wrongly-classified samples: Towards unified open-set recognition. *arXiv preprint arXiv:2302.04002*, 2023.

Mircea Cimpoi, Subhransu Maji, Iasonas Kokkinos, Sammy Mohamed, and Andrea Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3606–3613, 2014.

Sanjoy Dasgupta and Anupam Gupta. An elementary proof of a theorem of johnson and lindenstrauss. *Random Structures & Algorithms*, 22(1):60–65, 2003.

Nikolaos Dimitriadis, Pascal Frossard, and François Fleuret. Pareto manifold learning: Tackling multiple tasks via ensembles of single-task models. In *International Conference on Machine Learning*, pp. 8015–8052. PMLR, 2023.

Andrija Djurisic, Nebojsa Bozanic, Arjun Ashok, and Rosanne Liu. Extremely simple activation shaping for out-of-distribution detection. In *The Eleventh International Conference on Learning Representations*, 2022.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

Xuefeng Du, Zhaoning Wang, Mu Cai, and Yixuan Li. Vos: Learning what you don't know by virtual outlier synthesis. In *International Conference on Learning Representations*, 2021.

Xuefeng Du, Yiyou Sun, Jerry Zhu, and Yixuan Li. Dream the impossible: Outlier imagination with diffusion models. *Advances in Neural Information Processing Systems*, 36, 2024.

Yonatan Geifman and Ran El-Yaniv. Selective classification for deep neural networks. In *Advances in Neural Information Processing Systems*, pp. 4878–4887, 2017.

Almog Gueta, Elad Venezian, Colin Raffel, Noam Slonim, Yoav Katz, and Leshem Choshen. Knowledge is a region in weight space for fine-tuned language models. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 1350–1370, 2023.

Simon Haykin. *Neural networks: a comprehensive foundation*. Prentice Hall PTR, 1998.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. In *International Conference on Learning Representations*, 2018.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *International Conference on Learning Representations*, 2016.

Dan Hendrycks, Mantas Mazeika, and Thomas Dietterich. Deep anomaly detection with outlier exposure. In *International Conference on Learning Representations*, 2018.

Dan Hendrycks, Kimin Lee, and Mantas Mazeika. Using pre-training can improve model robustness and uncertainty. In *International conference on machine learning*, pp. 2712–2721. PMLR, 2019a.

Dan Hendrycks, Norman Mu, Ekin Dogus Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. Augmix: A simple data processing method to improve robustness and uncertainty. In *International Conference on Learning Representations*, 2019b.

Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, et al. The many faces of robustness: A critical analysis of out-of-distribution generalization. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 8340–8349, 2021.

Dan Hendrycks, Steven Basart, Mantas Mazeika, Andy Zou, Joe Kwon, Mohammadreza Mostajabi, Jacob Steinhardt, and Dawn Song. Scaling out-of-distribution detection for real-world settings. In *International Conference on Machine Learning*, 2022.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Edward J Hu, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2021.

Rui Huang, Andrew Geng, and Yixuan Li. On the importance of gradients for detecting distributional shifts in the wild. *Advances in Neural Information Processing Systems*, 34:677–689, 2021.

Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Wortsman, Ludwig Schmidt, Hannaneh Hajishirzi, and Ali Farhadi. Editing models with task arithmetic. In *The Eleventh International Conference on Learning Representations*, 2022.

Paul F Jaeger, Carsten Tim Lüth, Lukas Klein, and Till J Bungert. A call to reflect on evaluation practices for failure detection in image classification. In *The Eleventh International Conference on Learning Representations*, 2022.

Julian Katz-Samuels, Julia B Nakhleh, Robert Nowak, and Yixuan Li. Training ood detectors in their natural habitats. In *International Conference on Machine Learning*, pp. 10848–10865. PMLR, 2022.

Alex Kendall, Yarin Gal, and Roberto Cipolla. Multi-task learning using uncertainty to weigh losses for scene geometry and semantics. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7482–7491, 2018.

Jang-Hyun Kim, Sangdoo Yun, and Hyun Oh Song. Neural relation graph: A unified framework for identifying label noise and outlier data. *Advances in Neural Information Processing Systems*, 2023a.

Jihyo Kim, Jiin Koo, and Sangheum Hwang. A unified benchmark for the unknown detection capability of deep neural networks. *Expert Systems with Applications*, 229:120461, 2023b.

Yuting Li, Yingyi Chen, Xuanlong Yu, Dexiong Chen, and Xi Shen. Sure: Survey recipes for building reliable and robust deep networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 17500–17510, 2024.

Shiyu Liang, Yixuan Li, and R Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *International Conference on Learning Representations*, 2018.

Jiashuo Liu, Zheyan Shen, Yue He, Xingxuan Zhang, Renzhe Xu, Han Yu, and Peng Cui. Towards out-of-distribution generalization: A survey. *arXiv preprint arXiv:2108.13624*, 2021.

Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. *Advances in neural information processing systems*, 33:21464–21475, 2020.

Xixi Liu, Yaroslava Lochman, and Christopher Zach. Gen: Pushing the limits of softmax-based out-of-distribution detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 23946–23955, 2023.

Yifei Ming, Ying Fan, and Yixuan Li. Poem: Out-of-distribution detection with posterior sampling. In *International Conference on Machine Learning*, pp. 15650–15665. PMLR, 2022.

Jooyoung Moon, Jihyo Kim, Younghak Shin, and Sangheum Hwang. Confidence-aware learning for deep neural networks. In *international conference on machine learning*, pp. 7034–7044. PMLR, 2020.

Harikrishna Narasimhan, Aditya Krishna Menon, Wittawat Jitkrittum, and Sanjiv Kumar. Plugin estimators for selective classification with out-of-distribution detection. In *The Twelfth International Conference on Learning Representations*, 2024.

Yuval Netzer, Tao Wang, Adam Coates, A. Bissacco, Bo Wu, and A. Ng. Reading digits in natural images with unsupervised feature learning. 2011.

Anh Nguyen, Jason Yosinski, and Jeff Clune. Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 427–436, 2015.

Jaewoo Park, Yoon Gyo Jung, and Andrew Beng Jin Teoh. Nearest neighbor guidance for out-of-distribution detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1686–1695, 2023.

Francesco Pinto, Harry Yang, Ser-Nam Lim, Philip Torr, and Puneet K. Dokania. Regmixup: Mixup as a regularizer can surprisingly improve accuracy and out distribution robustness. In *Advances in Neural Information Processing Systems*, 2022.

Evgenia Rusak, Lukas Schott, Roland S Zimmermann, Julian Bitterwolf, Oliver Bringmann, Matthias Bethge, and Wieland Brendel. A simple way to make neural networks robust against diverse image corruptions. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part III 16*, pp. 53–69. Springer, 2020.

Christos Sakaridis, Dengxin Dai, and Luc Van Gool. Acdc: The adverse conditions dataset with correspondences for semantic driving scene understanding. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 10765–10775, 2021.

Steffen Schneider, Evgenia Rusak, Luisa Eck, Oliver Bringmann, Wieland Brendel, and Matthias Bethge. Improving robustness against common corruptions by covariate shift adaptation. *Advances in neural information processing systems*, 33:11539–11551, 2020.

Yuge Shi, Jeffrey Seely, Philip Torr, N Siddharth, Awni Hannun, Nicolas Usunier, and Gabriel Synnaeve. Gradient matching for domain generalization. In *International Conference on Learning Representations*, 2021.

Yue Song, Nicu Sebe, and Wei Wang. Rankfeat: Rank-1 feature removal for out-of-distribution detection. *Advances in Neural Information Processing Systems*, 35:17885–17898, 2022.

Yiyou Sun and Yixuan Li. Dice: Leveraging sparsification for out-of-distribution detection. In *European Conference on Computer Vision*, pp. 691–708. Springer, 2022.

Yiyou Sun, Chuan Guo, and Yixuan Li. React: Out-of-distribution detection with rectified activations. *Advances in Neural Information Processing Systems*, 34:144–157, 2021.

Yiyou Sun, Yifei Ming, Xiaojin Zhu, and Yixuan Li. Out-of-distribution detection with deep nearest neighbors. In *International Conference on Machine Learning*, pp. 20827–20840. PMLR, 2022.

Hidenori Tanaka, Daniel Kunin, Daniel L Yamins, and Surya Ganguli. Pruning neural networks without any data by iteratively conserving synaptic flow. *Advances in neural information processing systems*, 33:6377–6389, 2020.

Jindong Wang, Cuiling Lan, Chang Liu, Yidong Ouyang, Tao Qin, Wang Lu, Yiqiang Chen, Wenjun Zeng, and S Yu Philip. Generalizing to unseen domains: A survey on domain generalization. *IEEE transactions on knowledge and data engineering*, 35(8):8052–8072, 2022.

Hongxin Wei, Renchunzi Xie, Hao Cheng, Lei Feng, Bo An, and Yixuan Li. Mitigating neural network overconfidence with logit normalization. In *International conference on machine learning*, pp. 23631–23644. PMLR, 2022.

Guoxuan Xia and Christos-Savvas Bouganis. Augmenting the softmax with additional confidence scores for improved selective classification with out-of-distribution data. *International Journal of Computer Vision*, pp. 1–39, 2024.

Pingmei Xu, Krista A Ehinger, Yinda Zhang, Adam Finkelstein, Sanjeev R Kulkarni, and Jianxiong Xiao. Turkergaze: Crowdsourcing saliency with webcam based eye tracking. *arXiv preprint arXiv:1504.06755*, 2015.

Jingkang Yang, Kaiyang Zhou, Yixuan Li, and Ziwei Liu. Generalized out-of-distribution detection: A survey. *arXiv preprint arXiv:2110.11334*, 2021.

Huaxiu Yao, Yu Wang, Sai Li, Linjun Zhang, Weixin Liang, James Zou, and Chelsea Finn. Improving out-of-distribution robustness via selective augmentation. In *International Conference on Machine Learning*, pp. 25407–25437. PMLR, 2022.

Mingyang Yi, Lu Hou, Jiacheng Sun, Lifeng Shang, Xin Jiang, Qun Liu, and Zhiming Ma. Improved ood generalization via adversarial training and pretraing. In *International Conference on Machine Learning*, pp. 11987–11997. PMLR, 2021.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

Jingyang Zhang, Nathan Inkawhich, Randolph Linderman, Yiran Chen, and Hai Li. Mixture outlier exposure: Towards out-of-distribution detection in fine-grained environments. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 5531–5540, 2023a.

Jingyang Zhang, Jingkang Yang, Pengyun Wang, Haoqi Wang, Yueqian Lin, Haoran Zhang, Yiyou Sun, Xuefeng Du, Kaiyang Zhou, Wayne Zhang, et al. Openood v1. 5: Enhanced benchmark for out-of-distribution detection. *arXiv preprint arXiv:2306.09301*, 2023b.

Haotian Zheng, Qizhou Wang, Zhen Fang, Xiaobo Xia, Feng Liu, Tongliang Liu, and Bo Han. Out-of-distribution detection learning with unreliable out-of-distribution sources. *Advances in Neural Information Processing Systems*, 36, 2024.

Bolei Zhou, Àgata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(6):1452–1464, 2018.

Fei Zhu, Zhen Cheng, Xu-Yao Zhang, and Cheng-Lin Liu. Openmix: Exploring outlier samples for misclassification detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12074–12083, 2023a.

Fei Zhu, Xu-Yao Zhang, Zhen Cheng, and Cheng-Lin Liu. Revisiting confidence estimation: Towards reliable failure prediction. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2023b.

Fei Zhu, Zhen Cheng, Xu-Yao Zhang, Cheng-Lin Liu, and Zhaoxiang Zhang. Rcl: Reliable continual learning for unified failure detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12140–12150, 2024a.

Jianing Zhu, Yu Geng, Jiangchao Yao, Tongliang Liu, Gang Niu, Masashi Sugiyama, and Bo Han. Diversified outlier exposure for out-of-distribution detection via informative extrapolation. *Advances in Neural Information Processing Systems*, 36, 2024b.

A   RELATED WORK

Covariate OOD generalization. To improve the generalization, some methods assume that a set of covariate-shifted samples are available at training time (Yao et al., 2022; Wang et al., 2022; Shi et al., 2021; Bai et al., 2023), others aim to learn domain-invariant representations that generalize better under covariate shifts (Rusak et al., 2020; Hendrycks et al., 2019b;a). Recently, Bai et al., (Bai et al., 2023) leveraged unlabeled wild data consisting of covariate and semantic shifts to build a model to recognize covariate-shifted data while rejecting semantic-shifted data. However, there is no rejection option in covariate shits generalization, and users would accept the widely existing misclassification blindly. Contrary to the above prior works, in this work, we aim to reject misclassified covariate-shifted samples reliably.

Semantic OOD detection. Current OOD detection methods have been proposed under the setting of post hoc or training regularization, aiming to reject samples from unseen classes. Some post hoc methods (Hendrycks & Gimpel, 2016; Liu et al., 2020; Liang et al., 2018; Basart et al., 2022; Huang et al., 2021; Sun et al., 2022; Hendrycks et al., 2022; Park et al., 2023; Kim et al., 2023a; Liu et al., 2023) focus on designing proper confidence scores, which others (Sun et al., 2021; Sun & Li, 2022; Djurisic et al., 2022; Song et al., 2022; Djurisic et al., 2022) remove undesirable parts of feature or activation to facilitate the separation of ID and OOD examples. Training regularization approaches (Hendrycks et al., 2018; Du et al., 2024; Ming et al., 2022; Zheng et al., 2024; Du et al., 2021; Zhu et al., 2024b; Zhang et al., 2023a; Katz-Samuels et al., 2022) often require real or synthesized auxiliary dataset with extra training processes. Nevertheless, current OOD detection methods could harm the performance of detecting misclassified examples from known classes. This work aims to develop unified and flexible framework to detect different kinds of failures.

Recently, there are a few studies (Zhu et al., 2024a; Cen et al., 2023; Zhu et al., 2023a; Li et al., 2024) focused on developing reliable models that can reject both misclassified ID and semantic-shifted OOD data. For example, Zhu et al. (2023a; 2024a) observed that existing popular OOD detection methods are harmful for misclassification detection on clean ID test data, and proposed unified failure detection methods by exploring outlier data (Zhu et al., 2023a) or reliable continual learning paradigm (Zhu et al., 2024a). Cen et al. (2023) found that the uncertainty distribution of wrongly classified samples is extremely close to semantic-shifted samples rather than known and correctly classified samples, and proposed FS-KNN, which is an improvement of the KNN score. Li et al. (2024) proposed a method named SURE for reliable prediction by combining multiple techniques, across model regularization, classifier and optimization. Nevertheless, they typically overlook covariate-shifted samples, and it is hard to distinguish correct covariate-shifted samples from semantic-shifted ones. Besides, they often train a model from scratch or fully fine-tune it, which is computationally heavy and inefficient.

B   THEORETICAL ANALYSIS

B.1   PROOF OF PROPOSITION 3.1

Proposition: Given a compact $\mathcal{X} \subseteq \mathbb{R}^D$ and a family of continuous mappings $f_n : \mathcal{X} \to \mathbb{R}^{D'}$, $n = 1, \dots, N$, there exists a ReLU multi-layer perceptron f with base parameters θ_{pre} and two low-rank vectors $\tau_{\text{LoRA,cov}}$ and $\tau_{\text{LoRA,sem}}$, such that for any $\epsilon > 0$ and all n, there exists an $\alpha \in [0,1]$ satisfying

$$\|f_n(\boldsymbol{x}) - f(\boldsymbol{x}; \theta_{\text{pre}} + (1-\alpha) \cdot \tau_{\text{LoRA,cov}} + \alpha \cdot \tau_{\text{LoRA,sem}})\| \leq \epsilon, \quad \forall \boldsymbol{x} \in \mathcal{X}.$$

Proof: The proof is based on (Dimitriadis et al., 2023). Formally, denote σ the ReLU non-linearity $\sigma(x) = \max(0, x)$. From the universal approximation theorem (Haykin, 1998), for any $\epsilon > 0$, there exists $Q \in \mathbb{N}$, $M \in \mathbb{R}^{(D+2) \times Q}$, $C \in \mathbb{R}^Q$, $M' \in \mathbb{R}^{Q \times D'}$ such that:

$$\forall \boldsymbol{x} \in \mathcal{X}, \forall n \in \{1, \dots, N\}, \quad \|f_n(\boldsymbol{x}) - g(\boldsymbol{x}, \alpha)\| \leq \epsilon,$$

where $g(\boldsymbol{x}, \alpha) = M' \sigma(M(\boldsymbol{x}, \alpha) + C)$.

Define two matrices $R \in \mathbb{R}^{D \times (2D+2)}$ and $S \in \mathbb{R}^{(2D+2) \times D}$ as follows:

$$R_{i,j} = \begin{cases} 1, & \text{if } j = 2i-1, \\ -1, & \text{if } j = 2i, \\ 0, & \text{otherwise,} \end{cases} \quad \text{and} \quad S_{i,j} = \begin{cases} 1, & \text{if } i = 2j-1 \text{ or } (i > 2u \text{ and } j = u), \\ -1, & \text{if } i = 2j, \\ 0, & \text{otherwise.} \end{cases}$$

Let $W_k = (0, \ldots, 0, k), k = 1, 2$. Then, with $\boldsymbol{x} \in \mathbb{R}^D$, we have:

$$\forall \alpha \geq 0, \quad S^\top \sigma(R^\top \boldsymbol{x} + (1 - \alpha)W_1 + \alpha W_2) = (\boldsymbol{x}, \alpha).$$

We can learn a ReLU multi-layer perceptron $f(\boldsymbol{x}, M, C, M', R, S, W) = M'\sigma(MS^\top \sigma(R^\top \boldsymbol{x} + W) + C)$. Then with $\theta_{\text{pre}} = (M, C, M', R, S, 0)$ and $\theta_i = (0, 0, 0, 0, 0, W_i)$ for $i = 1, 2$, we have:

$$\begin{aligned}
f(\boldsymbol{x}; \theta_{\text{pre}} + (1 - \alpha) \cdot \theta_1 + \alpha \cdot \theta_2) &= f(\boldsymbol{x}; M, C, M', R, S, (1 - \alpha)W_1 + \alpha W_2) \\
&= M'\sigma(MS^\top \sigma(R^\top \boldsymbol{x} + (1 - \alpha)W_1 + \alpha W_2) + C) \\
&= g(S^\top (R^\top \boldsymbol{x} + (1 - \alpha)W_1 + \alpha W_2)) \\
&= g(\boldsymbol{x}, \alpha).
\end{aligned}$$

Note that $\theta_i, i = 1, 2$ can be reshaped into a matrix $B_i A_i$, and in this paper we define them as $\theta_1 = \tau_{\text{LoRA,cov}}$ and $\theta_2 = \tau_{\text{LoRA,sem}}$, respectively.

C EXPERIMENTS

C.1 EXPERIMENTAL SETUP DETAILS

For pre-trained model, we train the ResNet-18 model with SGD optimizer, a momentum of 0.9, an initial learning rate of 0.1, a weight decay of 5e-4 and mini-batch size of 128. The number of training epoch is 200, and the learning rate is reduced by a factor of 10 at 100, and 150 epochs.

Training configures for Augmix: For augmentation, we use the official AugMix code and follow the setup on the original AugMix paper to randomly sample k augmentation chains, where $k = 3$ by default. The sample mixing weights $(w1, w2, ..., wk) \sim \text{Dirichlet}(\alpha, \alpha, ..., \alpha)$, where $\alpha = 1$ by default. The λ is set to be 12 following the official code of AugMix at line 234 in the above address. We then train the ResNet-18 model with SGD optimizer, a momentum of 0.9, an initial learning rate of 0.1, a weight decay of 5e-4, and a mini-batch size of 128. The number of training epochs is 200, and the learning rate is reduced by a factor of 10 at 100, and 150 epochs.

Training configures for TrustLoRA: For AugMixLoRA fine-tuning, we set the rank of the LoRA as 4 and use a cosine learning rate with an initial learning rate of 0.001 and a total 10 epochs. The augmentation configures are the same as that of AugMix described above.

For experiments on ViT, we use the pre-trained ViT-B16, which is fine-tuned for 10 epochs using cosine learning rate with the initial learning rate of 0.03. We set the momentum to be 0.9 and the weight decay to 0. For compared methods, the main hyper-parameters come from their original papers. For KNN, we set k to 50. For NNGuide, we set k to 100. For GEN, the parameters (γ, M) in calculating generalized entropy score are set to (0.1, 100). We run each trial 3 times and report the average performance.

For evaluation metric, the AURC, FPR95 and AUC are widely used in prior works. We further define the F-AUC as follow: $\text{F} - \text{AUC} = (2 \times \text{AUC}_{\text{cov}} \times \text{AUC}_{\text{sem}})/(\text{AUC}_{\text{cov}} + \text{AUC}_{\text{sem}})$, where AUC_{cov} denotes the AUC value of separating correct and incorrect covariate-shifted data and AUC_{cov} denotes the AUC value of separating covariate-shifted and semantic-shifted data.

C.2 ADDITIONAL RESULTS

Unknown rejection performance can be well maintained. In Table 9, we show that the unknown rejection ability under covariate and semantic shits can be well maintained after further integrating the third LoRA, which demonstrates the flexibility and effectiveness of the proposed TrustLoRA framework.

Results on less overparameterised model. We conduct experiments on ResNet-20 (which is much small than ResNet-18) for CIFAR-10/100 and the fine-grained results are shown in Table 10. As can be seen, the proposed TrustLoRA successfully enhances the misclassification detection, OOD detection, and unknown rejection ability of the base model (0.287M) by only tuning a very small number (0.0275M) of parameters in LoRAs. Those results verify that our method can capture the benefit of AugMix/OE when models are less overparameterised.

Table 9: Unknown rejection ability under covariate and semantic shits can be well maintained.

Method	Severity-1				Severity-2				Severity-3			
	AURC	FPR95	AUC	F-AUC	AURC	FPR95	AUC	F-AUC	AURC	FPR95	AUC	F-AUC
TrustLoRA (LoRA-2)	129.64	46.46	87.29	83.73	149.14	50.12	85.77	81.40	172.35	53.32	84.41	79.28
TrustLoRA (LoRA-3)	128.14	46.65	86.33	81.68	140.64	49.45	85.29	80.00	155.53	52.04	84.25	78.29

Table 10: Results on less overparameterised model.

Method	MD-AURC	MD-FPR	MD-AUC	OOD-FPR	OOD-AUC	UR-AURC	UR-FPR	UR-AUC	F-AUC
Baseline (C10)	57.28	41.60	86.93	48.24	81.47	85.80	40.92	87.05	84.11
w/ TrustLoRA	**41.89**	**38.46**	**87.99**	**41.92**	**84.64**	**69.78**	**36.79**	**88.81**	**86.28**
Baseline (C100)	210.34	54.94	81.61	84.31	62.14	222.40	67.65	78.30	70.56
w/ TrustLoRA	**165.16**	**51.72**	**83.14**	**78.52**	**67.43**	**188.41**	**62.10**	**81.08**	**74.46**

Table 11: Comparison with more baselines and multi-task learning on CIFAR-100, severity-1.

Method	Severity-1				Severity-2			
	AURC	FPR95	AUC	F-AUC	**AURC**	FPR95	AUC	F-AUC
SIRC* (MSP,z1)	160.26	52.17	83.75	76.65	214.24	60.07	80.22	71.85
FlatLoRA	152.94	51.97	84.40	78.74	201.94	58.51	81.43	74.46
SIRC (AugMixLoRA)	139.86	50.53	85.50	80.04	156.63	54.03	83.86	78.25
AugMix (Full FT)	133.68	49.79	85.05	80.48	146.83	52.47	83.92	78.66
AugMix+OE (Full FT)	138.92	50.26	85.40	81.44	142.66	50.66	84.52	80.12
TrustLoRA	**129.64**	**46.46**	**87.29**	**83.73**	**149.14**	**50.12**	**85.77**	**81.4**

More results in comparison with more baselines and multi-task learning. Table 11 provides more results of comparison with SIRC, FlatLoRA and multi-task learning (i.e., AugMix+OE (Full FT)).

Detailed individual unknown rejection performance. Table 13 provides the fine-grained results for misclassification detection on covariate shifts, OOD detection on semantic shifts and the unified unknown rejection results on C10/100 with severity-1. We observe that our method achieves the best unknown rejection performance. Besides, it is worth mentioning that our formulation is different from existing works that

Figure 8: Risk-coverage curves on the mixture of ID, covariate and semantic shifts.

evaluate OOD generalization via accuracy and OOD detection via rejection metrics like FPR95, and AUC. We use the ARUC metric to reflect the classification with rejection ability on covariate shifts, which has integrated the classification and rejection performance. We also added the accuracy performance in Table 13, including methods that train the model from scratch (*) and others that fine-tune the model with LoRA. All post hoc methods have the same accuracy as AugMixLoRA, since they are applied to the model trained with AugMixLoRA.

Risk-coverage curves. Fig. 8 provides the comparison of the risk-coverage curves when testing on the mixture of covariate shifts (Frost with Severity-1) and semantic shifts (Textures) on CIFAR10 and CIFAR-100 datasets. Ours achieves the smallest risk given a specific coverage value.

Table 12: Random projection based LoRA *v.s.* the original LoRA on CIFAR-10/100, severity-1.

Method	CIFAR-10				CIFAR-100			
	AURC	FPR95	AUC	F-AUC	AURC	FPR95	AUC	F-AUC
B only	28.68	23.80	93.67	92.53	129.64	46.46	87.29	83.73
A & B	28.07	24.12	93.82	92.95	127.51	45.72	87.17	83.34

Table 13: Individual performance on the misclassification detection under covariate shifts, OOD detection under semantic shifts, and the unified unknown rejection on CIFAR-10/100 with severity-1.

Method	ACC	MD-AURC	MD-FPR	MD-AUC	OOD-FPR	OOD-AUC	UR-AURC	UR-FPR	UR-AUC	F-AUC
					CIFAR-10					
CE*	87.86	35.33	42.33	88.61	39.96	86.24	56.04	37.53	89.49	87.41
RegMixUp*	89.27	34.01	55.70	87.65	50.18	86.08	57.05	50.60	88.56	86.86
CRL*	87.68	29.63	32.91	90.00	38.08	86.31	50.25	32.06	90.35	88.12
LogitNorm*	87.46	36.45	40.19	87.57	20.77	94.46	48.15	32.56	91.92	90.88
OE*	87.13	36.04	39.31	88.78	27.34	92.02	51.24	33.30	91.73	90.37
RegMixUp (LoRA)	88.48	36.62	55.64	87.52	54.89	84.74	62.17	53.63	87.97	86.11
CRL (LoRA)	88.14	35.04	43.20	88.40	41.03	86.36	56.28	38.40	89.36	87.37
LogitNorm (LoRA)	86.87	37.83	38.33	88.76	40.97	85.74	59.05	36.71	89.41	87.22
AugMix (LoRA)	90.53	18.05	33.51	90.47	41.92	87.88	36.62	36.09	90.72	89.16
OE (LoRA)	87.38	32.67	33.82	89.89	15.47	96.06	43.63	26.01	93.51	92.47
Energy (AugMixLoRA)	90.53	26.77	59.77	84.16	39.36	89.69	43.50	49.19	88.03	86.84
TrustLoRA	90.77	16.27	28.98	91.40	22.41	93.68	**28.68**	**23.80**	**93.67**	**92.53**
					CIFAR-100					
CE*	66.08	134.63	49.00	84.74	70.45	69.44	163.66	54.88	82.95	76.33
RegMixUp*	68.64	115.84	48.72	85.10	69.27	69.84	154.87	54.34	83.12	76.72
CRL*	67.91	125.45	44.88	85.79	70.21	70.96	152.20	53.03	83.94	77.67
LogitNorm*	65.13	145.75	54.49	83.31	66.90	72.00	166.34	56.51	82.91	77.24
OE*	62.16	163.93	51.93	83.08	47.64	84.68	149.02	45.48	87.69	83.87
RegMixUp (LoRA)	67.53	126.07	50.51	84.54	66.98	72.39	155.58	53.51	83.81	77.99
CRL (LoRA)	67.44	115.43	48.90	84.85	66.20	73.16	153.48	52.10	84.27	78.57
LogitNorm (LoRA)	67.15	127.64	49.10	84.77	66.91	72.88	155.08	52.55	84.14	78.38
AugMix (LoRA)	70.48	102.55	49.80	84.52	63.66	75.39	141.23	51.24	84.69	79.69
OE (LoRA)	63.96	147.07	51.66	83.69	51.71	82.41	147.40	46.57	87.21	83.04
Energy (AugMixLoRA)	70.48	124.68	64.17	79.67	63.98	75.59	158.37	60.62	81.52	77.58
TrustLoRA	70.25	107.13	51.30	83.95	51.05	83.51	**129.64**	**46.46**	**87.29**	**83.73**

Compare the random projection based LoRA with the original LoRA. In our method, we propose LoRA with random projection, where only the **B** matrix of LoRA is trained. In Table 12, we show that random projection based LoRA achieves similar with that training both **A** and **B**, while needing less computation and memory cost.

Rank of the LoRA. A higher rank r in LoRA means a greater number of trainable parameters and might lead to overfitting, while a lower rank r means fewer trainable parameters and might lead to underfitting. When fine-tuning a pretrained model, if the dataset is significantly different and more complex, then it's would be better to use a high rank value (e.g., 64–256). On the other hand, if there doesn't involve a complex new dataset that the model hasn't encountered before, lower values of rank (e.g., 4–12) are sufficient. We conduct experiments under different settings of rank in LoRA (Severity-1). As shown in Table 14, our method is robust to the different ranks of LoRA, and we simply set $r = 4$ (which is a common choice for LoRA tuning) for all experiments in our main paper. In our case, we aim to teach the model learn reliability knowledge about the current task, without introducing a complex new dataset. Therefore, low value of rank like 4 or 2 is sufficient to learn the additional reliability knowledge without underfitting.

TrustLoRA approximates a family of mappings. One of the primary advantages of our method is to control the strength of each kind of reliability flexibly based on end-user preference. In Fig. 9, we

Table 14: Performance of TrustLoRA with different rank r on CIFAR-10/100, severity-1.

Method	CIFAR-10				CIFAR-100			
	AURC	FPR95	AUC	F-AUC	**AURC**	FPR95	AUC	F-AUC
$r = 2$	29.31	24.92	93.32	92.24	131.06	47.17	87.11	83.38
$r = 4$	28.68	23.80	93.67	92.53	129.64	46.46	87.29	83.73
$r = 8$	28.45	23.11	93.60	92.72	128.15	46.03	87.40	83.82

show that the scaling α in Eq. (7) can easily control the preference between MisD under covariate shits and OOD detection. Specifically, when increasing the α, the OOD detection ability can be remarkably enhanced, and the Cov-MisD is increased at the beginning, and then decreased. Therefore, we can conclude that the proposed TrustLoRA can approximate a family of mappings with the simple linear combination of LoRA weights regarding different kinds of reliability knowledge flexibly.

D BROADER IMPACTS

Reliable prediction is an essential requirement for safe AI. The method proposed in this work would help the model detect unreliable prediction under both covariate and semantic shifts. Our work could contribute to the understanding of failure prediction in the wild. We are not aware of any negative social impact, and we believe the ethical aspects are not applicable.

Figure 9: Cov-MisD and OOD detection performance with different addition weight.

Limitations and Future Work. Since our method is built on OE (Hendrycks et al., 2018), auxiliary outlier data is need. We have shown that TrustLoRA is robust to different auxiliary outlier data. Future work will consider developing outlier-free methods within the proposed framework. Besides, this paper only considers discriminative classifier in classification scenarios. Future work will explore unknown rejection in generative models, e.g., large language model and diffusion model, and more complex tasks such as Object detection and segmentation.