Learning Physical Dynamics with Subequivariant Graph Neural Networks

Abstract

Graph Neural Networks (GNNs) have become a prevailing tool for learning physical dynamics. However, they still encounter several challenges: 1) Physical laws abide by symmetry, which is a vital inductive bias accounting for model generalization and should be incorporated into the model design. Existing simulators either consider insufficient symmetry, or enforce excessive equivariance in practice when symmetry is partially broken by gravity. 2) Objects in the physical world possess diverse shapes, sizes, and properties, which should be appropriately processed by the model. To tackle these difficulties, we propose a novel backbone, called *Subequivariant Graph Neural Network*, which 1) relaxes equivariance to subequivariance by considering external fields like gravity, where the universal approximation ability holds theoretically; 2) introduces a new subequivariant object-aware message passing for learning physical interactions between multiple objects of various shapes in the particle-based representation; 3) operates in a hierarchical fashion, allowing for modeling long-range and complex interactions. Our model achieves on average over 3% enhancement in contact prediction accuracy across 8 scenarios on Physion and $2\times$ lower rollout MSE on RigidFall compared with state-of-the-art GNN simulators, while exhibiting strong generalization and data efficiency.

1 Introduction

Learning and predicting the complicated physical dynamics and interactions between objects are vital to many tasks including physical reasoning [7, 17], scene understanding [3], and model-based planning and control [18, 21, 32, 1]. Several learning-based differentiable simulators [27, 26, 20, 23] have been proposed, and they obtain promising achievements in simulating various kinds of interacting objects including rigid and fluids. The success mainly relies on the prevalence of graph neural networks [11, 26, 12], which are desirable tools for physical simulation, by modeling particles as nodes, physical relations as edges, and their interactions as the message passing thereon.

Notably, physical world exhibits certain symmetries. For example, the way dominoes fall from left to right will exactly be preserved when the system is rotated horizontally to another direction. Inherently, humans reason about the dynamics with the preservation of such symmetry, and this inductive bias has been endorsed by the physical laws that also abide by the symmetries in our 3D world. Yet, regardless of this inductive bias, current differentiable simulators like GNS [26] and DPI [20] would fail to learn the real dynamics that can generalize to all directions. In the example of dominoes, if the data in training are positioned from left to right, GNS can predict well during testing when the dominoes also fall in the same direction, but performs poorly if the scene is rotated horizontally (see demo in the Supplementary Video). This observation implies that GNS overfits training samples without learning the true dynamics that obey the symmetry, limiting its generalization.

With this consideration, there have been a number of works, named geometrically equivariant graph neural networks [13], that leverage symmetry as an inductive bias in learning to simulate. These models are designed such that their outputs will rotate/translate/reflect in the same way as the inputs, hence retaining the symmetry. However, the works like EGNN [28] and GMN [14] are exerted the full symmetry of the 3D Euclidean space, or so called E(3)-equivariance. Such equivariance constraint is so strong that it penalizes all directions in the 3D space, which cannot be applied to scenarios with external fields, like gravity. The existence of gravity breaks the symmetry in the vertical direction, reducing E(3) to its subgroup. We formally characterize this phenomenon of equivariance relaxation as *subequivariance*.

Another weakness of current GNN-based methods is that, from a practical point of view, they seldom explicitly involve the object information (shapes, sizes, etc) into message passing. When modeling multiple interacting objects of different shapes, the interactions between or within objects are usually different. For example, the former aims to exchange momentum or energy across objects, while the latter usually accounts for maintaining the geometrical constraint. It is thus important to involve objectness to distinguish interactions between particles within objects from those across objects.

In this work, we propose Subequivariant Graph Neural Networks (SGNN) that consist of several features to tackle the above challenges. **1.** We relax equivariance to subequivariance and design subequivariant functions to physical scenarios with the existence of gravity, and excitingly, we have proved that our designed form inherits the approximation universality. **2.** We formulate a novel subequivariant object-aware message passing framework for modeling dynamics and interactions between objects of varying shapes. **3.** We incorporate the subequivariant message passing into a hierarchical model to deal with long-range and complicated object interactions. We demonstrate the efficacy of our SGNN for learning physical dynamics on a large-scale challenging dataset Physion with 8 different scenarios, and a 3-object RigidFall dataset. Experimental results show that our model is capable of yielding more accurate dynamics prediction, is highly data-efficient, and has strong generalization compared with the state-of-the-art learning-based differentiable physical simulators.

2 Related Work

GNN-based physical dynamics simulators. There have been many works that employ graph neural networks as physical simulators of dynamical systems. Interaction Network (IN) [2] is the pioneer in modeling the dynamics of evolving systems represented by objects and particles. [22] introduces a hierarchical representation of objects to efficiently perform message passing on different objects. NRI [16] leverages variational auto-encoders to infer the latent relationship between objects from the evolution of the system. Graph Network Simulator (GNS) proposed by [26] has been showcased a simple yet powerful tool in simulating large systems in particle-based representation of rigids and fluids by dynamically constructing interaction graph and performing multiple steps of information propagation. DPI [20] adds one-level of hierarchy to the rigids and predicts the rigid transformation via generalized coordinates, with applications to manipulation and control. There are also several works that incorporate physical priors like Hamiltonian mechanics [25, 33], geometrical constraints [24] and shapes [23]. Despite the promising empirical results, these works have not given sufficient considerations on the important inductive bias of symmetry, which is crucial for a simulator to generalize to unseen testing data.

Geometrically equivariant graph neural networks. Equivariant graph neural networks [13] are a family of GNNs that are specifically designed to meet the constraint of certain symmetry, mostly involving translations, rotations, and/or reflections in Euclidean space. This goal is approached by several measures, including solving group convolution with irreducible representation [29, 10], lifting and sampling via Lie algebra [8, 15], or leveraging invariant scalarization [30] like taking the inner product [28, 14]. Our approach also belongs to the scalarization family together with EGNN [28] and GMN [14]. Specifically, EGNN models the interaction with the invariant distance as input, computed as an inner product of the relative positions, and GMN generalizes to a multi-channel version by taking into consideration a stack of multiple vectors. These equivariant GNNs operate on particle graphs or point clouds, while we additionally consider a combination of both particle- and object-level information. More importantly, they are assumed a full Euclidean symmetry with strong equivariance constraint, while we elaborate how to relax the constraint in the existence of external fields like gravity by leveraging subequivariance. Besides, [31] and [6] aim to develop equivariant models given any E(3)/E(2) and their subgroups, while our focus here mainly lies in how the external

 force field relaxes the equivariance from an E(3)-equivariant model. Moreoever, they are steerable
CNNs and not explored on GNNs especially challenging tasks like physical dynamics prediction.

3 Subequivariant Graph Neural Networks

3.1 Background

GNN-based simulators. We start by introducing the mechanism of GNN-based simulators for learning physical dynamics. We consider the particle-based representation of a physical system with N particles consisting of M objects. At time t, each particle within the system possesses some state information, including **1.** the position $\vec{\boldsymbol{x}}_i^{(t)} \in \mathbb{R}^3$ and the velocity $\vec{\boldsymbol{v}}_i^{(t)} \in \mathbb{R}^3$, which are both directional vectors; **2.** some attributes $\boldsymbol{h}_i \in \mathbb{R}^n$ without geometric context, such as the rigidness; **3.** the dynamic spatial connections with other particles, where an edge will be constructed if the distance between two particles is smaller than a threshold r, namely, $\mathcal{E}^{(t)} = \{(i,j) : \|\vec{\boldsymbol{x}}_i^{(t)} - \vec{\boldsymbol{x}}_j^{(t)}\|_2 < r\}$. We denote the object category of particle i as $o(i) \in \mathbb{Z}$ satisfying $o(i) = k$ if particle i belongs to object k. The goal here is to predict the position of the next step $\vec{\boldsymbol{x}}_i^{(t+1)}$ given the above system information at time t, which can be favorably modeled by GNNs, *i.e.*, $\vec{\boldsymbol{x}}_i^{(t+1)} = \varphi_{\text{GNN}}\left(\{\vec{\boldsymbol{x}}_i^{(t)}\}, \{\vec{\boldsymbol{v}}_i^{(t)}\}, \{\boldsymbol{h}_i\}, \mathcal{E}^{(t)}\right)$. Since the prediction at different time shares the same model, we will henceforth omit the temporal superscript t for all variables for brevity.

The conventional GNN simulators φ_{GNN} [20, 26, 22] offer a favorable solution by leveraging message-passing on the interaction graph, which computes:

$$\boldsymbol{m}_{ij} = \phi\left(\vec{\boldsymbol{x}}_i, \vec{\boldsymbol{v}}_i, \vec{\boldsymbol{x}}_j, \vec{\boldsymbol{v}}_j, \boldsymbol{h}_i, \boldsymbol{h}_j\right), \tag{1}$$

$$\vec{\boldsymbol{x}}_i', \vec{\boldsymbol{v}}_i', \boldsymbol{h}_i' = \psi\left(\sum_{j \in \mathcal{N}(i)} \boldsymbol{m}_{ij}, \vec{\boldsymbol{x}}_i, \vec{\boldsymbol{v}}_i, \boldsymbol{h}_i\right), \tag{2}$$

where $\mathcal{N}(i) = \{j : (i,j) \in \mathcal{E}\}$ is the neighbors of node i, and ϕ, ψ are the edge message function and node update function, respectively. The prediction is obtained by conducting several iterations of message passing. Nevertheless, such form does not guarantee the desirable symmetry context with common choices of ϕ and ψ, and meanwhile the object information has not been elaborated, leaving room for a more exquisite message passing scheme for learning complex physical dynamics. Recent works such as EGNN [28] and GMN [14] have actually considered E(3)-equivariance in the design of the functions ϕ and ψ to pursue symmetry. However, they are not applicable to the case when symmetry is partially violated by gravity, which motivates our proposal in § 3.2. Prior to introducing our work, we first provide necessary preliminaries related to equivariance.

Equivariance. In this paper, we basically focus on equivariance in terms of E(3) transformations: translation, rotation, and reflection. The formal definition is provided below.

Definition 1 (Equivariance and Invariance). *We call that the function $f : \mathbb{R}^{3 \times m} \times \mathbb{R}^n \to \mathbb{R}^{3 \times m'}$ is E(3)-equivariant, if for any transformation g in E(3), $f(g \cdot \vec{\boldsymbol{Z}}, \boldsymbol{h}) = g \cdot f(\vec{\boldsymbol{Z}}, \boldsymbol{h}), \forall \vec{\boldsymbol{Z}} \in \mathbb{R}^{3 \times m}$, $\forall \boldsymbol{h} \in \mathbb{R}^n$. Similarly, f is invariant if $f(g \cdot \vec{\boldsymbol{Z}}, \boldsymbol{h}) = f(\vec{\boldsymbol{Z}}, \boldsymbol{h}), \forall g \in E(3)$.*

In Definition 1, the group action $\cdot$ is instantiated as $g \cdot \vec{\boldsymbol{Z}} \coloneqq \boldsymbol{O}\vec{\boldsymbol{Z}}$ for the orthogonal transformation (rotation and reflection) where $\boldsymbol{O} \in O(3) \coloneqq \{\boldsymbol{O} \in \mathbb{R}^{3 \times 3} | \boldsymbol{O}^\top \boldsymbol{O} = \boldsymbol{I}\}$, and $g \cdot \vec{\boldsymbol{Z}} \coloneqq \vec{\boldsymbol{Z}} + \boldsymbol{t}$ for translation where $\boldsymbol{t} \in \mathbb{R}^3$. Note that for the input of f, we have added the the right-arrow superscript on $\vec{\boldsymbol{Z}}$ to distinguish it from the scalar $\boldsymbol{h}$ that is unaffected by the transformation, akin to our notations for the position $\vec{\boldsymbol{x}}_i$, velocity $\vec{\boldsymbol{v}}_i$, and attribute $\boldsymbol{h}_i$.

It is non-trivial to derive equivariant function particularly for orthogonal transformations. GMN [14] proposes a multichannel scalarization form, which yields,

$$f(\vec{\boldsymbol{Z}}, \boldsymbol{h}) \coloneqq \vec{\boldsymbol{Z}}\boldsymbol{V}, \quad \text{s.t.} \boldsymbol{V} = \sigma(\vec{\boldsymbol{Z}}^\top \vec{\boldsymbol{Z}}, \boldsymbol{h}), \tag{3}$$

where the inner product $\vec{\boldsymbol{Z}}^\top \vec{\boldsymbol{Z}} \in \mathbb{R}^{m \times m}$ is firstly computed and concatenated with $\boldsymbol{h}$, the resultant invariant term is then transformed by a function (usually a Multi-Layer Perceptron (MLP)) $\sigma : \mathbb{R}^{m \times m + n} \mapsto \mathbb{R}^{m \times m'}$ producing $\boldsymbol{V} \in \mathbb{R}^{m \times m'}$, and the directional output is acquired by taking a matrix multiplication of the basis $\vec{\boldsymbol{Z}}$ with $\boldsymbol{V}$. By joining the analyses in GMN along with [30], we have the universality of the formulation in Eq. (3), which is provided in Appendix.

Figure 1: Comparison between different message passing. We omit the scalars $\boldsymbol{h}_i$ for simplicity.

3.2 Subequivariant Object-aware Message Passing

To simultaneously benefit from symmetry and object-aware information, we develop Subequivariant Object-aware Message Passing (SOMP). It characterizes information aggregation between multi-channel vectors and scalars, while taking into account both the particle and object information. We use $\vec{\boldsymbol{Z}}_i \in \mathbb{R}^{3 \times m}$ to indicate a stack of m multi-channel 3D vectors; particularly, $\vec{\boldsymbol{Z}}_i = [\vec{\boldsymbol{x}}_i, \vec{\boldsymbol{v}}_i], 1 \leq i \leq N$ by involving both the position and velocity. We additionally initialize the object features by pooling its particles: for object k, we have $(\vec{\boldsymbol{C}}_k, \boldsymbol{c}_k) = \frac{1}{|\{i:o(i)=k\}|} \sum_{\{i:o(i)=k\}} (\vec{\boldsymbol{Z}}_i, \boldsymbol{h}_i), 1 \leq k \leq M$. We also introduce a binary operation "$\ominus$" which yields $\vec{\boldsymbol{Z}}_i \ominus \vec{\boldsymbol{Z}}_j = [\vec{\boldsymbol{Z}}_i - \vec{\boldsymbol{Z}}_j, \vec{\boldsymbol{v}}_i, \vec{\boldsymbol{v}}_j]$. This operation not only produces a translation-invariant representation but also enriches the input stack of vectors with more channels. The direction of gravity is set to be along the third axis, namely $\vec{\boldsymbol{g}} = [0; 0; 1]$.

In a high-level overview, we denote our message passing as the function φ that updates each particle given the input states of all particles, objects, and graph connectivity:

$$\{(\vec{\boldsymbol{Z}}_i', \boldsymbol{h}_i')\}_{i=1}^N = \varphi\left(\{(\vec{\boldsymbol{Z}}_i, \boldsymbol{h}_i)\}_{i=1}^N, \{(\vec{\boldsymbol{C}}_k, \boldsymbol{c}_k)\}_{k=1}^M, \mathcal{E}\right). \tag{4}$$

Specifically, φ is unfolded as the following message passing and aggregation computations:

$$\vec{\boldsymbol{Z}}_{ij} = (\vec{\boldsymbol{Z}}_i \ominus \vec{\boldsymbol{C}}_{o(i)}) \| (\vec{\boldsymbol{Z}}_j \ominus \vec{\boldsymbol{C}}_{o(j)}) \| (\vec{\boldsymbol{Z}}_i \ominus \vec{\boldsymbol{Z}}_j), \tag{5}$$

$$\boldsymbol{h}_{ij} = \boldsymbol{h}_i \| \boldsymbol{c}_{o(i)} \| \boldsymbol{h}_j \| \boldsymbol{c}_{o(j)}, \tag{6}$$

$$\vec{\boldsymbol{M}}_{ij}, \boldsymbol{m}_{ij} = \phi_{\vec{\boldsymbol{g}}}\left(\vec{\boldsymbol{Z}}_{ij}, \boldsymbol{h}_{ij}\right), \tag{7}$$

$$(\vec{\boldsymbol{Z}}_i', \boldsymbol{h}_i') = (\vec{\boldsymbol{Z}}_i, \boldsymbol{h}_i) + \psi_{\vec{\boldsymbol{g}}}\left((\textstyle\sum_{j \in \mathcal{N}(i)} \vec{\boldsymbol{M}}_{ij}) \| (\vec{\boldsymbol{Z}}_i \ominus \vec{\boldsymbol{C}}_{o(i)}), (\textstyle\sum_{j \in \mathcal{N}(i)} \boldsymbol{m}_{ij}) \| \boldsymbol{h}_i \| \boldsymbol{c}_{o(i)}\right), \tag{8}$$

where $\|$ is the concatenation along the channel dimension, $\mathcal{N}(i) = \{j : (i, j) \in \mathcal{E}\}$ is the neighbors of node i, and both $\phi_{\vec{\boldsymbol{g}}}$ and $\psi_{\vec{\boldsymbol{g}}}$ are subequivariant and will be defined in detail in Eq. (9). In detail, we first derive the multi-channel vector input $\vec{\boldsymbol{Z}}_{ij}$ for the interaction between particle i and j in Eq. 5 by stacking the three terms along the channel dimension, including the relative information of the particle with respect to its belonged object: $\vec{\boldsymbol{Z}}_i \ominus \vec{\boldsymbol{C}}_{o(i)}$ and $\vec{\boldsymbol{Z}}_i \ominus \vec{\boldsymbol{C}}_{o(i)}$, and the relative information between particles $\vec{\boldsymbol{Z}}_i \ominus \vec{\boldsymbol{Z}}_j$. By this means, we arrive at a translation-invariant representation $\vec{\boldsymbol{Z}}_{ij}$ with rich object-aware geometric information. For the invariant features we simply concatenate them in Eq. 6. Subsequently, in Eq. 7 we feed the interactions $\vec{\boldsymbol{Z}}_{ij}$ and $\boldsymbol{h}_{ij}$ into the subequivariant message function $\phi_{\vec{\boldsymbol{g}}}$, yielding the vector message $\vec{\boldsymbol{M}}_{ij}$ and scalar message $\boldsymbol{m}_{ij}$[1]. Finally, Eq. 8 first performs message aggregation and then updates the states by another subequivariant function $\psi_{\vec{\boldsymbol{g}}}$, obtaining the eventual result. With the updated $\vec{\boldsymbol{Z}}_i'$ and $\boldsymbol{h}_i'$, one can readily obtain the output with equivariance or invariance as desired, which, in our case, implies $\vec{\boldsymbol{Z}}_i' = [\vec{\boldsymbol{x}}_i']$ by setting $m' = 1$.

Comparison with existing GNN-based simulators. The core of satisfying equivariance lies in taking the invariant inner product before feeding the vectors into the MLP. Such design shares a similar spirit in nature with existing works including EGNN [28] and GMN [14]. The interaction modeling of EGNN only considers the relative position $\vec{\boldsymbol{x}}_i - \vec{\boldsymbol{x}}_j$ and its inner product $\|\vec{\boldsymbol{x}}_i - \vec{\boldsymbol{x}}_j\|^2$, which might have limited expressivity while tackling complex physical interactions and dynamics

---

[1]For both $\phi_{\vec{\boldsymbol{g}}}$ and $\psi_{\vec{\boldsymbol{g}}}$, we expand more output channels besides $\boldsymbol{V}_{\vec{\boldsymbol{g}}}$ of σ in Eq. (9), and assign it to the invariant message $\boldsymbol{m}_{ij}$ in Eq. (7) and $\boldsymbol{h}_i'$ in Eq. (8), respectively.

between objects. GMN further extends to a multi-channel interaction $\vec{\boldsymbol{Z}}_i \ominus \vec{\boldsymbol{Z}}_j$ where $\vec{\boldsymbol{Z}}_i = [\vec{\boldsymbol{x}}_i, \vec{\boldsymbol{v}}_i]$ akin to our setup. Nevertheless, GMN is not object-aware, lacking the necessary object information, while in our message-passing we explicitly involve the particle-object correlation $\vec{\boldsymbol{Z}}_i \ominus \vec{\boldsymbol{C}}_{o(i)}$. Another line of work including GNS [26] and DPI [20] only enforces translation equivariance by directly feeding $[\vec{\boldsymbol{x}}_i - \vec{\boldsymbol{x}}_j, \vec{\boldsymbol{v}}_i, \vec{\boldsymbol{v}}_j]$ into an MLP without taking the inner product. These approaches fail to preserve the O(3)-equivariance and consequently have weaker generalization as we will illustrate in our experiments. Fig. 1 summarizes and compares the message-passing schemes of GNS, EGNN, GMN and our SOMP. We provide detailed comparisons in the theoretical perspective in Appendix by showing that EGNN and GMN are indeed special cases of SGNN.

We now provide the detailed formulations of $\phi_{\vec{\boldsymbol{g}}}$ in Eq. 7 and $\psi_{\vec{\boldsymbol{g}}}$ in Eq. 8. Since the full symmetry is violated by gravity $\vec{\boldsymbol{g}} \in \mathbb{R}^3$, and the dynamics of the system will naturally preserve a gravitational acceleration in the vertical direction. By this means, the orthogonal symmetry is no longer maintained in every direction but only restricted to the subgroup $O_{\vec{\boldsymbol{g}}}(3) \coloneqq \{\boldsymbol{O} \in O(3) \mid \boldsymbol{O}\vec{\boldsymbol{g}} = \vec{\boldsymbol{g}}\}$, that is, the rotations/reflections around the gravitational axis. We term such a reduction of equivariance as a novel notion: *subequivariance*. To reflect this special symmetry, we augment Eq. 3 by:

$$f_{\vec{\boldsymbol{g}}}(\vec{\boldsymbol{Z}}, \boldsymbol{h}) = [\vec{\boldsymbol{Z}}, \vec{\boldsymbol{g}}]\boldsymbol{V}_{\vec{\boldsymbol{g}}}, \quad \text{s.t.} \boldsymbol{V}_{\vec{\boldsymbol{g}}} = \sigma([\vec{\boldsymbol{Z}}, \vec{\boldsymbol{g}}]^\top[\vec{\boldsymbol{Z}}, \vec{\boldsymbol{g}}], \boldsymbol{h}), \tag{9}$$

where $\sigma : \mathbb{R}^{(m+1) \times (m+1)} \to \mathbb{R}^{(m+1) \times m'}$ is an MLP. Compared with Eq. (3), here we just augment the directional input with $\vec{\boldsymbol{g}}$. Interestingly, such a simple augmentation is universally expressive:

Theorem 1. *Let $f_{\vec{\boldsymbol{g}}}(\vec{\boldsymbol{Z}}, \boldsymbol{h})$ be defined by Eq. (9). Then, $f_{\vec{\boldsymbol{g}}}$ is $O_{\vec{\boldsymbol{g}}}(3)$-equivariant. More importantly, For any $O_{\vec{\boldsymbol{g}}}(3)$-equivariant function $\hat{f}(\vec{\boldsymbol{Z}}, \boldsymbol{h})$, there always exists an MLP σ satisfying $\|\hat{f} - f_{\vec{\boldsymbol{g}}}\| < \epsilon$ for arbitrarily small positive value ϵ.*

The proof is non-straightforward and deferred to the appendix. We thus leverage our designed subequivariant function with such desirable properties for $\phi_{\vec{\boldsymbol{g}}}$ and $\psi_{\vec{\boldsymbol{g}}}$ in our subequivariant object-aware message passing introduced above. We immediately have the following theorem guaranteeing the validity of our design.

Theorem 2. *The message passing φ (Eq. 4) is $O_{\vec{\boldsymbol{g}}}(3)$-equivariant.*

3.3 Application to Physical Scenes with Hierarchical Modeling

This subsection introduce the entire architecture of our subequivariant GNN. Many physical scenes are complicated, possibly involving contact, collision, and friction amongst multiple objects. In light of this, we further incorporate our message passing into a multi-stage hierarchical modeling framework. One of our interesting findings here is the edge separation. This is indeed motivated by the consideration that the interactions *between* or *within* objects are usually different. The former serves as a bridge of exchanging momentum and energy via interaction forces, while the latter usually accounts for maintaining the rigid or plastic constraints. Therefore, it would be beneficial to disentangle these two kinds of interactions by different types of message passing, which also distinguishes our hierarchical modeling from DPI [20]. The overall flowchart is provided in Fig. 2. To be specific, we alternate between the following three stages that implement φ in Eq. (4) distinctly.

1. Particle-level inter-object message passing. We start by modeling the local interactions from the particle-level, where we only involve those between different objects. That is,

$$\{(\vec{\boldsymbol{Z}}_i', \boldsymbol{h}_i')\}_{i=1}^N = \varphi_1\left(\{(\vec{\boldsymbol{Z}}_i, \boldsymbol{h}_i)\}_{i=1}^N, \{(\vec{\boldsymbol{C}}_k, \boldsymbol{c}_k)\}_{k=1}^M, \mathcal{E}_{\text{inter}}\right), \tag{10}$$

where $\mathcal{E}_{\text{inter}} = \{(i, j) : (i, j) \in \mathcal{E}, o(i) \neq o(j)\}$.

2. Object-level message passing. Given the renewed particle-level information produced by the first stage, we are now ready to construct the object-level message passing graph. The object-level message passing is proceeded as

$$\{(\vec{\boldsymbol{C}}_k', \boldsymbol{c}_k')\}_{k=1}^M = \varphi_2\left(\{(\vec{\boldsymbol{C}}_k, \boldsymbol{c}_k)\}_{k=1}^M, \{\emptyset\}, \mathcal{E}_{\text{obj}}\right), \tag{11}$$

where $\mathcal{E}_{\text{obj}}$ comprises the edges between interacted objects, indicating $\mathcal{E}_{\text{obj}} = \{(k, l) : \exists (i, j) \in \mathcal{E}_{\text{inter}}, o(i) = k, o(j) = l\}$. As a specific instantiation of φ in Eq. (4), here each object is considered as a node and the original object information in Eq. (5-8) is omitted (this is why we denote the second

Figure 2: The overall architecture with hierarchical modeling, specified as three stages.

input of φ_2 as the empty set $\emptyset$). Furthermore, we leverage a pooling of the updated particle-level information from the first stage as the object-level interactions, or formally, we re-define the calculation of "$\ominus$" for two different objects indexed by k, l as $\vec{C}_k \ominus \vec{C}_l = \text{Mean-Pool}_{(i,j) \in \mathcal{E}_{\text{inter}}} \left(\vec{Z}'_i \ominus \vec{Z}'_j \right)$, and similarly, $c_k \| c_l = \text{Mean-Pool}_{(i,j) \in \mathcal{E}_{\text{inter}}} \left(h'_i \| h'_j \right)$.

3. Particle-level inner-object message passing. Finally, given the updated object state information, we carry out the message passing for the particles only along the inner-object edges $\mathcal{E}_{\text{inner}} = \{(i, j) : (i, j) \in \mathcal{E}, o(i) = o(j)\}$, namely,

$$\{(\vec{Z}''_i, h''_i)\}_{i=1}^N = \varphi_3 \left(\{(\vec{Z}_i, h_i)\}_{i=1}^N, \{(\vec{C}'_k, c'_k)\}_{k=1}^M, \mathcal{E}_{\text{inner}} \right). \tag{12}$$

We use $\{\vec{Z}''_i\}_{i=1}^N$ as the proposal of the positions in the next time step, akin to the way in § 3.2.

4 Experiments

We conduct evaluations on Physion [4] and RigidFall [19]. Physion [4] is a large scale dataset consisting of eight different scenarios, including Dominoes, Contain, Collide, Drop, Roll, Link, Support, and Drape. These scenarios possess diverse physical scenes with complicated object interactions, serving as a challenging benchmark for evaluating dynamics models. Particularly, Drape also involves simulating *deformable* objects. RigidFall [19] is a simulation dataset whose scenes involve several cubes falling and colliding under varying magnitude of gravitational acceleration.

4.1 Baselines

We compare SGNN with several SOTA particle-based GNN simulators, including two non-equivariant models GNS [26] and DPI [20], as well as two equivariant models EGNN [28] and GMN [14]. Notably, the data preprocessing provided by Physion [4] for particle-based methods does not consider the camera-angle for the rotation of 3D coordinates, leading to the situation that in some scenarios, *e.g.*, Dominoes, Link, Support, and Collide, there exist a directional bias (from left to right horizontally) in the trajectories. This motivates us to consider three evaluation protocols: **1.** Use the original training and testing set with directional bias. **2.** Train on the original set and test on the randomly-rotated testing set. **3.** Train on the randomly-rotated training set (akin to applying data augmentation of rotations [5]), and test on the randomly-rotated testing set. Here all rotations are restricted to the ones around gravity. We dub the results obtained from the three cases GNS*, GNS, and GNS-Rot for GNS, and similarly for DPI. As for EGNN and GMN, we also propose to modify them into their subequivariant variants (EGNN-S and GMN-S) by adding an extra vector along the gravity in their update of velocities. Details are in Appendix. Note that EGNN, EGNN-S, GMN, GMN-S, and our SGNN always produce exactly the same result in the three scenarios due to their equivariance (or subequivariance). Hence, we do not distinguish the results of them under different settings. For RigidFall, such bias is not observed since the cubes are falling vertically driven by gravity.

4.2 Evaluation on Physion

Experimental setup. We strictly follow the training and evaluation protocol proposed in [4] for the particle-based simulators. We employ two evaluation metrics: **1.** Contact prediction accuracy. This metric, as also adopted by [4], evaluates whether two targeted objects labeled in the dataset will

Table 1: Contact prediction accuracy (%) on Physion. Results are averaged across 3 runs.

	Dominoes	Contain	Link	Drape	Support	Drop	Collide	Roll
GNS* [26]	$78.6_{\pm0.9}$	$71.6_{\pm1.6}$	$66.7_{\pm1.5}$	$58.8_{\pm1.0}$	$68.2_{\pm1.6}$	$65.3_{\pm1.1}$	$\mathbf{86.1}_{\pm0.5}$	$81.3_{\pm1.8}$
DPI* [20]	$82.3_{\pm1.3}$	$72.3_{\pm1.8}$	$63.7_{\pm2.2}$	$53.3_{\pm0.9}$	$64.8_{\pm2.0}$	$70.7_{\pm0.8}$	$84.4_{\pm0.7}$	$82.3_{\pm0.6}$
GNS [26]	$53.3_{\pm1.8}$	$70.7_{\pm2.2}$	$58.0_{\pm1.7}$	$58.0_{\pm1.3}$	$61.3_{\pm1.7}$	$65.0_{\pm0.7}$	$76.7_{\pm1.2}$	$80.0_{\pm0.4}$
DPI [20]	$57.3_{\pm2.2}$	$71.9_{\pm1.3}$	$63.0_{\pm1.9}$	$52.3_{\pm1.2}$	$58.0_{\pm1.1}$	$68.7_{\pm0.7}$	$78.7_{\pm1.3}$	$80.5_{\pm0.8}$
GNS-Rot [26]	$74.7_{\pm1.2}$	$72.7_{\pm2.0}$	$63.1_{\pm2.1}$	$57.3_{\pm1.0}$	$65.5_{\pm1.3}$	$64.7_{\pm1.3}$	$84.0_{\pm1.0}$	$79.4_{\pm2.1}$
DPI-Rot [20]	$72.7_{\pm1.7}$	$69.4_{\pm2.1}$	$65.2_{\pm2.3}$	$52.8_{\pm1.0}$	$66.7_{\pm0.8}$	$72.3_{\pm0.5}$	$83.2_{\pm1.6}$	$80.1_{\pm0.5}$
EGNN [28]	$61.3_{\pm1.1}$	$66.0_{\pm1.9}$	$52.7_{\pm1.2}$	$54.7_{\pm0.8}$	$60.0_{\pm0.5}$	$63.3_{\pm0.9}$	$76.7_{\pm1.4}$	$79.8_{\pm0.4}$
EGNN-S [28]	$72.0_{\pm2.1}$	$64.6_{\pm1.8}$	$55.3_{\pm2.1}$	$55.3_{\pm1.0}$	$60.5_{\pm1.5}$	$69.3_{\pm2.0}$	$79.3_{\pm1.5}$	$81.6_{\pm0.9}$
GMN [14]	$54.7_{\pm0.5}$	$57.6_{\pm2.2}$	$54.5_{\pm1.6}$	$57.6_{\pm1.3}$	$55.1_{\pm1.6}$	$54.2_{\pm1.1}$	$79.5_{\pm1.5}$	$81.3_{\pm1.3}$
GMN-S [14]	$55.6_{\pm1.3}$	$65.3_{\pm1.7}$	$55.1_{\pm2.8}$	$57.0_{\pm1.8}$	$59.3_{\pm2.2}$	$57.3_{\pm1.5}$	$81.2_{\pm1.2}$	$79.3_{\pm1.5}$
Our SGNN	$\mathbf{89.1}_{\pm1.5}$	$\mathbf{78.1}_{\pm1.5}$	$\mathbf{73.3}_{\pm1.1}$	$\mathbf{60.6}_{\pm0.5}$	$\mathbf{71.2}_{\pm0.9}$	$\mathbf{74.3}_{\pm1.0}$	$85.3_{\pm1.1}$	$\mathbf{84.2}_{\pm0.6}$

Figure 3: The rollout-MSE curves on Dominoes, Link, and Contain. Our model achieves the lowest MSE compared with baselines. Colored areas indicate 95% confidence intervals.

contact during the model rollout. **2.** Rollout MSE, the mean squared error between model rollout and the ground truth. We reuse the training protocol and hyper-parameters suggested in Physion for baselines and our model to ensure a fair comparison. In detail, all MLPs are initialized with 3 projection layers and a hidden dimension of 200. The networks are trained with an Adam optimizer, using an initial learning rate 0.0001 and an early-stopping of 10 epochs on the validation loss. We use 4 iterations in each message passing of our model. To take into account the floor constraint in all scenarios, we extra concatenate an indicator $\mathbb{I}(\vec{x}_i[2] < \gamma)$ to the input h_i for EGNN, GMN, and SGNN, while for GNS and DPI, we reuse the non-equivariant approach adopted by [4] that connects the nodes satisfying $\vec{x}_i[2] < \gamma$ with a virtual floor node with all features as $\mathbf{0}$. We run RANSAC [9] during testing on all models to help enforce the rigid constraint as suggested by Physion. More experimental details including a comparison of computational complexity are deferred to Appendix.

Results. We present the average contact prediction accuracy with std in Table 1, and the rollout MSE in Fig. 3. The detailed MSE on all 8 scenarios is deferred to Appendix due to space limit. We interpret our results by answering the following questions. **Q1.** *Is maintaining the symmetry important to models that learn to simulate?* For the non-equivariant models GNS and DPI, their performance usually encounters a significant drop if they are trained on the original data but tested on the rotated, particularly on the scenarios with bias in directions. For example, the accuracy of GNS drops from 78.6% to 53.3% on Dominoes when comparing GNS* with GNS. Such observation also holds for DPI and on more scenarios like Collide and Support. Using data augmentation would help in relieving the issue, but is still hard to recover the performance. The accuracy on Dominoes yielded by GNS-Rot is 74.7%, still worse than 78.6% by GNS*. Our SGNN instead leverages subequivariance to generalize to all horizontal directions, and is always guaranteed to produce the same prediction regardless of any rotations around gravity, and there is also no need to apply any data augmentation of rotations during training. **Q2.** *Does SGNN learn the physics and simulate the dynamics better than other models?* As displayed in Table 1, SGNN achieves the highest prediction accuracy on 7 out of the 8 scenarios, and is also very competitive on Collide. The improvements are very significant (>5% accuracy enhancement over the second best) on scenarios including Dominoes, Contain, and Link, where there are multiple objects contacting, colliding, and interacting. This observation is also supported by the rollout MSE curves in Fig. 3, showing our SGNN consistently yielding lower prediction error along the trajectories. **Q3.** *How does SGNN perform compared with other equivariant models?* For EGNN

277 and GMN, enforcing such a strong constraint of E(3)-equivariance leads to inferior performance in
278 these physical scenes with gravity involved. For instance, in the challenging scenarios Dominoes,
279 Contain, and Link, the accuracy of EGNN and GMN only stays around 60%, while SGNN achieves
promising results with subequivariant object-aware message passing.

Figure 4: Visualization examples on Physion. Our model yields accurate long-term predictions.

Generalization across scenarios. We further evaluate the generalization capability of our model
across various scenarios. To fulfill this goal, we leverage models trained in certain scenarios
to test them in others. We summarize the results in Fig. 5, where the models are trained in the scenarios indexed by the rows and evaluated on those indexed by the columns. It is observed that our model exhibits significantly stronger generalization than GNS, the best-performed baseline on Physion. For example, our model, although trained with the dynamics of Contain or Link, still yields a high accuracy (>78%) when tested on Drop, showcasing that our model is more advantageous in learning the dynamics and interactions of various objects.

Figure 5: Generalization across different tasks. Each row and column indicates the training and testing scenario, respectively. Darker color implies higher accuracy.

Ablation studies. Here we conduct several ablations to inspect how our proposed components contribute to the overall performance, and the results are given in Table 2. **1.** Subequivariance. We replace our subequivariant formulation of $\phi_{\vec{g}}$ and $\psi_{\vec{g}}$ by the E(3)-equivariant counterpart without gravity. It is clear that, in this way, the model is restricted by strong equivariance constraints, which leads to a significant degradation in performance. This verifies the necessity of

Table 2: Ablation studies.

	Dominoes	Contain	Drop
SGNN	89.1	78.1	74.1
E(3)-equivariance	79.6	65.3	68.1
w/o object-aware	81.2	68.7	70.1
w/o hierarchy	83.5	72.5	71.3
w/o edge separation	85.0	74.8	72.0

308 relaxing the full-equivariant model with our introduced method for physical scenarios with gravity.
309 **2.** Object-aware message passing. We replace $\vec{C}_k$ and c_k in Eq. 10 by zeros, eliminating the object
310 information from message passing. Without this necessary information, the model might fail to
311 capture useful geometric vectors like $\vec{x}_i - \vec{x}_{o(i)}$, which is closely related to physical quantities like
312 torque. **3.** Hierarchy. We compare our model with its counterpart without hierarchy. The flat model

Table 3: Rollout MSE ($\times 10^{-2}$) on RigidFall. |Train| denotes the number of training samples.

| | |Train| = 200 | | |Train| = 500 | | |Train| = 1000 | | |Train| = 5000 | |
	$t = 20$	$t = 40$	$t = 20$	$t = 40$	$t = 20$	$t = 40$	$t = 20$	$t = 40$
GNS [26]	$2.40_{\pm1.32}$	$6.79_{\pm3.43}$	$1.89_{\pm0.87}$	$5.41_{\pm2.78}$	$1.09_{\pm0.70}$	$3.38_{\pm2.15}$	$0.65_{\pm0.43}$	$2.38_{\pm1.66}$
DPI [20]	$1.71_{\pm0.87}$	$5.37_{\pm2.86}$	$1.48_{\pm0.78}$	$4.67_{\pm2.55}$	$1.24_{\pm0.72}$	$3.97_{\pm2.35}$	$0.52_{\pm0.36}$	$2.40_{\pm1.53}$
EGNN [28]	$1.89_{\pm1.34}$	$5.66_{\pm2.81}$	$1.07_{\pm0.71}$	$3.94_{\pm2.20}$	$0.95_{\pm0.44}$	$2.72_{\pm1.75}$	$0.78_{\pm0.45}$	$2.63_{\pm1.72}$
GMN [14]	$2.74_{\pm1.24}$	$7.08_{\pm3.37}$	$2.50_{\pm0.98}$	$6.34_{\pm3.11}$	$1.91_{\pm1.10}$	$4.50_{\pm2.21}$	$1.36_{\pm0.63}$	$3.50_{\pm1.98}$
Our SGNN	$\mathbf{0.72}_{\pm0.60}$	$\mathbf{2.44}_{\pm1.74}$	$\mathbf{0.39}_{\pm0.23}$	$\mathbf{1.47}_{\pm1.26}$	$\mathbf{0.31}_{\pm0.17}$	$\mathbf{1.09}_{\pm0.93}$	$\mathbf{0.20}_{\pm0.14}$	$\mathbf{1.01}_{\pm0.97}$

encounters an average of 4% drop in the prediction accuracy, showcasing the advantages of leveraging the particle- and object-level message passing for modeling complex object interactions in physical scenes. **4. Edge separation.** We employ different sets of edges in the inter-object and inner-object message passing. We argue that this design relieves the learning complexity of the message-passing with different types of relations. This is observed that removing edge separation consistently leads to detriment in the accuracy in various scenarios.

Qualitative comparisons. We provide visualization samples on Physion in Fig. 4. More cases are shown by our Supplementary Video. Our model consistently yields accurate predictions.

4.3   Evaluation on RigidFall

Experimental setup. We use the code provided by [20]. We record the rollout MSE at $t = 20$ and 40. To compare the data efficiency of different models, we consider four cases with the size of training set ranging from 200 to 5000. More details are in Appendix.

Results. The results are presented in Table 3. Our model consistently yields the best predictions regardless of the time step t and the number of training samples. Notably, the rollout error still maintains a very low value even if only 200 training samples are provided, which verifies the strong data-efficiency and generalization of SGNN. Consistent observations are also visualized in Fig. 6.

Figure 6: Visualization examples on RigidFall. Our SGNN provides accurate simulation trajectories.

5   Discussion

Limitations and Future Work. Our model relies on the particle-based representation of the physical systems, which, in real-world scenarios, might be difficult to obtain, or usually with noise. An interesting future direction lies in combining our dynamics model with groundings of visual prior, akin to [19], and applies to more sophisticated tasks like physical reasoning or robot manipulation.

Conclusion. We propose Subequivariant Graph Neural Networks for modeling physical dynamics of multiple interacting objects. We inject appropriate symmetry into a hierarchical message passing framework, and takes into account both particle- and object-level state messages. In particular, subequivariance is a novel concept for characterizing the relaxation of equivariance from a group to its subgroup. We show that relaxation from full equivariance to subequivariance can be applied to systems with gravity involved. Experiments verify that SGNN accurately captures the dynamics with the guarantee of the desirable symmetry, and exhibits strong generalization with high data-efficiency.

References

[1] Pulkit Agrawal, Ashvin V Nair, Pieter Abbeel, Jitendra Malik, and Sergey Levine. Learning to poke by poking: Experiential learning of intuitive physics. *Advances in neural information processing systems*, 29, 2016. 1

[2] Peter Battaglia, Razvan Pascanu, Matthew Lai, Danilo Jimenez Rezende, and koray kavukcuoglu. Interaction networks for learning about objects, relations and physics. In *Advances in Neural Information Processing Systems*, volume 29, 2016. 2

[3] Peter W Battaglia, Jessica B Hamrick, and Joshua B Tenenbaum. Simulation as an engine of physical scene understanding. *Proceedings of the National Academy of Sciences*, 110(45):18327–18332, 2013. 1

[4] Daniel Bear, Elias Wang, Damian Mrowca, Felix Jedidja Binder, Hsiao-Yu Tung, RT Pramod, Cameron Holdaway, Sirui Tao, Kevin A. Smith, Fan-Yun Sun, Li Fei-Fei, Nancy Kanwisher, Joshua B. Tenenbaum, Daniel LK Yamins, and Judith E Fan. Physion: Evaluating physical prediction from vision in humans and machines. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 1)*, 2021. 6, 7

[5] Gregory Benton, Marc Finzi, Pavel Izmailov, and Andrew G Wilson. Learning invariances in neural networks from training data. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 17605–17616. Curran Associates, Inc., 2020. 6

[6] Gabriele Cesa, Leon Lang, and Maurice Weiler. A program to build e (n)-equivariant steerable cnns. In *International Conference on Learning Representations*, 2021. 2

[7] Zhenfang Chen, Kexin Yi, Yunzhu Li, Mingyu Ding, Antonio Torralba, Joshua B. Tenenbaum, and Chuang Gan. Comphy: Compositional physical reasoning of objects and events from videos. In *International Conference on Learning Representations*, 2022. 1

[8] Marc Finzi, Samuel Stanton, Pavel Izmailov, and Andrew Gordon Wilson. Generalizing convolutional neural networks for equivariance to lie groups on arbitrary continuous data. In *ICML*, 2020. 2

[9] Martin A Fischler and Robert C Bolles. Random sample consensus: a paradigm for model fitting with applications to image analysis and automated cartography. *Communications of the ACM*, 24(6):381–395, 1981. 7

[10] Fabian Fuchs, Daniel Worrall, Volker Fischer, and Max Welling. Se(3)-transformers: 3d roto-translation equivariant attention networks. In *Advances in Neural Information Processing Systems*, volume 33, pages 1970–1981. Curran Associates, Inc., 2020. 2

[11] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International conference on machine learning*, pages 1263–1272. PMLR, 2017. 1

[12] Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. *Advances in neural information processing systems*, 30, 2017. 1

[13] Jiaqi Han, Yu Rong, Tingyang Xu, and Wenbing Huang. Geometrically equivariant graph neural networks: A survey. *arXiv preprint arXiv:2202.07230*, 2022. 2

[14] Wenbing Huang, Jiaqi Han, Yu Rong, Tingyang Xu, Fuchun Sun, and Junzhou Huang. Equivariant graph mechanics networks with constraints. In *International Conference on Learning Representations*, 2022. 2, 3, 4, 6, 7, 9

[15] Michael J Hutchinson, Charline Le Lan, Sheheryar Zaidi, Emilien Dupont, Yee Whye Teh, and Hyunjik Kim. Lietransformer: equivariant self-attention for lie groups. In *ICML*, 2021. 2

[16] Thomas Kipf, Ethan Fetaya, Kuan-Chieh Wang, Max Welling, and Richard Zemel. Neural relational inference for interacting systems. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 2688–2697. PMLR, 10–15 Jul 2018. 2

[17] Adam Lerer, Sam Gross, and Rob Fergus. Learning physical intuition of block towers by example, 2016. 1

[18] Sizhe Li, Zhiao Huang, Tao Du, Hao Su, Joshua B. Tenenbaum, and Chuang Gan. Contact points discovery for soft-body manipulations with differentiable physics. In *International Conference on Learning Representations*, 2022. 1

[19] Yunzhu Li, Toru Lin, Kexin Yi, Daniel Bear, Daniel Yamins, Jiajun Wu, Joshua Tenenbaum, and Antonio Torralba. Visual grounding of learned physical models. In *International conference on machine learning*, pages 5927–5936. PMLR, 2020. 6, 9

[20] Yunzhu Li, Jiajun Wu, Russ Tedrake, Joshua B Tenenbaum, and Antonio Torralba. Learning particle dynamics for manipulating rigid bodies, deformable objects, and fluids. In *International Conference on Learning Representations*, 2018. 1, 2, 3, 5, 6, 7, 9

[21] Xingyu Lin, Zhiao Huang, Yunzhu Li, David Held, Joshua B. Tenenbaum, and Chuang Gan. Diffskill: Skill abstraction from differentiable physics for deformable object manipulations with tools. In *International Conference on Learning Representations*, 2022. 1

[22] Damian Mrowca, Chengxu Zhuang, Elias Wang, Nick Haber, Li F Fei-Fei, Josh Tenenbaum, and Daniel L Yamins. Flexible neural representation for physics prediction. *Advances in neural information processing systems*, 31, 2018. 2, 3

[23] Tobias Pfaff, Meire Fortunato, Alvaro Sanchez-Gonzalez, and Peter Battaglia. Learning mesh-based simulation with graph networks. In *International Conference on Learning Representations*, 2021. 1, 2

[24] Yulia Rubanova, Alvaro Sanchez-Gonzalez, Tobias Pfaff, and Peter Battaglia. Constraint-based graph network simulator, 2022. 2

[25] Alvaro Sanchez-Gonzalez, Victor Bapst, Kyle Cranmer, and Peter Battaglia. Hamiltonian graph networks with ode integrators. *arXiv preprint arXiv:1909.12790*, 2019. 2

[26] Alvaro Sanchez-Gonzalez, Jonathan Godwin, Tobias Pfaff, Rex Ying, Jure Leskovec, and Peter Battaglia. Learning to simulate complex physics with graph networks. In *International Conference on Machine Learning*, pages 8459–8468. PMLR, 2020. 1, 2, 3, 5, 6, 7, 9

[27] Alvaro Sanchez-Gonzalez, Nicolas Heess, Jost Tobias Springenberg, Josh Merel, Martin Riedmiller, Raia Hadsell, and Peter Battaglia. Graph networks as learnable physics engines for inference and control. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 4470–4479. PMLR, 10–15 Jul 2018. 1

[28] Víctor Garcia Satorras, Emiel Hoogeboom, and Max Welling. E(n) equivariant graph neural networks. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 9323–9332. PMLR, 18–24 Jul 2021. 2, 3, 4, 6, 7, 9

[29] Nathaniel Thomas, Tess Smidt, Steven Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, and Patrick Riley. Tensor field networks: Rotation-and translation-equivariant neural networks for 3d point clouds. *arXiv preprint arXiv:1802.08219*, 2018. 2

[30] Soledad Villar, David W Hogg, Kate Storey-Fisher, Weichi Yao, and Ben Blum-Smith. Scalars are universal: Equivariant machine learning, structured like classical physics. In *Advances in Neural Information Processing Systems*, 2021. 2, 3

[31] Maurice Weiler and Gabriele Cesa. General e (2)-equivariant steerable cnns. *Advances in Neural Information Processing Systems*, 32, 2019. 2

[32] Yufei Ye, Dhiraj Gandhi, Abhinav Gupta, and Shubham Tulsiani. Object-centric forward modeling for model predictive control. In Leslie Pack Kaelbling, Danica Kragic, and Komei Sugiura, editors, *Proceedings of the Conference on Robot Learning*, volume 100 of *Proceedings of Machine Learning Research*, pages 100–109. PMLR, 30 Oct–01 Nov 2020. 1

[33] Yaofeng Desmond Zhong, Biswadip Dey, and Amit Chakraborty. Extending lagrangian and hamiltonian neural networks with differentiable contact models. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. 2