Federated Submodel Optimization for Hot and Cold Data Features

Abstract

We study federated learning from the new perspective of feature heat, where distinct data features normally involve different numbers of clients, generating the differentiation of hot and cold features. Meanwhile, each client's local data tend to interact with part of features, updating only the feature-related part of the full model, called a submodel. We further identify that the classical federated averaging algorithm (FedAvg) or its variants, which randomly selects clients to participate and uniformly averages their submodel updates, will be severely slowed down, because different parameters of the global model are optimized at different speeds. More specifically, the model parameters related to hot (resp., cold) features will be updated quickly (resp., slowly). We thus propose federated submodel averaging (FedSubAvg), which introduces the number of feature-related clients as the metric of feature heat to correct the aggregation of submodel updates. We prove that due to the dispersion of feature heat, the global objective is ill-conditioned, and FedSubAvg works as a suitable diagonal preconditioner. We also rigorously analyze FedSubAvg's convergence rate to stationary points. We finally evaluate FedSubAvg over several public and industrial datasets. The evaluation results demonstrate that FedSubAvg significantly outperforms FedAvg and its variants.

1 Introduction

Federated learning (FL) [1] allows a large number of clients (e.g., millions of smartphone users) to collaborate in the training of a global machine learning (ML) model under the coordination of a cloud server without sharing raw data. Google also has deployed FL on its Andriod keyboard, called Gboard, to polish language models [2]. As the default optimization algorithm of FL, federated averaging (FedAvg) averages the participating clients' local models to update the global model. Later, much effort was devoted to proving the convergence of FedAvg, and the key challenge is that local data are normally non-independent and identically distributed (non-i.i.d.) [3, 4, 5, 6]. One line of work [7, 8, 9, 10, 11] established an $O(1/\sqrt{NT})$ convergence, where N denotes the total number of clients and T denotes the total number of iterations. However, these work required all the clients to participant in each round of FL, which is not practical in cross-device FL. Another line of work [12, 13, 14, 15, 16, 17] allowed partial client participation and proved an $O(1/\sqrt{KT})$ convergence of FedAvg, where K denotes the number of chosen clients in each round. Some other work proposed variants of FedAvg to better deal with data heterogeneity. Li et al. [18] proposed FedProx by adding a proximal term to local objective. Karimireddy et al. [19] proposed Scaffold by adding a control variate for each client to control local training.

Besides non-i.i.d. from data distribution, the interactions between the data features and the clients are mutual, partial, and differentiated, especially in practical recommender systems (RS) and natural language processing (NLP) scenarios. On the one hand, distinct data features are normally involved

by different numbers of clients. For example, the differentiation of popular and unpopular items in RS or hot and cold words in NLP is common and obvious. We call such an observation *feature heat dispersion*. On the other hand, a certain client's local data normally involve a small subspace of the full feature space, and the client downloads and updates only the feature-related part of the full global model, called a *submodel* in [20], such as the embedding vectors of the client's few local items and words rather than the full and huge embedding layer in RS and NLP, respectively.

The existing work on FL has not well studied the issue of feature heat dispersion. However, it will severely deteriorate the performance of FedAvg and its variants. We take an extreme example in RS for illustration. For some hot items involving nearly 100% of clients (resp., some cold items involving less than 1% of clients), the corresponding item embeddings are involved by a majority (resp., minority) of the clients' submodels. In expectation, at the end of each round in FedAvg and its variants, the embeddings related to the hot items will be updated approximately by adding the average of the involved clients' updates, while the embeddings related to the cold items will be updated by adding less than 1% of the average of the involved clients' updates. The inaccurate aggregation without considering the feature heat dispersion leads to different parameters of the global model being optimized at different speeds.

To deal with feature heat dispersion, we propose federated submodel averaging (FedSubAvg), which first averages the local updates of the chosen clients, just like FedAvg, but then multiplies the aggregate update of each model parameter with the ratio between the total number of clients and the number of clients who involve this model parameter. Such a small correction ensures that the expectation of each model parameter's global update is equal to the average of the local updates of the clients who involve this parameter. We theoretically demonstrate the advantage of FedSubAvg over FedAvg and analyze the convergence of FedSubAvg. We first prove that the global objective is ill-conditioned, leading to the slow convergence of FedAvg, and FedSubAvg works as a suitable diagonal preconditioner. We also obtain an $O(\sqrt{N/(n_{\min}KT)})$ convergence with respect to stationary points, where $n_{\min}$ denotes the minimum of the number of clients who involve each individual parameter.

We summarize the key contributions: (1) To the best of our knowledge, we are the first to make an in-depth study of FL from the differentiation of hot and cold data features, which is common in practice; (2) we identify the defect of FedAvg and its variants in handling feature heat dispersion and propose a new and efficient algorithm FedSubAvg; (3) we theoretically show that the the global objective is ill-conditioned, and FedSubAvg works as a preconditioner for acceleration. We also give the convergence rate of FedSubAvg in the general non-convex case; and (4) using the public MovieLens, Sentiment140, and Amazon datasets, as well as an industrial dataset from Alibaba, we evaluate FedSubAvg and compare its performance with FedAvg, FedProx, and Scaffold. The evaluation results reveal the superiority of FedSubAvg from faster convergence and smaller train loss.

2 Problem Formulation

We focus on a distributed optimization in RS or NLP scenario, in which N clients collaboratively solve the following consensus optimization problem:

$$f(\mathbf{X}) = \frac{1}{N} \sum_{i=1}^{N} \mathbb{E}_{\xi_i \sim D_i} [F(\mathbf{X}, \xi_i)] = \frac{1}{N} \sum_{i=1}^{N} f_i(\mathbf{X}),$$

where $\xi_i \sim D_i$ denotes the local training data of client i; $\mathbf{X}$ is the full global model, following the structure of an embedding layer plus some other network layers, where sparse input features are mapped into embedding vectors, concatenated, and fed into the upper layers; $F(\mathbf{X}, \xi_i)$ is the train loss of $\mathbf{X}$ over the local data ξ_i; and $f_i(\mathbf{X})$ is the local generalization error, taking expectation over the randomness of the local data.

We then consider that a client's local data involve only part of the full global model, namely, a submodel, which is related to the client's local data features. For example, in a RS scenario, a client can use the data collected in the previous week as its local training set, and retrieve the submodel in a key-value lookup way, typically, by retrieving a few embedding vectors based on the local item ids and directly taking the other network layers. Considering the full embedding layer is far beyond any mobile device's capacity, such a submodel design makes federated learning in these industrial scenarios possible. Formally, we use $S = \{1, 2, \cdots, M\}$ to index the parameters of the full model $\mathbf{X} \in \mathbb{R}^M$ and call it the full index set. We let $S(i) \subseteq S$ denote the index

Figure 1: FedAvg vs. FedSubAvg with $N = 3$ clients in total and 2 clients involving the first model parameter. The dashed line indicates that the client does not download the parameter and upload no update.

Figure 2: FedAvg (learning rate η) vs. FedSubAvg (learning rate γ) for Example 1 with the parameter heat dispersion of 100.

set of client i's submodel $\mathbf{X}_{S(i)}$. In other words, the full model excluding the submodel (i.e., $\mathbf{X}_{S \setminus S(i)}$) does not affect the model output and the local gradient of $\mathbf{X}_{S \setminus S(i)}$ will always be zero. This further implies that we can rewrite the global objective function in a distributed submodel way: $f(\mathbf{X}) = \frac{1}{N} \sum_{i=1}^{N} f_i(\mathbf{X}_{\mathcal{S}(i)})$. The gradient of f is $\nabla f(\mathbf{X}) = \frac{1}{N} \sum_{i=1}^{N} \nabla f_i(\mathbf{X}_{\mathcal{S}(i)})$, and the Hessian is $\mathbf{H} \triangleq \nabla^2 f(\mathbf{X}) = \frac{1}{N} \sum_{i=1}^{N} \nabla^2 f_i(\mathbf{X}_{\mathcal{S}(i)}) = \frac{1}{N} \sum_{i=1}^{N} \mathbf{H}_i$. Note that when doing any operation (e.g., summation) over multiple submodels, gradients, and Hessians, they will be automatically aligned according to the indices.

We finally introduce the metric of feature heat dispersion (resp., the resulting parameter heat dispersion), which is defined as the ratio between the maximum and the minimum of the number of clients who involve each individual feature (resp., parameter). Considering the fact that a parameter may involve one or multiple data features in RS and NLP[1], the feature heat dispersion is a lower bound of the parameter heat dispersion. In other words, *high feature heat dispersion inevitably leads to high parameter heat dispersion.* For convenience and clarity in the submodel-level analysis, we mainly take the metric of parameter heat dispersion. We let n_m denote the number of clients involving the parameter with index $m \in S$ and set $n_{\max} = \max_{m \in S} n_m, n_{\min} = \min_{m \in S} n_m$. Then, the parameter heat dispersion is $n_{\max}/n_{\min}$.

3 Algorithm Design

In this section, we first show that FedAvg suffers from high parameter heat dispersion in distributed submodel optimization and then propose FedSubAvg to remedy the defect.

3.1 Slow Convergence of FedAvg

Example 1. *We consider a special distributed convex optimization problem with two model parameters, denoted as w_1 and w_2. Each client i's local data $\xi_i \sim D_i$ are with mean $\mathbf{e}_i = \mathbb{E}[\xi] = \mathbf{0}$. In addition, w_1 involves only client 1, while w_2 involves all the N clients. Then, the parameter heat dispersion is $n_2/n_1 = N$. We formulate this learning problem as minimizing the mean square error:*

$$f((w_1, w_2)) = \frac{1}{N} \sum_{i=1}^{N} f_i\left((w_1, w_2)_{S(i)}\right),$$

where $f_1\left((w_1, w_2)_{S(1)}\right) = \mathbb{E}_{\xi_1 \sim D_1}\left[\| (w_1, w_2) - \xi_1 \|^2\right]$; and for $i = 2, 3, \cdots, N$, $f_i\left((w_1, w_2)_{S(i)}\right) = \mathbb{E}_{\xi_i \sim D_i}[(w_2 - \xi_i)^2] = w_2^2 + \mathbb{E}_{\xi_i \sim D_i}[(\xi_i - \mathbf{e}_i)^2]$.

For this example, the optimal model is $(w_1^*, w_2^*) = (0, 0)$. We leverage FedAvg with only one local iteration and let each client compute the exact (not stochastic) gradient. The learning rate is denoted

---

[1]For example, an embedding vector corresponds to an item in RS or a certain word in NLP, while the fully connected layer is related to all the words or items.

as η, and the model is initialized as (w_1^0, w_2^0). After r rounds, the model will become

$$(w_1^r, w_2^r)^\top = \begin{bmatrix} 1 - \frac{2\eta}{N} & 0 \\ 0 & 1 - 2\eta \end{bmatrix}^r (w_1^0, w_2^0)^\top.$$

By choosing $\eta = 0.5$, $(w_1^r, w_2^r) = ((1 - 1/N)^r w_1^0, 0)$. We can find that in the FL scenario with high parameter heat dispersion N, w_1 will converge at a quite low speed.

3.2 Federated Submodel Averaging

To mitigate parameter heat dispersion, we propose FedSubAvg. As shown in Figure 1, compared with FedAvg, the key principle of FedSubAvg is to further multiply the aggregate update of each model parameter with the ratio between the total number of clients and the number of clients who involve this model parameter (i.e., for the model parameter with index m, the correction coefficient is N/n_m). We still examine Example 1 for illustration. FedSubAvg will multiply the aggregate update of w_1 and w_2 with N and 1, respectively. By correction, the model at the r-th round is:

$$(w_1^r, w_2^r)^\top = \begin{bmatrix} 1 - 2\gamma & 0 \\ 0 & 1 - 2\gamma \end{bmatrix}^r (w_1^0, w_2^0)^\top,$$

where γ is the learning rate of FedSubAvg. Therefore, FedSubAvg converges quickly to the optimal model $(0, 0)$. We also depict the optimization processes of FedSubAvg and FedAvg for Example 1 in Figure 2, when the parameter heat dispersion is 100. We can observe that FedSubAvg greatly outperforms FedAvg from convergence speed and loss.

Algorithm 1 Federated Submodel Averaging (FedSubAvg)

Require: The total number of clients N, the number of local iterations I, the number of clients involving the m-th model parameter n_m, the number of selected clients K per round.

    /* Cloud server's process */
1: Initializes the global model $\mathbf{X}^1$;
2: **for** each communication round $r = 1, 2, \cdots, R$ **do**
3:     Randomly selects K clients, denoted as C_r;
4:     **for** each client $i \in C_r$ **do**
5:         Receives the index set $S(i)$, returns the submodel $\mathbf{X}_{S(i)}^r$, and receives the submodel update $\Delta \mathbf{x}_i^r$;
6:     **end for**
7:     $\mathbf{X}^{r+1} \leftarrow \mathbf{X}^r$;
8:     **for** each index $m \in \bigcup_{i \in C_r} S(i)$ **do**
9:         $\mathbf{X}_{\{m\}}^{r+1} \leftarrow \mathbf{X}_{\{m\}}^r + \frac{N}{n_m K} \sum_{i \in C_r} \Delta \mathbf{x}_{i,\{m\}}^r$;
10:    **end for**
11: **end for**
    /* Client i's process */
12: Determines its index set $S(i)$ based on the local data;
13: Uses $S(i)$ to download the submodel $\mathbf{X}_{S(i)}^r$ from the cloud server;
14: Initializes the local submodel $\mathbf{x}_i^{r,1} \leftarrow \mathbf{X}_{S(i)}^r$
15: **for** local iteration $j = 1, 2, \cdots, I$ **do**
16:    $\mathbf{x}_i^{r,j+1} \leftarrow \mathbf{x}_i^{r,j} - \gamma \nabla F(\mathbf{x}_i^{r,j}, \xi_i)$ for $\xi_i \sim D_i$;
17: **end for**
18: Uploads $\Delta \mathbf{x}_i^r = \mathbf{x}_i^{r,I+1} - \mathbf{x}_i^{r,1}$ to the cloud server.

We now present the design details of FedSubAvg in Algorithm 1. In each round r of FL, the cloud server first selects K clients to participate (Line 3), denoted as C_r. Each selected client $i \in C_r$ determines its index set $S(i)$ of submodel based on the local training set (Line 12). Then, client i uses $S(i)$ to download the submodel $\mathbf{X}_{S(i)}^r$ from the cloud server and initializes the local submodel $\mathbf{x}_i^{r,1}$ (Lines 13–14). Client i locally trains its submodel by doing I iterations of stochastic gradient descent (SGD) (Lines 15–17) and uploads the submodel update $\Delta \mathbf{x}_{S(i)}^r$ (Line 18). After receiving the submodel updates from the selected clients, the cloud server performs aggregation for each index

in the union of the participating clients' index sets and updates the global full model (Lines 7–10). In particular, for the global model parameter with m, namely, $\mathbf{X}^r_{\{m\}}$, its expected update, after being corrected with the coefficient N/n_m, is

$$\mathbb{E}_{C_r}\left[\Delta \mathbf{X}^r_{\{m\}}\right] = \frac{N}{n_m}\left[\frac{1}{N}\sum_{i=1}^{N}\Delta \mathbf{x}^r_{i,\{m\}}\right] = \frac{1}{n_m}\sum_{\{i|m\in S(i)\}}\Delta \mathbf{x}^r_{i,\{m\}},$$

which is equal to the average of the local updates of the participating clients involving it, as required.

4 Theoretical Analysis

In this section, we first prove that in FL with high parameter heat dispersion, the global objective f is ill-conditioned. We then prove that optimizing f with FedSubAvg approximates to optimizing a preconditioning objective $\hat{f}$ with gradient descent (GD), thereby remedying ill conditioning. In particular, the diagonal preconditioning matrix comprises of the correction coefficients $\{N/n_m|m\in S\}$ in FedSubAvg and can be obtained without needing to access any client's local raw data and without any expensive computing, which keeps the tenet of FL. Further by analyzing the Hessian of $\hat{f}$, we demonstrate that the superiority of optimizing $\hat{f}$ over f. We also obtain the convergence guarantee for FedSubAvg.

4.1 FedAvg with Ill-Conditioned Global Objective

We first make an assumption about the eigenvalues of each client's local Hessian.

Assumption 1 (Bounded Hessian). *For any model $\mathbf{X}$, the global Hessian is non-singular, and for each client i, the Hessian of f_i satisfies:*

$$-\rho_2 I_i \preceq \nabla^2 f_i(\mathbf{X}_{S(i)}) \preceq -\rho_1 I_i \ \ or \ \ \rho_1 I_i \preceq \nabla^2 f_i(\mathbf{X}_{S(i)}) \preceq \rho_2 I_i, \ \ with \ \ 0 < \rho_1 < \rho_2.$$

Further, if $\mathbf{X}$ is in a locally convex area of f, for each parameter m, more than $1-\alpha$ of the related clients satisfies $\rho_1 I_i \preceq \nabla^2 f_i(\mathbf{X}_{S(i)}) \preceq \rho_2 I_i$, where α is a constant with $(1-\alpha)\rho_1 - \alpha\rho_2 > 0$.

Assumption 1 bounds the eigenvalues of $\nabla^2 f_i(\mathbf{X}_{S(i)})$ and ensures that when $\mathbf{X}$ is in a locally convex area of f, $\mathbf{X}_{S(i)}$ is also in a locally convex area of f_i for most of the clients, which helps to obtain the bounds of the global Hessian. Under Assumption 1, we can analyze the condition number of $\mathbf{H}$: $\kappa(\mathbf{H}) \overset{\triangle}{=} \sigma_{\max}(\mathbf{H})/\sigma_{\min}(\mathbf{H})$, where $\sigma_{\max}(\mathbf{H})$ and $\sigma_{\min}(\mathbf{H})$ denote the biggest and smallest singular values of $\mathbf{H}$, respectively.

Theorem 1. *Under Assumption 1, for any model $\mathbf{X}$ in a locally convex area, the condition number of the global Hessian of f satisfies:*

$$\kappa(\mathbf{H}) \geq \frac{n_{\max}\left(\rho_1 - \alpha(\rho_1 + \rho_2)\right)}{n_{\min}\rho_2}.$$

Proof. Please refer to Appendix A. $\qquad\qquad\square$

Theorem 1 reveals that when the parameter heat dispersion $n_{\max}/n_{\min}$ is high, then the global objective is ill-conditioned. Specifically, in the large-scale RS and NLP scenarios, since the fully connected layer involves all the N clients, while the embedding vector of a cold word or item normally involves a few clients, we have $\kappa(\mathbf{H}) = \Theta(N)$. This further implies with a large N in practice, the global objective is extremely ill-conditioned. Therefore, the conventional FedAvg and its variants, which are the approximations to GD, will converge at a quite slow speed, even when the global model is in a locally convex area.

4.2 FedSubAvg as a Preconditioner Better than FedAvg

For brevity, we introduce t to denote the global iteration index, thus replacing the round index r and the local iteration index j, where $t = (r-1)\times I + j$. We consider a single iteration of FedSubAvg:

$$\mathbf{X^{t+1}} = \mathbf{X^t} - \gamma\mathbf{D}\left(\frac{1}{N}\sum_{i=1}^{N}\nabla f_i(\mathbf{x}^t_i)\right) \approx \mathbf{X^t} - \gamma\mathbf{D}\nabla f(\mathbf{X^t}), \tag{1}$$

where $\mathbf{X}^t \triangleq \mathbf{D}(\frac{1}{N}\sum_{i=1}^{N}\mathbf{x}_i^t)$ is defined as the global model at iteration t, and $\mathbf{D} =$ $\text{diag}\{N/n_1, N/n_2, \cdots, N/n_M\}$. By treating $\mathbf{D}$ as a preconditioning matrix [21], we can construct a new objective $\hat{f}(\hat{\mathbf{X}}) \triangleq f(\mathbf{D}^{\frac{1}{2}}\hat{\mathbf{X}}) = f(\mathbf{X})$ with variable $\hat{\mathbf{X}}=\mathbf{D}^{-\frac{1}{2}}\mathbf{X}$. The gradient and the Hessian[2] of $\hat{f}$ are:

$$\nabla\hat{f}(\hat{\mathbf{X}}) = \mathbf{D}^{\frac{1}{2}}\nabla f(\mathbf{X}), \quad \nabla^2\hat{f}(\hat{\mathbf{X}}) = \mathbf{D}^{\frac{1}{2}}\mathbf{H}\mathbf{D}^{\frac{1}{2}}. \tag{2}$$

Dauphin et al. [21] showed that one SGD update for $\hat{f}$ corresponds to equation 1. Therefore, we can compare FedSubAvg and FedAvg by comparing the characteristics of $\hat{f}$ and f.

Theorem 2. *Under Assumption 1, for any $\mathbf{X}$, the upper bound of the condition number of the corresponding Hessian, $\hat{\mathbf{H}} \triangleq \nabla^2\hat{f}(\hat{\mathbf{X}})$, is always smaller than that of $\mathbf{H}$:*

$$\kappa\left(\mathbf{H}\right) \leq \frac{\rho_2 n_{\max}}{N\sigma_{\min}(\mathbf{H})} \triangleq k, \quad \kappa\left(\hat{\mathbf{H}}\right) \leq \frac{\rho_2}{N\sigma_{\min}(\hat{\mathbf{H}})} \triangleq \hat{k} \ \text{ with } \ \hat{k} \leq k.$$

Further, if $\mathbf{X}$ in a locally convex area, the condition number of $\nabla^2\hat{f}(\hat{\mathbf{X}})$, satisfies:

$$\kappa(\hat{\mathbf{H}}) \leq \frac{\rho_2}{(\rho_1 - \alpha(\rho_1 + \rho_2))}, \ \text{ with } \ \hat{\mathbf{H}} = \nabla^2\hat{f}(\hat{\mathbf{X}}).$$

Proof. Please refer to Appendix B. $\qquad\square$

Theorem 2 indicates that $\hat{\mathbf{H}}$ always has a smaller condition number upper bound compared with $\mathbf{H}$. Further, in a locally convex area, the proposed FedSubAvg significantly reduce the condition number: $\hat{\mathbf{H}}$ is well-conditioned with $\kappa(\mathbf{H}) \leq \Theta(1)$. Therefore, the proposed FedSubAvg, which is an approximation to GD for objective $\hat{f}$, will maintain the efficiency of FedAvg in any case and converge much faster than FedAvg in a locally convex area of f.

4.3 Convergence Guarantee for FedSubAvg

We analyze the convergence rate of FedSubAvg in the general non-convex case. We use $\| \nabla\hat{f}(\hat{\mathbf{X}}) \|^2 = \nabla f(\mathbf{X})^\top \mathbf{D}\nabla f(\mathbf{X})$ rather than $\| \nabla f(\mathbf{X}) \|^2$ to characterize the convergence rate. This is because the curvature of the original global objective f has been severely "diluted". In particular, most model parameters involve only a small number of clients, while the zero gradients contributed by many non-involved clients are inaccurately counted in when computing the global gradient[3].

We next make the following assumptions about the objective functions, as well as the variance and the feasible space of the stochastic gradients.

Assumption 2 (Smoothness). $f_i(\cdot)$ *is L-smooth if*

$$\forall \mathbf{x}, \mathbf{y}, f_i(\mathbf{y}) \leq f_i(\mathbf{x}) + \langle \mathbf{y} - \mathbf{x}, \nabla f_i(\mathbf{x})\rangle + \frac{L}{2}\| \mathbf{x} - \mathbf{y} \|^2 .$$

Assumption 3 (Bounded Variance). *During local training, the variance of stochastic gradients on each client is bounded by σ^2: $\forall i, t : \mathbb{E}_{\xi_i \sim D_i}\left[\| \nabla f_i(\mathbf{x}_i^t) - \nabla F(\mathbf{x}_i^t, \xi_i) \|^2\right] \leq \sigma^2$.*

Assumption 4 (Bounded Gradient Norm). *During local training, the expected l_2-norm of the stochastic gradients is bounded by a constant G^2: $\forall i, t : \mathbb{E}_{\xi_i \sim D_i}\left[\| \nabla F(\mathbf{x}_i^t, \xi_i) \|^2\right] \leq G^2$.*

Assumption 2 is standard. Assumptions 3 and 4 were widely made in the literature [8, 9, 11, 22, 13]. Under these assumptions, we can bound the gradient norm.

Theorem 3. *Under Assumptions 2, 3, and 4, we can bound the expected average of the squared gradient norm*

$$\mathbb{E}\left[\frac{1}{T}\sum_{i=1}^{T}\nabla f(\mathbf{X}^t)^\top \mathbf{D}\nabla f(\mathbf{X}^t)\right] \leq \frac{2\left(f\left(\mathbf{X}^1\right) - f\left(\mathbf{X}^*\right)\right)}{\gamma T} + \frac{2\gamma L\sigma^2}{n_{\min}} + \frac{4N\gamma^2 I^2 G^2 L^2}{n_{\min}} + \frac{2\gamma N I^2 G^2 L}{n_{\min}K}.$$

---

[2]The gradient and the Hessian of $\hat{f}$ are with respect to $\hat{\mathbf{X}}$.

[3]Please refer to Appendix C for detailed explaination.

Table 1: Statistics of four datasets.

	# Clients	# Samples	# Samples Per Client	Feature Heat Dispersion
MovieLens	6,040	1,000,209	165	4,331
Sent140	1,473	79,050	54	1,451
Amazon	1,870	123,147	66	232
Alibaba	49,023	16,864,641	344	3,142

When $T > n_{\min}K^3/N$ and $\gamma = \Theta\left(\sqrt{\frac{n_{\min}K}{NT}}\right)$, we have

$$\mathbb{E}\left[\frac{1}{T}\sum_{i=1}^{T}\nabla f(\mathbf{X}^t)^\top \mathbf{D}\nabla f(\mathbf{X}^t)\right] \leq O\left(\sqrt{\frac{N}{n_{\min}KT}}\right)$$

Proof. Please refer to Appendix C. $\square$

5 Evaluation

In this section, we extensively evaluate the performance of FedSubAvg over several datasets with different feature heat dispersion. We also introduce FedAvg and its variants, including FedProx and Scaffold, as baselines for comparsion.

5.1 Experimental Setups

We choose the following tasks and models for evaluation. The statistics about clients and samples, as well as the feature heat dispersion are shown in Table 1.

LR for rating classification: We perform a rating classification task over the MovieLens-1M dataset [23], which contains 6,040 users, 3,883 movies, and 1,000,209 samples. We preprocess the dataset to be suitable for binary classification. In particular, the original user ratings of movies range from 0 to 5. We label the samples with the ratings of 4 and 5 to be positive and label the rest to be negative. We randomly select 20% of the samples as the test dataset and leave the remaining 80% as the training dataset for FL. The task is to predict whether users will rate a given movie to be positive based on the user's gender and age and on the movie ID. We first encode gender, age, movie, gender cross movie, and age cross movie, based on the one-hot encoder. Next, the features are input into a logistic regression (LR) model to predict the label.

LSTM for sentiment analysis: We perform a text sentiment classification task on the Sentiment140 dataset [24], which comprises 1,600,000 tweets collected from 659,775 twitter users. In this task, we use a two-layer long short-term memory (LSTM) network with 100 hidden units and an embedding layer as the binary classifier, where the embedding dimension is set to 25. We naturally partition this dataset by letting each Twitter account correspond to a client. We keep only the clients who hold more than 40 samples and get 1,473 clients in total. We randomly select 20% of the samples as the test dataset and leave the remaining 80% as the training set for FL.

DIN for CTR prediction: We perform a click-through rate (CTR) prediction task on the Amazon electronics dataset and an Alibaba industrial dataset. The Amazon dataset contains 1,689,188 reviews contributed by 192,403 users for 63,001 items. The ratings range from 0 to 5. We label the samples with the rating of 5 to be positive and label the rest to be negative. We naturally partition this dataset by letting each Amazon user correspond to a client. For each client, we take the user ID, the historical sequence of positively rated product as the input to predict the label. We keep only the clients who hold more than 40 samples and get 1,870 clients in total. We select samples with the timestamps more than 1,385,000,000 as the test dataset and leave the remaining samples as the training set. The Alibaba dataset is built from 30-day impression and click logs of $49,023$ Taobao users from June 15, 2019 to July 15, 2019. For a certain Taobao user, we leverage its click behaviors in previous 14 days as historical data to predict its click and non-click behaviors in the following 1 day. We leave out the behaviors within the last 1 day as the target items of the test set while putting the other samples into the training set. For both datasets, we take the deployed deep interest network (DIN) [25] in Alibaba as the model, where the embedding dimension is set to 18.

| (a) MovieLens | (b) Sentiment140 | (c) Amazon | (d) Alibaba |

Figure 3: Train losses or test AUCs of FedSubAvg and the baselines on different datasets.

Table 2: Number of communication rounds to reach the target train loss or test AUC with different algorithms. #+ indicates that the target was not reached even after # rounds.

	CentralSGD	FedAvg	FedProx	Scaffold	FedSubAvg
MovieLens	180	170	170	180	**100**
Sent140	980	1,000+	1,000+	1,000+	**260**
Amazon	**20**	200+	200+	200+	53
Alibaba	**265**	5,000+	5,000+	5,000+	610

We use the following four baselines for comparison.

- **FedAvg** averages the local model updates from the participating clients to update the global model.

- **FedProx** is the first variant of FedAvg. We set the coefficient of the proximal term to 0.01 throughout the evaluation.

- **Scaffold** is another important variant of FedAvg. The key difference from FedAvg is that each client keeps a variate to control the local model updates in Scaffold. However, the size of the control variate is equal to size of the full model, which is prohibitively inefficient for the learning tasks with large-scale full models. Therefore, for the CTR prediction tasks, we make an approximation to Scaffold. In particular, the cloud server performs the controlled update step every round by weighted averaging the historical updates. Please refer to Appendix D.2 for details.

- **CentralSGD** runs the standard SGD algorithm to train the global model using the whole dataset, sets the number of iterations in each round as I, and sets the batch size to the sum of the selected clients' local batch sizes in each round. This ensures the same amount of data per round with the distributed algorithms.

Regarding the experimental settings, we choose mini-batch SGD as the optimization algorithm. For the tasks of rating classification and sentiment analysis, $K = 50$ clients are randomly chosen per round as default; and for the CTR prediction tasks, K is set to 100 as default. The settings of the other hyperparameters are deferred to Appendix D.3.

5.2 Evaluation Results

We first present the results of FedSubAvg and the baselines under the default K. We then vary K to show its impact.

FedSubAvg vs. Baselines: For the rating classification on the MovieLens dataset and the sentiment analysis on the Sent140 dataset, we plot the train loss in Figure 3(a) and Figure 3(b); and for the CTR prediction on Amazon and the Alibaba dataset, we plot the test area under the curve (AUC)[4] in Figure 3(c) and 3(d). In addition, we measure the convergence rates of different algorithms by counting the communication rounds to reach a target train loss or test AUC. We set the target loss in the rating classification (resp., the sentiment analysis) to be the minimum loss of CentralSGD, which is 0.325 (resp., 0.380); and we set the target test AUC to be 0.6 in two CTR prediction tasks. The results are listed in Table 2.

---

[4]The positive and negative samples in CTR datasets (especially the Alibaba dataset) are extremely uneven. Even if all the samples are predicted to be negative (or positive), the train loss is very small. As a result, the train losses of different algorithms are hard to distinguish, and we choose to plot the test AUCs instead.

| | (a) MovieLens | (b) Sentiment140 | (c) Amazon | (d) Alibaba |

Figure 4: Train losses or test AUCs of FedSubAvg on different datasets with the varying number of selected clients per round K.

Table 3: Number of communication rounds for FedSubAvg to reach the target train loss or test AUC with the varying number of selected clients per round K.

	MovieLens			Sent140			Amazon			Alibaba		
K	10	30	50	10	30	50	20	60	100	20	60	100
Rounds	100	110	100	420	270	260	95	57	53	3,469	1,030	610

From Figure 3 and Table 2, we observe that FedSubAvg consistently outperforms FedAvg and FedProx. Specifically, (1) in the rating classification, FedSubAvg always has the smallest train loss during FL and reaches the target at the 100-th communication round, $1.7\times$ faster than FedAvg and FedProx, and $1.8\times$ faster than Scaffold and CentralSGD; (2) in the sentiment analysis, FedSubAvg still has the smallest train loss during FL and reaches the target at the 260-th round, $3.77\times$ faster than CentralSGD, while FedAvg, FedProx, and Scaffold cannot reach the target even in 1,000 rounds; (3) in the CTR prediction on the Amazon dataset, FedSubAvg performs the best among all the FL algorithms. FedSubAvg achieves the highest AUC of 0.641 in 200 rounds, decreasing by 0.013 in terms of AUC compared with the ideal CentralSGD. In contrast, FedAvg achieves the highest AUC of 0.523, FedProx achieves the highest AUC of 0.519, and Scaffold achieves the highest AUC of 0.514. In addition, FedSubAvg reaches the target test AUC at the 53-th round, while the other FL algorithms cannot reach the target even after 200 rounds; and (4) in the CTR prediction on the Alibaba dataset, FedSubAvg still outperforms all the other FL algorithms. FedSubAvg achieves the highest AUC of 0.626 in 5,000 rounds, decreasing by 0.016 compared with CentralSGD. In contrast, FedProx achieves the highest AUC of 0.514, FedAvg achieves the highest AUC of 0.509, and Scaffold achieves the highest AUC of 0.507. Moreover, FedSubAvg reaches the target test AUC at the 610-th round, whereas the other FL algorithms cannot reach the target even after 5,000 rounds.

Impact of participating clients: We next evaluate the impact of the number of selected clients K per round on FedSubAvg. We set $K =$10, 30, and 50 for the rating classification and the sentiment analysis, and set $K = 20$, 60, and 100 for the CTR prediction. We plot the results in Figure 4 and record the minimum number of rounds to reach the target in Table 3. We observe that FedSubAvg with a larger K generally converges much faster, which validates the speedup with respect to K. (1) In the rating classification, FedSubAvg with different K behaves somewhat uniformly. This is because a larger K improves the convergence by reducing the variance of the global model update, while for such a simple convex optimization scenario, the variance is already small enough with $K = 10$; (2) in the sentiment analysis, FedSubAvg with $K = 50$ reaches the target train loss $1.62\times$ faster than FedSubAvg with $K = 10$; (3) in the CTR prediction on the Amazon dataset , FedSubAvg with $K = 100$ reaches the target test AUC $1.79\times$ faster than FedSubAvg with $K = 20$; and (4) in the CTR prediction on the Alibaba dataset, FedSubAvg with $K = 100$ reaches the target test AUC $5.69\times$ faster than FedSubAvg with $K = 20$.

6 Conclusion

In this work, we studied federated submodel optimization over non-i.i.d. data with feature heat dispersion. We proposed FedSubAvg, which ensures the expectation of the global update of each model parameter is equal to the average of the local updates of the clients who involve it. We also proved that FedSubAvg works as a preconditioner to improve collaborative training and thoroughly analyzed the convergence. Empirical studies demonstrated the remarkable superiority of FedSubAvg over FedAvg and its variants.

References

[1] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Proceedings of AISTATS*, pages 1273–1282, 2017.

[2] Andrew Hard, Kanishka Rao, Rajiv Mathews, Françoise Beaufays, Sean Augenstein, Hubert Eichner, Chloé Kiddon, and Daniel Ramage. Federated learning for mobile keyboard prediction. *CoRR*, abs/1811.03604, 2018.

[3] Mu Li, David G. Andersen, Jun Woo Park, Alexander J. Smola, Amr Ahmed, Vanja Josifovski, James Long, Eugene J. Shekita, and Bor-Yiing Su. Scaling distributed machine learning with the parameter server. In *OSDI*, pages 583–598. USENIX Association, 2014.

[4] Xiangru Lian, Wei Zhang, Ce Zhang, and Ji Liu. Asynchronous decentralized parallel stochastic gradient descent. In *ICML*, Proceedings of Machine Learning Research, pages 3049–3058. PMLR, 2018.

[5] Hanlin Tang, Xiangru Lian, Ming Yan, Ce Zhang, and Ji Liu. D^2: Decentralized training over decentralized data. In *ICML*, Proceedings of Machine Learning Research, pages 4855–4863. PMLR, 2018.

[6] Hao Yu and Rong Jin. On the computation and communication complexity of parallel SGD with dynamic batch sizes for stochastic non-convex optimization. In *ICML*, Proceedings of Machine Learning Research, pages 7174–7183. PMLR, 2019.

[7] Ahmed Khaled, Konstantin Mishchenko, and Peter Richtárik. First analysis of local GD on heterogeneous data. *CoRR*, abs/1909.04715, 2019.

[8] Sebastian U. Stich and Sai Praneeth Karimireddy. The error-feedback framework: Better rates for SGD with delayed gradients and compressed communication. *CoRR*, abs/1909.05350, 2019.

[9] Sebastian U. Stich. Local SGD converges fast and communicates little. In *ICLR (Poster)*. OpenReview.net, 2019.

[10] Jianyu Wang and Gauri Joshi. Cooperative SGD: A unified framework for the design and analysis of communication-efficient SGD algorithms. *CoRR*, abs/1808.07576, 2018.

[11] Hao Yu, Sen Yang, and Shenghuo Zhu. Parallel restarted SGD with faster convergence and less communication: Demystifying why model averaging works for deep learning. In *Proceedings of AAAI*, pages 5693–5700, 2019.

[12] Yae Jee Cho, Jianyu Wang, and Gauri Joshi. Client selection in federated learning: Convergence analysis and power-of-choice selection strategies. *CoRR*, abs/2010.01243, 2020.

[13] Xiang Li, Kaixuan Huang, Wenhao Yang, Shusen Wang, and Zhihua Zhang. On the convergence of fedavg on non-iid data. In *ICLR*. OpenReview.net, 2020.

[14] Sai Praneeth Karimireddy, Satyen Kale, Mehryar Mohri, Sashank J. Reddi, Sebastian U. Stich, and Ananda Theertha Suresh. SCAFFOLD: stochastic controlled averaging for federated learning. In *ICML*, Proceedings of Machine Learning Research, pages 5132–5143. PMLR, 2020.

[15] Dmitrii Avdiukhin and Shiva Prasad Kasiviswanathan. Federated learning under arbitrary communication patterns. In *ICML*, Proceedings of Machine Learning Research, pages 425–435. PMLR, 2021.

[16] Yann Fraboni, Richard Vidal, Laetitia Kameni, and Marco Lorenzi. Clustered sampling: Low-variance and improved representativity for clients selection in federated learning. In *ICML*, Proceedings of Machine Learning Research, pages 3407–3416. PMLR, 2021.

[17] Xinran Gu, Kaixuan Huang, Jingzhao Zhang, and Longbo Huang. Fast federated learning in the presence of arbitrary device unavailability. *CoRR*, abs/2106.04159, 2021.

[18] Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated optimization in heterogeneous networks. In *MLSys*. mlsys.org, 2020.

[19] Sai Praneeth Karimireddy, Satyen Kale, Mehryar Mohri, Sashank J. Reddi, Sebastian U. Stich, and Ananda Theertha Suresh. SCAFFOLD: stochastic controlled averaging for federated learning. In *ICML*, Proceedings of Machine Learning Research, pages 5132–5143. PMLR, 2020.

[20] Chaoyue Niu, Fan Wu, Shaojie Tang, Lifeng Hua, Rongfei Jia, Chengfei Lv, Zhihua Wu, and Guihai Chen. Billion-scale federated learning on mobile clients: a submodel design with tunable privacy. In *MobiCom*, pages 31:1–31:14. ACM, 2020.

[21] Yann N. Dauphin, Harm de Vries, and Yoshua Bengio. Equilibrated adaptive learning rates for non-convex optimization. In *NIPS*, pages 1504–1512, 2015.

[22] Hao Yu, Rong Jin, and Sen Yang. On the linear speedup analysis of communication efficient momentum SGD for distributed non-convex optimization. In *ICML*, Proceedings of Machine Learning Research, pages 7184–7193. PMLR, 2019.

[23] F. Maxwell Harper and Joseph A. Konstan. The movielens datasets: History and context. *ACM Trans. Interact. Intell. Syst.*, 5(4):19:1–19:19, 2016.

[24] Tapan Sahni, Chinmay Chandak, Naveen Reddy Chedeti, and Manish Singh. Efficient twitter sentiment classification using subjective distant supervision. In *COMSNETS*, pages 548–553. IEEE, 2017.

[25] Guorui Zhou, Xiaoqiang Zhu, Chengru Song, Ying Fan, Han Zhu, Xiao Ma, Yanghui Yan, Junqi Jin, Han Li, and Kun Gai. Deep interest network for click-through rate prediction. In *KDD*, pages 1059–1068. ACM, 2018.