Mantis: Interleaved Multi-Image Instruction Tuning

Abstract

Large multimodal models (LMMs) have shown great results in single-image vision language tasks. However, their abilities to solve multi-image visual language tasks is yet to be improved. The existing LMMs like OpenFlamingo, Emu2, and Idefics gain their multi-image ability through pre-training on hundreds of millions of noisy interleaved image-text data from the web, which is neither efficient nor effective. In this paper, we aim to build strong multi-image LMMs via instruction tuning with academic-level resources. Therefore, we meticulously construct MANTIS-INSTRUCT containing 721K multi-image instruction data to train a family of MANTIS models. The instruction tuning empowers MANTIS with different multi-image skills like co-reference, comparison, reasoning, and temporal understanding. We evaluate MANTIS on 8 multi-image benchmarks and 6 single-image benchmarks. MANTIS-Idefics2 can achieve SoTA results on all the multi-image benchmarks and beat the strongest multi-image baseline, Idefics2-8B by an average of 13 absolute points. Notably, Idefics2-8B was pre-trained on 140M interleaved multi-image data, which is 200x larger than MANTIS-INSTRUCT. We observe that MANTIS performs equivalently well on the held-in and held-out benchmarks, which shows its generalization ability. We further evaluate MANTIS on single-image benchmarks and demonstrate that MANTIS also maintains a strong single-image performance on par with CogVLM and Emu2. Our results show that multi-image abilities are not necessarily gained through massive pre-training, instead, they can be gained by low-cost instruction tuning. The training and evaluation of MANTIS has paved the road for future work to improve LMMs' multi-image abilities.

Figure 1: Mantis can accept interleaved text-image to perform different multi-image tasks like coherence, comparison, logical reasoning, and temporal understanding. Mantis achieves state-of-the-art performance on the five multi-image benchmarks and preserves abilities for single-image tasks.

1 Introduction

Large Multimodal Models (LMMs) have advanced significantly in recent years. Both closed-source models like GPT-4V (Achiam et al., 2023), Gemini (Team et al., 2023), Reka (Ormazabal et al., 2024), MM1 (McKinzie et al., 2024) and open-source models like LLaVA (Liu et al., 2023c;b), LLaVA-NeXT (Liu et al., 2024), BLIP (Li et al., 2023c), CogVLM (Wang et al., 2023), Idefics (Laurençon et al., 2023) have shown strong visual-language understanding and generation capabilities in single-image tasks like VQA (Antol et al., 2015), TextVQA (Singh et al., 2019b), GQA (Hudson & Manning, 2019), etc. Despite the significant interest in improving LMMs' performance on single-image vision-language tasks, relatively less work attempts to improve LMMs' capability to solve multi-image vision-language tasks. To the best of our knowledge, only a few open-source models (e.g. Idefics (Laurençon et al., 2023), OpenFlamingo (Awadalla et al., 2023), Emu2 (Sun et al., 2023)) and VILA (Lin et al., 2023c) support multi-image inputs.

We argue that multi-image visual ability is also a crucial in real-world applications. Specifically, we categorize the ability into four major skills we want the LMM to encompass: (1) **Co-reference**: understanding the references like "second image" in the natural language expression and grounding it on the referred image to generate a response. (2) **Comparison**: capturing the nuances and commonalities between several images. (3) **Reasoning**: capturing the information across multiple images and reasoning over these multiple pieces to derive the response. (4) **Temporal understanding**: observing multiple frames of a video or a scene to understand the temporal information like actions, behaviors, interactions, etc.

The existing multi-image LMMs like Idefics (Laurençon et al., 2023), OpenFlamingo (Awadalla et al., 2023), Emu2 (Sun et al., 2023), MM1 (McKinzie et al., 2024), VILA (Lin et al., 2023c) heavily rely on pre-training on a massive interleaved image-text web documents like MMC4 (Zhu et al., 2024), Obelics (Laurençon et al., 2023). For example, MMC4 contains 500 million examples, while Obelics contains 140 million examples. Such a pre-training procedure would require a massive amount of computation, which hampered its adoption in most open-source LMM training pipelines. In this paper, we attempt to build LMMs with academic-level resources to support interleaved multi-image inputs. Specifically, we made a few efforts along this line:

Dataset: We create the first multi-image instruction-tuning dataset MANTIS-INSTRUCT. It has a total of 721K instances, consisting of 14 subsets to cover all the multi-image skills. Among the 14 subsets, 10 subsets are from the existing datasets. For example, `NLVR2` (Suhr et al., 2018), `IconQA` (Jhamtani & Berg-Kirkpatrick, 2018), etc are used to cover 'reasoning' skill; `DreamSim` (Fu et al., 2023), `Birds-to-Words` (Forbes et al., 2019), etc are used to cover 'comparison' skill; `NExT-QA` (Xiao et al., 2021), `STAR` (Wu & Yu, 2021), etc are used to cover 'temporal understanding' skill. Additionally, 4 new subsets are newly curated, where `LLaVA-665k-multi`, and `LRV-multi` are used to to cover the 'coref' skill, **Contrast-Caption**, and **Multi-VQA** are used to broaden the 'reasoning' skill. The interleaving image placeholders are inserted into the text under various heuristics.

Architecture: Similar to LLaVA (Liu et al., 2024), we start from a pre-trained language model like LLaMA-3 (AI@Meta, 2024) or Fuyu (Adept AI, 2023) and a vision transformer encoder from CLIP (Radford et al., 2021) or SigLIP (Zhai et al., 2023). We use the same multimodal projector as LLaVA to map the vision embeddings to the text embeddings space to simply concatenate them with the text embeddings. We also define a text-image interleaving format: "...(image {i}: `<BOI>`image embeddings`</EOI>`)...", where `<BOI>` and`</EOI>` are the image delimiters. We explored multiple instantiations and found this optimal design.

Evaluation: We manually curate a new challenging dataset Mantis-Eval to cover several multi-image skills. This evaluation can help us better analyze LMMs' multi-image abilities.

We train MANTIS by combining MANTIS-INSTRUCT with another 268K single-image vision-language data to balance the multi-image and single-image abilities. To evaluate the multi-image skills, we adopt 8 benchmarks including NLVR2 (Suhr et al., 2018), BLINK (Fu et al., 2024), MVBench (Li et al., 2023d), Mantis-Eval, etc. to cover all the mentioned skills. We include 15 competitive baseline models including single-image LMMs like LLaVA-Next (Liu et al., 2024), Qwen-VL (Bai et al., 2023) and multi-image LMMs like GPT-4V, Idefics1/2, etc. For single-image LMMs, we merge multiple images horizontally as a single-image input. By training on 16 x A100 for 36 hours, MANTIS achieves state-of-the-art performance on all the multi-image tasks, while preserving competitive performance in single-image tasks. Notably, MANTIS-Idefics2 outperforms

the strongest baseline Idefics2 (Laurençon et al., 2023) by an average of 13 absolute points on the 7 avaialble benchmarks (excluding MileBench), where Idefics2 is multi-image pre-trained, showcasing the effectiveness of multi-image instruction-tuning. The held-in and held-out results are equivalently strong, which shows the generalization ability of MANTIS.

These results are encouraging because we show that the low-cost instruction tuning on 721K high-quality data can lead to a much better generalization performance than other LMMs intensively pre-trained on 100x larger datasets. Mantis also preserves its strong performance of single-image tasks and is on par with CogVLM (Wang et al., 2023) and Emu2 (Sun et al., 2023). We also present insights on the architecture selection and inference approaches based on the results in section 3. We believe MANTIS-INSTRUCT can serve as an essential baseline for future studies on multi-image LMMs due to its simplicity and low cost. We will release all the code, data, and models to help with the reproducibility of our results.

2 Mantis: Interleaved Multi-Image Instruction Tuning

2.1 Method

Model Architecture: Most existing LMMs do not support multi-image inputs, either due to the architecture design (Huang et al., 2016; Li et al., 2023c), or the lack of associated code support (Peng et al., 2023; Adept AI, 2023). To enable multi-image training and inference, we have modified the LLaVA architecture and added code support for it. Idefics2 (Laurenccon et al., 2024) already supports multi-image as inputs naturally, we thus inherit their structure.

Image Context Length: How many images can a multi-image supported model accept? This is limited by both the LLM backbone's max token length and the number of image tokens the vision encoder generated. For the LLaVA architecture, each image consumes a fixed $(336/14)^2 = 576$ image tokens. For Llama3 with a maximum window size of 8K, we can feed at most 14 images. For Idefics2, the number of tokens per image is resampled to be 64 tokens only due to the existence of perceiver, which is pretty efficient. Given 8K context length, it can accept 128 images at most, even more than some video models.

Interleaving Text-Image: A proper text-image interleaving format can help acquire multi-image understanding and reasoning ability. We contend that a good text-image interleaving format should: (1) mark boundaries between images clearly, and (2) denote the serial number of images. Following this principle, we designed our interleaving format as follows: "`(image {i}: <BOI><image><EOI>)`", where `<BOI>` is the begin of image token and `<EOI>` is the end of image token. `<image>` is the placeholder for image patches. This format adds clear separators between images, and gives serialized information of the image through "`image {i}`". In practice, we set `<BOI>` and `<EOI>` to be `<Image>` and `</Image>` respectively. Previous work also demonstrates its effectiveness through a comprehensive ablation study (Wu et al., 2024).

2.2 Mantis-Instruct: A large scale multiple image question answering dataset

We construct MANTIS-INSTRUCT from multiple publicly available datasets. Detailed statistics are shown in Table 1 with several newly curated subset by us. We use a similar dataset format with LLaVA's, where each data item contains multiple images and multiple turns of QA pairs are gathered. We demonstrate some examples of our newly curated subset in Figure 2. We report the number of examples, the number of images per item, the average conversation turns, and the average length. MANTIS-INSTRUCT is collected based on the 4 multi-image skills. We here describe the gathered subsets for each skill briefly. Construction details can be found in subsection A.1.

Co-reference requires the model to create a mapping from natural language references, such as "second image," to the actual images in the input. It does not require the model to infer across multiple images. To achieve this, we constructed `LLaVA-665k-multi` and `LRV-multi` by concatenating multiple single-image conversations into a multi-image sequence. Deliberately, we included natural language references like "For the second image" for each question.

Subsets	Skill	# Instance	# Avg-I	# Max-I	# Turns	Length^T	Length^{T+I}
		Multi-Image Reasoning Datasets					
LLaVA-665k-multi♣	Coref	313K	2.0	4	21.4	558	1710
LRV-multi♣	Coref	8K	3.5	9	83.4	2234	4251
CoInstruct	Compare	151K	2.7	4	7.5	314	1620
Dreamsim	Compare	16K	3.0	3	2.0	103	1831
Spot-the-Diff	Compare	8K	2.0	2	4.0	121	1273
Birds-to-Words	Compare	3K	2.0	2	2.0	101	1253
NLVR2	Reason	86K	2.0	2	2.0	105	1257
IconQA	Reason	64K	2.4	6	2.0	71	1454
Contrast-Caption♣	Reason	36K	3.8	8	7.6	871	3067
ImageCoDe	Reason	17K	10	10	1.0	126	5886
Multi-VQA♣	Reason	5K	4.0	6	11.0	1102	3417
VIST	Temporal	7K	20.3	50	9.7	530	12238
NExT-QA	Temporal	4K	8.0	8	17.6	572	5180
STAR	Temporal	3K	8.0	8	30.2	961	5569
Total	-	721K	4.7	50	14.4	555	3584
		Single-Image Reasoning Datasets					
DVQA	Doc	200K	1.0	1	40.0	304	880
DocVQA	Doc	39K	1.0	1	2.0	62	638
ChartQA	Chart	28K	1.0	1	2.0	66	642
Total	-	268K	1.0	1	14.7	144	720

Table 1: The statistics of MANTIS-INSTRUCT. We list the number of examples, average images per example, maximum image per example, average turns, average text token lengths, and average text+image token lengths. ♣ means the new subsets we constructed in this paper. Here we use Llava's tokenizer and assume each image occupies 576 image tokens, which is the number of tokens for each image. Here "Avg Length^T" denotes the average number of tokens for the text part, while "Avg Length$^{T\&I}$" means the average number of tokens of text and images in total. Heuristics about how each subset is curated can be found in subsection A.1.

Please generate 10 independent QA pairs. Each question shall involve at least 2 images to answer. Try to cover different ability like reasoning, planning, common sense understanding, etc. Be creative with your questions and **make sure the answers require integration of information from multiple images**. Use "image i" to refer to the i-th image in your questions.

Output format:
Question: First question?
Answer: The answer to the first question.
Question: Second question?
Answer: The answer to the second question.
...

Table 2: Propmt template used to curate the `Multi-VQA` subset.

Comparison requires the model to not only have good co-reference ability but also be able to compare and understand differences across multiple images. We gather `Co-Instruct`, `Dreamsim`, `Spot-the-Diff`, and `Birds-to-Words` together to enhance the model's comparison ability. They cover a wide range of topics such as image quality, visual similarity, and difference description.

Reasoning requires the model to further make inferences by combining its world knowledge with the information collected using the co-reference and comparison ability. It distinguishes from the comparison

Figure 2: Illustrations of MANTIS-INSTRUCT datasets from Contrast-Captioning and Multi-VQA. Contrastive-Captioning is constructed from existing image captioning datasets to enhance LMM's multi-image 'co-reference' ability. Multi-VQA is GPT-4V synthesized multi-turn multi-image data used to enhance LMM's multi-image 'reason' ability.

skill by introducing more complex human instruction associated with the images. We gather `NLVR2`, `IconQA`, `Contrast-Caption` by reformatting captioning datasets, `ImageCoDe`, and our self-collected `Multi-VQA` to further equip the model with reasoning ability. The topics include logical reasoning, counting, image matching, image retrieval, and free-form multi-image QA. `Multi-VQA` is synthesized by prompting GPT-4V, where the prompt template is shown in Table 2.

Temporal Understanding requires the model to understand temporal image sequences such as videos, comics, etc. We include a small number of video understanding datasets (14K), `VIST`, `NExT-QA`, and `STAR`, to activate the model's temporal understanding ability. We contend that a model with the above 3 multi-image skills shall be easily tuned to understand image sequences.

2.3 Heuristics of data curation

Similar to visual instruction tuning (Liu et al., 2023c), data curation is an important step to ensure good performance. During the curation, we have found some heuristics that can improve the performance. We list them below.

1. **Conflicts between short answers and long answers.** Many datasets we collected are domain-specific, and some of them are classification tasks like NLVR2 (Suhr et al., 2018) and DreamSim (Fu et al., 2023). For these datasets, we convert them into multiple-choice QA format to avoid conflicts between repeated short-answers and some long answers from other datasets.

2. **Addition of image denotation in the text for each question.** We manually add image denotations like "the first image", "image 2", "the right image", etc. to each question in our dataset to make sure the question involved with multiple images is clear to answer.

3. **Positions of the "<image>" placeholder.** For each item with multiple images, we write some rules to randomly put the image placeholders at the beginning of the first question or the end of the first question. This technique is also used by the curation LLaVA-665k (Liu et al., 2023b).

3 Experiments

In this section, we aim to evaluate MANTIS's ability on both multi-image and single-image vision-language tasks. For multi-image tasks, depending on whether the LMM can handle multiple images, we either concatenate multiple images ('merge') horizontally as a single image or feed multiple images as a 'sequence' to the model. We have trained four model variants listed in Table 3, where we list the architecture and

dataset details. Mantis-CLIP and Mantis-SigLIP only adopt the CC3M 560K subset for feature alignment. Mantis-Flamingo and Mantis-Idefics2 are initialized from OpenFlamingo and Idefics2, respectively, which have been intensively pre-trained on the multi-image corpus. We also include Mantis-Fuyu to investigate the significance of vision encoder in the LMM architecture. After this pre-training and preparation, we fine-tune them on MANTIS-INSTRUCT to get Mantis.

Mantis-Models	V-Encoder	LLM-backbone	Pre-Training (PT)	PT size	Fine-Tuning	# Tokens / I
Mantis-Fuyu	-	Persimmon-8B	Unknown	Unknown	Mantis-Instruct	[1,2304]
Mantis-Flamingo	CLIP	MPT-7B	MMC4, LAION	2421M	Mantis-Instruct	576
Mantis-CLIP	CLIP	LLaMA-3-8B	CC3M subset	0.56M	Mantis-Instruct	576
Mantis-SIGLIP	SigLIP	LLaMA-3-8B	CC3M subset	0.56M	Mantis-Instruct	576
Mantis-Idefics2	SiGLIP	Mistral-7B-v0.1	OBELICS, Cauldron	143M	Mantis-Instruct	64

Table 3: Architecture and training details of mantis model family. "I" for "Image" in last column.

3.1 Training Details

For MANTIS-CLIP and MANTIS-SigLIP, we first pre-train the multimodal projector on LLaVA pre-train data, where the learning rate is set to 1e-3, the batch size is set to 256. After pre-training, we fine-tune the 2 models on the MANTIS-INSTRUCT. For MANTIS-Fuyu, MANTIS-Flamingo and MANTIS-Idefics2, we directly fine-tune them on MANTIS-INSTRUCT since they have already been pre-trained on millions of data.

During the fine-tuning, we train each model on the data for 1 epoch, with a batch size of 128. The maximum context length is set to 8192. The learning rate is all set to 1e-5, except for Idefics2, where the learning rate is set to 5e-6 to better preserve its original knowledge. We set the warmup ratio to be 0.03 and use a cosine learning rate scheduler. We speed up our training and inference with Flash-attention2 (Dao, 2023). We use DeepSpeed Zero-3 (Aminabadi et al., 2022) for full fine-tuning. We apply QLoRA (Dettmers et al., 2023) along with DoRA (yang Liu et al., 2024) to more efficiently do comprehensive ablation studies under limited resources. All full fine-tuning ran on 16 A100 GPUs while the ablation study ran on 8 A100 GPUs.

3.2 Baselines

For 'merge' evaluation, we include BLIP-2-13B (Li et al., 2023c), InstructBLIP-13B (Dai et al., 2023), Qwen-VL-Chat (Bai et al., 2023), LLaVA-1.5-7B (Liu et al., 2023c), LLaVA-1.6-7B (Liu et al., 2024), Kosmos2 (Peng et al., 2023), and Fuyu-8B (Adept AI, 2023). For 'sequence' evaluation, we include OpenFlamingo (Awadalla et al., 2023), Otter (Li et al., 2023b), VideoLLaVA (Lin et al., 2023a), Emu2-Chat-34B (Sun et al., 2023), VILA (Lin et al., 2023b), Idefics1 (Laurençon et al., 2023), Idefics2 (Laurençon et al., 2023), GPT-4V (Achiam et al., 2023). Additionally, for single-image tasks, we include InstructBLIP-7B-Vicuna (Dai et al., 2023), Yi-VL-6B (AI et al., 2024).

3.3 Evaluation Benchmarks

For multi-image tasks, we use 2 held-in benchmarks: NLVR2 (Suhr et al., 2018) and Qbench (Wu et al., 2023a); and 3 held-out benchmarks: Mantis-Eval, BLINK (Fu et al., 2024), and MVBench (Li et al., 2023d). We report detailed statistics in Table 4.
NLVR2 (Suhr et al., 2018) evaluates the model's ability to conduct logical reasoning across the contents of images. It asks the model to compare the contents of the two given images and judge whether a given statement is correct or not. All questions are multiple-choice. We use the test-public split for evaluation.
Qbench (Wu et al., 2023a) is a benchmark evaluating whether LMMs can properly judge and compare the quality of a benchmark. Q-bench aims to evaluate the low-level visual abilities of LMMs, such as judging the image quality. All questions are multiple-choice. In our experiments, we evaluate the Qbench2-A2-pair dev set, where a low-level visual question is asked based on multiple image contents.
Mantis-Eval consists of 217 multiple-image reasoning examples that cover different topics, including size perceptions, weight comparisons, etc. This dataset is carefully curated by our annotators, where images

Benchmarks	Skill	Type	# Instances	# Avg-I	# Max-I	Lenght^{T+I}
NLVR2†	Reason	MCQ	6,967	2.0	2	1,190
Q-Bench†	Comparison	MCQ	1,000	2.0	2	1,167
Mantis-Eval	Reason & Coref	MCQ & Short	217	2.5	5	1,455
BLINK	Reason	MCQ	1,901	1.9	4	1,129
MVBench	Temporal	MCQ	4,000	8.0	8	4,625
MileBench	Mixed	MCQ	6,440	15.2	109	9,294
MuirBench	Mixed	MCQ	2,600	4.3	9	2,502
MMIU	Mixed	MCQ	11,600	6.6	32	3,852

Table 4: Statistics of the evaluation dataset. Held-in benchmarks, NLVR2 and Q-Bench, are marked with †notation. The rest of them are held-out benchmarks. "Mixed" means a .

are acquired via Google Search, and then come up with a proper question which requires understanding the contents in the two images well to answer. Mantis-Eval contains both multiple-choice and short-answer questions. We report results in the test split.

BLINK (Fu et al., 2024) is a benchmark on core visual perception abilities, where humans can solve most tasks "within a blink" (e.g., relative depth estimation, visual correspondence, forensics detection, and multi-view reasoning). Some questions in the benchmark involved multiple images, such as image similarity comparison. We report results in the validation set of the benchmark.

MVBench (Li et al., 2023d) is a comprehensive multimodal video understanding benchmark covering 20 challenging video tasks. The questions cannot be solved with a single frame, necessitating understanding an image sequence to solve the questions in the benchmark. We extract 8 frames per video for the evaluation. We report results in test split.

MileBench (Song et al., 2024) is a novel benchmark designed to test the multimodal long-context capabilities of MLLMs. It comprises realistic evaluation and diagnostic evaluation. The former involves tasks like temporal understanding and semantic multi-image comprehension. The later diagnostic evaluation involves TextNeedle and ImageNeedle retrieval tasks. We only reported the performance of the realistic evaluation. The results of the diagnostic evaluation can be found in MileBench's paper.

MuirBench (Wang et al., 2024a) is a comprehensive benchmark consisting of 12 diverse multi-image tasks, such as scene understanding, ordering, etc. It contains 2,600 multiple-choice questions with 11,264 images involved in total. We report the overall average performance across the 12 tasks.

MMIU (Meng et al., 2024) is a multi-image evaluation benchmark encompassing 7 types of multi-image relationships, 52 tasks, 77K images, and 11K multiple-choice questions. We report the overall average performance across all the tasks.

3.4 Results on Multi-Image Tasks

We report our results on the multi-image task in Table 5. We put the results of GPT-4V/o at the top of the table as it's a closed-source LMM. We can see that our best version Mantis-Idefics2 almost matches the overall performance of GPT-4V. We put comparison results between MANTIS and other open-source LMMs, along with the insights derived in the following paragraphs.

Mantis performs well on held-in evaluation: We found that Mantis-SigLIP without any multi-image pre-training can already achieve the best-known performance on these two benchmarks. Mantis-Idefics2 has better performance of 89.71 and 75.20 on NLVR2 and Q-Bench respectively, marking it the SoTA for these two tasks. Notably, Mantis-Idefics2 also beats the Idefics2 by 2.84 points, which was already trained on NLVR2. It shows the cross-task benefits of our instruction tuning. The remarkable performance on these 2 benchmarks demonstrates that Mantis has gained strong ability in multi-image logical reasoning and low-level vision understanding.

Mantis generalizes well on held-out evaluation: We show that our models can attain strong performance on the 6 held-out benchmarks. Mantis-SigLIP achieves 59.45 on Mantis-Eval, and Mantis-Idefics2 achieves 49.05, and 51.38 on BLINK and MVBench respectively, surpassing all other baselines on these held-out

Models	Size	NLVR2	Q-Bench	Mantis-Eval	BLINK	MVBench	MileBench	MuirBench	MMIU
GPT-4V/o	-	88.80	76.52	62.67	51.14	43.50	53.00	68.00	55.70
Open Source Models (merge)									
Random	-	48.93	40.20	23.04	38.09	27.30	22.30	23.99	27.40
Kosmos2	1.6B	49.00	35.10	30.41	37.50	21.62	-	-	-
LLaVA-v1.5	7B	53.88	49.32	31.34	37.13	36.00	38.00	23.46	19.20
LLaVA-V1.6	7B	58.88	54.80	45.62	39.55	40.90	38.10	-	22.20
Qwen-VL-Chat	7B	58.72	45.90	39.17	31.17	_42.15_	39.10	-	15.90
Fuyu	8B	51.10	49.15	27.19	36.59	30.20	-	-	-
BLIP-2	13B	59.42	51.20	49.77	39.45	31.40	-	-	-
InstructBLIP	13B	60.26	44.30	45.62	42.24	32.50	-	-	-
CogVLM	17B	58.58	53.20	45.16	41.54	37.30	-	20.85	-
Open Source Models (sequence)									
OpenFlamingo	9B	36.41	19.60	12.44	39.18	7.90	27.40	23.73	-
Otter-Image	9B	49.15	17.50	14.29	36.26	15.30	-	-	-
Idefics1	9B	54.63	30.60	28.11	24.69	26.42	-	_35.43_	12.80
VideoLLaVA	7B	56.48	45.70	35.94	38.92	44.30	-	-	-
Emu2-Chat	37B	58.16	50.05	37.79	36.20	39.72	-	-	-
VILA-1.5	8B	76.45	45.70	_51.15_	39.30	_49.40_	_44.40_	-	-
Idefics2	8B	_86.87_	_57.00_	48.85	_45.18_	29.68	-	26.08	_27.80_
Mantis-Fuyu	8B	72.41	54.10	37.79	39.87	39.12	-	-	-
Mantis-Flamingo	9B	52.96	46.80	32.72	38.00	40.83	-	-	-
Mantis-CLIP	8B	84.66	66.00	55.76	47.06	48.30	-	37.38	-
Mantis-SIGLIP	8B	87.43	69.90	**59.45**	46.35	50.15	**47.5**	36.12	-
Mantis-Idefics2	8B	**89.71**	**75.20**	57.14	**49.05**	**51.38**	-	**44.50**	**45.60**
Δ over SOTA	-	2.84	18.20	8.30	3.87	1.98	3.10	9.07	17.80

Table 5: Evaluation results on multi-image benchmarks. The highest score of open-source models for each task is bolded. The highest score of the open-source baseline model is underscored. Δ is the performance gains of MANTIS compared to the best baseline model for each task. We report the GPT-4o's results on MuirBench and MMIU, and GPT-4V's on the rest of them.

Model	Size	TextVQA	VQA	MMB	MMMU	OKVQA	SQA	Avg
OpenFlamingo	9B	46.3	58.0	32.4	28.7	51.4	45.7	43.8
Idefics1	9B	39.3	68.8	45.3	32.5	50.4	51.6	48.0
InstructBLIP	7B	33.6	75.2	38.3	30.6	45.2	70.6	48.9
Yi-VL	6B	44.8	72.5	68.4	39.1	51.3	71.7	58.0
Qwen-VL-Chat	7B	63.8	78.2	61.8	35.9	56.6	68.2	60.8
LLaVA-1.5-Vicuna	7B	58.2	76.6	64.8	35.3	53.4	70.4	59.8
LLaVA-1.6-Vicuna	7B	64.9	81.8	67.4	35.8	44.0	68.5	60.4
Emu2-Chat	37B	_66.6_	**84.9**	63.6	36.3	**64.8**	65.3	63.6
CogVLM	17B	**70.4**	_82.3_	65.8	32.1	_64.8_	65.6	63.5
VILA-1.5	8B	64.4	80.9	72.3	36.9	0.0	79.9	55.7
Idefics2	8B	70.4	79.1	_75.7_	**43.0**	53.5	**86.5**	**68.0**
Mantis-CLIP	8B	56.4	73.0	66.0	38.1	53.0	73.8	60.1
Mantis-SigLIP	8B	59.2	74.9	68.7	40.1	55.4	74.9	62.2
Mantis-Idefics2	8B	63.5	77.6	**75.7**	_41.1_	52.6	_81.3_	_65.3_

Table 6: Evaluation results of MANTIS on various single-image tasks. The full name of the abbreviations in the table are listed here. TextVQA: TextVQA validation set; VQA: VQA-v2 validation set; MMB: MMBench-English test set; SQA: ScienceQA-Image validation set. The highest score for each task is bolded, while the second highest is underscored.

tasks. It's also worth mentioning the reported performance of Mantis on the 3 recently released multi-image benchmarks with comprehensive evaluation tasks. Mantis models surpassed the VILA and Idefics2, which are pre-trained with millions of multi-image data, by a large margin, making them the best open-source models on the leaderboard. This is strong evidence of Mantis's good generalization ability in the unseen scenario.

Multi-Image Pre-training is not necessary: In these experiments, Mantis-CLIP and Mantis-SigLIP are attaining much better performance than Mantis-Flamingo, and similar performance as Mantis-Idefics, which are pre-trained on millions of text-image interleaved data. These results reveal that the multi-image pre-training (on massive web corpus) is not a necessary path toward strong multi-image performance.

'Merge' vs 'Sequence' input: The 'merge' evaluation is an important baseline to evaluate the multi-image understanding ability of those LMMs that can only accept one image at a time. LLaVA-v1.6's dynamic image resolution feature can divide a single image into multiple tiles, processing the 'merge' image like multiple images (Liu et al., 2024). But it still performs poorly on multi-image tasks, only getting 45.62 and 39.55 on the Mantis-Eval and BLINK benchmark, which are at least 10 absolute points lower than Mantis. This result indicates the advantages of building models to accept sequence image inputs.

Vision encoder matters: Unlike many other LMMs like Flamingo, LLaVA, and BLIP, Fuyu is a decoder-only LMM without a vision encoder. To investigate the importance of vision encoder, we also train an additional Mantis-Fuyu as a comparison. Results in Table 5 show that the performance of Mantis-Fuyu is worse than Mantis-CLIP and Mantis-SigLIP where a vision encoder exists. While we acknowledge a possible factor brought by the different LLM backbones, we think whether vision encoder exists is a bigger difference and conclude that a good vision encoder can enhances the performance.

3.5 Results on Single-Image Tasks

We also evaluate Mantis-CLIP and Mantis-SigLIP on various single-image tasks, including TextVQA (Singh et al., 2019a), VQA-v2 (Goyal et al., 2016), MMBench (Liu et al., 2023d), MMMU (Yue et al., 2023), etc. Results are shown in Table 6. All the evaluations are conducted with the help of LMMs-Eval (Li* et al., 2024) tool. Mantis-Flamingo's and Mantis-Fuyu's performance is omitted due to its bad performance.

Compared to a set of popular LMMs, Mantis-SigLIP gets significant improvements on MMBench-English, MMMU, and ScienceQA benchmarks though we did not specifically optimize the single-image abilities. Solving problems in these tasks requires not only the visual perception ability but also the good reasoning ability of the LLM backbone. Considering that we are using the powerful LLaMA-3 as the backbone LLM, these improvements are expected. We also compare the results of Mantis-Idefics2 against Idefics2 on single-image tasks. On several tasks like MMB, MMMU, and OKVQA, Mantis-Idefics maintains a similarly strong performance as Idefics2. However, we do observe some drops in ScienceQA, which are mainly due to a lower mix ratio of OCR and Math data in our instruction tuning. Overall, the average drop of 4% is tolerable.

3.6 Ablation Studies

Is multi-image instruction tuning necessary? To investigate, we further train a Mantis-Flamingo based on OpenFlamingo (Awadalla et al., 2023), which has been trained on MMC4 (Zhu et al., 2023), a text-image interleaved pre-training dataset. As shown in Table 5, the average performance of Mantis-Flamingo increased by 19.2 points after further fine-tuning on MANTIS-INSTRUCT. The results show that there is still a huge improvement space, even if a model is fully pre-trained on a multi-image dataset, which demonstrates the necessity of learning multi-image skills in the fine-tuning phase.

Is multi-image pre-training necessary? To investigate, we design an ablation study, where one model is pre-trained on the CC3M 560K subset, which contains only image-text pairs, while the other one is pre-trained additionally on OBELICS-100K subset, which contains interleaved multi-image-text pairs. Due to limited computation resources, we fine-tune both models on a downsampled MANTIS-INSTRUCT dataset to compare their performance. Results in Table 7 show that there are little improvements by adding additional pre-training on OBELICS-100K. We thus conclude that multi-image pre-training could be useful, but it is not a necessary path for models to gain multi-image abilities. The poor performance on Mantis-Flamingo also confirm our hypothesis.

Pretrain	NLVR2	Q-Bench	Mantis-Eval	BLINK	MVBench	Avg
CC3M subset + MantisInstruct subset	76.73	57.00	47.00	43.79	47.08	54.32
CC3M subset + MantisInstruct subset +OBELICS-100K	76.83	60.50	53.00	45.20	45.97	56.30
Δ (with OBELICS-100K)	+0.10	+3.50	+6.00	+1.41	-1.11	+1.98

Table 7: Ablation on whether multi-image pre-training is necessary. One model is pre-trained on the CC3M subset, while the other is additionally pre-trained on the a OBELICS-100K multi-image dataset. They are both fine-tuned on a subset MANTIS-INSTRUCT for comparison. Results show minor improvement with additional multi-image pre-training. Each ablation model is trained with QLoRA with DoRA.

Models	NLVR2	Q-Bench	Mantis-Eval	BLINK	MVBench	Avg	Δ
Idefics2-8B	86.87	57.00	48.85	45.18	29.68	53.52	-
+Coref	84.48	63.20	57.14	48.58	49.40	60.56	+7.04
+Compare	85.92	69.00	53.92	48.00	48.33	61.03	+0.47
+Reason	**89.62**	**68.50**	**62.21**	48.31	47.93	63.31	+2.28
+Temporal	89.54	67.00	61.29	**49.34**	**50.02**	**63.44**	+0.12

Table 8: Data ablation study results of different subsets of MANTIS-INSTRUCT, where each skill corresponding to a specific subsets defined in Table 1. Δ column of each row represents the performance improvements after adding new subsets to the last column results. Each ablation model is trained with QLoRA with DoRA.

Ablation study of Mantis-Instruct components: We conduct a data ablation study to analyze the effects of different subsets in MANTIS-INSTRUCT to enhance a model's multi-image ability. As shown in Table 8, As new subsets of MANTIS-INSTRUCT are added continually, the overall performance is continually improving, proving that every subset is contributing positively.

3.7 Qualitative Results

To conduct a qualitative analysis of Mantis models on specific multi-image scenarios, we include some case studies in Figure 3, where we include Emu2, which can accept a sequence of images as inputs, and LLaVA-1.5, which can only accept one image at a time, and the powerful GPT-4V, which perform well on both single-image and multi-image scenario.

Figure 3: Two case studies in multi-image scenario. MANTIS can understand multiple images and complete the given task, thanks to the 4 multi-image skills learned from MANTIS-INSTRUCT.

The first case requires the model to count the number of dice respectively in the two images. While previous LMMs might have learned good counting ability in the single-image scenario, most of them failed in the multi-image counting problem, including GPT-4V. The second case requires the model to involve their world knowledge to infer the mood of the character in three images. However, Emu2, and LLaVA-1.5 output similar contents, and both fall back into the simple captioning behavior. It demonstrates that these models struggle to distinguish two images as separate information. In contrast, Mantis can correctly do the task due to the existing of reasoning subset in Mantis-Instruct.

4 Related Works

4.1 Large Multimodal Models

Large Multimodal Models (LMMs) are mostly denoted as large language models that can understand multiple modalities besides the human language. Some works aim to fuse image, audio, video, or more modalities with language (Wu et al., 2023b; Zhan et al., 2024), while more works mainly focus on better-combining vision knowledge with the language (Alayrac et al., 2022; Awadalla et al., 2023; Dai et al., 2023). BLIP-2 has curated a large-scale image captioning dataset, bootstrapping a language model along with a vision encoder to be a powerful multimodal model (Li et al., 2023c). Following this, LLaVA further proposes a cheaper approach to train a powerful LMM through visual instruction tuning (Huang et al., 2016). LLaVA-Next further optimizes single-image performance, with a cost of an increasing number of image tokens per token (Liu et al., 2024), consuming more than 2k for each image, which is about 4 times of the original LLaVA model. Later LMMs like QwenVL (Bai et al., 2023), CogVLM (Wang et al., 2023), Yi-VL (AI et al., 2024), etc. all follow a similar architecture of LLaVA. However, real-world visual problems are way more complex and usually require a sequence of images to describe the situation. Although better performance is achieved in the single-image scenario, it's doubtful whether it's worth the cost.

4.2 Multi-Image Supported Large Multimodal Models

Previous works have also noticed the importance of multi-image ability. Deepmind's close-sourced Flamingo (Alayrac et al., 2022) focuses on optimizing in-context learning for a sequence of image/text pairs but lacking free-from image-text interleaved training examples. Kosmos2 (Peng et al., 2023), Fuyu (Adept AI, 2023) both support text-image interleaved format given the model structure, but they did not optimize in multi-image reasoning, and the released inference codes also do not support multi-image as input. Emu2 (Sun et al., 2023) is a generative multimodal model that supports interleaved text-image inputs, as well as generating both images and texts. However, it's mainly focused on in-context examples like Flamingo and auto-regressive image generation, instead of the 4 skills mentioned in section 1 Another common variant of LMMs that can accept multiple images as input is video understanding models, such as Video-LLaMA (Zhang et al., 2023a). However, as shown in the MVBench benchmark, it is also shown that Video-LLaMA behaves worse than LMMs that can only accept one image as input (Li et al., 2023d), which raises doubts about its multi-image understanding ability. Different from these works, Mantis aims to optimize the multi-image ability of LMMs guided by the 4 defined skills, co-reference, reasoning, comparison, and temporal understanding, thus equipping the model with better multi-image ability.

4.3 Multi-Image Evaluation

While many benchmarks have been developed for single-image tasks, such as TextVQA (Singh et al., 2019a), VQA-V2 (Goyal et al., 2016), MMBench (Liu et al., 2023d), and so on, the multi-image evaluation did not capture much attention until recently. Difference description is the first task which large-scale data and good evaluation benchmarks are developed for, including works like Spot-the-Diff (Jhamtani & Berg-Kirkpatrick, 2018), Birds-to-Words (Forbes et al., 2019), etc. They are usually evaluated by n-gram metrics like BLEU, and ROUGE, and only involve two images. The later NLVR2 (Suhr et al., 2018) further includes logical reasoning across 2 images into evaluation, focusing on a higher level of cognition ability. Q-bench (Wu et al., 2023a) and BLINK (Fu et al., 2024) are both proposed for low-level multi-image vision tasks, where humans easily do but model struggles. Another set of multi-image evaluations comes from video or image sequence

evaluation, including Mementos (Wang et al., 2024b), MVBench (Li et al., 2023d), etc. In this case, the model usually needs to take more than 2 images to answer. Recently, there are also attempts to prompt LMMs to evaluate vision-language task (Zhang et al., 2023b), or image-generation tasks (Ku et al., 2023), which also demands good multi-image reasoning ability. The accuracies of the these tasks of different LMMs can be seen as another form of benchmark for multi-image ability.

5 Conclusion

We propose MANTIS, a new large multimodal model family designed to be able to accept interleaved text-image inputs. MANTIS is fine-tuned on our MANTIS-INSTRUCT, a text-image interleaved dataset consisting of 721K examples, covering 4 crucial skills, including co-reference, reasoning, comparison, and temporal understanding, for multi-image tasks. We also propose Mantis-Eval, a high-quality multi-image evaluation benchmark consisting of 217 examples with an average of 2.5 images per example. Comprehensive experiments show that MANTIS models effectively acquire the 4 multi-image skills and achieves state-of-the-art performance on 5 multi-image evaluation benchmarks, and preserve decent single-image reasoning performance. We shared insights about the model architecture and inference approaches based on the experiment results. Extending the image sequence context length and compressing the number of tokens per tokens efficiently are regarded as our future work.

Limitations

Our work mainly focuses on improving the multi-image ability of LMMs. Our collected dataset Mantis-Instruct reformat some existing multi-image datasets, which might still contain some noise due to the quality of the original collection. Besides, we found that most of the examples in the Mantis-Instrut tend to be multiple-choice QA questions, where the response tends to be short, resulting in the current version of Mantis models tending to output shorter responses instead of long reasoning texts and falling short in instruction-following ability in the multi-image scenario. Although we have introduced `Multi-VQA` subset to alleviate this issue, this problem still exists, and we will leave it to future work by introducing more long-form multi-image data. While enhancing the multi-image ability well, we find out that there is a trend of performance degeneration in the single-image performance compared to the original model Table 6. Some single-image QA datasets have been introduced to alleviate this issue, but the conflicts between multi-image and single-image ability seem to exist continually. How to balance these two abilities will also be our future direction.

Societal Impacts

Our proposed model, Mantis, and released dataset, Mantis-Instruct, can have substantial impacts on society through the application of Large Multimodal Models. LMMs with multi-image ability can analyze, and reason in real-world scenarios, helping machines, and robots, to make decisions automatically, assisting people in website browsing, travel planning based on multiple maps and pictures, etc. We believe Mantis can serve as one of the first useful open-source LMMs that make progress in these applications to make these scenarios possible and efficient.

However, there is a potential that our Mantis can generate hallucinations, make the wrong decisions, and fail to reason across complex real-world scenarios. While we have tried to improve Mantis's accuracy and performance in instruction-following and multi-image understanding by carefully training on high-quality Mantis-Instruct, Mantis can still sometimes make mistakes, thus harming its faithfulness as a useful LMM tool. There is also the potential for misuse of our model and dataset after we make them open source. Though we have added proper licenses and terms of usage to our assets, misuse cannot be safely eliminated.

References

OpenAI Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, Red Avila, Igor Babuschkin, Suchir Balaji, Valerie Balcom, Paul Baltescu, Haiming Bao, Mo Bavarian, Jeff Belgum, Irwan Bello, Jake Berdine, Gabriel Bernadett-Shapiro, Christopher Berner, Lenny Bogdonoff, Oleg Boiko, Madelaine Boyd, Anna-Luisa Brakman, Greg Brockman, Tim Brooks, Miles Brundage, Kevin Button, Trevor Cai, Rosie Campbell, Andrew Cann, Brittany Carey, Chelsea Carlson, Rory Carmichael, Brooke Chan, Che Chang, Fotis Chantzis, Derek Chen, Sully Chen, Ruby Chen, Jason Chen, Mark Chen, Benjamin Chess, Chester Cho, Casey Chu, Hyung Won Chung, Dave Cummings, Jeremiah Currier, Yunxing Dai, Cory Decareaux, Thomas Degry, Noah Deutsch, Damien Deville, Arka Dhar, David Dohan, Steve Dowling, Sheila Dunning, Adrien Ecoffet, Atty Eleti, Tyna Eloundou, David Farhi, Liam Fedus, Niko Felix, Sim'on Posada Fishman, Juston Forte, Isabella Fulford, Leo Gao, Elie Georges, Christian Gibson, Vik Goel, Tarun Goginени, Gabriel Goh, Raphael Gontijo-Lopes, Jonathan Gordon, Morgan Grafstein, Scott Gray, Ryan Greene, Joshua Gross, Shixiang Shane Gu, Yufei Guo, Chris Hallacy, Jesse Han, Jeff Harris, Yuchen He, Mike Heaton, Johannes Heidecke, Chris Hesse, Alan Hickey, Wade Hickey, Peter Hoeschele, Brandon Houghton, Kenny Hsu, Shengli Hu, Xin Hu, Joost Huizinga, Shantanu Jain, Shawn Jain, Joanne Jang, Angela Jiang, Roger Jiang, Haozhun Jin, Denny Jin, Shino Jomoto, Billie Jonn, Heewoo Jun, Tomer Kaftan, Lukasz Kaiser, Ali Kamali, Ingmar Kanitscheider, Nitish Shirish Keskar, Tabarak Khan, Logan Kilpatrick, Jong Wook Kim, Christina Kim, Yongjik Kim, Hendrik Kirchner, Jamie Ryan Kiros, Matthew Knight, Daniel Kokotajlo, Lukasz Kondraciuk, Andrew Kondrich, Aris Konstantinidis, Kyle Kosic, Gretchen Krueger, Vishal Kuo, Michael Lampe, Ikai Lan, Teddy Lee, Jan Leike, Jade Leung, Daniel Levy, Chak Ming Li, Rachel Lim, Molly Lin, Stephanie Lin, Mateusz Litwin, Theresa Lopez, Ryan Lowe, Patricia Lue, Anna Adeola Makanju, Kim Malfacini, Sam Manning, Todor Markov, Yaniv Markovski, Bianca Martin, Katie Mayer, Andrew Mayne, Bob McGrew, Scott Mayer McKinney, Christine McLeavey, Paul McMillan, Jake McNeil, David Medina, Aalok Mehta, Jacob Menick, Luke Metz, Andrey Mishchenko, Pamela Mishkin, Vinnie Monaco, Evan Morikawa, Daniel P. Mossing, Tong Mu, Mira Murati, Oleg Murk, David M'ely, Ashvin Nair, Reiichiro Nakano, Rajeev Nayak, Arvind Neelakantan, Richard Ngo, Hyeonwoo Noh, Ouyang Long, Cullen O'Keefe, Jakub W. Pachocki, Alex Paino, Joe Palermo, Ashley Pantuliano, Giambattista Parascandolo, Joel Parish, Emy Parparita, Alexandre Passos, Mikhail Pavlov, Andrew Peng, Adam Perelman, Filipe de Avila Belbute Peres, Michael Petrov, Henrique Pondé de Oliveira Pinto, Michael Pokorny, Michelle Pokrass, Vitchyr H. Pong, Tolly Powell, Alethea Power, Boris Power, Elizabeth Proehl, Raul Puri, Alec Radford, Jack Rae, Aditya Ramesh, Cameron Raymond, Francis Real, Kendra Rimbach, Carl Ross, Bob Rotsted, Henri Roussez, Nick Ryder, Mario D. Saltarelli, Ted Sanders, Shibani Santurkar, Girish Sastry, Heather Schmidt, David Schnurr, John Schulman, Daniel Selsam, Kyla Sheppard, Toki Sherbakov, Jessica Shieh, Sarah Shoker, Pranav Shyam, Szymon Sidor, Eric Sigler, Maddie Simens, Jordan Sitkin, Katarina Slama, Ian Sohl, Benjamin D. Sokolowsky, Yang Song, Natalie Staudacher, Felipe Petroski Such, Natalie Summers, Ilya Sutskever, Jie Tang, Nikolas A. Tezak, Madeleine Thompson, Phil Tillet, Amin Tootoonchian, Elizabeth Tseng, Preston Tuggle, Nick Turley, Jerry Tworek, Juan Felipe Cer'on Uribe, Andrea Vallone, Arun Vijayvergiya, Chelsea Voss, Carroll Wainwright, Justin Jay Wang, Alvin Wang, Ben Wang, Jonathan Ward, Jason Wei, CJ Weinmann, Akila Welihinda, Peter Welinder, Jiayi Weng, Lilian Weng, Matt Wiethoff, Dave Willner, Clemens Winter, Samuel Wolrich, Hannah Wong, Lauren Workman, Sherwin Wu, Jeff Wu, Michael Wu, Kai Xiao, Tao Xu, Sarah Yoo, Kevin Yu, Qiming Yuan, Wojciech Zaremba, Rowan Zellers, Chong Zhang, Marvin Zhang, Shengjia Zhao, Tianhao Zheng, Juntang Zhuang, William Zhuk, and Barret Zoph. Gpt-4 technical report, 2023. URL `https://api.semanticscholar.org/CorpusID:257532815`.

Adept AI. Fuyu-8B: A Multimodal Architecture for AI Agents. `https://www.adept.ai/blog/fuyu-8b`, 2023.

01. AI, :, Alex Young, Bei Chen, Chao Li, Chengen Huang, Ge Zhang, Guanwei Zhang, Heng Li, Jiangcheng Zhu, Jianqun Chen, Jing Chang, Kaidong Yu, Peng Liu, Qiang Liu, Shawn Yue, Senbin Yang, Shiming Yang, Tao Yu, Wen Xie, Wenhao Huang, Xiaohui Hu, Xiaoyi Ren, Xinyao Niu, Pengcheng Nie, Yuchi Xu, Yudong Liu, Yue Wang, Yuxuan Cai, Zhenyu Gu, Zhiyuan Liu, and Zonghong Dai. Yi: Open foundation models by 01.ai, 2024.

AI@Meta. Llama 3 model card, 2024. URL https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md.

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katie Millican, Malcolm Reynolds, Roman Ring, Eliza Rutherford, Serkan Cabi, Tengda Han, Zhitao Gong, Sina Samangooei, Marianne Monteiro, Jacob Menick, Sebastian Borgeaud, Andy Brock, Aida Nematzadeh, Sahand Sharifzadeh, Mikolaj Binkowski, Ricardo Barreira, Oriol Vinyals, Andrew Zisserman, and Karen Simonyan. Flamingo: a visual language model for few-shot learning. *ArXiv*, abs/2204.14198, 2022. URL https://api.semanticscholar.org/CorpusID:248476411.

Reza Yazdani Aminabadi, Samyam Rajbhandari, Minjia Zhang, Ammar Ahmad Awan, Cheng Li, Du Li, Elton Zheng, Jeff Rasley, Shaden Smith, Olatunji Ruwase, and Yuxiong He. Deepspeed- inference: Enabling efficient inference of transformer models at unprecedented scale. *SC22: International Conference for High Performance Computing, Networking, Storage and Analysis*, pp. 1–15, 2022. URL https://api.semanticscholar.org/CorpusID:250243681.

Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C Lawrence Zitnick, and Devi Parikh. Vqa: Visual question answering. In *Proceedings of the IEEE international conference on computer vision*, pp. 2425–2433, 2015.

Anas Awadalla, Irena Gao, Josh Gardner, Jack Hessel, Yusuf Hanafy, Wanrong Zhu, Kalyani Marathe, Yonatan Bitton, Samir Yitzhak Gadre, Shiori Sagawa, Jenia Jitsev, Simon Kornblith, Pang Wei Koh, Gabriel Ilharco, Mitchell Wortsman, and Ludwig Schmidt. Openflamingo: An open-source framework for training large autoregressive vision-language models. *ArXiv*, abs/2308.01390, 2023. URL https://api.semanticscholar.org/CorpusID:261043320.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A frontier large vision-language model with versatile abilities. *ArXiv*, abs/2308.12966, 2023. URL https://api.semanticscholar.org/CorpusID:263875678.

Lin Chen, Jinsong Li, Xiao wen Dong, Pan Zhang, Conghui He, Jiaqi Wang, Feng Zhao, and Dahua Lin. Sharegpt4v: Improving large multi-modal models with better captions. *ArXiv*, abs/2311.12793, 2023. URL https://api.semanticscholar.org/CorpusID:265308687.

Wenliang Dai, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Junqi Zhao, Weisheng Wang, Boyang Albert Li, Pascale Fung, and Steven C. H. Hoi. Instructblip: Towards general-purpose vision-language models with instruction tuning. *ArXiv*, abs/2305.06500, 2023. URL https://api.semanticscholar.org/CorpusID:258615266.

Tri Dao. FlashAttention-2: Faster attention with better parallelism and work partitioning. *ArXiv*, 2023.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. Qlora: Efficient finetuning of quantized llms. *ArXiv*, abs/2305.14314, 2023. URL https://api.semanticscholar.org/CorpusID:258841328.

Maxwell Forbes, Christine Kaeser-Chen, Piyush Sharma, and Serge J. Belongie. Neural naturalist: Generating fine-grained image comparisons. In *Conference on Empirical Methods in Natural Language Processing*, 2019. URL https://api.semanticscholar.org/CorpusID:202542687.

Stephanie Fu, Netanel Tamir, Shobhita Sundaram, Lucy Chai, Richard Zhang, Tali Dekel, and Phillip Isola. Dreamsim: Learning new dimensions of human visual similarity using synthetic data. *ArXiv*, abs/2306.09344, 2023. URL https://api.semanticscholar.org/CorpusID:259171761.

Xingyu Fu, Yushi Hu, Bangzheng Li, Yu Feng, Haoyu Wang, Xudong Lin, Dan Roth, Noah A. Smith, Wei-Chiu Ma, and Ranjay Krishna. Blink: Multimodal large language models can see but not perceive, 2024.

Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the v in vqa matter: Elevating the role of image understanding in visual question answering. *International Journal of Computer Vision*, 127:398 – 414, 2016. URL https://api.semanticscholar.org/CorpusID:8081284.

Ting-Hao K. Huang, Francis Ferraro, Nasrin Mostafazadeh, Ishan Misra, Jacob Devlin, Aishwarya Agrawal, Ross Girshick, Xiaodong He, Pushmeet Kohli, Dhruv Batra, et al. Visual storytelling. In *15th Annual Conference of the North American Chapter of the Association for Computational Linguistics (NAACL 2016)*, 2016.

Drew A Hudson and Christopher D Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 6700–6709, 2019.

Harsh Jhamtani and Taylor Berg-Kirkpatrick. Learning to describe differences between pairs of similar images. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 4024–4034, 2018.

Kushal Kafle, Scott D. Cohen, Brian L. Price, and Christopher Kanan. Dvqa: Understanding data visualizations via question answering. *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5648–5656, 2018. URL https://api.semanticscholar.org/CorpusID:4445015.

Dohwan Ko, Ji Soo Lee, Wooyoung Kang, Byungseok Roh, and Hyunwoo J Kim. Large language models are temporal and causal reasoners for video question answering. In *EMNLP*, 2023.

Benno Krojer, Vaibhav Adlakha, Vibhav Vineet, Yash Goyal, E. Ponti, and Siva Reddy. Image retrieval from contextual descriptions. In *Annual Meeting of the Association for Computational Linguistics*, 2022. URL https://api.semanticscholar.org/CorpusID:247793003.

Max W.F. Ku, Dongfu Jiang, Cong Wei, Xiang Yue, and Wenhu Chen. Viescore: Towards explainable metrics for conditional image synthesis evaluation. *ArXiv*, abs/2312.14867, 2023. URL https://api.semanticscholar.org/CorpusID:266521161.

Alina Kuznetsova, Hassan Rom, Neil Gordon Alldrin, Jasper R. R. Uijlings, Ivan Krasin, Jordi Pont-Tuset, Shahab Kamali, Stefan Popov, Matteo Malloci, Alexander Kolesnikov, Tom Duerig, and Vittorio Ferrari. The open images dataset v4. *International Journal of Computer Vision*, 128:1956 – 1981, 2018. URL https://api.semanticscholar.org/CorpusID:53296866.

Hugo Laurenccon, Léo Tronchon, Matthieu Cord, and Victor Sanh. What matters when building vision-language models? 2024. URL https://api.semanticscholar.org/CorpusID:269587869.

Hugo Laurençon, Lucile Saulnier, Léo Tronchon, Stas Bekman, Amanpreet Singh, Anton Lozhkov, Thomas Wang, Siddharth Karamcheti, Alexander M. Rush, Douwe Kiela, Matthieu Cord, and Victor Sanh. Obelics: An open web-scale filtered dataset of interleaved image-text documents, 2023.

Bo Li, Yuanhan Zhang, Liangyu Chen, Jinghao Wang, Fanyi Pu, Jingkang Yang, C. Li, and Ziwei Liu. Mimic-it: Multi-modal in-context instruction tuning. *ArXiv*, abs/2306.05425, 2023a. URL https://api.semanticscholar.org/CorpusID:259108295.

Bo Li, Yuanhan Zhang, Liangyu Chen, Jinghao Wang, Jingkang Yang, and Ziwei Liu. Otter: A multi-modal model with in-context instruction tuning. *ArXiv*, abs/2305.03726, 2023b. URL https://api.semanticscholar.org/CorpusID:258547300.

Bo Li*, Peiyuan Zhang*, Kaicheng Zhang, Fanyi Pu, Xinrun Du, Yuhao Dong, Haotian Liu, Yuanhan Zhang, Ge Zhang, Chunyuan Li, and Ziwei Liu. Lmms-eval: Accelerating the development of large multimoal models, March 2024. URL https://github.com/EvolvingLMMs-Lab/lmms-eval.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven C. H. Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International Conference on Machine Learning*, 2023c. URL https://api.semanticscholar.org/CorpusID:256390509.

Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, Limin Wang, and Yu Qiao. Mvbench: A comprehensive multi-modal video understanding benchmark. *ArXiv*, abs/2311.17005, 2023d. URL https://api.semanticscholar.org/CorpusID:265466214.

Bin Lin, Bin Zhu, Yang Ye, Munan Ning, Peng Jin, and Li Yuan. Video-llava: Learning united visual representation by alignment before projection. *ArXiv*, abs/2311.10122, 2023a. URL https://api.semanticscholar.org/CorpusID:265281544.

Ji Lin, Hongxu Yin, Wei Ping, Yao Lu, Pavlo Molchanov, Andrew Tao, Huizi Mao, Jan Kautz, Mohammad Shoeybi, and Song Han. Vila: On pre-training for visual language models. *ArXiv*, abs/2312.07533, 2023b. URL https://api.semanticscholar.org/CorpusID:266174746.

Ji Lin, Hongxu Yin, Wei Ping, Yao Lu, Pavlo Molchanov, Andrew Tao, Huizi Mao, Jan Kautz, Mohammad Shoeybi, and Song Han. Vila: On pre-training for visual language models. *arXiv preprint arXiv:2312.07533*, 2023c.

Fuxiao Liu, Kevin Lin, Linjie Li, Jianfeng Wang, Yaser Yacoob, and Lijuan Wang. Aligning large multi-modal model with robust instruction tuning. *arXiv preprint arXiv:2306.14565*, 2023a.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. *ArXiv*, abs/2310.03744, 2023b. URL https://api.semanticscholar.org/CorpusID:263672058.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *ArXiv*, abs/2304.08485, 2023c. URL https://api.semanticscholar.org/CorpusID:258179774.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge, January 2024. URL https://llava-vl.github.io/blog/2024-01-30-llava-next/.

Yuanzhan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, Kai Chen, and Dahua Lin. Mmbench: Is your multi-modal model an all-around player? *ArXiv*, abs/2307.06281, 2023d. URL https://api.semanticscholar.org/CorpusID:259837088.

Ahmed Masry, Xuan Long Do, Jia Qing Tan, Shafiq R. Joty, and Enamul Hoque. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. *ArXiv*, abs/2203.10244, 2022. URL https://api.semanticscholar.org/CorpusID:247593713.

Minesh Mathew, Dimosthenis Karatzas, R. Manmatha, and C. V. Jawahar. Docvqa: A dataset for vqa on document images. *2021 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pp. 2199–2208, 2020. URL https://api.semanticscholar.org/CorpusID:220280200.

Brandon McKinzie, Zhe Gan, Jean-Philippe Fauconnier, Sam Dodge, Bowen Zhang, Philipp Dufter, Dhruti Shah, Xianzhi Du, Futang Peng, Floris Weers, et al. Mm1: Methods, analysis & insights from multimodal llm pre-training. *arXiv preprint arXiv:2403.09611*, 2024.

Fanqing Meng, Jin Wang, Chuanhao Li, Quanfeng Lu, Hao Tian, Jiaqi Liao, Xizhou Zhu, Jifeng Dai, Yu Qiao, Ping Luo, Kaipeng Zhang, and Wenqi Shao. Mmiu: Multimodal multi-image understanding for evaluating large vision-language models. 2024. URL https://api.semanticscholar.org/CorpusID:271720013.

Aitor Ormazabal, Che Zheng, Cyprien de Masson d'Autume, Dani Yogatama, Deyu Fu, Donovan Ong, Eric Chen, Eugenie Lamprecht, Hai Pham, Isaac Ong, et al. Reka core, flash, and edge: A series of powerful multimodal language models. *arXiv preprint arXiv:2404.12387*, 2024.

Zhiliang Peng, Wenhui Wang, Li Dong, Yaru Hao, Shaohan Huang, Shuming Ma, and Furu Wei. Kosmos-2: Grounding multimodal large language models to the world. *ArXiv*, abs/2306.14824, 2023. URL https://api.semanticscholar.org/CorpusID:259262263.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, 2021. URL https://api.semanticscholar.org/CorpusID:231591445.

Christoph Schuhmann and Peter Bevan. 220k-gpt4vision-captions-from-lvis. https://huggingface.co/datasets/laion/220k-GPT4Vision-captions-from-LIVIS, 2023.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8309–8318, 2019a. URL https://api.semanticscholar.org/CorpusID: 85553602.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8317–8326, 2019b.

Dingjie Song, Shunian Chen, Guiming Hardy Chen, Fei Yu, Xiang Wan, and Benyou Wang. Milebench: Benchmarking mllms in long context. *ArXiv*, abs/2404.18532, 2024. URL https://api.semanticscholar. org/CorpusID:269449774.

Alane Suhr, Stephanie Zhou, Iris Zhang, Huajun Bai, and Yoav Artzi. A corpus for reasoning about natural language grounded in photographs. *ArXiv*, abs/1811.00491, 2018. URL https://api.semanticscholar. org/CorpusID:53178856.

Quan Sun, Yufeng Cui, Xiaosong Zhang, Fan Zhang, Qiying Yu, Zhengxiong Luo, Yueze Wang, Yongming Rao, Jingjing Liu, Tiejun Huang, and Xinlong Wang. Generative multimodal models are in-context learners. *ArXiv*, abs/2312.13286, 2023. URL https://api.semanticscholar.org/CorpusID:266374640.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.

Fei Wang, Xingyu Fu, James Y. Huang, Zekun Li, Qin Liu, Xiaogeng Liu, Mingyu Derek Ma, Nan Xu, Wenxuan Zhou, Kai Zhang, Tianyi Yan, Wenjie Jacky Mo, Hsiang-Hui Liu, Pan Lu, Chunyuan Li, Chaowei Xiao, Kai-Wei Chang, Dan Roth, Sheng Zhang, Hoifung Poon, and Muhao Chen. Muirbench: A comprehensive benchmark for robust multi-image understanding. *ArXiv*, abs/2406.09411, 2024a. URL https://api.semanticscholar.org/CorpusID:270440454.

Weihan Wang, Qingsong Lv, Wenmeng Yu, Wenyi Hong, Ji Qi, Yan Wang, Junhui Ji, Zhuoyi Yang, Lei Zhao, Xixuan Song, Jiazheng Xu, Bin Xu, Juanzi Li, Yuxiao Dong, Ming Ding, and Jie Tang. Cogvlm: Visual expert for pretrained language models. *ArXiv*, abs/2311.03079, 2023. URL https://api.semanticscholar.org/CorpusID:265034288.

Xiyao Wang, Yuhang Zhou, Xiaoyu Liu, Hongjin Lu, Yuancheng Xu, Feihong He, Jaehong Yoon, Taixi Lu, Gedas Bertasius, Mohit Bansal, et al. Mementos: A comprehensive benchmark for multimodal large language model reasoning over image sequences. *arXiv preprint arXiv:2401.10529*, 2024b.

Bo Wu and Shoubin Yu. Star: A benchmark for situated reasoning in real-world videos. In *NeurIPS Datasets and Benchmarks*, 2021. URL https://api.semanticscholar.org/CorpusID:244907062.

Haoning Wu, Zicheng Zhang, Erli Zhang, Chaofeng Chen, Liang Liao, Annan Wang, Chunyi Li, Wenxiu Sun, Qiong Yan, Guangtao Zhai, and Weisi Lin. Q-bench: A benchmark for general-purpose foundation models on low-level vision. *ArXiv*, abs/2309.14181, 2023a. URL https://api.semanticscholar.org/CorpusID: 262824606.

Haoning Wu, Hanwei Zhu, Zicheng Zhang, Erli Zhang, Chaofeng Chen, Liang Liao, Chunyi Li, Annan Wang, Wenxiu Sun, Qiong Yan, Xiaohong Liu, Guangtao Zhai, Shiqi Wang, and Weisi Lin. Towards open-ended visual quality comparison. *ArXiv*, abs/2402.16641, 2024. URL https://api.semanticscholar.org/ CorpusID:268033140.

Shengqiong Wu, Hao Fei, Leigang Qu, Wei Ji, and Tat-Seng Chua. Next-gpt: Any-to-any multimodal llm. *ArXiv*, abs/2309.05519, 2023b. URL https://api.semanticscholar.org/CorpusID:261696650.

Junbin Xiao, Xindi Shang, Angela Yao, and Tat seng Chua. Next-qa: Next phase of question-answering to explaining temporal actions. *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9772–9781, 2021. URL https://api.semanticscholar.org/CorpusID:234763093.

Shih yang Liu, Chien-Yi Wang, Hongxu Yin, Pavlo Molchanov, Yu-Chiang Frank Wang, Kwang-Ting Cheng, and Min-Hung Chen. Dora: Weight-decomposed low-rank adaptation. *ArXiv*, abs/2402.09353, 2024. URL `https://api.semanticscholar.org/CorpusID:267657886`.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, Cong Wei, Botao Yu, Ruibin Yuan, Renliang Sun, Ming Yin, Boyuan Zheng, Zhenzhu Yang, Yibo Liu, Wenhao Huang, Huan Sun, Yu Su, and Wenhu Chen. Mmmu: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. *ArXiv*, abs/2311.16502, 2023. URL `https://api.semanticscholar.org/CorpusID:265466525`.

Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. *2023 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 11941–11952, 2023. URL `https://api.semanticscholar.org/CorpusID:257767223`.

Jun Zhan, Junqi Dai, Jiasheng Ye, Yunhua Zhou, Dong Zhang, Zhigeng Liu, Xin Zhang, Ruibin Yuan, Ge Zhang, Linyang Li, Hang Yan, Jie Fu, Tao Gui, Tianxiang Sun, Yugang Jiang, and Xipeng Qiu. Anygpt: Unified multimodal llm with discrete sequence modeling. *ArXiv*, abs/2402.12226, 2024. URL `https://api.semanticscholar.org/CorpusID:267750101`.

Hang Zhang, Xin Li, and Lidong Bing. Video-llama: An instruction-tuned audio-visual language model for video understanding. *ArXiv*, abs/2306.02858, 2023a. URL `https://api.semanticscholar.org/CorpusID:259075356`.

Xinlu Zhang, Yujie Lu, Weizhi Wang, An Yan, Jun Yan, Lianke Qin, Heng Wang, Xifeng Yan, William Yang Wang, and Linda Ruth Petzold. Gpt-4v(ision) as a generalist evaluator for vision-language tasks. *ArXiv*, abs/2311.01361, 2023b. URL `https://api.semanticscholar.org/CorpusID:264935635`.

Wanrong Zhu, Jack Hessel, Anas Awadalla, Samir Yitzhak Gadre, Jesse Dodge, Alex Fang, Youngjae Yu, Ludwig Schmidt, William Yang Wang, and Yejin Choi. Multimodal c4: An open, billion-scale corpus of images interleaved with text. *ArXiv*, abs/2304.06939, 2023. URL `https://api.semanticscholar.org/CorpusID:258170467`.

Wanrong Zhu, Jack Hessel, Anas Awadalla, Samir Yitzhak Gadre, Jesse Dodge, Alex Fang, Youngjae Yu, Ludwig Schmidt, William Yang Wang, and Yejin Choi. Multimodal c4: An open, billion-scale corpus of images interleaved with text. *Advances in Neural Information Processing Systems*, 36, 2024.

A   Appendix / supplemental material

A.1   Details of Mantis-Instruct subsets

We construct MANTIS-INSTRUCT from multiple publicly available datasets. Detailed statistics are shown in Table 1. We use a similar dataset format with LLaVA's, where each data item contains multiple images and multiple turns of QA pairs are gathered. We report the number of examples, the number of images per item, the average conversation turns, and the average length. We describe the task type of each dataset and the processing techniques used in the following:

LLaVA-665k-multi: Besides the above-mentioned multi-image reasoning tasks, we also manually reformat the LLaVA-655k dataset from LLaVA-1.5 into a "synthetic" multi-image dataset. Since each original data item consists of multiple QA pairs about a single image, we randomly merge 2 to 4 data items into a multi-image data item. Then we add proper image denotation like "For the second image, ..." for each question, and shuffle all the QA pairs to form the final multi-image data item. Answering each question in this "synthetic" dataset does not require reasoning across images, but demands high image co-reference ability. Besides, it also helps avoid forgetting single-image ability in multi-image scenarios and increases instruction-following ability.

Co-Instruct (Wu et al., 2024): Co-Instruct is a dataset curated to compare the quality of 2-4 images in the format of open-ended answer or multi-choice QA format. It's similar to the tasks in the Qbench (Wu et al., 2023a).

NLVR2 (Suhr et al., 2018): NLVR2 is a natural language reasoning dataset grounded in images. The task is to determine whether a statement is true or false given the visual contents of 2 images. NLVR2 covers many linguistic phenomena, such as cardinality, existential quantifiers, universal quantifiers, etc.

Dreamsim (Fu et al., 2023): DreamSim proposes a dataset to train a model to judge image similarity. We reuse their datasets, and the task is to judge which candidate image is more similar to a reference image.

ImageCoDe (Krojer et al., 2022): ImageCoDe is a multimodal challenge called image retrieval from contextual descriptions, where a multimodal model is required to retrieve/select the correct image from a set of 10 minimally contrastive images. For each image, 9 similar images are retrieved from Open Images Dataset V6 (Kuznetsova et al., 2018) using CLIP encodings.

Contrast-Caption: Inspired by the paradigm of contrastive learning, we reformat existing image captioning tasks into a multi-image version, where 2 tasks are defined. Given multiple images, the first task we defined is to judge which image matches the provided caption, and the second task is to generate a caption for a denoted image. We randomly select 2 to 8 images along with their captions to form a single item, then apply the template of the 2 tasks defined. We used the images and captions provided by ShareGPT-4V (Chen et al., 2023) and LAION GPT-4V captions from LVIS (Schuhmann & Bevan, 2023).

Spot-the-diff (Jhamtani & Berg-Kirkpatrick, 2018): This is a dataset that requires the model to generate the difference description given 2 images. We use the processed version from MIMIC-IT (Li et al., 2023a).

LRV-multi (Liu et al., 2023a): This is a single-image dataset used to mitigate hallucinations of LMMs. We process it similarly to LLaVA-665k-multi to get a "synthetic" multi-image dataset.

Birds-to-Words (Forbes et al., 2019): The task of this dataset is to generate different descriptions and give 2 images of different birds. We directly take the training split for training. Besides, we prompt GPT-3.5-turbo to generate a possible question given the reference answer, so we can get a diverse question pool.

Multi-VQA: This dataset contains multi-image reasoning QA pairs, where each question is generated by GPT-4 based on the captions of the images. Each question is required to involve at least two images. Images and captions are sampled from ShareGPT-4V (Chen et al., 2023). The prompt template is in Table 2.

Video QA: We also include some video question answering datasets, including NExTQA (Xiao et al., 2021), STAR (Wu & Yu, 2021), and visual-story-telling (Huang et al., 2016). nextqa and star are the processed version from Flipped-VQA (Ko et al., 2023). The visual-story-telling are the processed version from MIMIC-IT (Li et al., 2023a).

Single-image-VQA: Instead of focusing only on multi-image tasks, we claim that it's necessary to also include some single-image VQA dataset to avoid catastrophic forgetting on single-image tasks. We included some of the single image data from LLaVA-665k as well as DocVQA (Mathew et al., 2020), DVQA (Kafle

et al., 2018), and ChartQA (Masry et al., 2022) to enhance its ability on diagrams and OCR. In practice, since the size of DVQA is too large, we only use 30k out of 200k examples for the training.