Generative vs Discriminative: Rethinking The Meta-Continual Learning

Abstract

Deep neural networks have achieved human-level capabilities in various learning tasks. However, they generally lose performance in more realistic scenarios like learning in a continual manner. In contrast, humans can incorporate their prior knowledge to learn new concepts efficiently without forgetting older ones. In this work, we leverage meta-learning to encourage the model to learn how to learn continually. Inspired by human concept learning, we develop a generative classifier that efficiently uses data-driven experience to learn new concepts even from few samples while being immune to forgetting. Along with cognitive and theoretical insights, extensive experiments on standard benchmarks demonstrate the effectiveness of the proposed method. The ability to remember all previous concepts, with negligible computational and structural overheads, suggests that generative models provide a natural way for alleviating catastrophic forgetting, which is a major drawback of discriminative models.

1 Introduction

Deep learning methods have gained great success in a wide variety of tasks in various fields [25, 27]. However, in many real-world scenarios, where the data samples are neither i.i.d. nor available all at once, most of them lose performance on the older data points; a phenomenon known as catastrophic forgetting [13]. Continual learning, also called lifelong learning, aims to tackle this problem [46].

Animals as intelligent learning agents can easily learn a sequence of different tasks with minimum interference and forgetting [53, 12]. When facing new problems, the brain does not rewire all of the wirings [35, 5] but utilizes lifelong accumulated inductive biases to efficiently learn new concepts [9, 4]. In the field of cognitive and neuroscience, there are also two special cases of concept learning named prototypical and exemplar-based learning [42, 2, 57, 7]. Bayesian inference is another aspect of learning in the brain which aims to consider uncertainty [24, 29, 16, 4, 23]. In this paper, we integrate the hypothesis of generative concept learning and the Bayesian approach by considering a distribution over each concept. Figure 1 compares different characteristics and expressive power of the mentioned concept learning approaches. Inspired by the biological mechanism of learning, we suggest that the generative approach in category learning is an important principle for continual learning problems. Although the Bayesian approach requires proper priors about each concept, meta-learning can be used to provide data-driven prior knowledge or statistics from the previously encountered concepts similar to the biological intelligent systems [4].

Meta-learning is an endeavor to gather experience from solving related problems in order to solve new unseen ones more efficiently; which have been used to improve the learning process in different areas [19]. In this work, we employ meta-learning to derive proper inductive biases as well as a powerful feature extractor for a continual learning problem from a collection of similar continual

Figure 1: A simple schematic of exemplar-based learning (left), prototypical-based learning (center), and the proposed Bayesian approach (right). Exemplar-based learning suffers from high memory consumption and also the risk of overfitting, like 1-NN classifiers. Prototypical-based learning is memory efficient but also prone to underfitting. Our probabilistic approach enables using complex enough distributions over each category to capture class variations.

learning problems. By taking advantage of these inductive biases, we formulate the category learning problem from a probabilistic generative approach. Our main contributions are as follows:

- We take motivation from cognitive and neuroscience about meta-continual learning in intelligent animals and especially make use of bio-inspired concept learning to eradicate catastrophic forgetting.
- We investigate the problem of discriminative approaches in continual learning and propose generative classifiers as a general way of mitigating catastrophic forgetting.
- Encouraged by generative classifiers, we propose a new update scheme for discriminative classifiers to reduce the catastrophic forgetting problem.
- Existing prototypical learning is improved by adding extra statistics through the Bayesian approach.
- Different components of the proposed method can be implemented in a fully incremental setting which is useful in the shortage of data or computational resources.
- We achieve state-of-the-art accuracy with a notable gap compared to the existing methods.

2   Related Works

Continual Learning: Three main approaches have been proposed to address the forgetting issue [31]. (i) Replay-based methods rely on reusing samples from previous training tasks either by keeping them in an explicit episodic memory [28, 34, 6, 1] or generating pseudo-samples via a deep generative model [41, 51, 48]. (ii) Methods based on parameter isolation dynamically expand the model as the data for new tasks arrive by introducing task-specific weights[38, 55, 40] or masks[50, 56]. (iii) Regularization based methods consider a probability distribution, typically the Gaussian family, over parameters and penalize the substantial deviations from the prior distribution learned through the earlier tasks. Taking a Bayesian approach will lead to an incremental posterior update which is naturally consistent with continual learning [30], while considering a point estimation for the parameters will results in a regularization term in the objective function [43, 58, 22]. Besides theoretical foundations, simplifying assumptions and approximations often make the regularization-based methods fail when the number of tasks is large and they are more prone to catastrophic forgetting compared to the first two approaches [47].

Compared to the first approach, merely storing low dimensional sufficient statistics of categories, makes our model extremely memory efficient and applicable even when there are thousands of tasks or categories. However, our method is more related to the second approach in the sense that we isolate class-specific parameters. Like the Bayesian methods [30], we also consider a distribution over parameters. Nevertheless in our method, using generative classifiers and restricting the distribution to the class-specific parameters enables exact closed-form solutions with zero forgetting.

Meta-Learning: Existing methods in the literature of meta-learning can be categorized into optimization-based [10, 33], black-box [39, 14], and metric-based [44, 45, 54] approaches. In this paper we use metric-based methods that meta-learn an embedding space in which a metric-based classifier performs well. Some methods called Bayesian meta-learning, approach the problem from a

probabilistic point of view, obtaining a distribution over the problem-specific parameters, therefore capable of providing information about the uncertainty of a learned model [15, 11, 52]. We also provide a probabilistic framework capable of using various statistics of data and learnable prior distributions.

Meta-Continual Learning: Both continual and meta-learning have mutual impacts on each other, introducing two new research branches [8]: Continual meta-learning [18, 21] and meta-Continual learning [17, 36, 20, 3]. In the second branch, various techniques from meta-learning are used to tackle catastrophic forgetting. Here, we especially focus on the settings in which explicit episodic meta-training on continual problems is used [20, 3]. OML [20] meta-learns a representation network to avoid interference between the continual tasks and reduce the catastrophic forgetting. ANML [3] also takes the same approach but instead of merely having a representation network, it generates a data-dependent mask that modulates the activity of neurons in the prediction network.

Motivated by them, we utilize episodic meta-learning to tackle the continual learning problem, but instead of having a discriminative approach, we propose a probabilistic generative method that is completely immune to forgetting. Our approach falls into metric-based meta-learning, as opposed to the prior methods that are optimization-based [20, 3].

3   Preliminaries

Meta-Learning: In the meta-learning setting, we have access to a set of meta-training problems $\mathcal{D}_{\text{meta-train}}$ which help to learn a prior knowledge and thus generalize to unseen problems with data from $\mathcal{D}_{\text{meta-test}}$. Each problem is a pair of support and query sets, i.e. $(\mathcal{S}, \mathcal{Q})$, and labels from $\mathcal{D}_{\text{meta-train}}$ do not intersect with the labels in $\mathcal{D}_{\text{meta-test}}$. The mentioned prior knowledge can be encoded in the meta-parameters θ which is utilized by a problem-specific model parameterized by ϕ to solve a new problem instance. The overall learning procedure of the meta-parameters can be formulated as [11]:

$$\theta^{\star} = \underset{\theta}{\arg\max} \log P(\theta \mid \mathcal{D}_{\text{meta-train}}). \tag{1}$$

And the distribution of the problem-specific parameters, given a support set $\mathcal{S}$, can be formulated as:

$$P(\phi \mid \mathcal{S}, \mathcal{D}_{\text{meta-train}}) = \int_{\theta} P(\phi \mid \mathcal{S}, \theta) P(\theta \mid \mathcal{D}_{\text{meta-train}}) \, d\theta$$
$$\approx P(\phi \mid \mathcal{S}, \theta^{\star}) P(\theta^{\star} \mid \mathcal{D}_{\text{meta-train}}) \propto P(\phi \mid \mathcal{S}, \theta^{\star}). \tag{2}$$

While some works model this distribution, others use a point estimate as:

$$\phi^{\star} = \underset{\phi}{\arg\max} \log P(\phi \mid \mathcal{S}, \theta^{\star}). \tag{3}$$

Meta-Continual Learning: A meta-learning scenario where each individual problem $(\mathcal{S}, \mathcal{Q})$ is continual, i.e. the support-set is observed continually, is called meta-continual learning. We consider support stream as $\mathcal{S} = \{\mathcal{S}_1, \mathcal{S}_2, ..., \mathcal{S}_t, ...\}$, in which $\mathcal{S}_t = \{(x_i^t, y_i^t)_{i=1}^{|\mathcal{S}_t|}\}$ and the x_i^t and y_i^t are the ith data point and the corresponding label in $\mathcal{S}_t$ respectively. Each $\mathcal{S}_t$ is accessible only at time-step t due to continual learning restriction. The query-set $\mathcal{Q}$ is a set of samples sharing the same set of labels as those in $\mathcal{S}$. The objective here is to perform well on $\mathcal{Q}$ after sequentially observing all of the samples available in $\mathcal{S}$. We use the notation $\mathcal{S}_X$ and $\mathcal{S}_Y$ for the data points and their labels in $\mathcal{S}$ respectively, and the same holds for $\mathcal{Q}_X$ and $\mathcal{Q}_Y$. Furthermore $\mathcal{S}_X^c$ shows the data points with the label $y = c$ available in $\mathcal{S}$, i.e. $\mathcal{S}_X^c = \{x | (x, c) \in \mathcal{S}\}$.

In this paper, we consider a model immune to catastrophic forgetting if the accuracy and decision boundaries of the model in continual learning and i.i.d. scenarios remain identical.

In the lifelong-learning literature, each S_t is called a learning task which may contain the data points and corresponding labels for multiple classes. With this in mind, three standard benchmarks are introduced for evaluation: task-incremental, domain-incremental, and class-incremental. The latest benchmark is known as the most difficult one in which each class is only observed in a single task while at the test-time the model is expected to classify across all observed classes from all tasks [47]. However, our proposed method is completely agnostic to the order in which data samples arrive and produces the same model, even in an extreme setting that we refer to as fully incremental. In this

Figure 2: Graphical models for the discriminative (left), generative (center), and our (right) approach.

setting, only one sample is available at each time step and each data point is visited exactly once. In fact, the only assumption in this work is that the samples with the same label in $\mathcal{S}$ are i.i.d., namely $P(\mathcal{S}^c) = \Pi_{x \in \mathcal{S}^c} P(x_i)$.

4   Method

Although recently meta-learning representations for continual learning have been introduced to alleviate the catastrophic forgetting [20, 3], these methods still greatly suffer from catastrophic forgetting. In the following subsections, we first shed light on the drawbacks of the existing meta-continual learning methods which originates from their discriminative nature. Then, we show how the generative approach can resolve the catastrophic forgetting problem of meta-continual learning. Finally, the proposed generative model for continual learning is presented.

4.1   Generative vs. Discriminative Approach

Probabilistic classifiers generally can be categorized into (1) Discriminative and (2) Generative models where they respectively model $P(Y \mid X)$, and $P(X \mid Y)$, demonstrated by Figure 2.

Given a classification problem $\mathcal{S} = \{\mathcal{S}_X, \mathcal{S}_Y\}$, the discriminative form of Equation 2 is:

$$P(\phi \mid \mathcal{S}_X, \mathcal{S}_Y, \theta^\star) \propto P(\mathcal{S}_Y \mid \phi, \mathcal{S}_X)P(\phi \mid \theta^\star). \tag{4}$$

In continual-learning settings, there is partial access to $\mathcal{S}$ at each time step, therefore the learning agent is prone to catastrophic forgetting. To clarify this, assume a class-incremental setting, where at each time step, the data of only one class is accessible but all the parameters are updated. Here, a trivial solution for each time step t (assuming uninformative prior $P(\phi \mid \theta^\star)$) is a model that assigns high probability to the currently available label even for samples from other categories. Therefore, the solution for each time step works poorly on other time steps.

The other choice for classifier formulation is the generative model which can be formulated as follows:

$$P(\phi \mid \mathcal{S}_X, \mathcal{S}_Y, \theta^\star) \propto P(\mathcal{S}_X \mid \phi, \mathcal{S}_Y)P(\phi \mid \theta^\star). \tag{5}$$

In this approach, there is no interference between learning of different classes and hence it does not suffer from forgetting. In fact, in each time step, only the parameters of those classes visited in that time step are changed and parameters of other classes are neither utilized nor updated.

Statement 1. In the class-incremental scenarios, The generative classifiers are immune to forgetting, given any class conditional parametric distributions.

Statement 2. In the fully incremental scenarios, The generative classifiers are immune to forgetting, if the class conditional distributions have incrementally-updatable sufficient statistics. In the case of Bayesian inference, this condition is satisfied if class conditional distributions have conjugate priors.

To provide more insights, here we compare Gaussian naive Bayes classifier (NB) and logistic regression (LR) as common generative and discriminative classifiers on a continual learning problem. We also implement a pseudo-generative version of the LR classifier (PGLR) to reduce the forgetting problem which is an inherent characteristic of the LR classifier. In the PGLR model, only the class-specific parameters are updated during optimization and the others remain frozen (see supplementary materials). Class-specific updates make the PGLR classifier one step closer to generative models and

Figure 3: Comparison of discriminative and generative approaches on a toy dataset in continual and i.i.d. scenarios. The first and second rows show the results of a Gaussian naive Bayes classifier and logistic regression as generative and discriminative classifiers respectively. The last row shows the performance of the described PGLR model. The average accuracy on all observed classes, current class samples, and the decision boundaries of each model are shown from the first to the sixth column. The last column shows the performance of each model in the i.i.d. batch learning setting.

prevent interference of tasks during learning. As shown in Figure 3, unlike the discriminative model, the generative models are immune to forgetting and there is no difference between the accuracy and decision boundaries of the continual (sixth column) and i.i.d. (seventh column) scenarios.

4.2 Proposed Model

As mentioned, generative classifiers are suitable for continual learning problems. However, the main challenge here is that training a reasonably expressive feature extractor is not straightforward in a fully generative manner. Hence, we employ meta-learning to tackle this challenge and propose a generative meta-continual learning (GeMCL) method. Like OML [20], we use a feature extractor network $f_\psi(X) : \mathcal{X} \to \mathbb{R}^d$, parametrized by ψ, that embeds the input into a proper d-dimensional representation space. However, inspired by the biological mechanism of concept learning, we incorporate a generative Bayesian classifier instead of using a discriminative one. Indeed, to have a tractable generative model, a proper representation space is first prepared by the embedding function and the optimal weights for this function are obtained via a meta-training procedure. Then, the hyper-parameters of the generative model in this space are computed based on $\mathcal{D}_{\text{meta-train}}$.

In the meta-test phase, the generative model on the test classes is formed using incrementally arriving samples in the embedding space and the meta-learned hyper-parameters. In this phase, same as the previous works [20, 3], the embedding parameters ψ are fixed. Moreover, in the prior continual learning works, it was investigated that the early representation layers are less responsible for forgetting, and remain nearly unchanged even after training for new tasks [32]. In fact, even a pretrained feature extractor along with a generative classifier outperforms the previous meta-continual models that are discriminative. We will investigate this more in Section 5.

4.2.1 Bayesian Generative Model

To derive a generative model, we need to choose a parametric family of distributions in the d-dimensional embedding space. We choose a Gaussian distribution to model each $P(z \mid Y = c)$ where $Z = f_\psi(X) \in \mathbb{R}^d$. In this generative model, we introduce $\mu^c \in \mathbb{R}^d$, $\lambda^c \in \mathbb{R}^d_+$ as the mean and precision of the class conditional Gaussian distributions respectively:

$$\forall_{1 \leq c \leq C} P\left(z \mid Y = c, \mu^{1:C}, \lambda^{1:C}\right) = \mathcal{N}\left(z \mid \mu^c, diag(\lambda^c)^{-1}\right), \tag{6}$$

where C denotes the number of observed classes, $\mu^{1:C} = \{\mu^1, \cdots, \mu^C\}$ and $\lambda^{1:C} = \{\lambda^1, \cdots, \lambda^C\}$ are the set of parameters for Gaussian distributions. To obtain a Bayesian perspective, we consider a Normal-Gamma prior for the mean and variance of each class:

$$P\left(\mu^c, \lambda^c \mid \alpha_0, \beta_0, \kappa_0, \mu_0\right) \propto \prod_{j=1}^{d} \mathcal{N}\left(\mu_j^c \mid \mu_0, (\kappa_0 \lambda_j^c)^{-1}\right) Ga\left(\lambda_j^c \mid \alpha_0, \beta_0\right), \tag{7}$$

where $\alpha_0, \beta_0, \kappa_0, \mu_0$ are the hyper-parameters of the generative model. Now, given the support set of each class in the embedding space, i.e. $f_\psi(\mathcal{S}_X^c) = \{f_\psi(x) \mid \forall x \in \mathcal{S}_X^c\}$, the posterior and the predictive distributions are in the form of Normal-Gamma and student's t-distribution respectively:

$$P\left(\mu^c, \lambda^c \mid f_\psi(\mathcal{S}_X^c), \alpha_0, \beta_0, \kappa_0, \mu_0\right) \propto \prod_{j=1}^{d} \mathcal{N}\left(\mu_j^c \mid \mu_{n,j}^c, (\kappa_n^c \lambda_j^c)^{-1}\right) Ga\left(\lambda_j^c \mid \alpha_n^c, \beta_{n,j}^c\right), \quad (8)$$

$$P\left(z \mid f_\psi(\mathcal{S}_X^c), \alpha_0, \beta_0, \kappa_0, \mu_0\right) = \prod_{j=1}^{d} t_{2\alpha_n^c}\left(z_j \mid \mu_{n,j}^c, \frac{\beta_{n,j}^c(\kappa_n^c + 1)}{\alpha_n^c \kappa_n^c}\right), \quad (9)$$

where $\alpha_n^c, \beta_{n,j}^c, \kappa_n^c, \mu_{n,j}^c$ are the posterior parameters after observing n^c samples of the class c, i.e.:

$$n^c = |S^c|, \quad \bar{z}_j^c = \frac{1}{n^c}\Sigma_{z \in f_\psi(\mathcal{S}_X^c)}z_j, \quad \kappa_n^c = \kappa_0 + n^c, \quad \mu_{n,j}^c = \frac{\kappa_0\mu_0 + n^c\bar{z}_j^c}{\kappa_n^c},$$

$$\alpha_n^c = \alpha_0 + \frac{n^c}{2}, \quad \beta_{n,j}^c = \beta_0 + \frac{1}{2}\Sigma_{z \in f_\psi(\mathcal{S}_X^c)}(z_j - \bar{z}_j^c)^2 + \frac{\kappa_0 n^c(\bar{z}_j^c - \mu_0)^2}{2(\kappa_0 + n^c)}. \quad (10)$$

At test time, it suffices to compute and store the above posterior parameters for each class separately. It is easy to show that the parameters can be updated incrementally as each sample arrives (see supplementary materials for detailed computations and incremental formulations).

It is noteworthy that all continual learning algorithms have to somehow support the new incoming classes, hence they have the obligation to expand the classifier parameters. While some of them mention this issue directly [34], others may consider an upper-bound on the number of classes [20]. Compared to their methods, our approach has no assumption on the maximum number of incoming classes, making it flexible for unknown length sequence of classes.

Using the Eq. 3, we also propose a method called MAP-GeMCL, which uses MAP estimation for the mean and precision of the Gaussian distributions instead of the predictive distribution:

$$\mu_{\text{MAP}}^c, \lambda_{\text{MAP}}^c = \underset{\mu^c, \lambda^c}{\text{argmax}} P\left(\mu^c, \lambda^c \mid f_\psi(\mathcal{S}_X^c), \alpha_0, \beta_0, \kappa_0, \mu_0\right) = \mu_n^c, \frac{\alpha_n^c - \frac{1}{2}}{\beta_n^c}$$

$$P\left(z \mid f_\psi(\mathcal{S}_X^c), \alpha_0, \beta_0, \kappa_0, \mu_0\right) \approx \mathcal{N}\left(z \mid \mu_{\text{MAP}}^c, diag(\lambda_{\text{MAP}}^c)^{-1}\right). \quad (11)$$

In order to adjust the hyper parameters for the prior distribution, we chose $\mu_0 = 0$ and $\kappa_0 = 0$ to provide a flat prior distribution for μ. α_0, β_0 are meta-learned as described in the next section.

4.2.2 Meta-Training And Meta-Testing

Following the previous meta-learning works, we first use episodic meta-learning to train the parameters of the embedding network. Although we consider a generative model in the embedding space, in the meta-training phase the embedding function itself is trained using a discriminative objective to avoid trivial solutions like $\forall x f_\psi(x) = c$. So using the generative forms presented in the previous section, we write the cross-entropy loss for a single episode as:

$$\mathcal{L}(\psi) = -\sum_{(x,y) \in \mathcal{Q}} \log P\left(y \mid f_\psi(x), f_\psi(\mathcal{S}_X), \mathcal{S}_Y, \alpha_0, \beta_0\right)$$

$$= -\sum_{(x,y) \in \mathcal{Q}} \log \frac{P(f_\psi(x) | y, f_\psi(\mathcal{S}_X), \mathcal{S}_Y, \alpha_0, \beta_0)}{\sum_{\hat{y}=1}^{C} P(f_\psi(x) | \hat{y}, f_\psi(\mathcal{S}_X), \mathcal{S}_Y, \alpha_0, \beta_0)} = -\sum_{(x,y) \in \mathcal{Q}} \log \frac{P\left(f_\psi(x) | f_\psi(\mathcal{S}_X^y), \alpha_0, \beta_0\right)}{\sum_{\hat{y}=1}^{C} P\left(f_\psi(x) | f_\psi(\mathcal{S}_X^{\hat{y}}), \alpha_0, \beta_0\right)} \quad (12)$$

Here, α_0 and β_0 are two hyperparameters that define the shape of prior Gamma distribution for precision parameter. During the meta-training, we set them to large values to better regularize the contractile behavior of embedding samples by imposing high variance on the embedding space of each category. Before the meta-testing phase, we calculate within-category variances of meta-train data embeddings and then use the obtained distribution to infer the amount of α_0 and β_0 by maximum likelihood estimation (see supplementary materials for more details).

210 Finally, in the meta-testing phase, we use estimated α_0 and β_0 for the prior distributions and update
211 the class-specific posterior parameters as the support stream arrives. Then, to classify a query data
212 point, we use $\hat{y} = \underset{y}{\text{argmax}}\, P\left(f_\psi(x) \mid \alpha_n^y, \beta_n^y, \mu_n^y, \kappa_n^y\right)$ as the predicted label.

5 Experiments

214 Following prior works [20, 3], we have performed our experiments on the Omniglot [26] and the
215 Mini-ImageNet [49] datasets. For both datasets, we used the backbones proposed in [44] with an
216 input size of 84×84, which uses less than 115K parameters compared to more than 3.9M ones in
217 the prior works [20, 3]. This backbone is meta-trained with a learning rate of 0.001 decaying to half
218 every 2000 and 3000 steps for the omniglot and imagenet respectively. The training is continued to a
219 maximum of 20K and 30K meta-train episodes for the omniglot and imagenet respectively, and the
220 best performing model is selected according to the meta-validation set.

221 The **Ominglot** dataset is commonly used in the meta-learning literature, containing 1623 classes
222 of handwritten characters each with 20 samples. We use 700 and 200 classes for meta-train and
223 meta-validation respectively, and others for meta-test. The reported experiments are done using
224 20-way 5-shot train episodes and 200-way 15-shot validation episodes with 15 and 5 query samples
225 respectively.

226 The **Mini-ImageNet** dataset is a subset of the ImageNet [37], originally proposed for evaluating
227 few-shot learning algorithms [49]. The dataset consists of 100 classes with 600 samples for each
228 class, and is divided into 64, 16, 20 classes for train, validation, and test meta-phases respectively. For
229 this dataset we used 20-way 10-shot and 20-way 30-shot train and validation episodes respectively
230 with 30 query samples for both. We apply horizontal flip and random crop augmentations during
231 meta-training.

232 For further insights, we introduce the following baselines in addition to the mentioned prior meta-
233 continual learning methods, OML and ANML. [3, 20].

234 **Meta-Trained Logistic Regression (MTLR):** We implement a fully discriminative baseline similar
235 to the OML in methodology but incorporating the simple backbone used in the other baselines.
236 Moreover, some implementation details of the OML are omitted in this baseline, to purely compare
237 different aspects of our proposed methods (refer to the supplementary materials for details).

238 **Pseudo-Generative Logistic Regression (PGLR):** This method was introduced in Section 4.1 to
239 limit the amount of forgetting in the discriminative settings. This baseline can be obtained by
240 applying two modifications to the MTLR: (i) To compute the logits, the class-specific weights are
241 normalized before dot-production. (ii) During the optimization, instead of updating all weights of the
242 classifier head, only the weights corresponding to the available sample are updated (see supplementary
243 materials).

244 **Prototypical:** This method was originally introduced for few-shot classification [44]. Here, we
245 employ this approach for the meta-continual learning scenarios. Indeed, this model is a special case
246 of our proposed method by choosing a unit-variance Gaussian model, and completely omitting the
247 prior distributions in Section 4.2.1 and merely using the maximum likelihood estimation instead.

248 **Pretrained:** To clarify the impact of meta-training on different models, we pretrain the same
249 backbone and replace it with the meta-trained feature extractors in some experiments.

5.1 Results

251 In Figure 4, we evaluate our baselines, proposed methods, and two previous meta-continual methods
252 from different perspectives. As shown in, our method (GeMCL) outperforms the OML and ANML
253 by a large margin on both datasets. This margin grows as the length of continual problems increases.
254 In fact, when observing more classes, the catastrophic forgetting causes a more notable performance
255 drop in the discriminative models. Comparing the first class accuracy during test episodes, gives
256 even better insights on the forgetting issue, as the earlier seen samples are more likely to be forgotten.
257 Comparing the first class accuracy shows that the comparably small performance loss of the generative
258 models (GeMCL and Prototypical) is due to generalization issues, not forgetting. Another way of
259 enlarging the problem size is by observing more samples per each class. While more support data

Figure 4: Effect of increasing the number of classes per problem on the Omniglot dataset. The effect is measured based on the first seen class (left) and the overall performance (middle and right). The generative methods can be better compared to each other on the right-hand side, separated from the other models.

Figure 5: Effect of increasing the number of classes per problem (left) and the number of samples per class (middle and right) on the Mini-Imagenet dataset. The latter effect is measured on both the overall performance (right) and the performance on the first seen class (middle).

should enhance the performance, the forgetting issue causes lower accuracy in the OML after a certain threshold. However, as the generative models do not suffer from forgetting, they perform even better in higher shots.

The prototypical baseline performs pretty well compared to the discriminative models, but its lower performance compared to the GeMCL shows the effect of using additional statistics and trainable prior distributions, especially with more shots or classes the performance gap increases.

Table 1 compares different aspects of the baselines in a standard scenario. Comparing the i.i.d. settings to continual, shows that generative approaches are more robust to accuracy fall in continual learning. The results of using a pretrained feature extractor compared to meta-training show that the GeMCL properly utilizes meta-learning to achieve better performance, which is not the case for the MTLR and PGLR in some settings. Moreover, the performance of the GeMCL is superior to most of baselines even in the i.i.d. settings.

6   Discussion

In the present study, inspired by neuroscience, we propose a probabilistic generative classifier that is completely immune to catastrophic forgetting. We utilize meta-learning to provide a rich feature extractor and prior knowledge about hyperparameters. Using this feature extractor, the proposed lightweight generative classifier achieves high accuracy for new unseen continual learning problems. It is noteworthy that our proposed method meta-learns hyperparameters on the meta-train dataset, and uses the same values for all meta-test episodes, but the optimization-based methods are highly

Table 1: The performance of the MTLR (discriminative), PGLR (pseudo-generative), and GeMCL (generative) methods in their original meta-learning approach compared with their performance when using pretrained feature extractor. All of the models are evaluated on Mini-Imagenet with 20-way 100-shot setting and Omniglot dataset with 600-way 15-shot setting.

Dataset	Mode	Head for Pretrained Backbone			Meta-train		
		MTLR	PGLR	GeMCL	MTLR	PGLR	GeMCL
Mini-Imagenet	Continual	$32.8_{\pm3.1}$	$54.2_{\pm1.0}$	$55.9_{\pm1.1}$	$28.5_{\pm0.4}$	$48.05_{\pm0.6}$	$\mathbf{59.2}_{\pm0.9}$
	IID	$\mathbf{60.9}_{\pm1.0}$	$55.83_{\pm1.}$	$55.9_{\pm1.1}$	$48.9_{\pm1.1}$	$57.0_{\pm0.9}$	$59.2_{\pm0.9}$
Omniglot	Continual	$23.6_{\pm0.7}$	$61.0_{\pm0.8}$	$75.9_{\pm0.8}$	$61.9_{\pm0.7}$	$72.8_{\pm0.6}$	$\mathbf{86.9}_{\pm0.6}$
	IID	$77.8_{\pm0.7}$	$74.2_{\pm0.6}$	$75.9_{\pm0.8}$	$82.9_{\pm0.5}$	$86.8_{\pm0.5}$	$\mathbf{86.9}_{\pm0.6}$

sensitive to the inner learning rate used in the meta-test, which needs to be re-tuned for different test settings.

Our proposed method is efficient in different aspects: First, the employed backbone is light and overall computations are negligible compared to the current deep learning methods or other meta-continual learning approaches. Opposed to the previous meta-continual methods our proposed method does not use second-order optimization and is even more lightweight by design. Moreover, the proposed model can be implemented in a fully incremental manner, reducing the need for powerful computation resources. Second, our method is scalable and memory-efficient in the sense that it does not store data samples, in contrast to the memory-based continual learning methods [28, 34]. With these in mind, our method can be used with much less energy consumption while achieving better results, making it more planet-friendly. We also propose an optimization-based baseline, called PGLR, to enhance robustness to forgetting, However, high energy consumption is still a downside of this baseline.

The proposed method has three main components. First, generative classifiers make our method immune to forgetting. Second, meta-learning makes training a deep generative classifier feasible. Third, the Bayesian approach improves the performance and interpretability of the model. However, there are also some shortcomings in the proposed method. Our method requires a meta-train dataset to train a good embedding network and also during the meta-test, the embedding function does not adapt to new samples. This property offers protection from forgetting, but it may also reduce the generalization capability that reduces the overall performance, especially in scenarios that the number of continual tasks is limited and forgetting is not a major issue for other methods.

Last but not the least, by taking the advantage of generative learning we extend our approach to discriminative classifiers through a hard regularization trick during optimization. Most of the existing continual learning methods use a discriminative approach for classification and try to overcome forgetting by employing various tricks such as using episodic memory [28, 34], parameter isolation [38], or various regularization techniques [22, 58]. Considering class-specific parameterization of our generative approach, continual learning methods based on parameter isolation are close to us as these methods try to divide parameters into task-specific partitions. Regularization-based techniques are also related to us since they try to penalize drift in parameters that are important for previous tasks.

References

[1] Rahaf Aljundi, Min Lin, Baptiste Goujaud, and Yoshua Bengio. Gradient based sample selection for online continual learning. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/e562cd9c0768d5464b64cf61da7fc6bb-Paper.pdf.

[2] F Gregory Ashby and W Todd Maddox. Human category learning. *Annu. Rev. Psychol.*, 56:149–178, 2005.

[3] Shawn Beaulieu, Lapo Frati, Thomas Miconi, Joel Lehman, Kenneth O. Stanley, Jeff Clune, and Nick Cheney. Learning to continually learn, 2020.

[4] Pietro Berkes, Gergő Orbán, Máté Lengyel, and József Fiser. Spontaneous cortical activity reveals hallmarks of an optimal internal model of the environment. *Science*, 331(6013):83–87, 2011.

[5] Maura Boldrini, Camille A Fulmore, Alexandria N Tartt, Laika R Simeon, Ina Pavlova, Verica Poposka, Gorazd B Rosoklija, Aleksandar Stankov, Victoria Arango, Andrew J Dwork, et al. Human hippocampal neurogenesis persists throughout aging. *Cell stem cell*, 22(4):589–599, 2018.

[6] Zalán Borsos, Mojmir Mutny, and Andreas Krause. Coresets via bilevel optimization for continual learning and streaming. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 14879–14890. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/aa2a77371374094fe9e0bc1de3f94ed9-Paper.pdf.

[7] Caitlin R Bowman, Takako Iwashita, and Dagmar Zeithamova. Tracking prototype and exemplar representations in the brain across learning. *Elife*, 9:e59360, 2020.

[8] Massimo Caccia, Pau Rodriguez, Oleksiy Ostapenko, Fabrice Normandin, Min Lin, Lucas Page-Caccia, Issam Hadj Laradji, Irina Rish, Alexandre Lacoste, David Vázquez, and Laurent Charlin. Online fast adaptation and knowledge accumulation (osaka): a new approach to continual learning. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 16532–16545. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/c0a271bc0ecb776a094786474322cb82-Paper.pdf.

[9] Kenji Doya. Metalearning and neuromodulation. *Neural networks*, 15(4-6):495–506, 2002.

[10] Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, pages 1126–1135. PMLR, 2017.

[11] Chelsea Finn, Kelvin Xu, and Sergey Levine. Probabilistic model-agnostic meta-learning. *arXiv preprint arXiv:1806.02817*, 2018.

[12] Timo Flesch, Jan Balaguer, Ronald Dekker, Hamed Nili, and Christopher Summerfield. Comparing continual task learning in minds and machines. *Proceedings of the National Academy of Sciences*, 115(44): E10313–E10322, 2018.

[13] Robert M French. Catastrophic forgetting in connectionist networks. *Trends in cognitive sciences*, 3(4): 128–135, 1999.

[14] Marta Garnelo, Dan Rosenbaum, Christopher Maddison, Tiago Ramalho, David Saxton, Murray Shanahan, Yee Whye Teh, Danilo Rezende, and SM Ali Eslami. Conditional neural processes. In *International Conference on Machine Learning*, pages 1704–1713. PMLR, 2018.

[15] Erin Grant, Chelsea Finn, Sergey Levine, Trevor Darrell, and Thomas Griffiths. Recasting gradient-based meta-learning as hierarchical bayes. *arXiv preprint arXiv:1801.08930*, 2018.

[16] Thomas L Griffiths and Joshua B Tenenbaum. Optimal predictions in everyday cognition. *Psychological science*, 17(9):767–773, 2006.

[17] Gunshi Gupta, Karmesh Yadav, and Liam Paull. Look-ahead meta learning for continual learning. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 11588–11598. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/85b9a5ac91cd629bd3afe396ec07270a-Paper.pdf.

[18] Xu He, Jakub Sygnowski, Alexandre Galashov, Andrei A. Rusu, Yee Whye Teh, and Razvan Pascanu. Task agnostic continual learning via meta learning, 2019.

[19] Timothy Hospedales, Antreas Antoniou, Paul Micaelli, and Amos Storkey. Meta-learning in neural networks: A survey. *arXiv preprint arXiv:2004.05439*, 2020.

[20] Khurram Javed and Martha White. Meta-learning representations for continual learning. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL `https://proceedings.neurips.cc/paper/2019/file/f4dd765c12f2ef67f98f3558c282a9cd-Paper.pdf`.

[21] Ghassen Jerfel, Erin Grant, Tom Griffiths, and Katherine A Heller. Reconciling meta-learning and continual learning with online mixtures of tasks. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL `https://proceedings.neurips.cc/paper/2019/file/7a9a322cbe0d06a98667fdc5160dc6f8-Paper.pdf`.

[22] James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, Demis Hassabis, Claudia Clopath, Dharshan Kumaran, and Raia Hadsell. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114(13):3521–3526, 2017. ISSN 0027-8424. doi: 10.1073/pnas.1611835114. URL `https://www.pnas.org/content/114/13/3521`.

[23] David C Knill and Alexandre Pouget. The bayesian brain: the role of uncertainty in neural coding and computation. *TRENDS in Neurosciences*, 27(12):712–719, 2004.

[24] Konrad P Körding and Daniel M Wolpert. Bayesian integration in sensorimotor learning. *Nature*, 427 (6971):244–247, 2004.

[25] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25:1097–1105, 2012.

[26] Brenden Lake, Ruslan Salakhutdinov, Jason Gross, and Joshua Tenenbaum. One shot learning of simple visual concepts. In *Proceedings of the annual meeting of the cognitive science society*, volume 33, 2011.

[27] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

[28] David Lopez-Paz and Marc' Aurelio Ranzato. Gradient episodic memory for continual learning. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30, pages 6467–6476. Curran Associates, Inc., 2017. URL `https://proceedings.neurips.cc/paper/2017/file/f87522788a2be2d171666752f97ddebb-Paper.pdf`.

[29] Wei Ji Ma, Jeffrey M Beck, Peter E Latham, and Alexandre Pouget. Bayesian inference with probabilistic population codes. *Nature neuroscience*, 9(11):1432–1438, 2006.

[30] Cuong V. Nguyen, Yingzhen Li, Thang D. Bui, and Richard E. Turner. Variational continual learning. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=BkQqq0gRb`.

[31] German I. Parisi, Ronald Kemker, Jose L. Part, Christopher Kanan, and Stefan Wermter. Continual lifelong learning with neural networks: A review. *Neural Networks*, 113:54–71, 2019. ISSN 0893-6080. doi: https://doi.org/10.1016/j.neunet.2019.01.012. URL `https://www.sciencedirect.com/science/article/pii/S0893608019300231`.

[32] Vinay Venkatesh Ramasesh, Ethan Dyer, and Maithra Raghu. Anatomy of catastrophic forgetting: Hidden representations and task semantics. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=LhY8QdUGSuw`.

[33] Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. 2016.

[34] S. Rebuffi, A. Kolesnikov, G. Sperl, and C. H. Lampert. icarl: Incremental classifier and representation learning. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5533–5542, 2017. doi: 10.1109/CVPR.2017.587.

[35] Blake A Richards and Paul W Frankland. The persistence and transience of memory. *Neuron*, 94(6): 1071–1084, 2017.

[36] Matthew Riemer, Ignacio Cases, Robert Ajemian, Miao Liu, Irina Rish, Yuhai Tu, , and Gerald Tesauro. Learning to learn without forgetting by maximizing transfer and minimizing interference. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=B1gTShAct7`.

[37] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge, 2015.

[38] Andrei A. Rusu, Neil C. Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks, 2016.

[39] Adam Santoro, Sergey Bartunov, Matthew Botvinick, Daan Wierstra, and Timothy Lillicrap. Meta-learning with memory-augmented neural networks. In *International conference on machine learning*, pages 1842–1850. PMLR, 2016.

[40] Jonathan Schwarz, Wojciech Czarnecki, Jelena Luketina, Agnieszka Grabska-Barwinska, Yee Whye Teh, Razvan Pascanu, and Raia Hadsell. Progress & compress: A scalable framework for continual learning. In Jennifer Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 4528–4537, Stockholmsmässan, Stockholm Sweden, 10–15 Jul 2018. PMLR. URL `http://proceedings.mlr.press/v80/schwarz18a.html`.

[41] Hanul Shin, Jung Kwon Lee, Jaehong Kim, and Jiwon Kim. Continual learning with deep generative replay. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL `https://proceedings.neurips.cc/paper/2017/file/0efbe98067c6c73dba1250d2beaa81f9-Paper.pdf`.

[42] J David Smith and John Paul Minda. Prototypes in the mist: The early epochs of category learning. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, 24(6):1411, 1998.

[43] Alex J Smola, SVN Vishwanathan, and Eleazar Eskin. Laplace propagation. In *NIPS*, pages 441–448, 2004.

[44] Jake Snell, Kevin Swersky, and Richard S Zemel. Prototypical networks for few-shot learning. *arXiv preprint arXiv:1703.05175*, 2017.

[45] Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip HS Torr, and Timothy M Hospedales. Learning to compare: Relation network for few-shot learning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1199–1208, 2018.

[46] Sebastian Thrun. Is learning the n-th thing any easier than learning the first? In *Advances in neural information processing systems*, pages 640–646. MORGAN KAUFMANN PUBLISHERS, 1996.

[47] Gido M. van de Ven and Andreas S. Tolias. Three scenarios for continual learning, 2019.

[48] Gido M. van de Ven, Hava T. Siegelmann, and Andreas S. Tolias. Brain-inspired replay for continual learning with artificial neural networks. *Nature Communications*, 11(1), August 2020. doi: 10.1038/s41467-020-17866-2. URL `https://doi.org/10.1038/s41467-020-17866-2`.

[49] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. *arXiv preprint arXiv:1606.04080*, 2016.

[50] Mitchell Wortsman, Vivek Ramanujan, Rosanne Liu, Aniruddha Kembhavi, Mohammad Rastegari, Jason Yosinski, and Ali Farhadi. Supermasks in superposition. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 15173–15184. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/ad1f8bb9b51f023cdc80cf94bb615aa9-Paper.pdf`.

[51] Chenshen Wu, Luis Herranz, Xialei Liu, yaxing wang, Joost van de Weijer, and Bogdan Raducanu. Memory replay gans: Learning to generate new categories without forgetting. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31, pages 5962–5972. Curran Associates, Inc., 2018. URL `https://proceedings.neurips.cc/paper/2018/file/a57e8915461b83adefb011530b711704-Paper.pdf`.

[52] Jin Xu, Jean-Francois Ton, Hyunjik Kim, Adam Kosiorek, and Yee Whye Teh. Metafun: Meta-learning with iterative functional updates. In *International Conference on Machine Learning*, pages 10617–10627. PMLR, 2020.

[53] Guang Yang, Feng Pan, and Wen-Biao Gan. Stably maintained dendritic spines are associated with lifelong memories. *Nature*, 462(7275):920–924, 2009.

[54] Han-Jia Ye, Hexiang Hu, De-Chuan Zhan, and Fei Sha. Few-shot learning via embedding adaptation with set-to-set functions. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 8808–8817, 2020.

[55] Jaehong Yoon, Eunho Yang, Jeongtae Lee, and Sung Ju Hwang. Lifelong learning with dynamically expandable networks. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=Sk7KsfW0-`.

[56] Jaehong Yoon, Saehoon Kim, Eunho Yang, and Sung Ju Hwang. Scalable and order-robust continual learning with additive parameter decomposition. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=r1gdj2EKPB`.

[57] Dagmar Zeithamova, Michael L Mack, Kurt Braunlich, Tyler Davis, Carol A Seger, Marlieke TR van Kesteren, and Andreas Wutz. Brain mechanisms of concept learning. *Journal of Neuroscience*, 39(42): 8259–8266, 2019.

[58] Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual learning through synaptic intelligence. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 3987–3995, International Convention Centre, Sydney, Australia, 06–11 Aug 2017. PMLR. URL `http://proceedings.mlr.press/v70/zenke17a.html`.