Graph Q-Learning
for Combinatorial Optimization

Abstract

Graph-structured data is ubiquitous throughout natural and social sciences, and Graph Neural Networks (GNNs) have recently been shown to be effective at solving prediction and inference problems on graph data. In this paper, we propose and demonstrate that GNNs can and should be applied to solve Combinatorial Optimization (CO) problems. Combinatorial Optimization (CO) concerns optimizing a function over a discrete solution space that is often intractably large. To learn to solve CO problems, we phrase specifying a candidate solution as a sequential decision making problem, where the return is related to how close the candidate solution is to optimality. We use a GNN to learn a policy to iteratively build increasingly promising candidate solutions. We present preliminary evidence that GNNs trained through Q-Learning can solve CO problems with performance approaching state-of-the-art heuristic-based solvers, using only a fraction of the parameters and training time.

1   Introduction

Many important real-world problems, from social networks to chemical systems, are naturally represented as graphs. Over the past five years, graph neural networks (GNNs) have emerged as a powerful approach for machine learning on such structural data [1], [2] by combining the representation learning capabilities of deep networks with bespoke adaptation based on graph properties. These approaches have achieved been effective in node classification [3], relation prediction [4], and graph classification [5]. More recently, the community has been exploring other applications [6] for GNNs and analyzing their theoretical limitations and mathematical properties [7].

Many of these successes have focused on prediction or inference problems. In this work, we demonstrate that GNNs can be applied to solve a different class of problems: Combinatorial Optimization (CO) problems are often encountered across diverse fields and are difficult to solve exactly. CO problems require optimizing a function over a combinatorial space, possibly subject to constraints; examples include finding the minimum spanning tree (MST) in a graph or determining if there exists a variable assignment that satisfies a given Boolean formula (k-SAT). The ubiquity of CO across domains and applications led to the development of heuristic-based solvers in the early days of computer engineering that remain state-of-the-art today [8].

Motivated by deep learning's success at learning representations that outperform hand-engineered features, we explore whether GNNs can learn to outperform heuristic-based CO solvers when trained via reinforcement learning (RL). Our specific contributions are:

1. Representing instances of combinatorial optimization problems as graphs and framing finding their optimal solution as a Markov decision process (MDP).

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

2. Showing how GNNs can be used to solved these types of problems and that this formulation generalizes to a form of meta-learning.

3. Demonstrating empirically that we meet the performance of other algorithms and baseline heuristics with a fraction of the parameters and training time.

2 Literature Review

The current research landscape in the field of graph based learning consist of theoretical improvements to the architecture [9], [10], explorations of limitations [11], and applications to a variety of domains through supervised learning.

Graph neural networks have only very recently transitioned into usage in the context of RL. However rather than end-to-end, GNNs are employed in a modularized fashion: Li *et al.* [12] use a GNN for inferring a graph given sequential data streams. Xiao *et al.* [13] employ a graph attention network (GAT) in a multi-agent RL context, but for optimal reward balancing to speed up the learning process. Liu *et al.* [14] is using a GNN for game abstraction to simplify complex multiplayer games. Ma *et al.* [15] leverage the node update to mimic k-logit in a two-player zero-sum games.

Very few papers explore GNNs in the context of CO [16]. These works focus on solving the travelling salesperson problem only, tailoring their implementation to fit this task specifically, and use GNNs as a search heuristics to prune the solution space rather than training a solver directly.

3 Preliminaries

Combinatorial optimization (CO) refers to optimizing an objective function whose domain is a discrete but combinatorially large configuration space, making the space of possible solutions typically too large to search exhaustively. Examples of well-known combinatorial optimization problems include the Travelling Salesman Problem (TSP), Minimum Spanning Tree (MST), and Boolean Satisfiability (SAT). While some instances of CO problems can be solved exactly through Branch-and-Bound, many are NP-Hard. We generally must resort to specialized heuristics that rule out large parts of the search space or approximation algorithms. Formally, a combinatorial optimization problem A is defined by the tuple $(\mathcal{I}, f, m, g)$, where $\mathcal{I}$ is a set of instances, $x \in \mathcal{I}$ is an instance, $f(x)$ is the finite set of feasible solutions y, $m(x, y)$ denotes the measure of $y = f(x)$, and g is the goal function, i.e. usually $\max$ or $\min$. The goal is then to find for some instance x an optimal solution, that is, a feasible solution y with

$$m(x, y) = g\{m(x, y') \mid y' \in f(x)\}. \tag{1}$$

In **graph-based Learning**, a GNN layer can be viewed as a message-passing step [17], where each node updates its state by aggregating messages flowing from its direct neighbors.

A graph is a tuple of nodes and edges $\mathcal{G} = (\mathcal{V}, \mathcal{E})$. The one-hop neighborhood of node u is $\mathcal{N}_u = \{v \in V \mid (v, u) \in \mathcal{E}\}$. A node feature matrix $X \in R^{|V| \times k}$ gives the k features of node u as x_u; we omit edge- and graph-level features for clarity. A (message passing) GNN over this graph is then executed as:

$$\mathbf{h}_u = \psi \mathrm{AGG}\big(\{\phi(x_u, x_v) | v \in \mathcal{N}_u\}\big) \tag{2}$$

where $\psi \colon R^k \times R^k \to R^k$ is a message function, $\phi \colon R^k \to R^k$ is a readout function, and AGG is a permutation-invariant aggregation function (such as Σ or $\max$). Both ϕ and ψ can be realised as MLPs, but many special cases exist, such as attentional GNNs [18].

Reinforcement Learning (RL) considers an agent learning how to select actions in an environment to maximize their long-term cumulative rewards, i.e., the return, in a sequential decision-making process [19]. The environment is modeled as a Markov Decision Process (MDP), defined by the tuple $(\mathcal{S}, \mathcal{A}, p, r, \gamma)$ with $\mathcal{S} = \{s\}$ the set of states, $\mathcal{A} = \{a\}$ the set of actions, $p(s' \mid s, a)$ the state transition distribution, $r \colon \mathcal{A} \times \mathcal{S} \to \mathcal{R}$ a bounded reward function, and γ the discount factor. RL aims to find a policy $\pi \colon \mathcal{S} \to \mathcal{A}$ that maps a state s to an optimal action a. Optimality is defined as maximizing the expected return.

Model-free RL refers to learning a policy or Q-function, though a form of trial-and-error, without explicitly modeling the transition probability distribution p or the reward function r. Deep Q-learning

[20] is a simple algorithm but can suffer from overestimation bias and catastrophic forgetting. Several other methods have been introduced to reduce overestimation bias: Weighted double Q-learning [21], for example, uses a weighted combination of the double Q-learning estimate, which likely has underestimation bias.

4 Method

We frame combinatorial optimization problems as a sequential decision making processes, where the return is related to how close a candidate solution is to optimal. We then use a GNN to learn a policy to select sequences of actions make up increasingly promising candidate solutions. We are interested in solving general classes of CO problems, but in this work we focus on the flexible Job Shop Scheduling problem (FJSP).

4.1 Problem Definition

The classical job-shop scheduling problem (JSSP) [22] defines n jobs that consist of sets of operations o_i of varying processing time each, which need to be processed in a specific order as specified by a set of precedence constraints. Each operation is assigned to one of m machines and the goal is to find a processing schedule that minimizes the makespan, i.e., the total length of the schedule from the start of the first job to the end of the last. The FJSP [23] is a generalization of the classical JSSP that allows processing operations on one machine out of a set of alternative machines. The FJSP is an NP-hard problem consisting of two sub-problems, which are the assignment and the scheduling problems. The scheduling problem by itself reduces to the classical JSSP. Viable solutions are evaluated with respect to their makespan, which is defined as the time difference between start and finish of a sequence of jobs or tasks.

In this paper, proposing a solution to an instance of the FJSP is treated as a sequential decision-making process, which iteratively takes a scheduling action to assign an operation to a compatible machine at each state until all operations are scheduled. The proposed workflow is shown in fig. 1.

Figure 1: Training cycle.

4.2 Combinatorial Optimization as MDPs

By reformualting FJSP as a sequential decision making problem, more specifically a Markov Decision Process (MDP), we can use traditional RL methods to find viable solutions to a given FJSP. The initial state s_0 defines the problem statement, e.g, it defines how many machines are available, how many operations will need to be processed, and in which sequence. A each timestep t, an action a_t specifies the identity of an unassigned operation to be added to the end of the queue of a machine. Consequentially, a state s_t defines the resource allocation and processing sequence defined so far. A sequence ends when all operations of all jobs have been assigned to a machine, which will be the proposed solution to the problem instance. If the agent assigns operations with upstream requirements first, these operations can not be executed and render a machine idle until its requirements are met. Gridlock defines the state where all machines are idle by assignment.

During a rollout, previously assigned jobs can start processing and the agent will receive positive unit
rewards for completed operations, which are then removed from the queue. To encourage solving for
a shorter makespan, a negative reward of -0.1 is accrued at each timestep.

An action-value function $Q(s_t, a_t)$ maps the expected return of taking action a_t in state s_t. This next
section defines the architecture of a heterogeneous graph neural network that we subsequently trained
to learn Q.

4.3 Heterogeneous Graph Neural Networks

We employ a disjunctive graph $\mathcal{G} = \{\mathcal{O}, \mathcal{M}, \mathcal{E}_j, \mathcal{E}_q, \mathcal{C}\}$ to model the current state of a FJSP. Here,
$\mathcal{O}$ is the set of operations independent of the job to which they belong, $\mathcal{M}$ is the set of available
machines, $\mathcal{E}_j$ and $\mathcal{E}_q$ are sets of directed edges that denote the sequence of operations within each job
and within each queue respectively, and $\mathcal{C}$ represents the set of conjunctive, undirected edges that
assign operations to machines.

Edges in $\mathcal{C}$, represented by dashed edges in fig. 2a, specify operation-machine compatibility and
their assigned weights define a speed up or slow down of the default processing time. The feature
space of operations is composed of i) the time required to finish the operation, ii) its completion
percentage, iii) the number of downstream dependencies, iv) a one-hot encoding of the current state
of this operation, i.e. whether it is scheduled, processing, or completed, and v) the remaining time.
The machine features comprise the number of queued operations and their minimal expected run
time.

To encode this state representation into a meaningful action-value function Q, we use a heterogeneous
graph neural network composed of graph convolution layers [3], [24]. Our network architecture uses
two fully connected layers to embed both node types into the same dimensionality, followed by a set
of convolutional layers, each for processing a different edge-type (no weight sharing). The resulting
intermediate node embeddings are summed. By looping over this same heterogeneous layer k times,
each node embedding considers the state information of nodes within a k step radius. A dot-product
readout layer is then used for edge-prediction over $\mathcal{C}$. The edge with the highest score defines the
new operation-to-machine assignment, shown by solid blue arrows in fig. 2b.

(a) Initial state representation. (b) State at $t = 5$

Figure 2: Graphical representation of a sample FJSP instance at $t = 0$ (a) and after 5 actions have
been taken, $s_{t=5}$ (b).

5 Experimental Results

5.1 Implementation details

Random FJSP samples are created by initializing m machine and $n \cdot \tilde{n}_o$ operation nodes, and then
queuing them randomly into n jobs. Here, $\tilde{n}_o$ refers to the average number of operations per job. To
create, $\mathcal{C}$, we fully connect each machine to each operation, to indicate possible assignments, and then
randomly drop a fraction p. Their weights indicate the relative speedup or slowdown for endpoint
operations. Each operation is assigned a baseline runtime, which, when adjusted by the connected
edge weights results in the actual runtime of operation o_i on machine w_j.

For the following experiments, we set the number of HGNN iterations to $k = 2$ and dimensions
of machine and operation embeddings to 16. With each epoch, we sample 128 trajectories, which

are stored in a replay buffer of size 5000, and run 64 training iterations with a batch size of 32 state transitions. The discount factor is set to $\gamma = 1.0$ and the explorations constant to $\epsilon = 0.1$. The network is updated using the Adam optimizer, with a learning rate of $8e^{-5}$.

5.2 Baselines

To evaluate our method, we benchmark against simulated annealing, a probabilistic approximation method, and a state-of-the-art meta-heuristic introduced by Nouri *et al.* [25]. To the best of our knowledge, this work is the first to solve FJSP using a deep learning-based method. We also benchmark our scheduling performance against recent deep learning methods designed for the simpler scheduling problem [26], JSSP.

To compare performance across methods, we evaluate the optimality gap

$$\epsilon = \frac{C_{\min}}{C^*} - 1$$

where $C_{\min}$ is the makespan of a candidate solution and C^* the optimal makespan. This metric can also be referred to as relative error. Throughout these experiments, we use Google's OR-tools solver [27] to solve for C^*.

5.3 Results

Figure 3 shows the learning curves for our Q-learner trained on sample problems of size 25×15. Around epoch 150, we find sudden jumps on success rate and training reward. These jumps show when the learnt solver transitions from gridlocking itself to producing feasible solutions for the specified problem instances. The optimality gap can only be evaluated for feasible solutions, therefore the relative error curve starts around that same epoch and then decreases sharply as the solver learns to improve on its general strategy.

Figure 3: Training performance summary (25×15).

After the Q-learner has been trained, it can be given a problem of any size to solve. As such, this formulation could be interpreted as a type of meta-learning, enabled by using a graphical

representation of the problem space that is not limited to a fixed problem size. We ran the same solver on multiple size problems and evaluated 128 samples in each case. Table 1 summarizes our results. We find that the meta-heuristic is a strong baseline that solves optimally until the largest size problem 100×20, while FIFO is not preforming well from the beginning. The results reported for DQL are from the same network, but evaluated on different sample size. 100×20 is an exception: In this case the relative error was 29% but after 100 epochs of fine-tuning on larger problems, that error was mitigated to 6.2%.

For further reference, we also report optimality gaps for ScheduleNet [26], which is a similar deep RL approach but for the classic scheduling problem JSSP. Our network architecture only defines 960 independent weights, while ScheduleNet defines 6022 for the actor alone. Because ScheduleNet runs PPO, it further requires a trained critic. Therefore, we find that we maintain equal or better performance than an equivalent deep RL approach performs on a simpler problem, while using less than a sixth of its parameters.

Table 1: Optimality gaps for different FJSP sizes.

	15×15	15×25	30×20	50×15	50×20	100×20
FIFO	–	0.7647	0.69	0.857	–	1.235
Meta-Heuristic	–	0.0	0.0	0.0	0.0	0.022
DQL	0.01	0.011	0.0	0.052	0.04	0.062
ScheduleNet	0.153	0.194	0.187	0.138	0.135	0.066

In fig. 4, we compare the runtime performance for different sizes of FJSP. While the meta-heuristic is seemingly increasing in polynomial time, the runtime of DQL is nearly constant with problem size.

Figure 4: Runtimes per sample for different FJSP sizes.

6 Conclusion

In this work, we demonstrate how graph neural networks can be used to efficiently solve large, complex combinatorial optimization problems. By framing the CO instances as graph sequences, we can use reinforcement learning to find promising solutions. These solutions will be approximate, but while keeping the relative error low, we find our method scales a lot better in runtime than a more accurate meta-heuristic. We believe our results show promising initial results towards approaching the performance of state-of-the-art heuristic-based solvers.

References

[1] M. Gori, G. Monfardini, and F. Scarselli, "A new model for learning in graph domains," in *IEEE International Joint Conference on Neural Networks*, vol. 2, 2005, pp. 729–734.

[2] F. Scarselli, M. Gori, A. C. Tsoi, M. Hagenbuchner, and G. Monfardini, "The graph neural network model," *IEEE Transactions on Neural Networks*, vol. 20, no. 1, pp. 61–80, 2008.

[3] T. N. Kipf and M. Welling, "Semi-supervised classification with graph convolutional networks," in *International Conference on Learning Representations*, 2017.

[4]   R. Ying, R. He, K. Chen, P. Eksombatchai, W. L. Hamilton, and J. Leskovec, "Graph convolutional neural networks for web-scale recommender systems," in *ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2018, pp. 974–983.

[5]   C. Morris, M. Ritzert, M. Fey, *et al.*, "Weisfeiler and leman go neural: Higher-order graph neural networks," in *AAAI Conference on Artificial Intelligence (AAAI)*, 2019.

[6]   J. Zhao, Y. Dong, M. Ding, E. Kharlamov, and J. Tang, "Adaptive diffusion in graph neural networks," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[7]   M. Fereydounian, H. Hassani, J. Dadashkarimi, and A. Karbasi, "The exact class of graph functions generated by graph neural networks," *arXiv preprint arXiv:2202.08833*, 2022.

[8]   T. Koch, T. Achterberg, E. Andersen, *et al.*, "Miplib 2010," *Mathematical Programming Computation*, vol. 3, pp. 103–163, Jun. 2011.

[9]   K. Xu, C. Li, Y. Tian, T. Sonobe, K.-i. Kawarabayashi, and S. Jegelka, "Representation learning on graphs with jumping knowledge networks," in *International Conference on Machine Learning (ICML)*, PMLR, 2018, pp. 5453–5462.

[10] S. Brody, U. Alon, and E. Yahav, "How attentive are graph attention networks?" In *International Conference on Learning Representations*, 2022.

[11] U. Alon and E. Yahav, "On the bottleneck of graph neural networks and its practical implications," in *International Conference on Learning Representations*, 2021.

[12] S. Li, J. K. Gupta, P. Morales, R. Allen, and M. J. Kochenderfer, "Deep implicit coordination graphs for multi-agent reinforcement learning," in *AAMAS*, 2021.

[13] B. Xiao, B. Ramasubramanian, and R. Poovendran, "Agent-temporal attention for reward redistribution in episodic multi-agent reinforcement learning," *CoRR*, vol. abs/2201.04612, 2022. arXiv: 2201.04612.

[14] L. Liu, W. Wang, Y. Hu, J. Hao, X. Chen, and Y. Gao, "Multi-agent game abstraction via graph attention neural network," *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 34, pp. 7211–7218, Apr. 2020.

[15] X. Ma, D. Isele, J. K. Gupta, K. Fujimura, and M. J. Kochenderfer, "Recursive reasoning graph for multi-agent reinforcement learning," *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 36, no. 7, pp. 7664–7671, Jun. 2022.

[16] N. Mazyavkina, S. Sviridov, S. Ivanov, and E. Burnaev, "Reinforcement learning for combinatorial optimization: A survey," *Computers & Operations Research*, vol. 134, p. 105 400, 2021.

[17] J. Gilmer, S. S. Schoenholz, P. F. Riley, O. Vinyals, and G. E. Dahl, "Neural message passing for quantum chemistry," in *International Conference on Machine Learning (ICML)*, PMLR, 2017, pp. 1263–1272.

[18] P. Veličković, G. Cucurull, A. Casanova, A. Romero, P. Liò, and Y. Bengio, "Graph attention networks," in *International Conference on Learning Representations*, 2018.

[19] M. J. Kochenderfer, T. A. Wheeler, and K. H. Wray, *Algorithms for decision making*. MIT press, 2022.

[20] H. Van Hasselt, A. Guez, and D. Silver, "Deep reinforcement learning with double q-learning," in *Proceedings of the AAAI conference on artificial intelligence*, vol. 30, 2016.

[21] Z. Zhang, Z. Pan, and M. J. Kochenderfer, "Weighted double q-learning.," in *International Joint Conference on Artificial Intelligence (IJCAI)*, 2017, pp. 3455–3461.

[22] D. Applegate and W. Cook, "A computational study of the job-shop scheduling problem," *ORSA Journal on computing*, vol. 3, no. 2, pp. 149–156, 1991.

[23] I. A. Chaudhry and A. A. Khan, "A research survey: Review of flexible job shop scheduling techniques," *International Transactions in Operational Research*, vol. 23, no. 3, pp. 551–591, 2016.

[24] W. Hamilton, Z. Ying, and J. Leskovec, "Inductive representation learning on large graphs," in *Advances in Neural Information Processing Systems*, I. Guyon, U. V. Luxburg, S. Bengio, *et al.*, Eds., vol. 30, Curran Associates, Inc., 2017.

[25] H. E. Nouri, O. Belkahla Driss, and K. Ghedira, "Solving the flexible job shop problem by hybrid metaheuristics-based multiagent model," *International Journal of Industrial Engineering*, vol. 1, pp. 1–14, May 2017.

[26] J. Park, S. Bakhtiyarov, and J. Park, "Schedulenet: Learn to solve multi-agent scheduling problems with reinforcement learning," in *International Conference on Learning Representations*, 2022.

[27] Google AI, *Google or-tools*, version 9.3, Mar. 2022.