From Uniform to Learned Knots: A Study of Spline-Based Numerical Encodings for Tabular Deep Learning

Abstract

Numerical preprocessing remains a critical component of tabular deep learning, where the representation of continuous features can strongly affect downstream performance. Although this is well understood for classical statistical and machine learning models, the extent to which explicit numerical preprocessing systematically benefits tabular deep learning remains less well understood. In this work, we study this question with a particular focus on spline-based numerical encodings. We investigate three spline families for encoding numerical features, namely B-splines, M-splines, and integrated splines (I-splines), under uniform, quantile-based, target-aware, and learnable-knot (gradient-based) placement. For the learnable-knot variants, we adopt a differentiable knot parameterization that enables stable end-to-end optimization of knot locations jointly with the backbone. We evaluate these numerical encodings on a diverse collection of public regression and classification datasets using MLP, ResNet, and FT-Transformer backbones, and compare them against common numerical preprocessing baselines. Our results show that the effect of numerical encodings depends strongly on the task, the output size of the encoding, and the backbone. For classification, piecewise-linear encoding (PLE) is the most robust choice overall, while spline-based encodings remain competitive. For regression, no single encoding dominates uniformly. Instead, performance depends on the spline family, knot-placement strategy, and the output size of the encoding, with larger gains typically observed for MLP and ResNet than for FT-Transformer. We further find that learnable-knot variants can be optimized stably under the proposed parameterization, but may substantially increase training cost, especially for M-spline and I-spline expansions. Overall, the results show that numerical encodings should be assessed not only in terms of predictive performance, but also in terms of computational overhead. An anonymized implementation is publicly available at `https://anonymous.4open.science/r/tdl-numerical-encodings-881C/`.

1 Introduction

Most tabular datasets contain numerical columns whose effects are often non-uniform. A feature may matter only over specific value ranges, exhibit threshold behavior, or relate to the target through localized changes (Hastie et al., 2009; Breiman et al., 2017). However, a common deep learning pipeline represents each numerical feature as a single scaled scalar, for example, through normalization or min-max scaling, and relies on the backbone to learn nonlinear structure from these inputs (Gorishniy et al., 2021; Borisov et al., 2024). This induces a strong bias toward global smooth transformations and can be mismatched with tabular problems in which predictive structure is tied to specific value ranges. In such cases, localized or threshold-based effects must be recovered indirectly by the backbone from scalar inputs alone.

Prior work shows that the representation of numerical features can substantially affect tabular deep learning performance. In particular, explicit encodings such as piecewise-linear encoding (PLE), and periodic mappings can improve results across several backbones (Gorishniy et al., 2022). Surveys also note that numerical encodings remain less systematically explored than architectural modifications, despite their practical importance (Borisov et al., 2024; Somvanshi et al., 2024). These observations motivate alternative numerical encodings that provide localized flexibility while remaining compatible with standard tabular backbones.

In this work, we study spline-based feature expansions as numerical encodings for tabular deep learning. We consider B-splines (de Boor, 1972), M-splines (Ramsay, 1988), and integrated splines (I-splines) (Meyer, 2008), and evaluate multiple knot placement strategies, including uniform and quantile-based placement, target-aware knots derived from CART and LightGBM split points (Breiman et al., 1984; Ke et al., 2017), and learnable-knot placement. For the learnable-knot variants, we use a differentiable parameterization based on ordered spacings, implemented through a softmax followed by cumulative summation, which preserves knot ordering while remaining fully differentiable (Durkan et al., 2019; Suh et al., 2024). To isolate the effect of numerical encodings, we keep the downstream models unchanged and evaluate MLP, ResNet, and FT-Transformer backbones (Gorishniy et al., 2021).

We summarize our main contributions as follows:

1. We present a systematic benchmark of numerical encodings for tabular deep learning, comparing standard scaling, min-max scaling, PLE, and spline-based encodings across regression and classification tasks.
2. We study spline-based encodings within a unified framework, covering B-splines, M-splines, and I-splines under uniform, quantile-based, target-aware, and learnable-knot placement. For the learnable-knot variants, we use a differentiable parameterization that enables stable end-to-end optimization of knot locations.
3. We show empirically that the effect of numerical encodings depends on the task, output size, and backbone. PLE is the most consistent choice for classification, whereas for regression the strongest results depend on the spline family and knot-placement strategy, with the preferred output size varying across settings and spline-based encodings often among the best-performing methods. We also show that learnable-knot variants can introduce substantial training overhead, especially for M-spline and I-spline expansions.

2 Related Work

Tabular deep learning and tree ensembles. Tabular deep learning has been studied with a range of architectures, including decision-tree-inspired models such as TabNet and NODE, attention-based models such as TabTransformer and SAINT, sequential state-space models such as Mambular, and strong MLP-based baselines such as ResNet-style MLPs and RealMLP (Arik & Pfister, 2019; Popov et al., 2019; Huang et al., 2020; Somepalli et al., 2021; Gorishniy et al., 2021; Thielmann et al., 2024; Holzmüller et al., 2025). At the same time, large empirical studies show that relatively simple backbones such as MLP, ResNet, and FT-Transformer remain strong and reproducible baselines on standard benchmarks (Gorishniy et al., 2021; 2022; Holzmüller et al., 2025). In parallel, gradient-boosted decision trees remain widely used and often serve as the reference level of performance on tabular benchmarks, with common implementations including XGBoost, LightGBM, and CatBoost (Chen & Guestrin, 2016; Ke et al., 2017; Prokhorenkova et al., 2018; Shwartz-Ziv & Armon, 2021).

Numerical preprocessing and numerical encodings. Several surveys note that much of the tabular deep learning literature focuses on backbone design, while numerical preprocessing is often limited to standard scaling or simple transformations (Borisov et al., 2024; Somvanshi et al., 2024). A key exception is the work of Gorishniy et al. (2022), which studies explicit numerical encodings for continuous features, including piecewise-linear encoding (PLE) and periodic mappings, and shows improvements across MLP, ResNet, and FT-Transformer backbones. A related line of work views numerical encoding through the lens of function evaluations. For example, Shtoff et al. (2025) propose Function Basis Encoding (FBE) for factorization machines, where each numerical feature is mapped to a vector of function values, including spline bases. These works support the view that the representation of numerical features can materially affect tabular prediction performance.

Splines as bases and as neural components. Splines are classical tools for representing nonlinear effects. B-splines provide a standard stable basis, P-splines combine B-spline bases with smoothness penalties, and thin-plate regression splines provide low-rank constructions that are widely used in practice (de Boor, 1972; Eilers & Marx, 1996; Wood, 2003; 2017). M-splines and their integrals, integrated splines (I-splines), are

commonly used for nonnegative and monotone constructions (Ramsay, 1988; Meyer, 2008). In deep learning, splines have often appeared as trainable model components rather than as general-purpose preprocessing. Examples include spline-parameterized activations (Bohra et al., 2020), learnable spline-based input normalization for tabular representation learning (Suh et al., 2024), and spline-parameterized function modules in KAN-style architectures (Liu et al., 2025; Eslamian et al., 2025).

Learnable-knot spline models and free-knot splines. A natural extension of classical spline modeling is to treat knot locations as learnable parameters rather than fixing them in advance. In traditional spline regression, free-knot formulations can increase flexibility but lead to a difficult nonconvex optimization problem because of ordering constraints and possible knot degeneracies (Mohanty & Fahnestock, 2021; Thielmann et al., 2025). In deep learning, differentiable parameterizations have recently made gradient-based knot optimization practical at scale. A common strategy is to parameterize positive knot spacings with a softmax and recover ordered knots by cumulative summation, yielding a differentiable map from unconstrained parameters to strictly increasing knot vectors (Durkan et al., 2019). Variants of this idea appear in neural spline flows (Durkan et al., 2019), in learnable spline-based normalization for tabular data (Suh et al., 2024), and in spline-parameterized components within KAN-style models (Liu et al., 2025; Eslamian et al., 2025; Zheng et al., 2025). Closest to our setting, Suh et al. (2024) learn per-feature spline transforms end-to-end, but their focus is on input normalization rather than explicit basis expansions consumed by otherwise unchanged tabular backbones.

Tabular foundation models and PFN-based approaches. Another line of work studies tabular foundation models based on in-context learning. TabPFN introduced the PFN paradigm for tabular classification, where a transformer is pretrained on synthetic tabular tasks and applied without task-specific gradient-based training (Hollmann et al., 2022). Subsequent work extended this line to broader settings, including larger datasets, regression, categorical features, and missing values (Hollmann et al., 2025; Grinsztajn et al., 2025). Recent models such as TabICL, Mitra, and Orion-MSP further improve scalability or synthetic-pretraining design for tabular in-context learning (Qu et al., 2025; Zhang et al., 2025; Bouadi et al., 2025). These models follow a different evaluation paradigm from the one studied here. They are typically designed to consume tabular inputs directly, together with model-specific internal representations or tokenization schemes, rather than relying on external numerical encodings as the main object of comparison in standard benchmarking pipelines (Hollmann et al., 2022; Grinsztajn et al., 2025; Qu et al., 2025).

Overall, prior work shows that numerical encodings can affect tabular deep learning performance (Gorishniy et al., 2022; Shtoff et al., 2025), and that spline parameterizations can be trained end-to-end as neural components (Durkan et al., 2019; Bohra et al., 2020; Suh et al., 2024; Liu et al., 2025; Eslamian et al., 2025). However, most existing spline-based approaches place splines inside the model architecture, for example as activations, normalization layers, or KAN-style modules, rather than using them as explicit numerical preprocessing for standard tabular backbones. It therefore remains unclear how learnable-knot spline encodings behave when used as preprocessing and compared directly against standard scaling, min-max scaling, and PLE. We address this by evaluating B-spline, M-spline, and I-spline encodings under uniform, quantile-based, target-aware placement based on CART and LightGBM split points (Breiman et al., 1984; Ke et al., 2017), and learnable-knot placement within a unified benchmark on MLP, ResNet, and FT-Transformer backbones.

3 Methodology

In this section, we describe our numerical encoding framework based on spline bases and outline the knot-placement variants used throughout the study.

Notation and spline basis expansion. We consider supervised learning on tabular data with numerical and categorical features. Let $x = (x_{\text{num}}, x_{\text{cat}})$ denote an input, where $x_{\text{num}} \in \mathbb{R}^d$ contains d numerical features and x_{cat} denotes the categorical variables, and let y denote the target. For x_{num}, we write x_j for the jth numerical feature, $j \in \{1, \dots, d\}$.

Our goal is to construct an explicit spline-based expansion for each numerical feature x_j. For feature j, we define

$$\phi_j(x_j; \tau_j) = \big(b_{j,1}(x_j; \tau_j), \ldots, b_{j,m_j}(x_j; \tau_j)\big),$$

where $\{b_{j,\ell}\}_{\ell=1}^{m_j}$ are basis functions from a spline family and τ_j denotes the corresponding knot sequence. Throughout, we use cubic splines with degree $p = 3$. As a representative example, B-spline basis functions are defined by the Cox de Boor recursion over a non-decreasing knot sequence τ_j:

$$B_{j,\ell}^{(0)}(x_j) = \begin{cases} 1, & \tau_{j,\ell} \le x_j < \tau_{j,\ell+1}, \\ 0, & \text{otherwise}, \end{cases}$$

and, for $p \ge 1$,

$$B_{j,\ell}^{(p)}(x_j) = \frac{x_j - \tau_{j,\ell}}{\tau_{j,\ell+p} - \tau_{j,\ell}} B_{j,\ell}^{(p-1)}(x_j) + \frac{\tau_{j,\ell+p+1} - x_j}{\tau_{j,\ell+p+1} - \tau_{j,\ell+1}} B_{j,\ell+1}^{(p-1)}(x_j),$$

with each fraction defined as zero when its denominator is zero. For B-, M-, and I-splines, the number of basis functions is determined by the number of internal knots K_j through

$$m_j = K_j + p + 1.$$

Thus, $\phi_j(x_j; \tau_j) \in \mathbb{R}^{m_j}$, and the expanded numerical representation is the concatenation

$$\Phi(x_{\text{num}}) = [\phi_1(x_1; \tau_1) | \cdots | \phi_d(x_d; \tau_d)].$$

In addition to B-splines (de Boor, 1972), we include M-splines and I-splines because they provide nonnegative and monotone basis families, respectively, while retaining the same knot-based construction (Ramsay, 1988; Meyer, 2008). M-splines are obtained as normalized B-splines, and I-splines are defined as integrated M-splines. The downstream model takes $\Phi(x_{\text{num}})$ together with the categorical features, which are processed separately as described in Section 4. The backbone architecture is kept fixed to isolate the effect of numerical encodings.

Spline encodings in the pipeline. For fixed-knot variants, the spline encoding is computed from knot sequences constructed during preprocessing using the training split of each fold. In these cases, we do not fit spline coefficients, that is, we do not define or learn a spline function of the form

$$f_j(x_j) = \sum_{\ell=1}^{m_j} \alpha_{j,\ell} b_{j,\ell}(x_j; \tau_j).$$

Instead, the downstream network learns its own weights on the encoded features $\phi_j(x_j; \tau_j)$. For learnable-knot variants, we use the same basis expansion but update the knot locations jointly with the downstream model during training rather than fixing them during preprocessing. We next describe knot-placement strategies in detail. The corresponding basis definitions for each spline family, together with the indexing conventions used throughout, are given in Appendix C.

3.1 Knot Placement Strategies

A central methodological component of our work is the treatment of knot placement. For each numerical feature x_j, we construct a set of K_j internal knots

$$\kappa_j = (\kappa_{j,1}, \ldots, \kappa_{j,K_j}), \qquad \kappa_{j,1} < \cdots < \kappa_{j,K_j}. \tag{1}$$

These internal knots are then augmented with the usual boundary knots to form the full spline knot sequence τ_j used by the basis definitions in Section 3. Except for the learnable-knot variant, the internal knots are determined during preprocessing using only the training split of each fold and remain fixed during downstream training. In the learnable-knot variant, the internal knots are treated as learnable parameters, and the full knot sequence is constructed from them during training.

We consider four knot-placement strategies, namely uniform placement, quantile-based placement, target-aware placement, and learnable-knot placement. For target-aware placement, we consider two variants based on CART and LightGBM split points. The individual strategies are described below.

3.1.1 Uniform knot placement

Uniform internal knots are equally spaced over the observed range of x_j:

$$\kappa_{j,\ell} = \min(x_j) + \frac{\ell}{K_j + 1}\big(\max(x_j) - \min(x_j)\big), \qquad \ell = 1, \ldots, K_j. \tag{2}$$

3.1.2 Quantile knot placement

Quantile internal knots place more knots in regions where samples are concentrated:

$$\kappa_{j,\ell} = Q_j\left(\frac{\ell}{K_j + 1}\right), \qquad \ell = 1, \ldots, K_j, \tag{3}$$

where $Q_j(\cdot)$ is the empirical quantile function of x_j computed on the training split. This strategy is target-agnostic and adapts only to the marginal distribution of x_j.

3.1.3 Target-aware knot placement

For each numerical feature x_j after min-max scaling to $[0, 1]$, we construct a *univariate* target-aware set of internal knots by fitting a predictive tree on the training fold only. We consider two variants, CART-based and LightGBM-based. Let

$$\{(x_{i,j}, y_i)\}_{i=1}^n \tag{4}$$

denote the training pairs for feature j.

CART-based knots. We fit a depth- and sample-constrained univariate CART tree T_j, using a regressor for regression and a classifier for classification (Breiman et al., 1984). Let $\mathcal{S}_j$ be the multiset of split thresholds used by the internal nodes of T_j on x_j. We first map thresholds to the observed range:

$$\widetilde{\mathcal{S}}_j = \big\{\mathrm{clip}(s; \min_i x_{i,j}, \max_i x_{i,j}) : s \in \mathcal{S}_j\big\}, \tag{5}$$

and then deduplicate and sort them to obtain candidates $\{s_{j,(1)} < \cdots < s_{j,(r)}\}$.

For numerical stability, we enforce a minimum spacing constraint by pruning near-duplicates. We keep a subsequence $\mathcal{C}_j \subseteq \{s_{j,(1)}, \ldots, s_{j,(r)}\}$ such that

$$|s - s'| \geq \epsilon \quad \text{for all distinct } s, s' \in \mathcal{C}_j, \tag{6}$$

where ϵ is set as a small fraction of the normalized range (DiMatteo et al., 2001; Spiriti et al., 2013).

To match a desired spline complexity, we convert the target number of basis functions m_j and the spline degree p into a target number of internal knots:

$$K_j = m_j - p - 1. \tag{7}$$

If $|\mathcal{C}_j| > K_j$, we retain the K_j most informative thresholds, ranked by the impurity reduction of their corresponding split. For a split at threshold s occurring at node v with children L and R, we use

$$\Delta I_v(s) = I(v) - \frac{n_L}{n_v}I(L) - \frac{n_R}{n_v}I(R), \tag{8}$$

where $I(\cdot)$ denotes the node impurity and n_v, n_L, n_R are sample counts. If $|\mathcal{C}_j| < K_j$, we supplement the remaining knots with quantiles of $\{x_{i,j}\}$ computed on the training fold until reaching K_j. The resulting internal-knot vector κ_j is then obtained by sorting the selected thresholds, and the full knot sequence τ_j is constructed from κ_j using the standard boundary handling for the chosen spline family.

LightGBM-based knots. We follow the same construction, but replace T_j with a univariate gradient-boosted tree ensemble (Friedman, 2001; Ke et al., 2017). Let $\mathcal{S}_j^{(t)}$ be the set of thresholds used by tree t, and let $g_t(s) \geq 0$ denote the split gain assigned by LightGBM to threshold s. We aggregate threshold importance across the ensemble via

$$w_j(s) = \sum_t g_t(s), \tag{9}$$

rank candidate thresholds by $w_j(s)$, and then apply the same spacing filter in equation 6 and the same target internal-knot budget in equation 7. If no valid splits are produced, for example because of sparsity or strong regularization, we fall back to quantile-based internal knots to ensure a usable basis. We include this variant because aggregating split thresholds across an ensemble can provide a more stable set of high-gain knot candidates than a single CART tree. The resulting internal-knot vector κ_j is then obtained by sorting the selected thresholds, and the full knot sequence τ_j is constructed from κ_j using the standard boundary handling for the chosen spline family.

Relation to target-aware binning in PLE. Our procedure is target-aware in the sense that knot candidates are derived from supervised split thresholds. It differs from the target-aware preprocessing used for PLE in Gorishniy et al. (2022) in two respects. First, PLE uses supervised split thresholds for binning and encoding, whereas we use them to define internal spline knots for a continuous basis expansion. Second, our construction enforces spline-specific constraints, including the conversion from basis size to an internal-knot budget in equation 7, the minimum-spacing condition in equation 6, and the supplementation or pruning of candidate thresholds when too few or too many are available. These steps are specific to spline basis construction and are not required for PLE.

3.1.4 Learnable knot placement

In the learnable-knot variant, also referred to as the *gradient-based* knot, we treat the internal knots κ_j as learnable parameters and optimize them jointly with the downstream backbone by backpropagation. As in the target-aware setting, all numerical features are first min-max scaled to $[0, 1]$ using the training split of each fold. This places all spline constructions on a common domain and ensures that the learned internal knots satisfy $\kappa_{j,\ell} \in (0, 1)$.

Initialization. For each numerical feature $j \in \{1, \ldots, d\}$, we fix the number of internal knots K_j and initialize the internal-knot vector

$$\kappa_j = (\kappa_{j,1}, \ldots, \kappa_{j,K_j})$$

from the same rule as the corresponding fixed-knot baseline, namely uniform placement. This provides a valid and well-spaced starting configuration.

Ordered knots via spacing parameterization. Direct optimization of κ_j is numerically fragile because the parameters must satisfy the strict ordering constraint

$$0 < \kappa_{j,1} < \cdots < \kappa_{j,K_j} < 1,$$

and neighboring knots may collide during training. We therefore optimize an unconstrained vector $a_j \in \mathbb{R}^{K_j+1}$ and map it to a strictly increasing internal-knot vector through positive interval widths. We first define normalized allocation weights

$$\pi_{j,r} = \frac{\exp(a_{j,r})}{\sum_{s=1}^{K_j+1} \exp(a_{j,s})}, \qquad r = 1, \ldots, K_j + 1, \tag{10}$$

and convert them into positive widths with minimum spacing $\delta > 0$,

$$w_{j,r} = \delta + \big(1 - (K_j + 1)\delta\big)\pi_{j,r}, \qquad r = 1, \ldots, K_j + 1. \tag{11}$$

By construction, $w_{j,r} \geq \delta$ and $\sum_{r=1}^{K_j+1} w_{j,r} = 1$. The internal knots are then obtained by cumulative summation,

$$\kappa_{j,\ell} = \sum_{r=1}^{\ell} w_{j,r}, \qquad \ell = 1, \ldots, K_j, \tag{12}$$

which guarantees

$$0 < \kappa_{j,1} < \cdots < \kappa_{j,K_j} < 1.$$

The resulting internal knots are combined with the standard boundary construction to form the full spline knot sequence τ_j used by the basis functions. This softmax-cumsum parameterization follows standard constructions for ordered spline breakpoints in differentiable spline models (Durkan et al., 2019; Suh et al., 2024).

Spline feature expansion and gradient flow. Given κ_j, we construct the full knot sequence τ_j and compute the spline encoding $\phi_j(x_j; \tau_j)$ in each forward pass. The expanded numerical representation is then formed as $\Phi(x_{\text{num}}; \tau(a))$ by concatenation across features. Since ϕ_j depends on τ_j, and τ_j is a differentiable function of a_j through equation 10–equation 12, gradients from the task loss propagate to a_j.

Learning objective. Let $a = (a_1, \ldots, a_d)$ collect the knot parameters, let $\kappa(a) = \{\kappa_j(a_j)\}_{j=1}^d$ denote the induced internal-knot vectors, and let $\tau(a)$ denote the corresponding full knot sequences. Let f_θ be the downstream backbone applied to the expanded numerical representation together with the categorical features. We minimize

$$\min_{\theta, a} \frac{1}{n} \sum_{i=1}^n \mathcal{L}\Big(f_\theta\Big(\Phi(x_{\text{num}}^{(i)}; \tau(a)), x_{\text{cat}}^{(i)}\Big), y^{(i)}\Big) + \lambda \, \mathcal{R}_{\text{space}}(a), \tag{13}$$

where $\mathcal{L}$ is cross-entropy for classification and squared loss for regression.

Collision avoidance regularization. Near-collisions can yield ill-conditioned basis evaluations. To discourage small interval widths, we penalize the induced spacings using a reciprocal barrier,

$$\mathcal{R}_{\text{space}}(a) = \frac{1}{d} \sum_{j=1}^d \frac{1}{K_j+1} \sum_{r=1}^{K_j+1} \frac{1}{w_{j,r}(a_j) + \varepsilon}, \tag{14}$$

where $\varepsilon > 0$ and $w_{j,r}(a_j)$ denotes the widths produced by equation 10 and equation 11. Such spacing penalties are common in free-knot spline optimization (DiMatteo et al., 2001; Spiriti et al., 2013; Thielmann et al., 2025) and are also consistent with stability heuristics used in differentiable spline models (Durkan et al., 2019; Suh et al., 2024). This design is also in line with recent work that incorporates structured smooth components into end-to-end trainable additive neural models (Luber et al., 2023). Detailed steps of learnable-knot optimization and the end-to-end preprocessing workflow are provided in Appendix G, Algorithms 2 and 1, respectively.

Stability considerations. In our implementation of gradient-based knot optimization, the number of internal knots K_j is fixed in advance, and only their locations κ_j are updated during training through the unconstrained parameters a_j, jointly with the backbone parameters θ as described in Algorithm 2. Stability is supported by the spacing parameterization in our formulation. The softmax variables $\pi_{j,r}$ are mapped to interval widths through equation 11, and the ordered internal knots are then recovered by cumulative summation as in equation 12. This guarantees valid ordered knot configurations with minimum spacing controlled by δ and removes the need for sorting or post-hoc merging (Durkan et al., 2019; Suh et al., 2024). In contrast to merge-based free-knot approaches, which use a predefined merge threshold α for nearby knots, our formulation enforces valid knot configurations directly through the spacing parameterization and the minimum-spacing constant δ. This avoids the need for an additional merge-threshold hyperparameter (Thielmann et al., 2025).

In practice, optimization was further supported by initialization from a well-spaced fixed-knot rule and, when used, by a warm-start phase in which a is frozen for the first E_{warm} epochs before joint updates of (θ, a) are enabled. Empirically, we observed stable knot updates for learning rates η_a comparable to, and in some cases up to twice, the backbone learning rate η_θ. By contrast, too small values of η_a often led to negligible knot movement. A qualitative illustration of knot relocation during training is provided in Appendix J.1.

4 Experimental Setup

4.1 Datasets and numerical encodings

Datasets and basic preprocessing. We evaluate our methods on 25 tabular datasets covering regression and classification tasks, collected from the UCI Machine Learning Repository and OpenML. Dataset statistics and abbreviations are reported in Table 3. We use 5-fold cross-validation for all experiments. In total, this yields $25 \times 5 \times 3 \times 14 = 5250$ training runs across 25 datasets, 5 folds, 3 backbones, and 14 numerical encoding methods. We apply a minimal preprocessing pipeline. Rows with missing values are removed and no explicit outlier treatment is performed. Numerical features are scaled to $[0, 1]$ before applying feature-expansion methods, which ensures comparable basis construction across heterogeneous feature scales. Categorical features are label-encoded as integer identifiers, without one-hot or target encoding. Unseen categories at evaluation time are assigned the identifier -1. For MLP and ResNet, these identifiers are used directly as scalar inputs. For FT-Transformer, numerical and categorical features are processed by separate tokenizers, using a linear tokenizer for numerical features and an embedding tokenizer for categorical features (Gorishniy et al., 2021).

Numerical encoding methods. We study spline-based numerical encodings and PLE under a capacity-controlled protocol; see Table 2. In the main benchmark, we evaluate Std, MinMax, PLE, B-splines (BS), I-splines (IS), and the learnable-knot M-spline variant. Fixed-knot M-spline variants are excluded from the main benchmark and are reported only in the ablation study. For BS and IS, we consider uniform, quantile-based, learnable-knot, and target-aware knot placement. For target-aware placement, we use two variants based on CART and LightGBM, as described in Section 3. The configuration details for the target-aware variants are provided in Table 6.

Output size and matched PLE baseline. To isolate the effect of knot or bin placement from representation size, we fix the per-feature output size to $m \in \{7, 15, 30\}$ for all features, for both spline encodings and PLE. For cubic splines ($p = 3$), $m = 7$ corresponds to three internal knots through $m = K + p + 1$, making it the smallest non-trivial spline resolution. We then increase the output size to $m = 15$ and $m = 30$ to examine how higher resolution affects predictive performance. Together, these settings cover low, medium, and relatively high output sizes while keeping the full benchmark computationally manageable. For PLE, the matched output size is implemented through the number of bins. An adaptive PLE variant is used only in the ablation study, where a tree-guided procedure selects the effective number of bins from $[5, 50]$

4.2 Models and evaluation protocol

Backbones. We evaluated three tabular backbones, MLP, ResNet, and FT-Transformer, to test whether the effect of numerical encodings is consistent across different model classes. MLP serves as a simple baseline with limited inductive bias, so improvements can be attributed more directly to the input representation. ResNet follows the tabular ResNet design of Gorishniy et al. (2021) and adds residual connections and normalization, providing a stronger MLP-based backbone. FT-Transformer uses feature tokenization and self-attention to model feature interactions (Gorishniy et al., 2021). Complete architectural hyperparameters are provided in Table 5.

Training and evaluation. Because the main focus of this study is the effect of numerical encodings, we adopt a shared training protocol across backbones. This provides a controlled comparison in which differences can be attributed more directly to the preprocessing method rather than to backbone-specific tuning. All backbones are trained with AdamW using learning rate 10^{-4}, weight decay 10^{-5}, batch size 512, and at most 200 epochs. We use early stopping on the validation metric with patience 15, together with a ReduceLROnPlateau scheduler with patience 10 and factor 0.1. We use 5-fold cross-validation for all experiments, with stratification for classification tasks, and hold out 10% of each training fold as a validation split for early stopping. To prevent information leakage, all preprocessing, including feature scaling, numerical encoding, and target standardization for regression, is fit using only the training portion of each fold and then applied to the corresponding validation and test partitions. For regression, targets are z-score normalized using training-fold statistics. For reproducibility, we use fold-specific seeds given by `seed + fold_id` and seed all random number generators consistently. We evaluate all methods using 5-fold

cross-validation. For regression, we report NRMSE ($\downarrow$), while for classification we report AUC ($\uparrow$). On multiclass datasets, AUC is computed as weighted one-vs-rest AUC. Reported results are summarized as mean $\pm$ standard deviation across folds.

To preserve the intrinsic geometry of B-spline and I-spline encodings, such as partition-of-unity and cumulative structure, we do not apply feature-wise normalization to these encodings; see Appendices C.2 and C.4. For learnable-knot M-splines, the normalization term in the M-spline basis, $(\tau_{j,\ell+p+1} - \tau_{j,\ell})^{-1}$, depends on the knot locations and changes during training; see Appendix C.3. When adjacent knot spans shrink, this term can become large and lead to large feature magnitudes in practice. We therefore apply LayerNorm to each learnable-knot M-spline feature block as a numerical stabilization step (Ba et al., 2016).

4.3 Results and Analysis

We compare preprocessing methods from two complementary perspectives. First, we summarize performance using critical difference (CD) diagrams based on average ranks, following the Friedman/Nemenyi protocol commonly used in multi-dataset benchmarking (Demšar, 2006; Feuer et al., 2024; Kadra et al., 2024; Thielmann et al., 2024). The regression and classification CD diagrams are shown in Figures 1 and 2, respectively. Second, we report backbone-specific heatmaps of the average test metric across datasets for each output size $m \in \{7, 15, 30\}$ in Figures 3 and 4. Each heatmap cell is the average NRMSE or AUC over all datasets of the corresponding task for a fixed backbone, preprocessing method, and output size. The CD diagrams provide an aggregate rank-based comparison, whereas the heatmaps are intended to show overall performance patterns across backbones, preprocessing methods, and output sizes. For Std and MinMax, feature expansion is not applicable, and their values therefore remain the same across output sizes in the heatmaps. These methods are included as baseline reference points for comparison. Implementation details and the associated significance tests are provided in Appendix H. Detailed per-dataset results are reported in Tables 7, 8, and 9 for regression, and in Tables 10, 11, and 12 for classification.

Across all six CD settings, corresponding to regression and classification for $m \in \{7, 15, 30\}$, the Friedman test rejects the null hypothesis of equal performance. This suggests that the choice of preprocessing method has a statistically significant overall effect. At the same time, the Nemenyi cliques indicate that several top-ranked methods are often not significantly different from one another. The CD diagrams should therefore be read as identifying clusters of strong methods rather than a single universally dominant winner.

Regression. The regression results are clearly output-size dependent. At $m = 7$, the CD diagram in Figure 1 is led by B-spline variants with fixed or target-aware knot placement, with BS-LGBM, BS-Q, and BS-CART occupying the top ranks. At $m = 15$ and $m = 30$, the ranking shifts toward I-spline and learnable-knot variants. In particular, IS-Q and IS-LGBM remain among the strongest methods at both larger output sizes, and IS-Grad-U becomes competitive at $m = 30$. PLE is not among the strongest methods at low output size, but becomes more competitive at $m = 30$. By contrast, Std and MinMax remain near the bottom across all regression settings.

The regression heatmaps in Figure 3 highlight the dependence on the backbone. For MLP and ResNet, increasing the output size often improves the average NRMSE of spline-based methods, especially for target-aware and learnable-knot variants. On MLP, for example, BS-Grad-U improves from 0.2491 at $m = 7$ to 0.2322 at $m = 15$ and 0.2278 at $m = 30$, while IS-Grad-U attains the lowest average NRMSE at $m = 30$ with 0.2273. On ResNet, the strongest methods likewise shift toward larger output sizes, with IS-LGBM achieving the lowest average NRMSE at $m = 30$ with 0.2246. However, FT-Transformer behaves differently. Several B-spline variants worsen as m increases, for example BS-Q changes from 0.2451 to 0.2666 to 0.3034 across $m = 7, 15, 30$. Std, with NRMSE 0.2465 remains competitive and in fact outperforms PLE at all three output sizes. At $m = 15$ and $m = 30$, it also outperforms many spline-based encodings, including all B-spline variants, IS-Grad-U, and MS-Grad-U. Overall, larger output sizes are often useful for regression with MLP and ResNet, but can become counterproductive for FT-Transformer.

Classification. The classification results are more stable than the regression results. In all three CD diagrams in Figure 2, PLE is the top-ranked method, and its average rank improves from 5.0 at $m = 7$ to 4.0 at $m = 15$ and 3.3 at $m = 30$. At $m = 7$, B-spline variants with target-aware or learnable-knot placement

remain competitive. As the output size increases, I-spline variants form the closest competing group to PLE. As in regression, Std and MinMax remain near the bottom across all settings.

The classification heatmaps in Figure 4 show a more stable pattern than in regression. Across all three backbones, PLE achieves the highest average AUC at every output size, with small but consistent gains as m increases. For example, its average AUC rises from 0.9194 to 0.9234 on MLP, from 0.9298 to 0.9312 on ResNet, and from 0.9319 to 0.9331 on FT-Transformer when moving from $m = 7$ to $m = 30$. More generally, many encoding methods improve with larger m, but the gain from $m = 15$ to $m = 30$ is usually smaller than the gain from $m = 7$ to $m = 15$. This pattern is visible for both B-spline and I-spline variants. For MLP and ResNet, several spline-based methods improve clearly over MinMax and often over Std, but they still do not consistently match PLE. In particular, several B-spline variants attain their strongest average AUC around $m = 15$, after which gains level off or slightly reverse at $m = 30$. FT-Transformer shows a different pattern. Std, with AUC 0.9256, remains competitive with most spline-based encodings. Among the spline variants, only BS-Q, BS-CART, and BS-LGBM at $m = 15$ surpass Std, while the remaining spline settings stay below it.

Backbone sensitivity and practical interpretation. The results show that the effect of numerical preprocessing depends on both the task and the backbone. In regression, the strongest methods vary with the output size, with B-spline variants tending to perform best at smaller sizes and I-spline or learnable-knot variants becoming more competitive as the output size increases. In classification, PLE is the most robust choice across backbones and output sizes, while spline-based encodings remain competitive but do not consistently surpass it. The heatmaps also indicate that expressive preprocessing is more beneficial for MLP and ResNet than for FT-Transformer, which often shows smaller or less consistent gains, especially in regression. These findings suggest that preprocessing should be selected jointly with the task and backbone rather than treated as an independent design choice.

Main takeaways:

- The CD diagrams show statistically significant differences among preprocessing methods across all output sizes for both regression and classification.
- In regression, the aggregate ranking changes with output size. At $m = 7$, the strongest ranks are typically obtained by B-spline variants such as BS-LGBM, BS-Q, and BS-CART, whereas at $m = 15$ and $m = 30$ the ranking shifts toward I-spline and learnable-knot methods, especially IS-Q, IS-LGBM, and IS-Grad-U.
- In classification, PLE is the strongest overall baseline. It is top-ranked in the CD diagrams for all three output sizes and yields the highest average AUC across MLP, ResNet, and FT-Transformer.
- Larger and more expressive preprocessing tends to benefit MLP and ResNet more than FT-Transformer. For FT-Transformer, the gains are generally smaller and less consistent.
- Std and MinMax are generally weaker than explicit numerical encodings, especially for MLP and ResNet. For stronger backbones such as FT-Transformer, however, Std often remains competitive and can be a reasonable choice when simplicity and computational budget are important.

Figure 1: Regression critical difference diagrams. CD diagrams aggregated over all backbones for output sizes $m \in \{7, 15, 30\}$. Lower average rank indicates better overall performance. Methods connected by a horizontal bar are not significantly different under the Nemenyi test. Preprocessing abbreviations are given in Appendix 2, and detailed regression results for the corresponding output sizes are provided in Tables 7, 8, and 9.

Figure 2: Critical difference diagrams for classification. The diagrams are aggregated over all backbones for output sizes $m \in \{7, 15, 30\}$. Lower average rank indicates better overall performance. Methods connected by a horizontal bar are not significantly different under the Nemenyi test. Preprocessing abbreviations are given in Appendix 2, and detailed classification results for the corresponding output sizes are reported in Tables 10, 11, and 12.

Figure 3: Average regression performance across backbones and output sizes. Each heatmap cell shows the mean test NRMSE ($\downarrow$) across all regression datasets for a given backbone, preprocessing method, and output size $m \in \{7, 15, 30\}$. Preprocessing abbreviations are given in Appendix 2, and detailed results are provided in Tables 7, 8, and 9.

Figure 4: Average classification performance across backbones and output sizes. Each heatmap cell shows the mean test AUC ($\uparrow$) across all classification datasets for a given backbone, preprocessing method, and output size $m \in \{7, 15, 30\}$. For multiclass datasets, AUC is computed as weighted one-vs-rest ROC-AUC. Higher values indicate better performance. Preprocessing abbreviations are given in Appendix 2, and detailed results are provided in Tables 10, 11, and 12.

4.4 Illustration of PLE and B-Spline Fits on Simple Synthetic Problems

To better understand the task-dependent behavior seen in the benchmark results, we compare PLE and cubic B-spline encodings on two simple one-dimensional synthetic problems. The goal is not to introduce another benchmark, but to provide a small controlled illustration of how the two encodings behave when the representation size is held fixed.

We consider one regression problem with a smooth nonlinear target and one classification problem with a class-probability function that contains flat regions and relatively sharp transitions. In both cases, we use the same number of output encoding size ($m = 10$), with uniform PLE bins and a clamped uniform cubic B-spline basis. Since this experiment is intended to illustrate the behavior of the encodings themselves rather than to reproduce the full benchmark setting, we use simple downstream models, namely Ridge regression for the regression task and logistic regression for the classification task. This keeps the comparison centered on the encoding and avoids additional effects from backbone expressiveness. Details of the synthetic data generation and preprocessing are provided in Appendix I.3.

Figure 5 shows the resulting fits. In the regression example (Fig. 5a), the B-spline basis gives a smoother fit and stays closer to the target curve, while the PLE fit shows more visible piecewise-linear changes at the bin boundaries. In the classification example (Fig. 5b), PLE follows the flat high-probability region and the sharper boundary changes more closely, whereas the B-spline fit changes more gradually across these regions. This difference is consistent with the structure induced by the two encodings. With logistic regression, PLE produces a piecewise-linear score function, and its cumulative bin construction can make it a natural match for threshold-like probability structure. By contrast, a cubic B-spline basis encourages a smoother local polynomial fit, which is often better aligned with smoothly varying regression targets.

Although these examples are intentionally simple, they are consistent with the broader pattern in the benchmark results. PLE is the most robust choice for classification, while spline-based variants are often more competitive on regression. This suggests that part of the difference may come from the kind of fitted function encouraged by the encoding itself. These plots are intended only as an illustration and should be read as a qualitative complement to the main benchmark rather than as a separate evaluation.

4.5 Efficiency Case Study: Learnable-Knot Overheads on SGEMM

We conduct an efficiency case study on SGEMM GPU, one of the 25 benchmark datasets, to examine the computational cost of learnable-knot spline encodings. SGEMM is a regression dataset with $d = 14$ numerical features. Dataset details are provided in Appendix 3. The analysis has three parts. We first summarize the asymptotic per-batch complexity of the preprocessing methods. We then quantify the additional parameter count introduced by learnable knots. Finally, using timestamps logged during training, we measure total GPU wall-clock time over 5-fold cross-validation.

As reference methods, we include Std, MinMax, and PLE together with selected spline-based encodings. The main comparison is between the learnable-knot variants BS-Grad-U and IS-Grad-U and their fixed-knot counterparts BS-U and IS-U. We also include MS-Grad-U to compare computational cost across learnable-knot spline families. This setup lets us separate asymptotic cost, parameter overhead, and observed runtime, and study how learnable-knot preprocessing scales with output size relative to fixed-knot baselines and standard reference methods.

4.5.1 Asymptotic complexity

Table 1 summarizes the asymptotic per-batch complexity of the preprocessing methods. Let d denote the number of numerical features, B the batch size, m the number of output bins or basis functions per feature, p the spline degree, and $K = m - p - 1$ the number of internal knots; see Appendix C.1. For fixed preprocessing methods such as Std, MinMax, and PLE, the cost is given by applying the corresponding feature transformation. For fixed-knot spline expansions, the dominant cost is basis evaluation, which scales as $O(d\,B\,m\,p)$. This applies to B-, M-, and I-spline bases, since all three use $m = K + p + 1$ basis functions per feature and share the same leading dependence on (d, B, m, p).

(a) Regression: smooth target approximation.

(b) Classification: threshold-like probability structure.

Figure 5: PLE and cubic B-spline fits on simple synthetic examples with the same basis budget ($m = 10$). (a) Regression example with a smooth nonlinear target, fitted using Ridge regression. The B-spline fit is smoother and tracks the target more closely, whereas the PLE fit shows piecewise-linear changes at the bin boundaries. (b) Classification example with a piecewise-constant class-probability function, fitted using logistic regression. The PLE fit better captures the sharp transitions and flat regions, whereas the B-spline fit changes more smoothly across the boundaries. This figure is intended as an illustration of the different behaviors of the two encodings rather than as a benchmark result.

For learnable-knot variants, the spline transform is part of the trainable computation graph, and additional overhead arises from differentiation with respect to knot parameters. Denoting the number of learnable internal knot parameters by n_{int}, this overhead appears in the forward and backward passes as summarized in Table 1. In our parameterization, n_{int} is proportional to K; see equation 10 and equation 12. The table reports per-batch cost once knot optimization is active and excludes one-time initialization costs. In our training setup, knot updates are activated only after an initial warm-up phase, so the measured end-to-end

Preprocessing variant	Transformation cost	Forward	Backward
Std	$O(d\,B)$	–	–
MinMax	$O(d\,B)$	–	–
PLE	$O(d\,B\,m)$	–	–
Fixed knots	$O(d\,B\,m\,p)$	–	–
Learnable knots	–	$O(d\,B\,m\,p) + O(d\,n_{\text{int}})$	$O(d\,B\,m\,p) + O(d\,B\,n_{\text{int}})$

Table 1: Asymptotic time complexity per batch. Here, d denotes the number of numerical features, B the batch size, m the per-feature output size, p the spline degree, and n_{int} the number of learnable internal knot parameters. Fixed knots refer to the B-, M-, and I-spline variants with uniform, quantile, and target-aware knot placement, while learnable knots refer to the gradient-based variants. Fixed preprocessing methods incur only transformation cost, whereas learnable-knot variants add forward and backward overhead during joint training with the backbone. Preprocessing abbreviations are given in Appendix 2.

runtime is lower than it would be if learnable-knot optimization were active from the first epoch. Although the three spline families share the same asymptotic order in our formulation, M-splines and I-splines incur larger constant factors due to normalization and cumulative or integral structure, which is reflected in the wall-clock measurements.

4.5.2 Parameter overhead of learnable knots

For learnable-knot variants, the additional parameters arise solely from making knot locations trainable and are independent of the downstream backbone. Under the softmax–cumsum parameterization in equation 10 and equation 12, we learn one scalar per interval width, giving $K + 1$ learnable parameters per numerical feature and therefore $d(K + 1) = d(m - p)$ additional parameters in total. For SGEMM, with $d = 14$ and $p = 3$, this corresponds to 56 extra parameters at $m = 7$, 168 at $m = 15$, and 378 at $m = 30$. This overhead is negligible relative to the backbone sizes, which range from approximately 66K to 1.13M parameters. Thus, learnable-knot variants primarily increase optimization cost rather than model capacity.

4.5.3 Wall-clock training time

Figure 6 reports total GPU wall-clock time over all five folds. Two effects drive the overall runtime. First, increasing the per-feature output size from $m \in \{7, 15, 30\}$ expands the numerical representation from $d = 14$ raw inputs to $dm \in \{98, 210, 420\}$ basis coordinates. This increases the computational load of the downstream backbone even when knots are fixed. On SGEMM, the effect is modest for MLP and ResNet, but clearly visible for FT-Transformer, where PLE and fixed-knot spline variants also become slower at larger m. Second, learnable-knot variants add backward-pass overhead through the knot parameters. Since BS-Grad-U, MS-Grad-U, and IS-Grad-U introduce the same number of additional knot parameters at a given m, their runtime differences are not explained by parameter count alone. They are more consistent with differences in basis-specific computation and the structure of the knot gradients.

Among the learnable-knot methods, BS-Grad-U is consistently the cheapest. Its runtime stays relatively stable for MLP and ResNet and increases only moderately for FT-Transformer. By contrast, MS-Grad-U and especially IS-Grad-U become much slower as m increases, with the largest gaps appearing for the MLP and, at $m = 30$, also for FT-Transformer. This suggests that the dominant overhead comes from the computational structure of the spline family rather than from the number of learnable knot parameters.

Why BS-Grad-U is cheaper than MS-Grad-U and IS-Grad-U. The separation in wall-clock time is consistent with the definitions of the three spline families and becomes more pronounced as m increases. B-splines have the most local computation. Under the Cox de Boor recursion, a degree-p basis function depends only on a local subset of knots and is nonzero on at most $(p + 1)$ consecutive knot intervals. When knots are learned, a perturbation therefore affects only a limited neighborhood of basis functions, which

keeps the backward pass comparatively cheap. M-splines add a knot-dependent normalization factor,

$$M_{j,\ell}^{(p)}(x_j) = \frac{p+1}{\tau_{j,\ell+p+1} - \tau_{j,\ell}} \, B_{j,\ell}^{(p)}(x_j),$$

so gradients must propagate not only through the B-spline recursion but also through the knot-dependent denominator. I-splines inherit this normalization and additionally introduce cumulative dependence through the integral structure,

$$I_{j,\ell}^{(p)}(x_j) = \int_{-\infty}^{x_j} M_{j,\ell}^{(p)}(t) \, dt.$$

As a result, their knot gradients pass through a less local computation graph with higher backward-pass cost.

These differences become more visible at larger m. Increasing m enlarges both the expanded representation and, through $K = m-p-1$, the number of internal knots. For BS-Grad-U, the added work remains relatively local. For MS-Grad-U and IS-Grad-U, the normalization and cumulative structure make this growth more expensive. This matches the stronger runtime increase observed for MS-Grad-U and IS-Grad-U in Fig. 6.

Backbone-dependent overhead. The downstream backbone also affects how these preprocessing costs appear in wall-clock time. With the expanded representation, the MLP consumes the full $d \times m$ input through a dense layer, so gradients from all expanded numerical features are mixed immediately before reaching the spline layer in the backward pass. This can make the more expensive knot-gradient computations of MS-Grad-U and IS-Grad-U more visible. ResNet may moderate this effect through its residual structure, while FT-Transformer processes features more independently before mixing them through attention. We do not attribute the backbone-specific differences to a single mechanism, since wall-clock time also depends on implementation details and optimization dynamics. Still, the larger overhead observed for the MLP is consistent with this interpretation.

Practical takeaway. Overall, the efficiency analysis shows that the cost of learnable-knot encodings is driven more by optimization overhead than by parameter count. Among these variants, BS-Grad-U offers the most favorable trade-off, while MS-Grad-U and IS-Grad-U become substantially more expensive as the output size increases.

5 Ablation study

To complement the main benchmark, we study how predictive performance changes with encoding resolution in a controlled synthetic regression setting. This allows us to isolate the effect of numerical feature encodings under a known input distribution and target structure.

Synthetic regression setup. We use a synthetic regression task to examine how performance changes with numerical encoding resolution in a controlled setting. The informative feature follows a skewed, non-uniform distribution, and the target combines smooth nonlinear variation, a threshold effect, and a localized peak. Detailed data generation and a visualization of the dataset are provided in Appendix J. We use the same MLP architecture and training setup as in the main experiments and vary only the encoding resolution, with $m \in \{5, 10, 15, 20, 25, 30, 35, 40, 45, 50\}$.

Compared methods and reporting. We compare Std, MinMax, and PLE with spline-based encodings using different knot-placement strategies. The sweep includes three reference methods without an output-size grid, namely Std, MinMax, and PLE_{adp}^{50}, together with 16 methods evaluated over $m \in \{5, 10, 15, 20, 25, 30, 35, 40, 45, 50\}$. This yields 163 method-resolution configurations in total. Each configuration is run with five random seeds, resulting in 815 training runs overall. Results are reported as mean test NRMSE, with shaded bands indicating $\pm$ one standard deviation across seeds. For Std and MinMax, output size is not applicable, while for PLE_{adp}^{50} the maximum number of bins is capped at 50 and the effective discretization is determined adaptively by tree-guided splits. All remaining optimization settings follow the main experiments. The resulting trends are shown in Fig. 7, with the corresponding numerical results reported in Table 13.

Figure 6: SGEMM efficiency case study: total GPU wall-clock time over 5-fold cross-validation. Comparison of Std, MinMax, PLE, fixed-knot spline variants (BS-U and IS-U), and learnable-knot spline variants (BS-Grad-U, MS-Grad-U, and IS-Grad-U) across basis budgets $m \in \{7, 15, 30\}$ for MLP, ResNet, and FT-Transformer. Values denote total end-to-end training time across all five folds. For learnable-knot variants, timings include the initial warm-up phase followed by joint optimization of knot parameters and backbone weights.

Main observations. Figure 7 shows that, for most methods, test NRMSE improves as m increases from 5 to roughly 15–35, after which the curves mostly plateau. This pattern is clearest for B-spline and I-spline variants, while PLE shows a similar but slightly flatter trend. The choice of knot-placement strategy mainly shifts the performance level within a spline family rather than changing the overall shape of the resolution curve. In this synthetic setting, CART-based and uniform placement give the strongest results.

Among all configurations, B-spline variants are the strongest overall. The best result is obtained by BS-CART at $m = 30$ with NRMSE 0.0456 ± 0.0014, and all top five settings are B-spline based, specifically BS-CART and BS-U. Several I-spline variants remain competitive, but they remain slightly above the best B-spline results within the same knot-placement group. By contrast, M-spline variants are generally weaker and often deteriorate at larger output sizes, with visibly wider uncertainty bands. One possible reason is the knot-dependent normalization factor $(\tau_{j,\ell+p+1} - \tau_{j,\ell})^{-1}$ in the M-spline definition in Appendix C.3, which may increase numerical sensitivity when adjacent knots become close. This larger variance is not apparent for MS-Grad-U, likely because the learnable-knot variant uses the LayerNorm-based stabilization described in Section 4. We do not investigate this effect further here.

Scope of the main benchmark. This ablation is consistent with the design choices made in the main benchmark. In particular, fixed-knot M-spline variants are not included there because, in this synthetic study, they are less stable and less competitive than the corresponding B-spline and I-spline variants, especially at larger output sizes. We nevertheless retain the learnable-knot M-spline variant, MS-Grad-U, as a reference point for end-to-end knot optimization, together with the numerical stabilization described in Section 4.

6 Conclusion

In this work, we showed that numerical encoding is an important modeling choice in tabular deep learning rather than a minor preprocessing detail. Our results demonstrate that basis expansion methods, and spline-based encodings in particular, provide a strong alternative to standard scaling approaches and can lead to clear performance gains. We further showed that spline knots can be optimized end to end in a stable manner under the proposed parameterization, making learnable-knot spline encodings a practical preprocessing approach. At the same time, their usefulness depends on the task, backbone, output size, knot-placement strategy, and computational budget, so no single method is uniformly best across all settings. The

Figure 7: Sensitivity to basis resolution on a synthetic regression task. Test NRMSE (mean $\pm$ std over 5 seeds) for PLE and spline-based encodings as the number of bins or basis functions varies over $\{5, 10, 15, 20, 25, 30, 35, 40, 45, 50\}$. Results are grouped by knot-selection strategy. Dotted horizontal lines show the Std, MinMax, and PLE_{adp}^{50} baselines. Preprocessing abbreviations are given in Appendix 2. All results use an MLP backbone.

ablation study supports this picture by showing that increasing encoding resolution is often beneficial up to a moderate range, after which gains tend to plateau, and that B-spline and I-spline variants are generally more stable than M-spline variants.

7 Limitations & Future Work

Our study covers only part of the design space of numerical preprocessing for tabular deep learning. We focus on a selected set of encodings, knot-placement strategies, output sizes, and backbones, and the efficiency analysis should be read as a case study rather than a universal runtime benchmark. The synthetic ablation is likewise controlled and does not capture the full heterogeneity of real-world tabular data.

Future work could examine broader adaptive encoding schemes, alternative learnable-knot parameterizations, and additional basis-function families such as thin-plate splines and radial basis functions (Wood, 2003; Buhmann, 2000). It would also be useful to better understand the task-dependent differences observed between regression and classification. In addition, we apply the same encoding family and output size to all numerical features. A natural extension would be to allow feature-specific choices, with different encodings or encoding sizes assigned to different features.

References

Sercan Ömer Arik and Tomas Pfister. Tabnet: Attentive interpretable tabular learning. *CoRR*, abs/1908.07442, 2019. URL http://arxiv.org/abs/1908.07442.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization, 2016. URL https://arxiv.org/abs/1607.06450.

Barry Becker and Ronny Kohavi. Adult. UCI Machine Learning Repository, 1996. DOI: https://doi.org/10.24432/C5XW20.

Pakshal Bohra, Joaquim Campos, Harshit Gupta, Shayan Aziznejad, and Michael Unser. Learning activation functions in deep (spline) neural networks. *IEEE Open Journal of Signal Processing*, 1:295–309, 2020. doi: 10.1109/OJSP.2020.3039379.

Vadim Borisov, Tobias Leemann, Kathrin Seßler, Johannes Haug, Martin Pawelczyk, and Gjergji Kasneci. Deep neural networks and tabular data: A survey. *IEEE Transactions on Neural Networks and Learning Systems*, 35(6):7499–7519, June 2024. ISSN 2162-2388. doi: 10.1109/tnnls.2022.3229161. URL http://dx.doi.org/10.1109/TNNLS.2022.3229161.

Mohamed Bouadi, Pratinav Seth, Aditya Tanna, and Vinay Kumar Sankarapu. Orion-msp: Multi-scale sparse attention for tabular in-context learning. *arXiv preprint arXiv:2511.02818*, 2025.

L. Breiman, J. Friedman, C.J. Stone, and R.A. Olshen. *Classification and Regression Trees.* Taylor & Francis, 1984. ISBN 9780412048418. URL https://books.google.de/books?id=JwQx-WOmSyQC.

Leo Breiman, Jerome Friedman, Richard A Olshen, and Charles J Stone. *Classification and regression trees.* Chapman and Hall/CRC, 2017.

Martin Dietrich Buhmann. Radial basis functions. *Acta numerica*, 9:1–38, 2000.

Tianqi Chen and Carlos Guestrin. Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '16, pp. 785–794, New York, NY, USA, 2016. Association for Computing Machinery. ISBN 9781450342322. doi: 10.1145/2939672.2939785. URL https://doi.org/10.1145/2939672.2939785.

Cerdeira A. Almeida F. Matos T. Cortez, Paulo and J. Reis. Wine Quality. UCI Machine Learning Repository, 2009. DOI: https://doi.org/10.24432/C56S3T.

C. de Boor. On calculating with b-splines. *Journal of Approximation Theory*, 6:50–62, 1972.

Janez Demšar. Statistical comparisons of classifiers over multiple data sets. *Journal of Machine learning research*, 7(Jan):1–30, 2006.

Ilaria DiMatteo, Christopher R Genovese, and Robert E Kass. Bayesian curve-fitting with free-knot splines. *Biometrika*, 88(4):1055–1071, 2001.

Conor Durkan, Artur Bekasov, Iain Murray, and George Papamakarios. *Neural spline flows.* Curran Associates Inc., Red Hook, NY, USA, 2019.

Paul H. C. Eilers and Brian D. Marx. Flexible smoothing with B-splines and penalties. *Statistical Science*, 11(2):89 – 121, 1996. doi: 10.1214/ss/1038425655. URL https://doi.org/10.1214/ss/1038425655.

Ali Eslamian, Alireza Afzal Aghaei, and Qiang Cheng. Tabkan: Advancing tabular data analysis using kolmogorov-arnold network. *Machine Learning for Computational Science and Engineering*, 1(2), November 2025. ISSN 3005-1436. doi: 10.1007/s44379-025-00042-y. URL http://dx.doi.org/10.1007/s44379-025-00042-y.

Benjamin Feuer, Robin T Schirrmeister, Valeriia Cherepanova, Chinmay Hegde, Frank Hutter, Micah Goldblum, Niv Cohen, and Colin White. Tunetables: Context optimization for scalable prior-data fitted networks. *Advances in Neural Information Processing Systems*, 37:83430–83464, 2024.

Jerome H Friedman. Greedy function approximation: a gradient boosting machine. *Annals of statistics*, pp. 1189–1232, 2001.

Milton Friedman. The use of ranks to avoid the assumption of normality implicit in the analysis of variance. *Journal of the american statistical association*, 32(200):675–701, 1937.

Yury Gorishniy, Ivan Rubachev, Valentin Khrulkov, and Artem Babenko. Revisiting deep learning models for tabular data. *Advances in Neural Information Processing Systems*, 34:18932–18943, 2021.

Yury Gorishniy, Ivan Rubachev, and Artem Babenko. On embeddings for numerical features in tabular deep learning. *Advances in Neural Information Processing Systems*, 35:24991–25004, 2022.

Léo Grinsztajn, Klemens Flöge, Oscar Key, Felix Birkel, Philipp Jund, Brendan Roof, Benjamin Jäger, Dominik Safaric, Simone Alessi, Adrian Hayler, et al. Tabpfn-2.5: Advancing the state of the art in tabular foundation models. *arXiv preprint arXiv:2511.08667*, 2025.

Trevor Hastie, Robert Tibshirani, Jerome Friedman, et al. The elements of statistical learning, 2009.

Noah Hollmann, Samuel Müller, Katharina Eggensperger, and Frank Hutter. Tabpfn: A transformer that solves small tabular classification problems in a second. *arXiv preprint arXiv:2207.01848*, 2022.

Noah Hollmann, Samuel Müller, Lennart Purucker, Arjun Krishnakumar, Max Körfer, Shi Bin Hoo, Robin Tibor Schirrmeister, and Frank Hutter. Accurate predictions on small data with a tabular foundation model. *Nature*, 637(8045):319–326, 2025.

David Holzmüller, Leo Grinsztajn, and Ingo Steinwart. Realmlp: Advancing mlps and default parameters for tabular data. In *ELLIS workshop on Representation Learning and Generative Models for Structured Data*, 2025.

Xin Huang, Ashish Khetan, Milan Cvitkovic, and Zohar Karnin. Tabtransformer: Tabular data modeling using contextual embeddings. *arXiv preprint arXiv:2012.06678*, 2020.

Ronald L Iman and James M Davenport. Approximations of the critical region of the fbietkan statistic. *Communications in Statistics-Theory and Methods*, 9(6):571–595, 1980.

Arlind Kadra, Sebastian Pineda Arango, and Josif Grabocka. Interpretable mesomorphic networks for tabular data. *Advances in Neural Information Processing Systems*, 37:31759–31787, 2024.

Guolin Ke, Qi Meng, Thomas Finley, Taifeng Wang, Wei Chen, Weidong Ma, Qiwei Ye, and Tie-Yan Liu. Lightgbm: A highly efficient gradient boosting decision tree. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper_files/paper/2017/file/6449f44a102fde848669bdd9eb6b76fa-Paper.pdf.

Ziming Liu, Yixuan Wang, Sachin Vaidya, Fabian Ruehle, James Halverson, Marin Soljačić, Thomas Y. Hou, and Max Tegmark. Kan: Kolmogorov-arnold networks, 2025. URL https://arxiv.org/abs/2404.19756.

Mattias Luber, Anton Thielmann, and Benjamin Säfken. Structural neural additive models: Enhanced interpretable machine learning. *arXiv preprint arXiv:2302.09275*, 2023.

Mary C. Meyer. Inference using shape-restricted regression splines. *The Annals of Applied Statistics*, 2(3): 1013 – 1033, 2008. doi: 10.1214/08-AOAS167. URL https://doi.org/10.1214/08-AOAS167.

Soumya D Mohanty and Ethan Fahnestock. Adaptive spline fitting with particle swarm optimization. *Computational Statistics*, 36(1):155–191, 2021.

Rita P. Moro, S. and P. Cortez. Bank Marketing. UCI Machine Learning Repository, 2014. DOI: https://doi.org/10.24432/C5K306.

Sellers Tracy Talbot Simon Cawthorn Andrew Nash, Warwick and Wes Ford. Abalone. UCI Machine Learning Repository, 1994. DOI: https://doi.org/10.24432/C55C7W.

Peter Bjorn Nemenyi. *Distribution-free multiple comparisons.* Princeton University, 1963.

Sergei Popov, Stanislav Morozov, and Artem Babenko. Neural oblivious decision ensembles for deep learning on tabular data, 2019. URL `https://arxiv.org/abs/1909.06312`.

Liudmila Prokhorenkova, Gleb Gusev, Aleksandr Vorobev, Anna Veronika Dorogush, and Andrey Gulin. Catboost: unbiased boosting with categorical features. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, pp. 6639–6649, Red Hook, NY, USA, 2018. Curran Associates Inc.

Jingang Qu, David HolzmÃžller, GaÃl Varoquaux, and Marine Le Morvan. Tabicl: A tabular foundation model for in-context learning on large data. *arXiv preprint arXiv:2502.05564*, 2025.

James O. Ramsay. Monotone regression splines in action. *Statistical Science*, 3(4):425–441, 1988. doi: 10.1214/ss/1177012761.

Alex Shtoff, Elie Abboud, Rotem Stram, and Oren Somekh. Function basis encoding of numerical features in factorization machines, 2025. URL `https://arxiv.org/abs/2305.14528`.

Ravid Shwartz-Ziv and Amitai Armon. Tabular data: Deep learning is not all you need, 2021. URL `https://arxiv.org/abs/2106.03253`.

Gowthami Somepalli, Micah Goldblum, Avi Schwarzschild, C. Bayan Bruss, and Tom Goldstein. Saint: Improved neural networks for tabular data via row attention and contrastive pre-training, 2021. URL `https://arxiv.org/abs/2106.01342`.

Shriyank Somvanshi, Subasish Das, Syed Aaqib Javed, Gian Antariksa, and Ahmed Hossain. A survey on deep tabular learning, 2024. URL `https://arxiv.org/abs/2410.12034`.

Steven Spiriti, Randall Eubank, Philip W Smith, and Dennis Young. Knot selection for least-squares and penalized splines. *Journal of Statistical Computation and Simulation*, 83(6):1020–1036, 2013.

Min-Kook Suh, Moonjung Eo, Ye Seul Sim, and Woohyung Lim. Learnable numerical input normalization for tabular representation learning based on b-splines. In *NeurIPS 2024 Third Table Representation Learning Workshop*, 2024.

Anton Thielmann, Thomas Kneib, and Benjamin Säfken. Enhancing adaptive spline regression: An evolutionary approach to optimal knot placement and smoothing parameter selection. *Journal of Computational and Graphical Statistics*, pp. 1–13, 2025.

Anton Frederik Thielmann, Manish Kumar, Christoph Weisser, Arik Reuter, Benjamin Säfken, and Soheila Samiee. Mambular: A sequential model for tabular deep learning. *arXiv preprint arXiv:2408.06291*, 2024.

Athanasios Tsanas and Max Little. Parkinsons Telemonitoring. UCI Machine Learning Repository, 2009. DOI: https://doi.org/10.24432/C5ZS3N.

Simon N. Wood. Thin plate regression splines. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 65(1):95–114, 01 2003. ISSN 1369-7412. doi: 10.1111/1467-9868.00374. URL `https://doi.org/10.1111/1467-9868.00374`.

Simon N Wood. *Generalized additive models: an introduction with R.* chapman and hall/CRC, 2017.

Xiyuan Zhang, Danielle C Maddix, Junming Yin, Nick Erickson, Abdul Fatir Ansari, Boran Han, Shuai Zhang, Leman Akoglu, Christos Faloutsos, Michael W Mahoney, et al. Mitra: Mixed synthetic priors for enhancing tabular foundation models. *arXiv preprint arXiv:2510.21204*, 2025.

Liangwewi Nathan Zheng, Wei Emma Zhang, Lin Yue, Miao Xu, Olaf Maennel, and Weitong Chen. Free-knots kolmogorov-arnold network: On the analysis of spline knots and advancing stability. *arXiv preprint arXiv:2501.09283*, 2025.

Category	Method	Description	Target-aware	Learnable-knot
Baseline	Std	Standardization (z-score)	–	–
	MinMax	min-max scaling to $[0, 1]$	–	–
	PLE	Piecewise Linear Encoding	✓	–
	PLE_{adp}^{50}	Adaptive PLE with $n_{bins} \in [5, 50]$ selected by tree splits (Table 6)	✓	–
B-Spline	BS-U	Uniform knot placement	–	–
	BS-Q	Quantile-based knot placement	–	–
	BS-CART	CART-based target-aware knot placement	✓	–
	BS-LGBM	LightGBM-based target-aware knot placement	✓	–
	BS-Grad-U*	Uniform initialization with end-to-end knot optimization	–	✓
I-Spline	IS-U	Uniform knot placement	–	–
	IS-Q	Quantile-based knot placement	–	–
	IS-CART	CART-based target-aware knot placement	✓	–
	IS-LGBM	LightGBM-based target-aware knot placement	✓	–
	IS-Grad-U*	Uniform initialization with end-to-end knot optimization	–	✓
M-Spline	MS-U	Uniform knot placement	–	–
	MS-Q	Quantile-based knot placement	–	–
	MS-CART	CART-based target-aware knot placement	✓	–
	MS-LGBM	LightGBM-based target-aware knot placement	✓	–
	MS-Grad-U*	Uniform initialization with end-to-end knot optimization	–	✓

Note. "–" indicates that the option is not applicable. "Target-aware" denotes knot placement based on target-dependent split points. "Learnable-knot" denotes variants in which internal knot locations are optimized jointly with the downstream model during training. Methods marked with * use uniform knot placement for initialization.

Table 2: Preprocessing abbreviations used throughout the paper. The table summarizes the naming convention for baseline, spline-based, target-aware, and learnable-knot variants.

A Preprocessing Abbreviations

For clarity and consistency, we refer to preprocessing methods throughout the paper using abbreviated names such as Std, MinMax, PLE, BS-*, IS-*, and MS-*. The complete mapping is provided in Table 2.

B Dataset Details

We benchmark on 25 tabular datasets, including 13 regression and 12 classification datasets, of which 3 are multiclass. The datasets are drawn from OpenML and the UCI Machine Learning Repository.[1][2] Table 3 reports per-dataset statistics, including the numbers of numerical and categorical features, split sizes, and class imbalance where applicable. Samples with missing values are removed. For classification datasets, we report the dominant-class ratio as a measure of class imbalance. Unless stated otherwise, numerical features are scaled to $[0, 1]$ before applying feature-expansion methods such as splines and PLE, while the baseline pipelines use standardization (Std) or min-max scaling (MinMax). For the Shuttle dataset, we

---

[1] https://www.openml.org
[2] https://archive.ics.uci.edu

Dataset	Abbr.	#cat	#num	Train	Val	Test	Ratio	Reference / OpenML ID
Regression								
Abalone	AB	1	7	3008	334	835	–	Nash & Ford (1994)
California Housing	CA	1	8	14861	1651	4128	–	OpenML: 45028
CPU Small	CPU	0	12	5899	655	1638	–	OpenML: –
Diamonds	DI	3	6	38837	4315	10788	–	OpenML: 44979
House Sales	HS	0	18	15562	1729	4322	–	OpenML: 42092
Parkinsons	PA	0	19	4230	470	1175	–	Tsanas & Little (2009)
Wine Quality	WI	0	11	4679	519	1299	–	Cortez & Reis (2009)
House8L	H8	0	8	16405	1822	4556	–	OpenML: 218
Pulsar	PU	0	8	12888	1431	3579	–	OpenML: 45558
Sulphur	SU	0	6	7259	806	2016	–	OpenML: 44020
FIFA Wage	FW	0	5	13006	1445	3612	–	OpenML: 44026
SGEMM GPU	SG	0	14	14400	1600	4000	–	OpenML: 44961
Protein	PR	0	9	32926	3658	9146	–	OpenML: 44963
Classification								
Adult	AD	8	5	35167	3907	9768	76.1%	Becker & Kohavi (1996)
Bank	BA	8	7	32553	3616	9042	88.3%	Moro & Cortez (2014)
Churn	CH	2	8	7200	800	2000	79.6%	OpenML: 46911
FICO	FI	0	23	7532	836	2091	52.2%	OpenML: 45554
Marketing	MA	7	7	31100	3455	8638	88.4%	OpenML: –
EEG Eye State	EEG	0	14	10786	1198	2996	55.1%	OpenML: 1471
Gamma Telescope	GT	1	9	9549	1060	2652	50.4%	OpenML: 44085
IPUMS (LA 97)	IP	1	19	3730	414	1036	50.1%	OpenML: 44084
Loan Status	LS	5	8	18905	2100	5251	77.7%	OpenML: 44556
Multiclass								
Air Quality (4-class)	AQ	1	8	3600	400	1000	40.0%	OpenML: 46880
Loan Type (7-class)	LT	0	6	6154	683	1709	27.9%	OpenML: 46511
Shuttle (7-class)	SH	0	9	18000	2000	5000	78.6%	OpenML: 40685

Table 3: Benchmark datasets used in the experiments. For each dataset, we report the abbreviation, the numbers of categorical (#cat) and numerical (#num) features, and the average train, validation, and test split sizes over 5-fold cross-validation. *Ratio* denotes the dominant-class percentage for classification and multiclass datasets. The last column gives the OpenML dataset ID or the corresponding UCI citation.

randomly subsample 25K instances while preserving class proportions to control computational cost. Table 4 summarizes the overall scale and feature dimensionality of the benchmark suite.

C   Spline Basis Definitions

C.1   Basis Indexing and Basis Function Counts

For each numerical feature x_j, the spline expansion is defined by basis functions $\{b_{j,\ell}(x_j; \tau_j)\}_{\ell=1}^{m_j}$, where ℓ indexes the basis functions for feature j and m_j is the resulting expansion dimension. Throughout the study, we use cubic splines ($p = 3$).

B-, M-, and I-splines.   For B-, M-, and I-splines, the number of basis functions is determined by the spline degree and the knot configuration. Let K_j denote the number of internal knots for feature j. Under

Metric	Regression	Classification	Total
Number of datasets	13	12	25
Total samples	255,489	255,928	511,417
Avg. samples per dataset	19,653	21,327	20,456
Avg. features per dataset	10.5	13.0	11.7
Min. features	5	6	5
Max. features	19	23	23

Table 4: Benchmark dataset summary. Aggregate statistics of the benchmark suite, including the number of datasets, total samples, average samples per dataset, and feature counts, reported separately for regression and classification datasets and for the full collection.

the standard open (clamped) knot construction,

$$m_j = K_j + p + 1, \qquad K_j = m_j - p - 1.$$

These relations apply to all three spline families. Thus, ℓ indexes a basis function within the expansion of feature j, and m_j gives the dimensionality contributed by that feature to the transformed numerical input.

C.2 B-spline Basis Definition

We follow the basis indexing convention in Appendix C.1. We use a nondecreasing knot sequence

$$\tau_j = (\tau_{j,1}, \ldots, \tau_{j,K_j+2p+2}),$$

obtained by augmenting the K_j internal knots with boundary knots repeated $p+1$ times at each end. The B-spline basis functions are defined by the Cox–de Boor recursion.

Zero-degree basis:

$$B_{j,\ell}^{(0)}(x_j) = \begin{cases} 1, & \tau_{j,\ell} \leq x_j < \tau_{j,\ell+1}, \\ 0, & \text{otherwise.} \end{cases}$$

Cox de Boor recursion:

$$B_{j,\ell}^{(p)}(x_j) = \frac{x_j - \tau_{j,\ell}}{\tau_{j,\ell+p} - \tau_{j,\ell}} B_{j,\ell}^{(p-1)}(x_j) + \frac{\tau_{j,\ell+p+1} - x_j}{\tau_{j,\ell+p+1} - \tau_{j,\ell+1}} B_{j,\ell+1}^{(p-1)}(x_j), \qquad p \geq 1,$$

with each fraction defined as zero when its denominator is zero.

Embedding:

$$\Phi_j^B(x_j) = \left(B_{j,1}^{(p)}(x_j), \ldots, B_{j,m_j}^{(p)}(x_j) \right).$$

C.3 M-Spline Basis Definition

M-splines are nonnegative, locally supported basis functions normalized to integrate to one. We follow the basis indexing convention in Appendix C.1. We use a nondecreasing knot sequence

$$\tau_j = (\tau_{j,1}, \ldots, \tau_{j,K_j+2p+2}),$$

obtained by augmenting the K_j internal knots with boundary knots repeated $p+1$ times at each end.

Definition (normalized B-splines): Let $B_{j,\ell}^{(p)}(x_j)$ denote the degree-p B-spline basis function defined in Appendix C.2. The corresponding M-spline basis is

$$M_{j,\ell}^{(p)}(x_j) = \frac{p+1}{\tau_{j,\ell+p+1} - \tau_{j,\ell}} B_{j,\ell}^{(p)}(x_j), \qquad \ell = 1, \ldots, m_j,$$

with $M_{j,\ell}^{(p)}(x_j) = 0$ whenever $\tau_{j,\ell+p+1} = \tau_{j,\ell}$.

Properties:

$$M_{j,\ell}^{(p)}(x_j) \geq 0, \qquad \int_{-\infty}^{\infty} M_{j,\ell}^{(p)}(t)\, dt = 1.$$

Support: Each M-spline basis function has compact support on

$$\mathrm{supp}\big(M_{j,\ell}^{(p)}\big) = [\tau_{j,\ell}, \tau_{j,\ell+p+1}).$$

Embedding:

$$\Phi_j^M(x_j) = \big(M_{j,1}^{(p)}(x_j), \ldots, M_{j,m_j}^{(p)}(x_j)\big).$$

C.4 I-Spline Basis Definition

I-splines are integrated M-splines and yield monotone (non-decreasing) basis functions. We follow the basis indexing convention in Appendix C.1. We use the same knot sequence τ_j and M-spline basis $M_{j,\ell}^{(p)}$ as in Appendix C.3.

Definition (integrated M-splines):

$$I_{j,\ell}^{(p)}(x_j) = \int_{-\infty}^{x_j} M_{j,\ell}^{(p)}(t)\, dt, \qquad \ell = 1, \ldots, m_j.$$

Monotonicity:

$$\frac{d}{dx_j} I_{j,\ell}^{(p)}(x_j) = M_{j,\ell}^{(p)}(x_j) \geq 0.$$

Embedding:

$$\Phi_j^I(x_j) = \big(I_{j,1}^{(p)}(x_j), \ldots, I_{j,m_j}^{(p)}(x_j)\big).$$

D PLE Definition

Piecewise Linear Encoding (PLE).

Let $x \in \mathbb{R}$ be a numerical feature and let

$$b_0 < b_1 < \cdots < b_T$$

denote a sequence of bin boundaries. The PLE representation of x is defined as

$$\mathrm{PLE}(x) = (e_1, \ldots, e_T) \in \mathbb{R}^T,$$

where each component e_t is given by

$$e_t = \begin{cases} 0, & x < b_{t-1} \text{ and } t > 1, \\ 1, & x \geq b_t \text{ and } t < T, \\ \dfrac{x - b_{t-1}}{b_t - b_{t-1}}, & \text{otherwise.} \end{cases}$$

Interpretation. The encoding can be viewed as a cumulative piecewise-linear basis: all bins strictly to the left of x are fully activated ($e_t = 1$), bins strictly to the right are inactive ($e_t = 0$), and the bin containing x is linearly interpolated.

Model	Architecture	Configuration
MLP	3-layer MLP	Hidden dims $[256, 128, 64]$; ReLU activations; dropout 0.3.
ResNet	Residual MLP blocks (Gorishniy et al. (2021))	Block: Linear $\to$ BN $\to$ ReLU $\to$ Dropout $\to$ Linear $\to$ BN + skip; $d_{\text{model}} = 256$; $n_{\text{blocks}} = 3$; $d_{\text{hidden\_factor}} = 2.0$; dropout 0.3; batch normalization.
FTT (FT-Transformer)	Feature Tokenizer + Transformer (Gorishniy et al. (2021))	$d_{\text{token}} = 192$; $n_{\text{blocks}} = 3$; $n_{\text{heads}} = 8$; attention dropout 0.2; FFN dropout 0.1; residual dropout 0.0; $ffn\_factor = 4/3$; ReGLU activations.

Shared training setup (all models)

AdamW with backbone learning rate $\eta_\theta = 10^{-4}$ and weight decay 10^{-5}, batch size 512, and a maximum of 200 epochs. Early stopping patience is set to 15, and ReduceLROnPlateau uses patience 10 with factor 0.1. For FT-Transformer, weight decay is excluded from feature token embeddings, layer normalization parameters, the `[CLS]` token, and bias terms.

Additional setup for gradient-based knot optimization

For learnable-knot spline variants, knot locations are optimized jointly with the backbone model. Knot updates are activated after a warm-up of $E_{\text{warm}} = 50$ epochs. A separate learning rate is used for the knot parameters, with $\eta_a = 2\eta_\theta = 2 \times 10^{-4}$.

Table 5: Backbone architectures and training configuration. We report the hyperparameters for the MLP, ResNet, and FT-Transformer backbones, along with the shared optimization strategy. Additional settings specific to gradient-based knot optimization are listed separately.

Properties:

$$0 \le e_t \le 1, \qquad \sum_{t=1}^{T} \mathbb{I}[e_t > 0] \le 2.$$

Thus, at most two adjacent components are nonzero, yielding a sparse and locally linear representation.

Embedding:

$$\Phi^{\text{PLE}}(x) = (e_1, \ldots, e_T).$$

E   Model Architecture and Training Configuration

Table 5 summarizes the backbone hyperparameters and shared optimization settings used throughout the experiments.

E.1   Hardware

All experiments were conducted on an Azure `Standard_NC48ads_A100_v4` virtual machine equipped with two NVIDIA A100 accelerators. Together, the two devices provided a total of $160\,\text{GB}$ of GPU memory. Unless stated otherwise, all reported training and evaluation results were obtained on this hardware setup.

F   Target-aware Knot Selection Configuration

Adaptive vs. non-adaptive output size. In *non-adaptive* mode, the per-feature output dimensionality is fixed in advance and shared across methods. We consider three output sizes, $m \in \{7, 15, 30\}$, corresponding to the number of basis functions for spline encodings and the number of bins for PLE. In *adaptive* mode, the output size is determined by the tree-guided procedure. This setting is used only for PLE in the ablation study, where the effective number of bins is selected from the range $[5, 50]$ subject to the regularization constraints reported in Table 6.

Method	Variant	Component	Non-adaptive (fixed)	Adaptive (range)
PLE	CART-based	Output size	$m = \{7, 15, 30\}$	$min\_bins = 5$
$max\_bins = 50$
		Tree regularization	$min\_samples\_leaf = 1$
$min\_samples\_split = 2$	$min\_samples\_leaf = 25$
$min\_samples\_split = 2$
Splines	CART-based	Output size	$m = \{7, 15, 30\}$	–
		Tree / knot constraints	$max\_depth = 6$
$min\_knot\_spacing = 0.01$	–
Splines	LightGBM-based	Output size	$m = \{7, 15, 30\}$	–
		GBDT hyperparameters	$n\_estimators = 100$
$max\_depth = 3$
$learning\_rate = 0.1$	–

Table 6: Target-aware configuration details and output-size settings. We report the configurations for target-aware PLE binning and target-aware spline knot placement using CART and LightGBM. Adaptive output size is used only for PLE in the ablation study; spline encodings use fixed output sizes $m \in \{7, 15, 30\}$.

G Preprocessing Pipeline

For completeness, we provide the full algorithmic details of the spline preprocessing pipeline and the learnable-knot optimization procedure in Algorithm 1 and Algorithm 2, respectively. The preprocessing pipeline is shared by all spline variants listed in Table 2, whereas the second algorithm applies only to the learnable-knot variants.

H Critical Difference (CD) Diagrams

We summarize comparisons of multiple preprocessing methods using *critical difference (CD) diagrams*, following the rank-based evaluation protocol for multi-dataset studies (Demšar, 2006). For each evaluation block i, here one *dataset × backbone* pair, we rank the k preprocessing methods by performance, where rank 1 is best and ties receive the average rank. Let $r_{i,j}$ denote the rank of method $j \in \{1, \ldots, k\}$ on block $i \in \{1, \ldots, N\}$. The diagram reports the *average rank*

$$\bar{r}_j \;=\; \frac{1}{N} \sum_{i=1}^{N} r_{i,j},$$

where lower $\bar{r}_j$ indicates better overall performance.

To test whether rank differences are attributable to chance, we first apply the Friedman test for repeated-measures comparisons (Friedman, 1937; Iman & Davenport, 1980). When the global null is rejected, we use the Nemenyi post-hoc procedure to account for multiple pairwise comparisons (Nemenyi, 1963; Demšar, 2006). The corresponding *critical difference* at significance level α is

$$\text{CD} \;=\; q_\alpha \sqrt{\frac{k(k+1)}{6N}},$$

where q_α is the critical value of the Studentized range used by the Nemenyi test. Two methods are considered significantly different if $|\bar{r}_a - \bar{r}_b| > \text{CD}$. CD diagrams are widely used in modern ML and DL benchmarking to summarize average ranks and statistically indistinguishable groups across many datasets (Feuer et al., 2024; Kadra et al., 2024).

In our setting, we compare $k = 14$ preprocessing methods across three backbones, MLP, ResNet, and FT-Transformer, and report CD diagrams separately for each output size $m \in \{7, 15, 30\}$. The number of blocks

---

Algorithm 1: Spline-Based Numerical Encoding Pipeline

Input: Numerical features $x_{\text{num}} = (x_1, \ldots, x_d)$; spline family $\mathcal{S} \in \{\text{B}, \text{M}, \text{I}\}$; knot strategy
$\quad$ $\mathcal{K} \in \{\text{uniform}, \text{quantile-based}, \text{target-aware}, \text{learnable-knot}\}$; (optional) targets y; number of internal knots
$\quad$ $\{K_j\}_{j=1}^d$

Output: Expanded numerical encoding $\Phi(x_{\text{num}})$

Normalize each numerical feature to $[0, 1]$ using training-split statistics

for $j \leftarrow 1$ **to** d **do**

$\quad$ **Knot placement** Construct an internal-knot vector $\kappa_j = (\kappa_{j,1}, \ldots, \kappa_{j,K_j})$

$\quad$ **if** $\mathcal{K}$ *is uniform* **then**

$$\kappa_{j,\ell} \leftarrow \frac{\ell}{K_j + 1}, \qquad \ell = 1, \ldots, K_j.$$

$\quad$ **else if** $\mathcal{K}$ *is quantile-based* **then**

$$\kappa_{j,\ell} \leftarrow Q_j\left(\frac{\ell}{K_j + 1}\right), \qquad \ell = 1, \ldots, K_j,$$

$\quad\quad$ where $Q_j(\cdot)$ is the empirical quantile function of the normalized feature x_j

$\quad$ **else if** $\mathcal{K}$ *is target-aware* **then**

$\quad\quad$ Fit a one-dimensional supervised splitter on (x_j, y) and collect candidate split points

$\quad\quad\quad$ Use either (i) CART or (ii) LightGBM to obtain candidate thresholds on x_j

$\quad\quad\quad$ Apply the spacing filter and retain up to K_j thresholds ranked by split gain

$\quad\quad\quad$ If fewer than K_j valid thresholds remain, supplement with quantiles of x_j

$\quad\quad\quad$ Set κ_j to the sorted selected thresholds

$\quad\quad$ `// Applicable to all spline families` $\mathcal{S} \in \{\text{B}, \text{M}, \text{I}\}$`.`

$\quad$ **else if** $\mathcal{K}$ *is learnable-knot* **then**

$\quad\quad$ `// Internal knots are optimized jointly with the downstream model.`

$\quad\quad$ Initialize κ_j from uniform placement

$\quad\quad$ Parameterize ordered internal knots via learnable spacings (softmax-cumsum) and update by backpropagation
$\quad\quad$ during training (Algorithm 2)

$\quad\quad$ `// Applicable to all spline families` $\mathcal{S} \in \{\text{B}, \text{M}, \text{I}\}$`.`

$\quad$ **Full knot sequence** Construct τ_j by augmenting κ_j with boundary knots using the standard boundary handling for
$\quad$ spline family $\mathcal{S}$

$\quad$ **Basis construction** Define basis functions $\{b_{j,\ell}(\cdot; \tau_j)\}_{\ell=1}^{m_j}$ according to spline family $\mathcal{S}$, where $m_j = K_j + p + 1$

$\quad$ **if** $\mathcal{S}$ *is B-splines* **then**

$\quad\quad$ Use the B-spline basis associated with τ_j (Appendix C.2)

$\quad$ **else if** $\mathcal{S}$ *is M-splines* **then**

$\quad\quad$ Use the corresponding nonnegative M-spline basis (Appendix C.3)

$\quad$ **else if** $\mathcal{S}$ *is I-splines* **then**

$\quad\quad$ Use the integrated I-spline basis (Appendix C.4)

$\quad$ **Basis evaluation**

$$\phi_j(x_j; \tau_j) \leftarrow \left(b_{j,1}(x_j; \tau_j), \ldots, b_{j,m_j}(x_j; \tau_j)\right).$$

Concatenation

$$\Phi(x_{\text{num}}) \leftarrow \left[\phi_1(x_1; \tau_1) \;\|\; \cdots \;\|\; \phi_d(x_d; \tau_d)\right].$$

---

is task-dependent. We have $N_{\text{reg}} = 13 \times 3 = 39$ for regression, $N_{\text{cls}} = 12 \times 3 = 36$ for classification, and $N_{\text{all}} = (13 + 12) \times 3 = 75$ when combining both tasks. To combine regression and classification in the same diagram, we orient all metrics so that higher is better, for example by negating regression errors such as NRMSE, before computing within-block ranks.

I   Experimental Results

We report detailed per-dataset results for both regression and classification in this appendix. For each task, we evaluate three fixed per-feature output sizes, corresponding to $m \in \{7, 15, 30\}$. For spline-based encodings (B-, I-, and M-splines), these values determine the number of basis functions. For PLE, the same values correspond to the number of bins. The baseline preprocessing methods, Std and MinMax, do not depend on output size and are therefore identical across all three settings. Within each backbone and dataset, the best-performing method is highlighted in bold.

Algorithm 2: Learnable-knot optimization for spline feature expansion

---

Input: Training data $\{(x_{\text{num}}^{(i)}, x_{\text{cat}}^{(i)}, y^{(i)})\}_{i=1}^{n}$ with d numerical features; numbers of internal knots $\{K_j\}_{j=1}^{d}$; minimum spacing $\delta > 0$; regularization weight $\lambda \geq 0$; stabilizer $\varepsilon > 0$; backbone f_θ; learning rates η_θ, η_a; warm-start epochs E_{warm}; total epochs E.

Output: Backbone parameters θ and knot parameters $a = (a_1, \ldots, a_d)$.

Normalize. Map all numerical features to $[0, 1]$ using training-split statistics

Initialize knot parameters. for $j \leftarrow 1$ **to** d **do**

    Choose an initial internal-knot vector
$$\kappa_j^{(0)} = (\kappa_{j,1}^{(0)}, \ldots, \kappa_{j,K_j}^{(0)})$$

    using uniform placement

    Convert internal knots to widths:
$$w_{j,1}^{(0)} = \kappa_{j,1}^{(0)}, \quad w_{j,r}^{(0)} = \kappa_{j,r}^{(0)} - \kappa_{j,r-1}^{(0)} \ (r = 2, \ldots, K_j), \quad w_{j,K_j+1}^{(0)} = 1 - \kappa_{j,K_j}^{(0)}.$$

    Invert the spacing map to initialize $a_j \in \mathbb{R}^{K_j+1}$:
$$\pi_{j,r}^{(0)} = \frac{w_{j,r}^{(0)} - \delta}{1 - (K_j + 1)\delta} \quad (r = 1, \ldots, K_j + 1), \qquad a_{j,r} \leftarrow \log\Big(\max(\pi_{j,r}^{(0)}, 10^{-12})\Big).$$

Initialize backbone parameters θ using a standard initialization scheme

for $e \leftarrow 1$ **to** E **do**

    if $e \leq E_{\text{warm}}$ **then**
        Freeze a (no updates)

    else
        Unfreeze a

    foreach *minibatch* $\mathcal{B}$ **do**

        Compute ordered internal knots. for $j \leftarrow 1$ **to** d **do**
$$\pi_{j,r} \leftarrow \frac{\exp(a_{j,r})}{\sum_{s=1}^{K_j+1} \exp(a_{j,s})} \quad (r = 1, \ldots, K_j + 1), \qquad w_{j,r} \leftarrow \delta + \Big(1 - (K_j + 1)\delta\Big)\pi_{j,r},$$
$$\kappa_{j,\ell} \leftarrow \sum_{r=1}^{\ell} w_{j,r} \quad (\ell = 1, \ldots, K_j).$$

        Construct full knot sequence τ_j from κ_j using boundary handling for chosen spline family

        Spline feature expansion. Compute $\Phi(x_{\text{num}}; \tau(a))$ by evaluating the chosen spline family (B-, M-, or I-splines; basis definitions are in Appendix C) using full knot sequences $\{\tau_j\}_{j=1}^{d}$

        Forward and task loss.
$$L_{\text{task}} \leftarrow \frac{1}{|\mathcal{B}|} \sum_{i \in \mathcal{B}} \mathcal{L}\Big(f_\theta\big(\Phi(x_{\text{num}}^{(i)}; \tau(a)), x_{\text{cat}}^{(i)}\big), y^{(i)}\Big).$$

        Collision avoidance.
$$\mathcal{R}_{\text{space}}(a) \leftarrow \frac{1}{d} \sum_{j=1}^{d} \frac{1}{K_j + 1} \sum_{r=1}^{K_j+1} \frac{1}{w_{j,r} + \varepsilon}.$$

        Total loss and update.
$$L \leftarrow L_{\text{task}} + \lambda \, \mathcal{R}_{\text{space}}(a).$$
        Take one optimizer step using $\nabla_\theta L$ and, if unfrozen, $\nabla_a L$, for example
$$\theta \leftarrow \theta - \eta_\theta \nabla_\theta L, \qquad a \leftarrow a - \eta_a \nabla_a L.$$
        The knot learning rate η_a is chosen separately from η_θ. In our experiments, we use $\eta_a = 2\eta_\theta$.

I.1 Regression Results

Regression tables report mean NRMSE ($\downarrow$) $\pm$ standard deviation over 5-fold cross-validation. Results are provided for $m = 7$, $m = 15$, and $m = 30$ in Tables 7, 8, and 9, respectively.

I.2 Classification Results

Classification tables report mean AUC ($\uparrow$) $\pm$ standard deviation over 5-fold cross-validation. For binary datasets, this corresponds to standard ROC-AUC. For multiclass datasets, we report weighted one-vs-rest ROC-AUC. Results are provided for $m = 7$, $m = 15$, and $m = 30$ in Tables 10, 11, and 12, respectively.

I.3 Synthetic Setup for the Illustrative Comparison of PLE and B-spline Encodings

This appendix provides the setup used for the illustrative comparison in Section 4.4. The experiment is intended only to visualize the different inductive biases of PLE and cubic B-spline encodings under the same basis budget. We generate two one-dimensional datasets on the interval $x \in [0, 1]$ using a fixed random seed. For regression, we sample $n = 2500$ inputs uniformly from $[0, 1]$ and define the target as

$$y = \sin(3\pi x) + 0.5 \cos(7\pi x) e^{-2x} + 0.3 x^2 + \varepsilon,$$

where $\varepsilon \sim \mathcal{N}(0, 0.04)$. This produces a smooth nonlinear target with varying local curvature.

For classification, we again sample $n = 2500$ inputs uniformly from $[0, 1]$ and draw labels from a Bernoulli distribution with class probability

$$p(x) = \text{clip}(\sigma(25(x - 0.33)) - \sigma(25(x - 0.72)) + 0.04,\ 0.04,\ 0.96),$$

where $\sigma(\cdot)$ denotes the logistic sigmoid. This creates a two-boundary band structure with sharp but noisy transitions.

Encodings. Both datasets are encoded with the same budget of $m = 10$ dimensions. For PLE, we use uniform bin boundaries on $[0, 1]$. For the spline representation, we use a clamped uniform cubic B-spline basis on $[0, 1]$. This keeps the basis budget fixed across the two encodings.

Predictive models. For the regression task, we fit a Ridge model on top of each encoding. For the classification task, we fit a logistic regression model on top of each encoding. The aim is to keep the downstream predictor simple so that the comparison mainly reflects the structure induced by the encoding.

Evaluation. For regression, we plot the fitted curve together with the noiseless target function and report NRMSE, computed against the noiseless target on a dense evaluation grid over $[0, 1]$. For classification, we plot the fitted class-probability curve together with the true probability function and report both AUC and Brier score. These figures are intended as qualitative illustrations rather than as a benchmark.

J Ablation Study Setup

This appendix gives the setup for the ablation study in Section **??**. We use a synthetic regression dataset to isolate the effect of numerical encoding resolution under a controlled feature and target relationship. The dataset contains one informative feature and one nuisance feature. The informative feature $x_0 \in [0, 1]$ is sampled from the mixture distribution

$$x_0 \sim \begin{cases} \text{Beta}(2, 8), & \text{with probability } 0.70, \\ \text{Beta}(8, 2), & \text{with probability } 0.20, \\ \text{Uniform}(0, 1), & \text{with probability } 0.10, \end{cases}$$

which gives a non-uniform marginal distribution over the input domain. The nuisance feature is defined as

$$x_1 = 0.6 \, x_0 + 0.4 \, U(0, 1),$$

where $U(0, 1)$ denotes a uniform random variable on $[0, 1]$.

Figure 8: Synthetic regression dataset used in the ablation study. Scatter plot of the informative feature x_0 against the target variable y, illustrating the heterogeneous structure induced by the synthetic target function.

The target depends only on x_0 through

$$f(x_0) = 0.8 \sin(2\pi x_0) + 1.5\,\mathbf{1}[x_0 > 0.55] + 2.0 \exp\left(-\frac{(x_0 - 0.78)^2}{2(0.03)^2}\right),$$

and the final response is

$$y = f(x_0) + \varepsilon, \qquad \varepsilon \sim \mathcal{N}(0, 0.10^2).$$

This construction combines smooth nonlinear variation, a threshold effect, and a narrow localized peak. Figure 8 shows the relationship between x_0 and y. We study sensitivity to the number of bins or basis functions on this synthetic regression task by varying the encoding resolution $m \in \{5, 10, 15, 20, 25, 30, 35, 40, 45, 50\}$, while keeping all other hyperparameters fixed. This isolates the effect of encoding capacity from other architectural choices. Test NRMSE ($\downarrow$), averaged over 5 random seeds and reported with standard deviation, is given in Table 13.

J.1   Knot Relocation During Training

To complement the ablation on encoding resolution, we include a small qualitative experiment on the same synthetic regression task to visualize how learnable knot locations evolve during training. Using the same MLP setup as in the main experiments, we fix the numerical encoding size to $m = 10$ basis functions per feature and optimize knot parameters jointly with the backbone. This gives six learnable internal knots per feature according to Appendix C.1. Unlike the encoding-resolution ablation, which reports results averaged over 5 random seeds, this experiment is shown for a single seed only and is intended as an illustration of knot movement during training rather than as a performance comparison.

Figure 9 shows the BS-Grad-U knot trajectories for the informative feature x_0 under uniform initialization and different knot learning rates. The learned knot movement depends on several factors, including the input distribution, the target structure, and the gradients induced during optimization. At the smallest learning rates, the knots move only slightly, whereas larger learning rates lead to more visible relocation during training. Across all settings shown, however, the trajectories remain well behaved and ordered, which is consistent with stable optimization under our parameterization. This figure should therefore be read as a qualitative illustration that knot relocation can remain stable during training, rather than as a complete analysis of the factors governing knot dynamics.

Backbone	Method	AB	CA	CPU	DI	HS	PA	WI	FW	H8	PR	PU	SG	SU
MLP	STD	0.4610 ± 0.020	0.2751 ± 0.021	0.0456 ± 0.007	0.0581 ± 0.006	0.1638 ± 0.008	0.6641 ± 0.018	0.7010 ± 0.015	0.3536 ± 0.009	0.3754 ± 0.019	0.5976 ± 0.016	0.2126 ± 0.015	0.0583 ± 0.004	0.2740 ± 0.082
	MinMax	0.4837 ± 0.013	0.3223 ± 0.016	0.0569 ± 0.006	0.0644 ± 0.003	0.2177 ± 0.012	0.7792 ± 0.029	0.7105 ± 0.012	0.4085 ± 0.023	0.4292 ± 0.011	0.6411 ± 0.017	0.2254 ± 0.015	0.0826 ± 0.009	0.3525 ± 0.070
	PLE	0.4676 ± 0.017	0.2650 ± 0.020	0.0297 ± 0.005	0.0601 ± 0.004	0.1470 ± 0.014	0.5098 ± 0.024	0.6685 ± 0.018	0.3413 ± 0.013	0.3624 ± 0.029	0.5599 ± 0.029	0.2100 ± 0.018	0.0373 ± 0.006	0.2611 ± 0.076
	BS-U	0.4431 ± 0.015	0.2595 ± 0.018	0.0287 ± 0.004	0.0612 ± 0.003	0.1396 ± 0.015	0.5489 ± 0.015	0.6606 ± 0.011	0.3455 ± 0.009	0.3611 ± 0.023	0.5645 ± 0.013	0.2047 ± 0.018	0.0637 ± 0.018	0.2624 ± 0.077
	BS-Q	0.4438 ± 0.015	0.2569 ± 0.019	0.0290 ± 0.004	0.0627 ± 0.003	0.1342 ± 0.013	0.5415 ± 0.015	0.6548 ± 0.015	0.3422 ± 0.008	0.3536 ± 0.021	0.5407 ± 0.021	0.2090 ± 0.018	0.0655 ± 0.018	0.2604 ± 0.087
	BS-CART	0.4456 ± 0.019	0.2602 ± 0.018	0.0285 ± 0.004	0.0610 ± 0.003	0.1364 ± 0.015	0.5228 ± 0.018	0.6570 ± 0.015	0.3404 ± 0.009	0.3515 ± 0.026	0.5521 ± 0.017	0.2022 ± 0.018	0.0591 ± 0.016	0.2637 ± 0.100
	BS-LGBM	0.4457 ± 0.014	0.2558 ± 0.018	0.0283 ± 0.004	0.0610 ± 0.004	0.1347 ± 0.016	0.5270 ± 0.011	0.6575 ± 0.013	0.3392 ± 0.009	0.3510 ± 0.024	0.5566 ± 0.013	0.2045 ± 0.019	0.0644 ± 0.018	0.2592 ± 0.096
	BS-Grad-U	**0.4372** ± 0.019	**0.2190** ± 0.017	**0.0273** ± 0.004	**0.0244** ± 0.001	**0.1033** ± 0.010	0.3187 ± 0.013	**0.6075** ± 0.014	0.3888 ± 0.009	0.3182 ± 0.030	0.4306 ± 0.013	**0.1939** ± 0.022	**0.0112** ± 0.002	**0.2079** ± 0.076
	IS-U	0.4449 ± 0.018	0.2618 ± 0.020	0.0296 ± 0.005	0.0614 ± 0.004	0.1498 ± 0.020	0.5726 ± 0.012	0.6671 ± 0.017	0.3464 ± 0.011	0.3616 ± 0.021	0.5791 ± 0.012	0.2105 ± 0.017	0.0511 ± 0.017	0.2610 ± 0.084
	IS-Q	0.4477 ± 0.022	0.2603 ± 0.018	0.0320 ± 0.004	0.0623 ± 0.004	0.1416 ± 0.017	0.5756 ± 0.015	0.6640 ± 0.015	0.3438 ± 0.007	0.3572 ± 0.023	0.5722 ± 0.012	0.2118 ± 0.017	0.0579 ± 0.016	0.2614 ± 0.086
	IS-CART	0.4434 ± 0.016	0.2635 ± 0.024	0.0299 ± 0.004	0.0612 ± 0.004	0.1479 ± 0.021	0.5687 ± 0.012	0.6658 ± 0.015	0.3424 ± 0.009	0.3534 ± 0.023	0.5741 ± 0.012	0.2078 ± 0.018	0.0564 ± 0.015	0.2590 ± 0.083
	IS-LGBM	0.4474 ± 0.022	0.2608 ± 0.021	0.0288 ± 0.005	0.0612 ± 0.004	0.1479 ± 0.021	0.5681 ± 0.011	0.6667 ± 0.018	0.3416 ± 0.009	0.3546 ± 0.023	0.5766 ± 0.011	0.2079 ± 0.018	0.0566 ± 0.014	0.2627 ± 0.086
	IS-Grad-U	0.4387 ± 0.018	0.2352 ± 0.019	0.0288 ± 0.004	0.0253 ± 0.001	0.1087 ± 0.013	0.3639 ± 0.010	0.6318 ± 0.013	0.3429 ± 0.009	0.3196 ± 0.027	0.4743 ± 0.014	0.1965 ± 0.021	0.0123 ± 0.002	0.2235 ± 0.076
	MS-Grad-U	0.4405 ± 0.022	0.2228 ± 0.013	0.0304 ± 0.004	0.0252 ± 0.002	0.1243 ± 0.018	0.4048 ± 0.010	0.6110 ± 0.018	0.3438 ± 0.009	0.3352 ± 0.029	**0.4126** ± 0.011	0.1993 ± 0.022	0.0257 ± 0.004	0.2324 ± 0.068
RESNET	STD	0.4277 ± 0.027	0.2545 ± 0.017	0.0329 ± 0.007	0.0339 ± 0.012	0.1336 ± 0.015	0.4344 ± 0.023	0.6484 ± 0.011	0.3605 ± 0.011	0.3450 ± 0.029	0.5103 ± 0.013	0.1983 ± 0.019	0.0296 ± 0.004	0.2449 ± 0.097
	MinMax	0.4291 ± 0.025	0.2805 ± 0.025	0.0326 ± 0.005	0.0362 ± 0.007	0.1321 ± 0.014	0.4345 ± 0.018	0.6486 ± 0.013	0.3644 ± 0.013	0.3464 ± 0.030	0.5301 ± 0.022	0.1988 ± 0.020	0.0383 ± 0.009	0.2313 ± 0.077
	PLE	0.4548 ± 0.018	0.2385 ± 0.013	0.0266 ± 0.004	0.0271 ± 0.004	0.1118 ± 0.009	0.3018 ± 0.034	0.6180 ± 0.019	0.3388 ± 0.015	0.3172 ± 0.032	0.4075 ± 0.012	0.1992 ± 0.022	0.0190 ± 0.004	0.2318 ± 0.081
	BS-U	0.4292 ± 0.017	0.2248 ± 0.016	0.0262 ± 0.004	0.0301 ± 0.006	0.1091 ± 0.014	0.2500 ± 0.028	0.6149 ± 0.013	0.3460 ± 0.012	0.3185 ± 0.022	0.4198 ± 0.008	0.1974 ± 0.019	0.0181 ± 0.005	**0.17785** ± 0.098
	BS-Q	0.4312 ± 0.016	**0.2129** ± 0.013	**0.0261** ± 0.003	0.0270 ± 0.003	**0.1072** ± 0.016	0.2332 ± 0.015	0.6160 ± 0.016	0.3326 ± 0.006	0.3105 ± 0.031	0.4036 ± 0.019	0.1975 ± 0.018	0.0191 ± 0.004	0.1856 ± 0.113
	BS-CART	0.4327 ± 0.014	0.2240 ± 0.012	0.0267 ± 0.004	0.0280 ± 0.002	0.1078 ± 0.013	0.2236 ± 0.015	0.6183 ± 0.010	0.3330 ± 0.007	0.3114 ± 0.023	0.4097 ± 0.011	**0.1955** ± 0.020	0.0194 ± 0.003	0.1874 ± 0.088
	BS-LGBM	0.4323 ± 0.015	0.2322 ± 0.019	**0.0261** ± 0.003	0.0273 ± 0.003	0.1091 ± 0.013	0.2369 ± 0.014	0.6199 ± 0.004	**0.3297** ± 0.009	**0.3054** ± 0.026	0.4313 ± 0.019	0.1990 ± 0.018	0.0166 ± 0.002	0.1985 ± 0.109
	BS-Grad-U	0.4401 ± 0.021	0.2281 ± 0.036	0.0372 ± 0.006	0.0229 ± 0.001	0.1362 ± 0.022	**0.1569** ± 0.008	**0.6114** ± 0.013	0.3491 ± 0.008	0.3340 ± 0.038	**0.3362** ± 0.010	0.2065 ± 0.020	0.0176 ± 0.006	0.2378 ± 0.092
	IS-U	**0.4257** ± 0.021	0.2297 ± 0.016	0.0261 ± 0.004	0.0280 ± 0.002	0.1155 ± 0.017	0.2842 ± 0.019	0.6250 ± 0.015	0.3447 ± 0.010	0.3138 ± 0.028	0.4472 ± 0.021	0.1965 ± 0.019	0.0245 ± 0.004	0.1914 ± 0.101
	IS-Q	0.4294 ± 0.014	0.2379 ± 0.017	0.0264 ± 0.004	0.0271 ± 0.002	0.1120 ± 0.018	0.2724 ± 0.035	0.6257 ± 0.014	0.3363 ± 0.010	0.3112 ± 0.033	0.4436 ± 0.016	0.1983 ± 0.016	0.0199 ± 0.002	0.1926 ± 0.091
	IS-CART	0.4288 ± 0.017	0.2314 ± 0.011	0.0262 ± 0.004	0.0264 ± 0.002	0.1111 ± 0.016	0.2690 ± 0.031	0.6179 ± 0.023	0.3353 ± 0.011	0.3075 ± 0.028	0.4416 ± 0.017	0.1957 ± 0.017	0.0223 ± 0.004	0.2118 ± 0.084
	IS-LGBM	0.4293 ± 0.019	0.2345 ± 0.017	**0.0261** ± 0.003	0.0279 ± 0.003	0.1086 ± 0.013	0.2660 ± 0.027	0.6160 ± 0.011	0.3343 ± 0.010	0.3126 ± 0.027	0.4520 ± 0.023	0.1971 ± 0.018	0.0211 ± 0.005	0.2051 ± 0.091
	IS-Grad-U	0.4298 ± 0.017	0.2270 ± 0.022	0.0312 ± 0.006	0.0235 ± 0.002	0.1304 ± 0.020	0.1993 ± 0.019	0.6121 ± 0.007	0.3762 ± 0.029	0.3335 ± 0.036	0.3654 ± 0.023	0.2046 ± 0.026	**0.0162** ± 0.006	0.2203 ± 0.092
	MS-Grad-U	0.4464 ± 0.023	0.2215 ± 0.017	0.0338 ± 0.007	**0.0220** ± 0.001	0.1307 ± 0.017	0.2999 ± 0.027	0.6222 ± 0.006	0.3565 ± 0.013	0.3427 ± 0.041	0.3427 ± 0.009	0.2081 ± 0.019	0.0279 ± 0.015	0.2375 ± 0.079
FTT	STD	0.4609 ± 0.028	**0.2290** ± 0.010	**0.0254** ± 0.003	0.0201 ± 0.002	**0.1219** ± 0.013	0.1318 ± 0.024	0.6727 ± 0.043	0.3396 ± 0.013	**0.3248** ± 0.030	0.3858 ± 0.016	0.2017 ± 0.029	**0.0097** ± 0.002	0.2805 ± 0.065
	MinMax	0.4565 ± 0.040	0.2496 ± 0.018	0.0310 ± 0.005	0.0204 ± 0.001	0.1276 ± 0.019	0.3347 ± 0.088	0.6724 ± 0.019	0.3485 ± 0.010	0.3531 ± 0.026	0.4333 ± 0.031	0.2066 ± 0.022	0.0101 ± 0.006	**0.2373** ± 0.078
	PLE	0.4871 ± 0.036	0.2395 ± 0.019	0.0330 ± 0.008	0.0198 ± 0.001	0.1409 ± 0.015	0.3246 ± 0.047	**0.6520** ± 0.021	0.3409 ± 0.015	0.3547 ± 0.033	0.4144 ± 0.033	0.2117 ± 0.035	0.0160 ± 0.007	0.2580 ± 0.085
	BS-U	0.4683 ± 0.027	0.2477 ± 0.020	0.0381 ± 0.010	0.0208 ± 0.003	0.1324 ± 0.023	0.1893 ± 0.097	0.6582 ± 0.040	0.3414 ± 0.009	0.3553 ± 0.030	0.4045 ± 0.028	0.2050 ± 0.035	0.0252 ± 0.004	0.2438 ± 0.092
	BS-Q	0.4633 ± 0.031	0.2512 ± 0.039	0.0269 ± 0.005	0.0197 ± 0.001	0.1339 ± 0.022	**0.0644** ± 0.059	0.6625 ± 0.039	0.3424 ± 0.014	0.3347 ± 0.039	0.4020 ± 0.019	0.2033 ± 0.023	0.0338 ± 0.006	0.2483 ± 0.080
	BS-CART	0.4717 ± 0.046	0.2428 ± 0.022	0.0301 ± 0.009	0.0197 ± 0.002	0.1368 ± 0.019	0.1357 ± 0.155	0.6666 ± 0.021	0.3398 ± 0.009	0.3334 ± 0.023	0.3863 ± 0.013	0.2065 ± 0.027	0.0395 ± 0.012	0.2407 ± 0.081
	BS-LGBM	0.4767 ± 0.046	0.2436 ± 0.017	0.0285 ± 0.004	**0.0196** ± 0.001	0.1383 ± 0.019	0.0829 ± 0.076	0.6582 ± 0.030	**0.3312** ± 0.009	0.3343 ± 0.033	**0.3843** ± 0.020	0.2046 ± 0.025	0.0339 ± 0.012	0.2492 ± 0.097
	BS-Grad-U	0.4772 ± 0.047	0.2416 ± 0.036	0.0386 ± 0.003	0.0219 ± 0.001	0.1502 ± 0.025	0.1813 ± 0.177	0.6717 ± 0.033	0.3412 ± 0.012	0.3563 ± 0.052	0.3985 ± 0.019	0.2017 ± 0.029	0.0516 ± 0.035	0.2479 ± 0.086
	IS-U	0.4686 ± 0.021	0.2431 ± 0.022	0.0469 ± 0.011	0.0205 ± 0.003	0.1457 ± 0.036	0.0723 ± 0.040	0.6546 ± 0.021	0.3371 ± 0.008	0.3439 ± 0.027	0.3915 ± 0.018	0.2081 ± 0.019	0.0126 ± 0.004	0.2450 ± 0.072
	IS-Q	0.4669 ± 0.019	0.2315 ± 0.016	0.0351 ± 0.007	0.0201 ± 0.002	0.1460 ± 0.028	0.0942 ± 0.097	0.6656 ± 0.024	0.3344 ± 0.011	0.3442 ± 0.030	0.4017 ± 0.031	0.1989 ± 0.023	0.0177 ± 0.005	0.2472 ± 0.080
	IS-CART	0.4671 ± 0.024	0.2443 ± 0.024	0.0430 ± 0.017	0.0202 ± 0.001	0.1478 ± 0.013	0.2028 ± 0.235	0.6679 ± 0.031	0.3324 ± 0.007	0.3362 ± 0.026	0.3904 ± 0.013	0.2048 ± 0.033	0.0139 ± 0.005	0.2539 ± 0.076
	IS-LGBM	**0.4551** ± 0.017	0.2551 ± 0.027	0.0335 ± 0.009	0.0202 ± 0.002	0.1437 ± 0.023	0.1607 ± 0.171	0.6627 ± 0.007	0.3322 ± 0.008	0.3320 ± 0.025	0.3879 ± 0.013	0.2039 ± 0.029	0.0171 ± 0.013	0.2568 ± 0.064
	IS-Grad-U	0.4988 ± 0.036	0.2749 ± 0.080	0.0462 ± 0.010	0.0222 ± 0.003	0.1652 ± 0.027	0.1585 ± 0.084	0.6799 ± 0.032	0.3451 ± 0.012	0.3672 ± 0.047	0.4109 ± 0.014	**0.1976** ± 0.021	0.0192 ± 0.007	0.2414 ± 0.088
	MS-Grad-U	0.5020 ± 0.027	0.2538 ± 0.026	0.0286 ± 0.004	0.0219 ± 0.002	0.1374 ± 0.008	0.3694 ± 0.176	0.6739 ± 0.041	0.3526 ± 0.018	0.3935 ± 0.025	0.4171 ± 0.023	0.2025 ± 0.020	0.2494 ± 0.135	0.2384 ± 0.080

Table 7: Regression results for $m = 7$. Mean NRMSE ($\downarrow$) ± standard deviation over 5-fold cross-validation. Dataset and preprocessing abbreviations are given in Tables 3 and 2 respectively. Bold indicates the lowest NRMSE for each dataset within each backbone.

Backbone	Method	AB	CA	CPU	DI	HS	PA	WI	FW	H8	PR	PU	SG	SU
MLP	STD	0.4610 ± 0.020	0.2751 ± 0.021	0.0456 ± 0.007	0.0581 ± 0.006	0.1638 ± 0.008	0.6641 ± 0.018	0.7010 ± 0.015	0.3536 ± 0.009	0.3754 ± 0.019	0.5976 ± 0.016	0.2126 ± 0.015	0.0583 ± 0.004	0.2740 ± 0.082
	MinMax	0.4837 ± 0.013	0.3223 ± 0.016	0.0569 ± 0.006	0.0644 ± 0.003	0.2177 ± 0.012	0.7792 ± 0.029	0.7105 ± 0.012	0.4085 ± 0.023	0.4292 ± 0.011	0.6411 ± 0.017	0.2254 ± 0.017	0.0826 ± 0.009	0.3525 ± 0.070
	PLE	0.4629 ± 0.011	0.2350 ± 0.012	0.0286 ± 0.004	0.0598 ± 0.004	0.1412 ± 0.018	0.4120 ± 0.014	0.6584 ± 0.017	0.3307 ± 0.008	0.3556 ± 0.025	0.5285 ± 0.013	0.2092 ± 0.017	0.0305 ± 0.007	0.2629 ± 0.082
	BS-U	0.4509 ± 0.014	0.2354 ± 0.013	0.0272 ± 0.005	0.0594 ± 0.005	0.1297 ± 0.011	0.4039 ± 0.016	0.6492 ± 0.013	0.3458 ± 0.008	0.3539 ± 0.023	0.5136 ± 0.016	0.2055 ± 0.019	0.0624 ± 0.019	0.2522 ± 0.094
	BS-Q	0.4588 ± 0.019	0.2273 ± 0.018	0.0268 ± 0.004	0.0621 ± 0.004	0.1289 ± 0.015	0.3585 ± 0.020	0.6627 ± 0.016	**0.3304** ± 0.007	0.3445 ± 0.027	0.4847 ± 0.011	0.2039 ± 0.018	0.0819 ± 0.016	0.2522 ± 0.089
	BS-CART	0.4566 ± 0.014	0.2360 ± 0.017	0.0273 ± 0.004	0.0604 ± 0.005	0.1310 ± 0.014	0.3738 ± 0.008	0.6493 ± 0.014	0.3312 ± 0.008	0.3493 ± 0.025	0.4982 ± 0.013	0.2079 ± 0.020	0.0835 ± 0.016	0.2545 ± 0.097
	BS-LGBM	0.4570 ± 0.020	0.2255 ± 0.016	0.0275 ± 0.004	0.0629 ± 0.004	0.1308 ± 0.015	0.3826 ± 0.025	0.6615 ± 0.016	0.3321 ± 0.009	0.3495 ± 0.019	0.4907 ± 0.012	0.2025 ± 0.018	0.0794 ± 0.018	0.2507 ± 0.089
	BS-Grad-U	0.4414 ± 0.025	**0.1971** ± 0.008	**0.0246** ± 0.002	**0.0226** ± 0.001	**0.1020** ± 0.008	**0.2099** ± 0.012	**0.5910** ± 0.027	0.3389 ± 0.007	0.3294 ± 0.032	0.3772 ± 0.012	0.1975 ± 0.023	0.0115 ± 0.002	**0.1757** ± 0.105
	IS-U	0.4436 ± 0.017	0.2446 ± 0.017	0.0279 ± 0.005	0.0605 ± 0.004	0.1435 ± 0.024	0.4950 ± 0.011	0.6570 ± 0.013	0.3441 ± 0.009	0.3547 ± 0.028	0.5458 ± 0.012	0.2063 ± 0.019	0.0436 ± 0.004	0.2646 ± 0.083
	IS-Q	0.4440 ± 0.018	0.2366 ± 0.017	0.0281 ± 0.005	0.0626 ± 0.004	0.1389 ± 0.018	0.4525 ± 0.012	0.6553 ± 0.012	0.3335 ± 0.009	0.3531 ± 0.026	0.5211 ± 0.012	0.2073 ± 0.015	0.0443 ± 0.009	0.2676 ± 0.084
	IS-CART	0.4485 ± 0.016	0.2456 ± 0.014	0.0297 ± 0.004	0.0602 ± 0.004	0.1394 ± 0.021	0.4657 ± 0.011	0.6494 ± 0.021	0.3327 ± 0.008	0.3510 ± 0.027	0.5303 ± 0.012	0.2085 ± 0.019	0.0444 ± 0.009	0.2579 ± 0.086
	IS-LGBM	0.4461 ± 0.016	0.2345 ± 0.016	0.0297 ± 0.004	0.0638 ± 0.004	0.1364 ± 0.016	0.4660 ± 0.022	0.6558 ± 0.014	0.3334 ± 0.010	0.3518 ± 0.025	0.5293 ± 0.017	0.2074 ± 0.016	0.0441 ± 0.009	0.2676 ± 0.086
	IS-Grad-U	**0.4364** ± 0.013	0.2105 ± 0.014	0.0256 ± 0.004	0.0228 ± 0.001	0.1086 ± 0.011	0.2836 ± 0.020	0.6042 ± 0.013	0.3397 ± 0.009	**0.3136** ± 0.029	0.4171 ± 0.013	**0.1967** ± 0.022	**0.0107** ± 0.002	0.2203 ± 0.078
	MS-Grad-U	0.4413 ± 0.048	0.2065 ± 0.004	0.0277 ± 0.003	0.0248 ± 0.001	0.1174 ± 0.009	0.2448 ± 0.007	0.5988 ± 0.012	0.3356 ± 0.009	0.3329 ± 0.032	**0.3572** ± 0.012	0.2036 ± 0.026	0.0207 ± 0.004	0.1984 ± 0.083
RESNET	STD	**0.4277** ± 0.027	0.2545 ± 0.017	0.0329 ± 0.007	0.0339 ± 0.012	0.1336 ± 0.015	0.4344 ± 0.023	0.6484 ± 0.011	0.3605 ± 0.011	0.3450 ± 0.029	0.5103 ± 0.013	0.1983 ± 0.019	0.0296 ± 0.004	0.2449 ± 0.097
	MinMax	0.4291 ± 0.025	0.2805 ± 0.025	0.0326 ± 0.005	0.0362 ± 0.007	0.1321 ± 0.018	0.4345 ± 0.018	0.6486 ± 0.013	0.3644 ± 0.013	0.3464 ± 0.030	0.5301 ± 0.022	0.1988 ± 0.020	0.0383 ± 0.009	0.2313 ± 0.077
	PLE	0.4558 ± 0.018	0.2003 ± 0.015	0.0260 ± 0.004	0.0270 ± 0.003	0.1067 ± 0.011	0.2079 ± 0.009	0.6091 ± 0.013	0.3288 ± 0.011	0.3168 ± 0.034	0.3758 ± 0.020	0.2007 ± 0.021	0.0213 ± 0.006	0.2258 ± 0.083
	BS-U	0.4460 ± 0.012	0.2125 ± 0.013	0.0256 ± 0.004	0.0264 ± 0.002	0.1129 ± 0.013	0.1563 ± 0.007	0.6080 ± 0.016	0.3419 ± 0.010	0.3242 ± 0.030	0.3800 ± 0.014	0.2020 ± 0.021	0.0164 ± 0.003	0.1810 ± 0.090
	BS-Q	0.4532 ± 0.011	0.2009 ± 0.013	0.0252 ± 0.004	0.0274 ± 0.003	0.1082 ± 0.012	0.1411 ± 0.014	0.6073 ± 0.017	0.3290 ± 0.011	0.3174 ± 0.030	0.3543 ± 0.014	0.2012 ± 0.021	0.0179 ± 0.002	0.1946 ± 0.107
	BS-CART	0.4522 ± 0.010	0.2075 ± 0.011	0.0258 ± 0.003	0.0291 ± 0.006	0.1138 ± 0.014	0.1539 ± 0.030	0.6101 ± 0.019	**0.3259** ± 0.007	0.3159 ± 0.025	0.3716 ± 0.016	0.2003 ± 0.022	0.0192 ± 0.003	0.1983 ± 0.110
	BS-LGBM	0.4512 ± 0.018	**0.1988** ± 0.017	0.0261 ± 0.003	0.0260 ± 0.003	0.1094 ± 0.011	0.1691 ± 0.015	0.6171 ± 0.023	0.3304 ± 0.010	0.3243 ± 0.026	0.3637 ± 0.009	0.2052 ± 0.020	0.0174 ± 0.003	0.1873 ± 0.083
	BS-Grad-U	0.4558 ± 0.036	0.2124 ± 0.017	0.0360 ± 0.007	**0.0204** ± 0.002	0.1269 ± 0.015	**0.1152** ± 0.012	**0.5761** ± 0.026	0.3471 ± 0.007	0.3477 ± 0.032	0.3336 ± 0.009	0.2144 ± 0.021	**0.0158** ± 0.004	0.2081 ± 0.059
	IS-U	0.4358 ± 0.018	0.2204 ± 0.014	0.0257 ± 0.003	0.0281 ± 0.002	0.1090 ± 0.017	0.1923 ± 0.013	0.6140 ± 0.015	0.3399 ± 0.009	0.3153 ± 0.028	0.4008 ± 0.014	0.1972 ± 0.020	0.0235 ± 0.003	0.1780 ± 0.090
	IS-Q	0.4372 ± 0.015	0.2102 ± 0.016	0.0252 ± 0.003	0.0258 ± 0.003	**0.1064** ± 0.016	0.2093 ± 0.025	0.6166 ± 0.013	0.3300 ± 0.007	**0.3098** ± 0.029	0.3856 ± 0.024	0.1987 ± 0.018	0.0195 ± 0.003	**0.1746** ± 0.084
	IS-CART	0.4414 ± 0.018	0.2136 ± 0.014	**0.0249** ± 0.004	0.0261 ± 0.001	0.1094 ± 0.014	0.2126 ± 0.033	0.6131 ± 0.023	0.3293 ± 0.009	0.3134 ± 0.023	0.3844 ± 0.019	**0.1965** ± 0.022	0.0191 ± 0.001	0.2000 ± 0.074
	IS-LGBM	0.4428 ± 0.023	0.2121 ± 0.022	0.0252 ± 0.004	0.0263 ± 0.003	0.1067 ± 0.014	0.1762 ± 0.010	0.6123 ± 0.017	0.3299 ± 0.009	0.3135 ± 0.032	0.3930 ± 0.032	0.2001 ± 0.017	0.0175 ± 0.002	0.1810 ± 0.084
	IS-Grad-U	0.4411 ± 0.016	0.2282 ± 0.018	0.0349 ± 0.005	0.0220 ± 0.002	0.1217 ± 0.008	0.1472 ± 0.029	0.6031 ± 0.007	0.3583 ± 0.007	0.3284 ± 0.023	0.3330 ± 0.015	0.2006 ± 0.020	0.0207 ± 0.009	0.1863 ± 0.035
	MS-Grad-U	0.4580 ± 0.048	0.2144 ± 0.013	0.0379 ± 0.007	0.0212 ± 0.001	0.1377 ± 0.017	0.1846 ± 0.010	0.6225 ± 0.032	0.3476 ± 0.008	0.3574 ± 0.045	**0.3320** ± 0.015	0.2057 ± 0.023	0.0298 ± 0.014	0.2473 ± 0.095
FTT	STD	0.4609 ± 0.028	0.2290 ± 0.010	**0.0254** ± 0.003	**0.0201** ± 0.002	**0.1219** ± 0.013	0.1318 ± 0.024	0.6727 ± 0.043	0.3396 ± 0.013	**0.3248** ± 0.030	**0.3858** ± 0.016	**0.2017** ± 0.029	**0.0097** ± 0.002	0.2805 ± 0.065
	MinMax	**0.4565** ± 0.040	0.2496 ± 0.018	0.0310 ± 0.005	0.0204 ± 0.005	0.1276 ± 0.019	0.3347 ± 0.088	0.6724 ± 0.038	0.3485 ± 0.010	0.3531 ± 0.026	0.4333 ± 0.031	0.2066 ± 0.022	0.0101 ± 0.006	0.2373 ± 0.078
	PLE	0.4957 ± 0.039	**0.2138** ± 0.018	0.0311 ± 0.007	0.0224 ± 0.001	0.1339 ± 0.015	0.0890 ± 0.058	0.6491 ± 0.023	0.3346 ± 0.015	0.3512 ± 0.025	0.4163 ± 0.035	0.2088 ± 0.021	0.0163 ± 0.006	0.2558 ± 0.085
	BS-U	0.4940 ± 0.017	0.2699 ± 0.020	0.0335 ± 0.007	0.0228 ± 0.002	0.1466 ± 0.018	0.2731 ± 0.271	0.6782 ± 0.019	0.3443 ± 0.011	0.3696 ± 0.033	0.4095 ± 0.022	0.2073 ± 0.025	0.0299 ± 0.013	0.2395 ± 0.108
	BS-Q	0.5140 ± 0.017	0.2426 ± 0.021	0.0356 ± 0.005	0.0209 ± 0.002	0.1458 ± 0.025	0.1949 ± 0.230	0.6773 ± 0.011	0.3434 ± 0.011	0.3671 ± 0.022	0.3979 ± 0.021	0.2116 ± 0.026	0.0685 ± 0.025	0.2468 ± 0.073
	BS-CART	0.4872 ± 0.031	0.2530 ± 0.022	0.0309 ± 0.005	0.0232 ± 0.002	0.1360 ± 0.011	0.4762 ± 0.096	0.6667 ± 0.024	0.3392 ± 0.009	0.3693 ± 0.031	0.3950 ± 0.021	0.2109 ± 0.030	0.0917 ± 0.077	0.2534 ± 0.075
	BS-LGBM	0.5121 ± 0.043	0.2290 ± 0.020	0.0371 ± 0.009	0.0208 ± 0.002	0.1514 ± 0.030	0.3669 ± 0.191	0.6815 ± 0.028	0.3422 ± 0.006	0.3669 ± 0.015	0.4053 ± 0.009	0.2102 ± 0.033	0.0642 ± 0.006	0.2360 ± 0.097
	BS-Grad-U	0.5157 ± 0.030	0.2291 ± 0.033	0.0438 ± 0.006	0.0220 ± 0.001	0.1472 ± 0.036	0.1313 ± 0.061	0.6798 ± 0.027	0.3384 ± 0.006	0.3924 ± 0.029	0.4448 ± 0.043	0.2039 ± 0.030	0.0657 ± 0.028	0.2810 ± 0.063
	IS-U	0.4766 ± 0.033	0.2426 ± 0.025	0.0321 ± 0.004	0.0217 ± 0.001	0.1448 ± 0.008	0.1122 ± 0.196	0.6541 ± 0.017	0.3366 ± 0.010	0.3669 ± 0.019	0.3957 ± 0.011	0.2058 ± 0.025	0.0175 ± 0.003	0.2735 ± 0.071
	IS-Q	0.4732 ± 0.021	0.2287 ± 0.008	0.0312 ± 0.009	0.0202 ± 0.001	0.1292 ± 0.023	0.0771 ± 0.120	0.6459 ± 0.018	0.3393 ± 0.003	0.3366 ± 0.030	0.3958 ± 0.017	0.2044 ± 0.029	0.0156 ± 0.005	0.2586 ± 0.094
	IS-CART	0.4607 ± 0.028	0.2352 ± 0.016	0.0342 ± 0.012	0.0214 ± 0.001	0.1345 ± 0.016	0.1381 ± 0.164	**0.6452** ± 0.037	**0.3521** ± 0.009	0.3399 ± 0.028	0.3959 ± 0.016	0.2057 ± 0.026	0.0164 ± 0.003	0.2463 ± 0.078
	IS-LGBM	0.4632 ± 0.031	0.2145 ± 0.018	0.0337 ± 0.012	0.0221 ± 0.002	0.1334 ± 0.016	**0.0400** ± 0.029	0.6481 ± 0.028	0.3362 ± 0.011	0.3365 ± 0.025	0.4008 ± 0.011	**0.2005** ± 0.028	0.0153 ± 0.007	0.2383 ± 0.079
	IS-Grad-U	0.5169 ± 0.065	0.2555 ± 0.016	0.0468 ± 0.016	0.0244 ± 0.003	0.1734 ± 0.036	0.0719 ± 0.006	0.6826 ± 0.043	0.3463 ± 0.014	0.3809 ± 0.067	0.4100 ± 0.011	0.2090 ± 0.025	0.0254 ± 0.009	**0.2270** ± 0.099
	MS-Grad-U	0.5012 ± 0.069	0.2786 ± 0.072	0.0347 ± 0.004	0.0270 ± 0.004	0.1571 ± 0.017	0.2290 ± 0.175	0.6698 ± 0.030	0.3486 ± 0.020	0.3892 ± 0.039	0.4254 ± 0.018	0.2067 ± 0.020	0.1353 ± 0.062	0.2320 ± 0.082

Table 8: Regression results for $m = 15$. Mean NRMSE ($\downarrow$) ± standard deviation over 5-fold cross-validation. Dataset and preprocessing abbreviations are given in Tables 3 and 2 respectively. Bold indicates the lowest NRMSE for each dataset within each backbone.

Backbone	Method	AB	CA	CPU	DI	HS	PA	WI	FW	H8	PR	PU	SG	SU
MLP	STD	0.4610 ± 0.020	0.2751 ± 0.021	0.0456 ± 0.007	0.0581 ± 0.006	0.1638 ± 0.008	0.6641 ± 0.018	0.7010 ± 0.015	0.3536 ± 0.009	0.3754 ± 0.019	0.5976 ± 0.016	0.2126 ± 0.015	0.0583 ± 0.004	0.2740 ± 0.082
	MinMax	0.4837 ± 0.013	0.3223 ± 0.013	0.0569 ± 0.006	0.0644 ± 0.003	0.2177 ± 0.012	0.7792 ± 0.029	0.7105 ± 0.012	0.4085 ± 0.023	0.4292 ± 0.011	0.6411 ± 0.017	0.2254 ± 0.015	0.0826 ± 0.009	0.3525 ± 0.070
	PLE	0.4627 ± 0.040	0.2117 ± 0.009	0.0292 ± 0.002	0.0600 ± 0.002	0.1381 ± 0.016	0.3021 ± 0.033	0.6372 ± 0.027	0.3272 ± 0.007	0.3531 ± 0.022	0.5113 ± 0.013	0.2099 ± 0.018	0.0304 ± 0.011	0.2663 ± 0.088
	BS-U	0.4672 ± 0.046	0.2086 ± 0.006	0.0270 ± 0.002	0.0601 ± 0.001	0.1348 ± 0.014	0.2561 ± 0.014	0.6573 ± 0.024	0.3437 ± 0.008	0.3609 ± 0.022	0.4791 ± 0.014	0.2080 ± 0.020	0.0703 ± 0.014	0.2509 ± 0.089
	BS-Q	0.4737 ± 0.037	0.1951 ± 0.006	0.0266 ± 0.002	0.0601 ± 0.001	0.1269 ± 0.016	0.2737 ± 0.012	0.6572 ± 0.025	**0.3268** ± 0.008	0.3590 ± 0.023	0.4597 ± 0.009	0.2069 ± 0.019	0.0872 ± 0.006	0.2475 ± 0.087
	BS-CART	0.4740 ± 0.039	0.2130 ± 0.006	0.0292 ± 0.003	0.0601 ± 0.002	0.1233 ± 0.012	0.2694 ± 0.034	0.6684 ± 0.025	0.3329 ± 0.009	0.3590 ± 0.022	0.4794 ± 0.009	0.2092 ± 0.019	0.0885 ± 0.007	0.2541 ± 0.093
	BS-LGBM	0.4725 ± 0.039	0.1974 ± 0.006	0.0269 ± 0.004	0.0606 ± 0.002	0.1252 ± 0.017	0.2036 ± 0.016	0.6557 ± 0.022	0.3272 ± 0.008	0.3572 ± 0.027	0.4642 ± 0.010	0.2104 ± 0.017	0.0876 ± 0.005	0.2486 ± 0.091
	BS-Grad-U	0.4656 ± 0.036	**0.1803** ± 0.008	**0.0246** ± 0.003	**0.0221** ± 0.002	0.1027 ± 0.011	0.1307 ± 0.016	0.5977 ± 0.021	0.3350 ± 0.008	0.3337 ± 0.027	0.3654 ± 0.009	0.2028 ± 0.022	**0.0101** ± 0.001	**0.1902** ± 0.076
	IS-U	**0.4475** ± 0.046	0.2205 ± 0.007	0.0265 ± 0.003	0.0593 ± 0.001	0.1412 ± 0.022	0.3577 ± 0.017	0.6417 ± 0.024	0.3406 ± 0.008	0.3576 ± 0.027	0.5196 ± 0.014	0.2078 ± 0.016	0.0572 ± 0.031	0.2558 ± 0.085
	IS-Q	0.4477 ± 0.037	0.2129 ± 0.006	0.0276 ± 0.002	0.0598 ± 0.002	0.1356 ± 0.016	0.3703 ± 0.014	0.6464 ± 0.023	0.3297 ± 0.008	0.3533 ± 0.023	0.5013 ± 0.011	0.2084 ± 0.019	0.0563 ± 0.031	0.2661 ± 0.080
	IS-CART	0.4581 ± 0.044	0.2245 ± 0.006	0.0290 ± 0.003	0.0607 ± 0.001	0.1401 ± 0.018	0.3837 ± 0.015	0.6472 ± 0.020	0.3353 ± 0.009	0.3577 ± 0.015	0.5232 ± 0.016	0.2077 ± 0.016	0.0564 ± 0.029	0.2634 ± 0.080
	IS-LGBM	0.4521 ± 0.037	0.2123 ± 0.004	0.0274 ± 0.002	0.0628 ± 0.002	0.1339 ± 0.016	0.3367 ± 0.013	0.6393 ± 0.019	0.3287 ± 0.007	0.3579 ± 0.021	0.5096 ± 0.014	0.2113 ± 0.016	0.0605 ± 0.034	0.2644 ± 0.085
	IS-Grad-U	0.4488 ± 0.043	0.1952 ± 0.007	0.0247 ± 0.002	0.0231 ± 0.002	**0.1001** ± 0.016	**0.1281** ± 0.015	0.5968 ± 0.026	0.3409 ± 0.008	**0.3123** ± 0.031	0.3858 ± 0.011	**0.1983** ± 0.023	0.0103 ± 0.004	0.1907 ± 0.079
	MS-Grad-U	0.4700 ± 0.042	0.1841 ± 0.005	0.0264 ± 0.002	0.0276 ± 0.002	0.1045 ± 0.011	0.1324 ± 0.015	**0.5930** ± 0.019	0.3412 ± 0.007	0.3462 ± 0.039	**0.3497** ± 0.007	0.2054 ± 0.018	0.0185 ± 0.001	0.1906 ± 0.087
RESNET	STD	**0.4277** ± 0.027	0.2545 ± 0.017	0.0329 ± 0.007	0.0339 ± 0.012	0.1336 ± 0.015	0.4344 ± 0.023	0.6484 ± 0.011	0.3605 ± 0.011	0.3450 ± 0.029	0.5103 ± 0.013	**0.1983** ± 0.019	0.0296 ± 0.004	0.2449 ± 0.097
	MinMax	0.4291 ± 0.025	0.2805 ± 0.025	0.0326 ± 0.005	0.0362 ± 0.007	0.1321 ± 0.014	0.4345 ± 0.018	0.6486 ± 0.013	0.3644 ± 0.013	0.3464 ± 0.030	0.5301 ± 0.022	0.1988 ± 0.020	0.0383 ± 0.009	0.2313 ± 0.077
	PLE	0.4588 ± 0.033	0.1847 ± 0.007	0.0249 ± 0.002	0.0257 ± 0.002	0.1077 ± 0.006	0.1353 ± 0.035	0.5942 ± 0.019	**0.3229** ± 0.009	0.3180 ± 0.029	0.3760 ± 0.016	0.2008 ± 0.021	0.0200 ± 0.004	0.2149 ± 0.076
	BS-U	0.4707 ± 0.046	0.1771 ± 0.007	0.0251 ± 0.002	0.0243 ± 0.001	0.1124 ± 0.007	**0.0782** ± 0.006	0.5953 ± 0.021	0.3343 ± 0.006	0.3444 ± 0.030	0.3636 ± 0.016	0.2055 ± 0.024	0.0185 ± 0.003	0.1976 ± 0.102
	BS-Q	0.4792 ± 0.036	0.1776 ± 0.006	0.0255 ± 0.003	0.0255 ± 0.002	0.1141 ± 0.016	0.1293 ± 0.007	0.6264 ± 0.043	0.3273 ± 0.008	0.3529 ± 0.032	0.3588 ± 0.016	0.2109 ± 0.027	0.0164 ± 0.002	0.2038 ± 0.119
	BS-CART	0.4680 ± 0.047	0.1896 ± 0.006	0.0270 ± 0.004	0.0261 ± 0.002	0.1080 ± 0.013	0.1437 ± 0.011	0.6219 ± 0.021	0.3321 ± 0.012	0.3481 ± 0.030	0.3795 ± 0.011	0.2082 ± 0.021	0.0175 ± 0.003	0.2215 ± 0.085
	BS-LGBM	0.4838 ± 0.037	**0.1763** ± 0.006	0.0254 ± 0.003	0.0270 ± 0.002	0.1100 ± 0.013	0.1176 ± 0.015	0.6105 ± 0.029	0.3249 ± 0.009	0.3470 ± 0.026	0.3637 ± 0.008	0.2091 ± 0.023	**0.0157** ± 0.002	0.2197 ± 0.112
	BS-Grad-U	0.4965 ± 0.046	0.2015 ± 0.011	0.0348 ± 0.004	0.0222 ± 0.002	0.1226 ± 0.008	0.0913 ± 0.017	**0.5823** ± 0.030	0.3470 ± 0.009	0.3636 ± 0.027	0.3652 ± 0.022	0.2214 ± 0.021	0.0176 ± 0.007	0.2258 ± 0.095
	IS-U	0.4395 ± 0.039	0.1939 ± 0.012	0.0238 ± 0.003	0.0254 ± 0.002	0.1096 ± 0.019	0.1603 ± 0.046	0.6020 ± 0.026	0.3402 ± 0.008	0.3198 ± 0.026	0.3756 ± 0.013	0.1998 ± 0.021	0.0221 ± 0.004	0.1843 ± 0.103
	IS-Q	0.4431 ± 0.039	0.1786 ± 0.007	**0.0237** ± 0.002	0.0262 ± 0.002	**0.1035** ± 0.011	0.1585 ± 0.019	0.6015 ± 0.030	0.3285 ± 0.009	**0.3126** ± 0.031	0.3646 ± 0.019	0.1993 ± 0.020	0.0215 ± 0.004	**0.1759** ± 0.059
	IS-CART	0.4483 ± 0.042	0.2012 ± 0.005	0.0258 ± 0.003	0.0254 ± 0.001	0.1078 ± 0.013	0.1463 ± 0.018	0.6043 ± 0.025	0.3332 ± 0.009	0.3215 ± 0.032	0.3920 ± 0.009	0.2040 ± 0.013	0.0182 ± 0.004	0.1908 ± 0.090
	IS-LGBM	0.4463 ± 0.037	0.1774 ± 0.008	0.0242 ± 0.002	0.0257 ± 0.003	0.1040 ± 0.012	0.1296 ± 0.023	0.6037 ± 0.028	0.3253 ± 0.008	0.3170 ± 0.032	0.3669 ± 0.012	0.2010 ± 0.020	0.0225 ± 0.007	0.1767 ± 0.070
	IS-Grad-U	0.4405 ± 0.045	0.2081 ± 0.016	0.0289 ± 0.005	0.0226 ± 0.003	0.1173 ± 0.011	0.0859 ± 0.025	0.5931 ± 0.020	0.3485 ± 0.008	0.3368 ± 0.027	**0.3440** ± 0.015	0.2094 ± 0.025	0.0189 ± 0.002	0.2139 ± 0.013
	MS-Grad-U	0.4877 ± 0.033	0.2030 ± 0.010	0.0320 ± 0.005	**0.0216** ± 0.001	0.1261 ± 0.011	0.0949 ± 0.025	0.6085 ± 0.015	0.3479 ± 0.008	0.3666 ± 0.026	0.3555 ± 0.014	0.2161 ± 0.019	0.0881 ± 0.106	0.2382 ± 0.068
FTT	STD	0.4609 ± 0.028	0.2290 ± 0.010	**0.0254** ± 0.003	**0.0201** ± 0.002	**0.1219** ± 0.013	**0.1318** ± 0.024	0.6727 ± 0.043	0.3396 ± 0.013	**0.3248** ± 0.030	**0.3858** ± 0.016	**0.2017** ± 0.029	**0.0097** ± 0.002	0.2805 ± 0.065
	MinMax	**0.4565** ± 0.040	0.2496 ± 0.018	0.0310 ± 0.005	0.0204 ± 0.001	0.1276 ± 0.019	0.3347 ± 0.088	0.6724 ± 0.038	0.3485 ± 0.010	0.3531 ± 0.026	0.4333 ± 0.031	0.2066 ± 0.022	0.0101 ± 0.006	**0.2373** ± 0.078
	PLE	0.4783 ± 0.051	**0.2090** ± 0.011	0.0321 ± 0.007	0.0238 ± 0.003	0.1285 ± 0.018	0.2594 ± 0.084	0.6521 ± 0.024	**0.3825** ± 0.012	0.3460 ± 0.043	0.4033 ± 0.016	0.2091 ± 0.018	0.0144 ± 0.009	0.2555 ± 0.073
	BS-U	0.5334 ± 0.055	0.2960 ± 0.021	0.0343 ± 0.007	0.0284 ± 0.006	0.1538 ± 0.032	0.4548 ± 0.140	0.7056 ± 0.042	0.3600 ± 0.015	0.3865 ± 0.031	0.4265 ± 0.010	0.2071 ± 0.023	0.0399 ± 0.011	0.2670 ± 0.079
	BS-Q	0.5773 ± 0.073	0.2558 ± 0.020	0.0373 ± 0.006	0.0260 ± 0.003	0.1425 ± 0.018	0.4200 ± 0.168	0.7167 ± 0.032	0.3536 ± 0.018	0.3823 ± 0.025	0.4339 ± 0.010	0.2184 ± 0.021	0.0887 ± 0.040	0.2912 ± 0.067
	BS-CART	0.5222 ± 0.043	0.2757 ± 0.037	0.0362 ± 0.005	0.0271 ± 0.005	0.1526 ± 0.026	0.4054 ± 0.094	0.7287 ± 0.046	0.3590 ± 0.028	0.3752 ± 0.025	0.4522 ± 0.010	0.2173 ± 0.034	0.0740 ± 0.015	0.2987 ± 0.056
	BS-LGBM	0.5655 ± 0.048	0.2533 ± 0.017	0.0345 ± 0.007	0.0260 ± 0.005	0.1430 ± 0.029	0.4390 ± 0.109	0.6885 ± 0.022	0.3598 ± 0.021	0.3817 ± 0.017	0.4837 ± 0.053	0.2191 ± 0.024	0.0889 ± 0.023	0.2891 ± 0.086
	BS-Grad-U	0.5173 ± 0.064	0.2166 ± 0.035	0.0393 ± 0.010	0.0290 ± 0.007	0.1393 ± 0.015	0.1377 ± 0.022	**0.6146** ± 0.040	0.3495 ± 0.015	0.4861 ± 0.164	0.4667 ± 0.039	0.2049 ± 0.020	0.0369 ± 0.013	0.2817 ± 0.102
	IS-U	0.4607 ± 0.050	0.2305 ± 0.021	0.0341 ± 0.004	0.0242 ± 0.002	0.1401 ± 0.023	0.2945 ± 0.198	0.6707 ± 0.027	0.3407 ± 0.012	0.3501 ± 0.030	0.4164 ± 0.012	0.2125 ± 0.038	0.0148 ± 0.003	0.2938 ± 0.071
	IS-Q	0.4632 ± 0.054	0.2105 ± 0.010	0.0309 ± 0.007	0.0267 ± 0.003	0.1298 ± 0.010	0.1547 ± 0.102	0.6412 ± 0.018	0.3335 ± 0.010	0.3453 ± 0.020	0.3975 ± 0.012	0.2126 ± 0.031	0.0186 ± 0.006	0.2547 ± 0.094
	IS-CART	0.4769 ± 0.046	0.2286 ± 0.004	0.0357 ± 0.011	0.0221 ± 0.001	0.1396 ± 0.026	0.2034 ± 0.134	0.6485 ± 0.025	0.3384 ± 0.008	0.3393 ± 0.028	0.4050 ± 0.016	0.2094 ± 0.023	0.0161 ± 0.010	0.2417 ± 0.088
	IS-LGBM	0.4576 ± 0.046	0.2164 ± 0.008	0.0307 ± 0.007	0.0234 ± 0.003	0.1341 ± 0.034	0.1927 ± 0.067	0.6493 ± 0.025	0.3349 ± 0.009	0.3522 ± 0.025	0.4089 ± 0.010	0.2049 ± 0.020	0.0147 ± 0.010	0.2460 ± 0.077
	IS-Grad-U	0.4866 ± 0.045	0.2385 ± 0.031	0.0458 ± 0.009	0.0264 ± 0.005	0.1479 ± 0.023	0.1463 ± 0.033	0.6680 ± 0.042	0.3437 ± 0.009	0.3809 ± 0.026	0.4407 ± 0.033	0.2076 ± 0.029	0.0147 ± 0.006	0.2664 ± 0.080
	MS-Grad-U	0.5595 ± 0.051	0.3371 ± 0.096	0.0345 ± 0.004	0.0248 ± 0.001	0.1737 ± 0.023	0.1722 ± 0.033	0.7229 ± 0.024	0.3911 ± 0.027	0.4389 ± 0.087	0.4506 ± 0.025	0.2170 ± 0.029	0.1900 ± 0.033	0.2878 ± 0.082

Table 9: Regression results for $m = 30$. Mean NRMSE ($\downarrow$) ± standard deviation over 5-fold cross-validation. Dataset and preprocessing abbreviations are given in Tables 3 and 2 respectively. Bold indicates the lowest NRMSE for each dataset within each backbone.

Backbone	Method	AD	BA	CH	FI	MA	AQ	EEG	GT	IP	LS	LT	SH
MLP	STD	0.9017 ± 0.004	0.8907 ± 0.007	0.8425 ± 0.011	0.7871 ± 0.005	0.8857 ± 0.006	0.9934 ± 0.001	0.7758 ± 0.054	0.9125 ± 0.006	0.8999 ± 0.006	0.9548 ± 0.002	0.9199 ± 0.004	**0.9994** ± 0.004
	MinMax	0.8910 ± 0.004	0.8799 ± 0.005	0.7566 ± 0.017	0.7840 ± 0.004	0.8714 ± 0.004	0.9931 ± 0.001	0.5800 ± 0.013	0.8916 ± 0.007	0.8993 ± 0.006	0.9475 ± 0.002	0.8945 ± 0.002	0.9945 ± 0.002
	PLE	**0.9089** ± 0.003	0.9021 ± 0.004	0.8405 ± 0.010	0.7975 ± 0.006	0.8952 ± 0.002	**0.9958** ± 0.001	**0.9311** ± 0.004	0.9144 ± 0.004	**0.9477** ± 0.004	0.9601 ± 0.002	**0.9406** ± 0.003	0.9986 ± 0.000
	BS-U	0.9046 ± 0.004	0.8974 ± 0.004	0.8451 ± 0.011	**0.7985** ± 0.005	0.8925 ± 0.004	0.9954 ± 0.001	0.6146 ± 0.024	0.9173 ± 0.003	0.9363 ± 0.005	0.9576 ± 0.001	0.9265 ± 0.001	0.9985 ± 0.001
	BS-Q	0.9037 ± 0.004	0.8988 ± 0.003	0.8441 ± 0.011	0.7981 ± 0.007	0.8901 ± 0.004	0.9957 ± 0.001	0.7612 ± 0.029	0.9208 ± 0.003	0.9432 ± 0.005	0.9572 ± 0.001	0.9355 ± 0.002	0.9987 ± 0.001
	BS-CART	0.9061 ± 0.003	0.8987 ± 0.003	0.8447 ± 0.010	0.7977 ± 0.006	0.8937 ± 0.005	0.9954 ± 0.001	0.7426 ± 0.031	0.9211 ± 0.004	0.9435 ± 0.004	0.9581 ± 0.001	0.9367 ± 0.003	0.9986 ± 0.001
	BS-LGBM	0.9064 ± 0.003	0.8986 ± 0.003	0.8461 ± 0.011	0.7979 ± 0.006	0.8937 ± 0.006	0.9955 ± 0.000	0.7618 ± 0.032	0.9176 ± 0.003	0.9448 ± 0.005	0.9582 ± 0.001	0.9332 ± 0.004	0.9981 ± 0.001
	BS-Grad-U	0.9078 ± 0.003	0.9148 ± 0.003	**0.8598** ± 0.011	0.7981 ± 0.005	**0.9089** ± 0.006	0.9955 ± 0.001	0.7177 ± 0.132	0.9300 ± 0.004	0.9437 ± 0.004	**0.9618** ± 0.001	0.9193 ± 0.002	0.9987 ± 0.000
	IS-U	0.9040 ± 0.004	0.8971 ± 0.003	0.8425 ± 0.011	0.7972 ± 0.004	0.8898 ± 0.004	0.9955 ± 0.001	0.6029 ± 0.019	0.9167 ± 0.004	0.9325 ± 0.009	0.9572 ± 0.002	0.9244 ± 0.002	0.9975 ± 0.001
	IS-Q	0.9034 ± 0.004	0.8984 ± 0.004	0.8411 ± 0.013	0.7973 ± 0.004	0.8910 ± 0.003	**0.9958** ± 0.000	0.6327 ± 0.020	0.9185 ± 0.003	0.9436 ± 0.004	0.9574 ± 0.001	0.9342 ± 0.002	0.9978 ± 0.001
	IS-CART	0.9054 ± 0.003	0.8968 ± 0.003	0.8425 ± 0.011	0.7954 ± 0.003	0.8918 ± 0.005	0.9957 ± 0.000	0.6342 ± 0.018	0.9179 ± 0.003	0.9442 ± 0.004	0.9578 ± 0.001	0.9326 ± 0.004	0.9983 ± 0.001
	IS-LGBM	0.9059 ± 0.003	0.8975 ± 0.003	0.8436 ± 0.011	0.7969 ± 0.004	0.8915 ± 0.006	0.9955 ± 0.001	0.6361 ± 0.016	0.9175 ± 0.003	0.9438 ± 0.003	0.9580 ± 0.001	0.9297 ± 0.003	0.9982 ± 0.001
	IS-Grad-U	0.9085 ± 0.004	0.9118 ± 0.005	0.8536 ± 0.007	0.7952 ± 0.005	0.9065 ± 0.006	0.9944 ± 0.001	0.6058 ± 0.074	0.9272 ± 0.006	0.9349 ± 0.003	0.9613 ± 0.000	0.9267 ± 0.004	0.9974 ± 0.001
	MS-Grad-U	0.9063 ± 0.004	**0.9161** ± 0.004	0.8453 ± 0.015	0.7948 ± 0.007	0.9077 ± 0.004	0.9953 ± 0.000	0.6751 ± 0.134	**0.9313** ± 0.005	0.9444 ± 0.002	0.9601 ± 0.000	0.9114 ± 0.005	0.9991 ± 0.001
RESNET	STD	0.9054 ± 0.004	0.9008 ± 0.004	0.8537 ± 0.010	0.7904 ± 0.005	0.8939 ± 0.004	0.9953 ± 0.001	0.7914 ± 0.107	0.9230 ± 0.005	0.9152 ± 0.009	0.9617 ± 0.001	0.9315 ± 0.004	0.9988 ± 0.001
	MinMax	0.9017 ± 0.004	0.8925 ± 0.003	0.8522 ± 0.015	0.7906 ± 0.004	0.8815 ± 0.007	0.9951 ± 0.001	0.8461 ± 0.057	0.9226 ± 0.004	0.9206 ± 0.014	0.9619 ± 0.001	0.9243 ± 0.005	**0.9997** ± 0.000
	PLE	**0.9125** ± 0.003	0.9155 ± 0.004	0.8562 ± 0.012	0.7939 ± 0.006	0.9040 ± 0.004	0.9962 ± 0.001	**0.9903** ± 0.002	0.9293 ± 0.002	**0.9473** ± 0.004	**0.9634** ± 0.002	**0.9498** ± 0.002	0.9993 ± 0.001
	BS-U	0.9078 ± 0.004	0.9094 ± 0.004	**0.8621** ± 0.011	0.7958 ± 0.004	0.9029 ± 0.003	0.9961 ± 0.001	0.8884 ± 0.039	0.9361 ± 0.005	0.9412 ± 0.001	0.9622 ± 0.002	0.9419 ± 0.002	0.9991 ± 0.001
	BS-Q	0.9072 ± 0.004	0.9126 ± 0.002	0.8594 ± 0.011	0.7958 ± 0.008	0.9029 ± 0.003	0.9962 ± 0.001	0.9539 ± 0.018	0.9369 ± 0.005	0.9451 ± 0.003	0.9613 ± 0.001	0.9465 ± 0.003	0.9995 ± 0.001
	BS-CART	0.9095 ± 0.004	0.9125 ± 0.005	0.8591 ± 0.013	**0.7984** ± 0.007	0.9030 ± 0.004	0.9962 ± 0.001	0.8965 ± 0.065	0.9360 ± 0.006	0.9470 ± 0.004	0.9620 ± 0.002	0.9492 ± 0.003	0.9995 ± 0.001
	BS-LGBM	0.9100 ± 0.003	0.9115 ± 0.004	0.8588 ± 0.010	0.7974 ± 0.007	0.9014 ± 0.004	0.9958 ± 0.001	0.9304 ± 0.033	0.9363 ± 0.005	0.9460 ± 0.003	0.9619 ± 0.002	0.9474 ± 0.002	0.9993 ± 0.001
	BS-Grad-U	0.9094 ± 0.004	**0.9263** ± 0.002	0.8525 ± 0.010	0.7891 ± 0.008	**0.9163** ± 0.006	0.9952 ± 0.001	0.8375 ± 0.080	0.9356 ± 0.005	0.9380 ± 0.004	0.9628 ± 0.002	0.9375 ± 0.003	0.9994 ± 0.001
	IS-U	0.9075 ± 0.004	0.9135 ± 0.004	0.8587 ± 0.015	0.7980 ± 0.006	0.9022 ± 0.004	**0.9965** ± 0.001	0.8705 ± 0.030	0.9345 ± 0.004	0.9402 ± 0.002	0.9620 ± 0.002	0.9404 ± 0.002	0.9992 ± 0.001
	IS-Q	0.9069 ± 0.004	0.9139 ± 0.004	0.8561 ± 0.013	**0.7984** ± 0.006	0.9017 ± 0.004	0.9964 ± 0.001	0.8970 ± 0.031	0.9370 ± 0.005	0.9433 ± 0.004	0.9627 ± 0.002	0.9435 ± 0.003	0.9994 ± 0.001
	IS-CART	0.9097 ± 0.004	0.9107 ± 0.002	0.8591 ± 0.013	0.7958 ± 0.004	0.9014 ± 0.004	0.9964 ± 0.001	0.8886 ± 0.041	**0.9375** ± 0.004	0.9465 ± 0.004	0.9612 ± 0.002	0.9455 ± 0.001	0.9995 ± 0.001
	IS-LGBM	0.9098 ± 0.004	0.9131 ± 0.004	0.8585 ± 0.013	0.7967 ± 0.006	0.9036 ± 0.004	0.9963 ± 0.001	0.9018 ± 0.041	0.9353 ± 0.004	0.9458 ± 0.004	0.9617 ± 0.002	0.9441 ± 0.002	0.9994 ± 0.001
	IS-Grad-U	0.9089 ± 0.003	0.9253 ± 0.003	0.8528 ± 0.011	0.7900 ± 0.007	0.9152 ± 0.005	0.9948 ± 0.001	0.6896 ± 0.067	0.9359 ± 0.004	0.9314 ± 0.004	0.9626 ± 0.002	0.9372 ± 0.003	0.9995 ± 0.000
	MS-Grad-U	0.9081 ± 0.004	0.9243 ± 0.004	0.8476 ± 0.013	0.7872 ± 0.009	0.9147 ± 0.005	0.9951 ± 0.001	0.6952 ± 0.134	0.9327 ± 0.002	0.9433 ± 0.002	0.9605 ± 0.001	0.9328 ± 0.002	0.9992 ± 0.001
FTT	STD	0.9152 ± 0.003	0.9294 ± 0.004	0.8540 ± 0.011	0.7909 ± 0.006	0.9215 ± 0.004	0.9952 ± 0.001	**0.9715** ± 0.011	0.9234 ± 0.005	0.9073 ± 0.013	0.9663 ± 0.001	0.9324 ± 0.008	**1.0000** ± 0.000
	MinMax	0.9147 ± 0.004	0.9293 ± 0.004	0.8565 ± 0.011	0.7952 ± 0.007	0.9229 ± 0.003	0.9938 ± 0.002	0.5766 ± 0.035	0.9257 ± 0.004	0.9181 ± 0.020	0.9666 ± 0.002	0.9250 ± 0.006	0.9989 ± 0.001
	PLE	**0.9233** ± 0.002	0.9324 ± 0.003	0.8561 ± 0.007	0.7973 ± 0.007	0.9244 ± 0.003	0.9956 ± 0.000	0.9675 ± 0.018	0.9238 ± 0.006	**0.9474** ± 0.003	0.9668 ± 0.002	**0.9488** ± 0.003	0.9994 ± 0.000
	BS-U	0.9155 ± 0.003	0.9320 ± 0.003	0.8579 ± 0.004	0.7962 ± 0.008	0.9255 ± 0.003	0.9955 ± 0.000	0.6680 ± 0.064	0.9299 ± 0.006	0.9436 ± 0.004	0.9666 ± 0.002	0.9412 ± 0.005	0.9992 ± 0.001
	BS-Q	0.9163 ± 0.003	0.9323 ± 0.003	0.8579 ± 0.004	0.7946 ± 0.008	0.9258 ± 0.004	0.9958 ± 0.000	0.8394 ± 0.115	0.9243 ± 0.007	0.9449 ± 0.004	0.9670 ± 0.003	0.9428 ± 0.004	0.9994 ± 0.001
	BS-CART	0.9168 ± 0.003	0.9306 ± 0.003	0.8557 ± 0.008	0.7974 ± 0.006	0.9252 ± 0.005	**0.9959** ± 0.001	0.8585 ± 0.090	0.9263 ± 0.005	0.9461 ± 0.002	0.9669 ± 0.002	0.9457 ± 0.004	**1.0000** ± 0.000
	BS-LGBM	0.9179 ± 0.004	0.9324 ± 0.004	0.8585 ± 0.008	0.7956 ± 0.006	0.9246 ± 0.004	0.9957 ± 0.000	0.7700 ± 0.062	0.9259 ± 0.004	0.9452 ± 0.006	0.9669 ± 0.002	0.9450 ± 0.003	0.9995 ± 0.000
	BS-Grad-U	0.9153 ± 0.003	0.9332 ± 0.003	**0.8623** ± 0.008	0.7983 ± 0.007	0.9262 ± 0.004	0.9943 ± 0.001	0.8027 ± 0.050	0.9271 ± 0.008	0.9451 ± 0.008	0.9675 ± 0.001	0.9394 ± 0.004	0.9988 ± 0.001
	IS-U	0.9162 ± 0.003	**0.9340** ± 0.002	0.8587 ± 0.008	0.7959 ± 0.008	**0.9269** ± 0.004	0.9958 ± 0.000	0.6739 ± 0.080	0.9300 ± 0.005	0.9402 ± 0.010	0.9673 ± 0.002	0.9393 ± 0.006	0.9989 ± 0.001
	IS-Q	0.9158 ± 0.003	0.9323 ± 0.004	0.8561 ± 0.011	0.7979 ± 0.006	0.9259 ± 0.004	0.9955 ± 0.001	0.6793 ± 0.069	0.9238 ± 0.003	0.9413 ± 0.008	0.9670 ± 0.002	0.9403 ± 0.001	0.9990 ± 0.000
	IS-CART	0.9163 ± 0.004	0.9336 ± 0.004	0.8593 ± 0.011	0.7989 ± 0.008	0.9258 ± 0.003	0.9956 ± 0.001	0.6840 ± 0.077	0.9265 ± 0.003	0.9433 ± 0.005	0.9666 ± 0.002	0.9436 ± 0.005	0.9988 ± 0.001
	IS-LGBM	0.9166 ± 0.003	0.9332 ± 0.003	0.8594 ± 0.010	0.7972 ± 0.006	0.9267 ± 0.004	0.9954 ± 0.001	0.6516 ± 0.051	0.9232 ± 0.009	0.9444 ± 0.005	0.9669 ± 0.001	0.9421 ± 0.003	0.9989 ± 0.001
	IS-Grad-U	0.9171 ± 0.004	0.9333 ± 0.004	0.8606 ± 0.006	**0.8006** ± 0.006	0.9261 ± 0.004	0.9953 ± 0.001	0.6190 ± 0.046	**0.9306** ± 0.010	0.9366 ± 0.003	**0.9680** ± 0.001	0.9427 ± 0.006	0.9977 ± 0.002
	MS-Grad-U	0.9159 ± 0.004	0.9300 ± 0.004	0.8553 ± 0.009	0.7924 ± 0.006	0.9231 ± 0.003	0.9941 ± 0.001	0.7681 ± 0.127	0.9246 ± 0.004	0.9444 ± 0.004	0.9659 ± 0.001	0.9291 ± 0.004	0.9992 ± 0.000

Table 10: Classification results for $m = 7$. Mean AUC ($\uparrow$) ± standard deviation over 5-fold cross-validation. For multiclass datasets, AUC corresponds to weighted one-vs-rest ROC-AUC. Dataset and preprocessing abbreviations are given in Tables 3 and 2 respectively. Bold indicates the highest AUC for each dataset within each backbone.

Backbone	Method	AD	BA	CH	FI	MA	AQ	EEG	GT	IP	LS	LT	SH
MLP	STD	0.9017 ± 0.004	0.8907 ± 0.007	0.8425 ± 0.011	0.7871 ± 0.005	0.8857 ± 0.006	0.9934 ± 0.001	0.7758 ± 0.054	0.9125 ± 0.006	0.8999 ± 0.006	0.9548 ± 0.002	0.9199 ± 0.004	0.9994 ± 0.001
	MinMax	0.8910 ± 0.004	0.8799 ± 0.005	0.7566 ± 0.017	0.7840 ± 0.004	0.8714 ± 0.006	0.9931 ± 0.001	0.5800 ± 0.013	0.8916 ± 0.007	0.8993 ± 0.006	0.9475 ± 0.002	0.8945 ± 0.004	0.9945 ± 0.002
	PLE	**0.9125** ± 0.003	0.9069 ± 0.003	0.8438 ± 0.010	0.7959 ± 0.004	0.9000 ± 0.003	**0.9961** ± 0.000	**0.9402** ± 0.003	0.9192 ± 0.003	**0.9474** ± 0.004	0.9602 ± 0.001	**0.9492** ± 0.003	**1.0000** ± 0.000
	BS-U	0.9066 ± 0.004	0.9042 ± 0.003	0.8449 ± 0.010	0.7965 ± 0.006	0.8986 ± 0.005	0.9959 ± 0.001	0.6683 ± 0.036	0.9164 ± 0.003	0.9415 ± 0.003	0.9585 ± 0.001	0.9362 ± 0.003	0.9983 ± 0.000
	BS-Q	0.9062 ± 0.004	0.9047 ± 0.003	0.8428 ± 0.011	0.7947 ± 0.007	0.8971 ± 0.004	0.9955 ± 0.001	0.9284 ± 0.004	0.9192 ± 0.004	0.9452 ± 0.003	0.9590 ± 0.001	0.9423 ± 0.002	0.9998 ± 0.000
	BS-CART	0.9097 ± 0.003	0.9054 ± 0.003	0.8442 ± 0.010	0.7950 ± 0.006	0.8999 ± 0.004	0.9958 ± 0.001	0.9218 ± 0.005	0.9179 ± 0.004	0.9458 ± 0.003	0.9592 ± 0.001	0.9437 ± 0.003	**1.0000** ± 0.000
	BS-LGBM	0.9076 ± 0.003	0.9041 ± 0.003	0.8422 ± 0.011	0.7935 ± 0.008	0.8979 ± 0.004	0.9957 ± 0.001	0.9233 ± 0.006	0.9174 ± 0.003	0.9463 ± 0.004	0.9589 ± 0.001	0.9429 ± 0.002	0.9999 ± 0.000
	BS-Grad-U	0.9111 ± 0.003	0.9167 ± 0.003	**0.8559** ± 0.013	**0.7980** ± 0.014	**0.9113** ± 0.003	0.9958 ± 0.005	0.7568 ± 0.100	0.9258 ± 0.005	0.9434 ± 0.005	**0.9607** ± 0.001	0.9279 ± 0.003	0.9989 ± 0.000
	IS-U	0.9068 ± 0.003	0.9032 ± 0.003	0.8446 ± 0.011	0.7968 ± 0.004	0.8971 ± 0.004	0.9959 ± 0.001	0.6229 ± 0.030	0.9186 ± 0.003	0.9397 ± 0.005	0.9577 ± 0.001	0.9322 ± 0.003	0.9981 ± 0.001
	IS-Q	0.9071 ± 0.004	0.9048 ± 0.002	0.8424 ± 0.012	0.7962 ± 0.005	0.8986 ± 0.005	0.9959 ± 0.000	0.8211 ± 0.044	0.9237 ± 0.003	0.9433 ± 0.005	0.9580 ± 0.001	0.9389 ± 0.003	0.9993 ± 0.000
	IS-CART	0.9085 ± 0.003	0.9039 ± 0.003	0.8445 ± 0.011	0.7951 ± 0.005	0.8986 ± 0.004	0.9960 ± 0.001	0.8099 ± 0.045	0.9194 ± 0.005	0.9430 ± 0.003	0.9588 ± 0.001	0.9378 ± 0.003	0.9998 ± 0.000
	IS-LGBM	0.9075 ± 0.003	0.9043 ± 0.003	0.8422 ± 0.013	0.7956 ± 0.005	**0.9961** ± 0.000... 0.8993 ± 0.005	0.9226 ± 0.004	0.8159 ± 0.045	0.9437 ± 0.003	0.9579 ± 0.001	0.9391 ± 0.002	0.9997 ± 0.000	
	IS-Grad-U	0.9107 ± 0.003	0.9163 ± 0.003	0.8551 ± 0.010	0.7960 ± 0.004	0.9100 ± 0.006	0.9951 ± 0.006	0.6561 ± 0.087	**0.9285** ± 0.005	0.9386 ± 0.001	0.9600 ± 0.001	0.9329 ± 0.003	0.9988 ± 0.000
	MS-Grad-U	0.9101 ± 0.004	**0.9173** ± 0.003	0.8442 ± 0.012	0.7927 ± 0.009	0.9099 ± 0.004	0.9955 ± 0.000	0.7291 ± 0.106	0.9284 ± 0.005	0.9468 ± 0.003	0.9579 ± 0.001	0.9261 ± 0.004	0.9992 ± 0.001
RESNET	STD	0.9054 ± 0.004	0.9008 ± 0.004	0.8537 ± 0.010	0.7904 ± 0.005	0.8939 ± 0.004	0.9953 ± 0.001	0.7914 ± 0.107	0.9230 ± 0.005	0.9152 ± 0.009	0.9617 ± 0.001	0.9315 ± 0.004	0.9988 ± 0.001
	MinMax	0.9017 ± 0.004	0.8925 ± 0.003	0.8522 ± 0.015	0.7906 ± 0.007	0.8815 ± 0.007	0.9951 ± 0.001	0.8461 ± 0.057	0.9226 ± 0.001	0.9206 ± 0.014	0.9611 ± 0.001	0.9243 ± 0.005	0.9997 ± 0.000
	PLE	**0.9154** ± 0.003	0.9159 ± 0.002	0.8485 ± 0.011	0.7957 ± 0.007	0.9083 ± 0.011	0.9961 ± 0.001	**0.9886** ± 0.001	0.9302 ± 0.006	0.9462 ± 0.006	**0.9630** ± 0.002	**0.9590** ± 0.002	**1.0000** ± 0.000
	BS-U	0.9098 ± 0.003	0.9158 ± 0.003	0.8571 ± 0.012	0.7964 ± 0.007	0.9088 ± 0.006	0.9962 ± 0.001	0.9467 ± 0.032	0.9293 ± 0.006	0.9428 ± 0.003	0.9613 ± 0.000	0.9499 ± 0.002	0.9995 ± 0.001
	BS-Q	0.9096 ± 0.003	0.9143 ± 0.004	0.8560 ± 0.012	0.7943 ± 0.008	0.9067 ± 0.005	0.9955 ± 0.001	0.9766 ± 0.004	0.9275 ± 0.005	0.9453 ± 0.004	0.9615 ± 0.001	0.9503 ± 0.001	**1.0000** ± 0.000
	BS-CART	0.9121 ± 0.003	0.9160 ± 0.003	**0.8573** ± 0.011	0.7943 ± 0.007	0.9072 ± 0.005	0.9962 ± 0.000	0.9711 ± 0.004	0.9279 ± 0.005	0.9455 ± 0.004	0.9619 ± 0.002	0.9527 ± 0.003	**1.0000** ± 0.000
	BS-LGBM	0.9101 ± 0.003	0.9131 ± 0.003	0.8548 ± 0.011	0.7919 ± 0.009	0.9065 ± 0.004	0.9957 ± 0.001	0.9728 ± 0.006	0.9258 ± 0.004	**0.9465** ± 0.004	0.9611 ± 0.002	0.9506 ± 0.003	0.9998 ± 0.000
	BS-Grad-U	0.9112 ± 0.003	0.9155 ± 0.003	0.8433 ± 0.010	0.7834 ± 0.008	0.9095 ± 0.005	0.9955 ± 0.000	0.9692 ± 0.031	0.9284 ± 0.005	0.9406 ± 0.003	0.9606 ± 0.001	0.9469 ± 0.002	0.9996 ± 0.001
	IS-U	0.9101 ± 0.003	0.9160 ± 0.002	0.8566 ± 0.011	**0.7985** ± 0.005	0.9078 ± 0.004	**0.9966** ± 0.000	0.9067 ± 0.034	0.9344 ± 0.004	0.9408 ± 0.002	0.9612 ± 0.001	0.9475 ± 0.003	0.9993 ± 0.001
	IS-Q	0.9098 ± 0.004	0.9144 ± 0.003	0.8526 ± 0.012	0.7952 ± 0.006	0.9068 ± 0.005	0.9963 ± 0.000	0.9302 ± 0.032	0.9348 ± 0.005	0.9409 ± 0.001	0.9609 ± 0.001	0.9475 ± 0.003	0.9998 ± 0.000
	IS-CART	0.9113 ± 0.003	0.9173 ± 0.003	0.8528 ± 0.012	0.7951 ± 0.008	0.9088 ± 0.005	0.9965 ± 0.001	0.9343 ± 0.028	0.9329 ± 0.007	0.9453 ± 0.004	0.9615 ± 0.002	0.9479 ± 0.003	**1.0000** ± 0.000
	IS-LGBM	0.9100 ± 0.004	0.9159 ± 0.001	0.8517 ± 0.011	0.7936 ± 0.008	0.9063 ± 0.006	0.9962 ± 0.000	0.9291 ± 0.033	**0.9358** ± 0.002	0.9453 ± 0.004	0.9605 ± 0.001	0.9478 ± 0.002	**1.0000** ± 0.000
	IS-Grad-U	0.9096 ± 0.004	**0.9242** ± 0.003	0.8527 ± 0.011	0.7862 ± 0.012	0.9111 ± 0.006	0.9952 ± 0.001	0.7376 ± 0.098	0.9346 ± 0.005	0.9343 ± 0.005	0.9610 ± 0.002	0.9425 ± 0.003	0.9995 ± 0.001
	MS-Grad-U	0.9093 ± 0.003	0.9235 ± 0.003	0.8412 ± 0.014	0.7843 ± 0.014	**0.9130** ± 0.005	0.9940 ± 0.001	0.6962 ± 0.101	0.9264 ± 0.005	0.9457 ± 0.002	0.9562 ± 0.001	0.9381 ± 0.003	0.9993 ± 0.001
FTT	STD	0.9152 ± 0.003	0.9294 ± 0.004	0.8540 ± 0.011	0.7909 ± 0.006	0.9215 ± 0.004	0.9952 ± 0.001	**0.9715** ± 0.011	0.9234 ± 0.005	0.9073 ± 0.013	0.9663 ± 0.001	0.9324 ± 0.008	**1.0000** ± 0.000
	MinMax	0.9147 ± 0.004	0.9293 ± 0.004	0.8565 ± 0.011	0.7952 ± 0.007	0.9229 ± 0.003	0.9938 ± 0.002	0.5766 ± 0.035	0.9257 ± 0.004	0.9181 ± 0.020	0.9666 ± 0.002	0.9250 ± 0.006	0.9989 ± 0.001
	PLE	**0.9254** ± 0.003	0.9319 ± 0.003	0.8573 ± 0.006	0.7950 ± 0.007	0.9269 ± 0.004	0.9956 ± 0.001	0.9711 ± 0.009	0.9172 ± 0.004	**0.9473** ± 0.003	0.9677 ± 0.002	**0.9598** ± 0.006	**1.0000** ± 0.000
	BS-U	0.9192 ± 0.004	0.9328 ± 0.004	0.8525 ± 0.011	0.7955 ± 0.007	**0.9281** ± 0.004	0.9959 ± 0.001	0.7556 ± 0.087	0.9142 ± 0.002	0.9400 ± 0.005	0.9664 ± 0.003	0.9389 ± 0.002	0.9997 ± 0.000
	BS-Q	0.9160 ± 0.003	0.9308 ± 0.006	0.8530 ± 0.013	0.7947 ± 0.006	0.9224 ± 0.005	0.9954 ± 0.001	0.9436 ± 0.008	0.9199 ± 0.006	0.9441 ± 0.006	0.9660 ± 0.001	0.9433 ± 0.004	**1.0000** ± 0.000
	BS-CART	0.9189 ± 0.003	0.9324 ± 0.002	0.8560 ± 0.011	0.7931 ± 0.006	0.9231 ± 0.004	0.9954 ± 0.001	0.9429 ± 0.009	0.9162 ± 0.005	0.9440 ± 0.006	0.9662 ± 0.001	0.9484 ± 0.004	**1.0000** ± 0.000
	BS-LGBM	0.9180 ± 0.003	0.9319 ± 0.003	0.8556 ± 0.013	0.7951 ± 0.006	0.9231 ± 0.004	0.9958 ± 0.000	0.9404 ± 0.004	0.9160 ± 0.007	0.9428 ± 0.005	0.9669 ± 0.001	0.9435 ± 0.005	**1.0000** ± 0.000
	BS-Grad-U	0.9205 ± 0.003	0.9297 ± 0.003	0.8572 ± 0.007	0.7946 ± 0.006	0.9266 ± 0.005	0.9954 ± 0.000	0.7986 ± 0.151	0.9250 ± 0.005	0.9445 ± 0.005	0.9674 ± 0.001	0.9338 ± 0.004	0.9986 ± 0.001
	IS-U	0.9176 ± 0.004	0.9334 ± 0.003	0.8572 ± 0.007	0.7974 ± 0.006	0.9279 ± 0.004	0.9959 ± 0.000	0.7335 ± 0.054	0.9213 ± 0.007	0.9436 ± 0.004	0.9676 ± 0.002	0.9453 ± 0.004	0.9996 ± 0.001
	IS-Q	0.9194 ± 0.003	**0.8339** ± 0.003	0.8538 ± 0.005	0.7967 ± 0.006	0.9253 ± 0.005	0.9958 ± 0.000	0.8895 ± 0.048	0.9226 ± 0.006	0.9431 ± 0.005	0.9676 ± 0.002	0.9441 ± 0.004	**1.0000** ± 0.000
	IS-CART	0.9203 ± 0.003	0.9323 ± 0.003	0.8567 ± 0.009	0.7956 ± 0.005	0.9264 ± 0.004	**0.9961** ± 0.001	0.8665 ± 0.050	0.9245 ± 0.005	0.9453 ± 0.005	0.9679 ± 0.002	0.9455 ± 0.004	**1.0000** ± 0.000
	IS-LGBM	0.9197 ± 0.003	0.9335 ± 0.002	0.8543 ± 0.013	0.7941 ± 0.009	0.9257 ± 0.004	0.9957 ± 0.001	0.8599 ± 0.045	**0.9271** ± 0.004	0.9440 ± 0.004	**0.9684** ± 0.001	0.9463 ± 0.001	**1.0000** ± 0.000
	IS-Grad-U	0.9194 ± 0.002	0.9324 ± 0.004	**0.8616** ± 0.009	**0.7997** ± 0.009	0.9256 ± 0.004	0.9960 ± 0.001	0.8414 ± 0.122	0.9254 ± 0.006	0.9459 ± 0.003	**0.9684** ± 0.001	0.9420 ± 0.003	0.9996 ± 0.001
	MS-Grad-U	0.9181 ± 0.003	0.9294 ± 0.006	0.8519 ± 0.010	0.7943 ± 0.007	0.9234 ± 0.004	0.9948 ± 0.001	0.8366 ± 0.081	0.9205 ± 0.004	0.9451 ± 0.005	0.9639 ± 0.001	0.9367 ± 0.004	**1.0000** ± 0.000

Table 11: Classification results for $m = 15$. Mean AUC ($\uparrow$) ± standard deviation over 5-fold cross-validation. For multiclass datasets, AUC corresponds to weighted one-vs-rest ROC-AUC. Dataset and preprocessing abbreviations are given in Tables 3 and 2 respectively. Bold indicates the highest AUC for each dataset within each backbone.

Backbone	Method	AD	BA	CH	FI	MA	AQ	EEG	GT	IP	LS	LT	SH
MLP	STD	0.9017 ± 0.004	0.8907 ± 0.007	0.8425 ± 0.011	0.7871 ± 0.005	0.8857 ± 0.006	0.9934 ± 0.001	0.7758 ± 0.054	0.9125 ± 0.006	0.8999 ± 0.006	0.9548 ± 0.002	0.9199 ± 0.004	0.9994 ± 0.001
	MinMax	0.8910 ± 0.004	0.8799 ± 0.005	0.7566 ± 0.017	0.7840 ± 0.004	0.8714 ± 0.006	0.9931 ± 0.001	0.5800 ± 0.013	0.8916 ± 0.007	0.8993 ± 0.006	0.9475 ± 0.002	0.8945 ± 0.004	0.9945 ± 0.002
	PLE	**0.9135** ± 0.005	0.9073 ± 0.005	0.8436 ± 0.009	**0.7971** ± 0.009	0.9015 ± 0.006	0.9957 ± 0.000	**0.9401** ± 0.004	0.9175 ± 0.003	0.9467 ± 0.003	**0.9615** ± 0.002	**0.9559** ± 0.003	**1.0000** ± 0.000
	BS-U	0.9077 ± 0.006	0.9054 ± 0.004	0.8431 ± 0.010	0.7961 ± 0.008	0.9003 ± 0.007	0.9954 ± 0.000	0.7457 ± 0.051	0.9117 ± 0.003	0.9435 ± 0.002	0.9584 ± 0.002	0.9440 ± 0.003	0.9994 ± 0.000
	BS-Q	0.9092 ± 0.006	0.9043 ± 0.005	0.8422 ± 0.009	0.7959 ± 0.008	0.8983 ± 0.008	0.9948 ± 0.000	0.9237 ± 0.002	0.9091 ± 0.004	0.9434 ± 0.003	0.9596 ± 0.002	0.9469 ± 0.002	1.0000 ± 0.000
	BS-CART	0.9100 ± 0.006	0.9017 ± 0.006	0.8416 ± 0.008	0.7962 ± 0.007	0.8964 ± 0.007	0.9948 ± 0.000	0.9154 ± 0.003	0.9118 ± 0.005	0.9428 ± 0.003	0.9606 ± 0.001	0.9501 ± 0.004	1.0000 ± 0.000
	BS-LGBM	0.9082 ± 0.005	0.9038 ± 0.004	0.8424 ± 0.009	0.7944 ± 0.008	0.8973 ± 0.007	0.9945 ± 0.001	0.9202 ± 0.002	0.9109 ± 0.003	0.9440 ± 0.003	0.9598 ± 0.001	0.9472 ± 0.003	1.0000 ± 0.000
	BS-Grad-U	0.9119 ± 0.006	0.9158 ± 0.005	0.8515 ± 0.012	0.7946 ± 0.006	0.9078 ± 0.006	0.9955 ± 0.001	0.8495 ± 0.006	0.9224 ± 0.004	0.9455 ± 0.003	0.9598 ± 0.001	0.9363 ± 0.004	0.9996 ± 0.000
	IS-U	0.9059 ± 0.006	0.9060 ± 0.004	0.8452 ± 0.008	0.7966 ± 0.008	0.9002 ± 0.007	0.9959 ± 0.000	0.6470 ± 0.031	0.9173 ± 0.004	0.9426 ± 0.001	0.9583 ± 0.001	0.9396 ± 0.003	0.9983 ± 0.001
	IS-Q	0.9064 ± 0.005	0.9060 ± 0.003	0.8441 ± 0.008	0.7963 ± 0.009	0.9019 ± 0.006	0.9960 ± 0.000	0.8332 ± 0.047	0.9233 ± 0.003	0.9433 ± 0.003	0.9588 ± 0.001	0.9443 ± 0.003	0.9997 ± 0.000
	IS-CART	0.9077 ± 0.006	0.9054 ± 0.005	0.8438 ± 0.008	0.7967 ± 0.008	0.9005 ± 0.007	**0.9961** ± 0.000	0.8248 ± 0.047	0.9198 ± 0.003	0.9432 ± 0.002	0.9587 ± 0.001	0.9440 ± 0.002	0.9999 ± 0.000
	IS-LGBM	0.9070 ± 0.006	0.9057 ± 0.005	0.8434 ± 0.008	0.7965 ± 0.006	0.9017 ± 0.006	0.9960 ± 0.000	0.8351 ± 0.044	0.9226 ± 0.004	0.9434 ± 0.004	0.9588 ± 0.001	0.9444 ± 0.003	0.9997 ± 0.000
	IS-Grad-U	0.9110 ± 0.004	**0.9176** ± 0.004	**0.8532** ± 0.011	0.7962 ± 0.010	**0.9094** ± 0.005	0.9950 ± 0.001	0.7049 ± 0.069	**0.9270** ± 0.005	0.9416 ± 0.003	0.9581 ± 0.001	0.9358 ± 0.003	0.9988 ± 0.000
	MS-Grad-U	0.9120 ± 0.005	0.9102 ± 0.005	0.8369 ± 0.013	0.7890 ± 0.008	0.9006 ± 0.005	0.9947 ± 0.000	0.7887 ± 0.116	0.9227 ± 0.006	**0.9476** ± 0.003	0.9513 ± 0.001	0.9368 ± 0.004	0.9998 ± 0.000
RESNET	STD	0.9054 ± 0.004	0.9008 ± 0.004	**0.8537** ± 0.010	0.7904 ± 0.005	0.8939 ± 0.004	0.9953 ± 0.001	0.7914 ± 0.107	0.9230 ± 0.005	0.9152 ± 0.009	0.9617 ± 0.001	0.9315 ± 0.004	0.9988 ± 0.001
	MinMax	0.9017 ± 0.004	0.8925 ± 0.003	0.8522 ± 0.015	0.7906 ± 0.004	0.8815 ± 0.007	0.9951 ± 0.001	0.8461 ± 0.057	0.9226 ± 0.004	0.9206 ± 0.014	0.9619 ± 0.001	0.9243 ± 0.005	0.9997 ± 0.000
	PLE	**0.9179** ± 0.005	0.9161 ± 0.006	0.8488 ± 0.012	0.7956 ± 0.011	**0.9104** ± 0.005	0.9956 ± 0.001	**0.9870** ± 0.001	0.9299 ± 0.004	0.9458 ± 0.004	**0.9634** ± 0.002	**0.9638** ± 0.002	**1.0000** ± 0.000
	BS-U	0.9126 ± 0.005	0.9136 ± 0.005	0.8522 ± 0.012	0.7912 ± 0.006	0.9076 ± 0.004	0.9948 ± 0.001	0.9679 ± 0.012	0.9222 ± 0.004	0.9461 ± 0.004	0.9599 ± 0.001	0.9545 ± 0.003	0.9999 ± 0.000
	BS-Q	0.9130 ± 0.005	0.9116 ± 0.006	0.8508 ± 0.010	0.7900 ± 0.007	0.9055 ± 0.005	0.9942 ± 0.001	0.9441 ± 0.004	0.9136 ± 0.004	0.9439 ± 0.004	0.9606 ± 0.001	0.9529 ± 0.002	1.0000 ± 0.000
	BS-CART	0.9140 ± 0.005	0.9105 ± 0.005	0.8500 ± 0.006	0.7895 ± 0.006	0.9038 ± 0.006	0.9941 ± 0.001	0.9408 ± 0.005	0.9165 ± 0.004	0.9433 ± 0.003	0.9619 ± 0.001	0.9560 ± 0.001	1.0000 ± 0.000
	BS-LGBM	0.9134 ± 0.005	0.9106 ± 0.006	0.8486 ± 0.011	0.7876 ± 0.007	0.9056 ± 0.005	0.9939 ± 0.001	0.9430 ± 0.007	0.9135 ± 0.004	0.9449 ± 0.003	0.9610 ± 0.001	0.9509 ± 0.001	1.0000 ± 0.000
	BS-Grad-U	0.9119 ± 0.006	0.9180 ± 0.005	0.8394 ± 0.016	0.7748 ± 0.016	0.9080 ± 0.003	0.9939 ± 0.001	0.9740 ± 0.007	0.9224 ± 0.003	0.9410 ± 0.003	0.9596 ± 0.001	0.9526 ± 0.003	0.9999 ± 0.000
	IS-U	0.9108 ± 0.004	0.9167 ± 0.005	0.8499 ± 0.013	0.7965 ± 0.008	0.9101 ± 0.006	0.9962 ± 0.001	0.9043 ± 0.030	0.9291 ± 0.003	0.9411 ± 0.001	0.9603 ± 0.001	0.9499 ± 0.001	0.9996 ± 0.001
	IS-Q	0.9111 ± 0.004	0.9151 ± 0.005	0.8481 ± 0.007	**0.7968** ± 0.009	0.9095 ± 0.005	**0.9964** ± 0.001	0.9403 ± 0.034	0.9328 ± 0.004	0.9431 ± 0.001	0.9608 ± 0.001	0.9514 ± 0.002	1.0000 ± 0.000
	IS-CART	0.9124 ± 0.005	0.9143 ± 0.006	0.8507 ± 0.012	0.7961 ± 0.009	0.9080 ± 0.006	0.9961 ± 0.001	0.9326 ± 0.027	0.9313 ± 0.005	0.9447 ± 0.005	0.9608 ± 0.001	0.9518 ± 0.002	1.0000 ± 0.000
	IS-LGBM	0.9116 ± 0.004	0.9159 ± 0.005	0.8492 ± 0.011	**0.7968** ± 0.010	0.9089 ± 0.005	0.9961 ± 0.001	0.9378 ± 0.031	**0.9342** ± 0.004	0.9424 ± 0.004	0.9610 ± 0.001	0.9512 ± 0.003	0.9998 ± 0.000
	IS-Grad-U	0.9111 ± 0.006	**0.9224** ± 0.004	0.8470 ± 0.013	0.7857 ± 0.010	0.9097 ± 0.004	0.9956 ± 0.000	0.7183 ± 0.091	0.9318 ± 0.004	0.9371 ± 0.003	0.9589 ± 0.001	0.9459 ± 0.003	0.9998 ± 0.000
	MS-Grad-U	0.9110 ± 0.005	0.9129 ± 0.005	0.8360 ± 0.010	0.7724 ± 0.008	0.9046 ± 0.005	0.9930 ± 0.001	0.8299 ± 0.099	0.9215 ± 0.006	**0.9470** ± 0.004	0.9495 ± 0.002	0.9453 ± 0.004	0.9993 ± 0.001
FTT	STD	0.9152 ± 0.003	0.9294 ± 0.004	0.8540 ± 0.011	0.7909 ± 0.006	0.9215 ± 0.004	0.9952 ± 0.001	**0.9715** ± 0.011	0.9234 ± 0.005	0.9073 ± 0.013	0.9663 ± 0.001	0.9324 ± 0.008	**1.0000** ± 0.000
	MinMax	0.9147 ± 0.004	0.9293 ± 0.004	0.8565 ± 0.011	0.7952 ± 0.007	0.9229 ± 0.003	0.9938 ± 0.002	0.5766 ± 0.035	**0.9257** ± 0.004	0.9181 ± 0.020	0.9666 ± 0.002	0.9250 ± 0.006	0.9989 ± 0.001
	PLE	**0.9243** ± 0.004	0.9314 ± 0.005	0.8539 ± 0.009	0.7965 ± 0.008	0.9246 ± 0.004	0.9958 ± 0.000	**0.9715** ± 0.010	0.9198 ± 0.005	**0.9469** ± 0.004	**0.9695** ± 0.001	**0.9625** ± 0.004	**1.0000** ± 0.000
	BS-U	0.9177 ± 0.004	0.9265 ± 0.008	0.8489 ± 0.008	0.7954 ± 0.007	0.9181 ± 0.005	0.9951 ± 0.001	0.8390 ± 0.051	0.9076 ± 0.002	0.9420 ± 0.005	0.9647 ± 0.001	0.9375 ± 0.004	0.9999 ± 0.000
	BS-Q	0.9187 ± 0.003	0.9233 ± 0.007	0.8480 ± 0.010	0.7925 ± 0.009	0.9170 ± 0.007	0.9942 ± 0.001	0.8025 ± 0.020	0.9061 ± 0.004	0.9420 ± 0.006	0.9664 ± 0.001	0.9415 ± 0.004	1.0000 ± 0.000
	BS-CART	0.9200 ± 0.005	0.9279 ± 0.009	0.8478 ± 0.006	0.7945 ± 0.009	0.9235 ± 0.003	0.9945 ± 0.001	0.8033 ± 0.012	0.9068 ± 0.003	0.9436 ± 0.003	0.9661 ± 0.002	0.9448 ± 0.007	1.0000 ± 0.000
	BS-LGBM	0.9177 ± 0.004	0.9243 ± 0.005	0.8483 ± 0.008	0.7937 ± 0.007	0.9183 ± 0.007	0.9941 ± 0.001	0.8067 ± 0.024	0.9086 ± 0.005	0.9425 ± 0.004	0.9673 ± 0.001	0.9421 ± 0.001	1.0000 ± 0.000
	BS-Grad-U	0.9208 ± 0.006	0.9292 ± 0.003	0.8504 ± 0.010	0.7962 ± 0.009	0.9244 ± 0.003	0.9935 ± 0.003	0.8885 ± 0.044	0.9096 ± 0.005	0.9452 ± 0.004	0.9665 ± 0.002	0.9528 ± 0.010	0.9986 ± 0.002
	IS-U	0.9201 ± 0.004	0.9311 ± 0.005	0.8528 ± 0.012	0.7986 ± 0.008	0.9266 ± 0.004	0.9958 ± 0.001	0.8535 ± 0.022	0.9237 ± 0.005	0.9387 ± 0.007	0.9675 ± 0.002	0.9411 ± 0.004	1.0000 ± 0.000
	IS-Q	0.9209 ± 0.004	0.9322 ± 0.005	0.8539 ± 0.009	0.7978 ± 0.008	0.9263 ± 0.004	**0.9959** ± 0.000	0.8500 ± 0.062	0.9238 ± 0.007	0.9445 ± 0.005	0.9682 ± 0.001	0.9473 ± 0.002	1.0000 ± 0.000
	IS-CART	0.9197 ± 0.004	**0.9339** ± 0.006	0.8537 ± 0.011	0.7986 ± 0.008	0.9266 ± 0.004	0.9958 ± 0.001	0.8663 ± 0.021	0.9214 ± 0.009	0.9435 ± 0.005	0.9683 ± 0.001	0.9483 ± 0.005	1.0000 ± 0.000
	IS-LGBM	0.9207 ± 0.004	0.9324 ± 0.005	0.8533 ± 0.007	0.7972 ± 0.008	0.9253 ± 0.004	0.9953 ± 0.001	0.8810 ± 0.066	0.9252 ± 0.007	0.9437 ± 0.006	0.9680 ± 0.002	0.9480 ± 0.002	1.0000 ± 0.000
	IS-Grad-U	0.9208 ± 0.005	0.9326 ± 0.006	**0.8566** ± 0.014	**0.8001** ± 0.009	**0.9275** ± 0.004	0.9956 ± 0.000	0.8770 ± 0.041	0.9237 ± 0.010	0.9460 ± 0.004	0.9675 ± 0.001	0.9533 ± 0.013	1.0000 ± 0.000
	MS-Grad-U	0.9202 ± 0.005	0.9264 ± 0.005	0.8470 ± 0.008	0.7937 ± 0.006	0.9224 ± 0.005	0.9941 ± 0.000	0.9149 ± 0.034	0.9102 ± 0.007	0.9455 ± 0.004	0.9642 ± 0.001	0.9417 ± 0.005	0.9999 ± 0.000

Table 12: Classification results for $m = 30$. Mean AUC ($\uparrow$) ± standard deviation over 5-fold cross-validation. For multiclass datasets, AUC corresponds to weighted one-vs-rest ROC-AUC. Dataset and preprocessing abbreviations are given in Tables 3 and 2 respectively. Bold indicates the highest AUC for each dataset within each backbone.

Method	m=5	10	15	20	25	30	35	40	45	50
Std					0.0663 ± 0.0075					
MinMax					0.0725 ± 0.0100					
PLE$_{adp}^{50}$					0.0474 ± 0.0015					
PLE	0.0625 ± 0.0020	0.0592 ± 0.0029	0.0505 ± 0.0024	0.0491 ± 0.0011	0.0491 ± 0.0010	0.0485 ± 0.0010	0.0473 ± 0.0012	0.0476 ± 0.0012	0.0473 ± 0.0010	0.0472 ± 0.0014
BS-U	0.0499 ± 0.0012	0.0474 ± 0.0015	0.0467 ± 0.0019	0.0463 ± 0.0013	0.0460 ± 0.0020	0.0465 ± 0.0018	0.0459 ± 0.0013	0.0463 ± 0.0012	0.0460 ± 0.0013	0.0462 ± 0.0016
BS-Q	0.0510 ± 0.0012	0.0479 ± 0.0017	0.0477 ± 0.0017	0.0474 ± 0.0013	0.0472 ± 0.0018	0.0473 ± 0.0016	0.0472 ± 0.0014	0.0476 ± 0.0014	0.0474 ± 0.0016	0.0478 ± 0.0016
BS-CART	0.0507 ± 0.0006	0.0473 ± 0.0010	0.0465 ± 0.0016	0.0461 ± 0.0018	0.0461 ± 0.0019	0.0456 ± 0.0014	0.0457 ± 0.0013	0.0457 ± 0.0010	0.0459 ± 0.0013	0.0460 ± 0.0014
BS-LGBM	0.0504 ± 0.0013	0.0484 ± 0.0017	0.0471 ± 0.0018	0.0473 ± 0.0019	0.0474 ± 0.0019	0.0472 ± 0.0014	0.0472 ± 0.0015	0.0473 ± 0.0013	0.0474 ± 0.0012	0.0474 ± 0.0014
BS-Grad-U	0.0505 ± 0.0015	0.0478 ± 0.0010	0.0470 ± 0.0018	0.0465 ± 0.0016	0.0467 ± 0.0019	0.0462 ± 0.0017	0.0463 ± 0.0014	0.0462 ± 0.0013	0.0463 ± 0.0014	0.0464 ± 0.0016
IS-U	0.0509 ± 0.0019	0.0499 ± 0.0023	0.0483 ± 0.0013	0.0480 ± 0.0020	0.0471 ± 0.0009	0.0478 ± 0.0021	0.0474 ± 0.0015	0.0472 ± 0.0015	0.0471 ± 0.0018	0.0471 ± 0.0018
IS-Q	0.0515 ± 0.0017	0.0515 ± 0.0018	0.0502 ± 0.0012	0.0494 ± 0.0017	0.0501 ± 0.0015	0.0499 ± 0.0018	0.0498 ± 0.0014	0.0498 ± 0.0017	0.0499 ± 0.0016	0.0500 ± 0.0016
IS-CART	0.0515 ± 0.0020	0.0500 ± 0.0015	0.0485 ± 0.0016	0.0475 ± 0.0012	0.0471 ± 0.0010	0.0471 ± 0.0014	0.0468 ± 0.0010	0.0466 ± 0.0014	0.0467 ± 0.0015	0.0468 ± 0.0016
IS-LGBM	0.0510 ± 0.0022	0.0510 ± 0.0021	0.0497 ± 0.0019	0.0495 ± 0.0018	0.0491 ± 0.0020	0.0490 ± 0.0027	0.0488 ± 0.0020	0.0489 ± 0.0021	0.0491 ± 0.0020	0.0493 ± 0.0019
IS-Grad-U	0.0528 ± 0.0015	0.0509 ± 0.0018	0.0494 ± 0.0013	0.0486 ± 0.0020	0.0492 ± 0.0018	0.0481 ± 0.0018	0.0482 ± 0.0017	0.0481 ± 0.0018	0.0483 ± 0.0017	0.0485 ± 0.0016
MS-U	0.0507 ± 0.0028	0.0528 ± 0.0046	0.0563 ± 0.0052	0.0526 ± 0.0053	0.0567 ± 0.0088	0.0614 ± 0.0022	0.0592 ± 0.0031	0.0566 ± 0.0060	0.0559 ± 0.0067	0.0561 ± 0.0054
MS-Q	0.0511 ± 0.0020	0.0520 ± 0.0017	0.0520 ± 0.0029	0.0513 ± 0.0048	0.0512 ± 0.0059	0.0536 ± 0.0092	0.0530 ± 0.0033	0.0521 ± 0.0030	0.0519 ± 0.0030	0.0519 ± 0.0028
MS-CART	0.0521 ± 0.0021	0.0525 ± 0.0005	0.0564 ± 0.0041	0.0552 ± 0.0066	0.0611 ± 0.0025	0.0600 ± 0.0042	0.0608 ± 0.0052	0.0593 ± 0.0048	0.0594 ± 0.0042	0.0595 ± 0.0038
MS-LGBM	0.0513 ± 0.0023	0.0554 ± 0.0057	0.0505 ± 0.0016	0.0519 ± 0.0029	0.0483 ± 0.0023	0.0534 ± 0.0080	0.0535 ± 0.0077	0.0514 ± 0.0022	0.0517 ± 0.0013	0.0524 ± 0.0010
MS-Grad-U	0.0534 ± 0.0032	0.0494 ± 0.0024	0.0487 ± 0.0020	0.0473 ± 0.0021	0.0479 ± 0.0017	0.0469 ± 0.0016	0.0473 ± 0.0020	0.0472 ± 0.0020	0.0474 ± 0.0027	0.0478 ± 0.0022

Table 13: Sensitivity to encoding resolution on the synthetic regression task. NRMSE (mean ± std over 5 seeds; lower is better) for varying encoding resolution $m \in \{5, 10, 15, 20, 25, 30, 35, 40, 45, 50\}$, corresponding to the number of bins or basis functions. Preprocessing abbreviations are given in Table 2.

(a) $\eta_a = 0.00001$

(b) $\eta_a = 0.00005$

(c) $\eta_a = 0.0001$

(d) $\eta_a = 0.0002$

Figure 9: Effect of knot learning rate on knot relocation during training. Learned knot trajectories for the informative feature under the learnable-knot B-spline variant BS-Grad-U, shown for increasing knot learning rates $\eta_a \in \{0.00001, 0.00005, 0.0001, 0.0002\}$. All panels use the same synthetic regression setup and training configuration, differing only in the knot learning rate. Smaller values of η_a lead to limited knot movement, whereas larger values produce more pronounced relocation during training. Details of BS-Grad-U and the appendix setup are provided in Appendix J.1.