Learning to Guide and to Be Guided in the Architect-Builder Problem

Abstract

We are interested in interactive agents that learn to coordinate, namely, a *builder* – which performs actions but ignores the goal of the task – and an *architect* which guides the builder towards the goal of the task. We define and explore a formal setting where artificial agents are equipped with mechanisms that allow them to simultaneously learn a task while at the same time evolving a shared communication protocol. Ideally, such learning should only rely on high-level communication priors and be able to handle a large variety of tasks and meanings while deriving communication protocols that can be reused across tasks. The field of Experimental Semiotics has shown the extent of human proficiency at learning from a priori unknown instructions meanings. Therefore, we take inspiration from it and present the Architect-Builder Problem: an asymmetrical setting in which an architect must learn to guide a builder towards constructing a specific structure. The architect knows the target structure but cannot act in the environment and can only send arbitrary messages to the builder. The builder on the other hand can act in the environment but has no knowledge about the task at hand and must learn to solve it relying only on the messages sent by the architect. Crucially, the meaning of messages is initially not defined nor shared between the agents but must be negotiated throughout learning. Under these constraints, we propose Architect-Builder Iterated Guiding (ABIG), a solution to the Architect-Builder Problem where the architect leverages a learned model of the builder to guide it while the builder uses self-imitation learning to reinforce its guided behavior. To palliate to the non-stationarity induced by the two agents concurrently learning, ABIG structures the sequence of interactions between the agents into interaction frames. We analyze the key learning mechanisms of ABIG and test it in a 2-dimensional instantiation of the Architect-Builder Problem where tasks involve grasping cubes, placing them at a given location, or building various shapes. In this environment, ABIG results in a low-level, high-frequency, guiding communication protocol that not only enables an architect-builder pair to solve the task at hand, but that can also generalize to unseen tasks.

1 Introduction

Humans are notoriously successful at teaching – and learning from – each others. This enables skills and knowledge to be shared and passed along generations, being progressively refined towards mankind's current state of proficiency. People can teach and be taught in situations where there is no shared language and very little common ground, such as a parent teaching a baby how to stack blocks during play. Experimental Semiotics (Galantucci & Garrod, 2011), a line of work that studies the forms of communication that people develop when they cannot use pre-established ones, reveals that humans can even teach and learn without direct reinforcement signal, demonstrations or a shared communication protocol. Vollmer et al. (2014) for example investigate a co-construction (CoCo) game experiment where an architect must rely only on arbitrary instructions to guide a builder toward constructing a structure. In this experiment, both the task of building the structure and the meanings of the instructions – through which the architect guides the builder – are simultaneously learned throughout interactions. Such flexible teaching – and learning – capabilities are essential to autonomous artificial agents if they are to master an increasing number of skills without extensive human supervision. As a first step toward this research direction, we draw inspiration

from the CoCo game and propose the *Architect-Builder Problem* (ABP): an interactive learning setting that models agents' interactions with *Markov Decision Processes* (Puterman, 2014) (MDPs). In the ABP learning has to occur in a social context through observations and communication, in the absence of direct imitation or reinforcement (Bandura & Walters, 1977). Specifically, the constraints of the Architect-Builder Problem are: (1) the builder has absolutely no knowledge about the task at hand (no reward and no prior on the set of possible tasks), (2) the architect can only interact with the builder through communication signals (cannot interact with the environment or provide demonstrations), and (3) the communication signals have no pre-defined meanings (nor belong to a set of known possible meanings). (1) sets this work apart from reinforcement learning and even multi-agent reinforcement learning where explicit rewards are available to all the agents. (2) implies the absence of tele-operation or third-person demonstrations and thus distinguishes the ABP from imitation and inverse reinforcement learning on expert demonstrations. Finally, (3) prevents the architect from relying on a fixed communication protocol since the meanings of instructions must be negotiated. This contrasts the Architect-Builder Problem with *Human-Robot Interaction* (HRI) (Goodrich & Schultz, 2008) and work interested in "a learner trying to figure out what a teacher wants them to do" (Grizou et al., 2013; Cederborg & Oudeyer, 2014). Indeed, most work in HRI considers that the teacher (i.e. the human) is fixed, in the sense that it does not adapt to the learner and uses pre-defined instructions meanings that the learner must figure out. In our ABP formulation however, the architect is dynamic and, as interactions unfold, must learn to best guide a learning builder by tuning the meanings of instructions according to the builder's reactions.

With all these constraints in mind, we propose Architect Builder Iterated Guiding (ABIG), an algorithmic solution to ABP when both agents are AIs. ABIG is inspired by the field of experimental semiotics and relies on two high-level interaction priors: *shared intent* and *interaction frames*. Shared intent refers to the fact that, although the builder ignores the objective of the task to fulfill, it will assume that its objective is aligned with the architect's. This assumption is characteristic of cooperative tasks and shown to be a necessary condition for the emergence of communication both in practice (Foerster et al., 2016; Cao et al., 2018) and in theory (Crawford & Sobel, 1982). Specifically, the builder should assume that the architect is guiding it towards a shared objective. Knowing this, the builder must reinforce the behavior it displays when guided by the architect. We show that the builder can efficiently implement this by using imitation learning on its own guided behavior. Because the builder imitates itself, we call it self-imitation learning. The notion of *interaction frames* (also called *pragmatic frames*) states that agents that interact in sequence can more easily interpret the interaction history (Bruner, 1985; Vollmer et al., 2016). In ABIG, we consider two distinct interaction frames. These are stationary which means that when one agent learns, the other agent's behavior is fixed. During the first frame (the modelling frame), the builder is fixed and the architect learns a model of the builder's message-conditioned behavior. During the second frame (the guiding frame), the architect is fixed and the builder learns to be guided via self-imitation learning.

We show that ABIG results in a low-level, high-frequency, guiding communication protocol that not only enables an architect-builder pair to solve the task at hand, but can also be used to solve unseen tasks. **Our contributions are:**

- The formulation of the Architect-Builder Problem (ABP), an interactive learning setting to investigate the mechanisms by which artificial agents can simultaneously learn to solve a task and derive a communication protocol.
- Architect-Builder Iterated Guiding (ABIG), an algorithmic solution to the ABP.
- An analysis of ABIG's key learning mechanisms.
- An evaluation of ABIG on a construction environment where we show that ABIG agents evolve communication protocols that generalize to unseen harder tasks.
- A detailed analysis of ABIG's learning dynamics and impact on the mutual information between messages and actions (in the Supplementary Material).

2 PROBLEM DEFINITION

The Architect-Builder Problem. We consider a multi-agent setup composed of two agents: an architect and a builder. Both agents observe the environment state s but only the architect knows the goal at hand. The architect cannot take actions in the environment but receives the environmental

reward r whereas the builder does not receive any reward and has thus no knowledge about the task at hand. In this asymmetrical setup, the architect can only interact with the builder through a communication signal m sampled from its policy $\pi_A(m|s)$. These messages, that have no a priori meanings, are received by the builder which acts according to its policy $\pi_B(a|s, m)$. This makes the environment transition to a new state s' sampled from $P_E(s'|s, a)$ and the architect receives reward r'. A sketch of the problem is provided in Figure 1(a) while the overall architect-builder-environment interaction diagram is given in Figure 1(b).

(a)   (b)

Figure 1: (a) **Sketch of the Architect-Builder Problem.** The architect must learn how to use messages to guide the builder while the builder needs to learn to make sense of the messages in order to be guided by the architect. (b) **Interaction diagram between the agents and the environment in the Architect-Builder Problem.** The architect communicates messages (m) to the builder. Only the builder can act (a) in the environment. The builder conditions its action on the message sent by the builder ($\pi_B(a|s, m)$). The builder never perceives any reward from the environment.

BuildWorld. We conduct our experiments in *BuildWorld*. BuildWorld is a 2D construction grid-world of size $(w \times h)$. At the beginning of an episode, the agent and N_b blocks are spawned at different random locations. The agent can navigate in this world and grasp blocks by activating its gripper while on a block. More specifically, the agent has a discrete action space $\mathcal{A}$ of size 6: the first four actions control the direction of navigation (North, South, East, West); the fifth action toggles the gripper (grasp/drop) and the last one is a "do nothing" action. At each time step, the agent observes its position in the grid, its gripper state as well as the position of all the blocks and if they are grasped. The dimensionality of the state space is therefore $|\mathcal{S}| = 3 + 3N_b$.

Tasks. BuildWorld contains 4 different training tasks: 1) 'Grasp': The agent must grasp any of the blocks; 2) 'Place': The agent must place any block at a specified location in the grid; 3/4) 'H-Line/V-line': The agent must place all the blocks in a horizontal/vertical line configuration. BuildWorld also has a harder fifth testing task, '6-blocks-shapes', that consists of more complex configurations and that is used to challenge an algorithm's transfer abilities. For all tasks, rewards are sparse and only given when the task is completed.

This environment can be used to encapsulate the interactive learning challenge of ABP while removing the need for complex perception or locomotion. In the Reinforcement Learning (RL) setting, where the agent that acts in the environment is also the one that receives the ground-truth reward, this environment would not be very impressive. However, it remains to be shown that the tasks can be solved in the challenging learning setting of ABP (with a reward-less builder and an action-less architect).

Communication. The architect guides the builder by sending messages m. The messages are one-hot vectors of size $|\mathcal{V}|$ ranging from 2 to 72. We study the impact of this parameter in Suppl. Section B.3.

Additional Assumptions. In order to focus on the architect-builder interactions, the architect has access to $P_E(s'|s, a)$ and to the reward function $r(s, a)$ of the goal at hand. This assumes that, if the architect were to act in the environment instead of the builder, it would be able to use planning to quickly figure out how to solve the task. Removing this assumption would correspond to an architect that learns to guide a builder while at the same time trying to figure out how to solve the task. This is a much more challenging set-up and is left for future work.

(a) Architect MDP (b) Implicit Architect MDP

(c) Builder MDP (d) Implicit Builder MDP

Figure 2: Agent's Markov Decision Processes. Highlighted regions refer to MDP coupling. (a) The architect's transitions and rewards are conditioned by the builder's policy π_B. (b) Architect's MDP where transition and reward models implicitly account for builder's behavior. (c-d) The builder's transition model depends on the architect's message policy π_A. The builder's learning signal r is unknown.

3 ABIG: ARCHITECT-BUILDER ITERATED GUIDING

3.1 ANALYTICAL DESCRIPTION

Agents-MDPs. In the Architect-Builder Problem, agents are operating in different, yet coupled, MDPs. Those MDPs depend on their respective point of view (see Figure 2). From the point of view of the architect, messages are actions that influence the next state as well as the reward (see Figure 2 (a)). The architect knows the environment transition function $P_E(s'|s,a)$ and $r(s,a)$, the true reward function associated with the task that does not depend explicitly on messages. It can thus derive the effect of its messages on the builder's actions that drive the reward and the next states (see Figure 2 (b)). On the other hand, the builder's state is composed of the environment state and the message, which makes estimating state transitions challenging as one must also capture the message dynamics (see Figure 2 (c)). Yet, the builder can leverage its knowledge of the architect picking messages based on the current environment state. The equivalent transition and reward models, when available, are given below (see derivations in Suppl. Section A).

$$\left.\begin{aligned} P_A(s'|s,m) &= \sum_{a\in\mathcal{A}} \tilde{\pi}_B(a|s,m)P_E(s'|a,s) \\ r_A(s,m) &= \sum_{a\in\mathcal{A}} \tilde{\pi}_B(a|s,m)r(s,a) \end{aligned}\right\} \quad \text{with} \quad \tilde{\pi}_B(a|s,m) \triangleq P(a|s,m) \qquad (1)$$

$$P_B(s',m'|s,m,a) = \tilde{\pi}_A(m'|s')P_E(s'|s,a) \quad \text{with} \quad \tilde{\pi}_A(m'|s') \triangleq P(m'|s') \qquad (2)$$

where subscripts A and B refer to the architect and the builder, respectively. $\tilde{x}$ denotes that x is unknown and must be approximated. From the builder's point of view, the reward – denoted $\tilde{r}$ – is unknown. This prevents the use of classical reinforcement learning algorithms.

Shared Intent and Interaction Frames. It follows from Eq. (1) that, provided that it can approximate the builder's behavior, the architect can compute the reward and transition models of its MDP. It can then use these to derive an optimal message policy π_A^* that would maximize its objective:

$$\pi_A^* = \underset{\pi_A}{\mathrm{argmax}}\, G_A = \underset{\pi_A}{\mathrm{argmax}}\, \mathbb{E}[\sum_t \gamma^t r_{A,t}] \qquad (3)$$

$\gamma \in [0,1]$ is a discount factor and the expectation can be thought of in terms of π_A, P_A and the initial state distribution. However, the expectation can also be though in terms of the corresponding trajectories $\tau \triangleq \{(s,m,a,r)_t\}$ generated by the architect-builder interactions. In other words, when using π_A^* to guide the builder, the architect-builder pair generates trajectories that maximizes G_A. The builder has no reward signal to maximize, yet, it relies on a shared intent prior and assumes

that its objective is the same as the architect's one:

$$G_B = G_A = \mathbb{E}_\tau[\sum_t \gamma^t r_{A,t}] = \mathbb{E}_\tau[\sum_t \gamma^t \tilde{r}_t] \tag{4}$$

where the expectations are taken with respect to trajectories τ of architect-builder interactions. Therefore, under the shared intent prior, architect-builder interactions where the architect uses π_A^* to maximize G_A also maximize G_B. This means that the builder can interpret these interaction trajectories as demonstrations that maximize its unknown reward function $\tilde{r}$. Consequently, the builder can reinforce the desired behavior – towards which the architect guides it – by performing self-Imitation Learning[1] on the interaction trajectories τ.

Note that in Eq. (1), the architect's models can be interpreted as expectations with respect to the builder's behavior. Similarly, the builder's objective depends on the architect's guiding behavior. This makes one agent's MDP highly non-stationary and the agent must adapts its behavior if the other agent's policy changes. To palliate to this, agents rely on interaction frames which means that, when one agent learns, the other agent's policy is fixed to restore stationarity.

3.2 Practical Algorithm

Figure 3: Architect-Builder Iterated Guiding. Agents iteratively interact through two frames: the modelling and guiding frames. During each of the frames, one agent collects data and improves its policy while the other agent's behavior is fixed.

ABIG iteratively structures the interactions between a builder-architect pair into interaction frames. Each iteration starts with a *modelling frame* during which the architect learns a model of the builder. Directly after, during the *guiding frame*, the architect leverages this model to produce messages that guide the builder. On its side, the builder stores the guiding interactions to train and refine its policy π_B. The interaction frames are described below. The algorithm is illustrated in Figure 3 and the pseudo-code is reported in **Algorithm 1 in Suppl. Section A.2**.

Modelling Frame. The architect records a data-set of interactions $\mathcal{D}_A \triangleq \{(s, m, a, s')_t\}$ by sending random messages m to the builder and observing its reaction. After collecting enough interactions, the architect learns a model of the builder $\tilde{\pi}_B$ using *Behavioral Cloning* (BC) (Pomerleau, 1991).

Guiding Frame. During the guiding frame, the architect observes the environment states s and produces messages so as to maximize its return (see Eq. 3). The policy of the architect is a Monte Carlo Tree Search Algorithm (MCTS) (Kocsis & Szepesvári, 2006) that searches for the best message

---

[1]not to be confused with Oh et al. (2018) which is an off-policy actor-critic algorithm promoting exploration in single-agent Reinforcement Learning.

by simulating the reaction of the builder using $\tilde{a} \sim \tilde{\pi}_B(\cdot|m, s)$ alongside the dynamics and reward models. During this frame, the builder stores the interactions in a buffer $\mathcal{D}_B \triangleq \{(s, m, a, s')_t\}$. At the end of the guiding frame, the builder self-imitates by updating its policy π_B with BC on $\mathcal{D}_B$.

Practical Considerations. All models are parametrized by two-hidden layer 126-units feedforward networks with ReLu activation functions. BC minimizes the cross-entropy loss with Adam optimizer (Kingma & Ba, 2015). Networks are re-initialized before each BC training. The architect's MCTS uses Upper-Confidence bound for Trees and relies on heuristics rather than Monte-Carlo rollouts to estimate the value of states. For more details about training, MCTS and hyper-parameters please see Suppl. Section A.2.

The resulting method (ABIG) is general and can handle a variety of tasks while not restricting the kind of communication protocol that can emerge. Indeed, it only relies on a few high-level priors, namely, the architect's access to environment models, shared intent and interaction frames. In addition to ABIG we also investigate two control settings:

- ABIG *-no-intent* - The builder interacts with an architect that disregards the goal and therefore sends random messages during training. At evaluation, the architect has access to the exact model of the builder ($\tilde{\pi}_B = \pi_B$) and leverages it to guide it towards the evaluation goal (the architect no longer disregards the goal).
- *random* - The builder takes random actions.

The comparison between ABIG and ABIG-no-intent measures the impact of doing self-imitation on guiding versus on non-guiding trajectories. The random baseline is used to provide a performance lower bound that indicates the task's difficulty.

3.3 UNDERSTANDING THE LEARNING DYNAMICS

Architect-Builder Iterated Guiding relies on two steps. First, the architect selects *favorable* messages, i.e. messages that maximize the likelihood of the builder picking optimal actions with respect to the architect's reward. Then, the builder does self-imitation and reinforces the guided behavior by maximizing the likelihood of the corresponding messages-actions sequence under its policy. The message-to-action associations (or preferences) are encoded in the builder's policy $\pi_B(a|s, m)$. Maximum likelihood assumes that actions are initially equiprobable for a given message. Therefore, actions under a message that is not present in the data-set ($\mathcal{D}_B$) remains so. In other words, if the builder never observes a message, it assumes that this message is equally associated with all the possible actions. This enables the builder to *forget* past message-to-action associations that are not used – and thus not reinforced – by the architect. In practice, initial uniform likelihood is ensured by resetting the builder's policy network before each self-imitation. The architect can leverage the forget mechanism to erase unfavorable associations until a favorable one emerges. Such favorable associations can then be reinforced by the architect-builder pair until it is made deterministic. The *reinforcement* process of favorable associations is also enabled by the self-imitation phase. Indeed, for a given message m, the self-imitation objective for π on a data-set $\mathcal{D}$ collected using π is:

$$J(m, \pi) = -\sum_{a \sim \mathcal{D}} \log \pi(a|m) \approx \mathbb{E}_{a \sim \pi(\cdot|m)}[-\log \pi(a|m)] \approx H[\pi(\cdot|m)] \tag{5}$$

where H stands for the entropy of a distribution. Therefore, maximizing the likelihood in this case results in minimizing the entropy of $\pi(\cdot|m)$ and thus reinforces the associations between messages and actions. Using these mechanisms the architect can adjust the policy of the builder until it becomes *controllable*, i.e. deterministic (strong preferences over actions for a given message) and flexible (varied preferences across messages). Conversely, in the case of ABIG-no-intent, the architect does not guide the builder and simply sends messages at random. Favorable and unfavorable messages are thus sampled alike which prevents the forget mechanism to undo unfavorable message-to-action associations. Consequently in that case, self-imitation tends to simply reinforce initial builder's preferences over actions making the controllability of the builder policy depend heavily on the initial preferences. We illustrate the above learning mechanisms in Suppl. Section A.3 by applying ABIG to a simple instantiation of the Architect-Builder Problem. Figure 7 and Figure 9 confirm that ABIG uses the forget and reinforcement mechanisms to circumvent the unfavorable initial conditions while ABIG-no-intent simply reinforces them. Eventually, Figure 9 reports that ABIG

always reaches 100% success rate regardless of the initial conditions while ABIG-no-intent success rate depends on the initial preferences (only 3% when they are unfavorable).

Interestingly, the emergent learning mechanisms discussed here are reminiscent of the amplification and self-enforcement of random fluctuations in naming games (Steels, 1995). In naming games however, the self-organisation of vocabularies are driven by each agent maximizing its communicative success whereas in our case the builder has no external learning signal and simply self-imitates.

4 RELATED WORK

This work is inspired by experimental semiotics (Galantucci & Garrod, 2011) and more specifically Vollmer et al. (2014) that studied the Architect-Builder Problem (ABP) with human subjects as a key step towards Human-Robot Interaction (HRI). Here we take a complementary approach by defining and investigating solutions to the ABP where both agents are AIs.

Recent work (Woodward et al., 2020; Roy et al., 2020; Ndousse et al., 2021), have investigated how RL agents trained in the presence of other agents can leverage the behaviors they observe to improve learning. In these settings, the behaviors of other agents is used to build useful representation or gain information but the main learning signal is still a ground truth reward. Ahilan & Dayan (2019) investigate a Hierarchical Learning setting where a manager agent sets sub-goals to worker agents in order to maximize its return. Workers are pre-trained goal-conditioned RL agents. They are fine-tuned when the RL manager selects their goal thanks to the associated goal-conditioned ground-truth reward. This can be seen as a simplification of the ABP where the meanings of messages are pre-defined and consists of sub-tasks the builder knows how to perform. In our case however, meanings are not pre-defined and the builder does not have access to any ground-truth reward. It can only rely on the messages it observes from its interactions with the architect.

Inverse Reinforcement Learning (IRL) (Ng et al., 2000) and Imitation Learning (IL) (Pomerleau, 1991) have been investigated for HRI when it is challenging to specify a reward function. Instead of defining rewards, IRL and IL rely on expert demonstrations. Hadfield-Menell et al. (2016) argue that learning from expert demonstrations is not always optimal and investigate how to produce instructive demonstrations to best teach an apprentice. Crucially, the expert is aware of the mechanisms by which the apprentice learns, namely RL on top of IRL. This allows the expert to assess how its demonstrations influence the apprentice policy, effectively reducing the problem to a single agent POMDP. In our case however, the architect and the builder do not share the same action space which prevents the architect from producing demonstrations. In addition, the architect ignores the builder's learning process which makes the simplification to a single agent teacher problem impossible.

In essence, the ABP is closest to the Human-Robot Interaction framework where "a learner must figure out what a teacher wants it to do" (Cederborg & Oudeyer, 2014). Grizou et al. (2013), in particular, devise a learning algorithm enabling a robot to simultaneously learn a task and the meaning of human instructions. Yet, Grizou et al. (2013) investigate a single-agent problem by considering a fixed teacher. The fact that the teacher can use a fixed protocol, without adapting it to the learner, is enabled by the amount of prior knowledge given to the robot. Indeed, in Grizou et al. (2013) the robot knows the set of possible mappings between instructions and their meanings as well as the set of possible tasks. This enables the robot to estimate the likelihood of each instructions meanings for each possible task. The most likely pair is then selected as the task at hand and instructions meanings. In our case however, the builder has no a priori knowledge of the set of possible meanings or tasks and therefore using such procedure would be unfeasible.

Our BuildWorld tasks are reminiscent of the GridLU environment proposed by Bahdanau et al. (2019) to analyze reward modelling in language-conditioned learning. However, their setting is fundamentally different to ours as it investigates single agent goal-conditioned Imitation Learning where goals are predefined episodic linguistic instructions labelling expert demonstrations. Our Architect-Builder Problem formulation is related to the Minecraft Collaborative Building Task (Narayan-Chen et al., 2019); however, they do not tackle the problem from an emergent communication perspective. Rather, they focus on the problem of generating architect utterances by leveraging a human-human dialogues corpus to learn pre-established meanings expressed in natural language. Conversely, we consider the case where both agents are AIs and must evolve the meanings of messages while solving the task without relying on any form of demonstration.

5 RESULTS

In the following sections, success rates (sometimes referred as scores) are averaged over 10 random seeds and error bars are ± 2SEM with SEM the Standard Error of the Mean. If not stated otherwise, the grid size is (5×6), contains three blocks ($N_b = 3$) and the vocabulary size is $|\mathcal{V}| = 18$.

ABIG's learning performances. We apply ABIG to the four learning tasks of BuildWorld and compare it with the two control settings: ABIG-no-intent (no guiding during training) and random (builder takes random actions). Figure 4 reports the mean success rate on the four tasks defined in Section 2. First, we observe that ABIG significantly outperforms the control conditions on all tasks. Second, we notice that on the simpler 'grasp' task ABIG-no-intent achieves a satisfactory mean score of 0.77 ± 0.03. This is consistent with the learning dynamic analysis provided in Sup. Section A.3 that shows that, in favorable settings, a self-imitating builder can develop a reasonably controllable policy (defined in Section 3.3) even if it learns on non-guiding trajectories. Nevertheless, when the tasks get more complicated and involve placing objects or drawing lines, the performances of ABIG-no-intent drop significantly whereas ABIG continues to achieve high success rates (> 0.8). This demonstrates that ABIG enables a builder-architect pair to successfully agree on a communication protocol that makes the builder's policy controllable and enables the architect to efficiently guide it.

Figure 4: Methods performances (stars indicate significance with respect to ABIG model according to Welch's t-test with null hypothesis $\mu_1 = \mu_2$, at level $\alpha = 0.05$). ABIG outperforms control baselines on all goals.

ABIG's transfer performances. Building upon previous results, we propose to study whether a learned communication protocol can transfer to new tasks. The architect-builder pairs are trained on a single task and then evaluated without retraining on the four tasks. In addition, we include 'all-goals': a control setting in which the builder learns a single policy by being guided on all four goals during training. Figure 5 shows that, on all training tasks except 'grasp', ABIG enables a transfer performance above 0.65 on all testing tasks. Notably, training on 'place' results in a robust communication protocol that can be used to solve the other tasks with a success rate above 0.85, being effectively equivalent as training on 'all-goals' directly. This might be explained by the fact that placing blocks at specified locations is an atomic operation required to build lines.

Figure 5: ABIG transfer performances without retraining depending on the training goal. ABIG agents learn a transferable communication protocol that can be used to solve new tasks. The highest transfer performances are achieved when training on 'place'.

Challenging ABIG's transfer abilities. Motivated by ABIG's transfer performances, we propose to train it on the 'place' task in a bigger grid (6×6) with $N_b = 6$ and $|\mathcal{V}| = 72$. Then, with-

out retraining, we evaluate it on the '6-block-shapes' task[2] that consists in constructing the shapes given in Figure 6. The training performance on 'place' is 0.96 ± 0.02 and the transfer performance on the '6-block-shapes' is 0.85 ± 0.03. This further demonstrates ABIG's ability to derive robust communication protocols that can solve more challenging unseen tasks.

Figure 6: 6-block-shapes that ABIG can construct in transfer mode when trained on the 'place' task.

Additional experiments. The Supplementary Materials contains the following experiments:

- Figures 7, 8 and 9 analyse the builder's message-to-action preferences. They illustrate ABIG's learning mechanisms (forget and reinforce) and compare them to ABIG-no-intent's.
- Figure 10 displays the evolution of the builder policy's properties during learning. In particular it showcases that, as the communication protocol settles, the message-action mutual information increases to becomes greater than the state-action mutual information which is a desirable feature for the emergence of communication.
- Figure 11 reports ABIG outperforming complementary baselines.
- Figure 12 shows ABIG's performance increasing with the vocabulary size, suggesting that with more messages available, the architect can more efficiently refer to the desired action.

6 DISCUSSION AND FUTURE WORK

This work formalizes the Architect-Builder Problem (ABP) as an interactive setting where learning must occur without explicit reinforcement, demonstrations or a shared language. To tackle ABP, we propose Architect-Builder Iterated Guiding (ABIG): an algorithm allowing to learn how to guide and to be guided. ABIG is based only on two high-level priors to communication emergence (shared intent and interactions frames). ABP's general formulation allows us to formally enforce those priors during the learning process. We study their influence through ablation studies, highlighting the importance of shared intent achieved by doing self-imitation on guiding trajectories. When performed in interaction frames, this mechanism enables agents to efficiently evolve a communication protocol that allows them to solve all the tasks defined in BuildWorld. More impressively, we find that communication protocols derived on a simple task can be used to solve harder, never-seen goals.

Our approach has several limitations which open up different opportunities for further work. First, ABIG trains agents in a stationary configuration which implies doing several interaction frames. Each interaction frame involves collecting numerous transitions. Thus, ABIG is not data efficient. A challenging avenue would be to relax this stationarity constraint and have agents learn from buffers containing non-stationary data with obsolete agent behaviors. Second, the builder remains dependent on the architect's messages even at convergence. Using a Vygotskian approach (Colas et al., 2020; 2021), the builder could internalize the guidance from the architect to become autonomous in the task. This could, for instance, be achieved by having the builder learn a model of the architect's message policy once the communication protocol has converged.

Because we present the first step towards interactive agents that learn in the ABP, our method uses simple tools (feed-forward networks and self-imitation learning). It is however important to note that our proposed formulation of the ABP can support many different research directions. Experimenting with agents' models could allow for the investigation of other forms of communication. One could, for instance, include memory mechanisms in the models of agents in order to facilitate the emergence of retrospective feedback, a form of emergent communication observed in Vollmer et al. (2014). ABP is also compatible with low-frequency feedback. As a further experiment in this direction, one could penalize the architect for sending messages and assess whether a pair can converge to higher-level meanings. Messages could also be composed of several tokens in order to allow for the emergence of compositionality. Finally, our proposed framework can serve as a testbed to study the fundamental mechanisms of emergent communication by investigating the impact of high level communication priors from experimental semiotics.

---

[2]For rollouts see `https://sites.google.com/view/architect-builder-problem/`

7 ETHICS STATEMENT

This work investigates a novel interactive approach to autonomous agent learning and proposes a fundamental learning setting. This work does not directly present sensitive applications or data. While the implications of autonomous agents learning are not trivial, we do not aim here at discussing the general impact of autonomous agents. Rather, we focus on discussing how the proposed learning setting contrasts with more classical supervisions such as reward signals and demonstrations. By proposing an iterative and interactive learning setting, the Architect-Builder Problem (ABP) promotes a finer control over learned behavior than designing rewards or demonstrations. Indeed, the behavior is constantly evaluated and refined throughout learning as interactions unfold. Still, in this process it is essential to keep in mind the importance of the architect as it is the agent that judges if the learned behavior is satisfactory.

8 REPRODUCIBILITY STATEMENT

We ensure the reproducibility of the experiments presented in this work by providing our code. Additional information regarding the methods and hyper-parameters can be found in Section 3.2 and in the Suppl. Section A.2. We ensure the statistical significance of our experimental results by using 10 random seeds, reporting the standard error of the mean and using Welch's t-test. Finally, we propose complete analytical derivations in Suppl. Section A.

REFERENCES

Sanjeevan Ahilan and Peter Dayan. Feudal multi-agent hierarchies for cooperative reinforcement learning. *arXiv preprint arXiv:1901.08492*, 2019.

Dzmitry Bahdanau, Felix Hill, Jan Leike, Edward Hughes, Pushmeet Kohli, and Edward Grefenstette. Learning to understand goal specifications by modelling reward. In *International Conference on Learning Representations*, 2019.

Albert Bandura and Richard H Walters. *Social learning theory*, volume 1. Englewood cliffs Prentice Hall, 1977.

Jerome Bruner. Child's talk: Learning to use language. *Child Language Teaching and Therapy*, 1 (1):111–114, 1985.

Kris Cao, Angeliki Lazaridou, Marc Lanctot, Joel Z Leibo, Karl Tuyls, and Stephen Clark. Emergent communication through negotiation. In *International Conference on Learning Representations*, 2018.

Thomas Cederborg and Pierre-Yves Oudeyer. A social learning formalism for learners trying to figure out what a teacher wants them to do. *Paladyn: Journal of Behavioral Robotics*, 5:64–99, 2014.

Cédric Colas, Tristan Karch, Clément Moulin-Frier, and Pierre-Yves Oudeyer. Language as a Cognitive Tool: Dall-E, Humans and Vygotskian RL Agents, March 2021. URL `https://hal.archives-ouvertes.fr/hal-03159786`.

Cédric Colas, Tristan Karch, Nicolas Lair, Jean-Michel Dussoux, Clément Moulin-Frier, F Peter Dominey, and Pierre-Yves Oudeyer. Language as a cognitive tool to imagine goals in curiosity driven exploration. *NeurIPS*, 2020.

Vincent P Crawford and Joel Sobel. Strategic information transmission. *Econometrica: Journal of the Econometric Society*, pp. 1431–1451, 1982.

Jakob Foerster, Ioannis Alexandros Assael, Nando de Freitas, and Shimon Whiteson. Learning to communicate with deep multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 2137–2145, 2016.

Bruno Galantucci and Simon Garrod. Experimental semiotics: a review. *Frontiers in human neuroscience*, 5:11, 2011.

Michael A Goodrich and Alan C Schultz. *Human-robot interaction: a survey*. Now Publishers Inc, 2008.

Jonathan Grizou, Manuel Lopes, and Pierre-Yves Oudeyer. Robot learning simultaneously a task and how to interpret human instructions. In *2013 IEEE Third Joint International Conference on Development and Learning and Epigenetic Robotics (ICDL)*, pp. 1–8, 2013. doi: 10.1109/DevLrn.2013.6652523.

Dylan Hadfield-Menell, Stuart J Russell, Pieter Abbeel, and Anca Dragan. Cooperative inverse reinforcement learning. *Advances in neural information processing systems*, 29:3909–3917, 2016.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Levente Kocsis and Csaba Szepesvári. Bandit based monte-carlo planning. In *European conference on machine learning*, pp. 282–293. Springer, 2006.

Anjali Narayan-Chen, Prashant Jayannavar, and Julia Hockenmaier. Collaborative dialogue in minecraft. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 5405–5415, 2019.

Kamal K Ndousse, Douglas Eck, Sergey Levine, and Natasha Jaques. Emergent social learning via multi-agent reinforcement learning. In *International Conference on Machine Learning*, pp. 7991–8004. PMLR, 2021.

Andrew Y Ng, Stuart J Russell, et al. Algorithms for inverse reinforcement learning. In *International Conference on Machine Learning*, volume 1, pp. 2, 2000.

Junhyuk Oh, Yijie Guo, Satinder Singh, and Honglak Lee. Self-imitation learning. In *ICML*, 2018.

Dean A Pomerleau. Efficient training of artificial neural networks for autonomous navigation. *Neural computation*, 3(1):88–97, 1991.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Julien Roy, Paul Barde, Félix Harvey, Derek Nowrouzezahrai, and Chris Pal. Promoting coordination through policy regularization in multi-agent deep reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 33, pp. 15774–15785, 2020.

Luc Steels. A self-organizing spatial vocabulary. *Artificial life*, 2(3):319–332, 1995.

Anna-Lisa Vollmer, Jonathan Grizou, Manuel Lopes, Katharina Rohlfing, and Pierre-Yves Oudeyer. Studying the co-construction of interaction protocols in collaborative tasks with humans. In *4th International Conference on Development and Learning and on Epigenetic Robotics*, pp. 208–215. IEEE, 2014.

Anna-Lisa Vollmer, Britta Wrede, Katharina J Rohlfing, and Pierre-Yves Oudeyer. Pragmatic frames for teaching and learning in human–robot interaction: Review and challenges. *Frontiers in neurorobotics*, 10:10, 2016.

Mark Woodward, Chelsea Finn, and Karol Hausman. Learning to interactively learn and assist. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 2535–2543, 2020.

SUPPLEMENTARY MATERIAL

This Supplementary Material provides additional derivations, implementation details and results. More specifically:

- Section A proposes derivations, implementation details and analysis related to our method.
  - Subsection A.1 proposes the full derivation of the agents' MDP.
  - Subsection A.2 proposes our methods pseudo-code, algorithmic implementation details (for BC and MCTS), hyper-parameters and compute resources.
  - Subsection A.3 proposes analysis that explore our method's learning mechanisms.
- Section B provides additional results.
  - Subsection B.1 monitors the builder's behavior properties as training progresses.
  - Subsection B.2 compares our method to additional baselines.
  - Subsection B.3 analyses the impact of the vocabulary size on the learning performance.

A SUPPLEMENTARY METHODS

A.1 ANALYTICAL DESCRIPTION

Transition Probabilites from the architect point of view   Using the laws of total probabilities and conditional probabilities we have:

$$
\begin{aligned}
P_A(s'|s,m) &= \sum_{a\in\mathcal{A}} P(s',a|s,m) \\
&= \sum_{a\in\mathcal{A}} P(s'|a,s,m)P(a|s,m) \\
&= \sum_{a\in\mathcal{A}} P_E(s'|a,s)\tilde{\pi}_b(a|s,m)
\end{aligned}
\tag{6}
$$

Where the final equality uses the knowledge that next-states only depends on states and builder's actions.

Reward function from the architect point of view

$$
\begin{aligned}
r_A(s,m,s') &\triangleq \mathbb{E}[R|s,m,s'] \\
&= \int_{\mathbb{R}} rP(r|s,m,s')dr \\
&= \int_{\mathbb{R}} r\sum_{a\in\mathcal{A}} P(r,a|s,m,s')dr \\
&= \int_{\mathbb{R}} r\sum_{a\in\mathcal{A}} P(r|s,m,a,s')P(a|s,m,s')dr \\
&= \int_{\mathbb{R}} r\sum_{a\in\mathcal{A}} P(r|s,a,s')\tilde{\pi}_b(a|s,m)dr \\
&= \sum_{a\in\mathcal{A}} \tilde{\pi}_b(a|s,m)\int_{\mathbb{R}} rP(r|s,a,s')dr \\
&= \sum_{a\in\mathcal{A}} \tilde{\pi}_b(a|s,m)r(s,a,s')
\end{aligned}
\tag{7}
$$

Transition function from the builder point of view

$$
\begin{aligned}
P(s',m'|s,m,a) &= P(m'|s',s,m,a)P(s'|s,m,a) \\
&= P(m'|s')P(s'|s,a) \\
&= \tilde{\pi}_A(m'|s')P_E(s'|s,a)
\end{aligned}
\tag{8}
$$

A.2 PRACTICAL ALGORITHM

Algorithm 1: Architect-Builder Iterated Guiding (ABIG)

Require: randomly initialized builder policy π_B, reward function r, transition function P_E, BC
   algorithm, MCTS algorithm
   for i in range($N_{iterations}$) **do**
      MODELLING FRAME:
         for e in range($N_{collect}/2$) **do**
            Architect populates $\mathcal{D}_A$ using $m \sim$ Uniform() and observing $a \sim \pi_B(\cdot|s, m)$
         end for
         Architect learns $\tilde{\pi}_B(a|s, m)$ on $\mathcal{D}_A$ with BC
         Architect sets $\pi_A(m|s) \triangleq \text{MCTS}(r, \tilde{\pi}_B, P_E)$
         Architect flushes $\mathcal{D}_A$
      GUIDING FRAME:
         for e in range($N_{collect}/2$) **do**
            Builder populates $\mathcal{D}_B$ using π_B while guided by Architect, i.e. $m \sim \pi_A(\cdot|s)$
         end for
         Builder learns $\pi_B(a|s, m)$ on $\mathcal{D}_B$ with BC
         Builder flushes $\mathcal{D}_B$
   end for
   Architect runs one last Modelling Frame
Result: π_A, π_B

Behavioral Cloning The data-set is split into training (70%) and validation (30%) sets. If the validation accuracy does not improve during a *wait for* number of epochs the training is early stopped. For a training data-set $\mathcal{D} = \{(s, m, a)\}$ of size N the BC loss to minimize for a policy π_θ parametrized by θ is given by:

$$J(\theta) = \frac{1}{N} \sum_{\mathcal{D}} -\log \pi_\theta(a|s, m) \tag{9}$$

Monte-Carlo Tree Search In the architect's MCTS, nodes are labeled by environment's states and they are expanded by selecting messages. Selecting message m from a node with label s yields a builder action according to the architect's builder model $a \sim \tilde{\pi}_B(a|s, m)$, this sampled action in turn yields the label of the child node according to the environment's transition model $s' \sim P_E(s'|s, a)$. We repeat this process until we select a message that was never selected from the current node or we sample a next state that does not correspond to a child node yet. In both of these cases a new node has to be created. We estimate the value of the new node using an engineered heuristic that estimates the return of an optimal policy $\pi^*(a|s)$ from state s. This value is scaled down by a factor 2 to avoid overestimation: the builder's policy may not allow the architect to have it follow π^*. This estimated value for a newly created node at depth l is back-propagated as a return to parents node at depth k according to:

$$G^k = \sum_{\tau=0}^{l-1-k} \gamma^\tau r_{k+1+\tau} + \gamma^{l-k} v^l \qquad k = l, ..., 0 \tag{10}$$

where r_j is the reward collected from node at depth j to child node at depth $j+1$. From a node with label s we select messages according to the Upper Confidence Bound rule:

$$m = \underset{m}{\operatorname{argmax}} \, Q(s, m) + c\sqrt{\frac{\ln \sum_b N(s, b)}{N(s, m)}}$$
$$Q(s, m) = \frac{\sum_i G_i(s, m)}{N(s, m)} \tag{11}$$

where $N(s, m)$ is the number of times message m was selected from the node, $G_i(s, m)$ are the returns obtained from the node when selecting m and c is a constant set to $\sqrt{2}$. When the architect must choose a message from the environment state s, its policy $\pi_A(m|s)$ runs the above procedure

from a root node labeled with the current environment state s. After expanding a budget b of nodes the architect picks the best message to send according to Eq. (11) applied to the root node. It is then possible to reuse the tree for the next action selection or to discard it, if a tree is reused its maximal depth should be constrained.

Hyper-parameters

sampling temperature	samples per iteration	learning rate	number of epochs	batch size
0.5	100	0.1	1000	50

Table 1: Toy experiment hyper-parameters

budget	reuse tree	max tree depth
100	true	500

Table 2: MCTS parameters

episode len	grid size	reward	message
40	5×6 / (6 × 6)	sparse	one-hot

discount factor	episodes per iteration	vocab size	evaluation episode len
0.95	600	18 / (72)	40 / (60)

Table 3: BuildWorld parameters for 3 blocks / (for 6 blocks if different)

learning rate	number of epochs	batch-size	wait for
5×10^{-4}	1000	256	300

Table 4: Architect's BC parameters on BuildWorld for 3 blocks / (for 6 blocks if different)

learning rate	number of epochs	batch-size	wait for
1×10^{-4}	1000	256	300

Table 5: Builder's BC parameters on BuildWorld for 3 blocks / (for 6 blocks if different)

Sparse reward means that the architect receives 1 if the goal is achieved and 0 otherwise. Episodes per iterations are equally divided into the modelling and guiding frames. Only the learning rates on BuildWorld were searched over with grid-searches. For BuildWorld with 3 blocks the searched range is $[5 \times 10^{-4}, 1 \times 10^{-4}, 1 \times 10^{-5}]$ for both architect and builder (vocabulary size was fixed at 6). For 'grasp' with 6 blocks the searched range is $[1 \times 10^{-3}, 5 \times 10^{-4}, 1 \times 10^{-4}]$ for the architect and $[5 \times 10^{-4}, 1 \times 10^{-4}, 5 \times 10^{-5}]$ for the builder (vocabulary size was fixed at 72). The other hyper-parameters do not seem to have a major impact on the performance provided that:

- the MCTS hyper-parameters enable an agent that has access to the reward to solve the task.
- there is enough BC epochs to approach convergence.

Regarding the vocabulary size, the bigger the better (see experiments in Figure 12).

Computing resources A complete ABIG training can take up to 48 hours on a single modern CPU (`Intel E5-2683 v4 Broadwell @ 2.1GHz`). The presented results require approximately 700 CPU hours. For each training, the main computation cost comes from the MCTS planning during the guiding frames. The self-imitation and behavior modelling steps only account for a small fraction of the computation.

A.3 INTUITIVE EXPLANATION OF THE LEARNING DYNAMICS

To illustrate the learning mechanisms of ABIG we propose to look at the simplest instantiation of the Architect-Builder Problem: there is one state (thus it can be ignored), two messages m_1 and m_2 and two possible actions a_1 and a_2. If the builder chooses a_1 it is a loss ($r(a_1) = -1$) but choosing a_2 results in a win ($r(a_2) = 1$). Figure 7 displays several iterations of ABIG on this problem when the initial builder's policy is unfavorable (a_1 is more likely than a_2 for all the messages). During each iteration the architect selects messages in order to maximize the likelihood of the builder picking action a_2 and then the builder does self-Imitation Learning by maximizing the likelihood of the corresponding messages-actions sequence under its policy. Figure 7 shows that this process leads to forgetting unfavorable associations until a favorable association emerges and can be reinforced. On the other hand, for ABIG-no-intent in Figure 8, favorable and unfavorable messages are sampled alike which prevents the forget mechanism to undo unfavorable message-to-action associations. Consequently, initial preferences are reinforced.

Figure 7: ABIG-driven evolution of message-conditioned action probabilities (builder's policy) for a simple problem where the builder must learn to produce action a_2. Even under unfavorable initial condition the architect-builder pair eventually manages to associate a message (here m_1) with the winning action (a_2). Initial conditions are unfavorable since a_1 is more likely than a_2 for both messages. ($i = 0$) Given the initial conditions, the architect only sends message m_1 since it is the most likely to result in action a_2. ($i = 1$) the builder guiding data only consisted of m_1 message therefore it cannot learn a preference over actions for m_2 and both actions are equally likely under m_2. The architect now only sends message m_2 since it is more likely than m_1 at triggering a_2. ($i = 2$) Unfortunately, the sampling of m_1 resulted in the builder doing more a_1 than a_2 during the guiding frame and the builder thus associates m_2 with a_1. The architect tries its luck again but now with m_1. ($i = 3$) Eventually, the sampling results in more a_2 actions being sampled in the guiding data and the builder now associates m_1 to a_2. ($i = 4$) and ($i = 5$) The architect can now keep on sending m_1 messages to reinforce this association.

Figure 8: ABIG-no-intent driven evolution of message-conditioned action probabilities for a simple problem where builder must learn to produce action a_2. Initial conditions are unfavorable since a_1 is more likely than a_2 for both messages. Without an architect's guiding messages during training, a self-imitating builder reinforces the action preferences of the initial conditions and fails (even when evaluated alongside a knowledgeable architect as both messages can only yield a_1).

To further assess how the architect's message choices impact the performance of a self-imitating builder, we compare the distribution of the builder's preferred actions obtained after using ABIG and ABIG-no-intent. We consider three different initial conditions (favorable, unfavorable, intermediate) that are each ran to convergence (meaning that the policy does not change anymore across iterations) for 100 different seeds. Figure 9 displays the resulting distributions of preferred – i.e. most likely – action for each message. When applying ABIG on the toy problem, the pair always reaches a success rate of 100/100 no matter the initial condition. We also observe that – at convergence – the builder never prefers action a_1, yet when an action is preferred for a given message, the other message yields no preference over action ($p(a_1|m) = p(a_2|m)$). This is due to the forget mechanism discussed in Section 3.3. The results when applying ABIG-no-intent on the toy problem are much more dependent on the initial condition. In the unfavorable scenario, ABIG-no-intent fails heavily with only 3 seeds succeeding over the 100 experiments. This is due to the fact that, in absence of message guidance

from the architect, the builder has high chances to continually reinforce the association between the two messages and a_1, therefore losing. However, in rare cases, the builder can inverse the initial message-conditioned probabilities by 'luckily' sampling more often a_2 when receiving m_1 and win. This only happened 3 times over the 100 seeds. Finally, when initial conditions are more favorable, the self-imitation steps reinforce the association between the messages and a_2 which makes the builder prefer a_2 for at least one message and enables high success rates (100/100 for favorable and 98/100 for intermediate).

Unfavorable	Favorable	Intermediate

(a) **Initial probabilities**

| $P(a_1\|m_1) = 0.8, P(a_2\|m_1) = 0.2$ | $P(a_1\|m_1) = 0.2, P(a_2\|m_1) = 0.8$ | $P(a_1\|m_1) = 0.9, P(a_2\|m_1) = 0.1$ |
| $P(a_1\|m_2) = 0.9, P(a_2\|m_2) = 0.1$ | $P(a_1\|m_2) = 0.1, P(a_2\|m_2) = 0.9$ | $P(a_1\|m_2) = 0.1, P(a_2\|m_2) = 0.9$ |

(b) ABIG: Distributions of final preferred action for each message calculated over 100 seeds

(c) ABIG-no-intent: Distributions of final preferred action for each message calculated over 100 seeds

Figure 9: Toy experiment analysis (a) Initial conditions: initial probability for each action a given a message m; distributions of final builder's preferred actions for each message after applying (b) ABIG and (c) ABIG-no-intent on the toy problem; distributions are calculated over 100 seeds. For each method and each initial condition, we report the success rate obtained by a knowledgeable architect guiding the builder. At evaluation, the architect has access to the builder's model and does not ignore the goal. ABIG always succeeds while ABIG-no-intent's success depends on the initial conditions.

B   SUPPLEMENTARY RESULTS

B.1   LEARNING ANALYSIS

The main document shows performances (success rates) of builder-architect pairs at convergence. In this supplementary section we propose to thoroughly study the evolution of the builder's policy in order to provide a deeper analysis of ABIG.

Metric definition.   We define three metrics that characterize the builder behavior. We compute these metrics on a constant *Measurement Set* $\mathcal{M}$ made of 6000 randomly sampled states, for each of these states we sample all the possible messages $m \sim \text{Uniform}(\mathcal{V})$ where $\mathcal{V}$ is the set of possible messages. Therefore, $|\mathcal{M}| = 6000 \times |\mathcal{V}|$. The set of possible actions is $\mathcal{A}$ and we denote by δ the indicator function.

We also define the following distributions:

$$p_S(s) \triangleq \frac{1}{|\mathcal{M}|} \sum_{s' \in \mathcal{M}} \delta(s' == s)$$

$$p_M(m) \triangleq P(m|s) = \frac{1}{|\mathcal{V}|}$$

$$p_{SM}(s, m) \triangleq p_S(s) P(m|s) = p_S(s) p_M(m)$$

$$p_{SMA}(s, m, a) \triangleq p_{SM}(s, m) P(a|s, m) = p_{SM}(s, m) \pi_B(a|s, m)$$

$$p_A(a) \triangleq \sum_{(s,m) \in \mathcal{M}} p_{SMA}(s, m, a)$$

$$p_{MA}(m, a) \triangleq \sum_{s \in \mathcal{M}} p_{SMA}(s, m, a)$$

$$p_{SA}(s, a) \triangleq \sum_{m \in \mathcal{M}} p_{SMA}(s, m, a)$$

From this we can define the monitoring metrics:

- *Mean Entropy:*

$$\bar{H}(\pi) = \frac{1}{|\mathcal{M}|} \sum_{(s,m) \in \mathcal{M}} \left[-\sum_{a \in \mathcal{A}} \pi(a|s, m) \log \pi(a|s, m) \right]$$

- *Mutual Information between messages and actions*

$$I_m = \sum_{m \in \mathcal{V}} \sum_{a \in \mathcal{A}} p_{MA}(m, a) \log \frac{p_{MA}(m, a)}{p_A(a) p_M(m)}$$

- *Mutual Information between states and actions*

$$I_s = \sum_{s \in \mathcal{M}} \sum_{a \in \mathcal{A}} p_{SA}(s, a) \log \frac{p_{SA}(s, a)}{p_A(a) p_S(s)}$$

Analysis. Figure 10 displays the evolution of these metrics after each iteration as well as the evolution of the success rate (a). As indicated by Eq. (5), doing self-imitation learning results in a decay of the mean entropy (b). This decay is similar for ABIG and ABIG-no-intent. The most interesting result is provided by the evolution of the mutual information (c). For ABIG-no-intent, we see that I_s and I_m slowly increase with $I_s > I_m$ over all iterations. This indicates that the builder policy $\pi_B(a|s, m)$ relies more on states than on messages to compute the actions. In this scenario the builder, therefore, tends to ignore messages. On the other hand, I_s and I_m evolve differently for ABIG. Both metrics first increase with $I_s > I_m$ until they cross around iteration 25. Then I_s starts decreasing and I_m grows. This shows that ABIG results in a builder policy that strongly selects actions based on the messages it receives which is a desirable feature of emergent communication.

(a) Evolution of the success rate

(b) Evolution of the builder policy mean entropy $\bar{H}_{\pi_B}$

(c) Evolution of the mutual information I_s and I_m

Figure 10: Comparison of the evolution of builder policy properties when applying ABIG and ABIG-no-intent on the 'place' task in BuildWorld. (a) ABIG enables much higher performance that ABIG-no-intent. (b) Both methods use self-imitation and thus reduce the entropy of the policy. (c) ABIG promotes the mutual information between messages and action which indicates successful communication protocols.

B.2 ADDITIONAL BASELINE COMPARISON

We define two extra baselines:

- Stochastic: where the builder policy is a fixed softmax policy parameterized by a randomly initialized network;
- Deterministic: where the builder policy is a fixed argmax policy parameterized by a randomly initialized network.

In the performances reported in Figure 11, the architect has direct access to the exact policy of the builder ($\tilde{\pi}_B = \pi_B$) and uses it to plan and guide the builder during evaluation. We observe that the stochastic condition exhibits similar performances as the random builder. This indicates that, even if the architect tries to guide the builder, the stochastic policy is not controllable and performances are not improved. Finally, we would expect a deterministic policy to be more easily controllable by the architect. Yet, as pointed out in Figure 11, the initial deterministic policies lack flexibility and fail. This shows that the builder must iteratively evolve its policy in order to make it controllable.

Figure 11: Baseline performance depending on the goal: stochastic policy behaves on par with random builder. Self-imitation with ABIG-no-intent remains the most controllable baseline.

B.3 IMPACT OF THE VOCABULARY SIZE

Figure 12: Influence of the Vocabulary size for ABIG on the 'place' task. Performance increases with the vocabulary size.