TabFlowM: Lightweight flow matching for Mixed-Type Tabular Data Synthesis in Latent Space

Abstract

Generative modeling for mixed-type tabular data has recently been dominated by diffusion-based methods, but their gains often come with schedule design, time dependent score parameterization, and multi-step solvers that increase computational overhead and tuning difficulty. We present **TabFlowM**, a lightweight framework that asks a more targeted question: once mixed-type records are mapped into a decoder compatible continuous transport space, is diffusion style score learning still necessary? TabFlowM answers this by training a single time conditioned velocity field via flow matching to deterministically transport Gaussian noise to the latent token space data distribution, replacing diffusion specific score estimation and scheduling machinery with direct velocity regression on a closed form coupling path. Experiments on six real world benchmark datasets show that TabFlowM attains the best Shape/Trend score on 7 out of 12 dataset–metric pairs, improving over the next best baseline by 15.6% on average, achieves the strongest column-wise MLE efficacy on 5 out of 6 datasets, and more than half the sampling time relative to the strongest diffusion baseline. Finally, on a million-scale fraud dataset with class ratios exceeding 100:1, where unconditional fidelity can decouple from rare event predictive utility and models with stronger Shape/Trend may underperform on minority class prediction, TabFlowM still delivers the strongest predictive utility with competitive fidelity and runtime. These findings suggest that, under an appropriate transport interface for mixed-type data, a minimalist flow matching generator can recover much of the benefit commonly associated with heavier diffusion models while substantially reducing computational and conceptual complexity.

1 Introduction

Tabular data is among the most widely used data formats across domains such as finance Liu & Liu (2024), healthcare Nik et al. (2023), e-commerce Mendikowski & Hartwig (2022), and public policy Aghaddar et al. (2024). Synthetic tabular data has gained substantial attention as a means of enabling privacy-preserving data sharing, scalable experimentation, and remediation of class imbalance, yet faithfully reproducing real world tabular data remains challenging: mixed numerical categorical domains, sharp sparsity patterns, and long range cross column dependencies demand generative models that are both expressive and computationally efficient Zhou et al. (2023).

Recent progress is driven by score-based continuous time diffusion models Kotelnikov et al. (2023); Shi et al. (2024); Zhang et al. (2024); Lee et al. (2023); Kim et al. (2023). Specifically, the class of elucidated diffusion models (EDM) Karras et al. (2022) adapt elegantly to mixed-type tables and have achieved SOTA performance in both fidelity and downstream predictive utility. A representative model *TabSyn* Zhang et al. (2024) maps numerical and categorical variables into a unified VAE latent space, allowing a single continuous-time model with a simple schedule and compact network to deliver strong fidelity at modest sampling cost. Building on this, *TabDiff* Shi et al. (2024) adds adaptively learned per-feature schedules, masked/absorbing categorical diffusion, and stochastic backward sampling, improving per-column consistency but at the expense of architectural and computational complexity Shi et al. (2024); Guzmán-Cordero et al. (2025).

Despite their popularity, EDM-style diffusion inherits several structural disadvantages. First, the training score target $\nabla_x \log p_t(x)$ changes scale dramatically across noise levels: as noise level $\sigma \to 0$, targets can explode, while for large σ they vanish, forcing delicate, noise dependent preconditioning Lipman et al. (2023). Second, *high-fidelity diffusion sampling* often relies on careful numerical choices (e.g., solver settings and sampler heuristics) and many model evaluations, introducing extra hyperparameters and increasing inference and tuning cost Shi et al. (2024). Third, there is a training–inference mismatch: models are optimized via stochastic denoising objectives but deployed through a deterministic probability-flow ODE, so discretization and conditioning gaps can bias endpoints. Fourth, the noise schedule $\sigma(t)$ is fixed *a priori*; adapting it per feature or to data geometry effectively alters p_t and requires re-deriving loss weights. Finally, in mixed-type tables, even when operating in a continuous latent space, calibrating discrete columns is only indirect, which can under-serve rare categories Gat et al. (2024); Lipman et al. (2023).

This work revisits a fundamental design question: is diffusion style score learning necessary when operating in a shared latent space for mixed-type tabular synthesis? We argue that much of the modeling burden attributed to diffusion can instead be handled by a simpler transport based formulation.

Subsequently we introduce **TabFlowM**: a mixed-type tabular synthesis framework that replaces EDM-style score learning with a pure *Flow Matching* (FM) objective. Motivated by the practical drawbacks of EDM, FM regresses a time dependent velocity field that directly transports a base distribution to the data distribution, offering three key advantages: (i) it targets well behaved velocities, alleviating noise-scale pathologies and reducing reliance on fragile preconditioning; (ii) it aligns training and sampling, since the same learned field is deterministically integrated at inference, narrowing the objective and sampler gap and often yielding more efficient training with competitive sampling cost; and (iii) it decouples learning from any fixed forward stochastic differential equation (SDE), enabling flexible transport paths without rederiving loss weights Lipman et al. (2023); Gat et al. (2024). Our contributions are as the following:

- **A controlled flow matching framework for mixed-type tabular synthesis**: We propose TabFlowM, which studies whether a single flow matched velocity field can replace diffusion style score learning once synthesis is carried out in a decoder compatible latent space, without auxiliary latent hierarchies, likelihood bounds, or moment-matching surrogates.

- **A transport interface for mixed-type data**: We show that mapping mixed-type records into a decoder compatible continuous token space makes lightweight Euclidean transport viable, and prove that in this space small pathwise velocity regression error yields endpoint control and Wasserstein convergence of the generated token-space distribution to the target distribution.

- **Extensive empirical comparison against diffusion baselines**: We evaluate TabFlowM on six public benchmarks and six million-scale fraud datasets with extreme class imbalance, showing that it delivers competitive or SOTA performance in fidelity, downstream predictive utility, privacy preservation, and runtime.

2 Problem Statement

We consider a mixed-type tabular dataset $\mathcal{T} = \{(x^{\mathrm{num}}, x^{\mathrm{cat}})\}$, where each data point consists of d_{num} numerical features and d_{cat} categorical features whose total dimension is $d = d_{\mathrm{num}} + d_{\mathrm{cat}}$. The numerical features are represented as a vector $x^{\mathrm{num}} \in \mathbb{R}^{d_{\mathrm{num}}}$, and the categorical features as a tuple $x^{\mathrm{cat}} = (x_1^{\mathrm{cat}}, \ldots, x_{d_{\mathrm{cat}}}^{\mathrm{cat}})$, where each $x_j^{\mathrm{cat}} \in \{0, 1, \ldots, C_j - 1\}$ is a discrete category label drawn from a finite set of size C_j.

Our goal is to learn a generative model that can produce synthetic samples $\tilde{x} = (\tilde{x}^{\mathrm{num}}, \tilde{x}^{\mathrm{cat}})$ that are statistically similar to the true data distribution.

3 Related Work

The field of tabular data synthesis has evolved rapidly, with early approaches adapting deep generative models such as GANs and VAEs to handle heterogeneous feature types leading to pioneering model such as CTGAN

Figure 1: TabFlowM Framework

and TVAE Xu et al. (2019). CTGAN introduced conditional generation based on frequency-sampled columns and applied mode-specific normalization to stabilize GAN training and better capture rare categories and multimodal distributions. TVAE followed a variational autoencoding framework, outputting each feature via a Gaussian or categorical head, enabling more faithful modeling of mixed-type marginals. While both models improved per-feature fidelity, they struggled to capture complex inter-feature dependencies.

To address this, transformer-based models treated rows as sequences to better model feature correlations. REaLTabFormer Solatorio & Dupriez (2023) employed an autoregressive GPT-style transformer to synthesize data, one feature at a time, capturing high-order dependencies and supporting relational synthesis. TabMT Gulati & Roysdon (2023) instead used a BERT-style masked transformer, enabling bidirectional feature modeling without relying on a fixed column order and naturally handling missing data. More recently, diffusion-based methods have emerged as the dominant paradigm for high-fidelity synthesis. STaSy Kim et al. (2023) introduced score-based diffusion with a self-paced training curriculum, improving diversity and stability. TabDDPM Kotelnikov et al. (2023) extended diffusion to mixed data by combining Gaussian and discrete forward processes. CoDi Lee et al. (2023) further refined this with dual cross-conditioned diffusion models for continuous and categorical features, improving dependency modeling across modalities. TabDDPM Kotelnikov et al. (2023) extended diffusion to mixed data by combining Gaussian and discrete forward processes.

TabSyn Zhang et al. (2024) proposed learning a score-based diffusion model in the latent space of a transformer-based VAE that tokenizes mixed-type columns into a continuous embedding; diffusion operates over this unified space and samples are decoded back to the original schema, yielding faster generation. The latest advance, TabDiff Shi et al. (2024), unifies all feature types within a single continuous-time diffusion process using feature-adaptive noise schedules and a transformer denoiser, achieving state-of-the-art results in both marginal fidelity and joint consistency.

Most recently, approaches such as Guzmán-Cordero et al. (2025); Jolicoeur-Martineau et al. (2024) explore utilizing FM as an auxiliary addition to more heavy designs such as explicit exponential-family parameterizations, variational moment matching, or per-time-step ensembles, leaving the benefits of a lean FM-based architecture underexplored.

4 Method

TabFlowM is organized around a simple principle: for mixed type tables, the generator should not be asked to solve heterogeneous representation and transport simultaneously. Accordingly, the two-stage pipeline in Fig. 1 first maps each record into a decoder compatible continuous token representation and normalizes it into the space where transport will be learned. With this interface fixed, the second stage keeps the generator deliberately minimal: a continuous-time flow matching model transports Gaussian noise to the token-space data distribution, after which the resulting samples are decoded back into tabular records.

The motivation is geometric. Flow matching is most natural when transport is performed in a continuous, approximately Euclidean space whose local neighborhoods are semantically meaningful Chen & Lipman (2024); Lipman et al. (2023); Gat et al. (2024). Raw mixed-type tables violate this premise: numerical columns may occupy incompatible scales, whereas categorical columns are discrete and induce discontinuous

changes under naive Euclidean interpolation. Consequently, fitting a lightweight Euclidean velocity field directly in raw table space is unnecessarily difficult, because the model must handle heterogeneous feature geometry at the same time as it learns transport. TabFlowM therefore first constructs a decoder compatible transport space in which these irregularities are reduced, and only then applies a simple flow matching generator in that space.

4.1 Constructing a decoder compatible Transport Space

Given a mixed-type record $(x^{\mathrm{num}}, x^{\mathrm{cat}})$, the goal of the first stage is to construct a continuous representation that supports both accurate decoding and stable downstream transport. In particular, we seek a latent space in which all columns admit a common parameterization, nearby latent points decode to nearby records, and the encoded data distribution is sufficiently regular where lightweight continuous transport becomes well posed.

Let d_{num} and d_{cat} denote the numbers of numerical and categorical columns, respectively, and let $M := d_{\mathrm{num}} + d_{\mathrm{cat}}$ be the total number of columns. Let $d_e \in \mathbb{N}$ denote the token dimension. Categorical column j has C_j categories. Writing each categorical value $x_j^{\mathrm{cat}} \in \{0, \ldots, C_j - 1\}$ in one-hot form as $x_j^{\mathrm{oh}} \in \{0, 1\}^{C_j}$, a record can be represented as

$$x = \left[x^{\mathrm{num}}, x_1^{\mathrm{oh}}, \ldots, x_{d_{\mathrm{cat}}}^{\mathrm{oh}} \right] \in \mathbb{R}^{d_{\mathrm{num}} + \sum_{j=1}^{d_{\mathrm{cat}}} C_j}.$$

Why transport is performed in latent space. As is, straight Euclidean interpolation is poorly aligned with mixed-type tabular structure. If x and x' differ only in one categorical column, then their one-hot encodings satisfy $\|x_j^{\mathrm{oh}} - x_j'^{\mathrm{oh}}\|_2 = \sqrt{2}$ regardless of whether the two categories are semantically similar or unrelated. Moreover, for any $t \in (0, 1)$, the convex combination $(1 - t)x_j^{\mathrm{oh}} + tx_j'^{\mathrm{oh}}$ lies in the interior of the simplex rather than at a valid vertex, so the straight segment immediately leaves the discrete data manifold. At the same time, heterogeneous numerical columns can induce anisotropic scaling, causing Euclidean distances to be dominated by only a few features. As a result, straight paths in raw table space are generally poor transport trajectories.

TabFlowM therefore performs transport in a learned latent space. The goal is not to make straight interpolation exact, but to move generation into a decoder compatible continuous representation where such paths are substantially better aligned with the underlying geometry. Specifically, we propose Proposition 1, with details shown in Appendix A.4.1:

Proposition 1 (Raw-space mismatch versus decoder compatible token-space regularity)
Straight interpolation is geometrically mismatched in raw mixed-type table space, whereas in decoder compatible token space it induces substantially more regular decoded trajectories under mild smoothness and nondegeneracy conditions on the decoder.

Column Tokenizer. We begin latentization by mapping each column into a shared continuous embedding space. Let the columns be indexed by $m \in [M]$, with $\mathcal{N} \subseteq [M]$ the numerical indices and $\mathcal{C} \subseteq [M]$ the categorical indices. Each column value x_m is mapped to a token $t_m \in \mathbb{R}^{d_e}$ via

$$t_m = \begin{cases} x_m \, a_m + c_m, & m \in \mathcal{N}, \\ U_m[x_m] + c_m, & m \in \mathcal{C}, \end{cases} \tag{1}$$

where $a_m, c_m \in \mathbb{R}^{d_e}$ are learnable for numerical columns, and for a categorical column $m \in \mathcal{C}$ with C_m categories, $U_m \in \mathbb{R}^{C_m \times d_e}$ is its embedding table and $U_m[x_m]$ denotes the row indexed by the category id x_m. Stacking the tokens yields:

$$E = \mathrm{Stack}(t_1, \ldots, t_M) \in \mathbb{R}^{M \times d_e}. \tag{2}$$

This provides a common continuous parameterization across columns.

Transformer Encoder (VAE). To obtain a more regular latent representation, we encode the token sequence with a Transformer VAE. A transformer encoder Enc_ϕ maps E to the parameters of a Gaussian

latent distribution:

$$(\mu, \log \sigma^2) \;=\; \mathrm{Enc}_\phi(E), \qquad z \;=\; \mu + \sigma \odot \xi, \;\; \xi \sim \mathcal{N}(0, I_\ell), \tag{3}$$

where $z \in \mathbb{R}^\ell$ and $\odot$ denotes elementwise multiplication. A transformer decoder then reconstructs the token matrix via

$$\widehat{E} \;=\; \mathrm{Dec}_\psi(z) \;\in\; \mathbb{R}^{M \times d_e}. \tag{4}$$

Note z is not itself the operating space of the downstream flow model. Rather, it regularizes the autoencoder and induces a decoder compatible token representation, whose flattened and normalized form is used by the flow model in Section 4.2. The reconstruction term preserves record-level information, while the KL regularizer discourages poorly conditioned latent coordinates by pulling the approximate posterior toward a centered Gaussian. For $q_\phi(z \mid E) = \mathcal{N}(\mu, \mathrm{diag}(\sigma^2))$, the KL term is

$$\mathrm{KL}\big(q_\phi(z \mid E) \,\|\, \mathcal{N}(0, I_\ell)\big) = \frac{1}{2} \sum_{r=1}^{\ell} \Big(\mu_r^2 + \sigma_r^2 - \log \sigma_r^2 - 1 \Big). \tag{5}$$

This suppresses large coordinate-wise shifts and extreme variance imbalance, encouraging the encoded data cloud to occupy a more regular region of $\mathbb{R}^\ell$. After flattening and empirical normalization of the decoder compatible token representation, transport is better conditioned than in raw mixed-type space.

Transformer Decoder (Columnwise Reconstruction). The reconstructed tokens are projected back to the data space with heads mirroring the tokenizer. For numerical column i and categorical column j,

$$\widehat{x}_i^{\mathrm{num}} \;=\; \widehat{e}_i^{\mathrm{num}} \, \widehat{w}_i^{\mathrm{num}} + \widehat{b}_i^{\mathrm{num}}, \quad \widehat{p}_j^{\mathrm{cat}} \;=\; \mathrm{Softmax}\big(\widehat{e}_j^{\mathrm{cat}} \, \widehat{W}_j^{\mathrm{cat}} + \widehat{b}_j^{\mathrm{cat}}\big), \tag{6}$$

with $\widehat{w}_i^{\mathrm{num}} \in \mathbb{R}^{d_e \times 1}$, $\widehat{b}_i^{\mathrm{num}} \in \mathbb{R}$, $\widehat{W}_j^{\mathrm{cat}} \in \mathbb{R}^{d_e \times C_j}$, and $\widehat{b}_j^{\mathrm{cat}} \in \mathbb{R}^{1 \times C_j}$. The categorical reconstruction is a probability vector $\widehat{p}_j^{\mathrm{cat}} \in \Delta^{C_j - 1}$ over the categories of column j. We write $\widehat{x} = (\widehat{x}^{\mathrm{num}}, \widehat{x}^{\mathrm{cat}})$, with $\widehat{x}_j^{\mathrm{cat}}$ sampled from taking the argmax of $\widehat{p}_j^{\mathrm{cat}}$ at generation time.

Objective with Adaptive Weight. The VAE is trained with a composite reconstruction loss together with a KL penalty:

$$\mathcal{L}(\phi, \psi) \;=\; \ell_{\mathrm{recon}}(x, \widehat{x}) \;+\; \beta \, \mathrm{KL}\big(q_\phi(z \mid E) \,\|\, \mathcal{N}(0, I_\ell)\big), \tag{7}$$

where

$$\ell_{\mathrm{recon}}(x, \widehat{x}) = \sum_{i=1}^{d_{\mathrm{num}}} \lambda_i^{\mathrm{num}} \big\| x_i^{\mathrm{num}} - \widehat{x}_i^{\mathrm{num}} \big\|_2^2 - \sum_{j=1}^{d_{\mathrm{cat}}} \lambda_j^{\mathrm{cat}} \big\langle x_j^{\mathrm{oh}}, \log \widehat{p}_j^{\mathrm{cat}} \big\rangle. \tag{8}$$

The weights $\lambda_i^{\mathrm{num}}, \lambda_j^{\mathrm{cat}} > 0$ balance heterogeneous units and category prevalences across columns.

Because the downstream flow model operates on the flattened and normalized decoder compatible token representation rather than directly on z, we avoid over-regularizing the VAE latent and employ an adaptive schedule that decreases β once reconstruction has plateaued. Let $\bar{\ell}_m(t)$ be an exponential moving average of the contribution of column $m \in [M]$ to ℓ_{recon} at epoch t. For patience $S \in \mathbb{N}$ and tolerance $\tau > 0$, define

$$\Delta(t) \;=\; \frac{1}{M} \sum_{m=1}^{M} \big(\bar{\ell}_m(t) - \bar{\ell}_m(t - S) \big). \tag{9}$$

With initialization $\beta \leftarrow \beta_{\max}$, we update

$$\beta \;\leftarrow\; \begin{cases} \max\{\beta_{\min}, \lambda \, \beta\}, & \text{if } \Delta(t) \geq -\tau, \\ \beta, & \text{otherwise}, \end{cases} \tag{10}$$

where $\lambda \in (0, 1)$ and $0 < \beta_{\min} \leq \beta_{\max}$. This schedule initially promotes a well-conditioned latent organization and later relaxes the KL pressure so that finer record-level structure is retained for downstream generation.

Interface to TabFlowM. We now enter the generative stage. The autoencoder stage induces a continuous decoder compatible token representation whose geometry is substantially more regular than that of the original table. Importantly, the VAE is not itself the generative model, but serves only as a learned transport interface that regularizes geometry and enables simple Euclidean flows. This is the regime in which a simple Euclidean transport surrogate becomes plausible. Accordingly, rather than learning a score field under an explicit forward noising process, TabFlowM adopts flow matching on the flattened and normalized decoder compatible token representation. Among admissible path constructions, we choose a linear coupling between Gaussian noise and encoded data because it is analytically closed form and implementation-light. The learned object is therefore a time-dependent velocity field whose induced ODE transports the base distribution to the learned token-space data distribution.

4.2 Flow Matching Generator in decoder compatible Token Space

Having constructed a regularized decoder compatible token space, TabFlowM adopts a deliberately *minimal* continuous-time generator. Specifically, we flatten and normalize the token representation, choose a linear coupling between Gaussian noise and the normalized token codes, train a single time-conditioned MLP by flow matching on this path, and generate samples by integrating the learned ODE with an RK2 (Heun) solver. We do not claim the linear path is optimal; rather, its viability hinges on the latentization step, which empirically produces a sufficiently regular token space where such simple Euclidean transport is geometrically plausible.

Vectorization and normalization. Let $\widehat{E} \in \mathbb{R}^{M \times d_e}$ be the decoder compatible token matrix produced by the autoencoder stage. We flatten tokens into a single vector

$$z_0 := \mathrm{vec}(\widehat{E}) \in \mathbb{R}^D, \qquad D = M d_e, \tag{11}$$

and apply a fixed affine normalization,

$$\tilde{z}_0 = \frac{z_0 - \bar{z}}{s},$$

where $\bar{z}$ is the dataset mean and $s > 0$ is a constant scale. The generator is trained *only* in this normalized space; sampling inverts the normalization before decoding.

Linear coupling path and target velocity. Having moved transport into this decoder compatible normalized token space, we instantiate flow matching with a linear coupling path. For each $\tilde{z}_0$, we draw $t \sim \mathrm{Unif}[0, 1]$ and $\varepsilon \sim \mathcal{N}(0, I_D)$, and define the straight path

$$x_t = (1 - t)\varepsilon + t\tilde{z}_0, \tag{12}$$

whose *true* velocity is the constant vector

$$v^\star(x_t, t) = \frac{d}{dt}x_t = \tilde{z}_0 - \varepsilon. \tag{13}$$

TabFlowM parameterizes a time-dependent vector field $v_\theta : \mathbb{R}^D \times [0, 1] \to \mathbb{R}^D$ with a single MLP that consumes x_t and a Fourier (sin/cos) embedding of t.

A more efficient training objective. The benefit of equation 12–equation 13 is that it yields a *simulation-free, scale-stable* supervised target. Training tuples $(x_t, t, v^\star)$ are obtained in closed form from i.i.d. draws $(\tilde{z}_0, \varepsilon, t)$, so each gradient step requires only a single forward/backward pass through v_θ. This contrasts with score-based diffusion objectives, which learn the time-indexed score $s^\star(x, t) = \nabla_x \log p_t(x)$ induced by a forward noising process. Under a common variance-exploding corruption $x_t = x_0 + \sigma(t)\varepsilon$, the conditional score obeys:

$$\nabla_{x_t} \log p(x_t \mid x_0) = -\frac{x_t - x_0}{\sigma(t)^2}, \tag{14}$$

so the effective regression target changes magnitude dramatically across t (exploding as $\sigma(t) \to 0$ and vanishing for large $\sigma(t)$), motivating noise-dependent parameterizations, loss weights, and preconditioning to balance

gradients. In contrast, the FM target $v^\star = \tilde{z}_0 - \varepsilon$ does not inherit any $\sigma(t)^{-2}$ amplification and remains a bounded displacement vector across time. Empirically, this produces a smoother optimization landscape and reduces tuning sensitivity, which is where we observe the largest efficiency gains.

Flow matching loss. We regress the velocity directly:

$$\mathcal{L}_{\mathrm{FM}}(\theta) \;=\; \frac{1}{2} \, \mathbb{E}_{\tilde{z}_0, \varepsilon, t} \, \big\| \, v_\theta(x_t, t) \;-\; (\tilde{z}_0 - \varepsilon) \, \big\|_2^2. \tag{15}$$

Compared to diffusion-style training, equation 15 replaces score estimation, which is tightly coupled to the forward noising schedule and its time-dependent scaling, with direct velocity regression along an analytically specified coupling path. Geometrically, the loss encourages $v_\theta(x_t, t)$ to align with and match the magnitude of the displacement from ε to $\tilde{z}_0$.

Sampling (ODE integration). At generation time we draw $x(0) \sim \mathcal{N}(0, I_D)$ and integrate the ODE

$$\frac{dx}{dt} \;=\; v_\theta\big(x(t), t\big), \quad t \in [0, 1], \quad x(0) \sim \mathcal{N}(0, I_D), \tag{16}$$

using Heun's method (RK2) with a fixed step grid $0 = t_0 < \cdots < t_S = 1$:

$$\begin{aligned}
x_{i+1}^{\mathrm{Euler}} &= x_i + \Delta t \, v_\theta(x_i, t_i), \\
x_{i+1} &= x_i + \tfrac{\Delta t}{2} \big[v_\theta(x_i, t_i) + v_\theta\big(x_{i+1}^{\mathrm{Euler}}, t_{i+1}\big) \big] .
\end{aligned} \tag{17}$$

Reduced solver heuristics. Both diffusion models and FM ultimately rely on evaluating a learned time-dependent field along a trajectory. However, diffusion sampling typically integrates reverse-time SDE/ODE dynamics whose stiffness and accuracy requirements can vary sharply across the noise schedule, often leading to many function evaluations (NFEs) and additional heuristics (e.g., step schedules and sometimes correction steps) to reach high fidelity. FM sampling instead integrates the learned velocity field directly, without recovering a score or multiplying by schedule-dependent factors (such as $\dot{\sigma}(t)\sigma(t)$ in probability-flow formulations), so the NFE–quality tradeoff is transparent: with a fixed-step RK2 solver, sampling cost is simply proportional to the chosen number of steps.

The resulting $x(1)$ is then de-normalized via $z^\star = s\, x(1) + \bar{z}$ and reshaped to $M \times d_e$ before decoding.

Mixed-type decoding. The (frozen) transformer decoder Dec_ψ maps $z^\star$ back to per-column heads: numerical means $\widehat{x}^{\mathrm{num}}$ and categorical logits $\widehat{p}^{\mathrm{cat}}$; we output categorical values by $\arg\max$ at generation time to ensure deterministic evaluation. Sampling from the softmax distribution was tested and showed minimal difference on aggregate evaluation metrics, though future work may consider temperature scaled sampling to improve rare category diversity. We then apply the dataset's inverse transformers to obtain the final table.

Once synthesis has been moved into a decoder compatible normalized token space, the role of the generator is no longer to discover a complex transport geometry from scratch. Instead, it must accurately follow the target velocity along a simple coupling path toward the target token code. A crucial claim of TabFlowM is that, in this regularized setting, small pathwise velocity regression error is already sufficient to control the generated endpoint and drive the generated token-space distribution toward the target distribution in Wasserstein distance:

Proposition 2 (Endpoint control from pathwise velocity regression) *Under the linear-path FM surrogate, if the learned velocity field is Lipschitz in state, then small flow-matching regression error along the reference coupling path implies small endpoint error, and hence Wasserstein closeness between the generated token-space distribution and the target token-space distribution.*

In other words, within the decoder compatible token space constructed above, optimizing equation 15 is sufficient to drive the generator toward the correct token-space law. Details of the proof including the regularity and numerical integration error are quantified in Appendix A.4.2.

5 Experiments

In this section, we present the methodologies and baselines used to benchmark TabFlowM against other existing general-purpose tabular-data synthesizers. Note that all baselines were tested five times with the average and standard deviation of results presented. All diffusion based methods have had their shared hyperparameter set equally to ensure fairness during evaluation. Specific hyperparameters for each model and hardware specifications are shown in Appendix A.5. Runtime comparisons use identical hardware and batch sizes across methods.

5.1 Baselines

We benchmark *TabFlowM* against classical methods such as CTGAN Xu et al. (2019), TVAE Xu et al. (2019), CopulaGAN Patki et al. (2016), and existing SOTA diffusion-based synthesizers TabSyn Zhang et al. (2024) and TabDiff Shi et al. (2024)[1]. Following the evaluation procedures in prior works Zhang et al. (2024); Shi et al. (2024), we assess synthethic quality through four axes: *Shape*, the average divergence between real and synthetic *marginal* column distributions; *Trend*, the discrepancy in pairwise dependence structure (via correlation or contingency-based statistics); *Machine Learning Efficiency* (column-wise MLE), which trains a predictor for each target column on synthetic data and tests on real data (AUC for classification; RMSE for regression) Zhang et al. (2024); Shi et al. (2024); and *C2ST-LR*, a logistic-regression two-sample test that quantifies distinguishability between real and synthetic rows. C2ST-LR is not a formal privacy guarantee but a distinguishability measure widely used as a heuristic proxy for memorization risk Zhang et al. (2024); Shi et al. (2024). The evaluation metrics used are introduced in Appendix A.2 with further evaluation settings specified in Appendix A.3 that varies from existing literature.

5.2 Datasets

We inherit the six real world tabular benchmarks used in prior work Shi et al. (2024); Zhang et al. (2024) from the UCI Machine Learning Repository Asuncion et al. (2007): *Adult*, *Default*, *Diabetes*, *Magic*, *News*, and *Beijing*. Across these datasets, the number of rows ranges from 768 (*Diabetes*) to 48,842 (*Adult*), and each benchmark contains a mix of numerical and categorical columns. *Adult*, *Default*, *Diabetes*, and *Magic* are treated as classification tasks, while *Beijing* and *News* are treated as regression tasks. In addition to these six controlled benchmarks, we also evaluate a large-scale rare-event prediction stress test on the BAF fraud dataset, described separately in Section 6.2. For every dataset, we adopt a fixed 8:1:1 split into training, validation, and test sets. Details can be found in Appendix A.1.

6 Results

6.1 Controlled Benchmark Comparison

We report **Shape** and **Trend** on the six benchmark datasets in Tables 1 and 2. Overall, **TabFlowM** delivers the strongest average performance across baselines. Specifically it is best on **7 out of 12** dataset–metric pairs and ranks **first or second on 10 out of 12**. In aggregate, TabFlowM achieves the lowest mean **Shape** (≈ 0.049) and the lowest mean **Trend** (≈ 0.045) across datasets. Across its wins, it improves over the next best method by an average of $\approx 15.6\%$, with gains as large as $\approx 31.6\%$ (Trend on *Magic*).

On **Shape**, TabFlowM is best on *Adult*, *Beijing*, *Default*, and *Magic*, with small but consistent gains on *Adult* ($\approx 2.7\%$) and larger gains on *Beijing* ($\approx 9.1\%$), *Default* ($\approx 21.9\%$), and *Magic* ($\approx 21.7\%$) relative to the next best method. On *News*, TabFlowM is essentially tied with the best method, trailing by only $\approx 1.5\%$. *Diabetes* remains the main outlier, where TabDiff is strongest.

On **Trend**, TabFlowM leads on *Adult*, *Default*, and *Magic*, improving over the next best method by $\approx 9.8\%$, $\approx 12.5\%$, and $\approx 31.6\%$, respectively. It is also competitive on *Beijing* and *News*, where it places second and is within $\approx 5.0\%$ of the best result on *News*.

---

[1]The implementation of TabbyFlow Guzmán-Cordero et al. (2025) is not available at the time of submission, and is therefore omitted.

Table 1: Shape Score Results ($\downarrow$)

Method	Adult	Beijing	Default	Diabetes	Magic	News
CTGAN	$0.192_{\pm0.016}$	$0.230_{\pm0.012}$	$0.107_{\pm0.007}$	$0.125_{\pm0.008}$	$0.077_{\pm0.029}$	$0.186_{\pm0.007}$
TVAE	$0.185_{\pm0.023}$	$0.287_{\pm0.025}$	$0.134_{\pm0.012}$	$0.149_{\pm0.004}$	$0.120_{\pm0.015}$	$0.167_{\pm0.008}$
CopulaGAN	$0.111_{\pm0.007}$	$0.192_{\pm0.009}$	$0.099_{\pm0.008}$	$0.124_{\pm0.004}$	$0.127_{\pm0.020}$	$0.184_{\pm0.009}$
TabSyn	$\underline{0.037}_{\pm0.004}$	$0.067_{\pm0.011}$	$0.079_{\pm0.030}$	$\underline{0.048}_{\pm0.006}$	$0.063_{\pm0.014}$	$\mathbf{0.066}_{\pm0.007}$
TabDiff	$0.043_{\pm0.015}$	$\underline{0.044}_{\pm0.014}$	$0.073_{\pm0.009}$	$\mathbf{0.028}_{\pm0.005}$	$0.046_{\pm0.008}$	$0.097_{\pm0.016}$
TabFlowM	$\mathbf{0.036}_{\pm0.008}$	$\mathbf{0.040}_{\pm0.005}$	$\mathbf{0.057}_{\pm0.014}$	$0.057_{\pm0.010}$	$\mathbf{0.036}_{\pm0.009}$	$\underline{0.067}_{\pm0.008}$

Table 2: Trend Score Results ($\downarrow$)

Method	Adult	Beijing	Default	Diabetes	Magic	News
CTGAN	$0.130_{\pm0.012}$	$0.105_{\pm0.015}$	$0.074_{\pm0.003}$	$0.117_{\pm0.011}$	$0.061_{\pm0.005}$	$0.045_{\pm0.001}$
TVAE	$0.093_{\pm0.009}$	$0.198_{\pm0.030}$	$0.112_{\pm0.018}$	$0.203_{\pm0.002}$	$0.045_{\pm0.010}$	$0.028_{\pm0.002}$
CopulaGAN	$0.112_{\pm0.010}$	$0.112_{\pm0.009}$	$0.078_{\pm0.003}$	$0.157_{\pm0.011}$	$0.054_{\pm0.003}$	$0.045_{\pm0.001}$
TabSyn	$\underline{0.051}_{\pm0.008}$	$0.051_{\pm0.005}$	$\underline{0.048}_{\pm0.013}$	$0.087_{\pm0.010}$	$\underline{0.019}_{\pm0.008}$	$\mathbf{0.020}_{\pm0.002}$
TabDiff	$0.065_{\pm0.018}$	$0.038_{\pm0.009}$	$0.067_{\pm0.012}$	$\mathbf{0.043}_{\pm0.006}$	$0.068_{\pm0.036}$	$0.032_{\pm0.006}$
TabFlowM	$\mathbf{0.046}_{\pm0.016}$	$\underline{0.043}_{\pm0.007}$	$\mathbf{0.042}_{\pm0.014}$	$0.104_{\pm0.015}$	$\mathbf{0.013}_{\pm0.004}$	$\underline{0.021}_{\pm0.001}$

Table 3: MLE Efficacy

Method	Adult (AUC$\uparrow$)	Beijing (RMSE$\downarrow$)	Default (AUC$\uparrow$)	Magic (AUC$\uparrow$)	Diabetes (AUC$\uparrow$)	News (RMSE$\downarrow$)
CTGAN	$0.875_{\pm0.007}$	$1.053_{\pm0.040}$	$0.724_{\pm0.015}$	$0.872_{\pm0.019}$	$0.601_{\pm0.036}$	$8721_{\pm706}$
TVAE	$0.878_{\pm0.008}$	$0.920_{\pm0.038}$	$0.716_{\pm0.009}$	$0.823_{\pm0.021}$	$0.614_{\pm0.009}$	$\underline{6059}_{\pm127}$
CopulaGAN	$0.859_{\pm0.009}$	$0.995_{\pm0.031}$	$0.647_{\pm0.020}$	$0.803_{\pm0.009}$	$0.570_{\pm0.040}$	$9340_{\pm193}$
TabSyn	$\underline{0.899}_{\pm0.003}$	$\mathbf{0.709}_{\pm0.017}$	$0.702_{\pm0.025}$	$\underline{0.915}_{\pm0.005}$	$0.627_{\pm0.021}$	$6102_{\pm470}$
TabDiff	$0.896_{\pm0.007}$	$\underline{0.716}_{\pm0.049}$	$\underline{0.741}_{\pm0.025}$	$0.890_{\pm0.016}$	$\underline{0.648}_{\pm0.005}$	$8315_{\pm638}$
TabFlowM	$\mathbf{0.905}_{\pm0.007}$	$0.739_{\pm0.012}$	$\mathbf{0.747}_{\pm0.020}$	$\mathbf{0.918}_{\pm0.003}$	$\mathbf{0.651}_{\pm0.021}$	$\mathbf{5785}_{\pm1193}$

Table 3 (**MLE Efficacy**) shows that TabFlowM achieves the best downstream performance on *Adult*, *Default*, *Magic*, *Diabetes*, and the *News* regression task, while remaining competitive on *Beijing*, where it is within ~4.2% of TabSyn (RMSE). Across all six datasets, TabFlowM attains the best average rank, indicating that its samples preserve task relevant predictive structure at least as well as, and often better than, other diffusion-based baselines.

For **C2ST-LR** (Table 4), TabFlowM shows favorable distinguishability while delivering state-of-the-art fidelity. It achieves the best C2ST-LR on *Adult* and is a close second on four of the remaining five datasets: it is within ≈4.0% of the best method on *Beijing* (0.603 vs. 0.580), ≈3.3% on *Default* (0.625 vs. 0.605), ≈2.5% on *Magic* (0.576 vs. 0.562), and ≈1.4% on *News* (0.592 vs. 0.584). Averaged over datasets, TabFlowM is *second only to TabDiff* in mean C2ST-LR (≈ 0.648 vs. ≈ 0.612), indicating that the substantial gains in sample quality are not accompanied by systematically worse distinguishability on these benchmarks.

Tables 5 and 6 report **training** and **sampling** times. TabFlowM is the fastest method for *training* on 5 of 6 datasets (*Adult*, *Default*, *Diabetes*, *Magic*, and *News*), and is competitive on *Beijing* (only ≈16.4% slower than TabDiff while being ≈2.2% faster than TabSyn). Importantly, it avoids the severe training-time blow-up exhibited by TabDiff on *Diabetes* (TabFlowM is ≈5.5× faster).

Lastly, looking back at *Diabetes*, it should be noted that FM with a single linear coupling path is not uniformly best. Outside the idealized limit of infinite capacity and perfect optimization, TabDiff's richer backbone and adaptive schedules still win on Shape/Trend, suggesting that regimes with very sparse, highly skewed, or strongly multimodal categorical structure, more expressive transport paths could be beneficial. We explore this in section 7.

6.2 Large-Scale Rare Event Prediction Stress Test: BAF (Kaggle)

Beyond the six controlled UCI benchmarks above, we evaluate a deployment-motivated stress test on the large-scale, severely imbalanced BAF fraud dataset Jesus et al. (2022) (Appendix A.1). This setting is

Table 4: C2ST-LR

Method	Adult	Beijing	Default	Diabetes	Magic	News
CTGAN	$0.712_{\pm0.016}$	$0.720_{\pm0.015}$	$0.742_{\pm0.033}$	$\underline{0.831}_{\pm0.014}$	$0.610_{\pm0.052}$	$0.653_{\pm0.016}$
TVAE	$0.803_{\pm0.012}$	$0.919_{\pm0.048}$	$0.823_{\pm0.010}$	$0.996_{\pm0.001}$	$0.713_{\pm0.040}$	$0.613_{\pm0.029}$
CopulaGAN	$0.678_{\pm0.022}$	$0.750_{\pm0.013}$	$0.766_{\pm0.032}$	$0.942_{\pm0.013}$	$0.722_{\pm0.028}$	$0.687_{\pm0.025}$
TabSyn	$\underline{0.607}_{\pm0.017}$	$0.620_{\pm0.015}$	$0.655_{\pm0.021}$	$0.887_{\pm0.027}$	$\mathbf{0.562}_{\pm0.014}$	$\mathbf{0.584}_{\pm0.035}$
TabDiff	$0.621_{\pm0.037}$	$\mathbf{0.580}_{\pm0.046}$	$\mathbf{0.605}_{\pm0.038}$	$\mathbf{0.598}_{\pm0.020}$	$0.662_{\pm0.078}$	$0.607_{\pm0.120}$
TabFlowM	$\mathbf{0.586}_{\pm0.035}$	$\underline{0.603}_{\pm0.021}$	$\underline{0.625}_{\pm0.052}$	$0.903_{\pm0.018}$	$\underline{0.576}_{\pm0.012}$	$\underline{0.592}_{\pm0.047}$

Table 5: Training Time (seconds; lower is better)

Method	Adult	Beijing	Default	Diabetes	Magic	News
TabSyn	$\underline{61.08}_{\pm15.10}$	$70.64_{\pm17.94}$	$64.55_{\pm15.25}$	$\underline{128.84}_{\pm39.47}$	$42.21_{\pm8.80}$	$\underline{72.81}_{\pm17.79}$
TabDiff	$65.38_{\pm4.64}$	$\mathbf{59.37}_{\pm2.71}$	$\underline{60.69}_{\pm3.05}$	$686.93_{\pm229.01}$	$\underline{35.75}_{\pm1.47}$	$76.11_{\pm6.29}$
TabFlowM	$\mathbf{59.53}_{\pm13.91}$	$\underline{69.08}_{\pm16.38}$	$\mathbf{28.08}_{\pm13.17}$	$\mathbf{125.09}_{\pm35.55}$	$\mathbf{21.68}_{\pm9.42}$	$\mathbf{69.41}_{\pm16.21}$

Table 6: Sampling Time (seconds; lower is better)

Method	Adult	Beijing	Default	Diabetes	Magic	News
TabSyn	$\underline{6.32}_{\pm1.21}$	$\underline{6.063}_{\pm1.07}$	$\mathbf{3.04}_{\pm0.05}$	$\underline{10.49}_{\pm1.38}$	$\mathbf{1.76}_{\pm0.04}$	$\mathbf{6.18}_{\pm0.19}$
TabDiff	$10.72_{\pm1.73}$	$8.49_{\pm0.74}$	$9.20_{\pm0.95}$	$488.44_{\pm2.90}$	$2.39_{\pm0.69}$	$11.31_{\pm1.06}$
TabFlowM	$\mathbf{4.07}_{\pm0.95}$	$\mathbf{4.35}_{\pm1.27}$	$\underline{3.47}_{\pm1.10}$	$\mathbf{9.52}_{\pm0.21}$	$\underline{1.96}_{\pm1.12}$	$\underline{6.44}_{\pm1.01}$

practically important because real world tabular synthesis often operates at substantially larger scale and must preserve structure relevant to rare-event labels such as fraud. We therefore use BAF to evaluate whether methods that perform well on standard benchmarks remain effective under the combined challenges of scale and extreme class imbalance.

We evaluate six BAF configurations (BAF-Base and BAF-V1–V5), each representing a distinct preprocessing or variant setting within the same large scale, heavily imbalanced regime. Given the computational footprint at this scale, we narrow the comparison to a focused study between diffusion-based methods (**TabDiff** and **TabSyn**) versus our flow matching model **TabFlowM**. Results are shown below:

Table 7: Large scale rare event prediction stress test on BAF (Kaggle)

Dataset	Method	Shape↓	Trend↓	MLE (AUC)↑	Train (s)↓	Sample (s)↓
BAF-Base	TabSyn	$0.7691_{\pm0.0035}$	$0.7954_{\pm0.0108}$	$\underline{0.8433}_{\pm0.0130}$	$\underline{5082.19}_{\pm438.36}$	$\mathbf{130.79}_{\pm9.17}$
	TabDiff	$\underline{0.7473}_{\pm0.0097}$	$\mathbf{0.6451}_{\pm0.0154}$	$0.5329_{\pm0.0668}$	$5179.24_{\pm27.92}$	$\underline{192.03}_{\pm1.07}$
	TabFlowM	$\mathbf{0.7375}_{\pm0.0032}$	$\underline{0.7795}_{\pm0.0033}$	$\mathbf{0.8502}_{\pm0.0179}$	$\mathbf{4795.51}_{\pm21.02}$	$195.62_{\pm7.44}$
BAF-V1	TabSyn	$0.7683_{\pm0.0041}$	$0.7853_{\pm0.0080}$	$\underline{0.8399}_{\pm0.0075}$	$\underline{4427.60}_{\pm471.61}$	$\mathbf{132.22}_{\pm18.03}$
	TabDiff	$\underline{0.7521}_{\pm0.0055}$	$\mathbf{0.7552}_{\pm0.0528}$	$0.5774_{\pm0.1296}$	$5231.47_{\pm24.41}$	$\underline{192.60}_{\pm2.36}$
	TabFlowM	$\mathbf{0.7342}_{\pm0.0031}$	$\underline{0.7792}_{\pm0.0031}$	$\mathbf{0.8415}_{\pm0.0225}$	$\mathbf{3479.30}_{\pm660.92}$	$198.22_{\pm4.95}$
BAF-V2	TabSyn	$\underline{0.7646}_{\pm0.0044}$	$0.8264_{\pm0.0076}$	$\underline{0.8666}_{\pm0.0059}$	$\underline{4055.10}_{\pm296.06}$	$\mathbf{138.69}_{\pm32.45}$
	TabDiff	$0.7682_{\pm0.0058}$	$\mathbf{0.8062}_{\pm0.0636}$	$0.7181_{\pm0.1677}$	$5234.40_{\pm29.54}$	$\underline{192.88}_{\pm2.46}$
	TabFlowM	$\mathbf{0.7577}_{\pm0.0052}$	$\underline{0.8146}_{\pm0.0049}$	$\mathbf{0.8714}_{\pm0.0197}$	$\mathbf{3503.80}_{\pm537.48}$	$195.57_{\pm6.09}$
BAF-V3	TabSyn	$0.7658_{\pm0.0036}$	$0.8229_{\pm0.0161}$	$\underline{0.8486}_{\pm0.0109}$	$\underline{3918.31}_{\pm264.18}$	$136.90_{\pm25.81}$
	TabDiff	$\underline{0.7642}_{\pm0.7642}$	$\mathbf{0.7998}_{\pm0.0639}$	$0.6299_{\pm0.1542}$	$5225.09_{\pm27.32}$	$192.90_{\pm1.74}$
	TabFlowM	$\mathbf{0.7619}_{\pm0.0047}$	$\underline{0.8133}_{\pm0.0052}$	$\mathbf{0.8605}_{\pm0.0148}$	$\mathbf{3506.36}_{\pm537.52}$	$\underline{189.93}_{\pm14.80}$
BAF-V4	TabSyn	$0.7703_{\pm0.0029}$	$0.8213_{\pm0.0079}$	$\underline{0.8752}_{\pm0.0156}$	$\underline{5008.23}_{\pm475.77}$	$\mathbf{132.56}_{\pm16.33}$
	TabDiff	$\mathbf{0.7529}_{\pm0.0363}$	$\mathbf{0.7108}_{\pm0.0432}$	$0.5862_{\pm0.1146}$	$5207.32_{\pm22.83}$	$\underline{191.42}_{\pm1.65}$
	TabFlowM	$\underline{0.7619}_{\pm0.0047}$	$\underline{0.8143}_{\pm0.0056}$	$\mathbf{0.8803}_{\pm0.0171}$	$\mathbf{4582.58}_{\pm526.32}$	$194.42_{\pm7.86}$
BAF-V5	TabSyn	$0.7685_{\pm0.0052}$	$0.8222_{\pm0.0057}$	$\underline{0.8546}_{\pm0.0228}$	$\underline{4667.96}_{\pm516.26}$	$\mathbf{126.84}_{\pm8.51}$
	TabDiff	$\underline{0.7644}_{\pm0.0090}$	$\mathbf{0.7994}_{\pm0.0633}$	$0.7055_{\pm0.1388}$	$5245.49_{\pm32.65}$	$\underline{192.36}_{\pm2.12}$
	TabFlowM	$\mathbf{0.7620}_{\pm0.0047}$	$\underline{0.8141}_{\pm0.0056}$	$\mathbf{0.8768}_{\pm0.0221}$	$\mathbf{4220.91}_{\pm599.00}$	$193.95_{\pm9.05}$

On the large-scale BAF fraud benchmarks, the **fidelity** picture is more mixed than on the standard UCI-style datasets. Overall, **TabFlowM** remains highly competitive, attaining the best **Shape** on **5 out of 6**

Figure 2: BAF Variant 1 Density Plots

variants and the second-best result on the remaining one ($BAF\text{-}V4$), where it trails TabDiff only modestly. In aggregate, TabFlowM achieves the lowest mean **Shape** across variants (approximately 0.753), indicating that its samples match marginal distributions better than the diffusion baselines. On **Trend**, however, the ranking differs: **TabDiff** is strongest on all six variants, suggesting that its heavier design can better capture certain global dependency patterns under this large scale regime. TabFlowM therefore does not uniformly dominate the unconditional fidelity metrics on BAF, but it remains consistently strong, especially on Shape, while staying close to the best method on Trend.

However, the practical objective in BAF is **fraud detection**, not unconditional distribution matching alone. Under this criterion, **TabFlowM** is clearly strongest: it achieves the best MLE on **all six** BAF variants, ranging from 0.8415 to 0.8803 and averaging approximately 0.863, ahead of TabSyn (approximately 0.855) and far above TabDiff (approximately 0.625). Although this may appear counterintuitive, prior work has shown that under *extreme data conditions*, especially large scale and severe imbalance, the usual alignment between unconditional fidelity and downstream utility can weaken Achterberg et al. (2025); Zuo et al. (2026). One hypothesis is that FM's displacement based supervision preserves finer grained geometric structure in encoded minority patterns, whereas diffusion's noise schedule can over smooth low density regions. A deeper investigation goes beyond the scope of this paper. Nevertheless, the empirical pattern is informative: it suggests that **TabFlowM**'s lightweight flow matching formulation can sometimes preserve underrepresented yet task-relevant structure better than heavier diffusion models optimized for stronger global dependency matching. This is qualitatively illustrated in Fig. 2: for `prev_address_months_count`, TabDiff achieves the best overall Trend score, but appears to smooth out smaller low density modes that other baselines preserve.

Lastly, training remains costly for all approaches (thousands of seconds per run), reflecting the large-scale setting. TabFlowM is the fastest to train in *every* variant, averaging 4015 s versus 5221 s for TabDiff and 4527 s for TabSyn (about 23% faster than TabDiff and 11% faster than TabSyn on average). Sampling exhibits the opposite pattern: TabSyn is the fastest sampler across variants (mean 133 s; range 126.84–138.69 s), while TabDiff and TabFlowM are similar (means 192 s and 195 s, respectively). Taken together, TabFlowM provides the best *utility at scale* with competitive fidelity and runtime.

7 Ablation Studies

To test whether flow matching still helps when combined with a more sophisticated numerical backbone, we introduce **cflow**, which reuses TabDiff's continuous-time transformer and per feature (column) adaptive noise schedules for numerical features, but is entirely retrained by replacing the EDM score objective with a FM loss. Table 8[2] shows that TabDiff's richer architecture, the joint multi-modal diffusion with learned per-feature schedules indeed increases modelling power: on harder regimes such as *Diabetes* it delivers the

---

[2]Shape/Trend and times: lower is better. MLE is AUC↑ except *Beijing* (RMSE↓) and *News* (RMSE↓).

Table 8: Consolidated results for **cflow**, **TabDiff**, and **TabFlowM**

Dataset	Method	Shape↓	Trend↓	MLE	Train (s)↓	Sample (s)↓
Adult	cflow	$\mathbf{0.035}_{\pm0.007}$	$\underline{0.059}_{\pm0.006}$	$0.887_{\pm0.002}$	$\underline{64.99}_{\pm4.42}$	$\underline{7.83}_{\pm1.25}$
	TabDiff	$0.043_{\pm0.015}$	$0.065_{\pm0.018}$	$\underline{0.896}_{\pm0.007}$	$65.38_{\pm4.64}$	$10.72_{\pm1.73}$
	TabFlowM	$\underline{0.036}_{\pm0.008}$	$\mathbf{0.046}_{\pm0.016}$	$\mathbf{0.905}_{\pm0.007}$	$\mathbf{59.53}_{\pm13.91}$	$\mathbf{4.07}_{\pm0.95}$
Default	cflow	$0.084_{\pm0.014}$	$0.155_{\pm0.010}$	$0.713_{\pm0.014}$	$\underline{59.10}_{\pm2.75}$	$\underline{3.73}_{\pm0.10}$
	TabDiff	$\underline{0.073}_{\pm0.009}$	$\underline{0.067}_{\pm0.012}$	$\underline{0.741}_{\pm0.025}$	$60.69_{\pm3.05}$	$9.20_{\pm0.95}$
	TabFlowM	$\mathbf{0.057}_{\pm0.014}$	$\mathbf{0.042}_{\pm0.014}$	$\mathbf{0.747}_{\pm0.020}$	$\mathbf{28.08}_{\pm13.17}$	$\mathbf{3.47}_{\pm1.10}$
Diabetes	cflow	$\underline{0.040}_{\pm0.006}$	$\underline{0.058}_{\pm0.008}$	$0.613_{\pm0.010}$	$\underline{452.74}_{\pm148.50}$	$\underline{250.80}_{\pm1.64}$
	TabDiff	$\mathbf{0.028}_{\pm0.005}$	$\mathbf{0.043}_{\pm0.006}$	$\underline{0.649}_{\pm0.005}$	$686.93_{\pm229.01}$	$488.44_{\pm2.90}$
	TabFlowM	$0.057_{\pm0.010}$	$0.104_{\pm0.015}$	$\mathbf{0.651}_{\pm0.021}$	$\mathbf{125.09}_{\pm35.55}$	$\mathbf{9.52}_{\pm0.21}$
Magic	cflow	$\mathbf{0.034}_{\pm0.008}$	$0.112_{\pm0.006}$	$0.831_{\pm0.028}$	$\underline{35.10}_{\pm1.87}$	$\mathbf{1.25}_{\pm0.08}$
	TabDiff	$0.046_{\pm0.008}$	$\underline{0.068}_{\pm0.036}$	$\underline{0.890}_{\pm0.016}$	$35.75_{\pm1.47}$	$2.39_{\pm0.69}$
	TabFlowM	$\underline{0.036}_{\pm0.009}$	$\mathbf{0.013}_{\pm0.004}$	$\mathbf{0.919}_{\pm0.003}$	$\mathbf{21.68}_{\pm9.42}$	$\underline{1.96}_{\pm1.12}$
Beijing	cflow	$\mathbf{0.034}_{\pm0.006}$	$0.079_{\pm0.013}$	$0.811_{\pm0.063}$	$\underline{60.80}_{\pm3.62}$	$\mathbf{3.60}_{\pm0.69}$
	TabDiff	$0.044_{\pm0.014}$	$\mathbf{0.038}_{\pm0.009}$	$\mathbf{0.716}_{\pm0.049}$	$\mathbf{59.37}_{\pm2.71}$	$8.49_{\pm0.74}$
	TabFlowM	$\underline{0.040}_{\pm0.005}$	$\underline{0.043}_{\pm0.007}$	$\underline{0.739}_{\pm0.012}$	$69.08_{\pm16.38}$	$\underline{4.35}_{\pm1.27}$
News	cflow	$\mathbf{0.052}_{\pm0.006}$	$0.038_{\pm0.001}$	$8551_{\pm0.441}$	$\underline{71.73}_{\pm5.70}$	$\underline{7.55}_{\pm1.23}$
	TabDiff	$0.097_{\pm0.016}$	$\underline{0.032}_{\pm0.006}$	$\underline{8315}_{\pm638}$	$76.11_{\pm6.29}$	$11.31_{\pm1.06}$
	TabFlowM	$\underline{0.067}_{\pm0.008}$	$\mathbf{0.021}_{\pm0.001}$	$\mathbf{5785}_{\pm1193}$	$\mathbf{69.41}_{\pm16.21}$	$\mathbf{6.44}_{\pm1.01}$

strongest Shape/Trend scores, and cflow tracks it closely while mildly improving MLE on some datasets. However, this expressivity comes at a substantial computational cost: both TabDiff and cflow remain an order of magnitude slower to sample than TabFlowM, and on *Diabetes* they are also far more expensive to train. By contrast, the minimalist TabFlowM latent generator attains the best overall balance: it matches or surpasses TabDiff and cflow on four of six datasets in Shape/Trend (*Adult*, *Default*, *Magic*, *News*), dominates MLE on five of six, and does so with consistently lower training and sampling times. This ablation therefore suggests that TabDiff-style per-feature schedulers can be combined with flow matching to boost a heavy backbone, but that most of the practical benefits can be captured by a lean FM design in the TabSyn style latent space.

8 Conclusion

We have introduced TabFlowM, a minimalist flow matching framework operating in the latent space of a transformer VAE for mixed-type tabular data. Experiments on six public benchmarks show that TabFlowM matches or surpasses strong diffusion based baselines in Shape, Trend, and column-wise MLE metrics, while achieving competitive C2ST-LR and markedly lower training and sampling cost. This performance extends to the BAF fraud dataset with class imbalance, where TabFlowM achieves the best MLE/fraud detection performance among the compared diffusion-based methods. Taken together, these results suggest that once a decoder-compatible latent transport space has been constructed, deterministic flow matching captures most of the practical benefits of diffusion without requiring its full score-based framework. Ablation studies further indicate that a single FM generator in a shared latent space captures most of the practical benefits of heavier diffusion backbones, highlighting transport design rather than architectural complexity as a key driver of performance.

A limitation of TabFlowM is that its minimalist flow matching design relies on a single global transport path in the learned latent space, which may underfit highly multimodal regions or regimes with extreme categorical sparsity. Moreover, model performance depends on the VAE's ability to construct a well behaved transport space. Future work will therefore investigate feature conditioned velocity fields, richer path geometries, and more adaptive latent transport mechanisms to better handle such challenging regimes.

References

Jim Achterberg, Marcel Haas, Bram van Dijk, and Marco Spruit. Fidelity-agnostic synthetic data generation improves utility while retaining privacy. *Patterns*, 6(10), 2025.

Mohamed Aghaddar, Liu Nuo Su, Manel Slokom, Lucas Barnhoorn, and Peter-Paul de Wolf. A case study exploring data synthesis strategies on tabular vs. aggregated data sources for official statistics. In *International Conference on Privacy in Statistical Databases*, pp. 420–435. Springer, 2024.

Arthur Asuncion, David Newman, et al. Uci machine learning repository, 2007.

Ricky TQ Chen and Yaron Lipman. Flow matching on general geometries. In *12th International Conference on Learning Representations, ICLR 2024*, 2024.

Itai Gat, Tal Remez, Neta Shaul, Felix Kreuk, Ricky TQ Chen, Gabriel Synnaeve, Yossi Adi, and Yaron Lipman. Discrete flow matching. *Advances in Neural Information Processing Systems*, 37:133345–133385, 2024.

Manbir Gulati and Paul Roysdon. Tabmt: Generating tabular data with masked transformers. *Advances in Neural Information Processing Systems*, 36:46245–46254, 2023.

Andrés Guzmán-Cordero, Floor Eijkelboom, and Jan-Willem van de Meent. Exponential family variational flow matching for tabular data generation. In *The Forty-Second International Conference on Machine Learning*, 2025.

Sérgio Jesus, José Pombal, Duarte Alves, André Cruz, Pedro Saleiro, Rita P. Ribeiro, João Gama, and Pedro Bizarro. Turning the Tables: Biased, Imbalanced, Dynamic Tabular Datasets for ML Evaluation. *Advances in Neural Information Processing Systems*, 2022.

Alexia Jolicoeur-Martineau, Kilian Fatras, and Tal Kachman. Generating and imputing tabular data via diffusion and flow-based gradient-boosted trees. In *International conference on artificial intelligence and statistics*, pp. 1288–1296. PMLR, 2024.

Tero Karras, Miika Aittala, Timo Aila, and Samuli Laine. Elucidating the design space of diffusion-based generative models. In *Annual Conference on Neural Information Processing Systems. NeurIPS*, 2022.

Jayoung Kim, Chaejeong Lee, and Noseong Park. Stasy: Score-based tabular data synthesis. In *11th International Conference on Learning Representations, ICLR*, 2023.

Akim Kotelnikov, Dmitry Baranchuk, Ivan Rubachev, and Artem Babenko. Tabddpm: Modelling tabular data with diffusion models. In *International Conference on Machine Learning*, pp. 17564–17579. PMLR, 2023.

Chaejeong Lee, Jayoung Kim, and Noseong Park. Codi: Co-evolving contrastive diffusion models for mixed-type tabular synthesis. In *International Conference on Machine Learning*, pp. 18940–18956. PMLR, 2023.

Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matthew Le. Flow matching for generative modeling. In *The Eleventh International Conference on Learning Representations*, 2023.

Changshuo Liu and Canyao Liu. Entity-based financial tabular data synthesis with diffusion models. In *5th ACM International Conference on AI in Finance*, pp. 547–554, 2024.

Melle Mendikowski and Mattis Hartwig. Creating customers that never existed: Synthesis of e-commerce data using ctgan. In *18th International Conference on Machine Learning and Data Mining (MLDM-22)*, pp. 91–105, 2022.

Alireza Hossein Zadeh Nik, Michael A Riegler, Pål Halvorsen, and Andrea M Storås. Generation of synthetic tabular healthcare data using generative adversarial networks. In *International Conference on Multimedia Modeling*, pp. 434–446. Springer, 2023.

Neha Patki, Roy Wedge, and Kalyan Veeramachaneni. The synthetic data vault. In *2016 IEEE international conference on data science and advanced analytics (DSAA)*, pp. 399–410. IEEE, 2016.

Juntong Shi, Minkai Xu, Harper Hua, Hengrui Zhang, Stefano Ermon, and Jure Leskovec. Tabdiff: a unified diffusion model for multi-modal tabular data generation. In *NeurIPS 2024 Third Table Representation Learning Workshop*, 2024.

Aivin V. Solatorio and Olivier Dupriez. Realtabformer: Generating realistic relational and tabular data using transformers, 2023. URL https://arxiv.org/abs/2302.02041.

Lei Xu, Maria Skoularidou, Alfredo Cuesta-Infante, and Kalyan Veeramachaneni. Modeling tabular data using conditional gan. *Advances in neural information processing systems*, 32, 2019.

Hengrui Zhang, Jiani Zhang, Balasubramaniam Srinivasan, Zhengyuan Shen, Xiao Qin, Christos Faloutsos, Huzefa Rangwala, and George Karypis. Mixed-type tabular data synthesis with score-based diffusion in latent space. In *12th International Conference on Learning Representations*, 2024.

Jiahui Zhou, Nayyar Abbas Zaidi, Yishuo Zhang, Paul Montague, Junae Kim, and Gang Li. Leveraging generative models for combating adversarial attacks on tabular datasets. In Hisashi Kashima, Tsuyoshi Ide, and Wen-Chih Peng (eds.), *Advances in Knowledge Discovery and Data Mining, PAKDD 2023, Proceedings, Part I*, pp. 147–158. Springer, 2023. doi: 10.1007/978-3-031-33374-3_12.

Michael Zuo, Inwon Kang, Stacy Patterson, and Oshani Seneviratne. Measuring privacy risks and tradeoffs in financial synthetic data generation. In *The Second International Workshop on Transformative Insights in Multifaceted Evaluation at The Web Conference 2026*, 2026.

A Appendix

A.1 Dataset Details

This section specifies the details of the datasets used for evaluation.

UCI Machine Learning Repository

Dataset	# Rows	# Num	# Cat	# Train	# Validation	# Test	Task
Adult	48,842	6	9	28,943	3,618	16,281	Classification
Default	30,000	14	11	24,000	3,000	3,000	Classification
Diabetes	768	7	2	614	77	77	Classification
Magic	19,019	10	1	15,215	1,902	1,902	Classification
Beijing	43,824	7	5	35,058	4,383	4,383	Regression
News	39,644	46	2	31,714	3,965	3,965	Regression

Bank Account Fraud Dataset Suite (BAF)

The *Bank Account Fraud (BAF) Dataset Suite* Jesus et al. (2022), published at NeurIPS 2022, is a widely used open-source collection of six synthetic tabular datasets released on Kaggle. It is specifically designed to benchmark machine learning models for *bank account opening fraud detection* and is often regarded as a realistic, privacy-preserving, and challenging testbed for detecting *synthetic identity fraud*. All variants of the BAF dataset contain 1,000,000 entries and 32 columns, comprising 17 categorical and 15 numerical features. The imbalance ratio across each variant is also on average 100:1.

A.2 Evaluation metrics

Let $\mathcal{N}$ and $\mathcal{C}$ denote the index sets of numerical and categorical columns, respectively, and let $d = |\mathcal{N}| + |\mathcal{C}|$.

Shape. For every column j we compare the empirical marginal distributions of real and synthetic data with

$$\text{Shape} \;=\; \frac{1}{d}\sum_{j=1}^{d}\begin{cases}\text{KST}\big(X_j^{\text{real}}, X_j^{\text{syn}}\big), & j \in \mathcal{N},\\ \text{TVD}\big(X_j^{\text{real}}, X_j^{\text{syn}}\big), & j \in \mathcal{C},\end{cases}$$

where KST denotes the two-sample Kolmogorov–Smirnov statistic and Total-variation distance TVD between empirical probability vectors. Shape $\in [0, 1]$ with lower values indicating closer agreement.

Trend. For every same-type column pair (j, k) we measure the discrepancy of second-order statistics:

$$\text{Trend} \;=\; \frac{1}{|\{(j, k)\}|}\sum_{\substack{j < k \\ (j,k) \text{ same type}}}\begin{cases}\frac{1}{2}\big|\rho_{jk}^{\text{real}} - \rho_{jk}^{\text{syn}}\big|, & j, k \in \mathcal{N},\\ \frac{1}{2}\sum_{a,b}\big|P_{jk}^{\text{real}}(a, b) - P_{jk}^{\text{syn}}(a, b)\big|, & j, k \in \mathcal{C}.\end{cases}$$

Pairs mixing numerical and categorical attributes are ignored, following TabDiff's original definition.

Column-wise MLE. We evaluate conditional fidelity by training a separate downstream predictor for each target column. For every feature x_j, we treat the remaining attributes $x_{\setminus j}$ as inputs and train an XGBoost model on the synthetic dataset to predict x_j. The trained model is then evaluated on a held-out 20% split of real data, quantifying how well relationships learned from synthetic samples generalize to the true distribution. For categorical targets, we employ binary or multiclass objectives and report the area under the receiver operating characteristic curve (AUC ↑), while for numerical targets we use a regression objective and report the root-mean-square error (RMSE ↓). Averaging these per-column scores yields dataset-level indicators of conditional dependency fidelity between real and synthetic data.

C2ST-LR. Classifier Two-Sample Test with Logistic Regression: we label real rows as 1 and synthetic rows as 0, train a logistic regression discriminator, and report the ROC-AUC on a held-out split. Values close to 0.5 indicate that real and synthetic samples are hard to distinguish (better), while higher values indicate greater distinguishability (worse). We average the ROC-AUC over five random train/test splits.

A.3 Further Evaluation Details

For all baselines, we use a common training budget of 100 epochs. Our goal is not to reproduce each method's original long run configuration exactly, but to compare methods under a unified and practical optimization budget. This controlled budget keeps runtime comparisons interpretable across heterogeneous model families, avoids large disparities in training duration across methods, and makes large scale experiments such as BAF tractable. To show that each model is trained sufficiently we show the training validation loss for Tabdiff and TabSyn's VAE in Fig.3 for News, the largest dataset among the UCI machine learning repository datasets.

Figure 3: News Dataset Validation Loss for Tabsyn (VAE) (left) and TabDiff (right)

Interestingly, under our unified preprocessing/splitting/evaluation pipeline, the 100 epoch versions of TabSyn and TabDiff achieve **improved** fidelity scores while exhibiting **lower** variance. This suggests that much of their practical performance may already emerge under a moderate training budget.

A.4 Proofs

A.4.1 Geometric Justification for Transport in decoder compatible Token Space (Proposition 1)

This section formalizes the geometric motivation for performing flow matching in the learned decoder compatible token space rather than directly in raw mixed-type coordinates. The first part of the result shows that straight interpolation in one-hot categorical space immediately leaves the set of valid categorical states. The second part shows that, under mild local regularity of the reconstruction map, straight segments in the continuous token representation decode to trajectories with controlled bending. Together, these two observations justify why simple transport paths are substantially more natural in this learned representation than in the original mixed-type space.

Proposition 1 (Raw-space mismatch versus decoder compatible token-space regularity)
Straight interpolation is geometrically mismatched in raw one-hot space, whereas in decoder compatible token space it decodes to trajectories with uniformly controlled bending under mild local regularity.

More precisely, consider two records that differ only in one categorical column j, whose one-hot encodings are $e_a, e_b \in \{0,1\}^{C_j}$ with $a \neq b$, where C_j is the number of categories in column j.

(Raw-space mismatch). For any $t \in (0,1)$,

$$(1-t)e_a + te_b \in \Delta^{C_j - 1} \setminus \{e_1, \ldots, e_{C_j}\},$$

so the straight segment between e_a and e_b leaves the set of valid categorical states. Hence straight Euclidean interpolation in raw one-hot space does not remain on the discrete data manifold.

(decoder compatible token-space regularity). Let $R : \mathbb{R}^D \to \mathbb{R}^q$ denote the reconstruction map from flattened decoder compatible token representations to decoded outputs, where $D = M d_e$ is the dimension of the flattened token representation and q is the ambient dimension of the decoded output space. Let

$$\gamma(t) = (1-t)r_1 + tr_2, \qquad t \in [0,1],$$

be a straight segment between two token-space points $r_1, r_2 \in \mathbb{R}^D$, and define the decoded trajectory

$$x(t) = R(\gamma(t)).$$

Assume that R is twice continuously differentiable on a convex region containing $\gamma([0,1])$, and that for all u on this segment,

$$\|H_R(u)\|_{\mathrm{op}} \leq \beta, \qquad \sigma_{\min}(J_R(u)) \geq m > 0,$$

where $J_R(u)$ and $H_R(u)$ denote the Jacobian and Hessian of R at u, respectively. Then

$$\|\dot{x}(t)\|_2 \geq m \|r_2 - r_1\|_2, \qquad \|\ddot{x}(t)\|_2 \leq \beta \|r_2 - r_1\|_2^2,$$

and therefore

$$\frac{\|\ddot{x}(t)\|_2}{\|\dot{x}(t)\|_2^2} \leq \frac{\beta}{m^2}.$$

Thus the decoded image of a straight token-space segment has uniformly controlled normalized bending.

Proof. We prove the two parts in turn.

For the raw-space statement, let e_a and e_b be distinct one-hot vectors. For any $t \in (0,1)$, the vector

$$(1-t)e_a + te_b$$

has two strictly positive entries, namely $1-t$ in coordinate a and t in coordinate b, and zeros elsewhere. Hence it lies in the simplex $\Delta^{C_j - 1}$ but is not itself a vertex, so it is not a valid categorical state.

For the token-space statement, differentiate the decoded path $x(t) = R(\gamma(t))$ along the straight segment $\gamma(t) = (1-t)r_1 + tr_2$. By the chain rule,

$$\dot{x}(t) = J_R(\gamma(t))(r_2 - r_1), \tag{18}$$

and

$$\ddot{x}(t) = H_R(\gamma(t))[r_2 - r_1,\, r_2 - r_1]. \tag{19}$$

The lower bound on the smallest singular value of $J_R(\gamma(t))$ yields

$$\|\dot{x}(t)\|_2 = \|J_R(\gamma(t))(r_2 - r_1)\|_2 \geq m \, \|r_2 - r_1\|_2.$$

Similarly, the Hessian bound implies

$$\|\ddot{x}(t)\|_2 = \|H_R(\gamma(t))[r_2 - r_1,\, r_2 - r_1]\|_2 \leq \beta \, \|r_2 - r_1\|_2^2.$$

Combining the two inequalities gives

$$\frac{\|\ddot{x}(t)\|_2}{\|\dot{x}(t)\|_2^2} \leq \frac{\beta \, \|r_2 - r_1\|_2^2}{m^2 \, \|r_2 - r_1\|_2^2} = \frac{\beta}{m^2}.$$

Proposition 1 isolates the geometric contrast used in the main text: raw mixed-type coordinates are poorly suited to straight interpolation, whereas decoder compatible token coordinates admit simple paths whose decoded trajectories remain well behaved under local regularity. This supports moving transport into the learned continuous representation, after which a lightweight path choice can be introduced in the main method.

A.4.2 Endpoint Control and Wasserstein Convergence of the Minimalist FM Surrogate (Proposition 2)

Proposition 2 (Endpoint control from pathwise velocity regression) *Under the linear-path FM surrogate, if the learned velocity field is Lipschitz in state, then small flow-matching regression error along the reference coupling path implies small endpoint error, and hence Wasserstein closeness between the generated token-space distribution and the target token-space distribution.*

Proof. Let $e_t := x_t - x_t^\star$. Since $x_0 = \varepsilon = x_0^\star$, we have $e_0 = 0$. Also,

$$\dot{e}_t = v_\theta(x_t, t) - v^\star = \big(v_\theta(x_t, t) - v_\theta(x_t^\star, t)\big) + \big(v_\theta(x_t^\star, t) - v^\star\big).$$

Hence, by the triangle inequality and the L-Lipschitz assumption,

$$\frac{d}{dt}\|e_t\|_2 \;\leq\; L\|e_t\|_2 + r_\theta(t; \varepsilon, \tilde{z}_0).$$

Applying Grönwall's inequality with $e_0 = 0$ yields

$$\|e_1\|_2 \leq \int_0^1 e^{L(1-s)} r_\theta(s; \varepsilon, \tilde{z}_0)\, ds \leq e^L \int_0^1 r_\theta(s; \varepsilon, \tilde{z}_0)\, ds.$$

Since $x_1^\star = \tilde{z}_0$, this proves

$$\|x_1 - \tilde{z}_0\|_2 \leq e^L \int_0^1 r_\theta(s; \varepsilon, \tilde{z}_0)\, ds.$$

Now couple x_1 and $\tilde{z}_0$ using the same draw $(\varepsilon, \tilde{z}_0)$. By the definition of W_1,

$$W_1(P_\theta, P_{\text{tok}}) \leq \mathbb{E}\|x_1 - \tilde{z}_0\|_2 \leq e^L \, \mathbb{E}\!\left[\int_0^1 r_\theta(t; \varepsilon, \tilde{z}_0)\, dt\right].$$

Next, because $t \sim \text{Unif}[0, 1]$, Eq. (15) implies

$$2L_{\text{FM}}(\theta) = \mathbb{E}\!\left[\int_0^1 \|v_\theta(x_t^\star, t) - v^\star\|_2^2\, dt\right].$$

Using Cauchy–Schwarz on $[0, 1]$,

$$\int_0^1 r_\theta(t)\, dt \leq \left(\int_0^1 r_\theta(t)^2\, dt \right)^{1/2},$$

and then Jensen's inequality gives

$$\mathbb{E}\left[\int_0^1 r_\theta(t)\, dt \right] \leq \sqrt{\mathbb{E}\left[\int_0^1 r_\theta(t)^2\, dt \right]} = \sqrt{2L_{\mathrm{FM}}(\theta)}.$$

Therefore,

$$W_1(P_\theta, P_{\mathrm{tok}}) \leq e^L \sqrt{2L_{\mathrm{FM}}(\theta)}.$$

Finally, if $\widehat{x}_1$ is the numerical endpoint produced by the solver, then by the triangle inequality,

$$\|\widehat{x}_1 - \tilde{z}_0\|_2 \leq \|\widehat{x}_1 - x_1\|_2 + \|x_1 - \tilde{z}_0\|_2.$$

Taking expectations and infimizing over couplings yields

$$W_1(\widehat{P}_\theta, P_{\mathrm{tok}}) \leq \mathbb{E}\|\widehat{x}_1 - x_1\|_2 + W_1(P_\theta, P_{\mathrm{tok}}) \leq \eta_h + e^L \sqrt{2L_{\mathrm{FM}}(\theta)}.$$

This completes the proof.

A.5 Hyperparameter Search and Hardware Specifications

All experiments are conducted on AMD Threadripper PRO 7955WX (16 cores), an NVIDIA RTX 6000 Ada (48 GB), and 128 GB DDR5 RAM. For each baseline, we performed a grid search over hyperparameter values reported in prior literature specifically Zhang et al. (2024); Shi et al. (2024). Note that TabSyn and TabFlowM shares the same parameter configuration. The final hyperparameters used for benchmarking are summarized below.

Table 9: Hyperparameters for TabSyn & TabFlowM.

Parameter	Value
token_dim (d)	4
vae_num_layers (encoder/decoder)	2
vae_transformer_ffn_dim	128
beta_max	0.01
beta_max (Shoppers)	0.001
beta_min	1e-5
lambda	0.7
diffusion_mlp_hidden_dim	1024

Table 10: Hyperparameters for TABDIFF (from the provided config file).

Parameter	Value
data.dequant_dist	none
data.int_dequant_factor	0
diffusion_params.cat_scheduler	log_linear
diffusion_params.edm_params.net_conditioning	sigma
diffusion_params.edm_params.precond	True
diffusion_params.edm_params.sigma_data	1
diffusion_params.noise_dist	uniform_t
diffusion_params.noise_dist_params.P_mean	-1.2
diffusion_params.noise_dist_params.P_std	1.2
diffusion_params.noise_schedule_params.eps_max	0.001
diffusion_params.noise_schedule_params.eps_min	1e-05
diffusion_params.noise_schedule_params.k_init	-6
diffusion_params.noise_schedule_params.k_offset	1
diffusion_params.noise_schedule_params.rho	7
diffusion_params.noise_schedule_params.rho_init	7
diffusion_params.noise_schedule_params.rho_offset	5
diffusion_params.noise_schedule_params.sigma_max	80
diffusion_params.noise_schedule_params.sigma_min	0.002
diffusion_params.num_timesteps	50
diffusion_params.sampler_params.second_order_correction	True
diffusion_params.sampler_params.stochastic_sampler	True
diffusion_params.scheduler	power_mean
train.main.batch_size	4096
train.main.c_lambda	1
train.main.check_val_every	500
train.main.closs_weight_schedule	anneal
train.main.d_lambda	1
train.main.ema_decay	0.997
train.main.factor	0.9
train.main.lr	0.001
train.main.lr_scheduler	reduce_lr_on_plateau
train.main.reduce_lr_patience	50
train.main.steps	500
train.main.weight_decay	0
sample.batch_size	10000
unimodmlp_params.bias	True
unimodmlp_params.d_token	4
unimodmlp_params.dim_t	1024
unimodmlp_params.factor	32
unimodmlp_params.n_head	1
unimodmlp_params.num_layers	2
unimodmlp_params.use_mlp	True

Table 11: Hyperparameters for TVAE.

Parameter	Value
enforce_min_max_values	True
enforce_rounding	True
embedding_dim	128
compress_dims	(128, 128)
decompress_dims	(128, 128)
l2scale	1e-05
batch_size	500
verbose	True
epochs	100
loss_factor	2
cuda	True

Table 12: Hyperparameters for CTGAN.

Parameter	Value
enforce_min_max_values	True
enforce_rounding	True
locales	['en_US']
embedding_dim	128
generator_dim	(256, 256)
discriminator_dim	(256, 256)
generator_lr	0.0002
generator_decay	1e-06
discriminator_lr	0.0002
discriminator_decay	1e-06
batch_size	500
discriminator_steps	1
log_frequency	True
verbose	True
epochs	100
pac	10
cuda	True

Table 13: Hyperparameters for CopulaGAN.

Parameter	Value
enforce_min_max_values	True
enforce_rounding	True
locales	['en_US']
numerical_distributions	{}
default_distribution	beta