LOCAL SEARCH ALGORITHMS FOR RANK-CONSTRAINED CONVEX OPTIMIZATION

ABSTRACT

We propose greedy and local search algorithms for rank-constrained convex optimization, namely solving $\min\limits_{\text{rank}(A)\leq r^*} R(A)$ given a convex function $R : \mathbb{R}^{m \times n} \to \mathbb{R}$ and a parameter r^*. These algorithms consist of repeating two steps: (a) adding a new rank-1 matrix to A and (b) enforcing the rank constraint on A. We provide a tight theoretical analysis showing that if the *rank-restricted* condition number of R is κ, a solution A with rank $O(r^* \cdot \min\{\kappa \log \frac{R(\mathbf{0})-R(A^*)}{\epsilon}, \kappa^2\})$ and $R(A) \leq R(A^*) + \epsilon$ can be recovered, where A^* is the optimal solution. This significantly generalizes associated results on sparse convex optimization, as well as rank-constrained convex optimization for smooth functions. We then introduce new practical variants of these algorithms that have superior runtime and recover better solutions in practice. We demonstrate the versatility of these methods on a wide range of applications involving matrix completion and robust principal component analysis.

1 INTRODUCTION

Given a real-valued convex function $R : \mathbb{R}^{m \times n} \to \mathbb{R}$ on real matrices and a parameter $r^* \in \mathbb{N}$, the *rank-constrained convex optimization* problem consists of finding a matrix $A \in \mathbb{R}^{m \times n}$ that minimizes $R(A)$ among all matrices of rank at most r^*:

$$\min_{\text{rank}(A)\leq r^*} R(A) \tag{1}$$

Even though R is convex, the rank constraint makes this problem non-convex. Furthermore, it is known that this problem is NP-hard and even hard to approximate (Natarajan (1995); Foster et al. (2015)).

In this work, we propose efficient greedy and local search algorithms for this problem. Our contribution is twofold:

1. We provide theoretical analyses that bound the rank and objective value of the solutions returned by the two algorithms in terms of the *rank-restricted condition number*, which is the natural generalization of the condition number for low-rank subspaces. The results are significantly stronger than previous known bounds for this problem.

2. We experimentally demonstrate that, after careful performance adjustments, the proposed general-purpose greedy and local search algorithms have superior performance to other methods, even for some of those that are tailored to a particular problem. Thus, these algorithms can be considered as a general tool for rank-constrained convex optimization and a viable alternative to methods that use convex relaxations or alternating minimization.

The rank-restricted condition number   Similarly to the work in sparse convex optimization, a restricted condition number quantity has been introduced as a reasonable assumption on R. If we let ρ_r^+ be the maximum smoothness bound and ρ_r^- be the minimum strong convexity bound only along rank-r directions of R (these are called rank-restricted smoothness and strong convexity respectively), the rank-restricted condition number is defined as $\kappa_r = \frac{\rho_r^+}{\rho_r^-}$. If this quantity is bounded, one can efficiently find a solution A with $R(A) \leq R(A^*) + \epsilon$ and rank $r = O(r^* \cdot \kappa_{r+r^*} \frac{R(\mathbf{0})}{\epsilon})$ using

a greedy algorithm (Shalev-Shwartz et al. (2011)). However, this is not an ideal bound since the rank scales linearly with $\frac{R(\mathbf{0})}{\epsilon}$, which can be particularly high in practice. Inspired by the analogous literature on sparse convex optimization by Natarajan (1995); Shalev-Shwartz et al. (2010); Zhang (2011); Jain et al. (2014) and more recently Axiotis & Sviridenko (2020), one would hope to achieve a logarithmic dependence or no dependence at all on $\frac{R(\mathbf{0})}{\epsilon}$. In this paper we achieve this goal by providing an improved analysis showing that the greedy algorithm of Shalev-Shwartz et al. (2011) in fact returns a matrix of rank of $r = O(r^* \cdot \kappa_{r+r^*} \log \frac{R(\mathbf{0})}{\epsilon})$. We also provide a new local search algorithm together with an analysis guaranteeing a rank of $r = O(r^* \cdot \kappa_{r+r^*}^2)$. Apart from significantly improving upon previous work on rank-restricted convex optimization, these results directly generalize a lot of work in sparse convex optimization, e.g. Natarajan (1995); Shalev-Shwartz et al. (2010); Jain et al. (2014). Our algorithms and theorem statements can be found in Section 2.

Runtime improvements Even though the rank bound guaranteed by our theoretical analyses is adequate, the algorithm runtimes leave much to be desired. In particular, both the greedy algorithm of Shalev-Shwartz et al. (2011) and our local search algorithm have to solve an optimization problem in each iteration in order to find the best possible linear combination of features added so far. Even for the case that $R(A) = \frac{1}{2} \sum_{(i,j) \in \Omega} (M - A)_{ij}^2$, this requires solving a least squares problem on $|\Omega|$ examples and r^2 variables. For practical implementations of these algorithms, we circumvent this issue by solving a related optimization problem that is usually much smaller. This instead requires solving n least squares problems with *total* number of examples $|\Omega|$, each on r variables. This not only reduces the size of the problem by a factor of r, but also allows for a straightforward distributed implementation. Interestingly, our theoretical analyses still hold for these variants. We propose an additional heuristic that reduces the runtime even more drastically, which is to only run a few (less than 10) iterations of the algorithm used for solving the inner optimization problem. Experimental results show that this modification not only does not significantly worsen results, but for machine learning applications also acts as a regularization method that can dramatically improve generalization. These matters, as well as additional improvements for making the local search algorithm more practical, are addressed in Section 2.3.

Roadmap In Section 2, we provide the descriptions and theoretical results for the algorithms used, along with several modifications to boost performance. In Section 3, we evaluate the proposed greedy and local search algorithms on optimization problems like robust PCA. Then, in Section 4 we evaluate their generalization performance in machine learning problems like matrix completion.

2 ALGORITHMS & THEORETICAL GUARANTEES

In Sections 2.1 and 2.2 we state and provide theoretical performancee guarantees for the basic greedy and local search algorithms respectively. Then in Section 2.3 we state the algorithmic adjustments that we propose in order to make the algorithms efficient in terms of runtime and generalization performance.

When the dimension is clear from context, we will denote the all-ones vector by $\mathbf{1}$, and the vector that is 0 everywhere and 1 at position i by $\mathbf{1}_i$. Given a matrix A, we denote by $\text{im}(A)$ its column span. One notion that we will found useful is that of *singular value thresholding*. More specifically, given a rank-k matrix $A \in \mathbb{R}^{m \times n}$ with SVD $\sum_{i=1}^{k} \sigma_i u^i v^{i\top}$ such that $\sigma_1 \geq \cdots \geq \sigma_k$, as well as an integer parameter $r \geq 1$, we define $H_r(A) = \sum_{i=1}^{r} \sigma_i u^i v^{i\top}$ to be the operator that truncates to the r highest singular values of A.

2.1 GREEDY

Theorem 2.1 (Algorithm 1 (greedy) analysis). *Let A^* be the optimal solution of (1) for some function R and rank bound r^*, and let $\epsilon > 0$ be an error parameter. For any integer $r \geq 2r^* \cdot \kappa_{r+r^*} \log \frac{R(\mathbf{0}) - R(A^*)}{\epsilon}$, if we let $A = \text{GREEDY}(r)$ be the solution returned by Algorithm 1, then $R(A) \leq R(A^*) + \epsilon$. The number of iterations is r.*

Algorithm 1 Greedy

1: **procedure** GREEDY($r \in \mathbb{N}$: target rank)
2:     function to be minimized $R : \mathbb{R}^{m \times n} \to \mathbb{R}$
3:     $U \in \mathbb{R}^{m \times 0}$ ▷ Initially rank is zero
4:     $V \in \mathbb{R}^{n \times 0}$
5:     **for** $t = 0 \ldots r - 1$ **do**
6:         $\sigma u v^\top \leftarrow H_1(\nabla R(UV^\top))$ ▷ Max singular value σ and corresp. singular vectors u, v
7:         $U \leftarrow (U \quad u)$ ▷ Append new vectors as columns
8:         $V \leftarrow (V \quad v)$
9:         $U, V \leftarrow$ OPTIMIZE(U, V)
10:     **return** $UV^\top$
11: **procedure** OPTIMIZE($U \in \mathbb{R}^{m \times r}, V \in \mathbb{R}^{n \times r}$)
12:     $X \leftarrow \underset{X \in \mathbb{R}^{r \times r}}{\arg \min} R(UXV^\top)$
13:     **return** UX, V

2.2 LOCAL SEARCH

Algorithm 2 Local Search

1: **procedure** LOCAL_SEARCH($r \in \mathbb{N}$: target rank)
2:     function to be minimized $R : \mathbb{R}^{m \times n} \to \mathbb{R}$
3:     $U \leftarrow \mathbf{0}_{m \times r}$ ▷ Initialize with all-zero solution
4:     $V \leftarrow \mathbf{0}_{n \times r}$
5:     **for** $t = 0 \ldots L - 1$ **do**   ▷ Run for L iterations
6:         $\sigma u v^\top \leftarrow H_1(\nabla R(UV^\top))$ ▷ Max singular value σ and corresp. singular vectors u, v
7:         $U, V \leftarrow$ TRUNCATE(U, V) ▷ Reduce rank of $UV^\top$ by one
8:         $U \leftarrow (U \quad u)$ ▷ Append new vectors as columns
9:         $V \leftarrow (V \quad v)$
10:         $U, V \leftarrow$ OPTIMIZE(U, V)
11:     **return** $UV^\top$
12: **procedure** TRUNCATE($U \in \mathbb{R}^{m \times r}, V \in \mathbb{R}^{n \times r}$)
13:     $U\Sigma V^\top \leftarrow$ SVD$(H_{r-1}(UV^\top))$ ▷ Keep all but minimum singular value
14:     **return** $U\Sigma, V$

Theorem 2.2 (Algorithm 2 (local search) analysis). *Let A^* be the optimal solution of (1) for some function R and rank bound r^*, and let $\epsilon > 0$ be an error parameter. For any integer $r \geq r^* \cdot (1 + 8\kappa_{r+r^*}^2)$, if we let $A = $ LOCAL_SEARCH(r) be the solution returned by Algorithm 2, then $R(A) \leq R(A^*) + \epsilon$. The number of iterations is $O\left(r^* \kappa_{r+r^*} \log \frac{R(\mathbf{0}) - R(A^*)}{\epsilon}\right)$.*

2.3 ALGORITHMIC ADJUSTMENTS

Inner optimization problem   The inner optimization problem that is used in both greedy and local search is:

$$\min_{X \in \mathbb{R}^{r \times r}} R(UXV^\top). \tag{2}$$

It essentially finds the choice of matrices U' and V', with columns in the column span of U and V respectively, that minimizes $R(U'V'^\top)$. We, however, consider the following problem instead:

$$\min_{V \in \mathbb{R}^{n \times r}} R(UV^\top). \tag{3}$$

Note that the solution recovered from (3) will never have worse objective value than the one recovered from (2), and that nothing in the analysis of the algorithms breaks. Importantly, (3) can usually be solved much more efficiently than (2). As an example, consider the following objective that appears in matrix completion: $R(A) = \frac{1}{2} \sum_{(i,j) \in \Omega} (M - A)_{ij}^2$ for some $\Omega \subseteq [m] \times [n]$. If

we let $\Pi_\Omega(\cdot)$ be an operator that zeroes out all positions in the matrix that are not in Ω, we have $\nabla R(A) = -\Pi_\Omega(M - A)$. The optimality condition of (2) now is $U^\top \Pi_\Omega(M - UXV^\top)V = \mathbf{0}$ and that of (3) is $U^\top \Pi_\Omega(M - UV^\top) = \mathbf{0}$. The former corresponds to a least squares linear regression problem with $|\Omega|$ examples and r^2 variables, while the latter can be decomposed into n independent

systems $U^\top \left(\sum_{i:(i,j)\in\Omega} \mathbf{1}_i \mathbf{1}_i^\top \right) UV^j = U^\top \Pi_\Omega(M\mathbf{1}_j)$, where the variable is V^j which is the j-th

column of V. The j-th of these systems corresponds to a least squares linear regression problem with $|\{i : (i,j) \in \Omega\}|$ examples and r variables. Note that the total number of examples in all systems is $\sum_{j\in[n]} |\{i : (i,j) \in \Omega\}| = |\Omega|$. The choice of V here as the variable to be optimized is

arbitrary. In particular, as can be seen in Algorithm 3, in practice we alternate between optimizing U and V in each iteration. It is worthy of mention that the OPTIMIZE_FAST procedure is basically the same as one step of the popular alternating minimization procedure for solving low-rank problems. As a matter of fact, when our proposed algorithms are viewed from this lens, they can be seen as alternating minimization interleaved with rank-1 insertion and/or removal steps.

Algorithm 3 Fast inner Optimization

1: **procedure** OPTIMIZE_FAST($U \in \mathbb{R}^{m\times r}, V \in \mathbb{R}^{n\times r}, t \in \mathbb{N}$: iteration index of algorithm)
2:     **if** $t \bmod 2 = 0$ **then**
3:         $X \leftarrow \underset{X\in\mathbb{R}^{m\times r}}{\arg\min} R(XV^\top)$
4:         **return** X, V
5:     **else**
6:         $X \leftarrow \underset{X\in\mathbb{R}^{n\times r}}{\arg\min} R(UX^\top)$
7:         **return** U, X

Singular value decomposition As modern methods for computing the top entries of a singular value decomposition scale very well even for large sparse matrices (Martinsson et al. (2011); Szlam et al. (2014); Tulloch (2014)), the "insertion" step of greedy and local search, in which the top entry of the SVD of the gradient is determined, is quite fast in practice. However, these methods are not suited for computing the *smallest* singular values and corresponding singular vectors, a step required for the local search algorithm that we propose. Therefore, in our practical implementations we opt to perfom the alternative step of directly removing one pair of vectors from the representation $UV^\top$. A simple approach is to go over all r possible removals and pick the one that increases the objective by the least amount. A variation of this approach has been used by Shalev-Shwartz et al. (2011). However, a much faster approach is to just pick the pair of vectors $U\mathbf{1}_i, V\mathbf{1}_i$ that minimizes $\|U\mathbf{1}_i\|_2\|V\mathbf{1}_i\|_2$. This is the approach that we use, as can be seen in Algorithm 4.

Algorithm 4 Fast rank reduction

1: **procedure** TRUNCATE_FAST($U \in \mathbb{R}^{m\times r}, V \in \mathbb{R}^{n\times r}$)
2:     $i \leftarrow \underset{i\in[r]}{\arg\min} \|U\mathbf{1}_i\|_2\|V\mathbf{1}_i\|_2$
3:     **return** $\left(U_{[m],[1,i-1]} \quad U_{[m],[i+1,r]} \right), \left(V_{[n],[1,i-1]} \quad V_{[n],[i+1,r]} \right)$ ▷ Remove column i

---

After the previous discussion, we are ready to state the fast versions of Algorithm 1 and Algorithm 2 that we use for our experiments. These are Algorithm 2.3 and Algorithm 5. Notice that we initialize Algorithm 5 with the solution of Algorithm 2.3 and we run it until the value of $R(\cdot)$ stops decreasing rather than for a fixed number of iterations.

Algorithm 2.3 (Fast Greedy). *The Fast Greedy algorithm is defined identically as Algorithm 1, with the only difference that it uses the* OPTIMIZE_FAST *routine as opposed to the* OPTIMIZE *routine.*

3 OPTIMIZATION APPLICATIONS

An immediate application of the above algorithms is in the problem of *low rank matrix recovery*. Given any convex distance measure between matrices $d : \mathbb{R}_{m\times n} \times \mathbb{R}_{m\times n} \to \mathbb{R}_{\geq 0}$, the goal is

---

Algorithm 5 Fast Local Search

1: **procedure** FAST_LOCAL_SEARCH($r \in \mathbb{N}$: target rank)
2:      function to be minimized $R : \mathbb{R}^{m \times n} \to \mathbb{R}$
3:      $U, V \leftarrow$ solution returned by FAST_GREEDY(r)
4:      **do**
5:          $U_{\text{prev}}, V_{\text{prev}} \leftarrow U, V$
6:          $\sigma uv^\top \leftarrow H_1(\nabla R(UV^\top))$ ▷ Max singular value σ and corresp. singular vectors u, v
7:          $U, V \leftarrow$ TRUNCATE_FAST(U, V)   ▷ Reduce rank of $UV^\top$ by one
8:          $U \leftarrow (U \quad u)$ ▷ Append new vectors as columns
9:          $V \leftarrow (V \quad v)$
10:         $U, V \leftarrow$ OPTIMIZE_FAST(U, V, t)
11:      **while** $R(UV^\top) < R(U_{\text{prev}}V_{\text{prev}}^\top)$
12:      **return** $U_{\text{prev}}V_{\text{prev}}^\top$

---

to find a low-rank matrix A that matches a target matrix M as well as possible in terms of d:
$\min_{\text{rank}(A) \leq r^*} d(M, A)$ This problem captures a lot of different applications, some of which we go over in the following sections.

3.1 LOW-RANK APPROXIMATION ON OBSERVED SET

A particular case of interest is when $d(M, A)$ is the Frobenius norm of $M - A$, but only applied to entries belonging to some set Ω. In other words, $d(M, A) = \frac{1}{2}\|\Pi_\Omega(M - A)\|_F^2$. We have compared our Fast Greedy and Fast Local Search algorithms with the SoftImpute algorithm of Mazumder et al. (2010) as implemented by Rubinsteyn & Feldman (2016), on the same experiments as in Mazumder et al. (2010). We have solved the inner optimization problem required by our algorithms by the LSQR algorithm Paige & Saunders (1982). More specifically, $M = UV^\top + \eta \in \mathbb{R}^{100 \times 100}$, where η is some noise vector. We let every entry of U, V, η be i.i.d. normal with mean 0 and the entries of Ω are chosen i.i.d. uniformly at random over the set $[100] \times [100]$. The experiments have three parameters: The true rank r^* (of $UV^\top$), the percentage of observed entries $p = |\Omega|/10^4$, and the signal-to-noise ratio SNR. We measure the normalized MSE, i.e. $\|\Pi_\Omega(M - A)\|_F^2 / \|\Pi_\Omega(M)\|_F^2$. The results can be seen in Figure 1, where it is illustrated that Fast Local Search sometimes returns significantly more accurate and lower-rank solutions than Fast Greedy, and Fast Greedy generally returns significantly more accurate and lower-rank solutions than SoftImpute.

(a) $r^* = 5, p = 0.2, SNR = 10$ (b) $r^* = 6, p = 0.5, SNR = 1$

Figure 1: Objective value error vs rank in the problem of Section 3.1.

3.2 ROBUST PRINCIPAL COMPONENT ANALYSIS (RPCA)

The robust PCA paradigm asks one to decompose a given matrix M as $L + S$, where L is a low-rank matrix and S is a sparse matrix. This is useful for applications with outliers where directly

computing the principal components of M is significantly affected by them. For a comprehensive survey on Robust PCA survey one can look at Bouwmans et al. (2018). The following optimization problem encodes the above-stated requirements:

$$\min_{\text{rank}(L) \leq r^*} \|M - L\|_0 \tag{4}$$

where $\|X\|_0$ is the sparsity (i.e. number of non-zeros) of X. As neither the rank constraint or the ℓ_0 function are convex, Candès et al. (2011) replaced them by their usual convex relaxations, i.e. the nuclear norm $\|\cdot\|_*$ and ℓ_1 norm respectively. However, we opt to only relax the ℓ_0 function but not the rank constraint, leaving us with the problem:

$$\min_{\text{rank}(L) \leq r^*} \|M - L\|_1 \tag{5}$$

In order to make the objective differentiable and thus more well-behaved, we further replace the ℓ_1 norm by the Huber loss $H_\delta(x) = \begin{cases} x^2/2 & \text{if } |x| \leq \delta \\ \delta|x| - \delta^2/2 & \text{otherwise} \end{cases}$, thus getting: $\min_{\text{rank}(L) \leq r^*} \sum_{ij} H_\delta(M - L)_{ij}$. This is a problem on which we can directly apply our algorithms. We solve the inner optimization problem by applying 10 L-BFGS iterations.

In Figure 2 one can see an example of foreground-background separation from video using robust PCA. The video is from the BMC 2012 dataset Vacavant et al. (2012). In this problem, the low-rank part corresponds to the background and the sparse part to the foreground. We compare three algorithms: Our Fast Greedy algorithm, standard PCA with 1 component (the choice of 1 was picked to get the best outcome), and the standard Principal Component Pursuit (PCP) algorithm (Candès et al. (2011)), as implemented in Lin et al. (2010), where we tuned the regularization parameter λ to achieve the best result. We find that Fast Greedy has the best performance out of the three algorithms in this sample task.

Figure 2: Foreground-background separation from video. From left to right: Fast Greedy with rank=3 and Huber loss with $\delta = 20$. Standard PCA with rank=1. Principal Component Pursuit (PCP) with $\lambda = 0.002$. Both PCA and PCP have visible "shadows" in the foreground that appear as "smudges" in the background. These are less obvious in a still frame but more apparent in a video.

4 MACHINE LEARNING APPLICATIONS

4.1 REGULARIZATION TECHNIQUES

In the previous section we showed that our proposed algorithms bring down different optimization objectives aggressively. However, in applications where the goal is to obtain a low generalization

Algorithm	random_error_13	random_error_1	random_error_2
SoftImpute (Mazumder et al. (2010))	0.1759/10	0.2465/28	0.2284/30
Fast Greedy (Algorithm 2.3)	0.0673/30	0.1948/13	0.1826/21
Fast Local Search (Algorithm 5)	0.0613/14	0.1952/15	0.1811/15

Table 1: Lowest test error for any rank in the matrix completion problem of Section 4.2, and associated rank returned by each algorithm. In the form error/rank.

error, regularization is needed. We considered two different kinds of regularization. The first method is to run the inner optimization algorithm for less iterations, usually 2-3. Usually this is straightforward since an iterative method is used. For example, in the case $R(A) = \frac{1}{2}\|\Pi_\Omega(M-A)\|_F^2$ the inner optimization is a least squares linear regression problem that we solve using the LSQR algorithm. The second one is to add an ℓ_2 regularizer to the objective function. However, this option did not provide a substantial performance boost in our experiments, and so we have not implemented it.

4.2 MATRIX COMPLETION WITH RANDOM NOISE

In this section we evaluate our algorithms on the task of recovering a low rank matrix $UV^\top$ after observing $\Pi_\Omega(UV^\top + \eta)$, i.e. a fraction of its entries with added noise. As in Section 3.1, we use the setting of Mazumder et al. (2010) and compare with the SoftImpute method. The evaluation metric is the normalized MSE, defined as $(\sum_{(i,j)\notin\Omega}(UV^\top - A)_{ij}^2)/(\sum_{(i,j)\notin\Omega}(UV^\top)_{ij}^2)$, where A is the predicted matrix and $UV^\top$ the true low rank matrix. A few example plots can be seen in Figure 3 and a table of results in Table 1. We have implemented the Fast Greedy and Fast Local Search algorithms with 3 inner optimization iterations. In the first few iterations there is a spike in the relative MSE of the algorithms that use the OPTIMIZE_FAST routine. We attribute this to the aggressive alternating minimization steps of this procedure and conjecture that adding a regularization term to the objective might smoothen the spike. However, the Fast Local Search algorithm still gives the best overall performance in terms of how well it approximates the true low rank matrix $UV^\top$, and in particular with a very small rank—practically the same as the true underlying rank.

(a) $k = 5, p = 0.2, SNR = 10$ (b) $k = 6, p = 0.5, SNR = 1$

Figure 3: Test error vs rank in the matrix completion problem of Section 4.2. Bands of ± 1 standard error are shown.

4.3 RECOMMENDER SYSTEMS

In this section we compare our algorithms on the task of movie recommendation on the Movielens datasets Harper & Konstan (2015). In order to evaluate the algorithms, we perform random 80%-20% train-test splits that are the same for all algorithms and measure the mean RMSE in the test set. If we let $\Omega \subseteq [m] \times [n]$ be the set of user-movie pairs in the training set, we assume that the true

user-movie matrix is low rank, and thus pose (1) with $R(A) = \frac{1}{2}\|\Pi_\Omega(M - A)\|_F^2$. We make the following slight modification in order to take into account the range of the ratings $[1, 5]$: We clip the entries of A between 1 and 5 when computing $\nabla R(A)$ in Algorithm 2.3 and Algorithm 5. In other words, instead of $\Pi_\Omega(A - M)$ we compute the gradient as $\Pi_\Omega(\text{clip}(A, 1, 5) - M)$. This is similar to replacing our objective by a Huber loss, with the difference that we only do so in the steps that we mentioned and not the inner optimization step, mainly for runtime efficiency reasons.

The results can be seen in Table 2. We do not compare with Fast Local Search, as we found that it only provides an advantage for small ranks (< 30), and otherwise matches Fast Greedy. For the inner optimization steps we have used the LSQR algorithm with 2 iterations in the 100K and 1M datasets, and with 3 iterations in the 10M dataset. Note that even though the SVD algorithm by Koren et al. (2009) as implemented by Hug (2020) (with no user/movie bias terms) is a highly tuned algorithm for recommender systems that was one of the top solutions in the famous Netflix prize, it has comparable performance to our general-purpose Algorithm 2.3.

Algorithm	MovieLens 100K	MovieLens 1M	MovieLens 10M
NMF (Lee & Seung (2001))	0.9659	0.9166	0.8960
SVD (Koren et al. (2009))	0.9533	0.8743	**0.8315**
Fast Greedy (Algorithm 2.3)	**0.9451**	**0.8714**	0.8330

Table 2: Mean RMSE and standard error among 5 random splits for 100K and 1M with standard errors < 0.01, and 3 random splits for 10M with standard errors < 0.001. The rank of the prediction is set to 100 except for NMF where it is 15 and Fast Greedy in the 10M dataset where it is chosen to be 35 by cross-validation.

Finally, Table 3 demonstrates the speedup achieved by our algorithms over the basic greedy implementation. It should be noted that the speedup is larger as rank increases, since the fast algorithms scale linearly with rank, but the basic greedy of Shalev-Shwartz et al. (2011) scales quadratically.

Experiment	Greedy (Shalev-Shwartz et al. (2011))	Fast Greedy	Fast Local Search
Figure 3 (a)	18.8	10.2	10.8
Movielens 100K	418.4	43.4	46.1
Movielens 1M	4087.3	244.2	263.0

Table 3: Runtimes (in seconds) of different algorithms for fitting a rank=30 solution in various experiments. Code written in python and tested on an Intel Skylake CPU with 16 vCPUs.

5 CONCLUSIONS

We presented simple algorithms with strong theoretical guarantees for optimizing a convex function under a rank constraint. Although the basic versions of these algorithms have appeared before, through a series of careful runtime, optimization, and generalization performance improvements that we introduced, we have managed to reshape the performance of these algorithms in all fronts. Via our experimental validation on a host of practical problems such as low-rank matrix recovery with missing data, robust principal component analysis, and recommender systems, we have shown that the performance in terms of the solution quality matches or exceeds other widely used and even specialized solutions, thus making the argument that our Fast Greedy and Fast Local Search routines can be regarded as strong and practical general purpose tools for rank-constrained convex optimization. Interesting directions for further research include the exploration of different kinds of regularization and tuning for machine learning applications, as well as a competitive implementation and extensive runtime comparison of our algorithms.

REFERENCES

Kyriakos Axiotis and Maxim Sviridenko. Sparse convex optimization via adaptively regularized hard thresholding. *arXiv preprint arXiv:2006.14571*, 2020.

Thierry Bouwmans, Sajid Javed, Hongyang Zhang, Zhouchen Lin, and Ricardo Otazo. On the applications of robust pca in image and video processing. *Proceedings of the IEEE*, 106(8):1427–1457, 2018.

Emmanuel J Candès, Xiaodong Li, Yi Ma, and John Wright. Robust principal component analysis? *Journal of the ACM (JACM)*, 58(3):1–37, 2011.

Steve Fisk. A note on weyl's inequality. 1996.

Dean Foster, Howard Karloff, and Justin Thaler. Variable selection is hard. In *Conference on Learning Theory*, pp. 696–709, 2015.

F Maxwell Harper and Joseph A Konstan. The movielens datasets: History and context. *Acm transactions on interactive intelligent systems (tiis)*, 5(4):1–19, 2015.

Nicolas Hug. Surprise: A python library for recommender systems. *Journal of Open Source Software*, 5(52):2174, 2020. doi: 10.21105/joss.02174. URL https://doi.org/10.21105/joss.02174.

Prateek Jain, Ambuj Tewari, and Purushottam Kar. On iterative hard thresholding methods for high-dimensional m-estimation. In *Advances in Neural Information Processing Systems*, pp. 685–693, 2014.

Yehuda Koren, Robert Bell, and Chris Volinsky. Matrix factorization techniques for recommender systems. *Computer*, 42(8):30–37, 2009.

Daniel D Lee and H Sebastian Seung. Algorithms for non-negative matrix factorization. In *Advances in neural information processing systems*, pp. 556–562, 2001.

Zhouchen Lin, Minming Chen, and Yi Ma. The augmented lagrange multiplier method for exact recovery of corrupted low-rank matrices. *arXiv preprint arXiv:1009.5055*, 2010.

Per-Gunnar Martinsson, Vladimir Rokhlin, and Mark Tygert. A randomized algorithm for the decomposition of matrices. *Applied and Computational Harmonic Analysis*, 30(1):47–68, 2011.

Rahul Mazumder, Trevor Hastie, and Robert Tibshirani. Spectral regularization algorithms for learning large incomplete matrices. *The Journal of Machine Learning Research*, 11:2287–2322, 2010.

Balas Kausik Natarajan. Sparse approximate solutions to linear systems. *SIAM journal on computing*, 24(2):227–234, 1995.

Christopher C Paige and Michael A Saunders. Lsqr: An algorithm for sparse linear equations and sparse least squares. *ACM Transactions on Mathematical Software (TOMS)*, 8(1):43–71, 1982.

Alex Rubinsteyn and Sergey Feldman. fancyimpute: Version 0.0.16, May 2016. URL https://doi.org/10.5281/zenodo.51773.

Shai Shalev-Shwartz, Nathan Srebro, and Tong Zhang. Trading accuracy for sparsity in optimization problems with sparsity constraints. *SIAM Journal on Optimization*, 20(6):2807–2832, 2010.

Shai Shalev-Shwartz, Alon Gonen, and Ohad Shamir. Large-scale convex minimization with a low-rank constraint. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, pp. 329–336, 2011.

Arthur Szlam, Yuval Kluger, and Mark Tygert. An implementation of a randomized algorithm for principal component analysis. *arXiv preprint arXiv:1412.3510*, 2014.

Andrew Tulloch. Fast randomized svd. https://research.fb.com/blog/2014/09/fast-randomized-svd/, 2014.

Antoine Vacavant, Thierry Chateau, Alexis Wilhelm, and Laurent Lequièvre. A benchmark dataset for outdoor foreground/background extraction. In *Asian Conference on Computer Vision*, pp. 291–300. Springer, 2012.

Tong Zhang. Sparse recovery with orthogonal matching pursuit under rip. *IEEE Transactions on Information Theory*, 57(9):6215–6221, 2011.

A APPENDIX

A.1 PRELIMINARIES AND NOTATION

Given an positive integer k, we denote $[k] = \{1, 2, \ldots, k\}$. Given a matrix A, we denote by $\|A\|_F$ its Frobenius norm, i.e. the ℓ_2 norm of the entries of A (or equivalently of the singular values of A). The following lemma is a simple corollary of the definition of the Frobenius norm:

Lemma A.1. *Given two matrices $A \in \mathbb{R}^{m \times n}, B \in \mathbb{R}^{m \times n}$, we have $\|A + B\|_F^2 \leq 2\left(\|A\|_F^2 + \|B\|_F^2\right)$.*

Proof.

$$\|A + B\|_F^2 = \sum_{ij}(A + B)_{ij}^2 \leq 2\sum_{ij}(A_{ij}^2 + B_{ij}^2) = 2(\|A\|_F^2 + \|B\|_F^2)$$

$\square$

Definition A.2 (Rank-restricted smoothness, strong convexity, condition number). *Given a convex function $R \in \mathbb{R}^{m \times n} \to \mathbb{R}$ and an integer parameter r, the rank-restricted smoothness of R at rank r is the minimum constant $\rho_r^+ \geq 0$ such that for any two matrices $A \in \mathbb{R}^{m \times n}, B \in \mathbb{R}^{m \times n}$ such that $\mathrm{rank}(A - B) \leq r$, we have*

$$R(B) \leq R(A) + \langle \nabla R(A), B - A \rangle + \frac{\rho_r^+}{2}\|B - A\|_F^2 .$$

Similarly, the rank-restricted strong convexity of R at rank r is the maximum constant $\rho_r^- \geq 0$ such that for any two matrices $A \in \mathbb{R}^{m \times n}, B \in \mathbb{R}^{m \times n}$ such that $\mathrm{rank}(A - B) \leq r$, we have

$$R(B) \geq R(A) + \langle \nabla R(A), B - A \rangle + \frac{\rho_r^-}{2}\|B - A\|_F^2 .$$

Given that ρ_r^+, ρ_r^- exist and are nonzero, the rank-restricted condition number of R at rank r is then defined as

$$\kappa_r = \frac{\rho_r^+}{\rho_r^-}$$

Note that ρ_r^+ is increasing and ρ_r^- is decreasing in r. Therefore, even though our bounds are proven in terms of the constants $\frac{\rho_1^+}{\rho_r^-}$ and $\frac{\rho_2^+}{\rho_r^-}$, these quantities are always at most $\frac{\rho_r^+}{\rho_r^-} = \kappa_r$ as long as $r \geq 2$, and so they directly imply the same bounds in terms of the constant κ_r.

Definition A.3 (Spectral norm). *Given a matrix $A \in \mathbb{R}^{m \times n}$, we denote its spectral norm by $\|A\|_2$. The spectral norm is defined as*

$$\|A\|_2 = \max_{x \in \mathbb{R}^n} \frac{\|Ax\|_2}{\|x\|_2} ,$$

Definition A.4 (Singular value thresholding operator). *Given a matrix $A \in \mathbb{R}^{m \times n}$ of rank k, a singular value decomposition $A = U\Sigma V^\top$ such that $\Sigma_{11} \geq \Sigma_{22} \geq \cdots \geq \Sigma_{kk}$, and an integer $1 \leq r \leq k$, we define $H_r(A) = U\Sigma'V^\top$, here Σ' is a diagonal matrix with*

$$\Sigma'_{ii} = \begin{cases} \Sigma_{ii} & \text{if } i \leq r \\ 0 & \text{otherwise} \end{cases}$$

In other words, $H_r(\cdot)$ is an operator that eliminates all but the top r highest singular values of a matrix.

Lemma A.5 (Weyl's inequality). *For any matrix A and integer $i \geq 1$, let $\sigma_i(A)$ be the i-th largest singular value of A or 0 if $i > \mathrm{rank}(A)$. Then, for any two matrices A, B and integers $i \geq 1, j \geq 1$:*

$$\sigma_{i+j-1}(A + B) \leq \sigma_i(A) + \sigma_j(B)$$

A proof of the previous fact can be found e.g. in Fisk (1996).

Lemma A.6 ($H_r(\cdot)$ optimization problem). *Let $A \in \mathbb{R}^{m \times n}$ be a rank-k matrix and $r \in [k]$ be an integer parameter. Then $M = \frac{1}{\lambda} H_r(A)$ is an optimal solution to the following optimization problem:*

$$\max_{\text{rank}(M) \leq r} \{\langle A, M \rangle - \frac{\lambda}{2} \|M\|_F^2\} \tag{6}$$

Proof. Let $U \Sigma V^\top = \sum_i \Sigma_{ii} U_i V_i^\top$ be a singular value decomposition of A. We note that (6) is equivalent to

$$\min_{\text{rank}(M) \leq r} \|A - \lambda M\|_F^2 := f(M) \tag{7}$$

Now, note that $f(\frac{1}{\lambda} H_r(A)) = \|A - H_r(A)\|_F^2 = \sum_{i=r+1}^{k} \Sigma_{ii}^2$. On the other hand, by applying Weyl's inequality (Lemma A.5) for $j = r + 1$,

$$f(M) = \|A - \lambda M\|_F^2 = \sum_{i=1}^{k+r} \sigma_i^2(A - \lambda M) \geq \sum_{i=1}^{k+r} (\sigma_{i+r}(A) - \sigma_{r+1}(\lambda M))^2 = \sum_{i=r+1}^{k} \Sigma_{ii}^2,$$

where the last equality follows from the fact that $\text{rank}(A) = k$ and $\text{rank}(M) \leq r$. Therefore, $M = \frac{1}{\lambda} H_r(A)$ minimizes (7) and thus maximizes 6. $\square$

A.2 PROOF OF THEOREM 2.1 (GREEDY)

We will start with the following simple lemma about the Frobenius norm of a sum of matrices with orthogonal columns or rows:

Lemma A.7. *Let $U \in \mathbb{R}^{m \times r}, V \in \mathbb{R}^{n \times r}, X \in \mathbb{R}^{m \times r}, Y \in \mathbb{R}^{n \times r}$ be such that the columns of U are orthogonal to the columns of X or the columns of V are orthogonal to the columns of Y. Then $\|UV^\top + XY^\top\|_F^2 = \|UV^\top\|_F^2 + \|XY^\top\|_F^2$.*

Proof. If the columns of U are orthogonal to those of X, then $U^\top X = \mathbf{0}$ and if the columns of V are orthogonal to those of Y, then $Y^\top V = \mathbf{0}$. Therefore in any case $\langle UV^\top, XY^\top \rangle = \text{Tr}(VU^\top XY^\top) = \text{Tr}(U^\top XY^\top V) = \mathbf{0}$, implying

$$\|UV^\top + XY^\top\|_F^2 = \|UV^\top\|_F^2 + \|XY^\top\|_F^2 + 2\langle UV^\top, XY^\top \rangle = \|UV^\top\|_F^2 + \|XY^\top\|_F^2$$

$\square$

Additionally, we have the following lemma regarding the optimality conditions of (2):

Lemma A.8. *Let $A = UXV^\top$ where $U \in \mathbb{R}^{m \times r}, X \in \mathbb{R}^{r \times r}$, and $V \in \mathbb{R}^{n \times r}$, such that X is the optimal solution to (2). Then for any $u \in \text{im}(U)$ and $v \in \text{im}(V)$ we have that $\langle \nabla R(A), uv^\top \rangle = 0$.*

Proof. By the optimality condition of 2, we have that

$$U^\top \nabla R(A) V = \mathbf{0}$$

Now, for any $u = Ux$ and $v = Vy$ we have

$$\langle \nabla R(A), uv^\top \rangle = u^\top \nabla R(A) v = x^\top U^\top \nabla R(A) V y = 0$$

$\square$

We are now ready for the proof of Theorem 2.1.

Proof. Let A_{t-1} be the current solution $UV^\top$ before iteration $t - 1 \geq 0$. Let
$$\mathcal{B}_t = \{B | B = A_{t-1} + \eta uv^T, \eta \in \mathbb{R}, u \in \mathbb{R}^m, v \in \mathbb{R}^n\}.$$
By smoothness we have
$$R(A_{t-1}) - R(A_t) \geq \max_{B \in \mathcal{B}_t} \{R(A_{t-1}) - R(B)\}$$

$$\geq \max_{B \in \mathcal{B}_t} \left\{ -\langle \nabla R(A_{t-1}), B - A_{t-1}\rangle - \frac{\rho_1^+}{2}\|B - A_{t-1}\|_F^2 \right\}$$

$$\geq \max_{\|u\|_2 = \|v\|_2 = 1, \eta} \left\{ \eta \langle \nabla R(A_{t-1}), uv^\top\rangle - \eta^2 \frac{\rho_1^+}{2} \right\}$$

$$= \max_{\eta} \left\{ \eta \|\nabla R(A_{t-1})\|_2 - \eta^2 \frac{\rho_1^+}{2} \right\}$$

$$= \frac{\|\nabla R(A_{t-1})\|_2^2}{2\rho_1^+}$$

where $\|\cdot\|_2$ is the spectral norm (i.e. maximum magnitude of a singular value).

On the other hand, by strong convexity and noting that
$$\text{rank}(A^* - A_{t-1}) \leq \text{rank}(A^*) + \text{rank}(A_{t-1}) \leq r^* + r,$$

$$R(A^*) - R(A_{t-1}) \geq \langle \nabla R(A_{t-1}), A^* - A_{t-1}\rangle + \frac{\rho_{r+r^*}^-}{2}\|A^* - A_{t-1}\|_F^2. \tag{8}$$

Let $A_{t-1} = UV^\top$ and $A^* = U^* V^{*\top}$. We let $\Pi_{\text{im}(U)} = U(U^\top U)^+ U^\top$ and $\Pi_{\text{im}(V)} = V(V^\top V)^+ V^\top$ denote the orthogonal projections onto the images of U and V respectively. We now write
$$A^* = U^* V^{*\top} = (U^1 + U^2)(V^1 + V^2)^\top = U^1 V^{1\top} + U^1 V^{2\top} + U^2 V^{*\top}$$
where $U^1 = \Pi_{\text{im}(U)} U^*$ is a matrix where every column of U^* is replaced by its projection on $\text{im}(U)$ and $U^2 = U^* - U^1$ and similarly $V^1 = \Pi_{\text{im}(V)} V^*$ is a matrix where every column of V^* is replaced by its projection on $\text{im}(V)$ and $V^2 = V^* - V^1$. By setting $U' = (-U \mid U^1)$ and $V' = (V \mid V^1)$ we can write
$$A^* - A_{t-1} = U'V'^\top + U^1 V^{2\top} + U^2 V^{*\top}$$
where $\text{im}(U') = \text{im}(U)$ and $\text{im}(V') = \text{im}(V)$. Also, note that
$$\text{rank}(U^1 V^{2\top}) \leq \text{rank}(V^2) \leq \text{rank}(V^*) = \text{rank}(A^*) \leq r^*$$
and similarly $\text{rank}(U^2 V^{*\top}) \leq r^*$. So now the right hand side of (8) can be reshaped as
$$\langle \nabla R(A_{t-1}), A^* - A_{t-1}\rangle + \frac{\rho_{r+r^*}^-}{2}\|A^* - A_{t-1}\|_F^2$$

$$= \langle \nabla R(A_{t-1}), U'V'^\top + U^1 V^{2\top} + U^2 V^{*\top}\rangle + \frac{\rho_{r+r^*}^-}{2}\|U'V'^\top + U^1 V^{2\top} + U^2 V^{*\top}\|_F^2$$

Now, note that since by definition the columns of U' are in $\text{im}(U)$ and the columns of V' are in $\text{im}(V)$, Lemma A.8 implies that $\langle \nabla R(A_{t-1}), U'V'^\top\rangle = 0$. Therefore the above is equal to
$$\langle \nabla R(A_{t-1}), U^1 V^{2\top} + U^2 V^{*\top}\rangle + \frac{\rho_{r+r^*}^-}{2}\|U'V'^\top + U^1 V^{2\top} + U^2 V^{*\top}\|_F^2$$

$$\geq \langle \nabla R(A_{t-1}), U^1 V^{2\top}\rangle + \langle \nabla R(A_{t-1}), U^2 V^{*\top}\rangle + \frac{\rho_{r+r^*}^-}{2}\left(\|U^1 V^{2\top}\|_F^2 + \|U^2 V^{*\top}\|_F^2\right)$$

$$\geq 2 \min_{\text{rank}(M) \leq r^*} \left\{ \langle \nabla R(A_{t-1}), M\rangle + \frac{\rho_{r+r^*}^-}{2}\|M\|_F^2 \right\}$$

$$= -2\frac{\|H_{r^*}(\nabla R(A_{t-1}))\|_F^2}{2\rho_{r+r^*}^-}$$

$$\geq -r^* \frac{\|\nabla R(A_{t-1})\|_2^2}{\rho_{r+r^*}^-}$$

where the first equality follows by noticing that the columns of V' and V^1 are orthogonal to those of V^2 and the columns of U' and U^1 are orthogonal to those of U^2, and applying Lemma A.7. The last equality is a direct application of Lemma A.6 and the last inequality states that the largest squared singular value is not smaller than the average of the top r^* squared singular values. Therefore we have concluded that

$$\|\nabla R(A_{t-1})\|_2^2 \geq \frac{\bar{\rho}_{r+r^*}}{r^*}\left(R(A_{t-1}) - R(A^*)\right)$$

Plugging this back into the smoothness inequality, we get

$$R(A_{t-1}) - R(A_t) \geq \frac{1}{2r^*\kappa}(R(A_{t-1}) - R(A^*))$$

or equivalently

$$R(A_t) - R(A^*) \leq \left(1 - \frac{1}{2r^*\kappa}\right)(R(A_{t-1}) - R(A^*)).$$

Therefore after $L = 2r^*\kappa \log \frac{R(A_0) - R(A^*)}{\epsilon}$ iterations we have

$$
\begin{aligned}
R(A_T) - R(A^*) &\leq \left(1 - \frac{1}{2r^*\kappa}\right)^L (R(A_0) - R(A^*)) \\
&\leq e^{-\frac{L}{2r^*\kappa}}(R(A_0) - R(A^*)) \\
&\leq \epsilon
\end{aligned}
$$

Since $A_0 = \mathbf{0}$, the result follows. $\qquad\square$

A.3 PROOF OF THEOREM 2.2 (LOCAL SEARCH)

Proof. Similarly to Section A.3, we let A_{t-1} be the current solution before iteration $t - 1 \geq 0$, and let

$$\mathcal{B}_t = \{B|B = A_{t-1} + \eta uv^T - \sigma_{\min}xy^\top, \eta \in \mathbb{R}, u \in \mathbb{R}^m, v \in \mathbb{R}^n\},$$

where $\sigma_{\min}xy^\top = A_{t-1} - H_{r-1}(A_{t-1})$ is the rank-1 term corresponding to the minimum singular value of A_{t-1}. By smoothness we have

$$
\begin{aligned}
&R(A_{t-1}) - R(A_t) \\
&\geq \max_{B \in \mathcal{B}_t} \{R(A_{t-1}) - R(B)\} \\
&\geq \max_{B \in \mathcal{B}_t} \left\{-\langle \nabla R(A_{t-1}), B - A_{t-1}\rangle - \frac{\rho_2^+}{2}\|B - A_{t-1}\|_F^2\right\} \\
&= \max_{\|u\|_2 = \|v\|_2 = 1, \eta \in \mathbb{R}} \left\{-\langle \nabla R(A_{t-1}), \eta uv^\top - \sigma_{\min}xy^\top\rangle - \frac{\rho_2^+}{2}\|\eta uv^\top - \sigma_{\min}xy^\top\|_F^2\right\} \\
&\geq \max_{\|u\|_2 = \|v\|_2 = 1, \eta \in \mathbb{R}} \left\{-\langle \nabla R(A_{t-1}), \eta uv^\top\rangle - \eta^2\rho_2^+ - \sigma_{\min}^2\rho_2^+\right\} \\
&= \max_{\eta \in \mathbb{R}} \left\{\eta\|\nabla R(A_{t-1})\|_2 - \eta^2\rho_2^+ - \sigma_{\min}^2\rho_2^+\right\} \\
&= \frac{\|\nabla R(A_{t-1})\|_2^2}{4\rho_2^+} - \sigma_{\min}^2\rho_2^+,
\end{aligned}
$$

where in the last inequality we used the fact that $\langle \nabla R(A_{t-1}), xy^\top\rangle = 0$ following from Lemma A.8, as well as Lemma A.1.

On the other hand, by strong convexity,

$$R(A^*) - R(A_{t-1}) \geq \langle \nabla R(A_{t-1}), A^* - A_{t-1}\rangle + \frac{\bar{\rho}_{r+r^*}}{2}\|A^* - A_{t-1}\|_F^2.$$

Let $A_{t-1} = UV^\top$ and $A^* = U^*V^{*\top}$. We write

$$A^* = U^*V^{*\top} = (U^1 + U^2)(V^1 + V^2)^\top = U^1V^{1\top} + U^1V^{2\top} + U^2V^{*\top}$$

where U^1 is a matrix where every column of U^* is replaced by its projection on $\mathrm{im}(U)$ and $U^2 = U^* - U^1$ and similarly V^1 is a matrix where every column of V^* is replaced by its projection on $\mathrm{im}(V)$ and $V^2 = V^* - V^1$. By setting $U' = (-U \mid U^1)$ and $V' = (V \mid V^1)$ we can write

$$A^* - A_{t-1} = U'V'^\top + U^1 V^{2\top} + U^2 V^{*\top}$$

where $\mathrm{im}(U') = \mathrm{im}(U)$ and $\mathrm{im}(V') = \mathrm{im}(V)$. Also, note that

$$\mathrm{rank}(U^1 V^{2\top}) \le \mathrm{rank}(V^2) \le \mathrm{rank}(V^*) = \mathrm{rank}(A^*) \le r^*$$

and similarly $\mathrm{rank}(U^2 V^{*\top}) \le r^*$. So we now have

$$\langle \nabla R(A_{t-1}), A^* - A_{t-1} \rangle + \frac{\rho^-_{r+r^*}}{2} \|A^* - A_{t-1}\|_F^2$$

$$= \langle \nabla R(A_{t-1}), U'V'^\top + U^1 V^{2\top} + U^2 V^{*\top} \rangle + \frac{\rho^-_{r+r^*}}{2} \|U'V'^\top + U^1 V^{2\top} + U^2 V^{*\top}\|_F^2$$

$$= \langle \nabla R(A_{t-1}), U^1 V^{2\top} + U^2 V^{*\top} \rangle + \frac{\rho^-_{r+r^*}}{2} \|U'V'^\top + U^1 V^{2\top} + U^2 V^{*\top}\|_F^2$$

$$= \langle \nabla R(A_{t-1}), U^1 V^{2\top} + U^2 V^{*\top} \rangle + \frac{\rho^-_{r+r^*}}{2} \left(\|U'V'^\top\|_F^2 + \|U^1 V^{2\top}\|_F^2 + \|U^2 V^{*\top}\|_F^2 \right)$$

$$\ge \langle \nabla R(A_{t-1}), U^1 V^{2\top} \rangle + \langle \nabla R(A_{t-1}), U^2 V^{*\top} \rangle + \frac{\rho^-_{r+r^*}}{2} \left(\|U^1 V^{2\top}\|_F^2 + \|U^2 V^{*\top}\|_F^2 \right)$$

$$+ \frac{\rho^-_{r+r^*}}{2} \|U'V'^\top\|_F^2$$

$$\ge 2 \min_{\mathrm{rank}(M) \le r^*} \left\{ \langle \nabla R(A_{t-1}), M \rangle + \frac{\rho^-_{r+r^*}}{2} \|M\|_F^2 \right\} + \frac{\rho^-_{r+r^*}}{2} \|U'V'^\top\|_F^2$$

$$= -2 \frac{\|H_{r^*}(\nabla R(A_{t-1}))\|_F^2}{2\rho^-_{r+r^*}} + \frac{\rho^-_{r+r^*}}{2} \|U'V'^\top\|_F^2$$

$$\ge -r^* \frac{\|\nabla R(A_{t-1})\|_2^2}{\rho^-_{r+r^*}} + \frac{\rho^-_{r+r^*}}{2} \|U'V'^\top\|_F^2$$

where the second equality follows from the fact that $\langle \nabla R(A_{t-1}), uv^\top \rangle = 0$ for any $u \in \mathrm{im}(U), v \in \mathrm{im}(V)$, the third equality from the fact that $\mathrm{im}(U^2) \perp \mathrm{im}(U') \cup \mathrm{im}(U^1)$ and $\mathrm{im}(V^2) \perp \mathrm{im}(V')$ and by applying Lemma A.7, and the last inequality from the fact that the largest squared singular value is not smaller than the average of the top r^* squared singular values. Now, note that since $\mathrm{rank}(U^1 V^{1\top}) \le r^* < r = \mathrm{rank}(UV^\top)$,

$$\|U'V'^\top\|_F^2 = \|U^1 V^{1\top} - UV^\top\|_F^2$$

$$= \sum_{i=1}^r \sigma_i^2 (U^1 V^{1\top} - UV^\top)$$

$$\ge \sum_{i=1}^r (\sigma_{i+r^*}(UV^\top) - \sigma_{r^*+1}(U^1 V^{1\top}))^2$$

$$= \sum_{i=r^*+1}^r \sigma_i^2 (UV^\top)$$

$$\ge (r - r^*) \sigma_{\min}^2 (UV^\top)$$

$$= (r - r^*) \sigma_{\min}^2 (A_{t-1}),$$

where we used the fact that $\mathrm{rank}(U^1 V^{1\top}) \le r^*$ together with Lemma A.5. Therefore we have concluded that

$$\|\nabla R(A_{t-1})\|_2^2 \ge \frac{\rho^-_{r+r^*}}{r^*} (R(A_{t-1}) - R(A^*)) + \frac{(\rho^-_{r+r^*})^2 (r - r^*)}{2r^*} \sigma_{\min}^2$$

Plugging this back into the smoothness inequality and setting $\widetilde{\kappa} = \frac{\rho_2^+}{\rho_{r+r^*}^-}$, we get

$$R(A_{t-1}) - R(A_t) \geq \frac{1}{4r^*\widetilde{\kappa}}(R(A_{t-1}) - R(A^*)) + \left(\frac{\rho_{r+r^*}^-(r - r^*)}{8r^*\widetilde{\kappa}} - \rho_2^+\right)\sigma_{\min}^2(A_{t-1})$$

$$\geq \frac{1}{4r^*\widetilde{\kappa}}(R(A_{t-1}) - R(A^*))$$

as long as $r \geq r^*(1 + 8\widetilde{\kappa}^2)$. The claim follows since $\widetilde{\kappa} \leq \kappa_{r+r^*}$. $\qquad\square$

A.4 ADDENDUM TO SECTION 4

Figure 4: One of the splits of the Movielens 100K dataset. We can see that for small ranks the Fast Local Search solution is better and more stable, but for larger ranks it does not provide any improvement over the Fast Greedy algorithm.

(a) $k = 10, p = 0.5, SNR = 1$

(b) $k = 10, p = 0.3, SNR = 3$

Figure 5: Test error vs rank in the matrix completion problem of Section 4.2. Bands of ± 1 standard error are shown.

(a) Train error vs rank

(b) Test error vs rank

Figure 6: Performance of greedy with fully solving the inner optimization problem (left) and applying 3 iterations of the LSQR algorithm (right) in the matrix completion problem of Section 4.2. $k = 5, p = 0.2, SNR = 10$. Bands of ± 1 standard error are shown. This experiment shows why it is crucial to apply some kind of regularization to the Fast Greedy and Fast Local Search algorithms for machine learning applications.