IgboNER: Expanding Named Entity Recognition Datasets via Projection

Abstract

Since the inception of the state-of-the-art neural network models for natural language processing research, the major challenge faced by low-resource languages is the lack or insufficiency of annotated training data. The named entity recognition (NER) task is no exception. The need for an efficient data creation and annotation process, especially for low-resource languages cannot be over-emphasized. In this work, we leverage an existing NER tool for English in a cross-language projection method that automatically creates a mapping dictionary of entities in a source language and their translations in the target language using a parallel English-Igbo corpus. The resultant mapping dictionary, which was manually checked and corrected by human annotators, was used to automatically generate and format an NER training dataset from the Igbo monolingual corpus thereby saving a lot of annotation time for the Igbo NER task. The generated dataset was also included in the training process and our experiments show improved performance results from previous works.

1 Introduction

Research has shown that pre-training language models have demonstrated improvement for many natural language processing (NLP) tasks like Machine Translation (Nekoto et al., 2020), Topic Classification (Hedderich et al., 2020), Part of Speech Tagging (Kann et al., 2020a) and Named Entity Recognition (NER) (Adelani et al., 2021; Ogueji et al., 2021). However, these models are known to require a lot of labelled data to perform well (Xie et al., 2020). In NLP tasks, there is a crucial and constant need for annotated corpora, which is often a challenge for low-resource languages. The African language Igbo is low-resourced in the task of NER and other NLP tasks (Adelani et al., 2021). This is a limitation in IgboNLP research and in the training and evaluation of some state-of-the-art (SOTA) models built in other languages. This is portrayed in the evaluation result of the study by Chukwuneke et al. (2022) using IgboNER[1] dataset. IgboNER was created from only 3,190 sentences obtained from BBC Igbo news[2]. This forms our motivation in creating further annotated datasets for the low-resourced Igbo language. The crucial question then becomes how can we efficiently create more annotated data for Igbo NLP tasks?

In this work, we adopt the cross-language projection method ((Li et al., 2021); (Ehrmann et al., 2011); (Xie et al., 2018); (Bari et al., 2020)) to automatically create more NER datasets as an alternative to the time-consuming and costly human-annotated method. The projection-based method generates a tagged corpus by projecting the tags from the source language to the target language. A parallel corpus is usually required for this method. This study aims at creating more annotated NER data for the Igbo language using the projection-based method. Figure 1 is an example of a projection-based task. Kulshreshtha et al. (2020) showed that using parallel corpora is better suited for aligning contextual embeddings as the context of words, especially the ambiguous words are maintained within the sentences. English-Igbo parallel corpora were used in this work. Firstly, we chose the English Language because it is the lingua franca of Nigeria where Igbo is one of the official native languages. Secondly, English has been widely researched in NLP and this has produced a lot of NLP resources for English. We tagged the English sentences (source language) using an

---

[1] https://github.com/Chiamakac/IgboNER-Models/tree/main/Igbo_dataset
[2] https://www.bbc.com/igbo

existing English annotation tool and then projected the tags onto the parallel Igbo sentences (target language). The Igbo language has historically faced a lot of disagreement with the adoption of an official written orthography (Oraka, 1983). This greatly affected the language and resulted in Igbo not having a long written tradition when compared to languages like Arabic, English and French (Agbo, 2013). This has resulted in the scarcity of Igbo corpora online, and the few Igbo texts written with mixed orthographies. Also, the time, labour and resource needed to manually annotate a large gold standard corpus is a severe constraint.

The contributions of this paper include the creation of an additional NER dataset for Igbo Language via annotation projection using parallel corpora to augment the already existing IgboNER datasets. We also built a mapping dictionary containing all the unique entities identified by spaCy[3] with their tags. This to the best of our knowledge is the first IgboNER mapping dictionary, which is an important contribution to Igbo NLP and African NLP at large. Crucially, the dictionary was used to handle the issue of multi-words and spelling variation during the tag projection. Our experiments showed that there is an increase in model performance with increasing data size. The rest of the paper is organised as follows: Section 2 discusses the related work; Section 3 describes the data collection and annotation; Section 4 is about building the mapping dictionary; Section 5 is conclusion and future work.

Figure 1: Projecting the tags from the source language to the target language.

2 RELATED WORK

Named Entity Recognition is a term defined as the task of identifying names of organisations, people, currency, time, percentage expression and geographic locations in text and was introduced at the Sixth Message Understanding Conference (Grishman & Sundheim, 1995). With the data-hungry deep neural networks recently used in training the SOTA models for performing NLP tasks as NER, the need for ever larger annotated datasets in various languages is inevitable. Over the past few years, attention has been drawn to weak or distant supervision[4] and a considerable number of studies (Mintz et al. (2009); Ratinov & Roth (2009); Peng et al. (2019); Yang et al. (2018); Liu et al. (2015); Lange et al. (2019); Shang et al. (2018); Cao et al. (2019); Xie et al. (2018); Chen et al. (2020); Hedderich et al. (2020); Kann et al. (2020b); He et al. (2020); Xiao et al. (2020); Liang et al. (2020); Hedderich et al. (2021); Rijhwani et al. (2020); Quirk & Poon (2016); Meng et al. (2021); Hogan (2022)) applied this method to generate a large amount of auto-labelled data without human effort. This method has helped address the issue of data scarcity and showed improvements in performance as seen in the above studies however, the availability of external resources like an existing knowledge base, gazetteers or dictionaries of named entities is a problem for some low-resource languages. For Igbo, there are no known existing knowledge base, gazetteers or dictionaries of named entities in Igbo.

The work by Li et al. (2021) built an entity alignment model on top of an XLM-R (Conneau et al., 2020a) and projected the labelled entities on the source English language sentences of the parallel data to the target language sentences. They evaluated on four languages: Spanish, Chinese, German and Dutch. Their result showed Chinese to have the highest improvement in F1 score

---

[3]https://spacy.io/models/en_core_web_sm
[4]an automatic method of creating labelled data using an external source like an already existing knowledge base, gazetteers or dictionaries of named entities, etc

Type	Sentence pairs	Source
Igbo	5,503	BBC News
English	5,630	Local newspapers
Total	11,133	

Table 1: Data source. This describes the parallel data sources.

by 6.4%. Fei et al. (2020) implemented automatic corpus translation of the source gold-standard corpus to the target languages and then projected the labels on the source dataset to the translated target languages. Their evaluation result on the Universal Proposition Bank (UPB, v1.0)[5] dataset showed the translation-based method to be effective with an F1 score increase of 6.7. Guo & Roth (2021) translated high-resource labelled sentences to the target language word-by-word with a dictionary. Then, they constructed target-language text from the source-language named entities with a pre-trained language model. The study achieved state-of-the-art performances on LORELEI (low-resource) languages and perform comparatively on CoNLL (high-resource) languages. García-Ferrero et al. (2022) automatically created data for the target language by translating the gold-labelled English data. Then they projected the gold labels from the source sentences to the translated sentences by leveraging automatic word alignments. Their result showed that data-based cross-lingual transfer approaches remain a useful option when high-capacity multilingual language models are not available. Enghoff et al. (2018) extensively studied annotation projection from multiple sources for low-resource NER. They showed that standalone multi-source annotation projection for NER works when the quality and availability of resources are high but suffers when parallel corpora are not available. THE PROJECTOR, an interactive graphical user interface tool that displays the sentence pair with all predicted and projected annotations was designed by Akbik & Vollgraf (2017). This is facilitate experiments and discussions in the research community. The study by Agerri et al. (2018) demonstrated the feasibility of automatically generating Named Entity Recognition (NER) taggers for a given language when no manual data is available. This they achieved with the use of parallel corpora, projecting the existing annotations from multiple source languages to the target language via strict match projections. Their evaluation showed that the automatically generated model outperforms the gold-standard trained model in an in-domain evaluation.

3 DATA COLLECTION AND ANNOTATION

3.1 DATA COLLECTION

Our work used a parallel corpus (English-Igbo) that was originally created for a machine translation project (Ezeani et al., 2020). The corpus was created by collecting English and Igbo sentences from local newspapers in Nigeria (e.g. Punch) and from BBC Igbo News website[6] respectively. The 5,630 English sentences collected were translated into Igbo and the 5,503 collected Igbo sentences to English via human translation to produce English-Igbo sentence pairs used to build a standard machine translation benchmark dataset for Igbo. We adopted and used this specific corpus because it contains more contemporary texts in both languages which will guarantee a significant representation of known named entities than the multilingual bible text data[7] often used in the parallel corpus research. In addition, it was assumed that the quality of the data will be good enough due to the human-translation process that it has gone through. Table 1 presents a description of the data splits that make up the parallel corpus used in this work.

3.2 DATA ANNOTATION

The key to building the mapping dictionary in the next section is the ability to identify all unique named entities in the source language text. Therefore, the initial data annotation (i.e. NER tagging) process involved running a NER tool over the source language (English in this case) to identify and

---

[5]https://github.com/System-T/ UniversalPropositions

[6]https://www.bbc.com/igbo

[7]Mostly from https://www.jw.org and other sources

extract the named entities in the text and their tags. To achieve this, the English SpaCy[8] pipeline was used to extract the named entities in the English text. The pipeline we used is the spaCy model 'en_core_web_sm version 3.4.0' [9] and the following tags or named entities were recognised by the model; PERSON(PER), NORP (Nationalities or religious or political groups), FAC (Faculty) ORG (Organisation), GPE (Geopolitical entity), LOC (Location), PRODUCT, EVENT, WORK_OF_ART, LAW, LANGUAGE, DATE, TIME, PERCENT, MONEY, QUANTITY, ORDINAL, CARDINAL. We passed our 11,133 English source sentences through SpaCy and it identified named entities in 7,894 sentences. This means that no entity was identified in 3,239 sentences. Table 2 gives a description of our annotated data.

Entity Types	Number of tagged entities	Cohen's kappa score
PER	4,205	0.9971
LOC	3,566	0.9968
ORG	2,781	0.9821
DATE	2,241	0.9966

Table 2: Describes our dataset annotation including the entity types, number of tagged entities, Cohen's Kappa inter-annotation scores.

4 BUILDING THE MAPPING DICTIONARY

The mapping dictionary is a key contribution of this work and could be useful for other NLP tasks such as machine translation and other structured prediction systems. Its creation follows a semi-automatic process described in Figure 2. The key idea is based on the assumption that the majority (not all) of the named entities in the source language are going to either remain the same or translate to unique words or expressions in the target language. For example in Figure 1, `Rishi Sunak`, tagged PER, is always going to remain the same in both languages as it is a person's name while `Yesterday`, tagged DATE, is most likely going to be translated as `Ụnyahụ`. For this work, the mapping dictionary is an actual python dictionary object which has a `key:value` structure. The entities from the English sentences are the *keys* while the corresponding Igbo entities and tags are the *values*. For example, looking at the sentences from Figure 1, the entry to the dictionary may be as shown below:

```
{
"Yesterday": {ig:"Ụnyahụ", tag:"DATE"}, "Rishi Sunak": {ig:"Rishi
Sunak", tag:"PER"},      "UN": {ig:"UN", tag:"ORG"},      "Egypt"
{ig:"Egypt", tag:"LOC"},
}
```

As shown in Figure 2, the input to the process of building the mapping dictionary is the parallel corpus containing the sentence pairs in both languages as well as an initial mapping dictionary. The initial dictionary could be empty at the start of the process but may also have been initialised by a previous run. The English sentences are passed through the spaCy pipeline as described in section **??** to extract the NER-tagged entities. Each of the extracted entities is passed through the pipeline checking the following conditions:

- if the entity is already in the mapping dictionary, discard and get another entity.
- else if the entity is found in the target (Igbo) text, key = entity, value = entity, tag
- else if the entity's translation is found in the target (Igbo) text, key = entity, value = translated, tag
- else manually annotate the target (Igbo) entity, key = entity, value = annotated, tag

Our experiment with the parallel text used shows that over 95% of the extracted entities from the source language (English) were found in the corresponding target (Igbo) sentence making human translation and annotation a lot easier.

---

[8]SpaCy is a free open-source library for Natural Language Processing in Python. SpaCy features NER tagging, part-of-speech tagging, dependency parsing, word vectors and more: https://spacy.io/

[9]Trained on written web text (blogs, news, comments), that includes vocabulary, syntax and entities

Figure 2: An illustration of the semi-automatic process used in creating the mapping dictionary.

4.1 ANNOTATION VALIDATION

Table 1 showed that our source data is from local news and newspapers which represents the daily communication of speakers of Igbo language. Because of the nature of our data (local news), spaCy's output was noisy. For example, an entity 'Sowore' was tagged as an ORG instead of a PER-SON. The tagged spaCy output was therefore manually corrected by two people who are among the authors of this paper following the MUC-6 annotation guide[10] which we adopt in this work. Agreement was made by them where there were discrepancies in the tags. The inter-annotation agreement was calculated using Cohen's Kappa Cohen (1960) which uses one distribution for each rater and takes into account the possibility of the agreement occurring by chance. Our dataset achieves an inter-annotator agreement of 0.985, i.e. excellent agreement. In section 3.2, we have the list of output tags by spaCy but for this work we are using only the PER, LOC, ORG, DATE tags for our dataset creation. We choose these four tags and replace all the 'GPE' tags with 'LOC', 'TIME' tag we also replace with 'DATE' following previously created IgboNER dataset (Chukwuneke et al., 2022). A python script which selects only the entity to replace was written and used for all the manual corrections. As mentioned in section 3, our method requires a parallel corpus and we used the data described in Table 1.

4.2 EXPERIMENTAL SETTINGS

In this section, we describe the IgboBERT 2.0 model we pre-trained for Igbo language and some state-of-the-art transformer models fine-tuned to the downstream Igbo NER task. We show the effect of dataset sizes on the performance by fine-tuning using various dataset sizes.

4.2.1 IGBOBERT 2.0 MODEL

IgboBERT 2.0 is another version of IgboBERT (Chukwuneke et al., 2022) language model, which we pre-trained using the same corpus as IgboBERT plus the corpus described in Table 1 as an addition to increase the training sentences. A total number of 402,582 training sentences is used. We train IgboBERT 2.0 at a learning-rate of 1e-4 for 5 epoch and a batch size of 16. Only 5 epoch training was carried out because of limited compute resource such as GPU at the time of the experiment.

4.2.2 FINE-TUNED MODELS

We fine-tuned the IgboBERT 2.0 model and some of the state-of-the-art (SOTA) transformer models on the IgboNER downstream task using the Igbo dataset created by Chukwuneke et al. (2022), MasakhaNER 2.0 dataset (Adelani et al., 2022). The fine-tuned SOTA models are

---

[10]https://cs.nyu.edu/grishman/muc6.html

- Multilingual BERT-base cased (mBERT-base cased) by Devlin et al. (2019).
- XLM-RoBERTa-base (XLM-R) by Conneau et al. (2020b).
- DistilBERT Sanh et al. (2019)

To predict the entity types, we added a linear classification layer to the pre-trained transformer models. 30 epoch training with a batch size of 8 at a learning rate of 1e-4 was run.

4.3 RESULTS

Table 3 and Table 4 shows the fine-tuned results of mBERT, XML-R, DistilBERT, and IgboBERT. Table 3 shows the Precision, Recall, F1-score of the fine-tuned models at the learning rate of 1e-4 with the Igbo dataset created by Chukwuneke et al. (2022) while Table 4 is the Precision, Recall, F1-score at learning rate of 1e-4 with the Igbo dataset created by Chukwuneke et al. (2022) and MasakhaNER 2.0 dataset (Adelani et al., 2022) combined. We calculated these scores as averages over multiple runs. The result comparison of Table 3 and Table 4 shows

- increase in performance with increase in the data size.
- XML-R consistently outperformed at F1-score of 86.23 and 89.26 in both different tables.
- IgboBERT2.0 with F1 of 78.23 and 81.03 is relatively comparable to the SOTA models in terms of the amount of data used in training these SOTA models.

Model	Precision	Recall	F1 Score
IgBERT2.0	77.45	79.00	78.23
mBERT	85.22	86.50	85.86
XLM–RoBERTa	86.23	87.67	86.94
DistilBERT	82.48	77.67	80.00

Table 3: Performance of mBERT, XML-R, DistilBERT and IgboBERT: We display the fine-tuned results of the models after 30 epoch at 1e-4 learning rate with the Igbo dataset created by Chukwuneke et al. (2022)

Model	Precision	Recall	F1 Score
IgBERT2.0	80.36	81.72	81.03
mBERT	86.06	87.26	86.65
XLM–RoBERTa	88.77	89.75	89.26
DistilBERT	83.95	82.38	83.16

Table 4: Performance of mBERT, XML-R, DistilBERT and IgboBERT: We display the fine-tuned results of the models after 30 epoch at 1e-4 learning rate with the Igbo dataset created by Chukwuneke et al. (2022), MasakhaNER 2.0 dataset (Adelani et al., 2022)

5 CONCLUSION AND FUTURE WORK

This paper highlights the challenge of the lack of adequate datasets for building NLP models in general for low-resource languages with particular emphasis on the named entity recognition task for the Igbo language. A novel and efficient approach was proposed that takes advantage of parallel data in English - a well-resourced language with highly developed NER tools - and Igbo. This approach is based on the idea that the majority of name entities in the English text (mostly proper nouns) remain untranslated in the corresponding Igbo text. The concept of a mapping dictionary 2 was introduced by creating a rule-based pipeline that enables the automatic transfer of the NER tags produced with the English NER tagger to the corresponding Igbo entities. With manual checks and corrections, this process not only speeds up the data creation effort but also produces the mapping dictionary which can serve as a key resource in other NLP tasks such as machine translation, and part-of-speech tagging. Our experiments show that the models performance increased with increase in the data size when fine-tuned in the NER downstream task. Our IgboBERT though was outperformed

by the other models as shown in the tables but the performance is comparative when compared to the huge amount of data used in pre-training these SOTA models. We hope to improve our model further by creating further IgboNER datasets with the help of the NER mapping dictionary created in this work.

ACKNOWLEDGEMENTS

We acknowledge the support of Tertiary Education Trust Fund (TETFund) in Nigeria, and would like to thank the anonymous reviewers for their useful comments and for reading the draft. We also acknowledge JW, Igbo-Radio and Kaoditaa who gave us permission to use data from their websites.

REFERENCES

David Ifeoluwa Adelani, Jade Abbott, Graham Neubig, Daniel D'souza, Julia Kreutzer, Constantine Lignos, Chester Palen-Michel, Happy Buzaaba, Shruti Rijhwani, Sebastian Ruder, et al. Masakhaner: Named entity recognition for african languages. *arXiv preprint arXiv:2103.11811*, 2021.

David Ifeoluwa Adelani, Graham Neubig, Sebastian Ruder, Shruti Rijhwani, Michael Beukman, Chester Palen-Michel, Constantine Lignos, Jesujoba O Alabi, Shamsuddeen H Muhammad, Peter Nabende, et al. Masakhaner 2.0: Africa-centric transfer learning for named entity recognition. *arXiv preprint arXiv:2210.12391*, 2022.

Maduabuchi Sennen Agbo. Orthography theories and the standard igbo orthography. 2013.

Rodrigo Agerri, Yiling Chung, Itziar Aldabe, Nora Aranberri, Gorka Labaka, and German Rigau. Building Named Entity Recognition Taggers via Parallel Corpora. In Nicoletta Calzolari (Conference chair), Khalid Choukri, Christopher Cieri, Thierry Declerck, Sara Goggi, Koiti Hasida, Hitoshi Isahara, Bente Maegaard, Joseph Mariani, Hélène Mazo, Asuncion Moreno, Jan Odijk, Stelios Piperidis, and Takenobu Tokunaga (eds.), *Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018)*, Miyazaki, Japan, May 7-12, 2018 2018. European Language Resources Association (ELRA). ISBN 979-10-95546-00-9.

Alan Akbik and Roland Vollgraf. The projector: An interactive annotation projection visualization tool. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 43–48, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/D17-2008. URL https://aclanthology.org/D17-2008.

M Saiful Bari, Shafiq Joty, and Prathyusha Jwalapuram. Zero-resource cross-lingual named entity recognition. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 7415–7423, 2020.

Yixin Cao, Zikun Hu, Tat-seng Chua, Zhiyuan Liu, and Heng Ji. Low-resource name tagging learned with weakly labeled data. *arXiv preprint arXiv:1908.09659*, 2019.

Luoxin Chen, Weitong Ruan, Xinyue Liu, and Jianhua Lu. Seqvat: Virtual adversarial training for semi-supervised sequence labeling. In *ACL*, 2020.

CI Chukwuneke, Paul Rayson, Ignatius Ezeani, and Mahmoud El-Haj. Igbobert models: Building and training transformer models for the igbo language. 2022.

Jacob Cohen. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46, 1960. doi: 10.1177/001316446002000104. URL https://doi.org/10.1177/001316446002000104.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Unsupervised cross-lingual representation learning at scale. In *ACL*, 2020a.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 8440–8451, Online, July 2020b. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.747. URL https://aclanthology.org/2020.acl-main.747.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://aclanthology.org/N19-1423.

Maud Ehrmann, Marco Turchi, and Ralf Steinberger. Building a multilingual named entity-annotated corpus using annotation projection. In *Proceedings of the International Conference Recent Advances in Natural Language Processing 2011*, pp. 118–124, Hissar, Bulgaria, September 2011. Association for Computational Linguistics. URL https://aclanthology.org/R11-1017.

Jan Vium Enghoff, Søren Harrison, and Željko Agić. Low-resource named entity recognition via multi-source projection: Not quite there yet? In *Proceedings of the 2018 EMNLP Workshop W-NUT: The 4th Workshop on Noisy User-generated Text*, pp. 195–201, 2018.

Ignatius Ezeani, Paul Rayson, Ikechukwu Onyenwe, Chinedu Uchechukwu, and Mark Hepple. Igbo-english machine translation: An evaluation benchmark, 2020.

Hao Fei, Meishan Zhang, and Donghong Ji. Cross-lingual semantic role labeling with high-quality translated training corpus. In *ACL*, 2020.

Iker García-Ferrero, Rodrigo Agerri, and German Rigau. Model and data transfer for cross-lingual sequence labelling in zero-resource settings. *arXiv preprint arXiv:2210.12623*, 2022.

Ralph Grishman and B Sundheim. Message understanding conference 6. In *Proceedings of the 16th conference on Computational linguistics*, volume 1, pp. 466, 1995.

Ruohao Guo and Dan Roth. Constrained labeled data generation for low-resource named entity recognition. In *FINDINGS*, 2021.

Qizhen He, Liang Wu, Yida Yin, and Heming Cai. Knowledge-graph augmented word representations for named entity recognition. In *AAAI*, 2020.

Michael A Hedderich, David Adelani, Dawei Zhu, Jesujoba Alabi, Udia Markus, and Dietrich Klakow. Transfer learning and distant supervision for multilingual transformer models: A study on african languages. *arXiv preprint arXiv:2010.03179*, 2020.

Michael A Hedderich, Lukas Lange, and Dietrich Klakow. Anea: distant supervision for low-resource named entity recognition. *arXiv preprint arXiv:2102.13129*, 2021.

William Hogan. An overview of distant supervision for relation extraction with a focus on denoising and pre-training methods. *ArXiv*, abs/2207.08286, 2022.

Katharina Kann, Ophélie Lacroix, and Anders Søgaard. Weakly supervised POS taggers perform poorly on truly low-resource languages. *CoRR*, abs/2004.13305, 2020a. URL https://arxiv.org/abs/2004.13305.

Katharina Kann, Ophélie Lacroix, and Anders Søgaard. Weakly supervised pos taggers perform poorly on truly low-resource languages. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 8066–8073, 2020b.

Saurabh Kulshreshtha, Jose Luis Redondo Garcia, and Ching-Yun Chang. Cross-lingual alignment methods for multilingual BERT: A comparative study. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 933–942, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.findings-emnlp.83. URL https://aclanthology.org/2020.findings-emnlp.83.

Lukas Lange, Michael A Hedderich, and Dietrich Klakow. Feature-dependent confusion matrices for low-resource ner labeling with noisy labels. *arXiv preprint arXiv:1910.06061*, 2019.

Bing Li, Yujie He, and Wenjin Xu. Cross-lingual named entity recognition using parallel corpus: A new approach using xlm-roberta alignment. *arXiv preprint arXiv:2101.11112*, 2021.

Chen Liang, Yue Yu, Haoming Jiang, Siawpeng Er, Ruijia Wang, Tuo Zhao, and Chao Zhang. Bond: Bert-assisted open-domain named entity recognition with distant supervision. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 1054–1064, 2020.

Shengyu Liu, Buzhou Tang, Qingcai Chen, and Xiaolong Wang. Effects of semantic features on machine learning-based drug name recognition systems: Word embeddings vs. manually constructed dictionaries. *Inf.*, 6:848–865, 2015.

Yu Meng, Yunyi Zhang, Jiaxin Huang, Xuan Wang, Yu Zhang, Heng Ji, and Jiawei Han. Distantly-supervised named entity recognition with noise-robust learning and language model augmented self-training. *arXiv preprint arXiv:2109.05003*, 2021.

Mike D. Mintz, Steven Bills, Rion Snow, and Dan Jurafsky. Distant supervision for relation extraction without labeled data. In *Annual Meeting of the Association for Computational Linguistics*, 2009.

Wilhelmina Nekoto, Vukosi Marivate, Tshinondiwa Matsila, Timi Fasubaa, Tajudeen Kolawole, Taiwo Fagbohungbe, Solomon Oluwole Akinola, Shamsuddee Hassan Muhammad, Salomon Kabongo, Salomey Osei, et al. Participatory research for low-resourced machine translation: A case study in african languages. *arXiv preprint arXiv:2010.02353*, 2020.

Kelechi Ogueji, Yuxin Zhu, and Jimmy Lin. Small data? no problem! exploring the viability of pretrained multilingual language models for low-resourced languages. In *Proceedings of the 1st Workshop on Multilingual Representation Learning*, pp. 116–126, Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. URL `https://aclanthology.org/2021.mrl-1.11`.

Louis Nnamdi Oraka. *The foundations of Igbo studies: A short history of the study of Igbo language and culture*. University Publishing Company, 1983.

Minlong Peng, Xiaoyu Xing, Qi Zhang, Jinlan Fu, and Xuanjing Huang. Distantly supervised named entity recognition using positive-unlabeled learning. *arXiv preprint arXiv:1906.01378*, 2019.

Chris Quirk and Hoifung Poon. Distant supervision for relation extraction beyond the sentence boundary. *arXiv preprint arXiv:1609.04873*, 2016.

Lev Ratinov and Dan Roth. Design challenges and misconceptions in named entity recognition. In *Proceedings of the Thirteenth Conference on Computational Natural Language Learning (CoNLL-2009)*, pp. 147–155, Boulder, Colorado, June 2009. Association for Computational Linguistics. URL `https://www.aclweb.org/anthology/W09-1119`.

Shruti Rijhwani, Shuyan Zhou, Graham Neubig, and Jaime Carbonell. Soft gazetteers for low-resource named entity recognition. *arXiv preprint arXiv:2005.01866*, 2020.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *ArXiv*, abs/1910.01108, 2019.

Jingbo Shang, Liyuan Liu, Xiang Ren, Xiaotao Gu, Teng Ren, and Jiawei Han. Learning named entity tagger using domain-specific dictionary. *arXiv preprint arXiv:1809.03599*, 2018.

Chaojun Xiao, Yuan Yao, Ruobing Xie, Xu Han, Zhiyuan Liu, Maosong Sun, Fen Lin, and Leyu Lin. Denoising relation extraction from document-level distant supervision. *arXiv preprint arXiv:2011.03888*, 2020.

Jiateng Xie, Zhilin Yang, Graham Neubig, Noah A Smith, and Jaime Carbonell. Neural cross-lingual named entity recognition with minimal resources. *arXiv preprint arXiv:1808.09861*, 2018.

Qizhe Xie, Zihang Dai, Eduard Hovy, Thang Luong, and Quoc Le. Unsupervised data augmentation for consistency training. *Advances in Neural Information Processing Systems*, 33:6256–6268, 2020.

YaoSheng Yang, Wenliang Chen, Zhenghua Li, Zhengqiu He, and Min Zhang. Distantly supervised ner with partial annotation learning and reinforcement learning. In *COLING*, 2018.