Variational Reparametrized Policy Learning with Differentiable Physics

Abstract

We study the problem of policy parameterization for reinforcement learning (RL) with high-dimensional continuous action space. Our goal is to find a good way to parameterize the policy of continuous RL as a multi-modality distribution. To this end, we propose to treat the continuous RL policy as a generative model over the distribution of optimal trajectories. We use a diffusion process-like strategy to model the policy and derive a novel variational bound which is the optimization objective to learn the policy. To maximize the objective by gradient descent, we introduce the Reparameterized Policy Gradient Theorem. This theorem elegantly connects classical method REINFORCE and trajectory return optimization for computing the gradient of a policy. Moreover, our method enjoys strong exploration ability due to the multi-modality policy parameterization; notably, when a strong differentiable world model presents, our method also enjoys the fast convergence speed of trajectory optimization. We evaluate our method on numerical problems and manipulation tasks within a differentiable simulator. Qualitative results show its ability to capture the multi-modality distribution of optimal trajectories, and quantitative results show that it can avoid local optima and outperforms baseline approaches.

1 Introduction

Reinforcement learning (RL) with *high-dimensional continuous action space* is notoriously hard despite its fundamental importance for many application problems such as robotic manipulation (OpenAI et al., 2019; Mu et al., 2021). Compared with the discrete action space counterpart setup, it is much trickier to represent policies for continuous RL – by the optimality theory of RL, the function class of discrete RL policies is simply categorical distributions (Sutton & Barto, 2018), while the function class of continuous RL policies has to include density functions of arbitrary probabilistic distributions.

In practice, popular frameworks (Silver et al., 2014; Haarnoja et al., 2018; Schulman et al., 2017) of deep RL formulate the continuous policy as a neural network that outputs a single-modality density function over the action space (e.g., a Gaussian distribution over actions). This formulation, however, breaks the promise of RL being a global optimizer of the return function because the single-modality policy parameterization introduces local minima that are hard to escape using gradients w.r.t. distribution parameters. Besides, a single-modality policy will significantly weaken the exploration ability of RL algorithms because the sampled actions are usually concentrated around the modality. Our Bandit examples show how a single-modality RL policy fails to solve a simple contextual bandit problem. Therefore, in practice, continuous RL often requires meticulous reward design that takes considerable human effort (Mu et al., 2021; Savva et al., 2019; Yu et al., 2020; Makoviychuk et al., 2021; Zhu et al., 2020).

In this paper, we propose a principled framework to learn the continuous RL policy as a multi-modality density function. We provide a holistic solution to two closely-related questions: *1) how to parameterize the continuous RL policy? 2) how to update the policy parameterized as in (1)?*

Our parameterization of the continuous RL policy is based on two ideas. First, we take a sequence modeling perspective (Chen et al., 2021) and view the policy as a density function over *the entire trajectory space* (instead of the action space) (Levine, 2018). Under this sequence modeling perspective, we can sample a population of trajectories that cover multiple modalities of trajectories,

which allows us to concurrently explore distant regions in the solution space. Second, we use a generative model to parameterize the multi-modality policies, inspired by their success in modeling highly complicated distributions such as natural images Goodfellow et al. (2016); Zhu et al. (2017); Rombach et al. (2022); Ramesh et al. (2021). We introduce a sequence of latent variables z, and we learn a decoder that "reparameterizes" the random distribution z into the multi-modality trajectory distribution (Kingma & Welling, 2013), from which we can sample trajectories τ. Our policy network is, in a spirit, akin to diffusion models Rombach et al. (2022); Ramesh et al. (2021) by learning to model the joint distribution $p(z, \tau)$. As a prototypical work, we prefer simple design and choose not to include the multi-step diffusion process as in image modeling.

Our choice of policy parameterization leads us to adopt the variational method (Kingma & Welling, 2013; Haarnoja et al., 2018; Moon, 1996) to derive an on-policy learning algorithm. Classical on-policy learning leverages the policy gradient theorem (Sutton & Barto, 2018), i.e., $\nabla J(\pi) = \mathbb{E}_\tau[R(\tau)\nabla \log p(\tau)]$. Because we model $p(z, \tau)$, that requires computing $p(\tau)$ and its gradient with $\int_z p(z, \tau)\,\mathrm{d}z$. However, marginalizing out z is often intractable when z is continuous, and it is well-known that optimizing the marginal distribution $\log p(\tau)$ by gradient descent suffers from local optimality issues (e.g., using gradient descent to optimize Gaussian mixture models which have latent variables is not effective, so EM is often used instead Ng (2000)). To overcome these obstacles, we take a different route and adopt variational method (maximum entropy RL) that directly optimizes the joint distribution of the optimal policy without hassels of integrating over z.

We derive a novel variational bound which is the optimization objective for policy learning. To maximize this objective, we introduce the **Reparameterized Policy Gradient Theorem**. The theorem states a principled way to compute the policy gradient by combining the reward-weighted gradient (as in the classical policy gradient theorem) and the path-wise gradient from a differentiable world model (as in classical trajectory optimization methods). The two sources of gradient complement each other – the reward-weighted gradient improves the likelihood of selecting trajectories from regions containing high-reward ones, whereas the path-wise gradient suggests updates to make local improvements to trajectories. This combination allows us to enjoy the precise gradient computation from differentiable world models (Werling et al., 2021; Hu et al., 2019; Huang et al., 2021) and also maintains the flexibility to sample and optimize the trajectory distribution globally. Note that this beautiful result is also a consequence of introducing the latent variable z.

The effectiveness of our method is rooted in our choice of generative policy modeling method. An ideal method needs to be powerful in modeling multi-modality distribution, and it needs to support sampling, density value computation, and stable gradient computation. Although there are other candidates of deep generative models, they often have limitations to be used for continuous policy modeling. For example, GAN-like generative models (Goodfellow et al., 2020) can only sample but not compute the density value. While normalizing flow (Rezende & Mohamed, 2015) can compute the density value, they might not be as robust numerically due to the dependency on the determinant of the network Jacobian; moreover, normalizing flows must apply continuous transformations onto a continuously connected distribution, making it difficult to model disconnected modes (Rasul et al., 2021).

We apply our methods to several numerical problems and three trajectory optimization tasks to manipulate rigid-body objects and deformable objects supported by differentiable physics engines (Werling et al., 2021; Huang et al., 2020). These environments contain various local optima that challenge single-modality policies (either reward-weighted policy gradients as in REINFORCE or path-wise gradients as in trajectory optimization). In contrast, our approach benefits from modeling the trajectories as generative models and the ability to sample in the trajectory space. In qualitative experiments, we observe a strong pattern of multi-modality distribution by visualizing the policy after the learning converges. By quantitative evaluation, policy learned by our framework does not suffer from the local optimality issue and significantly outperforms baselines.

2 VARIATIONAL REPARAMETERIZED POLICY LEARNING

In this section, we introduce our basic framework. All notations follow the convention of the community. To be more clear, we leave a section which introduces background knowledge in Appendix A and a mathematical table for notations in Appendix B.

a) Reward   b) Hidden space   c) Trajectory Distribution

Figure 1: a) the reward landscape where the agent needs to move from the red dots to the region containing a high reward; b) latent space $\mathcal{Z}$ modeled by random Gaussian; c) the state density of a sampled trajectory from $q_\theta(z, \tau)$. In (c), each red dot corresponds to a state in the trajectory. Our policy can be viewed as encoding the stochastic latent variable z into the trajectory distribution through the decoder $q_\theta(z, \tau)$. We rely on an encoder $p_{\phi(z|\tau)}$ to ensure the cycle consistency between the latent z and the sampled trajectory τ.

2.1 Generative Modeling of Optimal Trajectories

Following (Levine, 2018; Haarnoja et al., 2018), our Variational Reparameterized Policy (VRP) framework, as shown in Fig. 1, views policy optimization as learning a generative model that generates optimal trajectories. To capture the multimodalities of the optimal trajectories, we introduce a latent distribution and construct a decoder-encoder structure similar to recent deep generative models (Kingma & Welling, 2013; Ho et al., 2020; Rombach et al., 2022; Ramesh et al., 2021). The "encoder" maps trajectories to latent samples, while the decoder is a neural network that "reparameterizes" random samples from the latent distribution into different trajectories.

Unlike traditional generative models, which sample x from an observed data distribution $p(x)$, we hope to model such a distribution in the context of online RL or trajectory optimization. In this case, we can not sample trajectories from the density conditioning on the optimality O, i.e., $p(\tau|O)$, but can only sample τ first and retrieve its reward (score), the unnormalized density. Additional challenges arise when we want to take advantage of the reward gradients $\nabla_\theta \log p(\tau|O)$. We address these problems in our principled framework.

Method Overview. As introduced in Sec. 2.2, the latent distribution and the reparameterization function together form a policy that can generate diverse trajectories. We use a novel variational bound to approximate the posterior of optimal trajectories in Sec. 2.3 as the optimization objective. The variational bound naturally combines maximum entropy RL while also containing a term to enforce cycle consistency (Zhu et al., 2017) between the encoder and the decoder, preventing the policy from mode collapse. We then introduce a Reparameterized Policy Gradient Theorem in Sec. 2.4 to optimize our reparameterized policy to improve the variational bound. We find that the derived policy gradient includes two terms: one optimizes the latent distribution through a reward-weighted gradient as the classical policy gradient theorem, and another optimizes the reparameterization network, which can benefit from the path-wise gradient from a differentiable world model. This helps our inference algorithm to enjoy the efficiency of differentiable physics while being able to sample globally when the reward landscape is discontinuous or non-convex.

2.2 Trajectory Generation with Reparameterized Policy

Let $z \in \mathcal{Z}$ be a latent variable, which can be either continuous or categorical to model optimal trajectories. We design our "policy" as a joint distribution $q_\theta(z, \tau)$ of latent z and the trajectory τ. To model a sequential trajectory, we can consider the following two factorizations:

- Sample z before τ: $q_\theta(z, \tau) = p(s_1) q_\theta(z|s_1) \prod_{t=1}^T p(s_{t+1}|s_t, a_t) q_\theta(a_t|z, s_t)$. When z is discrete, this form is similar to a mixture-of-expert policy or population-based policies (Jia et al., 2022), where the agent needs to first select a categorical z and take actions conditioning on z.

- Sample z with τ: $q_\theta(z,\tau) = p(s_1)q_\theta(z_0|s_1)\prod_{t=1}^{T} p(s_{t+1}|s_t,a_t)q_\theta(a_t|z_{t-1},s_t)q_\theta(z_t|s_t,z_{t-1})$. This allows us to model the hybrid policy as in the option-critic (Bacon et al., 2017), where we can treat z_t as the option per step.

Though sampling from q_θ may require us to sample τ, z together, it is still convenient to view it as the combination of two marginal distributions: (1) the policy for the latent representation $p_\theta(z|s_1)p(s_1)$, and (2) a decoder $p_\theta(\tau|z,s_1)$ that reparameterizes z into a real trajectory. Note that we will use p_θ to refer to various marginal distribution of $q_\theta(z,\tau)$. For example, $p_\theta(\tau) = \int_z q_\theta(z,\tau)dz$ will be the marginal distribution of trajectories sampled from $q_\theta(z,\tau)$.

The term "reparameterization" is inspired by the reparameterization trick in (Kingma & Welling, 2013). When z is a Gaussian noise ξ, we can reparameterize the noise into actions by $a = \mu(\theta)+\xi\sigma(\theta)$ and optimize it with gradients directly. Similarly, we reparameterize latent z into trajectories through the combination of the policy and the environment. As will be discussed in Sec. 2.4, with the help of a differentiable world model, we can use a deterministic policy $a_t = \mathbf{f}_\theta(s_t,z,t)$ to "reparameterize" a random sample z into the whole trajectory τ. The reparameterized policy q_θ can be viewed as an instance of the stochastic computation graph (Schulman et al., 2015; Weber et al., 2019). In practice, $q_\theta(z|s)$ or $q_\theta(a|s,z)$ are modeled by neural networks as in common policy learning frameworks (Haarnoja et al., 2018).

2.3 THE VARIATIONAL LOWER BOUND FOR REPARAMETERIZED POLICIES

The Auxiliary Trajectory Encoder Intuitively, learning policy networks by injecting random noises can help generate diverse examples, but it will also suffer from the issues of mode collapse Li et al. (2017). To build a connection between the trajectory and τ and enforce a cycle consistency, we introduce an auxiliary distribution $p_\phi(z|\tau)$, which can look at the whole trajectories and map τ back into the latent z.

This section will illustrate how the auxiliary encoder naturally emerges from the variational lower bounds following (Rezende & Mohamed, 2015; Levine, 2018). Enforcing the cycle consistency through an additional encoder can be understood as maximizing mutual information between the latent code and the data as in (Zhu et al., 2017). This suggests the common approach to approximate it by a neural network. In addition, it is also possible to use a non-parametric $p_\phi(z|\tau)$, for example, a diffusion process or an intrinsic reward that can define a density function (Song et al., 2020).

The Evidence Lower Bound With the help of the auxiliary encoder $p_\phi(z|\tau)$, we can now define a joint distribution of optimality O, latent z, and the trajectory τ as $p_\phi(O,z,\tau) = p(O|\tau)p_\phi(z|\tau)p(\tau)$ where O and z are independent conditioning on τ. Treating $q_\theta(z,\tau)$ as the posterior approximation, we can write the Evidence Lower Bound (ELBO) for the optimality. Note that the following inequality holds for arbitrary distribution p_ϕ and q_θ,

$$\log p(O) = \underbrace{\mathbb{E}_{z,\tau\sim q_\theta}\left[\log p_\phi(O,z,\tau) - \log q_\theta(z,\tau)\right]}_{\text{ELBO}} + D_{KL}(q_\theta(z,\tau)||p_\phi(z,\tau|O))$$

$$\geq \mathbb{E}_{z,\tau\sim q_\theta}\left[\log p_\phi(O,\tau,z) - \log q_\theta(z,\tau)\right]$$

$$= \mathbb{E}_{z,\tau\sim q_\theta}\left[\log p(O,\tau) + \log p_\phi(z|\tau) - \log q_\theta(z,\tau)\right]$$

$$= \mathbb{E}_{z,\tau\sim q_\theta}\left[\underbrace{\log p(O|\tau)}_{\text{reward}} + \underbrace{\log p(\tau)}_{\text{prior}} + \underbrace{\log p_\phi(z|\tau)}_{\text{cross entropy}} - \underbrace{\log q_\theta(z,\tau)}_{\text{entropy}}\right] \tag{1}$$

The ELBO contains four parts that can all be computed directly given the sampled z and τ (the environment probability $p(s_{t+1}|s_t,a_t)$ is canceled as in (Levine, 2018)). The first two parts are the predefined reward $\log p(O|\tau) = R(\tau)/\mathcal{T} + c$, where c is the normalizing constant that can be ignored during optimization, and a prior distribution $p(\tau)$, which is assumed to be known. The third part is the log likelihood of z based on our encoder. It is easy to see that if we fix q_θ, and maximize p_ϕ alone will minimize the cross-entropy $E_{z,\tau\sim q_\theta}[-\log p_\phi(z|\tau)]$, similarly to the supervised learning. It achieves optimality when $p_\phi(z|\tau) = p_\theta(z|\tau) = \frac{q_\theta(z,\tau)}{\int_z q_\theta(z,\tau)dz}$, modeling the posterior of z for τ sampled from q_θ. On the other hand, fixing ϕ, the decoder q_θ is encouraged to generate trajectories that are easy

to identify or classify; this helps to increase diversity and enforce a cycle consistent to avoid mode collapse. The fourth part is the policy entropy that enables maximum entropy exploration.

Maximizing all terms together for the parameters θ and ϕ will minimize

$$D_{KL}(q_\theta(z,\tau)||p_\phi(z,\tau|O)) = D_{KL}(q_\theta(z,\tau)||p_\phi(z|\tau)p(\tau|O)),$$

where optimality can be achieved when $p_\theta(z|\tau) = p_\phi(z|\tau)$ and $p_\theta(\tau)p_\theta(z|\tau) = p_\phi(z|\tau)p(\tau|O) \Rightarrow p_\theta(\tau) = \int q_\theta(\tau, z)dz = p(\tau|O)$. We discuss the method's connection with other methods in Appendix C.

2.4 REPARAMETERIZED POLICY GRADIENT WITH DIFFERENTIABLE PHYSICS

Given θ, ϕ we can treat the ELBO as our reward $R_{\text{elbo}}(\tau) = \log p(O|\tau) + \log p(\tau) + \log p_\phi(z|\tau) - \log q_\theta(z,\tau)$. The maximization w.r.t. ϕ is straightforward. As for q_θ, depending on its structure, we can optimize it with various on-policy or off-policy RL methods as in (Weber et al., 2019).

Here we study a special case where $R_{\text{elbo}}(\tau)$ is differentiable to θ through a sampled trajectory τ. Thus, we can optimize θ by first-order path-wise gradients directly. This case is very interesting as analytical gradients provide a fast convergence speed but also suffer from the local optima issue (Li et al., 2017), while our reparameterization policy naturally includes a latent distribution for sampling and a parameterization part for optimization, providing more chances to search globally. One can obtain a path-wise gradient from a differentiable simulator (Hu et al., 2019; Werling et al., 2021), a learned neural model (Liang et al., 2022).

Reparameterized Policy in Differentiable Environments. Formally, we hope to find θ to maximize the expectation $\mathbb{E}[R_{\text{elbo}}(\tau)] = \int_{z,\tau} q_\theta(z,\tau)R_{\text{elbo}}(\tau)d\tau dz$[1]. The sampling process is usually non-differentiable. But if we let $a_t = \mathbf{f}_\theta(s_t, z, t)$ and the dynamics $s_{t+1} = h(s_t, a_t)$ be differentiable functions, the trajectory τ becomes a differentiable function of θ almost everywhere.

We further assume that s_1 is fixed and the functions $\mathbf{f}_\theta, h$ are deterministic to simplify the derivation. One can remove these assumptions easily through reparameterization as in (Silver et al., 2014; Heess et al., 2015) to generalize to stochastic functions. As a result, we can write $q_\theta(z, \tau_\theta) = q_\theta(z|\tau(z, s_1))$, where τ and the density q_θ is a deterministic function of the sampled z and s_1. Thus, we can write $\mathbb{E}[R_{\text{elbo}}(\tau_\theta)] = \int_z q_\theta(z, \tau_\theta)R_{\text{elbo}}(\tau_\theta)dz$ and for each sampled trajectory τ_θ and compute its path-wise gradient w.r.t. to the policy parameter θ as $\nabla_\theta R_{\text{elbo}}(\tau_\theta)$.

Differentiation under the Integration Sign. We are now ready to use path-wise gradients to estimate the policy gradient of the expectation. However, it is not always feasible to swap differentiation and integration in the following equations,

$$\nabla_\theta \mathbb{E}[R_{\text{elbo}}(\tau_\theta)] = \nabla_\theta \int_z q_\theta(z, \tau_\theta)R_{\text{elbo}}(\tau_\theta)dz = \int_z \nabla_\theta \left(q_\theta(z, \tau_\theta)R_{\text{elbo}}(\tau_\theta)\right)dz$$

As demonstrated by (Suh et al., 2022) and (Li et al., 2018), the above equality may suffer from the issue of discontinuities. When the reward landscape has discontinuous points, there will be a bias caused by the motion of the discontinuity as suggested by the Leibniz integral rule. We refer the interested readers to Appendix E for a detailed illustration of the difference between the zeroth-order gradient estimate and the first-order gradient estimate under the expectation we do not find in the literature.

We now state a policy gradient theorem under several regularity conditions. The major requirement is the Lipschitz continuity of the whole system. Note that we do not ask for the continuity of the neural networks and support functions such as ReLU.

Theorem 1 (Reparameterized Policy Gradient Theorem). *Given s_1 and under regularity conditions in Appendix F.1. For almost every θ, the expected reward $E[R_{elbo}(\tau_\theta)]$ exists and differentiable, and*

---

[1]Here we assume z contains only continuous variables to simplify the derivation. Adding discrete variables is straightforward by summing over all possibilities.

its gradient can be computed by

$$\nabla_\theta \mathbb{E}[R_{elbo}(\tau_\theta)] = \int_z q_\theta(z, \tau_\theta) \left[\underbrace{R_{elbo}(\tau_\theta)\nabla_\theta \log q_\theta(z, \tau_\theta)}_{\substack{\text{Reward-weighted Gradient} \\ \text{(REINFORCE)}}} + \underbrace{\nabla_\theta R_{elbo}(\tau_\theta)}_{\substack{\text{Pathwise Gradient} \\ \text{(Trajectory Optimization)}}} \right] dz.$$

We provide a short proof in Appendix F.2. We want to emphasize the importance of the Lipschitz continuity that helps to bound the integration. Informally, the Lipschitz condition is directly related to the scale of the path-wise gradient. When the Lipschitz constant is too large, the environments will generate exploding gradients or contains sharp changes in the reward landscape, similarly to the discontinuity and causing empirical bias Suh et al. (2022). The finite horizon assumption is necessary to make the theorem holds, otherwise the gradients $\nabla_\theta R_{elbo}(\tau_\theta)$ may be unbounded if we do not set up a suitable discount factor.

Combine Sampling and Optimization. Theorem 1 splits gradients into two parts. The first part is a reward-weighted gradient that aims to improve the likelihood of the distribution $q_\theta(z|\tau) = q_\theta(z, \tau_\theta)$ for high-reward ones. If the environment is differentiable, the second part may optimize the policy directly through a path-wise gradient to make local improvements to trajectories. The natural combination of the sampling and optimization may allow our approach to enjoy the benefits of both: it can search over the whole space but can also leverage local structures for fast convergence speed. This can not be achieved without the latent variable z.

Our methods provide the potential to avoid discontinuities in the reward landscape. If $q_\theta(z, \tau_\theta)$ does not depend on $s_{>1}$, the reward-weighted gradient can optimize the sampling distribution directly without relying on the path-wise gradients, providing the policy a chance to ignore the discontinuous point and move to the high reward region directly. Another appealing point in Theorem 1 is that in Assumption 2, we only require $R_{elbo}(\tau_\theta)$ to be Lipschitz continuous for $q_\theta(z, \tau_\theta) \geq 0$. Thus, our policy gradient estimate can make an unbiased estimation so long as the probability density of sampling a discontinuous trajectory is negligible. Even if a discontinuous point generates a biased gradient estimation for a sampled z, the zeroth-order part still has a chance to correct its density directly by observing the reward directly so long as the optimal trajectories have certain properties.

By defining latent distributions, building the reparameterized policy and the auxiliary encoder, then optimizing the ELBO with the reparameterized policy gradient through a differentiable world model, we can combine search and optimization to enjoy the generative modeling of the optimal trajectories. We summarize the whole recipe in Algorithm 1 of Appendix D and describe implementation details in Appendix D.

3 RELATED WORK

Differentiable simulation and trajectory optimization. Trajectory optimization (Kelly, 2017) aims to find a trajectory which optimizes the target metrics under given constraints over the trajectory. One branch of methods optimizes the trajectory using the gradient of the optimization objective (Ratliff et al., 2009; Kalakrishnan et al., 2011; Schulman et al., 2014). Recently, the development of differentiable simulation technique (Hu et al., 2019; Werling et al., 2021; Qiao et al., 2021; Freeman et al., 2021; Howell et al., 2022) enables to compute the the gradient from the reward function and optimize the trajectory in physical simulators. Such methods are efficient around the optimal solution; however, the optimization often gets stuck at local optima elsewhere, especially when the reward function is not smooth. In our work, one term in the formula of our RPG theorem corresponds to the gradient from trajectory optimization.

Policy as Sequential Generative Model. A line of works (Chen et al., 2021; Zheng et al.; Reed et al., 2022) treat the policy learning as sequence modeling tasks. They use autoregressive models to learn the distribution of the whole trajectory including actions, states, and rewards, and use the action prediction as policy. Most of the previous works focus on the *offline* RL setting (Chen et al., 2021; Reed et al., 2022), where the model is trained over a fixed dataset. In our work, we learn a sequential generative model of policy for *online* RL via the variational method. The policy has the ability to model any distributions in the trajectory space.

Hierarchical Methods. As mentioned in Sec. 2.2, the hierarchical methods, e.g. option critic (Bacon et al., 2017), can be seen as a special case of our work when we use a sequence of latent variables $z = (z_1, \cdots, z_T)$ to reparameterize the policy. Among existing works, (Co-Reyes et al., 2018; Jiang et al., 2022) are the most relevant ones. They both pre-train a sequence embedding model with a pre-determined dataset via variational inference and then utilize the pretrained model in planing or policy learning. Our work jointly optimizes the sequence of latent variables and the policy through RL and trajectory optimization.

4 EXPERIMENT

Figure 2: Environments for numerical experiments. We plot the reward landscapes in the first two bandit environments and show the rewards of the terminating positions in the left three 2d move environments.

In this section, we verify 1) whether our method is more efficient for trajectory optimization than gradient-free algorithms; 2) whether our method can search over the large solution space and avoid local optima that might trap a gradient-based optimizer; 3) whether our method can properly model the posterior distribution through variational policy learning. We also demonstrate how different designs affect our method's performance.

4.1 NUMERICAL EXPERIMENTS

We first evaluate our method for sample efficiency and evaluate its ability to escape local optima. We evaluate our method against the single modality policies learned from the following baselines: 1) REINFORCE (Williams, 1992), and 2) policies optimized through path-wise gradients with Adam (Kingma & Ba, 2014).

Bandit 1 and 2: Our bandit problems in Figure 2-Left have a 1d action space and a non-convex reward landscape. We initialize our policy as a Gaussian centralized around 0, thus is close to the local maximum on the right. The reward function of *Bandit 2* contains an additional discontinuous point. **Move 1 and 2**: An agent moves in an environment and receives a reward according to its terminal position. The terminal reward contains 4 Gaussian peaks (deeper color = higher reward), as shown in Figure 2-Mid. The agent is initialized at the center. Note that *Move 1* contains zero rewards near the initialization point, so the agent receives a non-zero gradient only if it arrives at a position closer to one of the four Gaussian peaks. **Move 3**: The terminal reward shown in Figure 2-Right. There is one obstacle consisting of three white circles. When an agent runs into an obstacle, it will bounce off due to an impulse normal to the contact surface. The small slot creates a local optimum.

Experiment results. To understand the difference of different algorithms in sample efficiency, for every number of simulator steps, for each algorithm, we plot the total rewards averaged over trajectories sampled from the current policy and show them in Figure 3. The error bar shows the standard deviation of this measurement over five runs with different random seeds.

Optimality. We can see pure gradient-based algorithms like Adam (Kingma & Ba, 2014) can easily get stuck at the local optima in all environments, though it converges fast. Adam therefore is unable to handle discontinuous and flat reward landscapes (Bandit 2, Move 1). Although REINFORCE can handle discontinuities due to its reward-weighted gradient estimation of the policy gradient, because it uses a single-modality Gaussian policy, it cannot explore over the multi-modality of the optimal trajectory distribution. Also, when the local optimum is closer to the initialization, it easily gets stuck in it and can hardly jump out. Besides, they show high variance across different seeds. Our method combines the advantage of both sampling and gradient-based methods with the help of

Figure 3: Training curve. X-axis: simulator samples. Y-axis: average undiscounted sum of rewards. Color: algorithm. Error bar shows std over 5 runs. Hyperparameters are available in Table 2.

latent distributions. It enjoys the fast convergence of the gradient-based optimizer. Meanwhile, it can simultaneously search and explore the whole reward landscape under the maximum-entropy principle and finally find the optimal solutions.

4.1.1 HOW LATENT DISTRIBUTIONS AFFECT THE TRAJECTORY MODELING?

Modeling the trajectories with a sequential $\{z_i\}$ instead of a single latent variable sampled before sampling the trajectory τ can help factorize the trajectory space to build a more compact representation. We construct an environment containing four obstacles to demonstrate its effects in Figure 4. The agent on the bottom left must avoid obstacles and reach the goal at the top right corner. We study the case where z is a discrete variable. We first plot the state and the action distributions for policies learned by sampling a single categorical z before the trajectory τ in Figure 4a. Different colors represent the different values of z. We plot the state and action distributions and use different colors to represent their corresponding z values. Though a categorical distribution can represent various paths toward the goal, the number of latent samples constrained its expressive power. However, as shown in Figure 4b, we model the distribution with a sequence of $z_1, z_{K+1}, z_{2K+1}, \ldots, z_{NK+1}$. This brings the compositionality that allows the agents to select various z sequences to generate trajectories that can better cover the state space. The action distribution on the right successfully captures the symmetry of the optimal trajectories and the action pattern of moving along different directions, which helps the policy better cover the whole state space compared with a single categorical distribution.

(a) Sample z before τ (b) Sample a sequence of $\{z_i\}$

Figure 4: A navigation task to demonstrate the effects of learning a sequence of z. An agent needs to move from the bottom left to the top right and avoid the green obstacles. Both the state and action space are 2D. Different colors represent different values of z or z_i.

4.2 EVALUATION ON MANIPULATION TASKS WITH DIFFERENTIABLE PHYSICS

We evaluate our approach in several physical environments to demonstrate its potential in trajectory optimization. Figure 5 compares our approaches against the gradient-based trajectory optimizer with a single Gaussian head in three environments. The **Grasp** environment, based on Nimble Physics (Werling et al., 2021), contains three balls. The agent needs to control a 3 DoF gripper to grasp the green ball and pick it up. However, the agent only knows that it needs to grasp an object, and it does not receive any reward before lifting it. We use a reward to minimize the distance between the gripper and the nearest balls, which creates a *local minimum* that encourages the gripper to touch the nearest ball in front of it, as shown in Figure 5. The first-order gradient-based trajectory optimization

got stuck. In contrast, our method can capture the multimodality of the reward landscape, approach different balls, and exploit different options (touching different balls) simultaneously. In the end, our method successfully finds the solution to pick up the green ball. The **Rope** and the **Cut** environments are two soft body environments built with PlasticineLab (Huang et al., 2020), each containing a 3DoF rigid body manipulator. In the **Rope** environment, an agent needs to push the left side of a rope forward. Similarly, in the **Cut** environment, an agent needs to cut off the left end of a rope. However, manipulators are initialized in the middle of the objects, which is far away from suitable contact points required to finish the tasks, leading to local optima (Li et al., 2022) as shown in Fig. 5. In contrast, our method can explore different contact points and find correct solutions in the end. These experiments show the potential of our approach in learning the optimal policies with differentiable physics.

Figure 5: Visualization of policy distribution for manipulation with differentiable physics. We qualitatively compare the Gaussian policy learned by ADAM and the multi-modality policy learned by our method. On the left, we overlay final states from three trajectories of the Gaussian policy. On the right, we also draw three samples (trajectories) from the policy, and we visualize the final state of each trajectory in a different plot. We see that the three final states from the Gaussian policy are similar, while the final states are very different for trajectories from our policy. Additionally, one of the modalities of our method can solve the problem (the rightmost column), while the Gaussian policies get stuck in local minima.

5 CONCLUSION AND FUTURE WORK

We derive a framework that models the policy of continuous RL by a multi-modality distribution in the variational inference framework. Under this framework, we also derive a Reparameterized Policy Gradient Theorem which enjoys the advantage of both classical sample-based methods (as in REINFORCE) and trajectory optimization methods (which require the support of differentiable world models).

Our framework opens a new venue of continuous RL. It has deep connections with diffusion model, decision sequence modeling, and differentiable physics techniques. In the future, we are interested in exploring how sequence modeling techniques, such as transformers, can be used to model the policy in our framework. We are also interested in testing our method for more complicated tasks, such as dexterous object manipulation. Finally, our method can be extended to offline RL and off-policy RL setups. We leave all these exploration efforts to future works.

REPRODUCIBLITY STATEMENT

We will provide an open-source implementation of our method on GitHub. We will also update more illustrative examples and demos to our website. The hyperparameter used in the experiment section can be found in Table 2 in the appendix. The theoretical results are also in multiple sections of our appendix.

REFERENCES

Rika Antonova, Jingyun Yang, Krishna Murthy Jatavallabhula, and Jeannette Bohg. Rethinking optimization with differentiable simulation from a global perspective. *arXiv preprint arXiv:2207.00167*, 2022.

Pierre-Luc Bacon, Jean Harb, and Doina Precup. The option-critic architecture. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31, 2017.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Misha Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34:15084–15097, 2021.

John Co-Reyes, YuXuan Liu, Abhishek Gupta, Benjamin Eysenbach, Pieter Abbeel, and Sergey Levine. Self-consistent trajectory autoencoder: Hierarchical reinforcement learning with trajectory embeddings. In *International conference on machine learning*, pp. 1009–1018. PMLR, 2018.

A. P. Dempster, N. M. Laird, and D. B. Rubin. Maximum likelihood from incomplete data via the em algorithm. *Journal of the Royal Statistical Society: Series B (Methodological)*, 39(1):1–22, 1977. doi: https://doi.org/10.1111/j.2517-6161.1977.tb01600.x. URL https://rss.onlinelibrary.wiley.com/doi/abs/10.1111/j.2517-6161.1977.tb01600.x.

Harley Flanders. Differentiation under the integral sign. *The American Mathematical Monthly*, 80(6): 615–627, 1973.

C Daniel Freeman, Erik Frey, Anton Raichuk, Sertan Girgin, Igor Mordatch, and Olivier Bachem. Brax–a differentiable physics engine for large scale rigid body simulation. *arXiv preprint arXiv:2106.13281*, 2021.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT Press, 2016.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks. *Communications of the ACM*, 63(11):139–144, 2020.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pp. 1861–1870. PMLR, 2018.

Nicolas Heess, Gregory Wayne, David Silver, Timothy Lillicrap, Tom Erez, and Yuval Tassa. Learning continuous control policies by stochastic value gradients. *Advances in neural information processing systems*, 28, 2015.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Taylor A Howell, Simon Le Cleac'h, J Zico Kolter, Mac Schwager, and Zachary Manchester. Dojo: A differentiable simulator for robotics. *arXiv preprint arXiv:2203.00806*, 2022.

Yuanming Hu, Luke Anderson, Tzu-Mao Li, Qi Sun, Nathan Carr, Jonathan Ragan-Kelley, and Frédo Durand. Difftaichi: Differentiable programming for physical simulation. *arXiv preprint arXiv:1910.00935*, 2019.

Zhiao Huang, Yuanming Hu, Tao Du, Siyuan Zhou, Hao Su, Joshua B Tenenbaum, and Chuang Gan. Plasticinelab: A soft-body manipulation benchmark with differentiable physics. In *International Conference on Learning Representations*, 2020.

Zhiao Huang, Yuanming Hu, Tao Du, Siyuan Zhou, Hao Su, Joshua B Tenenbaum, and Chuang Gan. Plasticinelab: A soft-body manipulation benchmark with differentiable physics. *arXiv preprint arXiv:2104.03311*, 2021.

Zhiwei Jia, Xuanlin Li, Zhan Ling, Shuang Liu, Yiran Wu, and Hao Su. Improving policy optimization with generalist-specialist learning. In *International Conference on Machine Learning*, pp. 10104–10119. PMLR, 2022.

Zhengyao Jiang, Tianjun Zhang, Michael Janner, Yueying Li, Tim Rocktäschel, Edward Grefenstette, and Yuandong Tian. Efficient planning in a compact latent action space. *arXiv preprint arXiv:2208.10291*, 2022.

Mrinal Kalakrishnan, Sachin Chitta, Evangelos Theodorou, Peter Pastor, and Stefan Schaal. Stomp: Stochastic trajectory optimization for motion planning. In *2011 IEEE international conference on robotics and automation*, pp. 4569–4574. IEEE, 2011.

Matthew Kelly. An introduction to trajectory optimization: How to do your own direct collocation. *SIAM Review*, 59(4):849–904, 2017.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representations*, 12 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Sergey Levine. Reinforcement learning and control as probabilistic inference: Tutorial and review. *arXiv preprint arXiv:1805.00909*, 2018.

Sizhe Li, Zhiao Huang, Tao Du, Hao Su, Joshua B Tenenbaum, and Chuang Gan. Contact points discovery for soft-body manipulations with differentiable physics. In *International Conference on Learning Representations*, 2022.

Tzu-Mao Li, Miika Aittala, Frédo Durand, and Jaakko Lehtinen. Differentiable monte carlo ray tracing through edge sampling. *ACM Transactions on Graphics (TOG)*, 37(6):1–11, 2018.

Yunzhu Li, Jiaming Song, and Stefano Ermon. Infogail: Interpretable imitation learning from visual demonstrations. *Advances in Neural Information Processing Systems*, 30, 2017.

Jacky Liang, Mohit Sharma, Alex LaGrassa, Shivam Vats, Saumya Saxena, and Oliver Kroemer. Search-based task planning with learned skill effect models for lifelong robotic manipulation. In *2022 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, 2022.

Viktor Makoviychuk, Lukasz Wawrzyniak, Yunrong Guo, Michelle Lu, Kier Storey, Miles Macklin, David Hoeller, Nikita Rudin, Arthur Allshire, Ankur Handa, et al. Isaac gym: High performance gpu-based physics simulation for robot learning. *arXiv preprint arXiv:2108.10470*, 2021.

Todd K Moon. The expectation-maximization algorithm. *IEEE Signal processing magazine*, 13(6): 47–60, 1996.

Tongzhou Mu, Zhan Ling, Fanbo Xiang, Derek Yang, Xuanlin Li, Stone Tao, Zhiao Huang, Zhiwei Jia, and Hao Su. Maniskill: Generalizable manipulation skill benchmark with large-scale demonstrations. *arXiv preprint arXiv:2107.14483*, 2021.

Andrew Ng. Cs229 lecture notes. *CS229 Lecture notes*, 1(1):1–3, 2000.

OpenAI, Ilge Akkaya, Marcin Andrychowicz, Maciek Chociej, Mateusz Litwin, Bob McGrew, Arthur Petron, Alex Paino, Matthias Plappert, Glenn Powell, Raphael Ribas, Jonas Schneider, Nikolas Tezak, Jerry Tworek, Peter Welinder, Lilian Weng, Qiming Yuan, Wojciech Zaremba, and Lei Zhang. Solving rubik's cube with a robot hand. *CoRR*, abs/1910.07113, 2019. URL http://arxiv.org/abs/1910.07113.

Yiling Qiao, Junbang Liang, Vladlen Koltun, and Ming Lin. Differentiable simulation of soft multi-body systems. *Advances in Neural Information Processing Systems*, 34:17123–17135, 2021.

Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, pp. 8821–8831. PMLR, 2021.

Kashif Rasul, Calvin Seward, Ingmar Schuster, and Roland Vollgraf. Autoregressive denoising diffusion models for multivariate probabilistic time series forecasting. In *International Conference on Machine Learning*, pp. 8857–8868. PMLR, 2021.

Nathan Ratliff, Matt Zucker, J Andrew Bagnell, and Siddhartha Srinivasa. Chomp: Gradient optimization techniques for efficient motion planning. In *2009 IEEE International Conference on Robotics and Automation*, pp. 489–494. IEEE, 2009.

Scott Reed, Konrad Zolna, Emilio Parisotto, Sergio Gomez Colmenarejo, Alexander Novikov, Gabriel Barth-Maron, Mai Gimenez, Yury Sulsky, Jackie Kay, Jost Tobias Springenberg, et al. A generalist agent. *arXiv preprint arXiv:2205.06175*, 2022.

Danilo Rezende and Shakir Mohamed. Variational inference with normalizing flows. In *International conference on machine learning*, pp. 1530–1538. PMLR, 2015.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10684–10695, 2022.

Manolis Savva, Abhishek Kadian, Oleksandr Maksymets, Yili Zhao, Erik Wijmans, Bhavana Jain, Julian Straub, Jia Liu, Vladlen Koltun, Jitendra Malik, et al. Habitat: A platform for embodied ai research. *ICCV*, 2019.

John Schulman, Yan Duan, Jonathan Ho, Alex Lee, Ibrahim Awwal, Henry Bradlow, Jia Pan, Sachin Patil, Ken Goldberg, and Pieter Abbeel. Motion planning with sequential convex optimization and convex collision checking. *The International Journal of Robotics Research*, 33(9):1251–1270, 2014.

John Schulman, Nicolas Heess, Theophane Weber, and Pieter Abbeel. Gradient estimation using stochastic computation graphs. *Advances in Neural Information Processing Systems*, 28, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

David Silver, Guy Lever, Nicolas Heess, Thomas Degris, Daan Wierstra, and Martin Riedmiller. Deterministic policy gradient algorithms. In *International conference on machine learning*, pp. 387–395. PMLR, 2014.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. *arXiv preprint arXiv:2011.13456*, 2020.

Hyung Ju Suh, Max Simchowitz, Kaiqing Zhang, and Russ Tedrake. Do differentiable simulators give better policy gradients? In *International Conference on Machine Learning*, pp. 20668–20696. PMLR, 2022.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Théophane Weber, Nicolas Heess, Lars Buesing, and David Silver. Credit assignment techniques in stochastic computation graphs. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 2650–2660. PMLR, 2019.

Keenon Werling, Dalton Omens, Jeongseok Lee, Ioannis Exarchos, and C Karen Liu. Fast and feature-complete differentiable physics for articulated rigid bodies with contact. *arXiv preprint arXiv:2103.16021*, 2021.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3):229–256, 1992.

Jie Xu, Viktor Makoviychuk, Yashraj Narang, Fabio Ramos, Wojciech Matusik, Animesh Garg, and Miles Macklin. Accelerated policy learning with parallel differentiable simulation. *arXiv preprint arXiv:2204.07137*, 2022.

Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on robot learning*, pp. 1094–1100. PMLR, 2020.

Qinqing Zheng, Amy Zhang, and Aditya Grover. Online decision transformer. *arXiv preprint arXiv:2202.05607*.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *Proceedings of the IEEE international conference on computer vision*, pp. 2223–2232, 2017.

Yuke Zhu, Josiah Wong, Ajay Mandlekar, and Roberto Martín-Martín. robosuite: A modular simulation framework and benchmark for robot learning. *arXiv preprint arXiv:2009.12293*, 2020.

A   PRELIMINARY

Markov decision process   A Markov decision process (MDP) is a tuple of $(\mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R})$, where $\mathcal{S}$ is the state space and $\mathcal{A}$ is the action space. $p(s'|s, a)$ is the transition probability that transits state s to another state s' after taking action a. The function $R(s, a, s')$ computes a reward per transition. A policy $\pi(a|s)$ selects an action distribution according to the state s. Executing a policy π starting from the initial state s_1 with density $p(s_1)$ will result in a *trajectory* τ, which is a sequence of states and actions $\{s_1, a_1, s_2, \ldots, s_t, a_t, \ldots\}$ where $a_t \sim \pi(a|s = s_t), s_{t+1} \sim p(s|s = s_t, a = a_t)$. We also use the terminology *environment* to refer to an MDP in an RL problem. The discounted reward of a trajectory is $R_\gamma(\tau) = \sum_{t=1}^{\infty} \gamma^t R(s_t, a_t, s_{t+1})$ where $0 < \gamma < 1$ is the discount factor to ensure the series converges. The goal of reinforcement learning (RL) is to find a parameterized policy π_θ that maximizes the expected reward $E_{s_1 \sim p(s_1)} V^{\pi_\theta}(s_1) = E_{\tau \sim \pi_\theta, s_1 \sim p(s_1)}[R_\gamma(\tau)]$, where we call $V^{\pi_\theta}(s_1)$ the value of the state s_1 for the policy π_θ.

For simplicity, we focus on optimization problems in a finite horizon MDP in this paper. This means that we only consider the first T states and actions $\{s_1, a_1, \ldots, s_T, a_T, s_{T+1}\}$. In this case, we can directly optimize for the total reward $R(\tau) = \sum_{t=1}^{T} R(s_t, a_t, s_{t+1})$. Defining the measure and ensuring the existence of policy gradients for infinite horizon MDP with differentiable physics requires more strict conditions, and we leave it as future work.

Policy gradient and zeroth-order gradient estimate   REINFORCE (Sutton & Barto, 2018) approximates the expected reward with Monte-Carlo sampling and optimizes the policy parameter θ with a zeroth order gradient estimate, which can be written as $\frac{\partial E_{s_1 \sim p(s_1)}[V^{\pi_\theta}(s_1)]}{\partial \theta} \approx \sum_{i=1}^{N_{\text{samples}}} R(\tau^i) \nabla_\theta \log \pi_\theta(\mathbf{a}^i)$ where N_{samples} is the number of sampled trajectories, τ^i and $\mathbf{a}^i = \{a_t^i\}_{1 \leq t \leq T}$ represent the trajectory and action sequence per sample, and the log-likelihood can be computed by $\log \pi_\theta(\mathbf{a}^i) = \sum_{1 \leq t \leq T} \log \pi_\theta(a_t|s_t)$.

Differentiable simulation   In differentiable physics we consider as a special MDP where the transition probability $p(s'|s, a)$ can be represented as $\delta(s' - h(s, a))^2$. The transition function $h : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{S}$ and reward function $R(s, a, s')$ are deterministic and differentiable. If we further assume that the policy $\pi_\theta(a|s) = \delta(a - \mathbf{f}_\theta(s))$ is a differentiable deterministic function w.r.t. θ and input s, then each element in a sampled trajectory τ and the total reward $R(\tau)$ are also differentiable w.r.t. each s_t, a_t and θ. We can optimize the reward $R(\tau)$ with gradient-based optimizers after computing the first-order path-wise gradient $\frac{\partial R(\tau)}{\partial \theta}$ through back-propogation.

It's argued that even if the environment is deterministic, it is still beneficial to optimize a stochastic policy (Suh et al., 2022; Xu et al., 2022) to leverage the advantages of stochastic sampling for the non-smooth reward landscape (Hu et al., 2019; Xu et al., 2022; Antonova et al., 2022). A typical choice is to add Gaussian noise $\mathbf{w}$ to the action sequence $\mathbf{a}$ and optimize it with the reparameterization trick (Kingma & Welling, 2013), which estimates the same policy gradient as REINFORCE by $\frac{\partial E_{s_1 \sim p(s_1)}[V^{\pi_\theta}(s_1)]}{\partial \theta} \approx \sum_{i=1}^{N_{\text{samples}}} \nabla_\theta R(\tau^i(\mathbf{a}^i + \mathbf{w}^i))$, where $\mathbf{a}^i$ and $\mathbf{w}^i$ are actions and Gaussian noises to generate the i-th trajectory τ^i.

RL as Probabilistic Inference   The RL as inference framework Levine (2018) defines optimality $p(O|\tau) \propto e^{R(\tau)/\mathcal{T}}$, where $\mathcal{T}$ is a defined temperature. It further defines a prior distribution of the trajectory $p(\tau) = p(\tau) = p(s_1) \prod_{t=1}^{T} p(a_t|s_t) p(s_{t+1}|s_t, a_t)$, where $p(a_t|s_t)$ is a known prior action distribution, e.g., a Gaussian distribution. Thus, we can compute the possibility of the optimality $p(O) = p(\tau|O) p(\tau)$. The goal of the framework is to approximate the posterior distribution of optimal trajectories $p(\tau|O) = \frac{p(O|\tau)p(\tau)}{\int p(O|\tau)p(\tau)d\tau}$, which can be considered as a softmax weighting among all prior trajectories based on their rewards, sharing the same spirit to path integral and the SoftMax policy.

---

[2] δ is the Dirac delta function.

B MATHEMATICAL NOTATIONS

Notation	Explanation
z	The latent variable
τ	The sampled trajectory
$p(O|\tau)$	Optimality of a trajectory τ
$p(\tau)$	Prior distribution of trajectories (for example, random actions)
$p(O)$	$\int p(O|\tau)p(\tau)d\tau$.
$p(\tau|O)$	The posterior policy we want to model
$p_\phi(z|\tau)$	The introduced auxiliary encoder
$q_\theta(z,\tau)$	Joint distribution of z,τ by sampling from the reparameterized policy in the environment $p(s_{t+1}|s_t,a_t)$.
$q_\theta(a_t|s_t,z)$ or $q_\theta(a_t|s_t,z_t)$	The policy to select actions at different steps
$q_\theta(z|s_1)$ or $q_\theta(z_t|s_t,z_{t-1})$	The policy to sample latent z
$p_\theta(z|\tau)$	The probability of sampling z or all z_i given τ in q_θ
$p_\theta(z|s_1)$	The marginal distribution of z in q_θ conditioning on s_1
$p_\theta(\tau)$	The marginal distribution of τ in q_θ
$p_\theta(\tau|z)$	The marginal distribution of τ conditioning on z in q_θ
R_{elbo}	The variational lower bound defined in Eq. 1
$\mathbf{f}_\theta(s_t,z,t)$	The deterministic policy function.
$h(s_t,a_t)$	The deterministic state transition function.
$q_\theta(z|\tau)$	Usually the $q_\theta(z,\tau_\theta)$ in deterministic environments
τ_θ or $\tau_\theta(z,s_1)$	In deterministic environment, the trajectory becomes a function of θ and s_1
$\nabla_\theta R_{\text{elbo}}(\tau_\theta)$	The path-wise gradient obtained from the differentiable environment

C CONNECTION WITH GENERATIVE MODELS

One can compare our approaches with other generative models. VAE defines $p_\theta(x,z) = p_\theta(x|z)p(z)$ and $q(z) = q_\phi(z|x)$ and then optimize θ, ϕ jointly to maximize the ELBO bound. By doing so, $q_\phi(z|x)$ has to align with the true posterior of $p_\theta(z|x)$.

The Expectation–maximization algorithm (EM) (Dempster et al., 1977) assumes that we have $p_\theta(x,z) = p_\theta(x|z)p_\theta(z)$ with finite z, thus we can compute the expectation $p_\theta(z|x)$ explicitly and treat it as q_ϕ, then E-step: compute $p_\theta(z|x)$ to solve $\max_\phi \log p_\theta(x) - D_{KL}(q_\phi(z|x)||p_\theta(z|x))$. M-step: fixing ϕ, find$\max_\theta E_{q_\phi}[\log p_\theta(x,z)] - E_{q_\phi}[\log q_\phi(z|x)]$ can maximize the ELBO bound.

In Maximum Entropy RL, we have $p(O,\tau) = p(O|\tau)p(\tau)$ defined by the reward, and we optimize $q_\theta(\tau|O)$ only. The ELBO bound becomes a maximum entropy term $\mathbb{E}_{\tau\sim\pi}[\log p(O|\tau) + \log p(\tau) - \log \pi(\tau)]$.

	Prior $p(z)$	Encoder $p(z|x)$	Decoder $q(z|x)$	MLE objective
VAE	$p(z)$	$p_\theta(z|x)$	$q_\phi(x|z)$	$p(x)$
EM	$p_\theta(z)$	$p_\theta(x|z)$	$\max_\phi \log p_\theta(x) - D_{KL}(q_\phi(z|x)||p_\theta(z|x))$	$p(x)$
Diffusion	$p(x_T)$	$\prod_{i=1}^T \mathcal{N}(x_t; \sqrt{1-\beta_t}x_{t-1}, \beta_t \mathbf{I})$	$\prod_{t\geq 1} p_\theta(x_{t-1}|x_t)$	$p(x_0)$
MaxEntRL	$p(\tau)$	$p(O|\tau)$	$\pi_\theta(\tau)$	$p(O)$
RPG	$p(\tau)$	$p(O|\tau)p_\phi(z|\tau)$	$q_\theta(z,\tau)$	$p(O)$

Table 1: Comparison of different algorithms that optimize ELBO bounds for inference

D IMPLEMENTATION DETAILS

The algorithm is shown in Algorithm 1.

Algorithm 1 Variational Reparameterized Policy

1: **Input:** $p_\phi, q_\theta(z, \tau)$.
2: Initialize p_ϕ, q_θ.
3: **while** time remains **do**
4:     Sample start state s_1.
5:     Sample from the latent code policy z, τ.
6:     Compute the variational lower bound R_{elbo} based Eq. 1.
7:     Update the auxiliary encoder p_ϕ to maximize R_{elbo}.
8:     Update the parameterized policy gradient q_θ to maximize R_{elbo} with Theorem 1.
9: **end while**

Table 2: Hyperparameters and rewards of our algorithms.

Hyperparameter\Env	Bandit1	Bandit 2	Move1	Move2	Move3
environment steps	1	1	8	8	50
num epoch	50	50	50	50	50
batch size	1000	1000	256	256	500
samples per epoch	50000	50000	12800	12800	25000
batch size	1000	1000	256	256	500

The learning rate (3×10^{-4}) is the same across all environments. Adam uses the exact same hyperparameter as our method except for the dimension of the latent variable is 1. REINFORCE uses the exact same hyperparameter as our method except for the dimension of the latent variable is 1 and the policy gradient is estimated using reinforce.

E   BIAS OF THE FIRST-ORDER GRADIENT ESTIMATOR

In this section, we analyze the difference between two types of policy gradient estimators, namely the Zeroth-Order (ZoBG) and First-Order (FoBG) gradient estimator (Suh et al., 2022). We establish a necessary condition for two to be equivalent when both action and parameter are 1 dimensional. From the 1D case, we also show the intractability of constructing a gradient estimator similarly to these two in higher dimensions.

Lemma 1 (Leibniz integral rule, general form). *Let $f(x, t)$ be a function such that both $f(x, t)$ and its partial derivative $\frac{\partial f(x,t)}{\partial x}$ are continuous in t and x in some region of the xt plane, including $a(x) \leq t \leq b(x)$, $x_0 \leq x \leq x_1$. Also suppose that the functions $a(x)$ and $b(x)$ are both continuous and both have continuous derivatives for $x_0 \leq x \leq x_1$. Then, for $x_0 \leq x \leq x1$*

$$\frac{d}{dx} \int_{a(x)}^{b(x)} f(x,t)dt = \int_{a(x)}^{b(x)} \frac{\partial}{\partial x} f(x,t)dt + \frac{d}{dx}b(x) \cdot f(x, b(x)) - \frac{d}{dx}a(x) \cdot f(x, a(x))$$

Lemma 2 (Jump Discontinuity, 1D version). *Let f(x, t) be a function such that both $f(x, t)$ and its partial derivative $\frac{\partial f(x,t)}{\partial x}$ are continuous in t and x in some region of the xt plane. f has jump discontinuity if and only if there exist $b_i = q_i(x)$ such that*

$$\lim_{t \to q_i(x)^-} f(x,t) \neq \lim_{t \to q_i(x)^+} f(x,t)$$

We define i to correspond the ith jump discontinuity of f. For convenience, we also abbreviate the above as $f(b_i^-) \neq f(b_i^+)$ in later parts of this section.

Corollary 1 (Leibniz integral rule, 1D region form). *Let f(x, t) be a function such that both $f(x, t)$ and its partial derivative $\frac{\partial f(x,t)}{\partial x}$ are continuous in t and x in some region of the xt plane, including*

$t \in T, T = \mathbb{R}$, $x \in X, X = \mathbb{R}$. *Also suppose that the functions $q_i(x)$ for all i are continuous and have continuous derivatives for $x \in \mathbb{R}$. Then, by Lemma 1 and 2, for $x \in X$*

$$\frac{d}{dx} \int_T f(x,t)dt = \underbrace{\int_T \frac{\partial}{\partial x} f(x,t)dt}_{\text{interior part}} + \underbrace{\sum_i \frac{\partial q_i(x)}{\partial x} \left(f(x, q_i(x)^-) - f(x, q_i(x)^+) \right)}_{\text{boundary part}}$$

For convenience, we also refer to the first term as the interior part and the second term as the boundary part in the later parts of this section.

Theorem 2 (Policy Gradient Theorem, zeroth order version). *Let $\pi_\theta(a)$ be a function such that $\pi_\theta(\cdot) \in C^0$ for all $\theta \in \mathbb{R}$ and $\pi_{(\cdot)}(a) \in C^1$ for all $a \in A$, $A = \mathbb{R}$. Let $R(a)$ be a function with jump discontinuities and defined for all $a \in A$*

$$\frac{d}{d\theta} \int_A \pi_\theta(a)R(a)da = \int_A \frac{\partial \pi_\theta(a)}{\partial \theta} R(a)da$$

holds.

Proof. Define the integrand $\pi_\theta(a)R(a) = f(\theta, a)$, by Corollary 1

$$\frac{d}{d\theta} \int_A \pi_\theta(a)R(a)da$$
$$= \int_A \frac{\partial \pi_\theta(a)}{\partial \theta} R(a)da + \sum_i \frac{\partial q_i(\theta)}{\partial \theta} \left(f(\theta, q_i(\theta)^-) - f(\theta, q_i(\theta)^+) \right)$$

Case 1: If $\pi_\theta(b_i) \neq 0$, by Lemma 2, the definition of the ith jump discontinuity can be rewritten as

$$q_i(\theta) = b_i : f(\theta, b_i^-) \neq f(\theta, b_i^+)$$
$$: \pi_\theta(b_i^-)R(b_i^-) \neq \pi_\theta(b_i^+)R(b_i^+)$$
$$: R(b_i^-) \neq R(b_i^+) \qquad\qquad \pi_\theta(\cdot) \in C^0 \text{ for all } \theta$$

, which means $q_i(\theta)$ is constant with respect to θ. $\frac{\partial q_i(\theta)}{\partial \theta} = 0$ reduces the boundary part to 0 and gives

$$\frac{d}{d\theta} \int_A \pi_\theta(a)R(a)da = \int_A \frac{\partial \pi_\theta(a)}{\partial \theta} R(a)da + 0$$

Case 2: If $\pi_\theta(b) = 0$, by Lemma 2, then $f(\theta, b) = \pi_\theta(b)R(b) = 0$, which means $f(\theta, b^-) = f(\theta, b^+) = 0$ and f does not have jump discontinuity at b. $\qquad\square$

Lemma 3 (Law of the unconscious statistician, continuous random variable). *Let x be a random variable and let $y = g(x)$ be a function of this random variable.*

$$E[g(x)] = \int_X f_X(x)g(x)dx$$

Theorem 3 (Policy Gradient Theorem, first-order version). *Let ω be a random variable such that $a = h(\theta, \omega)$ with probability distribution $p(\omega) \in C^0$ and $\frac{\partial h(\theta, \omega)}{\partial \omega} \neq 0$ for all θ. Let $f(\theta, \omega) = p(\omega)R(h(\theta, \omega))$ with the ith jump discontinuity of f defined to be $q_i(\theta)$. The first order gradient is*

$$\frac{d}{d\theta} \int_A \pi_\theta(a)R(a)da = \int_\Omega p(\omega)\frac{\partial}{\partial \theta} R(h(\theta, \omega))d\omega + \sum_i \frac{\partial q_i(\theta)}{\partial \theta} \left(f(\theta, q_i(\theta)^-) - f(\theta, q_i(\theta)^+) \right)$$

Proof. Reparameterize $a = h(\theta, \omega)$, substitute in f by definition

$$\frac{d}{d\theta} \int_A \pi_\theta(a)R(a)da = \frac{d}{d\theta} \int_\Omega p(\omega)R(h(\theta, \omega))d\omega = \frac{d}{d\theta} \int_\Omega f(\theta, \omega)d\omega$$

By Lemma 2 the definition of the ith jump discontinuity can be rewritten as

$$q_i(\theta) = b_i : f(\theta, b_i^-) \neq f(\theta, b_i^+)$$
$$: p(b_i^-)R(h(\theta, b_i^-)) \neq p(b_i^+)R(h(\theta, b_i^+))$$
$$: R(h(\theta, b_i^-)) \neq R(h(\theta, b_i^+)) \qquad\qquad p(\omega) \in C^0$$

[the following is not the proof of the theorem.] Suppose $\omega \sim \mathcal{N}(0, \sigma)$, $h(\theta, \omega) = \theta + \sigma\omega$ and exist action $a_i = h(\theta, b_i)$ such that $R(a_i^-) \neq R(a_i^+)$, the definition of $q_i(\theta)$ and its evaluation at a local neighbour $q_i(\theta + \Delta\theta)$ can be rewritten as

$$q_i(\theta) = b_i : h(\theta, b_i) = a_i$$
$$q_i(\theta + \Delta\theta) = b_i^\Delta : h(\theta + \Delta\theta, b_i^\Delta) = a_i$$

since function R is not parameterized, the location of its ith jump discontinuity is a_i and does not change. Therefore, substitute in $h(\theta, \omega) = \theta + \sigma\omega$ and solve for b_i and b_i^Δ gives $b_i = (a_i - \theta)/\sigma$ and $b_i^\Delta = (a_i - (\theta + \Delta\theta))/\sigma$. Differentiate $q_i(\theta)$ gives

$$\frac{dq_i(\theta)}{d\theta} = \lim_{\Delta\theta \to 0} \frac{q_i(\theta + \Delta\theta) - q_i(\theta)}{\Delta\theta}$$
$$= \lim_{\Delta\theta \to 0} \frac{b_i^\Delta - b_i}{\Delta\theta}$$
$$= \lim_{\Delta\theta \to 0} \frac{\Delta\theta/\sigma}{\Delta\theta}$$
$$= \frac{1}{\sigma} \neq 0$$

In general, ignoring the boundary term when estimating the left-hand side with a first-order estimator leads to a bias due to the discontinuity of the reward/value function. □

Therefore, we have shown that a gradient estimator for only the interior part of the first-order gradient is a biased estimator of the original policy gradient. The bias is the boundary term.

F   PROOF OF THE REPARAMETERIZED POLICY GRADIENT THEOREM

F.1   REGULARITY CONDITIONS

Let $\theta \in \Theta = (-\epsilon, \epsilon) \in \mathbb{R}$ without loss of generality and $\Omega = \{z \in \mathcal{Z} | q_\theta(z, \tau_\theta) > 0\}$ be a measure space, then for $z \in \Omega, \theta \in [-\epsilon, \epsilon]$, we make the following assumptions

Assumption 1 (Bounded ELBO). *The reward R, prior density* $\log p(\tau), \log q_\theta(z|\tau), \log p_\phi(z|\tau)$ *are bounded for all* τ.

Assumption 2 (Lipschitz Condition). $q_\theta(z|\tau)$, $\log q_\theta(z|\tau), \log p_\phi(z|\tau)$, *prior distribution* $\log p(\tau)$, *action policy* $\mathbf{f}_\theta(s_t, z, t)$, *reward R and dynamics* $h(a_t, s_t)$ *are Lipschitz continuous w.r.t. any* s, a *and continuous* z. *In addition,* q_θ *is Lipschitz continuous w.r.t.* θ.

Assumption 3 (Lebesgue-integrable). *The probability density* $q_\theta(z, \tau_\theta)$ *and its derivative* $|\nabla_\theta q_\theta(z, \tau_\theta)|$ *is Lebesgue-integrable jointly over* Ω *and their integration is bounded for all* $\theta \in [-\epsilon, \epsilon]$.

Assumption 1 is easy to guarantee when the state space and the action space are compact and the time horizon T is finite because continuous functions on a compact set are always bounded. Similarly, for bounded inputs, the common neural networks can also satisfy Assumption 2. Otherwise, we can simply clamp them before feeding them into a neural network to make the input bounded, as we do not need the network and the environment to be continuously differentiable as in Lemma 1 but only absolutely continuous. We require the dynamics $h(a_t, s_t)$ to be Lipschitz continuous, ruling out chaotic systems.

Assumption 3 holds for common distributions. For example, given a Gaussian distribution $p(z) = e^{(-z^2/(2\sigma^2))}/(\sqrt{2\pi}\sigma)$, the parameter σ's partial derivative $\frac{\partial p}{\partial \sigma}(z) = e^{(-z^2/(2\sigma^2))}(-\sigma^2 +$

$z^2)/(\sqrt{2\pi}\sigma^4)$ is simply a function of exponential family and can be verified to be absolutely integrable on $\mathbb{R}$ and bounded for any domain $\sigma \in [a, b], a, b > 0$.

F.2 PROOF

To differentiate under integration, we use the following Flanders (1973),

Lemma 4 (Leibniz integral rule). *Let X be an open subset of $\mathbb{R}$, and Ω be a measure space. Suppose that a function $f : X \times \Omega \to \mathbb{R}$ satisfies the following conditions:*

1. *$f(x, \omega)$ is a measurable function of x and ω jointly and is integrable over ω for almost all $x \in X$ fixed.*

2. *For almost all $\omega \in \Omega$, $f(x, \omega)$ is an absolutely continuous function of x (the derivative $\partial f(x, \omega)/\partial x$ exists almost everywhere).*

3. *$\partial f / \partial x$ is "locally integrable", that is, for all compact intevals $[a, b] \in X$,*

$$\int_a^b \int_\Omega \left| \frac{\partial}{\partial x} f(x, \omega) \right| d\omega dx < \infty.$$

Then for almost every $x \in X$, its derivative exists and

$$\frac{d}{dx} \int_\Omega f(x, \omega) d\omega = \int_\Omega \frac{\partial}{\partial x} f(x, \omega) d\omega$$

Then it is easy to prove Theorem 1.

Proof. Define the measurable function $f(\theta, z) = q_\theta(z, \tau_\theta) R_{\text{elbo}}(\tau_\theta)$.

Since $R_{\text{elbo}}(\tau_\theta)$ is bounded by a constant M by Assumption 1 and $q_\theta(z, \tau_\theta)$ is positive and Lebesgue-integrable by Assumption 3, their product's absolute value will be bounded by $q_\theta(z, \tau_\theta) M$, so $f(\theta, z)$ becomes Lebesgue-integrable for every θ.

By Assumption 2 and assuming the horizon is finite, the trajectory τ will become a Lipschitz function with respect to θ and z, so as $R_{\text{elbo}}(\tau_\theta)$, $q_\theta(z, \tau_\theta)$ and their products $f(\theta, z)$. Thus $\frac{\partial f(\theta, z)}{\partial \theta}$ exists almost everywhere for all $z \in \Omega$.

To bound its derivative, let $R_{\text{elbo}}(\tau_\theta)$ be L-Lipschitz w.r.t. θ, notice that

$$|\nabla_\theta f(\theta, z)| = |R_{\text{elbo}}(\tau_\theta) \nabla_\theta q_\theta(z, \tau_\theta) + q_\theta(z, \tau_\theta) \nabla_\theta R_{\text{elbo}}(\tau_\theta)| \leq M |\nabla_\theta q_\theta(z, \tau_\theta)| + L |q_\theta(z, \tau_\theta)|,$$

is dominated by the sum of two Lebesgue-integrable functions whose integration is bounded for all $\theta \in \Theta$ by Assumption 3. Thus its gradient must be locally integrable. Then applying Lemma 4, we can do differentiation under the integration sign, and finish the proof as

$$\begin{aligned}
\nabla_\theta E[R_{\text{elbo}}(\tau_\theta)] &= \int_z \nabla_\theta \left(q_\theta(z, \tau_\theta) R_{\text{elbo}}(\tau_\theta) \right) dz \\
&= \int_z R_{\text{elbo}}(\tau_\theta) \nabla_\theta q_\theta(z, \tau_\theta)(z|s_1) + q_\theta(z, \tau_\theta) \nabla_\theta R_{\text{elbo}}(\tau_\theta) dz \\
&= \int_z q_\theta(z, \tau_\theta) \left[R_{\text{elbo}}(\tau_\theta) \nabla_\theta \log q_\theta(z, \tau_\theta) + \nabla_\theta R_{\text{elbo}}(\tau_\theta) \right] dz.
\end{aligned}$$

$\square$