Reward-Adaptive Iterative Discovery: A Case Study on Automated Game Testing for NHL26

Florian Fuchs[*]**, Jessy Gosselin-Grant, Boris Skuin, Michele Petteni, Alessandro Sestini, Joakim Bergdahl, Amir Baghi, Linus Gisslén**[*]

{ffuchs, lgisslen}@ea.com

Electronic Arts (EA)
[*]Corresponding authors

Abstract

Testing is a major effort for the gaming industry, requiring a significant part of development budget and people power. We present a case study on a development version of the ice hockey game *EA SPORTS NHL 26*, for which human playtesters test the goalie AI for behavioral exploits. To reduce the effort of re-testing the goalie AI after every game or behavior modification in the development phase, we propose Reward-Adaptive Iterative Discovery (RAID), a novel approach to automatically find exploits using an iterative Reinforcement Learning (RL) approach that trains a population of goal scoring agents. While previous approaches can already successfully find exploits, RL algorithms tend to overfit to a single solution. We introduce a simple extension on top of existing RL algorithms, such that they find multiple diverse high-quality solutions. For our first deployment of this approach, within a single experiment we were able to find six hockey scoring exploit strategies that were qualitatively similar to those that playtesters had found in hours-long manual testing sessions.

Supplementary Video This paper is accompanied by videos of the agents trained with our algorithm, RAID: go.ea.com/RAID

1 Introduction

With game worlds becoming vaster and game systems becoming more complex, the effort to test games grows likewise. To reduce repetitive aspects of game testing, prior work has investigated automating parts of it through the use of autonomous agents playing a game and reporting bugs (Ariyurek et al., 2019; De Woillemont et al., 2022; Bergdahl et al., 2020). While Reinforcement Learning (RL) agents can find individual exploits within a game (Baker et al., 2019), they tend to converge to one single "best" solution of solving a task. In this paper, we use *EA SPORTS NHL 26* (short NHL) as our test-case. In particular, we aim to test the goalie AI of the game, training a forward agent to find high chance scoring strategies, which could represent potential exploits. Our results indicate that standard RL algorithms tend to collapse to a small set of high-reward behaviors, rather than exploring a larger, more diverse set. Thus, exploit discovery becomes sequential: developers must fix one issue before retraining the agent to find others. Since this slows down the exploit finding process, we aim to develop an algorithm that can find multiple potential exploits without human intervention.

Prior work on RL for game testing has proposed methods to increase coverage of a game environment (Gordillo et al., 2021; Sestini et al., 2022). However, the added bias towards exploration comes at the cost of a loss in optimality with respect to the original goal of the agent. For our use case, we are explicitly looking for high-performing scoring strategies and we therefore require a method that

Figure 1: **Left: Last frame before the goal of first 3 scoring strategies learned by agents trained with RAID.** The controlled forward player wears blue, the goalie white. The strategies are learned in an iterative fashion, with a reward function enforcing each new strategy's shot position to be at least 2 meters away from all previous strategies using the same shot type. Numbers indicate the algorithm iteration. Colors indicate the shot type. **Right: Shot locations and types of strategies found by first 4 iterations of RAID.** Small dots represent shot location and type of 100 goals after convergence of each iteration. Large circles represent 2 meter radius around average position of those goals inside which no reward is given for all succeeding iterations of RAID if scoring with the same shot type. Shots by the agent of iteration 3 are for example outside of the 2 meter radius of iteration 1, since the two agents use the same shot type.

achieves high performance with respect to the scoring chance, while also finding multiple diverse solutions without human intervention.

The field of quality diversity investigates how to find multiple diverse solution that are high-performing (Zahavy et al., 2023). While they have reported impressive results, existing solutions are often brittle in complex domains, one reason being a moving diversity target learned in parallel to the policies (Leon et al., 2024). We aim for playtesters to independently use our tool and therefore want the tool to be as simple as possible to require little RL expertise.

Following these requirements, we propose Reward-Adaptive Iterative Discovery (RAID), an approach to find a set of high-quality, diverse solutions by iteratively training a population of agents. Figure 1 shows a brief overview of the results of the approach. We enforce diversity through not rewarding agents for strategies that are similar to those found by any previously trained agent. By measuring diversity over sequentially trained agents, leaving the diversity measure fixed during an individual agent's training time, we increase robustness compared to previous work. We define diversity in an intuitive, domain-specific way, such that the diversity measure can be interpreted and adjusted by non-RL practitioners, facilitating the use by playtesters to extend their toolset.

2 Related Work

We present related work in two research directions connected to our approach: (1) automated playtesting, specifically approaches based on reinforcement learning, and (2) the field of behavior diversity, which motivates our approach.

2.1 Automated Playtesting

Contrary to recent work that apply reinforcement learning to train agents to master a game and surpass human players (Vinyals et al., 2019; Wurman et al., 2022), research on automated playtesting is generally less concerned with maximizing the same success metrics as human players, and more focused on having agents play a game in various ways that reveal insights on potential issues in the game. One direction for this is to maximize the coverage of states an agent visits in a game. A notable example is the work by Gordillo et al. (2021), that uses a count-based exploration reward scheme to promote visitation of less seen states in a game map. Another direction aims to train agents that play games with behavior similar to human players, for example to visualize the interactions a game designer can expect from users or to balance the effectiveness of different strategies within a

game (Holmgård et al., 2019; De Woillemont et al., 2022; Devlin et al., 2021). Sestini et al. (2022) combine both directions by exploring strategies similar to those of human players with an additional intrinsic reward for exploring new states.

While prior work achieves good results in terms of game state coverage and player-like behavior, we aim to investigate exploits that are closely tied to high performance with respect to the original human success metric of a game, in our case scoring goals with a high percentage in a hockey game. We therefore aim to develop an approach to increase the diversity in behaviors of the trained agents while preserving the performance with respect to the game's success metric as much as possible.

2.2 Diversity

The field of quality diversity aims to generate diverse populations of high-performing solutions through evolutionary algorithms (Lehman & Stanley, 2011; Mouret & Clune, 2015; Cully et al., 2015). More recent work brings the concept of diversity into the field of reinforcement learning through intrinsic rewards. The work by Gregor et al. (2017), for example, introduces an intrinsic reward based on optimizing the mutual information between options – i.e. closed-loop policies for taking action over a period of time – and the options' final states, using entropy optimization to maximize diversity across options and distinction of individual options. Similarly Eysenbach et al. (2019) optimize diversity over all visited states and show that this form of unsupervised discovery can serve as an effective pretraining mechanism for reinforcement learning. DOMiNO defines diversity in the space of state-action occupancy (Zahavy et al., 2023), represented by successor features (Barreto et al., 2017). It combines the intrinsic diversity reward and an extrinsic reward specific to the environment with Lagrange multipliers to control the trade off between diversity and optimality with respect to the extrinsic reward. While DOMiNO can train multiple diverse agents in parallel this way, Leon et al. (2024) highlight that the approach fails to learn diverse behaviors in complex domains and can suffer from instability due to the approach learning the successor feature representations in parallel to the agents' policies.

Due to this instability and our aim for a stable algorithm that can be used by non-RL practitioners, we train a group of agents in a simple, sequential fashion, by masking strategies similar to those found by a prior agent from the reward function of all subsequent agents. The diversity measurement introduced by this method of reward masking is static for a specific agent within a single training iteration and not any more complex in practice than simple static reward shaping in standard reinforcement learning (Ng et al., 1999). Similar to prior work by Gregor et al. (2017), we define diversity in terms of the final state of an agent. Rather than maximizing the distance between states, we however introduce diversity via hard constraints on state difference, enforced through reward masking of prior behaviors. This allows users of RAID to easily update the algorithm to their desired level of diversity, for example in the later introduced diversity criterion for NHL by increasing the area used for the shot similarity criterion to a $4\,\mathrm{m}$ radius. In comparison, the diversity hyperparameters of prior work, for example relative to the maximum achievable reward in the work by Zahavy et al. (2023), are significantly harder to interpret, especially for non-RL practitioners.

3 Methodology

Our goal is to create an RL-based approach to autonomously find multiple diverse, high chance scoring strategies for the NHL environment without any human intervention in between iterations. We first outline the base RL setup to find a single exploit within the NHL environment. We then describe RAID, a novel approach to satisfy the posed requirements. For the foundations of reinforcement learning, such as the concepts of reward, policy, and Q-value function, we refer the reader to the work by Sutton & Barto (2018).

3.1 Base RL Setup

Action Space. We aim to train a hockey forward player agent that learns high chance scoring strategies in a one-versus-goalie setting, similar to those that a human player could find by exploiting weaknesses in the goalie AI system. To make sure that the found strategies are executable by a human, we provide the agent with a selection of the same actions available to human players on a game controller:

- Discrete actions: the 4 face buttons and the left trigger button that execute so-called *dekes*, i.e., decoy movements to draw the goalie out of position.
- Continuous actions: the two sticks for player skating and hockey stick control, each represented by continuous x and y axes.

Through the use of those actions, the agent can perform different kinds of shot types – backhand, wrist shot, etc. – which we will later consider for defining shot diversity. Furthermore, we only let the agent act every 5 frames and smooth the stick actions using an exponential moving average with a smoothing factor of 0.2, to make sure that the agent does not leverage any super-human movement capability or reaction time.

Observation Space. We provide the agent with the normalized position, velocity, and orientation of puck, net, and goalie relative to the agent, as well as a stack of the 8 last performed actions.

Reward Function. We reward the agent for every goal. To simplify learning, we additionally include shaping rewards for the puck getting closer to the goal, as well as for the scoring chance of every shot taken, based on an NHL-internal calculation.

Algorithm & Architecture. While from an interface perspective all RL algorithms that use a reward function are technically compatible with RAID, RAID's effectiveness depends on the base algorithm's ability to explore various strategies – even when previously found strategies are no longer rewarded – before converging to the best one. We therefore use Soft Actor-Critic (Haarnoja et al., 2018), since it features a robust exploration mechanism through entropy maximization, exploring more in less known states. Furthermore, Soft Actor-Critic has a high sample efficiency, which is crucial for environments with slow data generation, such as full-scale games. To support both discrete and continuous actions, we use the architecture described by Delalleau et al. (2019) for 2 Q-value functions, as well as a mixed-action policy, each with 5 hidden layers with 512 units, allowing for a maximum of one discrete action at a time. When we use the term *agent*, we refer to both the policy and Q-value functions used for training and inference. For efficient training, we stop training once an agent either reaches a 90% scoring chance or does not improve its performance for 50k training steps.

3.2 Reward-Adaptive Iterative Discovery

We outline the general, domain-agnostic RAID method as a pseudo algorithm in Algorithm 1. The algorithm extends a standard reinforcement learning setup by training multiple agents sequentially, aiming for each agent to come up with a new strategy for maximizing the reward of the environment. For NHL we define a strategy z as the shot type and shot position at the end of an episode, the shot position meaning the last position of the puck before the puck is shot or, if the puck is not shot, the last puck position before a goal. We start by training a first agent with a standard reinforcement learning setup. After training of the first agent converges, we evaluate the agent to capture the strategy of its highest performing checkpoint. For the NHL game, we evaluate the agent until it scores 100 goals and describe the strategy z as the average shot position and the most common shot type over those 100 goals. We store this strategy in a list of previous strategies Z_{prev}. We then continue sequentially, training each next agent the same way, but for each new iteration modify the reward function to not reward strategies similar to those found by any previous agent. Based on feedback from the NHL development team, we define $\texttt{similar}(z, Z_{\text{prev}})$ as the shot position of a

---

Algorithm 1 Reward-Adaptive Iterative Discovery

    Input: N, Z_{prev} $\triangleright$ Z_{prev}: previous strategies, can be $\emptyset$ or warm-started

    Output: Z_{prev}

    for $i = 1$ to N **do**

         $r_i(z) \leftarrow r_{\text{base}}(z)$ IF !`similar`(z, Z_{prev}) ELSE 0 $\triangleright$ z: strategy, $r(z)$: reward function

         Initialize agent π_i

         while NOT `converged`(π_i) **do**

             `train`(π_i, r_i)

         end while

         $z_i \leftarrow$ `evaluate`(π_i)

         $Z_{\text{prev}} = Z_{\text{prev}} \cup \{z_i\}$

    end for

---

strategy being within a $2\,\text{m}$ radius of a previous strategy that used the same shot type, i.e. a strategy z is considered novel or sufficiently diverse with respect to a set of existing strategies Z_{prev} if:

$$\forall z' \in Z_{\text{prev}} \quad z_{\text{shottype}} \neq z'_{\text{shottype}} \vee l^2(z_{\text{shotpos}}, z'_{\text{shotpos}}) > 2\,\text{m}.$$

For NHL, we skip adding strategies with a scoring chance of less than 10% after convergence, since we are interested in high-performing strategies and convergence at this low performance potentially indicates that the algorithm got stuck in a local optimum, meaning that future iterations starting with a different random seed could potentially find more performant solutions for the same shot position and type. For NHL, we use the details from Section 3.1 for the base reward function, training algorithm, and convergence criterion.

While the definition of strategy similarity is highly domain specific, we argue that this is exactly what makes the method suitable for game development. While previous work defines diversity in a more general way that can be used across domains, for example via successor features (Zahavy et al., 2023), we argue this makes it significantly harder for a playtester without RL knowledge to tune diversity to a level fitting their domain, given that the work by Zahavy et al. (2023), for example, requires the diversity level to be expressed with respect to the maximum achievable reward. Furthermore, having an explicit list of previous strategies allows playtesters to warm start training using a list of manually defined strategies, instead of an empty set, for example using high scoring strategies that are known and desired by the game, or exploits that are known but the game studio could not fix yet.

4 Experiments

We compare RAID to a naive baseline to demonstrate the diversity in strategies found by the approach. This is most notably supported by RAID finding 6 exploit strategies that were previously also found by human playtesters, but had not been fixed on the outdated version of the game that we conducted the experiments on. We furthermore test the limitations of the algorithm with respect to the number of high chance scoring strategies it finds before failing to find any new strategies.

4.1 Experimental Setup

We run all experiments on a single PC with an *NVIDIA GeForce RTX 4090* GPU and an *AMD Ryzen Threadripper PRO 7975WX* CPU. We use a pre-release development version of *EA SPORTS NHL 26*, additionally reducing rendering to a minimum to speed up the simulation. The simulation includes a single goalie, controlled by the game's AI we want to test, as well as a forward player, controlled by RL. For both training and evaluation we slightly vary the initial position of the forward around the centerline to make the approach more robust to variations in the setup and to help with exploration.

Figure 2: The average shot position and most common shot type after convergence for 20 independent repetitions of the baseline experiment, as well as two experiments using RAID started with different random seeds ran for 10 iterations each. The color represents the most common shot type of an agent and the number represents the iteration of the algorithm that leads to the shot strategy. The naive baseline shows that a standard reinforcement learning algorithm keeps finding the same small set of solutions when repeated multiple times, with the algorithm finding 9 snapshot strategies and 11 backhand strategies, all from similar positions. The two experiments using RAID not only find the two strategies found by the baseline, but additionally also find 8 more strategies that adhere to our definition of diversity, maintaining a distance of at least $2\,\mathrm{m}$ between shot strategies that use the same shot type.

4.2 Naive Baseline

As a baseline, we run the base RL setup from Section 3.1 for 20 independent iterations, each with a different random seed, changing the initialization of the policy and value networks, as well as the random states of the game environment. Each iteration uses the full reward function, assigning rewards for all goals, independent of shot position or type, without masking previous strategies. The experiments take between $16\,\mathrm{min}$ and $152\,\mathrm{min}$ to converge. RL algorithms aim to find the best solution to a problem with respect to a reward function. In environments with a set of clearly superior strategies, returning a higher reward, an optimal algorithm therefore always converges to this same set of solutions, if not otherwise incentivized. The left of Figure 2 shows how all of the 20 independent iterations end up with either one of two patterns, a snapshot from the left side of the goal or a backhand shot from the right side.

Assuming that a playtester classifies the found strategies as unwanted exploits, they have to improve the goalie AI behavior to mitigate those exploits before the baseline approach is likely to find any additional ones. The naive RL approach therefore adds considerable overhead to the exploit finding process by requiring human intervention between iterations. If on the contrary the playtester considers the found strategies to be a desired way of scoring in the game, they would need to find a way for the reward function to distinguish between exploits and desired scoring strategies, such that the agent ignores the desired strategies and finds novel exploits. Exploits are highly unique in their appearance and therefore hard to define before first seeing them.

4.3 Reward-Adaptive Iterative Discovery

We run RAID starting with two different initial random seeds, influencing the random initialization of the agents of all iterations, for $N = 30$ and $N = 10$ iterations respectively. The 30 iteration experiment takes $48\,\mathrm{h}$ and the 10 iteration experiment takes $14\,\mathrm{h}$ for all iterations to converge. Figure 2 shows how the strategies found by RAID adhere to the diversity criteria we set for NHL: while the average shot positions of strategies with the same shot type are all at least $2\,\mathrm{m}$ away from each other, for example the three backhand shot strategies in green for seed 1, the algorithm still finds strategies with close shot position but different shot types, e.g. strategies 8 and 2 for seed 1, sharing

Figure 3: Movement of the agents of a hand-picked selection of iterations of seed 1 of RAID for 10 different random starting positions each. This demonstrates that while diversity is only defined in terms of shot type and position of the shot, the positions before the shot, are also implicitly impacted to create a high scoring chance. For example, while iterations 12 and 13 have almost the same shot position, they approach the position from the opposite side to facilitate different shot types.

almost the same position. This way the algorithm finds a set of diverse strategies without any human intervention in between iterations to fix prior exploits, as would be required for the naive baseline.

As an illustrative example of the usefulness of RAID for playtesting, when we ran RAID for the first time and presented the results to the development team, 6 of the found strategies matched with exploits previously found by human playtesters. Since we did however use an outdated version of the game for our experiments, those exploits were still available for the agents to find. This shows that the agents are able to find exploits qualitatively similar to those found by human playtesters, while only requiring human supervision after the algorithm has found a set of candidates for a human expert to review. To not reveal any information that allows players to further exploit game mechanisms, we do not reveal which of the found strategies match with those deemed exploits.

Pre-shot Diversity. Figure 3 shows 10 trajectories each for a selection of iterations of seed 1 of RAID. While we only define diversity in terms of shot position and type, the visualized trajectories demonstrate how this diversity definition implicitly generates diversity in states before the shot as well. This shows that the agents take into account player direction, as well as orientation and stick position, which are visible in the supplementary videos, when learning scoring strategies. While trajectories found by iterations 12 and 13, for example, have similar shot positions, they require significantly different skating trajectories to score with their respective shot types, backhand and snapshot.

No-shot Goals. To our surprise, the agent also finds strategies to score without shooting, marked in dark blue in Figure 2 and visible in the supplementary video. This initially led to a bug in our setup, since previous shot strategies were only recorded when the agent actually shot the puck. This further underlines the difficulty of defining exploits before first seeing them, outlined in Section 4.2.

Re-testing after Behavior Update. While most of the strategies found in seed 1 and seed 2 resemble each other, they appear in different order and do not match completely – for instance, strategies found in iteration 8 of seed 1 and iteration 8 of seed 2 are not found by the other seed. RL algorithms have a high variance in their exploration process and therefore converge to different solutions given the existence of multiple similarly performant solutions, as we also demonstrate with the two dominant solutions the naive baseline finds. This however means that if a playtester attempts to fix an exploit found by a first run of RAID, the same exploit not appearing in a second run of RAID after the fix is not a sufficient guarantee that the fix was successful. Similarly, the policies trained in the first run can not be used for this purpose, since RL is highly overfitting to the

Figure 4: Training progress of seed 1 of RAID running for 30 iterations, represented by the goal rate of the agents during training episodes. For this figure, we smooth the goal rate using a maximum over 50 neighbors to maintain information on whether an iteration reaches the goal rate threshold of 10% at any point in training. The coloring shows that later iterations of RAID, which are represented in brighter colors, are less likely to discover high chance scoring strategies, because most of those strategies were already found by previous iterations, represented in darker colors.

exact dynamics of the environment and can therefore be easily thrown off by slight changes in the goalie's behavior, without proving that the exploit is fixed. Playtesters therefore still have to validate that an exploit is indeed fixed by imitating the strategy found by the approach before the fix.

Iteration Limit. Figure 4 shows the training progress of the 30 iterations of seed 1. The first 10 iterations all reach performances above the 10% goal rate cut-off criterion before triggering any of the early stopping criteria. The longer the experiment goes on, the more iterations do not make the cut, with iterations 11, 15, 17, 20, 21, $23 - 25$ and $27 - 29$ all converging at goal rates below the threshold and therefore not being added to the previous strategies list (Z_{prev}). We manually stop the search after 30 iterations, since we only find 3 valid strategies in the last 11 iterations, reducing the likelihood of discovering further interesting strategies in practical time. More generally, limit allows for a trade-off between run time and the expected number of diverse solutions found, with the optimal choice being highly domain-specific and dependent on the diversity criterion. In NHL for example, if we did not differentiate the shot type and only used the position as discriminative feature, we would expect to find less solutions over all, reducing the optimal search time.

Multimodality of shot distribution

Figure 5 shows the shot position of 100 goals after training converged for the 8th iteration of seed 2. Around one third of all shot positions lie outside of the $2\,\text{m}$ radius around the average of all shot positions, meaning that in succeeding training iterations of RAID the exact same shots will still be rewarded. This highlights a potentially bigger problem around the introduced diversity criterion for NHL: in a more extreme hypothetical case, a single agent can learn to shoot from two positions that are more than 4 meters apart, going for either of the two shot positions at a rate of 50% depending on where the agent is spawned. This way, most of the shots of the agent could be outside of the $2\,\text{m}$ radius around the average of the shots' positions, meaning that future iterations could still learn the exact same behavior without it being excluded. This motivates further investigations into more elaborate representations of a policy's strategy, for example through clustering methods such as k-means (McQueen, 1967).

Figure 5: 100 shot positions of the agent in iteration 8 of seed 2 of RAID, as well as the average of those shot positions. In succeeding iterations, shots within 2 m of that average position are no longer rewarded if they use the same shot type as the most common shot type among those 100 shots. The agent learns a bi-modal behavior, shooting from either one of two shot positions depending on its spawn position. This leads to around 1/3 of shots not being within the radius. Succeeding iterations of the algorithm are therefore still rewarded for shots similar to this part of the behavior, meaning that the exclusion mechanism based on the radius around the average does not completely exclude this scoring strategy.

5 Conclusion, Limitations, and Future Work

We introduce Reward-Adaptive Iterative Discovery, a method to find multiple diverse high chance scoring strategies without human intervention in between iterations. The algorithm extends a standard reinforcement learning setup by training multiple agents sequentially, aiming for each agent to come up with a new strategy by not rewarding agents for strategies similar to those of previous iterations. As a domain expert's review of the learned strategies shows, RAID finds exploits similar to those identified by human playtesters. We furthermore argue that defining diversity with respect to NHL allows game testers to better follow and adjust the method, compared to prior work that requires RL expertise to interpret the hyperparameters for tuning diversity.

Limitations.   While our method finds potential exploits autonomously, it still requires human supervision post training, since telling high chance scoring strategies intended by game designers and actual exploits apart is not covered by the method. Furthermore, due to the high variance in RL's exploration process, our method is not sufficient to determine whether a found exploit has been fixed successfully by an engineer, relying on playtesters for this verification task. Our method's runtime grows (at least) linearly with the number of strategies we aim to find. While previous work trains multiple diverse behaviors in parallel (Zahavy et al., 2023), we deliberately forego this option to keep our method simple and therefore facilitate its use by playtesters not familiar with RL.

Future Work.   We design parts of the RAID method specifically for the use on NHL, though the base idea outlined in Algorithm 1 could be applicable to other domains as well. While diversity is somewhat intuitive to define for the domain of scoring goals in NHL, future work could research how diversity can be defined in more complex domains, including multiplayer scenarios or even agents outputting text as actions. While previous work that defines diversity in a domain-agnostic way often requires RL knowledge to interpret and adjust hyperparameters, it would be interesting to research definitions of diversity that are domain-agnostic but still interpretable by non-RL practitioners, for example by defining the minimum distance of trajectories used in RAID in a more general way.

References

Sinan Ariyurek, Aysu Betin-Can, and Elif Surer. Automated video game testing using synthetic and humanlike agents. *IEEE Transactions on Games*, 13(1):50–67, 2019.

Bowen Baker, Ingmar Kanitscheider, Todor Markov, Yi Wu, Glenn Powell, Bob McGrew, and Igor Mordatch. Emergent tool use from multi-agent autocurricula. In *International conference on learning representations*, 2019.

André Barreto, Will Dabney, Rémi Munos, Jonathan J Hunt, Tom Schaul, Hado P Van Hasselt, and David Silver. Successor features for transfer in reinforcement learning. *Advances in neural information processing systems*, 30, 2017.

Joakim Bergdahl, Camilo Gordillo, Konrad Tollmar, and Linus Gisslén. Augmenting automated game testing with deep reinforcement learning. In *2020 IEEE Conference on Games (CoG)*, pp. 600–603. IEEE, 2020.

Antoine Cully, Jeff Clune, Danesh Tarapore, and Jean-Baptiste Mouret. Robots that can adapt like animals. *Nature*, 521(7553):503–507, 2015.

Pierre Le Pelletier De Woillemont, Rémi Labory, and Vincent Corruble. Automated play-testing through rl based human-like play-styles generation. In *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment*, volume 18, pp. 146–154, 2022.

Olivier Delalleau, Maxim Peter, Eloi Alonso, and Adrien Logut. Discrete and continuous action representation for practical rl in video games. *arXiv preprint arXiv:1912.11077*, 2019.

Sam Devlin, Raluca Georgescu, Ida Momennejad, Jaroslaw Rzepecki, Evelyn Zuniga, Gavin Costello, Guy Leroy, Ali Shaw, and Katja Hofmann. Navigation turing test (ntt): Learning to evaluate human-like navigation. In *International Conference on Machine Learning*, pp. 2644–2653. PMLR, 2021.

Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=SJx63jRqFm.

Camilo Gordillo, Joakim Bergdahl, Konrad Tollmar, and Linus Gisslén. Improving playtesting coverage via curiosity driven reinforcement learning agents. In *2021 IEEE Conference on Games (CoG)*, pp. 1–8. IEEE, 2021.

Karol Gregor, Danilo Jimenez Rezende, and Daan Wierstra. Variational intrinsic control. *International Conference on Learning Representations, Workshop Track*, 2017.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pp. 1861–1870. Pmlr, 2018.

Christoffer Holmgård, Michael Cerny Green, Antonios Liapis, and Julian Togelius. Automated playtesting with procedural personas through mcts with evolved heuristics. *IEEE Transactions on Games*, 11(4):352–362, 2019. DOI: 10.1109/TG.2018.2808198.

Joel Lehman and Kenneth O. Stanley. Evolving a diversity of virtual creatures through novelty search and local competition. In *Proceedings of the 13th Annual Conference on Genetic and Evolutionary Computation*, GECCO '11, pp. 211–218, 2011. ISBN 9781450305570. DOI: 10.1145/2001576.2001606. URL https://doi.org/10.1145/2001576.2001606.

Borja G Leon, Francesco Riccio, Kaushik Subramanian, Peter R Wurman, and Peter Stone. Discovering creative behaviors through duplex: Diverse universal features for policy exploration. *Advances in Neural Information Processing Systems*, 37:49625–49648, 2024.

James B McQueen. Some methods of classification and analysis of multivariate observations. In *Proc. of 5th Berkeley Symposium on Math. Stat. and Prob.*, pp. 281–297, 1967.

Jean-Baptiste Mouret and Jeff Clune. Illuminating search spaces by mapping elites. *arXiv preprint arXiv:1504.04909*, 2015.

Andrew Y Ng, Daishi Harada, and Stuart Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *Icml*, volume 99, pp. 278–287. Citeseer, 1999.

Alessandro Sestini, Linus Gisslén, Joakim Bergdahl, Konrad Tollmar, and Andrew David Bagdanov. Automated gameplay testing and validation with curiosity-conditioned proximal trajectories. *IEEE Transactions on Games*, 16(1):113–126, 2022.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. The MIT Press, second edition, 2018. URL http://incompleteideas.net/book/the-book-2nd.html.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *nature*, 575(7782):350–354, 2019.

Peter R Wurman, Samuel Barrett, Kenta Kawamoto, James MacGlashan, Kaushik Subramanian, Thomas J Walsh, Roberto Capobianco, Alisa Devlic, Franziska Eckert, Florian Fuchs, et al. Outracing champion gran turismo drivers with deep reinforcement learning. *Nature*, 602(7896):223–228, 2022.

Tom Zahavy, Yannick Schroecker, Feryal Behbahani, Kate Baumli, Sebastian Flennerhag, Shaobo Hou, and Satinder Singh. Discovering policies with DOMiNO: Diversity optimization maintaining near optimality. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=kjkdzBW3b8p.