Coresets for Relational Data and The Applications

Abstract

A coreset is a small set that can approximately preserve the structure of the original input data set. Therefore we can run our algorithm on a coreset so as to reduce the total computational complexity. Conventional coreset techniques assume that the input data set is available to process explicitly. However, this assumption may not hold in real-world scenarios. In this paper, we consider the problem of coresets construction over relational data. Namely, the data is decoupled into several relational tables, and it is expensive to directly materialize the data matrix by joining the tables. We propose a novel approach called "aggregation tree with pseudo-cube" that can build a coreset from bottom to up. Moreover, our approach can neatly circumvent several troublesome issues of relational learning problems [Khamis et al., PODS 2019]. Under some mild assumptions, we show that our coreset approach can be applied for the machine learning tasks, such as clustering, logistic regression and SVM.

1 Introduction

As the rapid development of information technologies, we are often confronted with large-scale data in many practical scenarios. To reduce the computational complexity, a number of data summarization techniques have been proposed [40]. **Coreset** is a well-known sampling technique for compressing large-scale data sets [37, 23]. Roughly speaking, for a given large data set P, the coreset approach is to construct a new (weighted) set $\tilde{P}$ that approximately preserves the structure of P, and meanwhile the size $|\tilde{P}|$ is much smaller than $|P|$. Therefore, if we run an existing algorithm on $\tilde{P}$ rather than P, the runtime can be significantly reduced and the computational quality (e.g., the optimization objectives for the machine learning tasks [47]) can be approximately guaranteed. In the past decades, the coreset techniques have been successfully applied for solving many optimization problems, such as k-means clustering [23, 18], logistic regression [27, 38], Gaussian mixture models [33], and continual learning [10].

Usually we assume that the input data is stored in a matrix such that the coreset algorithm can easily access the data to compress. But this assumption may not hold in real-world scenarios. For example, according to the Kaggle 2017 "State of Data Science Survey", **65.5% of the data sets are relational data**. Namely, the data is decoupled into several relational tables, and we cannot obtain the data matrix (which is also called the "**design matrix**") unless joining all the tables. Relational database has a very large and fast growing market in this big data era. It is expected to reach USD 122.38 billion by 2027 [42]. Relational database has several favorable properties [48], e.g., the decoupled relational data can save a large amount of space, and it is friendly to several common statistical queries such as the aggregate functions `COUNT`, `SUM` and `AVG` in SQL. In recent years, the study on "in-database learning" has gained a significant amount of attention in the areas of machine learning and data management [39, 31, 20, 30].

However, constructing a coreset for relational database is much more challenging. Suppose there are $s > 1$ relational tables and the size of the largest table is N. Let n be the number of the

tuples obtained by joining all the tables, and then n can be as large as $O(N^s)$ (we illustrate an instance of joining two tables in Table 1). Obviously it will take extremely large time and space complexities if extracting all the tuples from the tables [6]. To remedy this issue, a straightforward idea is trying to complete the computing task without explicitly constructing the design matrix. Unfortunately, even for some very simple computational tasks, their implementations on relational data can be NP-hard.

To see why these implementations are so hard, we can consider the following simple clustering assignment task (which is often used as a building block for coresets construction [23, 18]): suppose the k cluster centers have already been given, and we want to determine the size of each cluster. Note that if we have the design matrix, this task is trivial (just assign each point to its nearest center, and then calculate the cluster sizes based on the assignment). However, if the data is decoupled into several relational tables, the problem of computing the assignment can be quite complicated. Khamis et al. [29] recently defined the problem of answering functional aggregate queries (FAQ) in which some of the input factors are defined by a collection of additive inequalities between variables (denote by FAQ-AI(m), where m is the number of additive inequalities). The problem of computing the clustering assignment can be formulated as an instance of FAQ-AI($k-1$) (to determine the cluster membership for one point (tuple), we need to certify that its distance to its own cluster center is lower than the distances to the other $k-1$ centers). Recently, Khamis et al.[1] showed that evaluating even a FAQ-AI(1) instance is #P-hard, and approximating a FAQ-AI(m) instance within any finite factor is NP-hard for any $m > 1$. Moseley et al. [36] also showed that even approximating the clustering assignment to any factor is NP-hard for $k \geq 3$. An intuitive understanding is that the query satisfying those inequalities require to access the information of each tuple on all the dimensions, where it is almost equivalent to constructing the entire design matrix.

1.1 Our Contributions

We consider *Empirical Risk Minimization (ERM)* problems in machine learning [50]. Let $\mathbb{R}^d$ be the data space. The training set $P = \{p_1, p_2, \cdots, p_n\} \subset \mathbb{R}^d$. But we assume that this set P is not explicitly given, where it is decoupled into s relational tables (the formal definitions are shown in Section 2). The goal is to learn the hypothesis θ (from the hypothesis space $\mathbb{H}$) so as to minimize the *empirical risk*

$$F(\theta) = \frac{1}{n} \sum_{i=1}^{n} f(\theta, p_i), \tag{1}$$

where $f(\cdot, \cdot)$ is the non-negative real-valued *loss function*.

Several coresets techniques on relational data have been studied very recently. Samadian et al. [43] showed that the simple uniform sampling yields a coreset for regularized loss minimization problems (note the uniform sampling can be efficiently implemented for relational database [52]). Their sample size is $\Theta(n^\kappa \cdot \mathtt{dim})$, where $\kappa \in (0, 1)$ (usually κ is set to be $1/2$ in practice) and $\mathtt{dim}$ is the VC dimension of loss function (usually it is $\Theta(d)$). Thus the size can be $\Theta(\sqrt{n} \cdot d)$, which is too large especially for high dimensional data. Curtin et al. [20] constructed a coreset for k-means clustering by building a weighted grid among the input s tables; the coreset yields a 9-approximation for the clustering objective. Independently, Ding et al. [21] also applied the "grid" idea to achieve a $(9 + \epsilon)$-approximation for k-means clustering with distributed dimensions (attributes). The major drawback of this "grid" idea is that the resulting coreset size can be as large as k^s which is exponential in the number of tables s. Moseley et al. [36] recently proposed a coreset for k-means clustering on relational data by using the k-means++ initialization method [5], however, their approximation ratio is too high (> 400) for real-world applications. Moreover, the coresets techniques proposed in [20, 21, 36] can only handle k-means clustering, and it is unclear that whether they can be extended for other machine learning problems in the form of (1).

In this paper, we aim to develop an efficient and general coreset construction method for optimizing (1) on relational data. First, we observe that real-world data sets often have low intrinsic dimensions (e.g, nearby a low-dimensional manifold) [9]. Our coreset approach is inspired by the well-known Gonzalez's algorithm for k-center clustering [24]. The algorithm greedily selects k points from the input point set, and the k balls centered at these selected k points with some appropriate radius can cover the whole input; if the input data has a low intrinsic dimension (e.g., the doubling dimension in Definition 3), the radius is no larger than an upper bound depending on k. Therefore, the set of cluster centers (each center has the weight equal to the corresponding cluster size) can serve as a

coreset for the ERM problem (1), where the error yielded from the coreset is determined by the radius. Actually this k-center clustering based intuition has been used to construct the coresets for various applications before [28, 46, 19].

However, we have to address two challenging issues for realizing this approach on relational data. First, the greedy selection procedure for the k cluster centers cannot be directly implemented for relational data. Second, it is hard to obtain the size of each cluster especially when the balls have overlap (the k balls can partition the space into 2^k parts). Actually, both of these two issues can be regarded as the instances of FAQ-AI($k-1$) which are NP-hard to compute [1, 36].

Our approach relies on a novel and easy-to-implement structure called "**aggregation tree with pseudo-cube**". We build the tree from bottom to up, where each relational table represents a leaf. Informally speaking, each node consists of a set of k cluster centers which is obtained by merging its two children; each center also associates with a "pseudo-cube" region in the space. Eventually, the root of the tree yields a qualified coreset for the implicit design matrix. The aggregation manner can help us to avoid building the high-complexity grid coreset as [20, 21]. Also, with the aid of "pseudo-cube", we can efficiently estimate the size of each cluster without tackling the troublesome FAQ-AI counting issue [1, 36].

Comparing with the previous coresets methods, our approach enjoys several significant advantages. For example, our approach can deal with more general applications. In fact, for most ERM problems in the form of (1) under some mild assumptions, we can construct their coresets by using our approach. Also our coresets have much lower complexities. It is worth to emphasize that our coreset size is independent of the dimensionality d; instead, it only depends on the doubling dimension of the input data.

1.2 Other Related Works

The earliest research on relational data was proposed by Codd [16]. A fundamental topic that is closely related to machine learning on relational data is how to take uniform and independent samples from the full join results [12]. Recently, Zhao et al. [52] proposed a random walk approach for this problem with acyclic join; Chen and Yi [13] generalized the result to some specific cyclic join scenarios.

Beside the aforementioned works [39, 31, 20, 21, 29, 1, 36], there also exist a number of results on other machine learning problems over relational data. Khamis et al. [2] and Yang et al. [51] respectively considered training SVMs and SVMs with Gaussian kernel on relational data. For the problem of linear regression on relational data, it is common to use the factorization techniques [44, 3]. The algorithms for training Gaussian Mixture Models and Neural Networks on relational data were also studied recently [14, 15]. We also refer the reader to the survey paper [45] for more details on learning over relational data.

2 Preliminaries

Suppose the training set for the problem (1) is a set P of n points in $\mathbb{R}^d$, and it is decoupled into s relational tables $\{T_1, \ldots, T_s\}$ with the feature (attribute) sets $\{D_1, \ldots, D_s\}$. Let $D = \bigcup_i D_i$ and therefore the size $|D| = d$. Actually, each table T_i can be viewed as projection of P onto a subspace spanned by D_i. To materialize the design matrix of P, a straightforward way is to compute the join over these s tables. With a slight abuse of notations, we still use "P" to denote the design matrix. We also let $[s] = \{1, 2, \ldots, s\}$ for simplicity.

Definition 1 (Join) *The join over the given s tables returns a $n \times d$ design matrix $P = T_1 \bowtie \cdots \bowtie T_s$, such that for any vector (point) $p \in \mathbb{R}^d$, $p \in P$ if and only if $\forall i \in [s]$, $\mathrm{Proj}_{D_i}(p) \in T_i$, where $\mathrm{Proj}_{D_i}(p)$ is the projection of p on the subspace spanned by the features of D_i.*

Table 1 is a simple illustration for joining two relational tables. To have a more intuitive understanding of join, we can generate a **hypergraph** $\mathcal{G} = (\mathcal{V}, \mathcal{E})$. Each vertex of $\mathcal{V}$ corresponds to an individual feature of D; each hyperedge of $\mathcal{E}$ corresponds to an individual relational table T_i, and connects all the vertices (features) of D_i. Then we can define the **acyclic** and **cyclic** join queries. A join is acyclic if the hypergraph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ can be ablated to be empty by performing the following operation iteratively: if there exists a vertex that connects with only one hyperedge, remove this vertex together

T_1	
d_1	d_2
1	1
2	1
2	2
3	3

T_2	
d_2	d_3
1	1
1	4
3	1
3	3

$T_1 \bowtie T_2$		
d_1	d_2	d_3
1	1	1
1	1	4
2	1	1
2	1	4
3	3	1
3	3	3

Table 1: An illustration for the join over two tables.

with the hyperedge. Otherwise, the join is cyclic. A cyclic query usually is extremely difficult and has a much higher complexity than that of an acyclic query. For example, for a cyclic join, it is even NP-hard to determine that whether the join is empty or not [35]. Fortunately, most real-world joins are acyclic, which allow us to take full advantage of relational data. Similar with most of the previous articles on relational learning [1, 2], we also assume that the join of the given tables is acyclic in this paper.

Counting is one of the most common aggregation queries on relational data. It returns the number of tuples that satisfy some particular conditions. The counting on an acyclic join (without additive inequalities) can be implemented effectively via dynamic programming [22]. But when the additive inequalities are included, the counting problem can be much more challenging and we may even need to materialize the whole design matrix [1]. For example, to count the tuples of $\{t \in T_1 \bowtie T_2 \ \& \ \|t\|_2^2 \leq 5\}$ in Table 1, we need to check the whole design matrix $T_1 \bowtie T_2$ for selecting the tuples that satisfy the constraint "$\|t\|_2^2 \leq 5$".

For the machine learning problems studied in this paper, we have the following assumption for the loss function in (1).

Assumption 1 (Continuity) *There exist real constants $\alpha, z \geq 0, \beta \in [0, 1)$, such that for any $p, q \in \mathbb{R}^d$ and any θ in the hypothesis space, we have*

$$|f(\theta, p) - f(\theta, q)| \leq \alpha \|p - q\|^z + \beta |f(\theta, q)|, \tag{2}$$

where $\| \cdot \|$ is the Euclidean norm in the space.

Remark 1 *Different machine learning problems have different values for α, β and z. For example, for the k-means clustering, we have $z = 2, \beta = \epsilon$ and $\alpha = O(\frac{1}{\epsilon})$ (where ϵ can be any small number in $(0, 1)$); for the k-median clustering, we have $z = 1, \beta = 0$ and $\alpha = 1$. Actually for a large number of problems, β is small or even 0, e.g., the logistic regression and SVM with soft margin problems have the value $\beta = 0$.*

We define the following coreset with both multiplicative error and additive error. We are aware that the standard coresets usually only have multiplicative errors [37, 23]. However, the deviation bounds for the ERM problems with finite training data set only yield additive error guarantees and the additive error is usually acceptable in practice [7, 49]. So the coresets with additive error have been also proposed recently [8].

Definition 2 ($(\epsilon_1, \epsilon_2)_z$-Coreset) *Let $P = \{p_1, p_2, \ldots, p_n\}$ be the training set (which is not explicitly given). Suppose $\epsilon_1 \in (0, 1)$ and $\epsilon_2, z > 0$. The $(\epsilon_1, \epsilon_2)_z$-coreset, denoted as $\tilde{P}$, is a point set $\{c_1, \cdots, c_{|\tilde{P}|}\}$ with a weight vector $W = [w_1, w_2, \ldots, w_{|\tilde{P}|}]$ satisfying that*

$$\tilde{F}(\theta) \in (1 \pm \epsilon_1) F(\theta) \pm \epsilon_2 \Delta^z, \tag{3}$$

for any θ in the hypothesis space $\mathbb{H}$, where $\tilde{F}(\theta) = \frac{1}{\sum_{i=1}^{|\tilde{P}|} w_i} \sum_{i=1}^{|\tilde{P}|} w_i f(\theta, c_i)$.

Usually we want the coreset size $|\tilde{P}|$ to be much smaller than $|P|$. So we can run our algorithm on $\tilde{P}$ and save a large amount of running time.

As mentioned in Section 1.1, we also assume that the training set P has a low intrinsic dimension. "Doubling dimension" is a widely used measure for indicating the intrinsic dimension of a given data

set [34]. Roughly speaking, it measures the growth rate of the given data in the space. Recently it has gained a lot of attention for studying its relation to coresets and machine learning problems [32, 26, 17]. For any $c \in \mathbb{R}^d$ and $r \geq 0$, we use $\mathbb{B}(c, r)$ to denote the ball centered at c with radius r.

Definition 3 (Doubling Dimension) *The doubling dimension of a data set P is the smallest number $\rho > 0$, such that for any $p \in P$ and $r \geq 0$, $P \cap \mathbb{B}(p, 2r)$ is always covered by the union of at most 2^ρ balls with radius r.*

It is easy to obtain the following proposition by recursively applying Definition 3 $\log \frac{\Delta}{r}$ times, where Δ is the diameter of P.

Claim 1 *For a given data set P and radius $r > 0$, if P has the doubling dimension ρ, then it can be covered by $(\frac{\Delta}{r})^\rho$ balls of radius r.*

3 Relational Coreset via Aggregation Tree

In this section, we present an efficient coreset construction method for relational data. First, we introduce the technique of aggregation tree with pseudo-cube. Actually there is an obstacle for obtaining the coreset from the aggregation tree. The weight of each point of the coreset is determined by the size of its corresponding pseudo-cube; however, the pesudo-cubes may have overlap and it is challenging to separate them in the environment of relational data. To explain our idea more clearly, we temporally ignore this "overlap" issue and show the "ideal" coreset construction result in Section 3.1. Then we show that the overlap issue can be efficiently solved by using random sampling and some novel geometric insights in Section 3.2.

Recall that our input is a set of s relational tables $\{T_1, \ldots, T_s\}$ with the feature (attribute) sets $\{D_1, \ldots, D_s\}$. Also $D = \bigcup_i D_i$ and $|D| = d$. For ease of presentation, we generate a new feature set $\hat{D}_i$ for each D_i as follows: initially, $\hat{D}_1 = D_1$; starting from $i = 2$ to s, we let $\hat{D}_i = D_i \backslash (\cup_{l=1}^{i-1} \hat{D}_l)$. It is easy to see that $\bigcup_i \hat{D}_i = D$, and $\forall i, j \in [s], i \neq j, \hat{D}_i \cap \hat{D}_j = \emptyset$. With a slight abuse of notations, we also use $\hat{D}_i$ to represent the subspace spanned by the features of $\hat{D}_i$ (so the Cartesian product $\hat{D}_1 \times \cdots \times \hat{D}_s$ is the the whole space $\mathbb{R}^d$). For any point set $Q \subset \mathbb{R}^d$ (resp., any point $c \in \mathbb{R}^d$) and any subspace H of $\mathbb{R}^d$, we use $\mathrm{Proj}_H(Q)$ (resp., $\mathrm{Proj}_H(c)$) to denote the projection of Q (resp., c) onto H.

3.1 Coreset Construction

Since our coreset construction algorithm is closely related to the Gonzalez's algorithm for k-center clustering [24], we briefly introduce it first. Initially, it arbitrarily selects a point from P, say c_1, and sets $C = \{c_1\}$; then it iteratively selects a new point that is farthest to the set C, i.e., $\arg\max_{p \in P} \min_{q \in C} ||p - q||$, and adds it to C. After k iterations, we obtain k points in C (suppose $C = \{c_1, \cdots, c_k\}$). The Gonzalez's algorithm yields a 2-approximation for k-center clustering. If the optimal radius of k-center clustering on P is r_{opt}, then P can be covered by the k balls $\mathbb{B}(c_1, 2r_{\mathrm{opt}}), \cdots, \mathbb{B}(c_k, 2r_{\mathrm{opt}})$. Together with Claim 1, for any given radius $r > 0$, we know that if we run the Gonzalez's algorithm on P with setting $k = (\frac{2\Delta}{r})^\rho$, the set P can be covered by the balls $\mathbb{B}(c_1, r), \cdots, \mathbb{B}(c_k, r)$ (since $r_{opt} \leq r/2$). If we set r to be small enough, the obtained C can be a good approximation (informally a coreset) for P.

However, as mentioned in Section 1, such k-center clustering approach cannot be implemented on relational data since it is equivalent to an instance of FAQ-AI($k - 1$). A straightfoward idea to remedy this issue is to run the Gonzalez's algorithm in each subspace $\hat{D}_i$, and then compute the Cartesian product to build a grid of size k^s as the methods of [20, 21]. But this approach will result in an exponentially large coreset (e.g., there are $s = 8$ tables and $k = 1000$). Below, we introduce our algorithm that can achieve a coreset with quasi-polynomial size.

Our high-level idea. We construct a **bottom-to-top tree** $\mathcal{T}$ where each relational table T_i corresponds to a leaf. For each node $\nu \in \mathcal{T}$, it is associated with a set of components: an index set $I_\nu \subseteq [s]$, the spanned subspace $H_\nu = \Pi_{i \in I_\nu} \hat{D}_i$, and a collection of centers $C_\nu = \{c_{\nu,1}, \cdots, c_{\nu,k}\} \subset H_\nu$. The center set C_ν determines a set of pseudo-cubes (as Definition 4 below) in H_ν. Obviously, for a leaf

Figure 1: For the example in the figure, $k = 4$. When merging two children, we have C_{ν_l} and C_{ν_r} from two disjoint subspaces (the purple points). Then we build the 4×4 grid, and select C_{ν_p} (the red points) by running the Gonzalez's algorithm on the grid points.

node (table) ν of T_i, the index set $I_\nu = \{i\}$ and the space $H_\nu = \hat{D}_i$; we directly run the Gonzalez's algorithm on the projection of P on $\hat{D}_i$ to obtain the set C_ν. Then, we grow the tree $\mathcal{T}$ from these leaves. For each parent node ν_p, we compute a grid $C_{\nu_l} \times C_{\nu_r}$ of size k^2 by taking the Cartesian product of the center sets from its two children ν_l and ν_r; then we remove the "empty" grid points (we will explain the meaning of "empty" after Definition 4) and run the Gonzalez's algorithm on the remaining grid points, which are denoted as $\widetilde{C_{\nu_l} \times C_{\nu_r}}$, to achieve the set C_{ν_p}. The index set $I_{\nu_p} = I_{\nu_l} \cup I_{\nu_r}$, and the subspace $H_{\nu_p} = H_{\nu_l} \times H_{\nu_r}$. Finally, the set C_{ν_0} of the root node ν_0 yields a coreset for the point set P. See an illustration of the aggregation tree in Figure 1.

It is worth noting that our aggregation tree approach is fundamentally different to the hierarchical decomposition tree methods that were commonly studied in doubling metrics [25, 11]. They build their trees from top to bottom, while our approach is from bottom to top. Actually, our approach can be viewed as a "compressed" version of the grid coreset methods [20, 21], where we deal with a grid of size at most k^2 each time. Also, the accumulated error can be also bounded since the height of $\mathcal{T}$ is $O(\log s)$.

Definition 4 (Pseudo-cube) *Given an index set $I \subseteq [s]$, a point $c \in H = \prod_{i \in I} \hat{D}_i$, and a number $r \geq 0$, we define the pseudo-cube*

$$\mathrm{PC}_I(c, r) = \prod_{i \in I} \mathbb{B}(\mathrm{Proj}_{\hat{D}_i}(c), r), \tag{4}$$

where $\mathrm{Proj}_{\hat{D}_i}(c)$ is the projection of c onto the subspace $\hat{D}_i$.

A nice property of pseudo-cube is that it is a Cartesian product of a set of regions from those subspaces $\hat{D}_i$s. More importantly, it does not involve any cross-table constraints or additive inequalities. Consequently, counting the size of a pseudo-cube is easy to implement over the relational data. Another property is that the Cartesian product of two pseudo-cubes is still a pseudo-cube, but in a new subspace with higher dimension. When we take the grid of the two center sets from two children nodes, we also obtain k^2 pseudo-cubes. For each pseudo-cube, we count its size (i.e., the size of its intersection with P); if the size is 0, we call the corresponding grid point is "empty" and remove it before running the Gonzalez's algorithm on the grid.

Let $\mathrm{d}(A, B) := \max_{a \in A} \min_{b \in B} ||a - b||$ for any two sets A and B in $\mathbb{R}^d$ (i.e., the directed Hausdorff Distance). First, for each $h = 0, 1, \cdots, \lceil \log s \rceil$, we define a key value

$$L_h : = \max\{\mathrm{d}(\mathrm{Proj}_{H_\nu}(P), C_\nu) \mid \nu \text{ is at the } h\text{-th level of } \mathcal{T}\}. \tag{5}$$

By using these L_hs, we present our coreset construction approach in Algorithm 1.

Theorem 1 *Suppose the loss function $f(\cdot, \cdot)$ satisfies Assumption 1. If we set $k = \left(\left(\frac{\alpha}{\epsilon_2} \right)^{\frac{1}{z}} 3^{\lceil \log s \rceil} \cdot 2^{\frac{\lceil \log s \rceil^2 + 3 \lceil \log s \rceil + 8}{4}} \right)^\rho = \left(\left(\frac{\alpha}{\epsilon_2} \right)^{\frac{1}{z}} 2^{O((\log s)^2)} \right)^\rho$ in Algorithm 1, the returned set C_{ν_0} with the weights $\{w_1, \cdots, w_k\}$ yields a $(\beta, \epsilon_2)_z$-coreset.*

Remark 2 *Note that our coreset size is quasi-polynomial since it has a factor $2^{O((\log s)^2)}$. But we would like to emphasize that this factor usually is small for most practical problems. For example, in*

Algorithm 1 AGGREGATION TREE

Input: A set of relational tables $\{T_1, \ldots, T_s\}$ and a parameter k (the coreset size).
Output: A weighted point set as the coreset.

1. Initialize an empty aggregation tree $\mathcal{T}$; when a node ν of $\mathcal{T}$ is constructed, it is associated with an index set I_ν and its corresponding subspace H_ν, and a set of k centers $C_\nu = \{c_{\nu,1}, \ldots, c_{\nu,k}\} \subset H_\nu$.

2. Construct s leaf nodes $\{\nu_1, \ldots, \nu_s\}$ corresponding to the s tables at the 0-th level: run the Gonzalez's algorithm to select k centers for each table T_i on the subspace $\hat{D}_i$. Also obtain the value L_0 defined in (5).

3. Let $\texttt{Children} = \{\nu_1, \ldots, \nu_s\}$ and $\texttt{Parent} = \emptyset$. Initialize $h = 0$ to indicate the current level on $\mathcal{T}$.

4. For $h = 1$ to $\lceil \log s \rceil$:

   (a) Initialize $l_h = 0$;

   (b) While $|\texttt{Children}| >= 2$:

     i. Select two different nodes ν_i, ν_j from $\texttt{Children}$, and $\texttt{Children} = \texttt{Children} \setminus \{\nu_i, \nu_j\}$;

     ii. Compute the Cartesian product to construct a grid $C_{\nu_i} \times C_{\nu_j}$ with k^2 centers in the space $H_{\nu_i} \times H_{\nu_j}$;

     iii. For each $c \in C_{\nu_i} \times C_{\nu_j}$, count the size of $\Big\{p \in P \mid \text{Proj}_{H_{\nu_i}}(p) \in \text{PC}_{I_{\nu_i}}(\text{Proj}_{H_{\nu_i}}(c), L_{h-1})$ & $\text{Proj}_{H_{\nu_j}}(p) \in \text{PC}_{I_{\nu_j}}(\text{Proj}_{H_{\nu_j}}(c), L_{h-1})\Big\}$;

     iv. Remove c from $C_{\nu_i} \times C_{\nu_j}$ if the size is 0, and then obtain $\widetilde{C_{\nu_i} \times C_{\nu_j}}$ that is the set of remaining non-empty grid points;

     v. Construct a parent node ν: run the Gonzalez's algorithm on $\widetilde{C_{\nu_i} \times C_{\nu_j}}$ to obtain a set C_v of k centers, let $l_h = \max(l_h, \texttt{d}(\widetilde{C_{\nu_i} \times C_{\nu_j}}, C_\nu))$, $I_\nu = I_{\nu_i} \cup I_{\nu_j}$ and $H_\nu = H_{\nu_i} \times H_{\nu_j}$;

     vi. $\texttt{Parent} = \texttt{Parent} \cup \{\nu\}$;

   (c) $L_h = \sqrt{2^h}(l_h + \sqrt{2}L_{h-1})$;

   (d) $\texttt{Children} = \texttt{Children} \cup \texttt{Parent}, \texttt{Parent} = \emptyset$;

5. Let ν_0 be the root node; for each $c_{\nu_0, i} \in C_{\nu_0}$, we assign a weight $w_i = |P \cap \text{PC}_{I_{\nu_0}}(c_{\nu_0,i}, L_{\lceil \log s \rceil})|$ (actually, this is not an accurate expression since the pseudo-cubes may have overlap with each other, and we will address this issue in Section 3.2).

return the set C_{ν_0} with the weights $\{w_1, \cdots, w_k\}$.

---

the standard TPC-H benchmark [41], s is no larger than 8, although the design matrix over joining the s tables can be quite large.

To prove the above theorem, we first introduce the following key lemma. We let $r_0 = \frac{\Delta}{k^{\frac{1}{\rho}}}$. From Claim 1 we know that the entire data set P can be covered by k balls with radius r_0.

Lemma 1 *For each $h = 0, 1, \cdots, \lceil \log s \rceil$, $L_h \leq 3^h \cdot 2^{\frac{h^2+3h+8}{4}} r_0$.*

Proof. Since the Gonzalez's algorithm yields an approximation factor 2, from Claim 1 we know that $L_0 \leq 2r_0$. Then we consider the case $h \geq 1$. Suppose the algorithm is constructing the h-th level of $\mathcal{T}$. In Step 4b we repeatedly select two nodes ν_i, ν_j from the $(h-1)$-th level that form a parent node ν at the h-th level. Let C_{opt} be the optimal solution of the k-center clustering on $\text{Proj}_{H_{\nu_i} \times H_{\nu_j}}(P)$. Since P can be covered by k balls with radius r_0, so can the projection $\text{Proj}_{H_{\nu_i} \times H_{\nu_j}}(P)$. That is,

$$\texttt{d}(\text{Proj}_{H_{\nu_i} \times H_{\nu_j}}(P), C_{opt}) \leq r_0. \tag{6}$$

Also, since $\texttt{d}(\text{Proj}_{H_{\nu_i}}(P), C_{\nu_i}) \leq L_{h-1}$ and $\texttt{d}(\text{Proj}_{H_{\nu_j}}(P), C_{\nu_j}) \leq L_{h-1}$, we have

$$\texttt{d}(\text{Proj}_{H_{C_{\nu_i}} \times H_{C_{\nu_j}}}(P), \widetilde{C_{\nu_i} \times C_{\nu_j}}) \leq \sqrt{2}L_{h-1}. \tag{7}$$

Together with (6), we know

$$\texttt{d}(\widetilde{C_{\nu_i} \times C_{\nu_j}}, C_{opt}) \leq r_0 + \sqrt{2}L_{h-1}. \tag{8}$$

That is, if we run k-center clustering on $\widetilde{C_{\nu_i} \times C_{\nu_j}}$, the optimal radius should be no larger than $r_0 + \sqrt{2}L_{h-1}$. So if we run the 2-approximation Gonzalez's algorithm on $\widetilde{C_{\nu_i} \times C_{\nu_j}}$ and obtain the center set C_ν, then

$$\mathtt{d}(\widetilde{C_{\nu_i} \times C_{\nu_j}}, C_\nu) \leq 2(r_0 + \sqrt{2}L_{h-1}). \tag{9}$$

Further, we combine (7) and (9), and obtain

$$\mathtt{d}(\mathrm{Proj}_{H_{\nu_i} \times H_{\nu_j}}(P), C_\nu) \leq 2(r_0 + \sqrt{2}L_{h-1}) + \sqrt{2}L_{h-1}. \tag{10}$$

For each $c_{\nu,l} \in C_\nu$, we construct a pseudo-cube

$$\prod_{t \in I_{\nu_i} \cup I_{\nu_j}} \mathbb{B}(\mathrm{Proj}_{\hat{D}_t}(c_{\nu,l}), 2(r_0 + \sqrt{2}L_{h-1}) + \sqrt{2}L_{h-1}). \tag{11}$$

Then we know that $\mathrm{Proj}_{H_{\nu_i} \times H_{\nu_j}}(P)$ is covered by the union of the obtained k pseudo-cubes. Because $|I_\nu| = |I_{\nu_i} \cup I_{\nu_j}| \leq 2^h$, we have $L_h \leq (2(r_0 + \sqrt{2}L_{h-1}) + \sqrt{2}L_{h-1}) \cdot \sqrt{2^h}$. Together with $L_0 \leq 2r_0$, we can solve this recursion function and obtain

$$L_h \leq 3^h \cdot 2^{\frac{h^2+3h+8}{4}} r_0. \tag{12}$$

$\square$

Lemma 1 indicates that the difference between C_{ν_0} and P is bounded in the space. To prove it is a qualified coreset with respect to the ERM problem (1), we also need to assign a weight to each point of C_{ν_0}. In Step 5 of Algorithm 1, we set the weight $w_i = |P \cap \mathtt{PC}_{I_{\nu_0}}(c_{\nu_0,i}, L_{\lceil \log s \rceil})|$ (for simplicity, we temporarily assume these pseudo-cubes are disjoint, and leave the discussion on the overlap issue to Section 3.2). The detailed proof of Theorem 1 is placed to our supplement.

Remark 3 *In a real implementation, if the coreset size is given (e.g., 5% of the input data size $|P|$), we can directly set the value for k to run Algorithm 1. Another scenario is that we are given a restricted variance between P and the output C_{ν_0} (i.e., the difference $\mathtt{d}(P, C_{\nu_0})$ is required to be no larger than a threshold). Then we can try the value for k via doubling search. For example, starting from $k = k_0$ (k_0 is a small constant), we can try $k = k_0, 2k_0, 2^2 k_0, \cdots$, until the difference is lower than the threshold.*

3.2 The Overlap Issue

We consider the k pseudo-cubes $\mathtt{PC}_{I_{\nu_0}}(c_{\nu_0,i}, L_{\lceil \log s \rceil})$, $1 \leq i \leq k$, obtained from Algorithm 1. Since ν_0 is the root, it is easy to know $I_{\nu_0} = [s]$ and $H_{\nu_0} = \mathbb{R}^d$. For the sake of simplicity, we use $\mathtt{PC}_i$ to denote the pseudo-cube $\mathtt{PC}_{I_{\nu_0}}(c_{\nu_0,i}, L_{\lceil \log s \rceil})$ and L to denote $L_{\lceil \log s \rceil}$ below.

If these pseudo-cubes are disjoint, we can simply set the weight $w_i = |P \cap \mathtt{PC}_i|$ as Step 5 of Algorithm 1. However, these pseudo-cubes may have overlaps and such an assignment for the weights cannot guarantee the correctness of our coreset. For example, if a point $q \in P$ is covered by two pseudo-cubes $\mathtt{PC}_{i_1}$ and $\mathtt{PC}_{i_2}$, we should assign q to only one pseudo-cube. Note that this overlap issue is trivial if the whole data matrix P is available. But it can be troublesome for relational data, because it is quite inefficient to perform the counting on their union $P \cap (\mathtt{PC}_{i_1} \cup \mathtt{PC}_{i_2})$. Moreover, the k pseudo-cubes can partition the space into as large as 2^k different regions, and it is challenging to deal with so many overlaps.

Fortunately, we can solve this issue by using random sampling. The key observation is that we can tolerate a small error on each weight w_i. Let $\delta \in (0, 1)$. If we obtain a set of approximate weights $W' = \{w'_1, \cdots, w'_k\}$ that satisfy $w'_i \in (1 \pm \delta)w_i$ for $1 \leq i \leq k$, then we have

$$\sum_{i=1}^{k} w'_i f(\theta, c_{\nu_0,i}) \in (1 \pm \delta) \sum_{i=1}^{k} w_i f(\theta, c_{\nu_0,i}), \tag{13}$$

for any θ in the hypothesis space $\mathbb{H}$. We can use the following idea to obtain a qualified W'.

High-level idea. Without loss of generality, we assume all the k pseudo-cubes are not empty (otherwise, we can directly remove the empty pseudo-cubes). Then we consider the pseudo-cubes

one by one. For $\texttt{PC}_1$, we directly set $w'_1 = |P \cap \texttt{PC}_1|$. Suppose currently we have already obtained the values $w'_1, \cdots, w'_{i_0}$, and try to determine the value for w'_{i_0+1}. We take a uniform sample of m points from $P \cap \texttt{PC}_{i_0+1}$ by using the sampling technique for relational data [52]. Each sampled point corresponds a binary random variable x: if it belongs to $\texttt{PC}_{i_0+1} \setminus (\cup_{i=1}^{i_0} \texttt{PC}_i)$, $x = 1$; otherwise, $x = 0$. If m is sufficiently large, from the Chernoff bound, we can prove that the sum of these m random variables (denote by g) over m can serve as a good estimation of

$$\tau_{i_0+1} = \frac{|P \cap (\texttt{PC}_{i_0+1} \setminus (\cup_{i=1}^{i_0} \texttt{PC}_i))|}{|P \cap \texttt{PC}_{i_0+1}|}. \tag{14}$$

Thus we can set $w'_{i_0+1} = \frac{g}{m} \cdot |P \cap \texttt{PC}_{i_0+1}| \approx |P \cap (\texttt{PC}_{i_0+1} \setminus (\cup_{i=1}^{i_0} \texttt{PC}_i))|$.

A remaining issue of the above method is that the ratio τ_{i_0+1} can be extremely small, that is, we have to set m to be too large for guaranteeing the multiplicative "$1 \pm \delta$" error bound. Our idea for solving this issue is from the geometry. If τ_{i_0+1} is extremely small, we call $\texttt{PC}_{i_0+1}$ as a "light" pseudo-cube. Meanwhile, it should has at least one "heavy" neighbor from $\{\texttt{PC}_1, \cdots, \texttt{PC}_{i_0}\}$. The reason is that a small τ_{i_0+1} implies that there must exist some $1 \le i_1 \le i_0$, such that the intersection $P \cap \texttt{PC}_{i_0+1} \cap \texttt{PC}_{i_1}$ takes a significant part of $P \cap \texttt{PC}_{i_0+1}$. And we call $\texttt{PC}_{i_1}$ as a "heavy" neighbor of $\texttt{PC}_{i_0+1}$. Moreover, the distance between $\texttt{PC}_{i_1}$ and $\texttt{PC}_{i_0+1}$ should be bounded (since they have overlap in the space). Therefore, we can just ignore $\texttt{PC}_{i_0+1}$ and use $\texttt{PC}_{i_1}$ to represent their union $\texttt{PC}_{i_1} \cup \texttt{PC}_{i_0+1}$. This idea can help us to avoid taking a too large sample for light pseudo-cube. Overall, we have the following theorem, and the detailed proof is placed to our supplement.

Theorem 2 *Suppose the loss function $f(\cdot, \cdot)$ satisfies Assumption 1 and $\epsilon_1 > \beta$. If we set k in Algorithm 1 as Theorem 1, and let $m = O\left(\frac{k}{\epsilon_1^3} \ln \frac{k}{\lambda} \left(\beta + \frac{\alpha L^z}{M}\right)\right)$ where $M := \min F(\theta)$ and $\lambda \in (0,1)$, the returned set C_{ν_0} with the weights W' yields a $(\epsilon_1, \epsilon_2)_z$-coreset with probability $1 - \lambda$.*

The computational complexity. We analyze the total complexity of Algorithm 1 together with the above sampling procedure. It is easy to know that the Gonzalez's algorithm takes $O(kNd)$ time for computing the cluster centers on the s leaf nodes in total, where N is the maximum number of tuples among the input s tables. When merging two nodes ν_i and ν_j, we first remove the empty grid points from $C_{\nu_i} \times C_{\nu_j}$ by counting the sizes of the pseudo-cubes, where we use $\Psi(N, s, d)$ to denote the complexity of performing the counting one time [4] (for counting an acyclic join, $\Psi(N, s, d) = O\left(sd^2 N \log(N)\right)$). Also we run the Gonzalez's algorithm on $\widetilde{C_{\nu_i} \times C_{\nu_j}}$. Note that the distance between any two points of $\widetilde{C_{\nu_i} \times C_{\nu_j}}$ can be obtained in $O(1)$ time, since it can be directly obtained by combining the distances of their projections on H_{ν_i} and H_{ν_j} which are respectively stored in ν_i and ν_j. So the total complexity for merging two nodes is $O\left(k^2 \Psi(N, s, d) + k^3\right)$ (the term "k^3" is from the complexity of the Gonzalez's algorithm). As a consequence, the complexity for constructing the tree $\mathcal{T}$ is $O\left(sk^2 \Psi(N, s, d) + sk^3\right)$. Also note that it takes $O(s)$ time for taking a single sample [52]. Each sample is a d-dimensional vector and it takes $O(i_0 \cdot d)$ time to check that whether it belongs to $\texttt{PC}_{i_0+1} \setminus (\cup_{i=1}^{i_0} \texttt{PC}_i)$ or not. So the sampling procedure takes $\sum_{i_0=1}^{k} O(ms + i_0 \cdot md) = O(k^2 md)$ time. Overall, the whole coreset construction takes $O\left(k^2(s\Psi(N, s, d) + sk + md)\right)$ time.

4 Conclusion

In this paper, we propose a novel relational coreset method based on the aggregation tree with pseudo-cube technique. Our method can be applied to several popular machine learning models. In our experiments, we consider the SVM with soft margin ($\alpha = O(\|\theta\|_2)$, $\beta = 0$, and $z = 1$), the k-means clustering ($\alpha = O(\frac{1}{\epsilon})$, $\beta = \epsilon$, and $z = 2$, where ϵ can be any small number in $(0,1)$), and the logistic regression ($\alpha = O(\|\theta\|_2)$, $\beta = 0$, and $z = 1$) problems. **Due to the space limit, we leave the detailed experimental results to our supplement.** In future, there are also several interesting problems deserved to study, e.g., the relational coresets construction for more complicated machine learning models, and the privacy-preserving issues for relational coresets when the input data contains sensitive attributes.

References

[1] Mahmoud Abo-Khamis, Sungjin Im, Benjamin Moseley, Kirk Pruhs, and Alireza Samadian. Approximate aggregate queries under additive inequalities. In *Symposium on Algorithmic Principles of Computer Systems (APOCS)*, pages 85–99. SIAM, 2021.

[2] Mahmoud Abo-Khamis, Sungjin Im, Benjamin Moseley, Kirk Pruhs, and Alireza Samadian. A relational gradient descent algorithm for support vector machine training. In *Symposium on Algorithmic Principles of Computer Systems (APOCS)*, pages 100–113. SIAM, 2021.

[3] Mahmoud Abo Khamis, Hung Q Ngo, XuanLong Nguyen, Dan Olteanu, and Maximilian Schleich. In-database learning with sparse tensors. In *Proceedings of the 37th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems*, pages 325–340, 2018.

[4] Mahmoud Abo Khamis, Hung Q Ngo, and Atri Rudra. Faq: questions asked frequently. In *Proceedings of the 35th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems*, pages 13–28, 2016.

[5] David Arthur and Sergei Vassilvitskii. k-means++: the advantages of careful seeding. In *SODA '07*, 2007.

[6] Albert Atserias, Martin Grohe, and Dániel Marx. Size bounds and query plans for relational joins. *SIAM J. Comput.*, 42(4):1737–1767, 2013.

[7] Olivier Bachem, Mario Lucic, S. Hamed Hassani, and Andreas Krause. Uniform deviation bounds for k-means clustering. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pages 283–291. PMLR, 2017.

[8] Olivier Bachem, Mario Lucic, and Andreas Krause. Scalable k -means clustering via lightweight coresets. In Yike Guo and Faisal Farooq, editors, *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, KDD 2018, London, UK, August 19-23, 2018*, pages 1119–1127. ACM, 2018.

[9] Mikhail Belkin. Problems of learning on manifolds, 2003.

[10] Zalán Borsos, Mojmir Mutny, and Andreas Krause. Coresets via bilevel optimization for continual learning and streaming. *Advances in Neural Information Processing Systems*, 33:14879–14890, 2020.

[11] T-H Hubert Chan, Anupam Gupta, Bruce M Maggs, and Shuheng Zhou. On hierarchical routing in doubling metrics. *ACM Transactions on Algorithms (TALG)*, 12(4):1–22, 2016.

[12] Surajit Chaudhuri, Rajeev Motwani, and Vivek R. Narasayya. On random sampling over joins. In Alex Delis, Christos Faloutsos, and Shahram Ghandeharizadeh, editors, *SIGMOD 1999, Proceedings ACM SIGMOD International Conference on Management of Data, June 1-3, 1999, Philadelphia, Pennsylvania, USA*, pages 263–274. ACM Press, 1999.

[13] Yu Chen and Ke Yi. Random sampling and size estimation over cyclic joins. In *23rd International Conference on Database Theory (ICDT 2020)*. Schloss Dagstuhl-Leibniz-Zentrum für Informatik, 2020.

[14] Zhaoyue Cheng and Nick Koudas. Nonlinear models over normalized data. In *2019 IEEE 35th International Conference on Data Engineering (ICDE)*, pages 1574–1577. IEEE, 2019.

[15] Zhaoyue Cheng, Nick Koudas, Zhe Zhang, and Xiaohui Yu. Efficient construction of nonlinear models over normalized data. In *37th IEEE International Conference on Data Engineering, ICDE 2021, Chania, Greece, April 19-22, 2021*, pages 1140–1151. IEEE, 2021.

[16] E. F. Codd. A relational model of data for large shared data banks (reprint). *Commun. ACM*, 26(1):64–69, 1983.

[17] Vincent Cohen-Addad, Andreas Emil Feldmann, and David Saulpic. Near-linear time approximation schemes for clustering in doubling metrics. *J. ACM*, 68(6):44:1–44:34, 2021.

[18] Vincent Cohen-Addad, David Saulpic, and Chris Schwiegelshohn. A new coreset framework for clustering. In Samir Khuller and Virginia Vassilevska Williams, editors, *STOC '21: 53rd Annual ACM SIGACT Symposium on Theory of Computing, Virtual Event, Italy, June 21-25, 2021*, pages 169–182. ACM, 2021.

[19] Cody Coleman, Christopher Yeh, Stephen Mussmann, Baharan Mirzasoleiman, Peter Bailis, Percy Liang, Jure Leskovec, and Matei Zaharia. Selection via proxy: Efficient data selection for deep learning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020.

[20] Ryan R. Curtin, Benjamin Moseley, Hung Q. Ngo, XuanLong Nguyen, Dan Olteanu, and Maximilian Schleich. Rk-means: Fast clustering for relational data. In Silvia Chiappa and Roberto Calandra, editors, *The 23rd International Conference on Artificial Intelligence and Statistics, AISTATS 2020, 26-28 August 2020, Online [Palermo, Sicily, Italy]*, volume 108 of *Proceedings of Machine Learning Research*, pages 2742–2752. PMLR, 2020.

[21] Hu Ding, Yu Liu, Lingxiao Huang, and Jian Li. K-means clustering with distributed dimensions. In Maria-Florina Balcan and Kilian Q. Weinberger, editors, *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, volume 48 of *JMLR Workshop and Conference Proceedings*, pages 1339–1348. JMLR.org, 2016.

[22] Martin E. Dyer. Approximate counting by dynamic programming. In Lawrence L. Larmore and Michel X. Goemans, editors, *Proceedings of the 35th Annual ACM Symposium on Theory of Computing, June 9-11, 2003, San Diego, CA, USA*, pages 693–699. ACM, 2003.

[23] Dan Feldman. Core-sets: An updated survey. *WIREs Data Mining Knowl. Discov.*, 10(1), 2020.

[24] Teofilo F. Gonzalez. Clustering to minimize the maximum intercluster distance. *Theor. Comput. Sci.*, 38:293–306, 1985.

[25] Sariel Har-Peled and Manor Mendel. Fast construction of nets in low-dimensional metrics and their applications. *SIAM Journal on Computing*, 35(5):1148–1184, 2006.

[26] Lingxiao Huang, Shaofeng H.-C. Jiang, Jian Li, and Xuan Wu. Epsilon-coresets for clustering (with outliers) in doubling metrics. In Mikkel Thorup, editor, *59th IEEE Annual Symposium on Foundations of Computer Science, FOCS 2018, Paris, France, October 7-9, 2018*, pages 814–825. IEEE Computer Society, 2018.

[27] Jonathan H. Huggins, Trevor Campbell, and Tamara Broderick. Coresets for scalable bayesian logistic regression. In Daniel D. Lee, Masashi Sugiyama, Ulrike von Luxburg, Isabelle Guyon, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pages 4080–4088, 2016.

[28] Piotr Indyk, Sepideh Mahabadi, Mohammad Mahdian, and Vahab S. Mirrokni. Composable core-sets for diversity and coverage maximization. In Richard Hull and Martin Grohe, editors, *Proceedings of the 33rd ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems, PODS'14, Snowbird, UT, USA, June 22-27, 2014*, pages 100–108. ACM, 2014.

[29] Mahmoud Abo Khamis, Ryan R. Curtin, Benjamin Moseley, Hung Q. Ngo, XuanLong Nguyen, Dan Olteanu, and Maximilian Schleich. Functional aggregate queries with additive inequalities. *ACM Trans. Database Syst.*, 45(4):17:1–17:41, 2020.

[30] Mahmoud Abo Khamis, Sungjin Im, Benjamin Moseley, Kirk Pruhs, and Alireza Samadian. A relational gradient descent algorithm for support vector machine training. In Michael Schapira, editor, *2nd Symposium on Algorithmic Principles of Computer Systems, APOCS 2020, Virtual Conference, January 13, 2021*, pages 100–113. SIAM, 2021.

[31] Mahmoud Abo Khamis, Hung Q. Ngo, XuanLong Nguyen, Dan Olteanu, and Maximilian Schleich. In-database learning with sparse tensors. In Jan Van den Bussche and Marcelo Arenas, editors, *Proceedings of the 37th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems, Houston, TX, USA, June 10-15, 2018*, pages 325–340. ACM, 2018.

[32] Yi Li, Philip M Long, and Aravind Srinivasan. Improved bounds on the sample complexity of learning. *Journal of Computer and System Sciences*, 62(3):516–527, 2001.

[33] Mario Lucic, Matthew Faulkner, Andreas Krause, and Dan Feldman. Training gaussian mixture models at scale via coresets. *J. Mach. Learn. Res.*, 18:160:1–160:25, 2017.

[34] Jouni Luukkainen. Assouad dimension: antifractal metrization, porous sets, and homogeneous measures. *Journal of the Korean Mathematical Society*, 35(1):23–76, 1998.

[35] Dániel Marx. Tractable hypergraph properties for constraint satisfaction and conjunctive queries. *J. ACM*, 60(6):42:1–42:51, 2013.

[36] Benjamin Moseley, Kirk Pruhs, Alireza Samadian, and Yuyan Wang. Relational algorithms for k-means clustering. In *48th International Colloquium on Automata, Languages, and Programming (ICALP 2021)*. Schloss Dagstuhl-Leibniz-Zentrum für Informatik, 2021.

[37] Alexander Munteanu and Chris Schwiegelshohn. Coresets-methods and history: A theoreticians design pattern for approximation and streaming algorithms. *Künstliche Intell.*, 32(1):37–53, 2018.

[38] Alexander Munteanu, Chris Schwiegelshohn, Christian Sohler, and David P. Woodruff. On coresets for logistic regression. In Klaus David, Kurt Geihs, Martin Lange, and Gerd Stumme, editors, *49. Jahrestagung der Gesellschaft für Informatik, 50 Jahre Gesellschaft für Informatik - Informatik für Gesellschaft, INFORMATIK 2019, Kassel, Germany, September 23-26, 2019*, volume P-294 of *LNI*, pages 267–268. GI, 2019.

[39] Hung Q. Ngo, XuanLong Nguyen, Dan Olteanu, and Maximilian Schleich. In-database factorized learning. In Juan L. Reutter and Divesh Srivastava, editors, *Proceedings of the 11th Alberto Mendelzon International Workshop on Foundations of Data Management and the Web, Montevideo, Uruguay, June 7-9, 2017*, volume 1912 of *CEUR Workshop Proceedings*. CEUR-WS.org, 2017.

[40] Jeff M. Phillips. Coresets and sketches. *CoRR*, abs/1601.00617, 2016.

[41] Meikel Pöss and Chris Floyd. New TPC benchmarks for decision support and web commerce. *SIGMOD Rec.*, 29(4):64–71, 2000.

[42] Report. *Relational Database Management System Market: Industry Analysis and Forecast 2021-2027: By Type, Deployment, End users, and Region.* 2022.

[43] Alireza Samadian, Kirk Pruhs, Benjamin Moseley, Sungjin Im, and Ryan Curtin. Unconditional coresets for regularized loss minimization. In *International Conference on Artificial Intelligence and Statistics*, pages 482–492. PMLR, 2020.

[44] Maximilian Schleich, Dan Olteanu, and Radu Ciucanu. Learning linear regression models over factorized joins. In *Proceedings of the 2016 International Conference on Management of Data*, pages 3–18, 2016.

[45] Maximilian Schleich, Dan Olteanu, Mahmoud Abo Khamis, Hung Q. Ngo, and XuanLong Nguyen. Learning models over relational data: A brief tutorial. *CoRR*, abs/1911.06577, 2019.

[46] Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. In *International Conference on Learning Representations*, 2018.

[47] Suvrit Sra, Sebastian Nowozin, and Stephen J Wright. *Optimization for machine learning*. Mit Press, 2012.

[48] Sai Sumathi and S Esakkirajan. *Fundamentals of relational database management systems*, volume 47. Springer, 2007.

[49] Matus Telgarsky and Sanjoy Dasgupta. Moment-based uniform deviation bounds for *k*-means and friends. In Christopher J. C. Burges, Léon Bottou, Zoubin Ghahramani, and Kilian Q. Weinberger, editors, *Advances in Neural Information Processing Systems 26: 27th Annual Conference on Neural Information Processing Systems 2013. Proceedings of a meeting held December 5-8, 2013, Lake Tahoe, Nevada, United States*, pages 2940–2948, 2013.

[50] Vladimir Vapnik. Principles of risk minimization for learning theory. In John E. Moody, Stephen Jose Hanson, and Richard Lippmann, editors, *Advances in Neural Information Processing Systems 4, [NIPS Conference, Denver, Colorado, USA, December 2-5, 1991]*, pages 831–838. Morgan Kaufmann, 1991.

[51] Keyu Yang, Yunjun Gao, Lei Liang, Bin Yao, Shiting Wen, and Gang Chen. Towards factorized svm with gaussian kernels over normalized data. In *2020 IEEE 36th International Conference on Data Engineering (ICDE)*, pages 1453–1464. IEEE, 2020.

[52] Zhuoyue Zhao, Robert Christensen, Feifei Li, Xiao Hu, and Ke Yi. Random sampling over joins revisited. In *Proceedings of the 2018 International Conference on Management of Data*, pages 1525–1539, 2018.