# WaveFM: Wavelet Decomposition Masked Reconstruction for Multi-Scale Time-series Foundation Model

**Seongbeom Park[1], Hyunwoo Seo[1], Yichen Ma[2], Hojin Cho[1], Chiehyeon Lim[1,3], Jianjun Shi[2]**

[1] Ulsan National Institute of Science and Technology, Ulsan, Republic of Korea

[2] Georgia Institute of Technology, Atlanta, Georgia, USA

[3] POSCO N.EX.T Hub, POSCO Holdings Inc., 440, Teheran-ro, Gangnam-gu, Seoul, South Korea

{sbpark1021, hseo75, chjin314, chlim}@unist.ac.kr

{yma447, jianjun.shi}@gatech.edu

## ABSTRACT

Encoder-only Time-Series Foundation Models (TSFMs) learn to understand time series through time-domain masked reconstruction. This objective captures transferable temporal dynamics, making them a strong universal backbone across domains and tasks. However, simple time-domain masked reconstruction does not fully capture the underlying temporal dynamics. In particular, it does not explicitly reflect the multi-scale nature of real-world time series and can bias learning toward low-frequency trends, reducing sensitivity to fine-grained temporal changes. To address this, we propose WaveFM, which decomposes each time series into scale-separated components and is trained to model within-scale temporal structure and cross-scale composition back to the original time series signal. Therefore, WaveFM explicitly emphasizes key features for understanding time series, learning how coarse trends and fine-scale deviations jointly explain the time series. Experiments on long-horizon forecasting and imputation show consistent improvements over encoder-only TSFM baselines, supporting the importance of explicitly decomposing multi-scale components for understanding time series.

**Track:** Research

Figure 1: Reconstruction results comparing our method with MOMENT (Goswami et al., 2024) on the Weather dataset. WaveFM more faithfully reconstructs both coarse low-frequency structure and fine-grained fluctuations, indicating a stronger understanding of underlying temporal dynamics.

## 1 INTRODUCTION

Encoder-only time-series foundation models (TSFMs) learn transferable representations by reconstructing masked segments from surrounding context, enabling the capture of intrinsic temporal dependencies and dynamics (Woo et al., 2024; Prabhakar Kamarthi & Prakash, 2024). Through large-scale pre-training under this masked modeling paradigm, these models acquire general-purpose representations that adapt efficiently to diverse downstream tasks with minimal task-specific fine-tuning. Compared to encoder–decoder or decoder-only backbones (Wang et al., 2025a; Zhang et al., 2025), encoder-only TSFMs offer a compact and generalizable pre-training framework, making them a promising foundation for universal time series analysis.

Despite their empirical success, most encoder-only TSFMs rely on time-domain masked reconstruction as the sole pre-training objective (Figure 1), recovering missing values directly in the original signal space. However, real-world time series are inherently multi-scale: coarse low-frequency components coexist with fine high-frequency fluctuations and residual dynamics. Because low-frequency components typically dominate signal energy, time-domain reconstruction tends to bias learning toward smoother, large-scale patterns while under-emphasizing subtle yet informative high-frequency variations (Han et al., 2025). More fundamentally, multi-scale components are not independent (Li et al., 2025); they form a residual hierarchy whose interactions collectively compose the observed signal. However, time-domain masking provides no explicit supervision for disentangling scale-specific information or modeling cross-scale interactions, leaving compositional structure largely implicit and limiting representation expressiveness.

To address these limitations, we propose WaveFM, which learns to understand time series through (i) wavelet-decomposed multi-scale components and (ii) their composition into the original signal. Decomposition has been shown to reveal temporal patterns by separating signals across characteristic scales (Wu et al., 2021). In particular, the wavelet transform provides a principled multi-scale representation, expressing a time series as an approximation coefficient and a hierarchy of residual detail coefficients (Mallat, 1989). Its invertible structure yields a lossless mapping between coefficients and the original time series, making it well-suited for learning scale-wise information and cross-scale composition.

Building on this property, we propose a **scale coefficient attention (SCA)** mechanism that captures (i) hierarchical dependencies across scales and (ii) temporal dynamics within each scale. **Masked coefficient reconstruction** trains the model to recover missing coefficients at each scale, providing supervision for scale-wise disentanglement and residual composition. This approach not only complements the time-domain reconstruction but also achieves a comprehensive understanding of time series by modeling the composition among multi-scale components. Lastly, **scale energy ratio distribution calibration** guides the model to capture the scale-wise energy distribution of the time series. Together, these components introduce explicit self-supervisory signals for multi-scale disentanglement and cross-scale residual composition, mitigating over-smoothing of high-frequency dynamics and yielding more transferable representations for downstream tasks. Our experiments on long-horizon forecasting and imputation show consistent improvements over encoder-only TSFM baselines, highlighting the importance of explicit multi-scale decomposition.

## 2 WAVEFM METHODOLOGY

### 2.1 OVERVIEW

Figure 2 summarizes WaveFM, which pre-trains an encoder-only TSFM by masked reconstruction in the wavelet domain. Given an input window, a multi-level wavelet transform is applied to obtain one low-frequency approximation stream and multiple high-frequency detail streams. Each coefficient stream is patchified, embedded, and randomly masked. The resulting tokens are processed by scale-coefficient attention blocks that model interactions across scales and temporal dependencies within each scale. The model reconstructs the masked coefficient patches and maps them back to the time domain via the inverse wavelet transform. WaveFM is pre-trained under the three objectives: masked coefficient reconstruction, time-domain reconstruction, and scale energy ratio distribution calibration that learns the wavelet energy allocation of the input window.

### 2.2 WAVELET TRANSFORM AND TOKENIZATION

For each input window $\mathbf{x} \in \mathbb{R}^T$, apply an $L$-level wavelet transform $\mathcal{W}_L$ and obtain an approximation coefficient vector $\mathbf{a}^{(L)}$ and detail coefficient vectors $\{\mathbf{d}^{(\ell)}\}_{\ell=1}^L$. The set of coefficient streams is denoted as $\mathcal{S} = \{a^{(L)}, d^{(L)}, \ldots, d^{(1)}\}$ and write $\{\mathbf{c}_s\}_{s \in \mathcal{S}} = \mathcal{W}_L(\mathbf{x})$. The inverse wavelet transform satisfies $\mathbf{x} = \mathcal{W}_L^{-1}(\{\mathbf{c}_s\}_{s \in \mathcal{S}})$. Each stream $s \in \mathcal{S}$ is patchified into $N$ patches using a scale-dependent patch length $P_s = |\mathbf{c}_s|/N$, so that the number of patches is consistent across scales. Let $\mathbf{p}_{s,i} = \mathcal{P}_s(\mathbf{c}_s)_i$ for $i = 1, \ldots, N$ denote the $i$-th patch from stream $s$. Each patch is embedded with a stream-specific embedding layer $E_s$ as $\mathbf{z}_{s,i} = E_s(\mathbf{p}_{s,i}) \in \mathbb{R}^D$. Random masking is applied independently per stream by setting the embeddings of masked patches

Figure 2: Overview of the proposed WaveFM pre-training framework.

to zero. Also, a learnable stream summary token (SST) is added to every stream to learn how much each stream contributes to compose the time series. The SST token acts as a stream-level summary representation, denoted as $\mathbf{z}_{s,0} = \mathbf{z}_{\text{SST}}^{(s)} \in \mathbb{R}^D$. The final token sequence for stream $s$ is $\tilde{\mathbf{Z}}_s = [\tilde{\mathbf{z}}_{s,0}; \tilde{\mathbf{z}}_{s,1}; \dots; \tilde{\mathbf{z}}_{s,N}] \in \mathbb{R}^{(N+1)\times D}$. Additional background on wavelet transform is provided in Appendix A.

### 2.3 SCALE COEFFICIENT ATTENTION

To understand time series, a model should capture two complementary structures within time series: (1) compositional dependencies across multi-scale patterns and (2) temporal dependencies within each scale. Since each coefficient stream provides only a partial context of the underlying signal, patches across coefficients are statistically dependent; their dependencies must be integrated to reconstruct the time series. The model is therefore required to learn how coefficients jointly compose the time series, while also modeling temporal dynamics within each scale. Thus, we propose a scale coefficient attention (SCA) mechanism, consisting of (i) cross-scale embedding and (ii) coefficient attention. A sequence of patches across scales at the patch index $i$ is defined as $\tilde{\mathbf{Z}}_i = \left[\tilde{\mathbf{z}}_{s,i}\right]_{s \in \mathcal{S}} \in \mathbb{R}^{|\mathcal{S}|\times D}, i = 0, \dots, N$. Then, the SCA mechanism is formulated as

$$\mathbf{H}_i^{\text{scale}} = \text{CrossScaleEmb}\big(\tilde{\mathbf{Z}}_i\big) = \text{MHA}\big(\tilde{\mathbf{Z}}_i, \tilde{\mathbf{Z}}_i, \tilde{\mathbf{Z}}_i\big) \in \mathbb{R}^{|\mathcal{S}|\times D}. \tag{1}$$

$$\mathbf{H}_s^{\text{coef}} = \text{MHA}\big(\mathbf{H}_s^{\text{scale}}, \tilde{\mathbf{Z}}_s, \tilde{\mathbf{Z}}_s\big) \in \mathbb{R}^{(N+1)\times D}. \tag{2}$$

where $\mathbf{H}_s^{\text{scale}} \in \mathbb{R}^{(N+1)\times D}, \forall s \in \mathcal{S}$. Specifically, SCA constructs a cross-scale embedding that aggregates information across resolutions and encodes inter-scale relations by applying self-attention to $\tilde{\mathbf{Z}}_i$, yielding $\mathbf{H}_i^{\text{scale}}$. The outputs $\mathbf{H}_i^{\text{scale}}$ are rearranged into per-stream sequences $\mathbf{H}_s^{\text{scale}}$, providing each token with inter-scale contexts. Then, the coefficient attention integrates the multi-scale and within-scale dependencies encoded in wavelet coefficients. In particular, the coefficient attention defines the per-stream sequence of the cross-scale embeddings as queries and the original stream tokens $\tilde{\mathbf{Z}}_s$ as keys and values. It produces contextualized representations that align cross-scale contexts in $\mathbf{H}_s^{\text{scale}}$ with stream-specific content in $\tilde{\mathbf{Z}}_s$, thereby capturing the compositional structure of the underlying temporal dynamics.

### 2.4 SCALE ENERGY RATIO DISTRIBUTION

Time series are composed of multi-scale components, and the relative importance of each coefficient stream to the original signal can vary substantially across windows. Without an explicit constraint, masked reconstruction can over-rely on dominant low-frequency streams and fail to leverage

Table 1: **Long-horizon forecasting.** MAE/MSE averaged over horizons {96,192,336,720}.

| Dataset | WaveFM-small | | WaveFM-base | | MOMENT | | LPTM | |
|---|---|---|---|---|---|---|---|---|
| | MAE | MSE | MAE | MSE | MAE | MSE | MAE | MSE |
| ETTh1 | 0.4424 | 0.4275 | **0.4374** | **0.4189** | 0.4529 | 0.4442 | 0.4690 | 0.4740 |
| ETTh2 | 0.3919 | 0.3492 | **0.3909** | **0.3446** | 0.4006 | 0.3585 | 0.4029 | 0.3675 |
| ETTm1 | 0.3886 | 0.3733 | 0.3876 | 0.3701 | 0.3952 | 0.3798 | **0.3869** | **0.3653** |
| ETTm2 | 0.3177 | 0.2586 | **0.3153** | **0.2565** | 0.3246 | 0.2627 | 0.3216 | 0.2622 |
| Electricity | 0.2594 | 0.1653 | **0.2590** | **0.1653** | 0.2987 | 0.1973 | 0.2724 | 0.1739 |
| Weather | 0.2778 | 0.2401 | 0.2789 | 0.2411 | 0.2871 | 0.2472 | **0.2776** | **0.2375** |

Table 2: **Imputation.** MAE/MSE averaged over mask ratios {0.125, 0.25, 0.375, 0.5}.

| Dataset | WaveFM-small | | WaveFM-base | | MOMENT | |
|---|---|---|---|---|---|---|
| | MSE | MAE | MSE | MAE | MSE | MAE |
| ETTh1 | 0.234 | 0.223 | **0.206** | **0.217** | 0.698 | 0.581 |
| ETTh2 | 0.074 | 0.132 | **0.065** | **0.126** | 0.287 | 0.370 |
| ETTm1 | **0.173** | 0.192 | 0.189 | **0.190** | 0.405 | 0.423 |
| ETTm2 | **0.058** | **0.112** | 0.059 | **0.112** | 0.143 | 0.255 |
| Electricity | 0.179 | 0.246 | **0.156** | **0.224** | 0.181 | 0.307 |
| Weather | **0.052** | **0.091** | 0.056 | 0.092 | 0.096 | 0.157 |

fine-scale details. To capture and calibrate this scale-allocation behavior, the wavelet energy ratio distribution is used as a compact, window-level summary of how signal energy is allocated across coefficient streams. For each stream $s \in \mathcal{S}$ with coefficients $\mathbf{c}_s$, the energy ratio is defined as $r_s = \|\mathbf{c}_s\|_2^2 / \sum_{s \in \mathcal{S}} \|\mathbf{c}_s\|_2^2$, and collect $\mathbf{r} = (r_s)_{s \in \mathcal{S}}$ with $\sum_{s \in \mathcal{S}} r_s = 1$. By Parseval's theorem for orthonormal wavelets, $r_s$ is the fraction of the window's time-domain energy carried by stream $s$. Therefore, windows containing sharp or localized events typically concentrate energy in high-frequency detail streams, making $\mathbf{r}$ a useful indicator of when fine-scale is informative for time series composition. The $\mathbf{r}$ is leveraged as an auxiliary regularizer during training to calibrate the model's scale allocation, as specified in the pre-training objective.

## 2.5 PRE-TRAINING OBJECTIVES

**Masked Coefficient Reconstruction:** In pre-training, a lightweight reconstruction head is applied per coefficient stream. For each stream $s \in \mathcal{S}$, the masked patch $\hat{\mathbf{p}}_{s,i}$ is reconstructed from the encoded token using a stream-specific head $g_s$, and unpatchify the patches to obtain reconstructed coefficients $\{\hat{\mathbf{c}}_s\}_{s \in \mathcal{S}}$. First, the reconstruction of the masked wavelet coefficients is supervised, providing scale-separated learning signals so that each scale is learned explicitly rather than only through an aggregated time-domain objective, $\mathcal{L}_{\text{coef}} = \sum_{s \in \mathcal{S}} \sum_{i=1}^{N} m_{s,i} \|\hat{\mathbf{p}}_{s,i} - \mathbf{p}_{s,i}\|_2^2$. This scale-separated supervision complements the bias of time-domain reconstruction toward low-frequency structure and improves sensitivity to fine-scale dynamics.

**Time-domain Reconstruction:** The reconstructed coefficient streams are composed via the inverse wavelet transform to obtain a time-domain reconstruction $\hat{\mathbf{x}}$, and minimize a reconstruction loss against the input time series: $\mathcal{L}_{\text{time}} = \|\hat{\mathbf{x}} - \mathbf{x}\|_2^2$, where $\hat{\mathbf{x}} = \mathcal{W}_L^{-1}(\{\hat{\mathbf{c}}_s\}_{s \in \mathcal{S}})$.

**Scale Energy Ratio Distribution Calibration:** Finally, the model's scale allocation is calibrated by aligning a predicted scale-importance distribution with the ground truth scale energy ratio distribution. Stream-level representations are obtained by taking the SST token outputs from each coefficient stream, $\mathbf{h}_{\mathcal{S}} = \left[\mathbf{h}_{s,0}^{\text{coef}}\right]_{s \in \mathcal{S}} \in \mathbb{R}^{|\mathcal{S}| \times D}$, and scale energy importance is predicted as $\hat{\mathbf{r}} = \text{Softmax}(g_{er}(\mathbf{h}_{\mathcal{S}}))$, where $g_{er}$ is a linear head. The KL-divergence $\mathcal{L}_{\text{ER}} = D_{\text{KL}}(\mathbf{r} \,\|\, \hat{\mathbf{r}})$ is then minimized. This calibration is particularly helpful for windows with localized events, where energy concentrates in high-frequency details, encouraging the model to preserve high-frequency details that time-domain reconstruction alone tends to smooth out. The overall pre-training objectives of WaveFM are $\mathcal{L} = \mathcal{L}_{\text{coef}} + \mathcal{L}_{\text{time}} + \mathcal{L}_{\text{ER}}$.

## 3 EXPERIMENTS

We evaluate WaveFM against encoder-only TSFM baselines on two time series tasks, to test whether wavelet decomposed masked reconstruction yields transferable representations. For forecasting, we fine-tune all models with a lightweight forecasting head under different horizons. For imputation, we evaluate WaveFM in a zero-shot setting, while MOMENT is fine-tuned on the pre-training head. Full settings on pre-training, model parameters, and downstream tasks are provided in Appendix C.

**Long-horizon forecasting.** Overall, WaveFM achieves consistently lower errors than encoder-only TSFM baselines across datasets, indicating that wavelet domain pre-training improves long-range predictive representations. The gains are particularly visible on datasets where fine-scale

variations and regime changes are important, supporting our motivation that explicitly modeling multi-scale components benefits forecasting. Full experiment result is provided in Table 8.

**Imputation.** WaveFM shows strong zero-shot imputation performance, substantially improving over the TSFM baseline across diverse datasets. We attribute this to scale-separated coefficient reconstruction and cross-scale composition learning during pre-training, which encourages sensitivity to fine-grained dynamics that are often over-smoothed by the time-domain reconstruction objective. Notably, WaveFM remains competitive even in a zero-shot setting, suggesting that the learned representations transfer well to reconstruction without data-specific adaptation. Full experiment result is provided in Table 9.

## 4    CONCLUSION AND FUTURE WORKS

In this paper, we propose WaveFM, a wavelet domain multi-scale TSFM. WaveFM learns to understand how time series is decomposed into scale-separated wavelet streams and explicitly learns how these multi-scale components recompose into the original time series via the inverse wavelet transform. By combining masked coefficient reconstruction, scale coefficient attention, and an energy ratio distribution calibration, WaveFM provides a composition-aware self-supervisory signal that complements standard time-domain masked reconstruction. Across long-horizon forecasting and imputation benchmarks, WaveFM consistently improves over strong encoder-only TSFM baselines, supporting the importance of explicitly modeling multi-scale components for time series understanding and transferable representations.

For future work, we will further validate the time-series understanding learned by WaveFM through broader multi-task evaluations. Beyond long-horizon forecasting and imputation, we will extend our experiments to additional downstream tasks, including anomaly detection, short-term forecasting, and classification. We will also investigate how scale energy ratio distribution can be incorporated into downstream tasks as task-relevant signals, providing additional supervision or inductive bias tailored to each task.

## REFERENCES

Alexander Alexandrov, Konstantinos Benidis, Michael Bohlke-Schneider, Valentin Flunkert, Jan Gasthaus, Tim Januschowski, Danielle C. Maddix, Syama Rangapuram, David Salinas, Jasper Schulz, Lorenzo Stella, Ali Caner Türkmen, and Yuyang Wang. Gluonts: Probabilistic and neural time series modeling in python. *Journal of Machine Learning Research*, 21(116):1–6, 2020. URL `http://jmlr.org/papers/v21/19-820.html`.

Abdul Fatir Ansari, Lorenzo Stella, Ali Caner Turkmen, Xiyuan Zhang, Pedro Mercado, Huibin Shen, Oleksandr Shchur, Syama Sundar Rangapuram, Sebastian Pineda Arango, Shubham Kapoor, et al. Chronos: Learning the language of time series. *Transactions on Machine Learning Research*, 2024.

Anthony Bagnall, Hoang Anh Dau, Jason Lines, Michael Flynn, James Large, Aaron Bostrom, Paul Southam, and Eamonn Keogh. The uea multivariate time series classification archive, 2018. *arXiv preprint arXiv:1811.00075*, 2018.

Yanlong Chen, Mattia Orlandi, Pierangelo Maria Rapa, Simone Benatti, Luca Benini, and Yawei Li. Physiowave: A multi-scale wavelet-transformer for physiological signal representation. *Advances in Neural Information Processing Systems*, 2025.

Mingyue Cheng, Qi Liu, Zhiding Liu, Hao Zhang, Rujiao Zhang, and Enhong Chen. Timemae: Self-supervised representations of time series with decoupled masked autoencoders. *arXiv preprint arXiv:2303.00320*, 2023.

Charles R Cornish, Christopher S Bretherton, and Donald B Percival. Maximal overlap wavelet statistical analysis with application to atmospheric turbulence. *Boundary-Layer Meteorology*, 119(2):339–374, 2006.

Hoang Anh Dau, Eamonn Keogh, Kaveh Kamgar, Chin-Chia Michael Yeh, Yan Zhu, Shaghayegh Gharghabi, Chotirat Ann Ratanamahatana, Yanping, Bing Hu, Nurjahan Begum, Anthony Bagnall, Abdullah Mueen, Gustavo Batista, and Hexagon-ML. The ucr time series classification archive, October 2018. `https://www.cs.ucr.edu/~eamonn/time_series_data_2018/`.

Patrick Emami, Abhijeet Sahu, and Peter Graf. Buildingsbench: A large-scale dataset of 900k buildings and benchmark for short-term load forecasting. *Advances in Neural Information Processing Systems*, 36:19823–19857, 2023.

Rakshitha Godahewa, Christoph Bergmeir, Geoffrey I. Webb, Rob J. Hyndman, and Pablo Montero-Manso. Monash time series forecasting archive. In *Neural Information Processing Systems Track on Datasets and Benchmarks*, 2021.

Mononito Goswami, Konrad Szafer, Arjun Choudhry, Yifu Cai, Shuo Li, and Artur Dubrawski. Moment: a family of open time-series foundation models. In *Proceedings of the 41st International Conference on Machine Learning*, pp. 16115–16152, 2024.

Haokun Gui, Xiucheng Li, and Xinyang Chen. Vector quantization pretraining for eeg time series with random projection and phase alignment. In *International Conference on Machine Learning*, pp. 16731–16750. PMLR, 2024.

Tiantian Guo, Tongpo Zhang, Enggee Lim, Miguel López-Benítez, Fei Ma, and Limin Yu. A review of wavelet analysis and its applications: Challenges and opportunities. *IEEE Access*, 10:58869–58903, 2022. doi: 10.1109/ACCESS.2022.3179517.

Yudong Han, Haocong Wang, Yupeng Hu, Yongshun Gong, Xuemeng Song, and Weili Guan. Content-aware balanced spectrum encoding in masked modeling for time series classification. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 17059–17067, 2025.

Jiawei Jiang, Chengkai Han, Wenjun Jiang, Wayne Xin Zhao, and Jingyuan Wang. Libcity: A unified library towards efficient and comprehensive urban spatial-temporal prediction. *arXiv preprint arXiv:2304.14343*, 2023.

Gregory Lee, Ralf Gommers, Filip Waselewski, Kai Wohlfahrt, and Aaron O'Leary. Pywavelets: A python package for wavelet analysis. *Journal of Open Source Software*, 4(36):1237, 2019.

Jae-Neung Lee, Myung-Won Lee, Yeong-Hyeon Byeon, Won-Sik Lee, and Keun-Chang Kwak. Classification of horse gaits using fcm-based neuro-fuzzy classifier from the transformed data information of inertial sensor. *Sensors*, 16(5):664, 2016.

Beibu Li, Qichao Shentu, Yang Shu, Hui Zhang, Ming Li, Ning Jin, Bin Yang, and Chenjuan Guo. Crossad: Time series anomaly detection with cross-scale associations and cross-window modeling. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025.

Zhe Li, Zhongwen Rao, Lujia Pan, Pengyun Wang, and Zenglin Xu. Ti-mae: Self-supervised masked time series autoencoders. *arXiv preprint arXiv:2301.08871*, 2023.

Yong Liu, Haoran Zhang, Chenyu Li, Xiangdong Huang, Jianmin Wang, and Mingsheng Long. Timer: generative pre-trained transformers are large time series models. In *Proceedings of the 41st International Conference on Machine Learning*, pp. 32369–32399, 2024.

S.G. Mallat. A theory for multiresolution signal decomposition: the wavelet representation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 11(7):674–693, 1989. doi: 10.1109/34.192463.

Luca Masserano, Abdul Fatir Ansari, Boran Han, Xiyuan Zhang, Christos Faloutsos, Michael W Mahoney, Andrew Gordon Wilson, Youngsuk Park, Syama Sundar Rangapuram, Danielle C Maddix, et al. Enhancing foundation models for time series forecasting via wavelet-based tokenization. In *Forty-second International Conference on Machine Learning*, 2024.

Md Mahmuddun Nabi Murad, Mehmet Aktukmak, and Yasin Yilmaz. Wpmixer: Efficient multiresolution mixing for long-term time series forecasting. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 19581–19588, 2025.

John Paparrizos, Yuhao Kang, Paul Boniol, Ruey S Tsay, Themis Palpanas, and Michael J Franklin. Tsb-uad: an end-to-end benchmark suite for univariate time-series anomaly detection. *Proceedings of the VLDB Endowment*, 15(8):1697–1711, 2022.

Harshavardhan Prabhakar Kamarthi and B Aditya Prakash. Large pre-trained time series models for cross-domain time series analysis tasks. *Advances in Neural Information Processing Systems*, 37:56190–56214, 2024.

Xiaoming Shi, Shiyu Wang, Yuqi Nie, Dianqi Li, Zhou Ye, Qingsong Wen, and Ming Jin. Time-moe: Billion-scale time series foundation models with mixture of experts. In *The Thirteenth International Conference on Learning Representations*, 2024.

Ariel Slepyan, Michael Zakariaie, Trac Tran, and Nitish Thakor. Wavelet transforms significantly sparsify and compress tactile interactions. *Sensors*, 24(13):4243, 2024.

Christopher Torrence and Gilbert P Compo. A practical guide to wavelet analysis. *Bulletin of the American Meteorological society*, 79(1):61–78, 1998.

Wenxuan Wang, Kai Wu, Yujian Betterest Li, Dan Wang, and Xiaoyu Zhang. Synthetic series-symbol data generation for time series foundation models. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025a.

Yubo Wang, Hui He, Chaoxi Niu, and Zhendong Niu. Wavetuner: Comprehensive wavelet subband tuning for time series forecasting. *arXiv preprint arXiv:2511.18846*, 2025b.

Gerald Woo, Chenghao Liu, Akshat Kumar, and Doyen Sahoo. Pushing the limits of pre-training for time series forecasting in the cloudops domain. *arXiv preprint arXiv:2310.05063*, 2023.

Gerald Woo, Chenghao Liu, Akshat Kumar, Caiming Xiong, Silvio Savarese, and Doyen Sahoo. Unified training of universal time series forecasting transformers. In *Proceedings of the 41st International Conference on Machine Learning*, pp. 53140–53164, 2024.

Haixu Wu, Jiehui Xu, Jianmin Wang, and Mingsheng Long. Autoformer: Decomposition transformers with auto-correlation for long-term series forecasting. *Advances in neural information processing systems*, 34:22419–22430, 2021.

Shifeng Xie, Vasilii Feofanov, Marius Alonso, Ambroise Odonnat, Jianfeng Zhang, Themis Palpanas, and Ievgen Redko. Cauker: classification time series foundation models can be pretrained on synthetic data only. *arXiv preprint arXiv:2508.02879*, 2025.

Xiaoxiao Yang, Xiaojiao Chen, Kezhong Sun, Chuanyu Xiong, Dongran Song, Yingchun Lu, Liansheng Huang, Shiying He, and Xiuqing Zhang. A wavelet transform-based real-time filtering algorithm for fusion magnet power signals and its implementation. *Energies*, 16(10):4091, 2023.

Haoran Zhang, Yong Liu, Yunzhong Qiu, Haixuan Liu, Zhongyi Pei, Jianmin Wang, and Mingsheng Long. Timesbert: A bert-style foundation model for time series understanding. In *Proceedings of the 33rd ACM International Conference on Multimedia*, pp. 10975–10983, 2025.

## A    WAVELET TRANSFORM

Wavelets provide a multi-resolution view of a signal by decomposing it into one coarse component and a sequence of residual components at progressively finer temporal scales (Mallat, 1989). In our setting, an $L$-level discrete wavelet transform (DWT) maps an input window $\mathbf{x} \in \mathbb{R}^T$ to an approximation coefficient stream $\mathbf{a}^{(L)}$ and detail coefficient streams $\{\mathbf{d}^{(\ell)}\}_{\ell=1}^L$ (Figure 3), where $\mathbf{a}^{(L)}$ summarizes the low-frequency trend and each $\mathbf{d}^{(\ell)}$ captures scale-specific fluctuations relative to the coarser representation. These coefficient streams are the multi-scale inputs used by WaveFM, as described in the main paper.

Figure 3: Wavelet transform. The multi-level discrete wavelet transform decomposes the input time series into one low-frequency approximation stream and multiple high-frequency detail streams, providing scale-separated representations.

**Forward transform $\mathcal{W}_L$.**    Let $h[\cdot]$ and $g[\cdot]$ denote the low-pass and high-pass analysis filters associated with a chosen wavelet family, and define the level-0 approximation coefficients as $\mathbf{a}^{(0)} = \mathbf{x}$. For each level $\ell = 1, \ldots, L$, the DWT applies filtering followed by dyadic downsampling to produce the next approximation stream and the corresponding detail stream:

$$a^{(\ell)}[k] = \sum_n h[n - 2k]\, a^{(\ell-1)}[n], \qquad d^{(\ell)}[k] = \sum_n g[n - 2k]\, a^{(\ell-1)}[n].$$

The resulting coefficient set is

$$\mathcal{W}_L(\mathbf{x}) = \left( \mathbf{a}^{(L)}, \{\mathbf{d}^{(\ell)}\}_{\ell=1}^L \right), \qquad \mathcal{S} = \{\mathbf{a}^{(L)}, \mathbf{d}^{(L)}, \ldots, \mathbf{d}^{(1)}\}.$$

**Choice of wavelet basis.**    In our implementation, we use symlet-4 (`sym4`) as the default wavelet basis. Symlets offer a favorable trade-off between time localization and frequency selectivity via moderately long, near-symmetric filters, which helps reduce phase distortion and boundary artifacts in discrete-time signals(Slepyan et al., 2024). Compared to shorter bases such as haar, sym4 provides smoother approximation streams and more stable detail coefficients, while remaining computationally lightweight compared to higher-order bases(Cornish et al., 2006). Empirically, this choice yields robust multi-scale coefficient representations across diverse time series domains without introducing excessive filter length or sensitivity to edge effects (Guo et al., 2022).

**Incremental information across levels.**    The multi-level construction of $\mathcal{W}_L$ can be viewed as an incremental information process; at each level $\ell$, the approximation $\mathbf{a}^{(\ell)}$ provides a progressively coarser summary of $\mathbf{x}$, while the detail coefficients $\mathbf{d}^{(\ell)}$ capture the information discarded by the low-pass downsampled approximation when moving from level $\ell - 1$ to $\ell$(Lee et al., 2016). Intuitively, $\mathbf{d}^{(\ell)}$ encodes the residual information needed to refine $\mathbf{a}^{(\ell)}$ back toward $\mathbf{a}^{(\ell-1)}$. Collecting details across levels, therefore, yields a hierarchy of residual streams, from coarse-to-fine, that together characterize temporal dynamics at multi-scale.

**Coefficient lengths and scale interpretation.** Each level downsamples by a factor of 2, so the temporal resolution decreases with $\ell$. With common boundary extension rules, coefficient lengths scale on the order of $T/2^\ell$:

$$|\mathbf{a}^{(\ell)}| \approx \left\lceil \tfrac{T}{2^\ell} \right\rceil, \qquad |\mathbf{d}^{(\ell)}| \approx \left\lceil \tfrac{T}{2^\ell} \right\rceil,$$

where exact lengths depend on the extension mode and the wavelet filter length (Lee et al., 2019). Thus, $\mathbf{a}^{(L)}$ represents the coarsest trend over the entire window, while $\mathbf{d}^{(1)}$ captures the finest-scale residual variations. This motivates using scale-dependent patch lengths $P_s$ in WaveFM so that each stream produces the same number of patches $N$ despite different native resolutions.

**Inverse transform $\mathcal{W}_L^{-1}$ and perfect reconstruction.** Let $\tilde{h}[\cdot]$ and $\tilde{g}[\cdot]$ denote the low-pass and high-pass synthesis filters. For $\ell = L, \ldots, 1$, the inverse recursion reconstructs $\mathbf{a}^{(\ell-1)}$ from $\mathbf{a}^{(\ell)}$ and $\mathbf{d}^{(\ell)}$ by dyadic upsampling and filtering:

$$a^{(\ell-1)}[n] = \sum_k \tilde{h}[n - 2k]\, a^{(\ell)}[k] + \sum_k \tilde{g}[n - 2k]\, d^{(\ell)}[k].$$

Applying this recursion from $\ell = L$ down to $\ell = 1$ yields the inverse mapping

$$\mathbf{x} = \mathcal{W}_L^{-1}\Big(\mathbf{a}^{(L)}, \{\mathbf{d}^{(\ell)}\}_{\ell=1}^L\Big).$$

If $(h, g, \tilde{h}, \tilde{g})$ form a perfect reconstruction filter bank and the same extension rule is used in analysis and synthesis, then $\mathcal{W}_L^{-1}\big(\mathcal{W}_L(\mathbf{x})\big) = \mathbf{x}$ holds up to numerical precision.

**Boundary handling.** Because filtering requires samples beyond the finite window, practical DWT implementations adopt a boundary extension rule (periodic or symmetric extension) (Yang et al., 2023). In WaveFM, $\mathcal{W}_L$ and $\mathcal{W}_L^{-1}$ use the same boundary handling so that reconstruction remains stable and coefficient streams align consistently across windows.

## B  RELATED WORKS

### B.1  ENCODER-ONLY TSFMs

Encoder-only TSFMs typically follow a BERT-style pre-training paradigm (Gui et al., 2024), where a Transformer encoder learns transferable representations by reconstructing masked portions of a time series or its patch tokens from the surrounding bidirectional context (Cheng et al., 2023). This enables strong adaptation to diverse downstream tasks. TimesBERT follows this encoder-only design for multivariate time series and pre-trains with masked patch modeling and additional objectives to improve transfer across datasets and tasks (Zhang et al., 2025). Ti-MAE uses masked autoencoding over tokenized time series and shows that reconstruction-based pre-training can learn useful representations for forecasting and classification while reducing the gap between pre-training and downstream objectives (Li et al., 2023). LPTM further explores pre-training with adaptive segmentation so that the model can form consistent tokens across different datasets, improving transfer under fine-tuning and in zero-shot settings (Prabhakar Kamarthi & Prakash, 2024). Together, these results support encoder-only backbones as efficient foundation models for time series representation learning when broad transfer is preferred over autoregressive generation. However, time-domain masked reconstruction fails to explicitly disentangle scale-specific information and supervise cross-scale interactions required to compose the original signal. We address this problem with wavelet domain masked coefficient reconstruction. Scale-coefficient attention (SCA) aggregates information across scales and time, and complements masked coefficient reconstruction by modeling how multi-scale components jointly compose the original time series.

### B.2  WAVELET TRANSFORM ON TIME SERIES ANALYSIS

Wavelet transform is a classical tool for time-series analysis providing multi-resolution time-frequency localization, enabling signals with temporal structure to be decomposed into approximation and detail coefficients for scale-wise inspection (Torrence & Compo, 1998). Recent time series analysis models adopt this property in different ways. For forecasting, WaveTuner performs wavelet

decomposition and learns an adaptive router that assigns importance weights to sub-bands, explicitly emphasizing informative frequency components to improve forecasting performance (Wang et al., 2025b). Similarly, WPMixer decomposes an input series and processes each resolution in a dedicated branch, leveraging multi-resolution mixing to enhance long-horizon forecasting (Murad et al., 2025). In a foundation model approach, WaveToken uses a decimated DWT as a tokenizer by quantizing wavelet coefficients and pretraining an autoregressive model directly in the space of time-localized frequencies, targeting general-purpose forecasting (Masserano et al., 2024). For representation learning on biosignals, PhysioWave introduces a learnable wavelet decomposition pipeline to adaptively capture heterogeneous, non-stationary physiological dynamics during self-supervised pretraining (Chen et al., 2025). While these works demonstrate that wavelet transforms are useful intermediate representations, most of them optimize task-driven objectives such as forecasting; however, they do not explicitly model how within-scale structure and cross-scale interactions compose the time series. Our approach addresses this gap by pre-training with masked coefficient reconstruction coupled with explicit inverse wavelet transform, thereby encouraging the model to learn how multi-scale components jointly explain the time series.

## C  EXPERIMENT SETTINGS

### C.1  PRE-TRAINING DATASETS

WaveFM is pre-trained on a diverse set of public time-series datasets, including subsets from Monash (Godahewa et al., 2021), UEA/UCR (Bagnall et al., 2018; Dau et al., 2018), and TSB-UAD (Paparrizos et al., 2022). Also, we include datasets provided by previously curated large-scale collections, UTSD (Liu et al., 2024), LOTSA (Woo et al., 2024), and Time Series Pile (Goswami et al., 2024), along with selected subsets from BuildingsBench (Emami et al., 2023), LibCity (Jiang et al., 2023), CloudOps (Woo et al., 2023), GluonTS (Alexandrov et al., 2020), and some other time series datasets (Ansari et al., 2024). In total, WaveFM is pre-trained on **29.18 GB** of data, comprising **2.61B** observations (timestamps × channels), as summarized in Tables 3–5. Following prior work, we convert multivariate series into channel-wise univariate sequences under a channel-independent setting (Shi et al., 2024; Xie et al., 2025).

Table 3: Pre-training datasets from Paparrizos et al. (2022).WaveFM is pre-trained on the training split of each dataset.

| Dataset | # Channels | # Obs. |
|---|---|---|
| ECG | 1 | 7,186,928 |
| KDD21 | 1 | 4,545,977 |
| IOPS | 1 | 1,802,408 |
| YAHOO | 1 | 343,451 |
| NAB | 1 | 219,249 |
| NASA-MSM | 1 | 118,215 |
| NASA-MSL | 1 | 49,949 |
| Occupancy | 1 | 14,655 |

### C.2  PRE-TRAINING SETTINGS

Pre-training uses the datasets in Appendix C.1 with fixed-length windows of 512 and a stride of 8. Each window is patchified into non-overlapping patches of length 8 (stride 8). We apply a 3-level discrete wavelet transform with the Symlet-4 basis (sym4), producing one approximation stream and three detail streams. For every wavelet coefficient stream, 30% of patches are randomly masked, and WaveFM is trained to reconstruct the missing coefficients; the reconstructed coefficients are then mapped back to the time domain via the inverse wavelet transform. All WaveFM variants are trained for 2 epochs, with architectural configurations, such as encoder layers, hidden size, and attention setup, summarized in Table 6.

Table 4: Pre-training datasets. We report the total number of time stamps (including channels).

| Dataset | # Obs. | Dataset | # Obs. |
|---|---|---|---|
| Residential_Load_Power | 437,983,677 | Health_PigArtPressure | 624,000 |
| Residential_Pv_Power | 376,016,850 | Health_PigCVP | 624,000 |
| Q-TRAFFIC | 264,386,688 | SZ_TAXI | 464,256 |
| Alibaba_Cluster_Trace_2018 | 190,385,060 | M5 | 457,350 |
| Wind_Farms_Minutely | 172,178,060 | Bdg-2_Hog | 421,056 |
| London_Smart_Meters | 166,528,896 | Godaddy | 257,070 |
| IoT_Baian | 165,361,266 | Nature_Worms | 232,200 |
| Kaggle_Web_Traffic | 116,485,589 | Hierarchical_Sales | 212,164 |
| Health_TDBrain_Csv | 73,299,996 | Cdc_Fluview_Who_Nrevss | 167,040 |
| Health_MotorImagery | 72,576,000 | Gfc17_Load | 140,352 |
| Health_BIDMC32HR | 63,592,000 | Car_Parts | 136,374 |
| Subseasonal | 56,788,560 | Tourism_Monthly | 109,280 |
| Taxi_30min | 54,999,056 | Smart | 95,709 |
| Weather | 43,032,000 | Traffic_Weekly | 89,648 |
| Wiki-rolling_Nips | 40,619,100 | Nn5_Daily | 87,801 |
| LOOP_SEATTLE | 33,953,760 | Borealis | 83,269 |
| Nature_EigenWorms | 27,947,136 | Fred_Md | 77,896 |
| PEMS07 | 24,921,792 | Bitcoin | 75,364 |
| Temperature_Rain | 23,252,200 | Sunspot | 73,924 |
| Dominick | 19,092,987 | Hospital | 64,428 |
| Environment_BenzeneConcentration | 16,343,040 | Covid_Deaths | 56,392 |
| PEMS04 | 15,649,632 | M1_Monthly | 55,998 |
| Health_IEEEPPG | 15,480,000 | Electricity_Weekly | 50,076 |
| Traffic_Hourly | 15,122,928 | Uber_Tlc_Daily | 47,087 |
| Environment_AustraliaRainfall | 11,539,224 | Tourism_Quarterly | 42,544 |
| Subseasonal_Precip | 9,760,426 | Vehicle_Trips | 42,382 |
| Nature_StarLightCurves | 9,457,664 | Health_AtrialFibrillation | 38,400 |
| PEMS03 | 9,382,464 | Spain | 35,064 |
| PEMS08 | 9,106,560 | Sceaux | 34,223 |
| Electricity_Hourly | 8,443,584 | Covid19_Energy | 31,912 |
| Solar_4_Seconds | 7,397,222 | Saugeenday | 23,741 |
| Energy_Wind_4_Seconds | 7,397,147 | Elf | 21,792 |
| Solar_10_Minutes | 7,200,720 | Bdg-2_Cockatoo | 17,544 |
| LOS_LOOP | 7,094,304 | Gfc14_Load | 17,520 |
| Bdg-2_Rat | 4,728,288 | Elecdemand | 17,520 |
| Environment_BeijingPM25Quality | 3,664,656 | Pdb | 17,520 |
| Pedestrian_Counts | 3,132,346 | M3_Other | 13,325 |
| Health_SelfRegulationSCP2 | 3,064,320 | Tourism_Yearly | 12,757 |
| Health_SelfRegulationSCP1 | 3,015,936 | Nn5_Weekly | 12,543 |
| Kdd_Cup_2018 | 2,942,364 | M1_Quarterly | 9,944 |
| Bdg-2_Fox | 2,324,568 | Us_Births | 7,305 |
| Nature_Phoneme | 2,160,640 | Solar_Weekly | 7,124 |
| Bdg-2_Bear | 1,482,312 | Cif_2016 | 7,108 |
| Ideal | 1,255,253 | M1_Yearly | 4,515 |
| Rideshare | 1,246,464 | HeartRate | 1,801 |
| Energy_Australian_Electricity_Demand | 1,155,264 | GasRateCO2 | 593 |
| Uber_Tlc_Hourly | 1,129,444 | AusBeer | 217 |
| Bdg-2_Panther | 919,800 | Wine | 182 |
| Oikolab_Weather | 800,456 | MonthlyMilk | 174 |
| Gfc12_Load | 788,280 | AirPassengers | 150 |
| Bdg-2_Bull | 719,304 | Wooly | 125 |

## C.3 FINE-TUNING SETTINGS

We keep the wavelet basis and decomposition level fixed to the pre-training configuration. We also report parameter sizes for each model in Table 7. Compared to MOMENT-base and LPTM, WaveFM-small and WaveFM-base use substantially fewer parameters, while achieving competitive performance.

**Long-horizon Forecasting.** We fine-tune the pre-trained WaveFM encoder for downstream tasks. For long-horizon forecasting, we attach a lightweight forecasting head for each wavelet stream, and train only the heads while keeping the encoder frozen. Each stream-specific head predicts the future wavelet coefficients for its corresponding stream, and the final forecast in the time domain is obtained by inverse wavelet transformation. To ensure a fair comparison, we freeze the pre-

Table 5: Classification datasets from Dau et al. (2018); Bagnall et al. (2018). We train on the training split of each dataset (including channels).

| Dataset | # Ch. | Time series Length | # Obs. |
|---|---|---|---|
| InsectWingbeat | 200 | 22 | 94,283,200 |
| MotorImagery | 64 | 3,000 | 45,696,000 |
| FaceDetection | 144 | 62 | 45,068,544 |
| PEMS-SF | 963 | 144 | 31,617,216 |
| DuckDuckGeese | 1,345 | 270 | 15,252,300 |
| EigenWorms | 6 | 17,984 | 11,761,536 |
| SpokenArabicDigits | 13 | 93 | 6,838,104 |
| PhonemeSpectra | 11 | 217 | 6,781,467 |
| Heartbeat | 61 | 405 | 4,298,670 |
| HandOutlines | 1 | 2,709 | 2,321,613 |
| FordB | 1 | 500 | 1,558,000 |
| FordA | 1 | 500 | 1,543,000 |
| SelfRegulationSCP2 | 7 | 1,152 | 1,378,944 |
| SelfRegulationSCP1 | 6 | 896 | 1,231,104 |
| EthanolConcentration | 3 | 1,751 | 1,171,419 |
| NonInvasiveFetalECGThorax1 | 1 | 750 | 1,156,500 |
| NonInvasiveFetalECGThorax2 | 1 | 750 | 1,156,500 |
| StarLightCurves | 1 | 1,024 | 877,568 |
| EthanolLevel | 1 | 1,751 | 756,432 |
| ElectricDevices | 1 | 96 | 734,400 |
| UWaveGestureLibraryAll | 1 | 945 | 725,760 |
| Cricket | 6 | 1,197 | 660,744 |
| PLAID | 1 | 1,344 | 618,240 |
| SemgHandSubjectCh2 | 1 | 1,500 | 577,500 |
| SemgHandMovementCh2 | 1 | 1,500 | 577,500 |
| HandMovementDirection | 10 | 400 | 548,000 |
| LSST | 6 | 36 | 455,112 |
| MixedShapesRegularTrain | 1 | 1,024 | 438,272 |
| EOGHorizontalSignal | 1 | 1,250 | 387,500 |
| EOGVerticalSignal | 1 | 1,250 | 387,500 |
| SemgHandGenderCh2 | 1 | 1,500 | 385,500 |
| FingerMovements | 28 | 50 | 378,000 |
| ArticularyWordRecognition | 9 | 144 | 304,560 |
| Crop | 1 | 46 | 283,866 |
| ShapesAll | 1 | 512 | 263,168 |
| UWaveGestureLibraryZ | 1 | 315 | 241,920 |
| UWaveGestureLibraryY | 1 | 315 | 241,920 |
| UWaveGestureLibraryX | 1 | 315 | 241,920 |
| LargeKitchenAppliances | 1 | 720 | 231,120 |
| ScreenType | 1 | 720 | 231,120 |
| SmallKitchenAppliances_Industrial | 1 | 720 | 231,120 |
| SmallKitchenAppliances | 1 | 720 | 231,120 |
| RefrigerationDevices | 1 | 720 | 231,120 |
| NATOPS | 24 | 51 | 188,496 |
| Phoneme | 1 | 1,024 | 187,392 |
| PigAirwayPressure | 1 | 2,000 | 178,000 |
| PigArtPressure | 1 | 2,000 | 178,000 |
| PigCVP | 1 | 2,000 | 178,000 |
| InlineSkate | 1 | 1,882 | 159,970 |
| Computers | 1 | 720 | 154,080 |
| Haptics | 1 | 1,092 | 144,144 |
| Earthquakes | 1 | 512 | 141,312 |
| Worms | 1 | 900 | 139,500 |
| WormsTwoClass | 1 | 900 | 139,500 |
| Wafer | 1 | 152 | 130,264 |
| ACSF1 | 1 | 1,460 | 124,100 |
| Strawberry | 1 | 235 | 123,375 |
| PhalangesOutlinesCorrect | 1 | 80 | 123,360 |
| TwoPatterns | 1 | 128 | 109,696 |
| Yoga | 1 | 426 | 109,482 |
| FiftyWords | 1 | 270 | 103,950 |
| PenDigits | 2 | 8 | 102,768 |
| CricketY | 1 | 300 | 100,200 |
| CricketZ | 1 | 300 | 100,200 |
| CricketX | 1 | 300 | 100,200 |
| StandWalkJump | 4 | 2,500 | 100,000 |
| AllGestureWiimoteX | 1 | 385 | 98,945 |
| UWaveGestureLibrary | 3 | 315 | 96,390 |
| AllGestureWiimoteY | 1 | 369 | 94,833 |
| MixedShapesSmallTrain | 1 | 1,024 | 87,040 |
| AllGestureWiimoteZ | 1 | 326 | 83,782 |
| OSULeaf | 1 | 427 | 73,017 |
| Epilepsy | 3 | 206 | 72,306 |
| JapaneseVowels | 12 | 26 | 72,072 |
| Fish | 1 | 463 | 69,450 |
| HouseTwenty | 1 | 2,000 | 68,000 |
| ChlorineConcentration | 1 | 166 | 66,400 |
| GestureMidAirD1 | 1 | 360 | 64,080 |
| GestureMidAirD2 | 1 | 360 | 64,080 |
| GestureMidAirD3 | 1 | 360 | 64,080 |

| Dataset | # Ch. | Time series Length | # Obs. |
|---|---|---|---|
| FaceAll | 1 | 131 | 62,880 |
| WordSynonyms | 1 | 270 | 61,560 |
| ECG5000 | 1 | 140 | 59,920 |
| Adiac | 1 | 176 | 58,784 |
| Handwriting | 3 | 152 | 58,368 |
| GesturePebbleZ2 | 1 | 455 | 56,875 |
| CinCECGTorso | 1 | 1,639 | 55,726 |
| SwedishLeaf | 1 | 128 | 54,784 |
| GesturePebbleZ1 | 1 | 455 | 51,415 |
| Rock | 1 | 2,844 | 48,348 |
| Mallat | 1 | 1,024 | 48,128 |
| InsectWingbeatSound | 1 | 256 | 48,128 |
| DistalPhalanxOutlineCorrect | 1 | 80 | 41,120 |
| ProximalPhalanxOutlineCorrect | 1 | 80 | 41,120 |
| MiddlePhalanxOutlineCorrect | 1 | 80 | 41,120 |
| Ham | 1 | 431 | 40,083 |
| FreezerRegularTrain | 1 | 301 | 38,528 |
| Lightning2 | 1 | 637 | 32,487 |
| MedicalImages | 1 | 99 | 32,274 |
| InsectEPGRegularTrain | 1 | 601 | 31,853 |
| Car | 1 | 577 | 29,427 |
| Herring | 1 | 512 | 27,648 |
| DistalPhalanxTW | 1 | 80 | 27,360 |
| MiddlePhalanxOutlineAgeGroup | 1 | 80 | 27,360 |
| ProximalPhalanxTW | 1 | 80 | 27,360 |
| ProximalPhalanxOutlineAgeGroup | 1 | 80 | 27,360 |
| MiddlePhalanxTW | 1 | 80 | 27,360 |
| DistalPhalanxOutlineAgeGroup | 1 | 80 | 27,360 |
| MelbournePedestrian | 1 | 24 | 24,552 |
| Trace | 1 | 275 | 23,375 |
| RacketSports | 6 | 30 | 23,220 |
| Meat | 1 | 448 | 22,848 |
| FacesUCR | 1 | 131 | 22,401 |
| PowerCons | 1 | 144 | 22,176 |
| BasicMotions | 6 | 100 | 20,400 |
| Lightning7 | 1 | 319 | 19,140 |
| DodgerLoopDay | 1 | 288 | 19,008 |
| GunPointOldVersusYoung | 1 | 150 | 17,400 |
| GunPointAgeSpan | 1 | 150 | 17,250 |
| GunPointMaleVersusFemale | 1 | 150 | 17,250 |
| ShakeGestureWiimoteZ | 1 | 385 | 16,170 |
| SyntheticControl | 1 | 60 | 15,420 |
| AtrialFibrillation | 2 | 640 | 15,360 |
| PickupGestureWiimoteZ | 1 | 361 | 15,162 |
| OliveOil | 1 | 570 | 14,250 |
| Libras | 2 | 45 | 13,860 |
| Plane | 1 | 144 | 12,960 |
| Beef | 1 | 470 | 11,750 |
| Wine | 1 | 234 | 11,232 |
| ToeSegmentation2 | 1 | 343 | 10,290 |
| DodgerLoopWeekend | 1 | 288 | 9,792 |
| ToeSegmentation1 | 1 | 277 | 9,418 |
| BirdChicken | 1 | 512 | 8,704 |
| BeetleFly | 1 | 512 | 8,704 |
| ShapeletSim | 1 | 500 | 8,500 |
| InsectEPGSmallTrain | 1 | 601 | 8,414 |
| Symbols | 1 | 398 | 8,358 |
| ECG200 | 1 | 96 | 8,160 |
| ArrowHead | 1 | 251 | 7,530 |
| FreezerSmallTrain | 1 | 301 | 7,224 |
| FaceFour | 1 | 350 | 7,000 |
| Coffee | 1 | 286 | 6,864 |
| ERing | 4 | 65 | 6,500 |
| GunPoint | 1 | 150 | 6,300 |
| DodgerLoopGame | 1 | 288 | 4,896 |
| UMD | 1 | 150 | 4,500 |
| DiatomSizeReduction | 1 | 345 | 4,485 |
| BME | 1 | 128 | 3,200 |
| CBF | 1 | 128 | 3,200 |
| Fungi | 1 | 201 | 3,015 |
| ECGFiveDays | 1 | 136 | 2,584 |
| SmoothSubspace | 1 | 15 | 1,920 |
| TwoLeadECG | 1 | 82 | 1,558 |
| SonyAIBORobotSurface2 | 1 | 65 | 1,495 |
| MoteStrain | 1 | 84 | 1,428 |
| ItalyPowerDemand | 1 | 24 | 1,368 |
| SonyAIBORobotSurface1 | 1 | 70 | 1,190 |
| Chinatown | 1 | 24 | 408 |

Table 6: WaveFM architectural configurations.

|  | WaveFM-small | WaveFM-base |
|---|---|---|
| Encoder layers | 3 | 6 |
| Hidden size ($d_{\mathrm{model}}$) | 256 | 512 |
| Attention heads | 4 | 8 |
| FFN size ($d_{\mathrm{ff}}$) | 1024 | 2048 |
| Dropout | 0.1 | 0.1 |

trained encoders for all baselines and train only their forecasting heads, while following the official hyperparameter setting for each baselines.

**Imputation.** For imputation, we evaluate WaveFM in a zero-shot setting using the pre-training reconstruction head, without any dataset-specific fine-tuning. We randomly mask a subset of time steps and the corresponding wavelet streams. Then, we reconstruct each wavelet coefficient from the observed context. For baseline, we freeze the pre-trained encoder and train only its task-specific head, following the official hyperparameter setting.

Table 7: Model size comparison in terms of the total number of parameters (in millions).

| Model | Params (M) |
|---|---|
| MOMENT-base | 109.64 |
| LPTM | 109.71 |
| WaveFM-small | 12.17 |
| WaveFM-base | 47.93 |

## D  VISUALIZATION

Figure 4: Reconstruction visualization. We visualize reconstruction outputs on three datasets (ETTh1, ETTm1, Electricity). The input time series is shown in black, and the model reconstruction is shown in red. The left column reports MOMENT reconstructions, and the right column reports WaveFM reconstructions.

Figure 4 provides qualitative evidence of how different pre-training objectives affect reconstruction behavior. Across ETTh1 and ETTm1, both models broadly follow the global trajectory, but clear differences emerge in local fluctuations and abrupt changes. On Electricity, which exhibits a strong

periodic structure with sharp peaks, the reconstructions highlight how well each model preserves oscillatory patterns and peak timing under the same input window. Overall, WaveFM learns how information across temporal scales complements to compose the original time series with masked coefficient reconstruction. It leverages coarse-scale context to disambiguate local variations while using fine-scale cues to recover short transitions and transient deviations that are often smoothed out when only using time-domain masked reconstruction.

# E  FULL RESULTS

Table 8: Long-horizon forecasting results.

| Dataset | Horizon | WaveFM-small | | WaveFM-base | | MOMENT-base | | LPTM | |
|---------|---------|------|------|------|------|------|------|------|------|
| | | MAE | MSE | MAE | MSE | MAE | MSE | MAE | MSE |
| ETTh1 | 96 | **0.4074** | **0.3891** | 0.4145 | 0.3948 | 0.4206 | 0.3973 | 0.4428 | 0.4367 |
| | 192 | **0.4238** | **0.4123** | 0.4275 | 0.4136 | 0.4364 | 0.4221 | 0.4542 | 0.4564 |
| | 336 | 0.4497 | 0.4332 | **0.4437** | **0.4265** | 0.4537 | 0.4456 | 0.4700 | 0.4695 |
| | 720 | 0.4888 | 0.4755 | **0.4639** | **0.4406** | 0.5010 | 0.5118 | 0.5090 | 0.5335 |
| ETTh2 | 96 | **0.3493** | 0.2942 | 0.3518 | **0.2932** | 0.3624 | 0.3093 | 0.3654 | 0.3240 |
| | 192 | **0.3826** | 0.3452 | 0.3835 | **0.3423** | 0.3948 | 0.3585 | 0.3968 | 0.3682 |
| | 336 | 0.4009 | 0.3612 | **0.4007** | **0.3581** | 0.4060 | 0.3642 | 0.4114 | 0.3754 |
| | 720 | 0.4350 | 0.3963 | **0.4274** | **0.3848** | 0.4393 | 0.4018 | 0.4381 | 0.4023 |
| ETTm1 | 96 | 0.3620 | 0.3257 | **0.3604** | 0.3215 | 0.3674 | 0.3276 | 0.3622 | **0.3190** |
| | 192 | 0.3785 | 0.3545 | 0.3769 | 0.3505 | 0.3849 | 0.3605 | **0.3764** | **0.3464** |
| | 336 | 0.3932 | 0.3816 | 0.3920 | 0.3778 | 0.4009 | 0.3904 | **0.3912** | **0.3732** |
| | 720 | 0.4206 | 0.4316 | 0.4209 | 0.4305 | 0.4278 | 0.4405 | **0.4176** | **0.4227** |
| ETTm2 | 96 | 0.2633 | 0.1752 | **0.2594** | **0.1714** | 0.2716 | 0.1824 | 0.2664 | 0.1795 |
| | 192 | 0.2966 | 0.2254 | **0.2936** | **0.2223** | 0.3046 | 0.2300 | 0.2989 | 0.2282 |
| | 336 | 0.3287 | 0.2744 | **0.3268** | **0.2728** | 0.3345 | 0.2782 | 0.3342 | 0.2797 |
| | 720 | 0.3823 | 0.3596 | **0.3815** | **0.3594** | 0.3878 | 0.3603 | 0.3871 | 0.3615 |
| Electricity | 96 | 0.2340 | **0.1370** | **0.2339** | **0.1370** | 0.2782 | 0.1724 | 0.2484 | 0.1466 |
| | 192 | 0.2464 | 0.1514 | **0.2461** | **0.1512** | 0.2877 | 0.1842 | 0.2605 | 0.1606 |
| | 336 | 0.2623 | **0.1669** | **0.2619** | **0.1669** | 0.3004 | 0.1979 | 0.2752 | 0.1755 |
| | 720 | 0.2949 | **0.2060** | **0.2942** | 0.2061 | 0.3285 | 0.2345 | 0.3054 | 0.2130 |
| Weather | 96 | **0.2215** | **0.1679** | 0.2233 | 0.1691 | 0.2351 | 0.1779 | 0.2242 | 0.1685 |
| | 192 | 0.2582 | 0.2119 | 0.2592 | 0.2126 | 0.2678 | 0.2192 | 0.2569 | **0.2082** |
| | 336 | 0.2926 | 0.2577 | 0.2932 | 0.2584 | 0.2996 | 0.2635 | **0.2911** | **0.2535** |
| | 720 | 0.3390 | 0.3229 | 0.3400 | 0.3243 | 0.3459 | 0.3283 | **0.3380** | **0.3198** |

**Long-horizon forecasting.**  Table 8  shows the full results of long-horizon forecasting.  Both WaveFM variants (small, base) achieve competitive performance despite a substantial difference in the number of parameters, indicating that wavelet-domain pre-training yields parameter-efficient representations for long-horizon forecasting. Moreover, training only with a lightweight forecasting head suggests that the frozen encoder representations already encode multi-scale structures of future long-horizon dynamics in the wavelet coefficient streams. This is likely because scale coefficient attention (SCA) captures cross-scale dependencies, allowing information to flow across temporal scales.

**Imputation.**  Table 9 shows the full results of imputation. Across all datasets and masking ratios, WaveFM achieves substantially lower errors than MOMENT, demonstrating strong robustness under sparse observations. This advantage continues as the missing rate increases, suggesting that masked reconstruction of wavelet coefficient streams provides informative multi-scale context for recovering missing values by leveraging both cross-scale and within-scale dependencies. Since WaveFM is evaluated in a zero-shot setting without any dataset-specific fine-tuning, these results indicate that the pre-trained encoder learns transferable multi-scale representations of time series.

Table 9: Imputation results.

| Dataset | Ratio | WaveFM-small | | WaveFM-base | | MOMENT-base | |
|---|---|---|---|---|---|---|---|
| | | MSE | MAE | MSE | MAE | MSE | MAE |
| ETTm1 | 12.5% | **0.068** | 0.094 | 0.070 | 0.096 | 0.393 | 0.416 |
| | 25.0% | 0.129 | 0.161 | 0.148 | 0.163 | 0.397 | 0.419 |
| | 37.5% | **0.193** | 0.221 | 0.226 | **0.220** | 0.406 | 0.425 |
| | 50.0% | **0.302** | 0.294 | 0.312 | 0.282 | 0.424 | 0.433 |
| | Avg | **0.173** | 0.192 | 0.189 | **0.190** | 0.405 | 0.423 |
| ETTm2 | 12.5% | 0.023 | 0.055 | 0.025 | 0.058 | 0.138 | 0.251 |
| | 25.0% | 0.042 | 0.091 | 0.050 | 0.096 | 0.140 | 0.253 |
| | 37.5% | 0.066 | 0.129 | 0.070 | 0.130 | 0.144 | 0.256 |
| | 50.0% | 0.101 | 0.173 | 0.092 | 0.165 | 0.148 | 0.260 |
| | Avg | 0.058 | 0.112 | 0.059 | 0.112 | 0.143 | 0.255 |
| ETTh1 | 12.5% | 0.087 | 0.110 | 0.099 | 0.125 | 0.693 | 0.579 |
| | 25.0% | 0.170 | 0.185 | 0.156 | 0.186 | 0.694 | 0.580 |
| | 37.5% | 0.293 | 0.262 | 0.256 | 0.250 | 0.699 | 0.581 |
| | 50.0% | 0.388 | 0.337 | 0.313 | 0.306 | 0.706 | 0.584 |
| | Avg | 0.234 | 0.223 | 0.206 | 0.217 | 0.698 | 0.581 |
| ETTh2 | 12.5% | 0.028 | **0.064** | **0.028** | 0.067 | 0.284 | 0.368 |
| | 25.0% | 0.055 | 0.111 | **0.052** | **0.107** | 0.285 | 0.369 |
| | 37.5% | 0.086 | 0.152 | **0.079** | **0.145** | 0.287 | 0.371 |
| | 50.0% | 0.127 | 0.203 | **0.103** | **0.185** | 0.290 | 0.373 |
| | Avg | 0.074 | 0.132 | **0.065** | **0.126** | 0.287 | 0.370 |
| Electricity | 12.5% | 0.068 | 0.123 | 0.073 | 0.129 | 0.167 | 0.298 |
| | 25.0% | 0.137 | 0.209 | 0.144 | 0.207 | 0.174 | 0.303 |
| | 37.5% | 0.201 | 0.279 | 0.185 | **0.258** | **0.184** | 0.309 |
| | 50.0% | 0.311 | 0.373 | 0.222 | **0.304** | **0.200** | 0.319 |
| | Avg | 0.179 | 0.246 | **0.156** | **0.224** | 0.181 | 0.307 |
| Weather | 12.5% | **0.018** | 0.044 | 0.021 | 0.045 | 0.090 | 0.154 |
| | 25.0% | **0.039** | **0.076** | 0.046 | 0.080 | 0.093 | 0.155 |
| | 37.5% | **0.061** | 0.106 | 0.072 | 0.110 | 0.098 | 0.158 |
| | 50.0% | 0.091 | 0.139 | **0.086** | 0.135 | 0.103 | 0.161 |
| | Avg | **0.052** | 0.091 | 0.056 | 0.092 | 0.096 | 0.157 |

## F  ACKNOWLEDGMENTS

This work was supported by the Institute of Information & Communications Technology Planning & Evaluation (IITP) grant funded by the Korea government(MSIT) (RS-2024-00443780, Development of Foundation Models for Bioelectrical Signal Data and Validation of Their Clinical Applications: A Noise-and-Variability Robust, Generalizable Self-Supervised Learning Approach; RS-2024-00439932, SW Starlab), Korean Institute for Advancement of Technology(KIAT) grant funded by the Korea Government(MOTIE) (RS-2024-00435815, Human Resource Development Program for Industrial Innovation(Global)), the Basic Science Research Program through the National Research Foundation of Korea (NRF) grant funded by the Ministry of Education (RS-2024-00463188), and the Korea Planning & Evaluation Institute of Industrial Technology (KEIT) funded by the Ministry of Trade, Industry and Resources (RS-2025-25458052, Development of Core Technologies for Manufacturing Foundation Models).