Random Walk Diffusion for Efficient Large-Scale Graph Generation

Abstract

Graph generation addresses the problem of generating new graphs that have a data distribution similar to real-world graphs. While previous diffusion-based graph generation methods have shown promising results, they often struggle to scale to large graphs. In this work, we propose ARROW-Diff (AutoRegressive RandOm Walk Diffusion), a novel random walk-based diffusion approach for efficient large-scale graph generation. Our method encompasses two components in an iterative process of random walk sampling and graph pruning. We demonstrate that ARROW-Diff can scale to large graphs efficiently, surpassing other baseline methods in terms of both generation time and multiple graph statistics, reflecting the high quality of the generated graphs.

1 Introduction

Graph generation addresses the problem of generating graph structures with specific properties similar to real-world ones, with applications ranging from modeling social interactions to constructing knowledge graphs, as well as designing new molecular structures. For example, an emerging task in drug discovery is to generate molecules with high drug-like properties. Traditional methods for graph generation focused on generating graphs with a predefined characteristic (Erdős et al., 1960; Barabási & Albert, 1999). Due to their hand-crafted nature, these methods fail to capture other graph properties, e.g., the graphs generated by Barabási & Albert (1999) are designed to capture the scale-free topology but fail to capture community structures of real-world graphs.

Recently, deep learning-based approaches have gained attention for overcoming the limitations of traditional graph generation methods by learning the complex topology of real-world graphs. These approaches typically involve an encoder that learns a dense representation of the graph, a sampler that generates samples from this representation, and a decoder which restores the sampled representation into a graph structure (Zhu et al., 2022). Different decoding strategies have been proposed, including sequential decoders that generate the graph step-by-step (You et al., 2018; Liao et al., 2019), and one-shot generators that can create the entire graph in a single step (Kipf & Welling, 2016b; Simonovsky & Komodakis, 2018; Grover et al., 2019). While sequential decoders struggle to model long-term dependencies and require node-ordering process, one-shot generators suffer from scalability issues and compromised quality due the to treatment of edges as independent (Chanpuriya et al., 2021), making these methods suboptimal for large-scale graph generation (Guo & Zhao, 2022).

An even more recent body of work in graph generation are diffusion-based probabilistic models, inspired by non-equilibrium thermodynamics and first introduced by Sohl-Dickstein et al. (2015). Briefly, diffusion models consist of two processes: A forward diffusion process which gradually corrupts input data until it reaches pure noise, and a reverse diffusion process which learns the generative mechanism of the original input data using a neural network. Diffusion-based methods for graph generation can be divided into two main categories. The first one includes methods that implement diffusion in the continuous space e.g., by adding Gaussian noise to the node features and graph adjacency matrix (Niu et al., 2020; Jo et al., 2022). This form of diffusion however makes it difficult to capture the underlying structure of graphs since it destroys their sparsity pattern (Vignac et al., 2023). The second category includes methods that

are based on diffusion in the discrete space (Haefeli et al., 2022; Vignac et al., 2023; Chen et al., 2023) by performing successive graph modifications e.g., adding or deleting edges/nodes or edge/node features. Diffusion-based graph generation methods are invariant to node ordering and do not suffer from long-term memory dependency which makes them advantageous over autoregressive (sequential) methods. However, many approaches found in the literature are only designed for small graphs (Niu et al., 2020; Jo et al., 2022; Vignac et al., 2023). One of the most recent diffusion-based graph generation approaches is EDGE (Chen et al., 2023), which uses a combination of a discrete diffusion model and a Graph Neural Network (GNN). EDGE scales to large graphs (up to ∼4k nodes and ∼38k edges), however, the number of required diffusion steps and hence graph generation time increases linearly with the number of edges in the graph.

To address the existing gaps in this field, we introduce ARROW-Diff (AutoRegressive RandOm Walk Diffusion), a novel iterative procedure designed for efficient, high-quality, and large-scale graph generation. To the best of our knowledge, ARROW-Diff is the first method to perform (discrete) diffusion on the level of random walks within a graph. Our method overcomes many limitations of existing graph generation approaches, including scalability issues, the independent treatment of edges, the need for post-processing, and the high computational complexity resulting from operations performed directly on the adjacency matrix. ARROW-Diff integrates two components: (1) A discrete diffusion model based on the order-agnostic autoregressive diffusion framework (OA-ARDM) (Hoogeboom et al., 2022) applied on random walks sampled from a real-world input graph, and (2) a GNN trained to predict the validity of the proposed edges in the generated random walks from component (1). The random walk-based diffusion in component (1) enables ARROW-Diff to capture the complex and sparse structure of graphs (Perozzi et al., 2014; Grover & Leskovec, 2016; Bojchevski et al., 2018), avoid any dense computation, and scale to large graphs, since the required number of diffusion steps is only equal to the random walk length. Moreover, due to the autoregressive nature of the implemented diffusion framework (OA-ARDM), ARROW-Diff overcomes the edge-independence limitation of methods like NetGAN (Bojchevski et al., 2018) and VGAE (Kipf & Welling, 2016b). On the other hand, the GNN in component (2) enables ARROW-Diff to select highly probable edges based on the topological structure learned from the original graph. It also helps to overcome the need for post-processing as in NetGAN (Bojchevski et al., 2018). ARROW-Diff builds the final graph by integrating the two components in an iterative process. This process is further guided by node degrees inspired by EDGE (Chen et al., 2023) to generate graphs with a similar degree distribution to the original graph. Using this iterative approach, we show that ARROW-Diff demonstrates superior or comparable performance to other baselines on multiple graph statistics. Furthermore, ARROW-Diff is able to efficiently generate large graphs (in this work, up to ∼20k nodes), such as the citation networks from McCallum et al. (2000); Sen et al. (2008); Pan et al. (2016), with significantly reduced (down to almost 50%) generation time compared to other baselines.

2 Related Work

In the following, we provide an overview of the different classes of graph generation models and identify their strengths, as well as their limitations.

One-Shot Graph Generation Models These methods include graph generation approaches based on the Variational Autoencoder (VAE) (Kingma & Welling, 2013), like VGAE (Kipf & Welling, 2016b), Graph-VAE (Simonovsky & Komodakis, 2018) and Graphite (Grover et al., 2019), which embed a graph G into a continuous latent representation $\boldsymbol{z}$ using an encoder defined by a variational posterior $q_\phi(\boldsymbol{z}|G)$, and a generative decoder $p_\theta(G|\boldsymbol{z})$. These models are trained by minimizing the upper bound on the negative log-likelihood $\mathbb{E}_{q_\phi(\boldsymbol{z}|G)}[-\log p_\theta(G|\boldsymbol{z})] + \mathrm{KL}[q_\phi(\boldsymbol{z}|G)||p(\boldsymbol{z})]$ (Kingma & Welling, 2013). However, due to their run time complexity of $\mathcal{O}(N^2)$, VAE-based graph generation approaches are unable to scale to large graphs.

Sequential Graph Generation Models The most scalable non-diffusion and sequential graph generation method so far is NetGAN (Bojchevski et al., 2018), which is based on the concept of Generative Adversarial Networks (GANs) (Goodfellow et al., 2014). Specifically, it uses a Long Short-Term Memory (LSTM) (Hochreiter & Schmidhuber, 1997) network to generate random walks. After training, the generated random walks are used to construct a score matrix from which the edges of the generated graph are sampled. The aforementioned approach generates edges in an independent manner, sacrificing the quality

of the generated graphs and limiting their ability to reproduce some statistics of the original graphs such as triangle counts and clustering coefficient (Chanpuriya et al., 2021). In contrast, ARROW-Diff overcomes this problem by directly using the edges generated by an autoregressive diffusion process on the level of random walks. Other edge-dependent sequential approaches include GraphRNN (You et al., 2018) and GRAN (Liao et al., 2019). These methods iteratively generate the entries of a graph adjacency matrix one entry or one block of entries at a time. To overcome the long-term bottleneck issue of Recurrent Neural Networks (RNNs), Liao et al. (2019) propose to use a GNN architecture instead of an RNN, which utilizes the already generated graph structure to generate the next block, allowing it to model complex dependencies between each generation step. To satisfy the permutation invariance property of graphs, these methods require a node ordering scheme. Moreover, they are only able to scale to graphs of up to 5k nodes.

Discrete Diffusion-Based Graph Generation Models To exploit the sparsity property of graphs, discrete diffusion-based graph generation models focus on diffusion in the discrete space i.e., on the level of the adjacency matrix (Haefeli et al., 2022; Vignac et al., 2023). Although these approaches generate high-quality graphs (Niu et al., 2020; Jo et al., 2022) and overcome the limitation of autoregressive models, they are restricted to small graph generation, like chemical molecules, because they perform prediction for every pair of nodes. Recently, Kong et al. (2023) developed GraphARM, an autoregressive graph generation approach based on diffusion in the node space. GraphARM demonstrates faster sampling time, since the number of diffusion steps required equals the number of nodes. Our method, however, requires only a number of diffusion steps equal to the random walk length, making it far more scalable than GraphARM. Aside from the method proposed in this work, the only diffusion-based approach able to scale to large graphs is EDGE (Chen et al., 2023). The forward diffusion process of EDGE is defined by successive edge removal until an empty graph is obtained. In the reverse diffusion process, only a fraction of edges are predicted between active nodes for which the degree changes during the forward diffusion process. This method generates graphs with a similar degree distribution to the original graph and has a decreased run time of $\mathcal{O}(T \max(M, K^2))$, where M is the number of edges in a graph and K is the number of active nodes. In this work, we introduce a random walk-based discrete diffusion approach to efficiently generate random walks as a first step for graph generation. The random walk-based diffusion implemented through the OA-ARDM (Hoogeboom et al., 2022) framework enables more efficient sampling than in other discrete diffusion models, with significantly reduced number of diffusion steps equal only to the random walk length. Additionally, a GNN component validates edges from the sampled random walks, enabling us to refine the generated graph and produce graphs of high quality.

3 Method

In this section, we introduce ARROW-Diff, an iterative procedure for efficient large-scale graph generation. We designed ARROW-Diff in a way to overcome the critical limitations of previous graph generation approaches and to enable it to scale to large graphs efficiently, without sacrificing the graph generation quality. Figure 1 provides an overview of ARROW-Diff, which leverages two models that are trained independently of each other on a training set of the edges from the original graph: (1) A random walk-based diffusion model based on the OA-ARDM (Hoogeboom et al., 2022) framework trained to generate random walks from the original graph. This involves first sampling of random walks and then masking nodes in the forward diffusion process, with the model predicting the original nodes in the reverse diffusion process. ARROW-Diff generates random walks from this learned diffusion model and uses the edges comprising these random walks as a first step of the graph generation process. (2) A GNN trained to capture the topology of the original graph. This component is used to predict the validity of the edges proposed by the first component. Our proposed method, ARROW-Diff, incorporates these two components in an iterative process guided by changes in the node degrees to generate the final graph. In the following, we provide background information on the OA-ARDM and its adaptation for random walk-based diffusion, followed by a detailed description of ARROW-Diff.

Background: Order Agnostic Autoregressive Diffusion Models Recent works show that diffusion models are applicable to discrete data (Sohl-Dickstein et al., 2015; Hoogeboom et al., 2021; Austin et al., 2021; Hoogeboom et al., 2022). The diffusion process of these models is based on the Categorical distribution over

Figure 1: Overview of ARROW-Diff graph generation (inference) using a trained OA-ARDM (Hoogeboom et al., 2022) and a trained GNN. Iteratively, and starting from an empty graph, a diffusion model samples random walks from a set of start nodes. Then, a GNN classifies the proposed edges and filters out invalid ones. This procedure is repeated using a different, sampled set of start nodes guided by the change of node degrees w.r.t. the original graph.

input features of a data point, instead of the Gaussian distribution. Initially, discrete diffusion models used uniform noise to corrupt the input in the forward diffusion process (Sohl-Dickstein et al., 2015; Hoogeboom et al., 2021). Later, Austin et al. (2021) extended this process and introduced a general framework for discrete diffusion (D3PM) based on Markov transition matrices $[\boldsymbol{Q}_t]_{ij} = q(x_t = j|x_{t-1} = i)$ for categorical random variables $x_{t-1}, x_t \in \{1, 2, \ldots, K\}$. One possible realization of the D3PM framework is the so-called absorbing state diffusion (Austin et al., 2021) that uses transition matrices with an additional absorbing state to stochastically mask entries of data points in each forward diffusion step. Recently, Hoogeboom et al. (2022) introduced the concept of OA-ARDMs combining order-agnostic autoregressive models (Uria et al., 2014) and absorbing state diffusion. Unlike standard autoregressive models, order-agnostic autoregressive models are able to capture dependencies in the input regardless of their temporal order. Let $\boldsymbol{x}$ be a D-dimensional data point. An order-agnostic autoregressive model can generate $\boldsymbol{x}$ in a random order that follows a permutation $\sigma \in S_D$, where S_D denotes the set of possible permutations of $\{1, 2, \ldots, D\}$. Specifically, their log-likelihood can be written as

$$\log p(\boldsymbol{x}) \geq \mathbb{E}_{\sigma \sim \mathcal{U}(S_D)} \sum_{t=1}^{D} \log p(x_{\sigma(t)}|\boldsymbol{x}_{\sigma(<t)}), \tag{1}$$

where $\boldsymbol{x}_{\sigma(<t)} = \{x_i|\sigma(i) < t, i \in \{1, \ldots, D\}\}$ represents all elements of $\boldsymbol{x}$ for which $\sigma(i)$ is less than t (Hoogeboom et al., 2022). In the following, we explain the proposed random walk-based autoregressive diffusion in more detail.

Random Walk Diffusion Consider a graph $G = (V, E)$ with $N = |V|$ nodes. We aim to learn the (unknown) generative process $p(G)$ of G. Inspired by DeepWalk (Perozzi et al., 2014), node2vec (Grover & Leskovec, 2016), and by the random walk-based graph generation approach introduced by Bojchevski et al. (2018), we suggest to sample random walks from a trained diffusion model and use the edges comprising the walks as proposals for generating a new graph. To achieve this, we train an OA-ARDM (Hoogeboom et al., 2022) by viewing each node in a random walk as a word in a sentence, and follow the proposed training

---

Algorithm 1 Optimizing Random Walk OA-ARDMs

1: **Input:** A random walk $\boldsymbol{x} \in V^D$, the number of nodes $N = |V|$, and a network f.
2: **Output:** ELBO $\mathcal{L}$.
3: Sample $t \sim \mathcal{U}(1, \ldots, D)$
4: Sample $\sigma \sim \mathcal{U}(S_D)$
5: Compute $\boldsymbol{m} \leftarrow (\sigma < t)$
6: Compute $\boldsymbol{i} \leftarrow \boldsymbol{m} \odot \boldsymbol{x} + (1 - \boldsymbol{m}) \odot ((N+1) \cdot \mathbf{1}_D)$
7: $\boldsymbol{l} \leftarrow (1 - \boldsymbol{m}) \odot \log \mathcal{C}(\boldsymbol{x}|f(\boldsymbol{i}, t))$
8: $\mathcal{L}_t \leftarrow \frac{1}{D-t+1} sum(\boldsymbol{l})$
9: $\mathcal{L} \leftarrow D \cdot \mathcal{L}_t$

Algorithm 2 ARROW-Diff Graph Generation

1: **Input:** A trained OA-ARDM, a trained GNN. The node set V, features $\boldsymbol{X}$ and degrees $\boldsymbol{d}_G$ of an original graph G with the same node ordering as for training the OA-ARDM. The number of steps L to generate the graph.
2: **Output:** A generated graph $\hat{G} = (V, \hat{E})$.
3: Start with an empty graph $\hat{G} = (V, \hat{E})$, where $\hat{E} = \emptyset$
4: Set the initial start nodes V_{start} to all nodes in the graph: $V_{\text{start}} = V$
5: **for** $l = 1$ **to** L **do**
6:     Sample one random walk for each start node $n \in V_{\text{start}}$ using the OA-ARDM: $\mathcal{R}$
7:     Compute edge proposals from $\mathcal{R}$:
        $\hat{E}_{\text{proposals}} := \{(n_i, n_j) \in \mathcal{R} | n_i, n_j \in V, i \neq j\}$
8:     Run the GNN on $G = (V, \hat{E} \cup \hat{E}_{\text{proposals}}, \boldsymbol{X})$ to obtain probabilities for all edges in $\hat{E} \cup \hat{E}_{\text{proposals}}$
9:     Sample valid edges $\hat{E}_{\text{valid}}$ from $\hat{E} \cup \hat{E}_{\text{proposals}}$ according to the edge probabilities
10:     Edge update: $\hat{E} \leftarrow \hat{E}_{\text{valid}}$
11:     **if** $l < L$ **then**
12:         Compute the node degrees $\boldsymbol{d}_{\hat{G}}$ of $\hat{G}$ based on $\hat{E}$
13:         Compute $\boldsymbol{d} := \max(0, \boldsymbol{d}_G - \boldsymbol{d}_{\hat{G}})$
14:         Compute a probability for each node $n \in V$: $p(n) = \frac{d_n}{\max(\boldsymbol{d})}$
15:         Sample start nodes V_{start} from V according to $p(n)$ using a Bernoulli distribution
16:     **end if**
17: **end for**

---

procedure of Hoogeboom et al. (2022) for OA-ARDMs on sequence data (Algorithm 1): For a random walk $\boldsymbol{x} \in V^D$ of length D, we start by sampling a time step $t \sim \mathcal{U}(1, \ldots, D)$ and a random ordering of the nodes in the walk, $\sigma \sim \mathcal{U}(S_D)$, both from a uniform distribution. For each time step t of the diffusion process, a BERT-like (Devlin et al., 2018) training is performed, in which $D - t + 1$ nodes (words) are masked and then predicted by a neural network. Specifically, the OA-ARDM is trained by maximizing the following log-likelihood component at each time step t (Hoogeboom et al., 2022):

$$\mathcal{L}_t = \frac{1}{D-t+1} \mathbb{E}_{\sigma \sim \mathcal{U}(S_D)} \sum_{k \in \sigma(\geq t)} \log p(x_k | \boldsymbol{x}_{\sigma(<t)}) \tag{2}$$

In the case of diffusion on random walks, masking of nodes is equivalent to setting them to an absorbing state represented by an additional class $N + 1$ (Hoogeboom et al., 2022). Thus, as suggested by Hoogeboom et al. (2022), the inputs to the network are (1) the masked random walk $\boldsymbol{i} = \boldsymbol{m} \odot \boldsymbol{x} + (1 - \boldsymbol{m}) \odot \boldsymbol{a}$, where $\boldsymbol{m} = \sigma < t$ is a Boolean mask, $\boldsymbol{a} = (N+1) \cdot \mathbf{1}_D$ and $\mathbf{1}_D$ is a D-dimensional vector of ones, and (2) the sampled time step t. During the training of the OA-ARDM, the random walks are sampled from the original graph.

ARROW-Diff Graph Generation Our proposed graph generation method, ARROW-Diff, is outlined in Algorithm 2. ARROW-Diff generates new graphs similar to a single, given original graph $G = (V, E)$

through an iterative procedure of L iterations: It starts with an empty graph $\hat{G} = (V, \hat{E} = \emptyset)$, which contains the same set of nodes V as the original graph but no edges. To add edges to $\hat{G}$, ARROW-Diff initially samples one random walk for every node in V and considers all edges in these random walks as edge proposals $\hat{E}_{\text{proposals}}$ for $\hat{G}$ (lines 6 and 7 in Algorithm 2). Next, and similar to the work of Liao et al. (2019), we sample valid edges from the proposed ones $\hat{E}_{\text{proposals}}$ using a Bernoulli distribution basen on the binary edge classification probabilities. These probabilities are calculated by taking the sigmoid of the dot-product of node embeddings predicted by the GNN component on $G = (V, \hat{E} \cup \hat{E}_{\text{proposals}}, \boldsymbol{X})$ (line 8). This GNN model is trained on a perturbed version of a training set of edges from the original graph G to perform edge classification. Specifically, the training set of edges is corrupted by deleting edges and inserting invalid (fake) edges. Inspired by the degree-guided graph generation process of Chen et al. (2023), we now sample nodes from V using a Bernoulli distribution by considering each node $n \in V$ according to a success probability $p(n) = \frac{d_n}{\max(\boldsymbol{d})}$, where $\boldsymbol{d} := \max(0, \boldsymbol{d}_G - \boldsymbol{d}_{\hat{G}})_n$ are the positive differences of node degrees $\boldsymbol{d}_G$ and $\boldsymbol{d}_{\hat{G}}$ from G and $\hat{G}$. This set of sampled nodes is then used as start nodes for sampling the random walks in the next iteration. Hence, we modify the sampling procedure of Hoogeboom et al. (2022), which originally starts from a sequence with only masked tokens, by manually setting the first node of a random walk $\boldsymbol{x}$ to a specific node $n \in V$, i.e.

$$x_k = \begin{cases} n & \text{if } k = 1, \\ \text{mask} & \text{if } k \in \{2, \ldots, D\}. \end{cases} \tag{3}$$

Additionally, we use a restricted set of permutations $S_D^{(1)} := \{\sigma \in S_D | \sigma(1) = 1\}$, in which the order of the first element does not change after applying the permutation. To sample the remaining parts $\boldsymbol{x}_{2:D}$ of the random walk $\boldsymbol{x}$, we follow the sampling procedure of Hoogeboom et al. (2022) by starting at time step $t = 2$ and using $\sigma \sim \mathcal{U}(S_D^{(1)})$. Our method can generate directed and undirected graphs. To generate undirected graphs, we suggest adding all reverse edges $\{(n_j, n_i) | (n_i, n_j) \in \hat{E}_{\text{proposals}}\}$ to the edge proposals $\hat{E}_{\text{proposals}}$ (line 7), and to sample edges from $\hat{E} \cup \hat{E}_{\text{proposals}}$ in a way to obtain undirected edges in $\hat{E}_{\text{valid}}$ (line 9).

4 Experiments and Results

In our experiments, we compare ARROW-Diff to five baseline methods that can scale to large graph generation. These methods cover the different graph generation techniques which are explained in Section 1 and Section 2. To evaluate the performance of all methods, we use five different real-world citation graph datasets, each containing a single undirected graph and all considered to be large with varying number of nodes/edges.

4.1 Experimental Setup

Datasets We use five citation graph datasets to evaluate our method: Cora-ML (McCallum et al., 2000), Cora (McCallum et al., 2000), CiteSeer (Giles et al., 1998), DBLP (Pan et al., 2016), and PubMed (Sen et al., 2008). For Cora-ML and Cora, we use the pre-processed version from Bojchevski & Günnemann (2018). Each of the five datasets contains one single, undirected, large-scale citation graph. Motivated by Bojchevski et al. (2018), we only take the largest connected component (LCC) of Cora-ML, Cora, CiteSeer, and DBLP, which all contain multiple connected components. Table 1 gives an overview of different characteristics for each graph/LCC. Similar to Bojchevski et al. (2018), we split the edges of each graph into training, validation, and test parts, and use only the training edges to train the baseline methods, as well as the OA-ARDM and GNN for ARROW-Diff.

Baseline Methods We use five different graph generation baseline methods, which are suitable for large graph generation to compare against ARROW-Diff: VGAE (Kipf & Welling, 2016b), Graphite (Grover et al., 2019), NetGAN Bojchevski et al. (2018), EDGE (Chen et al., 2023), and GraphRNN (You et al., 2018). Hence, previously mentioned methods like DiGress (Vignac et al., 2023) and GDSS (Jo et al., 2022), which are suitable for small graph generation, are excluded from our experiments. GraphRNN can scale to graphs with up to 5k nodes (You et al., 2018), so we only run it on the two smaller datasets Cora-ML (McCallum et al., 2000) and CiteSeer (Giles et al., 1998), since it is still affordable to train it on graphs of such sizes.

Table 1: Dataset statistics of single, large-scale graph datasets used in this paper: Number of nodes, undirected edges, node features, and average node degree. A star (⋆) indicates that the statistics are reported for the LCC of the respective dataset.

Dataset	# Nodes	# Edges	# Node Features	Avg. Degree
Cora-ML⋆	2,810	7,981	2,879	5.7
Cora⋆	18,800	62,685	8,710	6.7
CiteSeer⋆	1,681	2,902	602	3.5
DBLP⋆	16,191	51,913	1,639	6.4
PubMed	19,717	44,324	500	4.5

The recent autoregressive diffusion-based graph generation method GraphARM (Kong et al., 2023) is also excluded due to the absence of a code repository. However, as demonstrated in the complexity analysis in Section 5, ARROW-Diff outperforms GraphARM in terms of runtime. To train the baseline methods, we use the recommended hyper-parameters from their papers and code. The training of NetGAN is performed using their proposed VAL-criterion (Bojchevski et al., 2018) for early stopping on the validation edges from the data split. The training of EDGE took between 2-4 days on each dataset. Hence, for downstream evaluation, we consider the models at epoch 2600 (CiteSeer), 5550 (Cora-ML), 250 (Cora), 450 (DBLP), and 250 (PubMed). Additionally, to fit into GPU memory, we decreased the batch size from 4 (training) and 64 (validation) to 2 to train the models on the Cora, DBLP, and PubMed datasets. The aforementioned baselines do not incorporate node features in their training, hence, for a fair comparison, we report the performance of ARROW-Diff both with and without the use of original node features. In our case, node features are used for training and inference of the GNN model.

ARROW-Diff Models Training In the following, we provide details about the training of the OA-ARDM (Hoogeboom et al., 2022) and the GNN used in ARROW-Diff, which are trained independently. We train the OA-ARDM for random walk diffusion following the work of Hoogeboom et al. (2022), which is explained in Section 3. Specifically, we use a U-Net architecture similar to Ho et al. (2020) with one ResNet block and two levels for the down- and up-sampling processes. Similar to Bojchevski et al. (2018) we set the random walk length to $D = 16$ and sample batches of random walks from the training split comprising edges from the original graph. Each node in the random walks, as well as each diffusion time step, is then represented using 64-dimensional learnable embeddings and passed as input to the U-Net. For the GNN component, we train a two-layer GCN (Kipf & Welling, 2016a) to predict the validity of edges based on perturbed versions of the training split of the input graph. Specifically, the GCN is trained by minimizing the binary cross-entropy loss between predicted edge probabilities and the ground truth labels which indicate whether an edge in the perturbed graph is valid or invalid. The predicted probabilities are computed by taking the sigmoid of the dot-product between pairs of node embeddings. As input to the GCN, we use either the original node features (ARROW-Diff with node features) or positional encodings (Vaswani et al., 2017) (ARROW-Diff without node features). The positional encodings are 64-dimensional for Cora-ML and CiteSeer, and 128-dimensional for Cora, DBLP, and PubMed. The GCN uses node embeddings of sizes 100 and 10 in the hidden and output layer, respectively. The full list of hyperparameters for training the OA-ARDMs and the GNN models can be found in the supplementary materials.

Evaluation of Generated Graphs We use six different graph metrics to evaluate the performance of the trained models. Additionally, we report the edge overlap (EO) between the generated graphs and the original graph/LCC. Specifically, we generate 10 graphs per dataset and compute the mean and standard deviation of the metrics to obtain a more accurate estimate of the performance and assess robustness.

4.2 Hyperparameter Tuning

ARROW-Diff generates a graph within several iterations L. In the following, we investigate the influence of the choice of L on the performance of ARROW-Diff. In Figure 2 we show how the different graph

evaluation metrics change with respect to L on the CiteSeer (Giles et al., 1998) dataset. The increase trend on the average clustering coefficient, number of triangles, and maximum node degree can be explained by the increase in the total number of edges of the generated graph with respect to L (see Figure 3). With increasing L, more edges are added, which in turn increase the maximum degrees of some nodes as well as the number of triangles. This also explains why e.g. the global clustering coefficient remains mostly constant, since the number of closed and open triangles rise simultaneously. We choose $L = 10$ to generate graphs with ARROW-Diff across all datasets, since this value shows the closest results to the ground truth graph both in terms of number of triangles, and power-law exponent. In Figure 3, the strong drop in the number of edges for $L \in [1, 5]$ is due to the fact that ARROW-Diff samples one random walk for every node in the graph at $L = 1$, which results in a high number of edge proposals. With increasing L, these edges will either be selected or dropped from the final generated graph based on the sampling on the probabilities computed by the GNN model.

Figure 2: The change in different graph evaluation metrics with respect to L. The dotted line reports the value corresponding to the ground truth graph, in this case CiteSeer. For each metric, the mean and standard deviation were computed across 10 generated graphs using $L \in [1, 30]$ iterations for ARROW-Diff.

Figure 3: The mean and standard deviation of the number of edges of 10 graphs generated by ARROW-Diff, using the original node features, are reported for $L \in [1, 30]$. The dotted line represents the number of edges of the original CiteSeer graph.

Table 2: Graph generation results of NetGAN (Bojchevski et al., 2018), VGAE (Kipf & Welling, 2016b), Graphite (Grover et al., 2019), EDGE (Chen et al., 2023), GraphRNN (You et al., 2018), and ARROW-Diff with and without node features on the single, large-scale graph datasets from Table 1. The performance is given in terms of the mean of six graph statistics across 10 generated graphs. The edge overlap represents the mean overlap with the edges of the original graph. The last column reports the graph generation time for all methods, which, for ARROW-Diff, is the time for executing Algorithm 2.

Dataset / Methods	Max. degree	Assort-ativity	Triangle Count	Power law exp.	Avg. cl. coeff.	Global cl. coeff.	Edge Overlap	Time [s]
Cora-ML	246	-0.077	5,247	1.77	0.278	0.004	-	-
NetGAN	181	-0.025	384	1.67	0.011	0.001	3.2%	6.2
VGAE	948	-0.043	70 M	1.66	0.383	**0.002**	22.2%	0.0
Graphite	115	-0.188	11,532	1.57	**0.201**	0.009	0.3%	0.1
EDGE	**202**	-0.051	1,410	**1.76**	0.064	**0.002**	1.3%	5.5
GraphRNN	38	**-0.078**	98	2.05	0.015	0.042	0.2%	2.0
ARROW-Diff	373	-0.112	5,912	1.81	0.191	0.001	57.3%	1.8
ARROW-Diff (w/o features)	439	-0.117	**5,821**	1.82	0.182	0.001	55.2%	1.7
Cora	297	-0.049	48,279	1.69	0.267	0.007	-	-
NetGAN	135	0.010	206	1.61	0.001	0.000	0.1%	35.0
Graphite	879	-0.213	3 M	1.31	**0.338**	0.001	0.3%	0.9
EDGE	**248**	0.078	11,196	1.65	0.021	**0.002**	0.2%	85.8
ARROW-Diff	536	**-0.077**	89,895	**1.70**	0.122	**0.002**	40.8%	13.7
ARROW-Diff (w/o features)	579	-0.080	**77,075**	1.68	0.105	0.001	42.3%	13.4
CiteSeer	85	-0.165	771	2.23	0.153	0.007	-	-
NetGAN	42	-0.009	23	2.03	0.004	0.001	0.7%	4.5
VGAE	558	-0.036	15 M	1.69	0.383	0.003	22.1%	0.0
Graphite	58	-0.198	2,383	1.70	**0.157**	0.016	0.3%	0.1
EDGE	**82**	-0.128	205	2.08	0.054	0.003	1.1%	4.2
GraphRNN	31	-0.243	20	2.88	0.011	**0.007**	0.2%	5.7
ARROW-Diff	114	-0.192	**795**	**2.24**	0.109	0.004	57.8%	1.6
ARROW-Diff (w/o features)	148	**-0.178**	996	2.15	0.125	0.003	63.0%	2.0
DBLP	339	-0.018	36,645	1.76	0.145	0.004	-	-
NetGAN	215	0.053	1,535	1.62	0.002	0.000	0.9%	29.8
Graphite	734	-0.207	2 M	1.32	0.331	**0.002**	0.3%	0.8
EDGE	**258**	0.146	13,423	1.70	0.018	**0.002**	0.4%	62.0
ARROW-Diff	478	-0.098	**49,865**	**1.78**	0.069	0.001	34.2%	11.2
ARROW-Diff (w/o features)	675	**-0.063**	63,017	1.67	**0.079**	0.001	34.9%	9.4
PubMed	171	-0.044	12,520	2.18	0.060	0.004	-	-
NetGAN	**150**	**-0.021**	184	1.90	0.001	0.000	0.1%	39.7
Graphite	918	-0.209	4 M	1.31	0.341	**0.001**	0.3%	1.3
EDGE	131	0.027	**2,738**	**2.03**	0.005	**0.001**	0.2%	92.7
ARROW-Diff	478	-0.082	44,120	1.90	**0.039**	**0.001**	42.7%	14.4
ARROW-Diff (w/o features)	474	-0.126	41,379	1.85	0.034	**0.001**	41.2%	12.8

Figure 4: Visualization of the training graphs and generated graphs for Cora-ML and CiteSeer from NetGAN, Graphite, EDGE, and ARROW-Diff using the trained models from Section 4. We observe that ARROW-Diff is able to capture the basic structure of the ground-truth graph

4.3 Results and Efficiency

In Table 2, we present the results for all baselines and for ARROW-Diff trained both with and without node features on the five datasets (Table 1). The results are reported as the mean across 10 generated graphs. To evaluate the stability of all methods, we also report the standard deviation of all metrics across the 10 generated graphs in Table 4. The results presented in Table 2 indicate that ARROW-Diff achieves notable improvement across many metrics, surpassing nearly all baselines in terms of triangle counts and power-law exponent. We observe that, EDGE performs the best in terms of maximum node degree across all datasets. This is due to its ability to steer the graph generation process towards a degree distribution similar to that of the original graph. We would like to highlight that, the number of edges in the graphs generated by VGAE (Kipf & Welling, 2016b) and Graphite (Grover et al., 2019) was extremely high. Thus, we consider only edges for which the predicted probability $p(A_{ij} = 1 | z_i, z_j) = \sigma(z_i^T z_j) > 0.95$ for nodes $i, j \in V$. Even with this constraint, the graphs generated by VGAE had over 50 M edges on the Cora, DBLP, and PubMed datasets, which led to an exhaustive metric computation. Therefore, we have omitted the results for these datasets in Table 2. The scalability of ARROW-Diff is demonstrated in the substantial decrease in graph generation time (down to more than 50% compared to all baselines). This remains true even when generating very large graphs such as Cora, DBLP, and PubMed (column 'Time' in Table 2). In the presented results, the graph generation time of VGAE and Graphite is almost zero because operating on tensors of sizes up to $3,000 \times 3,000$ entries is not challenging for modern computers. The scalability of ARROW-Diff is further reflected in the training speed. Due to the small number of diffusion steps needed to train the random walk-based OA-ARDM (Hoogeboom et al., 2022), ARROW-Diff converges within 30 minutes on all datasets. In contrast, EDGE requires between 2-4 days on each dataset.

4.4 Visualization of Generated Graphs

In Figure 4, we visualize the training split of the Cora-ML and CiteSeer graphs as well as one generated graph for each baseline method and for ARROW-Diff (using node features). We observe that ARROW-Diff is able to capture the basic structure of the ground truth graph. In Figure 5, we show the capability of ARROW-Diff in capturing community structures present in the community-20 dataset (Martinkus et al., 2022). To train ARROW-Diff for this setting, where the input comprises many small graphs, we train one model for each graph in the training set and then sample from all the trained models. As baselines, we choose those methods that are able to train on a dataset of multiple input graphs, like EDGE and GraphRNN. In Figure 6, we

further show that, the generated graphs from ARROW-Diff have a heavy-tailed degree distribution, similar to real-world graphs.

5 Complexity Analysis

ARROW-Diff can be used for fast generation of large graphs. In the following, we analyze the runtime complexity of ARROW-Diff, i.e., the complexity for executing Algorithm 2. Let N denote the number of nodes and $|E|$ the number of edges in a graph, D the random walk length which in this case is equal to the number of diffusion steps, and L the number of graph generation steps (iterations) of ARROW-Diff. In each iteration $l \in [1, L]$, ARROW-Diff first samples one random walk of length D for each start node $n \in V_{\text{start}}$ (line 6) to compute edge proposals. This step has a time complexity of $\mathcal{O}(ND)$ because $V_{\text{start}} \subseteq V$, and $V_{\text{start}} = V$ in the first step. Next, ARROW-Diff uses a GCN Kipf & Welling (2016a), to compute the probabilities for each edge in the so far generated graph including the set of newly proposed edges (line 8), which requires a maximum of $\mathcal{O}(|E|)$ operations. The computation of the new start nodes for the next iteration requires a maximum of $\mathcal{O}(|E|)$ operations with a complexity of $\mathcal{O}(|E|)$ for computing the node degrees of $\hat{G}$ (line 12), and $\mathcal{O}(N)$ to compute the probabilities (line 14) and sample the new start nodes (line 15). Overall, for L generation steps, ARROW-Diff has a run time of $\mathcal{O}(L(ND + |E|))$. This is a great reduction in complexity compared to most existing diffusion-based graph generation approaches which have a runtime complexity of $\mathcal{O}(TN^2)$ and are therefore not suitable for large-scale graph generation. The runtime of ARROW-Diff also outperforms that of EDGE (Chen et al., 2023), which is the only diffusion-based method in the literature that tests large graph generation at the magnitude we show here. In Table 3 we provide an overview of the runtime complexities required for the graph generation process for every baseline method. We also show that ARROW-Diff has a better runtime complexity compared to the recent autoregressive diffusion-based method GraphARM (Kong et al., 2023), which has a runtime complexity of $\mathcal{O}(N^2)$, using overall $N(N-1)/2$ operations to predict the connecting edges of each node to all previously denoised nodes across all sampling steps.

Table 3: Runtime complexity $\mathcal{O}(\cdot)$ for all baseline models and ARROW-Diff. For all methods, N is the number of nodes. For NetGAN, D is the random walk length, M is the number of sampled random walks, and K is the average degree of the nodes. For VGAE and Graphite, F is the size of the latent vector. For EDGE, M is the number of edges in an input graph, and K is the number of active nodes.

Method	Diffusion-based	Generation Type	Runtime
NetGAN	No	Sequential	$\mathcal{O}(MD + NK)$
VGAE	No	One-shot	$\mathcal{O}(FN^2)$
Graphite	No	One-shot	$\mathcal{O}(FN^2)$
GraphRNN	No	Sequential	$\mathcal{O}(N^2)$
EDGE	Yes	Sequential	$\mathcal{O}(T \max(M, K^2))$
GraphARM	Yes	Sequential	$\mathcal{O}(N^2)$
ARROW-Diff	Yes	Sequential	$\mathcal{O}(L(ND + |E|))$

6 Conclusion

In this paper, we present ARROW-Diff, a novel approach for large-scale graph generation based on random walk diffusion. ARROW-Diff generates graphs by integrating two components: (1) An order agnostic autoregressive diffusion model on the level of random walks that learns the generative process of random walks of an input graph, and (2) a GNN component that learns to filter out unlikely edges from the generated graph. Due to the random-walk based diffusion, ARROW-Diff efficiently scales to large graphs, significantly reducing generation time compared to baselines. It generates graphs of high quality, reflected in the high performance on many graph statistics. One limitation of ARROW-Diff is that it generates graphs with the same number of nodes as the original graph, due to the framework of the OA-ARDM. Potential future

work could focus on a more flexible implementation of ARROW-Diff including an adaptation for learning on multiple graphs.

References

Jacob Austin, Daniel D. Johnson, Jonathan Ho, Daniel Tarlow, and Rianne van den Berg. Structured denoising diffusion models in discrete state-spaces. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=h7-XixPCAL.

Albert-László Barabási and Réka Albert. Emergence of scaling in random networks. *science*, 286(5439): 509–512, 1999.

Aleksandar Bojchevski and Stephan Günnemann. Deep gaussian embedding of graphs: Unsupervised inductive learning via ranking. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=r1ZdKJ-0W.

Aleksandar Bojchevski, Oleksandr Shchur, Daniel Zügner, and Stephan Günnemann. NetGAN: Generating graphs via random walks. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 610–619. PMLR, 10–15 Jul 2018. URL https://proceedings.mlr.press/v80/bojchevski18a.html.

Sudhanshu Chanpuriya, Cameron Musco, Konstantinos Sotiropoulos, and Charalampos Tsourakakis. On the power of edge independent graph models. *Advances in Neural Information Processing Systems*, 34: 24418–24429, 2021.

Xiaohui Chen, Jiaxing He, Xu Han, and Li-Ping Liu. Efficient and degree-guided graph generation via discrete diffusion modeling. *arXiv preprint arXiv:2305.04111*, 2023.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Paul Erdős, Alfréd Rényi, et al. On the evolution of random graphs. *Publ. Math. Inst. Hung. Acad. Sci*, 5 (1):17–60, 1960.

C. Lee Giles, Kurt D. Bollacker, and Steve Lawrence. Citeseer: An automatic citation indexing system. In *Proceedings of the Third ACM Conference on Digital Libraries*, DL '98, pp. 89–98, New York, NY, USA, 1998. Association for Computing Machinery. ISBN 0897919653. doi: 10.1145/276675.276685. URL https://doi.org/10.1145/276675.276685.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 855–864, 2016.

Aditya Grover, Aaron Zweig, and Stefano Ermon. Graphite: Iterative generative modeling of graphs. In *International conference on machine learning*, pp. 2434–2444. PMLR, 2019.

Xiaojie Guo and Liang Zhao. A systematic survey on deep generative models for graph generation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(5):5370–5390, 2022.

Kilian Konstantin Haefeli, Karolis Martinkus, Nathanaël Perraudin, and Roger Wattenhofer. Diffusion models for graphs benefit from discrete state spaces. *arXiv preprint arXiv:2210.01549*, 2022.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in neural information processing systems*, 33:6840–6851, 2020.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.

Emiel Hoogeboom, Didrik Nielsen, Priyank Jaini, Patrick Forré, and Max Welling. Argmax flows and multinomial diffusion: Learning categorical distributions. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=6nbpPqUCIi7.

Emiel Hoogeboom, Alexey A. Gritsenko, Jasmijn Bastings, Ben Poole, Rianne van den Berg, and Tim Salimans. Autoregressive diffusion models. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=Lm8T39vLDTE.

Jaehyeong Jo, Seul Lee, and Sung Ju Hwang. Score-based generative modeling of graphs via the system of stochastic differential equations. In *International Conference on Machine Learning*, pp. 10362–10383. PMLR, 2022.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016a.

Thomas N Kipf and Max Welling. Variational graph auto-encoders. *arXiv preprint arXiv:1611.07308*, 2016b.

Lingkai Kong, Jiaming Cui, Haotian Sun, Yuchen Zhuang, B Aditya Prakash, and Chao Zhang. Autoregressive diffusion model for graph generation. In *International conference on machine learning*, pp. 17391–17408. PMLR, 2023.

Renjie Liao, Yujia Li, Yang Song, Shenlong Wang, Will Hamilton, David K Duvenaud, Raquel Urtasun, and Richard Zemel. Efficient graph generation with graph recurrent attention networks. *Advances in neural information processing systems*, 32, 2019.

Karolis Martinkus, Andreas Loukas, Nathanaël Perraudin, and Roger Wattenhofer. Spectre: Spectral conditioning helps to overcome the expressivity limits of one-shot graph generators. In *International Conference on Machine Learning*, pp. 15159–15179. PMLR, 2022.

Andrew Kachites McCallum, Kamal Nigam, Jason Rennie, and Kristie Seymore. Automating the construction of internet portals with machine learning. *Information Retrieval*, 3:127–163, 2000.

Chenhao Niu, Yang Song, Jiaming Song, Shengjia Zhao, Aditya Grover, and Stefano Ermon. Permutation invariant graph generation via score-based generative modeling. In *International Conference on Artificial Intelligence and Statistics*, pp. 4474–4484. PMLR, 2020.

Shirui Pan, Jia Wu, Xingquan Zhu, Chengqi Zhang, and Yang Wang. Tri-party deep network representation. *Network*, 11(9):12, 2016.

Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 701–710, 2014.

Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Galligher, and Tina Eliassi-Rad. Collective classification in network data. *AI magazine*, 29(3):93–93, 2008.

Martin Simonovsky and Nikos Komodakis. Graphvae: Towards generation of small graphs using variational autoencoders. In *Artificial Neural Networks and Machine Learning–ICANN 2018: 27th International Conference on Artificial Neural Networks, Rhodes, Greece, October 4-7, 2018, Proceedings, Part I 27*, pp. 412–422. Springer, 2018.

Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 2256–2265, Lille, France, 07–09 Jul 2015. PMLR. URL `https://proceedings.mlr.press/v37/sohl-dickstein15.html`.

Benigno Uria, Iain Murray, and Hugo Larochelle. A deep and tractable density estimator. In Eric P. Xing and Tony Jebara (eds.), *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pp. 467–475, Bejing, China, 22–24 Jun 2014. PMLR. URL `https://proceedings.mlr.press/v32/uria14.html`.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL `https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf`.

Clement Vignac, Igor Krawczuk, Antoine Siraudin, Bohan Wang, Volkan Cevher, and Pascal Frossard. Digress: Discrete denoising diffusion for graph generation. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=UaAD-Nu86WX`.

Jiaxuan You, Rex Ying, Xiang Ren, William Hamilton, and Jure Leskovec. GraphRNN: Generating realistic graphs with deep auto-regressive models. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 5708–5717. PMLR, 10–15 Jul 2018. URL `https://proceedings.mlr.press/v80/you18a.html`.

Yanqiao Zhu, Yuanqi Du, Yinkai Wang, Yichen Xu, Jieyu Zhang, Qiang Liu, and Shu Wu. A survey on deep graph generation: Methods and applications. In *Learning on Graphs Conference*, pp. 47–1. PMLR, 2022.

A   Standard Deviations of All Evaluation Metrics

Table 4: Standard deviation for each metric shown in Table 2.

Dataset / Methods	Max. degree	Assort-ativity	Triangle Count	Power law exp.	Avg. cl. coeff.	Global cl. coeff.	Edge Overlap	Time [s]
Cora-ML	246	-0.077	5,247	1.77	0.278	0.004	-	-
NetGAN	11	0.004	19	0.00	0.001	0.000	0.2%	1.0
VGAE	24	0.003	2 M	0.11	0.001	0.000	0.6%	0.0
Graphite	14	0.015	1,411	0.02	0.007	0.001	0.1%	0.0
EDGE	1	0.010	125	0.00	0.003	0.000	0.1%	3.7
GraphRNN	20	0.085	38.558	0.210	0.004	0.048	0.09%	1.47
ARROW-Diff	9	0.002	320	0.02	0.007	0.000	1.5%	0.0
ARROW-Diff (w/o features)	13	0.004	326	0.01	0.006	0.000	1.5%	0.0
Cora	297	-0.049	48,279	1.69	0.267	0.007	-	-
NetGAN	13	0.003	13	0.00	0.000	0.000	0.0%	0.9
Graphite	79	0.005	116,224	0.00	0.004	0.000	0.0%	0.0
EDGE	3	0.016	1,111	0.00	0.001	0.000	0.0%	0.8
ARROW-Diff	15	0.003	2,040	0.00	0.002	0.000	0.7%	0.7
ARROW-Diff (w/o features)	35	0.002	4,714	0.01	0.003	0.000	1.3%	1.3
CiteSeer	85	-0.165	771	2.23	0.153	0.007	-	-
NetGAN	8	0.019	6	0.01	0.002	0.000	0.2%	0.2
VGAE	16	0.004	337,244	0.11	0.001	0.000	0.8%	0.1
Graphite	6	0.022	419	0.02	0.010	0.001	0.1%	0.0
EDGE	0	0.011	27	0.01	0.007	0.000	0.2%	3.3
GraphRNN	8	0.054	5.76	0.367	0.003	0.004	0.07%	0.6
ARROW-Diff	5	0.007	69	0.03	0.008	0.000	1.4%	0.0
ARROW-Diff (w/o features)	8	0.008	68	0.02	0.008	0.000	1.1%	0.2
DBLP	339	-0.018	36,645	1.76	0.145	0.004	-	-
NetGAN	10	0.005	69	0.00	0.000	0.000	0.0%	0.4
Graphite	74	0.004	69,026	0.00	0.003	0.000	0.0%	0.0
EDGE	2	0.033	1,675	0.00	0.002	0.000	0.0%	0.5
ARROW-Diff	26	0.002	2,202	0.01	0.002	0.000	0.8%	0.7
ARROW-Diff (w/o features)	27	0.003	2,797	0.01	0.002	0.000	0.6%	0.0
PubMed	171	-0.044	12,520	2.18	0.060	0.004	-	-
NetGAN	14	0.004	9	0.00	0.000	0.000	0.0%	1.8
Graphite	70	0.005	244,816	0.00	0.004	0.000	0.0%	0.0
EDGE	4	0.038	741	0.00	0.001	0.000	0.0%	0.5
ARROW-Diff	11	0.003	1,454	0.00	0.001	0.000	0.8%	1.1
ARROW-Diff (w/o features)	15	0.004	2,427	0.01	0.001	0.000	1.0%	0.0

B Visualization of Community Structures Captured by ARROW-Diff

(a) Graphs from the test split.

(b) Graphs graphs from GraphRNN.

(c) Generated graphs from EDGE.

(d) Generated graphs from ARROW-Diff.

Figure 5: Visualization of six generated graphs from GraphRNN, EDGE, and ARROW-Diff trained on the Community-20 dataset, showing that ARROW-Diff is able to capture community structures in the ground-truth graph.

C Node Degree Distribution of Generated Graphs

Figure 6: Node degree distribution of the original CiteSeer graph and one generated graph from ARROW-Diff using the node features from CiteSeer.