Navigating Memory Construction by Global Pseudo-Task Simulation for Continual Learning

Abstract

Continual learning faces a crucial challenge of catastrophic forgetting. To address this challenge, experience replay (ER) that maintains a tiny subset of samples from previous tasks has been commonly used. Existing ER works usually focus on refining the learning objective for each task with a static memory construction policy. In this paper, we formulate the dynamic memory construction in ER as a combinatorial optimization problem, which aims at directly minimizing the global loss across all experienced tasks. We first apply three tactics to solve the problem in the offline setting as a starting point. To provide an approximate solution to this problem in the online continual learning setting, we further propose the Global Pseudo-task Simulation (GPS), which mimics future catastrophic forgetting of the current task by permutation. Our empirical results and analyses suggest that the GPS consistently improves accuracy across four commonly used vision benchmarks. We have also shown that our GPS can serve as the unified framework for integrating various memory construction policies in existing ER works.

1   Introduction

Data in real world is non-stationary and keeps changing. Adapting new knowledge while maintaining the old skills learned from previous data is an idealism for intelligent systems. However, deep artificial neural networks suffer from catastrophic forgetting of old behaviors as the learning of new tasks keeps overwriting the past [28, 29, 30, 38, 31]. To combat this issue, numerous novel algorithms have been designed in continual learning in recent years [34, 13, 26, 8, 18, 3, 25]. Amongst them, the experience replay (ER) methods have been attested as one of the few methods that consistently achieve strong results across different continual learning setups [6, 11, 43, 19]. In the ER, a slightly relieved continual learning setting is considered, where a learner stores a subset of old examples from previous tasks in a fixed-sized memory and jointly trains the memory with the upcoming task.

Existing ER based methods put rigorous efforts in refining the local learning objective to update the model parameters on one task at a time. They usually stick to a static memory construction policy, which is prone to failing in the long task sequence. For example, selecting random data examples from experienced tasks for the memory buffer can effect good generalization at the very beginning, but the forgetting rate would soon climb dramatically when the tasks sequence becomes longer, as some class representations are totally squeezed out from the memory [11]. This major drawback has inspired us to explore the optimal memory construction with a dynamic policy.

In this work, we formulate the memory construction problem in ER as a combinatorial optimization problem. Unlike previous memory construction methods [2, 4, 15], we explicitly optimize the global objective, *i.e.*, the minimum loss of the final model on all observed tasks, by finding the best memory configuration strategy. As a starting point, we approach this problem in an offline setting, where we can go through the task sequence for multiple trials independently. By utilizing three tactics, we

reduce the intractable search space to a significantly smaller one, then we use the binary search to solve the simplified problem in $O(T \log |\mathcal{M}|)$, where T is the total number of tasks and $|\mathcal{M}|$ is the size of the memory buffer. Based on the offline solution, in the online continual learning setup,[1] we propose our method **Global Pseudo-task Simulation (GPS)** as an approximate solution to the problem. The GPS mimics the catastrophic forgetting pattern for the current task by creating future pseudo-tasks. We examine a few simulation methods and find permutation is the favorable way to synthesize pseudo-tasks.

We conduct experiments on four widely used vision benchmarks to show that GPS achieves higher accuracy compared to baselines, especially when we have a long task sequence. Besides, GPS, as a solution for dynamic memory construction, can also be easily applied to other ER variants [6, 9] to further improve their performance.

2   Preliminary and Notations

Continual Learning   In continual learning, the model $f(\theta)$ experiences a stream of data points $(x_i, y_i) \sim P_i$ from a sequence of tasks t_i, where $i \in \mathcal{T} = \{1, ..., T\}$, and P_i is an unknown i.i.d. distribution of task t_i. Without experience replay, the model $f(\theta)$ is optimized on one task at a time following the task sequence under the tight constraint that the examples from previous tasks cannot be accessed [35]. We denote θ_i as the parameter of $f(\cdot)$ *after* training task t_i, and we refer to the function $g(\cdot)$ that updates θ_i for each task t_i as the *local updating method*. Once the local updating method is determined, θ_T can be derived recursively by $\theta_i = g(\theta_{i-1}, P_i)$ from θ_0, which is the initialization point.

After sequentially training T tasks, the objective of continual learning is to achieve the minimum loss across all observed tasks with the final model in the end. In the *global loss* $\mathcal{L}_G$, θ_T is the final parameter after T tasks and $l(\cdot)$ is the cross-entropy loss.

$$\mathcal{L}_G = \sum_{k=1}^{T} \mathbb{E}_{(x_k, y_k) \sim P_k} \ell(y_k, f(x_k; \theta_T)) \tag{1}$$

Experience Replay   Previous works [13, 35, 43] have proposed a series of local updating methods to optimize the global objective. Amongst them, one effective way is experience replay (ER) from [11]. Experience replay relieves a bit on the tight constraint in continual learning by adding a fixed-sized memory buffer $\mathcal{M}$ to store a limited subset of seen examples.

We denote the memory *after* training task t_i as $\mathcal{M}_i$. The modified local updating method g treats the memory as another input, and jointly optimizes examples of the current task and examples stored in the memory, with a factor λ on the loss of memory examples as shown in Eqn. (2). Thus, θ_i is iteratively updated by $\theta_i = g(\theta_{i-1}, P_i, \mathcal{M}_{i-1})$.

$$g(\theta, P, \mathcal{M}) = \arg\min_{\theta} \{\mathcal{L}_t(\theta, P) + \lambda \mathcal{L}_t(\theta, \mathcal{M})\} \tag{2}$$

$$\mathcal{L}_t(\theta, P) = \mathbb{E}_{(x,y) \sim P} \ell(y, f(x; \theta)) \tag{3}$$

Both empirical results [11, 6] and theoretical analysis [19] have suggested that the local updating method g of experience replay is effective on reducing the global loss $\mathcal{L}_G$. If not specially specified, we refer to local updating method g as Eqn. (2) in the following text.

3   Problem Formulation: Dynamic Memory Construction

Most previous works based on ER regard the global loss $\mathcal{L}_G$ as a function of g with a static memory construction strategy for $\mathcal{M}$. They utilize various techniques like regularization [6, 9] or memory sampling [2] to further refine the local updating method g. Unlike them, we view the global loss $\mathcal{L}_G$ as a function of the memory $\mathcal{M}$, and explicitly minimize $\mathcal{L}_G$ by optimizing the memory *without* modifying the local updating methods in Eqn. (2).

Following the setup of ER, we propose dynamic memory construction, which aims at finding the best memory construction $\mathcal{M}$ to optimize the global objective $\mathcal{L}_G$, as defined in Eqn. (1). This

---

[1]We use *online* as opposed to the multi-trial offline setup, while we still use the multi-pass training here.

Figure 1: Using three tactics on the S-CIFAR-10 dataset to solve the dynamic memory construction problem in the offline setting. The equal memory heuristic and the base policy assumption reduce the search space. The switching point existence enables the binary search.

combinatorial optimization problem is expressed by the Eqn. (4), where we minimize the global objective by considering each memory $\mathcal{M}_i$ after task t_i as a variable.

$$\min_{\{\mathcal{M}_i\}_{i \in \mathcal{T}}} \mathcal{L}_G(\{\mathcal{M}_i\}_{i \in \mathcal{T}}) \tag{4}$$

We denote the part in $\mathcal{M}_i$ storing the examples of task t_j as $\mathcal{M}_{i,j}$. There are four intrinsic constraints for the optimization problem. In all constraints, $i, j, i' \in \mathcal{T}$.

- $\mathcal{M}_i$ is the union of memories $\{\mathcal{M}_{i,j}\}_{j \in \mathcal{T}}$. The collection $\{\mathcal{M}_{i,j}\}_{j \in \mathcal{T}}$ is mutually disjoint.
- No future examples in the memory, *i.e.*, $\mathcal{M}_{i,j} = \varnothing$ when $i < j$.
- The size of memory is the same across the training procedure from t_1 to t_T, denoted as $|\mathcal{M}|$.
- As we cannot access previous examples that are not stored in the memory, once the set for task t_j in the memory is constructed after training task t_j, its size will not increase. Thus, the memory set for task j in $\mathcal{M}_i$ is always a subset of that in $\mathcal{M}_{i'}$ given $j \leq i' < i$.

4 An Offline Solution: Reduce the Search Space

In order to reduce the intractable search space of $\mathcal{M}_{\mathcal{T}}$ quantitatively, we first consider the dynamic memory construction problem in an offline setup as the starting point for analyzing the realistic online setting. In the offline setup, we can go through the task sequence for multiple trials independently, but we are still strictly not allowed to access previous examples that are not in $\mathcal{M}$ in each trial. We take three tactics to reduce the search space, referred to as the *equal memory heuristic*, the *base policy assumption* and the *switching point existence*. Fig. 1 illustrates how we apply three tactics to the S-CIFAR-10 dataset. Based on these tactics, we provide an approximate solution to the problem.

4.1 Equal Memory Buffer for Each Task

We first take the equal memory heuristic from [11], which has shown that an equal size of memory buffer for each observed task is effective to avoid catastrophic forgetting.[2] Based on this tactic, we add $|\mathcal{M}_{i,j}| = |\mathcal{M}|/i$, where $i \geq j$, to the previous constraints list. Given a fixed size of each $\mathcal{M}_{i,j}$, instead of optimizing $\mathcal{M}_i$ from previous observed tasks jointly, we can independently optimize each $\mathcal{M}_{i,j}$ and construct $\mathcal{M}_i$ from $\mathcal{M}_{i,j}$. To this end, we replace the optimization objective Eqn. (4) by a simplified version Eqn. (5), taking $\mathcal{M}_{i,j}$ as variables.

$$\min_{\{\mathcal{M}_{i,j}\}_{i,j \in \mathcal{T}}} \mathcal{L}_G(\{\mathcal{M}_{i,j}\}_{i,j \in \mathcal{T}}) \tag{5}$$

---

[2]For simiplicity of the formulation, we assume each task has the same number of classes in $\mathcal{M}$.

104 However, given the equal memory heuristic, the search space in Eqn. (5) is still very large. For each
105 task t_k, suppose the total number of examples for task t_k is n_k and $n_k > |\mathcal{M}|$, $\mathcal{M}_{i,k}$ has more than
106 $\binom{|\mathcal{M}|}{|\mathcal{M}|/i}$ different constructions.

4.2 Mix of Base Policies

108 To further reduce the search space in Eqn. (5), we introduce two base policies, ER-Res and ER-Ring-
109 Full [11]. For a given task t_i, ER-Res builds a memory by random samples, while ER-Ring-Full
110 builds a memory by selecting the same number of samples from each class.

111 We take the base policy assumption, where we deem that the memories having the same size and
112 taking the same base policies are the same. It implies that even though two memory buffers contain
113 different data examples, they are still identified as the same as long as they meet these two rules. This
114 assumption is backed up by [6] where the standard deviation of accuracy on different benchmarking
115 datasets is quite small ($\sim$0.5) when using the same policy with a relatively large $|\mathcal{M}|$. Based on the
116 assumption, we separate $\mathcal{M}_{i,j}$ into two disjoint parts and take the mixed policy, where $\mathcal{M}_{i,j}^{\text{res}}$ and
117 $\mathcal{M}_{i,j}^{\text{ring-full}}$ represent two parts in $\mathcal{M}_{i,j}$, namely the former taking the ER-Res and the latter taking ER-
118 Ring-Full policies, respectively. For completeness, we extend the subset constraint to $\mathcal{M}_{i,j}^{\text{res}} \subseteq \mathcal{M}_{i',j}^{\text{res}}$,
119 $\mathcal{M}_{i,j}^{\text{ring-full}} \subseteq \mathcal{M}_{i',j}^{\text{ring-full}}$, where $j \leq i' < i$.

120 Previous studies of ER [11] have shown the randomness (ER-Res) is crucial in a large memory, while
121 guaranteeing the equal representation of each class (ER-Ring-Full) is crucial under a tiny memory.
122 As the number of tasks grows, the size of memory for each task t_i becomes smaller. Under a mixed
123 policy, it is natural to first shrink the ER-Res part of the memory and then shrink the ER-Ring-Full
124 part of the memory. By doing so, given $\mathcal{M}_{j,j}^{\text{res}}$ and $\mathcal{M}_{j,j}^{\text{ring-full}}$, we can determine $\mathcal{M}_{i,j}^{\text{res}}$ and $\mathcal{M}_{i,j}^{\text{ring-full}}$
125 accordingly for each $i > j$. We denote the size of $\mathcal{M}_{j,j}^{\text{ring-full}}$ as a_j and derive the size of $\mathcal{M}_{j,j}^{\text{res}}$ as
126 $(|\mathcal{M}|/j) - a_j$. Substituting the collection of sets $\{\mathcal{M}_{i,j}\}_{i,j \in \mathcal{T}}$ by an integer variable a_j, we therefore
127 further simplify the optimization objective, as in Eqn. (6).

$$\min_{\{a_j\}_{j \in \mathcal{T}}} \mathcal{L}_G(\{a_j\}_{j \in \mathcal{T}}) \tag{6}$$

128 where each a_j has $|\mathcal{M}|/j$ different choices, significantly smaller than the search space for $\mathcal{M}_{i,j}$ in
129 Eqn. (5). However, the total search space equals to $|\mathcal{M}|^{T-1}/(T-1)!$, which is still large.

4.3 Existence of a Switching Point

131 For the memory allocation after each task t_j, there exists a gold point $a_j = s_j$ that assigns exactly the
132 *required* ring-full memory to keep the best balance of $\mathcal{M}_{i,j}^{\text{ring-full}}$ and $\mathcal{M}_{i,j}^{\text{res}}$ for the following task t_i. If
133 the ring-full memory size is not large enough, we lose the power of forcing an equal representation
134 of classes as the task sequence grows. Conversely, if the ring-full memory is more than enough, we
135 sacrifice the randomness when the task number is still small. To this end, we assume s_j is a unique
136 switching point, *i.e.*, there exists a switching point s_j for each a_j, which satisfies the monotonicity

$$\mathcal{L}_G(\{a_j'\} \cup \{a_i\}_{i \in \mathcal{T}/\{j\}}) > \mathcal{L}_G(\{a_j\} \cup \{a_i\}_{i \in \mathcal{T}/\{j\}}), \quad a_j' < a_j < s_j \text{ or } s_j < a_j < a_j' \tag{7}$$

137 Given the switching point existence, though we still have the same search space, instead of a linear
138 search, we can apply a binary search algorithm to reduce the time complexity to $O(T \log |\mathcal{M}|)$. Note
139 that if we search by comparing against the exact left and right integer of the point, *i.e.*, comparing the
140 loss computed by $a_j + 1, a_j - 1$ and a_j, the variance of sampling may cause the algorithm to exit
141 unexpectedly. To increase the robustness of the algorithm, we take a search stride $\epsilon = 20$, where we
142 compare the loss computed by $a_j + \epsilon, a_j - \epsilon$ and a_j. The detailed binary search algorithm for s_j can
143 be found in our Appendix A.

144 This assumption is valid for over 95% of the cases from the observations in Fig. 1 (for the S-CIFAR-10
145 dataset) and Appendix B (for other benchmarks). For each a_j (*i.e.*, $|\mathcal{M}_{j,j}^{\text{ring-full}}|$) in the figures, the
146 global loss $\mathcal{L}_G$ initially decreases monotonically and then increases monotonically as a_j grows.
147 Rarely but possible, due to the variance of sampling, we cannot find the switching point s_j. In such
148 cases, we will choose a_j with the minimum loss amongst the values we searched.

5 Global Pseudo-task Simulation (GPS)

The offline solution of dynamic memory construction requires going through the task sequence for $O(T \log |\mathcal{M}|)$ times to find $\{s_j\}_{j \in \mathcal{T}}$, which violates the online continual learning setup. To circumvent this issue, we propose Global Pseudo-task Simulation (GPS), which provides an approximate solution $\{\tilde{s}_j\}_{j \in \mathcal{T}}$ to the problem by simulating the future training process under the online setup. Specifically, we simulate the local updating process Eqn. (2) by creating *pseudo-future tasks*.

5.1 Objective Function for Simulation

Perfectly simulating the future is a mission impossible in continual learning [19]. As we have no information about the future tasks, the distribution of the pseudo-future tasks we create could be quite different from the distribution of the real future ones. To find each approximated switching point $\tilde{s}_j$ more precisely, we intend to use more real tasks and less pseudo-future tasks as possible. As we are required to allocate examples of task t_j to a non-empty set $\mathcal{M}_{j,j}$ right after training the task t_j, we solve $\tilde{s}_j$ by a simulation process from θ_j to θ_T, without future modifications.

To this end, we modify the offline objective function Eqn. (6) to the online simulation objective Eqn. (8), where $\tilde{\theta}_{j:i}$ is the simulated θ_i from the real θ_j, for $i > j$.

$$\tilde{s}_j = \arg\min_{a_j} \mathbb{E}_{(x_j, y_j) \sim P_j} \ell(y_j, f(x_j; \tilde{\theta}_{j:T})) \tag{8}$$

Note that $\tilde{\theta}_{j:T}$ is derived recursively from $\tilde{\theta}_{j:i} = g(\tilde{\theta}_{j:(i-1)}, \tilde{P}_i, \tilde{\mathcal{M}}_{i-1})$, initialized with $\tilde{\theta}_{j:j} = \theta_j$. $\tilde{P}_i$ is the task distribution of the synthesized pseudo-tasks $\tilde{t}_i$, and $\tilde{\mathcal{M}}_i$ is the simulated pseudo-memory after training the pseudo-task $\tilde{t}_i$. We restrict the global objective to the evaluation of task t_j, as we cannot access the previous tasks as well as the future tasks. We show in Appendix C that the summed global loss $\mathcal{L}_G$ correlates with the global loss of a single task t_j positively as a function of a_j.

5.2 Synthesizing Pseudo-tasks

The goal of our pseudo-task simulation is to find s_j precisely, *i.e.*, $\tilde{s}_j \approx s_j$. Concretely, instead of accurately simulating the future training process, we use synthesized pseudo-tasks to *mimic the forgetting patterns of task t_j caused by the future tasks*. To achieve this, we expect the pseudo-tasks to hold two properties.

First, a pseudo-task $\tilde{t}_j$ should have similar difficulty as its real counterpart t_j in the future, measured by the accuracy in an identical end-to-end training setup. Otherwise, they are likely to induce different level of catastrophic forgetting [31]. Though we cannot forecast the future tasks, we observe that most widely used continual learning benchmarks [6, 23, 40] assume that tasks in a sequence have similar difficulties, detailed in our Appendix C.1. To this end, we expect the synthesized pseudo-future tasks to have similar difficulty as the previous tasks.

Second, a pseudo-future task should allow limited forward transfer from the current task. If pseudo-tasks can achieve high zero-shot accuracy with the model trained on the current task, the similarity between tasks could result in very little forgetting after training on the pseudo-tasks, hindering our purpose of mimicking the catastrophic forgetting.

Based on these two properties, we synthesize pseudo-future tasks from the task t_j by applying different permuting seeds to its input x_j to create a series of future tasks $\{\tilde{t}_{j+1}, ..., \tilde{t}_T\}$. We achieve this by permuting the pixels of each image on image datasets, i.e., a fresh permutation would be generated and applied to all images within a synthesized task [50].

Besides permutation, we have also considered two other synthesizing techniques that lack a certain property we discussed for comparison. One is rotation, where we rotate the image inputs of the task t_j gradually by 15 degrees to create pseudo-future tasks [6]. The other is blurring, where we repeatedly average pool the image with a 2×2 filter and rescale to create pseudo-future tasks. Rotation creates pseudo-tasks with similar difficulties as the real tasks, but the forward transferability is far too good. Blurring creates pseudo-tasks with limited forward transferability, yet the task difficulty is increasing along the pseudo-task sequence.

5.3 Construct Pseudo-memories

Fig. 2 visualizes the process of pseudo-task training and pseudo-memory construction. During the simulation process after task t_j, we try different a_j with a binary search and pick the best one as $\tilde{s}_j$ based on the online objective Eqn. (8).

We start from $\tilde{\mathcal{M}}_j$, which is the same as the real $\mathcal{M}_j$. The construction for $\tilde{\mathcal{M}}_i$ ($i > j$) is different for real tasks and pseudo-tasks. For real tasks $t_{j'}, j' \in \{1, ..., j\}$, $\tilde{\mathcal{M}}_{i,j'}$ is the real $\mathcal{M}_{i,j'}$ determined for a given $a_{j'}$, as we discussed in § 4.2. Note that the approximated switching points $\{\tilde{s}_{j'}\}_{j' \in \{1,...,j-1\}}$ for the previous $j-1$ tasks are solved before $\tilde{s}_j$. For pseudo-tasks $\tilde{t}_{j'}, j' \in \{j+1, ..., i\}$, $\tilde{\mathcal{M}}_{i,j'}$ is constructed by randomly selecting $|\mathcal{M}|/i$ pseudo-data from $\tilde{t}_{j'}$.

Figure 2: The Global Pseudo-task Simulation process to solve a_j after training task t_j.

5.4 Other Implementation Details

For the efficiency of simulation, the number of examples of the synthesized pseudo-tasks we use in the simulation is equal to $|\mathcal{M}|$. As the simulation quickly converges on a small number of examples, we train fewer epochs for each task compared with the real training process. Besides, when the number of tasks T are large or unknown, we extend GPS by simulating a fixed-sized sliding window of future tasks for the sequence, *e.g.*, simulating 10 pseudo-future tasks for each task. Also, during the local update of each task t_i, for a smooth transition, we allow the current training task t_i to take up to $|\mathcal{M}|/i$ the size of the memory without changing $\mathcal{M}_{i,j}$ for any previous task t_j.[3] We also put the detailed algorithm for GPS in Appendix A.

6 Experiments

6.1 Experimental Setup

Datasets We carry out evaluations on four widely used vision benchmarks in continual learning, **P-MNIST**, **S-CIFAR-10**, **S-CIFAR-100** and **TinyImageNet** [40, 6, 23]. P-MNIST was proposed in [16]. It contains 10 tasks where the first task is the MNIST dataset [21] while the later ones are constructed by permuting each image in MNIST with an unique permutation seed. The S-CIFAR-10 is constructed by splitting CIFAR-10 [1] into 5 sequential tasks where each task contain 2 classes and 12,000 images [20, 6]. Similarly, we split CIFAR-100 [1] into 10 tasks where each one contains 10 classes and 6, 000 images to construct S-CIFAR-100. The TinyImagenet [45] is a subset of ImageNet [14] with 200 classes. We split it into 10 consecutive tasks with 20 classes per task.

Architectures For P-MNIST, we apply a fully connected network with two hidden layers. Each comprises 100 ReLU units. For S-CIFAR-10, S-CIFAR-100 and TinyImageNet, we use Resnet18 following [6] and [13].

Baselines The baselines we used in experiments include ER-Res, ER-Ring-Full and ER-Hybrid [11]. ER-Hybrid is a mix of ER-Res and ER-Ring-Full, where the memory construction strategy would switch from the former to the latter once observing only one sample of some class is left in $\mathcal{M}$. We also compare to non-ER methods: online EWC (oEWC) [41], iCaRL [34], A-GEM [10] and GSS [4].

Training Details: Our training all use stochastic gradient descent (SGD) with a learning rate of 0.1. We use $\lambda = 1$ in the local updating method Eqn. (2). For P-MNIST, we train 5 epochs for each task while increasing the number of epochs to 50 for S-CIFAR-10, 100 for both S-CIFAR-100

---

[3]We will release our code at https://github.com/anonymous

Table 1: Accuracy of GPS using different simulation techniques and baselines on four vision benchmarks. ER-Oracle shows the performance of the offline solution as described in § 4. Reported numbers are all averaged over 5 runs.

Method $|\mathcal{M}|$	Simulation	P-MNIST 1000	S-CIFAR-10 200	S-CIFAR-100 2000	TinyImageNet 2000
ER-Res	-	$86.55_{\pm0.48}$	$92.01_{\pm0.80}$	$81.38_{\pm0.51}$	$61.50_{\pm0.54}$
ER-Ring-Full	-	$84.33_{\pm0.65}$	$91.53_{\pm0.56}$	$81.16_{\pm0.65}$	$61.24_{\pm0.32}$
ER-Hybrid	-	$86.84_{\pm0.35}$	$92.46_{\pm0.89}$	$81.47_{\pm0.23}$	$61.77_{\pm0.44}$
GPS	**Permutation**	$\mathbf{88.93_{\pm0.11}}$	$\mathbf{93.57_{\pm0.39}}$	$\mathbf{82.76_{\pm0.33}}$	$\mathbf{63.10_{\pm0.23}}$
	Rotation	$86.38_{\pm0.20}$	$92.61_{\pm0.49}$	$82.10_{\pm0.42}$	$62.45_{\pm0.33}$
	Blurring	$87.03_{\pm0.31}$	$92.96_{\pm0.38}$	$82.09_{\pm0.46}$	$62.85_{\pm0.27}$
ER-Oracle	Offline	$89.10_{\pm0.15}$	$93.60_{\pm0.35}$	$82.98_{\pm0.31}$	$63.54_{\pm0.32}$

and TinyImageNet regarding their data complexity, as done by works [6, 40]. For P-MNIST and S-CIFAR-10, we set the batch size as 10. For S-CIAFR-100 and TinyImageNet, batch size is set to 50. Following the implementation of ER [11], we set the same batch size for training the current task and the memory. Note the permutation seeds we use for simulation in P-MNIST is different from the ones used in P-MNIST itself to avoid peeping into test datasets. More training details and hyperparameter values can be found in the Appendix F.

6.2 Main Results

Our GPS using permutation shows improved accuracy compared to other baselines in Table 1. Its performance is close to the performance of the offline oracle solution, which implies it is a good approximation. We can also see that GPS using permutation performs better than using rotation and blurring, in terms of both accuracy and stability. The results support our hypotheses on the properties that synthesized tasks should bear, *i.e.*, similar level difficulties to previous tasks and limited forward transfer ability. We compute the L1-norm of the offline sampling ratios *vs*. permuting-simulated sampling ratios, which are 1.4, 1.7, 1.6 for P-MNIST, S-CIFAR-100 and TinyImageNet, respectively. This shows the method selects sampling ratios for other benchmarks almost as good as that for the P-MNIST, which implies the similarity of pseudo-tasks is not the major factor for the enhanced results.

Besides, we notice that the GPS using different simulation techniques is more stable as it achieves lower standard deviation on almost every evaluation dataset. We attribute this to the reduced interference from random seeds as we take the global objective into explicit consideration. We have also included the experimental results of GPS with smaller memory in Appendix D.1.

Method	$T = 20$	$T = 40$
ER-Res	$73.25_{\pm1.07}$	$47.33_{\pm2.75}$
ER-Ring-Full	$73.92_{\pm1.47}$	$49.26_{\pm2.66}$
ER-Hybrid	$74.87_{\pm0.88}$	$51.13_{\pm2.61}$
GPS	$\mathbf{77.93_{\pm0.20}}$	$\mathbf{56.57_{\pm0.63}}$
ER-Oracle	$78.51_{\pm0.17}$	$57.10_{\pm0.51}$

(a)   (b)   (c)

Figure 3: (a). Global loss of task t_3 from the S-CIFAR-100 benchmark w.r.t. different configurations of $\mathcal{M}_{3,3}$. The blue stars mark the switching points. (b). The loss of task t_3 after training future tasks. (c). Accuracy of GPS and baselines in long task sequence on P-MNIST.

6.3 Analysis of Simulation Methods

To further understand why permutation works better than other simulation techniques, we analyze the task t_3 of the S-CIFAR-100 benchmark. We plot the curve of global loss w.r.t. the ratio of

Table 2: (a). Time cost (in minutes) of training *vs*. simulation for P-MNIST and S-CIFAR-10. (b). Accuracy of GPS when incorporating existing ER variants, DER++ [6] and HAL[9], comparing to other methods.

(a)

Short Seq	# Tasks	Training	Simulation
P-MNIST	10	26.32	2.30
S-CIFAR-10	5	545.56	10.02
S-CIFAR-100	10	1187.93	137.63
TinyImageNet	10	2418.20	209.98
Long Seq	# Tasks	Training	Simulation
P-MNIST	20	55.29	6.21
P-MNIST	40	108.17	13.37

(b)

	P-MNIST	TinyImageNet
oEWC	$69.21_{\pm 2.92}$	$20.81_{\pm 0.95}$
iCaRL	-	$38.77_{\pm 3.68}$
GSS	$86.34_{\pm 4.28}$	-
A-GEM	$77.36_{\pm 1.28}$	$25.30_{\pm 0.87}$
OGD	$81.52_{\pm 2.21}$	-
HAL	$87.69_{\pm 0.34}$	$61.27_{\pm 1.10}$
GPS+HAL	$\mathbf{88.73_{\pm 0.03}}$	$\mathbf{63.24_{\pm 0.80}}$
DER++	$91.14_{\pm 0.22}$	$62.67_{\pm 1.08}$
GPS+DER++	$\mathbf{91.84_{\pm 0.16}}$	$\mathbf{63.01_{\pm 0.98}}$

ER-Ring-Full in the memory $\mathcal{M}_{3,3}$, and the forgetting curve of task t_3 after training future tasks, as in Fig. 3.

We can see that the rotation induces less forgetting (lower loss) than the real tasks (offline cases) along the sequence, as shown in Fig. 3(b), as rotation creates tasks sequences that bear good zero-shot transfer from the previous tasks. The pseudo-task sequence created by rotation is therefore too easy such that the switching point of the curve is close to 0, as shown in the Fig. 3(a), which implies it is similar to an ER-Res static policy. As for the blurring, the forgetting curve first climbs slowly, as it allows some forward transfer from the previous tasks. And then, the loss increases dramatically since the task difficulty goes up. Its pattern of forgetting is quite different from the real tasks (offline case) as shown in the Fig. 3(b). These empirical results have backed up our hypotheses in § 5.2.

We can also observe that the GPS using permutation has the closest switching point to the offline compared to the rest. Though permutation creates pseudo-task sequence that result in higher losses than the real task sequence, the pattern of forgetting is similar[4].

6.4 Long Task Sequence

We extend the 10-task P-MNIST benchmark to 20 and 40 tasks to create a longer task sequence. Fig. 3(c) implies the dynamic memory construction is even more crucial when the task sequence is long in continual learning. The offline solution, *i.e.*, ER-Oracle, outperforms the baseline policies by more than 5% accuracy when $T = 40$. We attribute the performance gain to optimizing the global objective directly. From the Fig. 3(c), We can also see that GPS solves the problem significantly better than the baselines. Interestingly, the GPS still achieves close performance to the offline solution when the task sequence is long, in terms of both accuracy and stability, which implies the final loss of task t_j (Eqn. (8)) correlates positively with the loss of task t_j after a long sequence of tasks.

6.5 Simulation Time Cost

We show the time cost of standard training (excluding simulation) *vs*. simulation (pseudo-task generation and training) process in GPS in Table 2(a). We take the asynchronous simulation, which applies a binary search to determine $\tilde{s}_j$ sequentially in $O(T \log |\mathcal{M}|)$ sweeps. Suppose simulating the training of each pseudo-task takes a unit time, each sweep is in $O(T)$. Then, the total simulation process is in $O(T^2 \log |\mathcal{M}|)$, which is dependent on the memory buffer size and the number of simulation training epochs. We disclose those values for each dataset in Appendix D.3. When the task sequence is short, from Table 2(a), we can see the simulation time is over ten times less than the standard training time. When the task sequence is long, we can see the simulation cost grows linearly w.r.t. the number of tasks, as we restrict the search window from $T - j$ to 10 to prevent the simulation cost increasing quadratically.

---

[4]In the following text, we refer to "GPS using permutation" as GPS.

6.6 Exploration of Other Local Updating Methods

We show the performance of adopting other local updating methods from the existing ER variants besides Eqn. 2, together with GPS. The exemplar base policies we take are from the DER++ and HAL. DER++ leverages knowledge distillation in the episodic memory construction. HAL selects pivotal learned data points besides random samples to store in the $\mathcal{M}$.

We change the local updating method from Eqn. (2) to the local updating method used in DER++ or HAL respectively to transplant them into GPS, without any other modifications to the algorithm. From Table 2(b), we can see the performance of DER++ and HAL has been further improved by taking the optimized memory construction for $\mathcal{M}$ by GPS. As the SOTA method DER++ outperforms other non-ER methods, GPS+DER++ naturally outperforms them.

7 Related Works

Continual Learning   Enabling an intelligent agent to learn progressively and adaptively without forgetting old knowledge is a long-standing objective in AI [46, 36]. To combat the catastrophic forgetting problem [28, 16], a few methods have been proposed in continual learning [12, 3, 13]. They usually can be categorized into three classes. One is the regularization-based methods, which introduce an additional regularization term in the loss function to consolidate old behaviors when learning new tasks [18, 41, 49, 8, 17, 33, 15]. One is the replay methods, which store a tiny amount of old examples in a size-bounded memory or condense previous knowledge in a generative model to generate pseudo samples [24, 43, 2, 9, 6, 11, 37, 2, 22, 44, 47, 7, 32]. The data stored in the buffer would be revisited and trained together with each current training task. The third is the parameter isolation methods, which usually allocate additional neural resources for new knowledge without constraints on the model size [39, 27, 42, 48]. The memory cost of these methods would therefore scale with the number of tasks.

The ER Family   Experience replay falls into the replay method category, which takes a fixed-sized buffer to store old examples. Existing experience replay variants have adopted the same setup as ER, and focus on refining the local updating method, *i.e.* how to optimally update model parameters by joint training of current task and examples in memory. The advanced techniques used to improve local updating step include additional regularization [9], knowledge distillation [5, 6] and selective memory sampling [2, 32]. Distinct to vanilla ER or its variants, which implicitly minimize the global loss of the final model parameters by designing a powerful local updating method, our work focus on directly optimizing the global objective function by creating pseudo-tasks to mimic the catastrophic forgetting for the current task.

8 Conclusion

In this paper, we propose the dynamic memory construction optimization problem for continual learning under the experience replay setup. The problem aims at finding the best memory construction strategy to optimize the global objective function in continual learning. We simplify the problem to a small space by taking three tactics, and find a solution in time complexity $O(T \log |\mathcal{M}|)$ in an offline setup. We then officially introduce our Global Pseudo-task Simulation (GPS), which provides an approximate solution to the simplified problem under the realistic online setup by creating pseudo-tasks to mimic the future catastrophic forgetting pattern for the current task. Our empirical results have shown our approach outperforms baselines and can improve the accuracy of existing ER variants [9, 6].

Future Studies   Some future improvements could be extending the Global Pseudo-task Simulation to task-agnostic scenarios in continual learning as we focus on the task- and domain-incremental in this work, where the task identity is known. This can potentially be achieved by triggering the simulation after experiencing a certain amount of data points instead of a task. Also, our GPS method with permutation is potentially limited when dealing with task sequences with variant difficulties or *specific* forward transfer patterns, as the pseudo-tasks have little to no forward transfer abilities. In such cases, we may need to customize simulation methods to mimic the forgetting of the future. We hope our work could inspire the community to design new datasets closer to the real-world setting.

References

[1] Learning multiple layers of features from tiny images, 2009.

[2] Rahaf Aljundi, Lucas Caccia, Eugene Belilovsky, Massimo Caccia, Min Lin, Laurent Charlin, and Tinne Tuytelaars. Online continual learning with maximally interfered retrieval, 2019.

[3] Rahaf Aljundi, Punarjay Chakravarty, and Tinne Tuytelaars. Expert gate: Lifelong learning with a network of experts, 2017.

[4] Rahaf Aljundi, Min Lin, Baptiste Goujaud, and Yoshua Bengio. Gradient based sample selection for online continual learning, 2019.

[5] Ari S. Benjamin, David Rolnick, and Konrad Kording. Measuring and regularizing networks in function space, 2019.

[6] Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara. Dark experience for general continual learning: a strong, simple baseline, 2020.

[7] Francisco M. Castro, Manuel J. Marín-Jiménez, Nicolás Guil, Cordelia Schmid, and Karteek Alahari. End-to-end incremental learning, 2018.

[8] Arslan Chaudhry, Puneet K. Dokania, Thalaiyasingam Ajanthan, and Philip H. S. Torr. Riemannian walk for incremental learning: Understanding forgetting and intransigence. *Lecture Notes in Computer Science*, page 556–572, 2018.

[9] Arslan Chaudhry, Albert Gordo, Puneet K. Dokania, Philip Torr, and David Lopez-Paz. Using hindsight to anchor past knowledge in continual learning, 2021.

[10] Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with a-gem, 2019.

[11] Arslan Chaudhry, Marcus Rohrbach, Mohamed Elhoseiny, Thalaiyasingam Ajanthan, Puneet K. Dokania, Philip H. S. Torr, and Marc'Aurelio Ranzato. On tiny episodic memories in continual learning, 2019.

[12] Zhiyuan Chen, Bing Liu, Ronald Brachman, Peter Stone, and Francesca Rossi. *Lifelong Machine Learning*. Morgan amp; Claypool Publishers, 2nd edition, 2018.

[13] Matthias Delange, Rahaf Aljundi, Marc Masana, Sarah Parisot, Xu Jia, Ales Leonardis, Greg Slabaugh, and Tinne Tuytelaars. A continual learning survey: Defying forgetting in classification tasks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, page 1–1, 2021.

[14] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009.

[15] Arthur Douillard, Eduardo Valle, Charles Ollion, Thomas Robert, and Matthieu Cord. Insights from the future for continual learning, 2020.

[16] Ian J. Goodfellow, Mehdi Mirza, Da Xiao, Aaron Courville, and Yoshua Bengio. An empirical investigation of catastrophic forgetting in gradient-based neural networks, 2015.

[17] Heechul Jung, Jeongwoo Ju, Minju Jung, and Junmo Kim. Less-forgetting learning in deep neural networks, 2016.

[18] James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, Demis Hassabis, Claudia Clopath, Dharshan Kumaran, and Raia Hadsell. Overcoming catastrophic forgetting in neural networks, 2017.

[19] Jeremias Knoblauch, Hisham Husain, and Tom Diethe. Optimal continual learning has perfect memory and is np-hard, 2020.

[20] Alex Krizhevsky. Learning multiple layers of features from tiny images. 2009.

[21] Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[22] Sang-Woo Lee, Jin-Hwa Kim, Jaehyun Jun, Jung-Woo Ha, and Byoung-Tak Zhang. Overcoming catastrophic forgetting by incremental moment matching, 2018.

[23] Sebastian Lee, Sebastian Goldt, and Andrew Saxe. Continual learning in the teacher-student setup: Impact of task similarity, 2021.

[24] Timothée Lesort, Alexander Gepperth, Andrei Stoian, and David Filliat. Marginal replay vs conditional replay for continual learning, 2019.

[25] Zhizhong Li and Derek Hoiem. Learning without forgetting, 2017.

[26] David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning, 2017.

[27] Arun Mallya and Svetlana Lazebnik. Packnet: Adding multiple tasks to a single network by iterative pruning, 2018.

[28] Michael McCloskey and Neal J. Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. volume 24 of *Psychology of Learning and Motivation*, pages 109–165. Academic Press, 1989.

[29] Seyed Iman Mirzadeh, Mehrdad Farajtabar, Razvan Pascanu, and Hassan Ghasemzadeh. Understanding the role of training regimes in continual learning, 2020.

[30] Behnam Neyshabur, Hanie Sedghi, and Chiyuan Zhang. What is being transferred in transfer learning?, 2021.

[31] Cuong V. Nguyen, Alessandro Achille, Michael Lam, Tal Hassner, Vijay Mahadevan, and Stefano Soatto. Toward understanding catastrophic forgetting in continual learning, 2019.

[32] Ameya Prabhu, Philip Torr, and Puneet Dokania. Gdumb: A simple approach that questions our progress in continual learning. In *The European Conference on Computer Vision (ECCV)*, August 2020.

[33] Amal Rannen, Rahaf Aljundi, Matthew B. Blaschko, and Tinne Tuytelaars. Encoder based lifelong learning. *2017 IEEE International Conference on Computer Vision (ICCV)*, Oct 2017.

[34] Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H. Lampert. icarl: Incremental classifier and representation learning, 2017.

[35] Matthew Riemer, Ignacio Cases, Robert Ajemian, Miao Liu, Irina Rish, Yuhai Tu, and Gerald Tesauro. Learning to learn without forgetting by maximizing transfer and minimizing interference, 2019.

[36] Mark B. Ring. Child: A first step towards continual learning. In *Learning to Learn*, 1998.

[37] David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy P. Lillicrap, and Greg Wayne. Experience replay for continual learning, 2019.

[38] Sebastian Ruder and Barbara Plank. Learning to select data for transfer learning with bayesian optimization, 2017.

[39] Andrei A. Rusu, Neil C. Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks, 2016.

[40] Gobinda Saha, Isha Garg, and Kaushik Roy. Gradient projection memory for continual learning, 2021.

[41] Jonathan Schwarz, Jelena Luketina, Wojciech M. Czarnecki, Agnieszka Grabska-Barwinska, Yee Whye Teh, Razvan Pascanu, and Raia Hadsell. Progress & compress: A scalable framework for continual learning, 2018.

[42] Joan Serrà, Dídac Surís, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task, 2018.

[43] Hanul Shin, Jung Kwon Lee, Jaehong Kim, and Jiwon Kim. Continual learning with deep generative replay, 2017.

[44] Konstantin Shmelkov, Cordelia Schmid, and Karteek Alahari. Incremental learning of object detectors without catastrophic forgetting, 2017.

[45] Stanford. Tiny ImageNet Challenge (CS231n), 2015. `http://tiny-imagenet.herokuapp.com/`.

[46] Sebastian Thrun. Lifelong learning algorithms. In *Learning to Learn*, 1998.

[47] Yue Wu, Yinpeng Chen, Lijuan Wang, Yuancheng Ye, Zicheng Liu, Yandong Guo, and Yun Fu. Large scale incremental learning, 2019.

[48] Jaehong Yoon, Eunho Yang, Jeongtae Lee, and Sung Ju Hwang. Lifelong learning with dynamically expandable networks, 2017.

[49] Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual learning through synaptic intelligence, 2017.

[50] Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization, 2017.