PROPERTY CONTROLLABLE VARIATIONAL AUTOENCODER VIA INVERTIBLE MUTUAL DEPENDENCE

ABSTRACT

Deep generative models have made important progress towards modeling complex, high dimensional data via learning latent representations. Their usefulness is nevertheless often limited by a lack of control over the generative process or a poor understanding of the latent representation. To overcome these issues, attention is now focused on discovering latent variables correlated to the data properties and ways to manipulate these properties. This paper presents the new Property-controllable VAE (PCVAE), where a new Bayesian model is proposed to inductively bias the latent presentation using explicit data properties via novel group-wise and property-wise disentanglement terms. Each data property corresponds seamlessly to a latent variable, by innovatively enforcing invertible mutual dependence between them. This allows us to move along the learned latent dimensions to control specific properties of the generated data with great precision. Quantitative and qualitative evaluations confirm that the PCVAE outperforms the existing models by up to 28% in capturing and 65% in manipulating the desired properties.

1 INTRODUCTION

Important progress has been made towards learning the underlying low-dimensional representation and generative process of complex high dimensional data such as images (Pu et al., 2016), natural languages (Bowman et al., 2016) and chemical molecules (Kadurin et al., 2017) via deep generative models. In recent years, a surge of research has developed new ways to further enhance the disentanglement and independence of the latent dimensions, creating models with better robustness, improved interpretability, and greater generalizability with inductive bias (see Figures 1(a) and 1(b)) (Kingma et al., 2014; Kulkarni et al., 2015; Creswell et al., 2017) or without any bias (Higgins et al., 2017; Chen et al., 2018; Kumar et al., 2018). Although it is generally assumed that the complex data is generated from the latent representations, their latent dimensions are typically not associated with physical meaning and hence cannot reflect real data generation mechanisms such as the relationships between structural and functional characteristics. A critical problem that remains unsolved is how to best identify and enforce the correspondence between the learned latent dimensions and key aspects of the data, such as the bio-physical properties of a molecule. Knowing such properties is crucial for many applications that depend on being able to interpret the data and control the data generation to yield the desired properties.

(a) CondVAE   (b) CondVAE-info   (c) CSVAE   (d) PCVAE (ours)

Figure 1: While most existing models (e.g., Sub-figures (a) and (b)) do not explicitly learn the correspondence between latent dimensions and data properties, some recent work (Sub-figures (c) and (d)) has started to explore this. The generative model (right) and its model inference (left) are shown in each sub-figure. Dotted arrows represent the enforcement of independence and double arrows represent the invertible mapping between two variables. x refers to data, z and w refer to two subsets of latent variables, and y refers to the properties.

In an effort to achieve this, several researchers (Klys et al., 2018; Locatello et al., 2019b) have suggested methods that enforce a subset of latent dimensions correspond to targeted categorical properties, as shown in Figure 1(c). Though the initial results have been encouraging, critical challenges remain unsolved such as: (1) **Difficulty in handling continuous-valued properties**. The

control imposed on data generation limits existing techniques to categorical (typically binary) properties, to enable tractable model inference and sufficient coverage of the data. However, continuous-valued properties (e.g., the scale and light level of images) are also common in real world data, while their model inference usually can be easily intractable. Also, many cases require to generate data with properties of which the values unseen during training process. This cannot be achieved by conventional techniques such as conditional models without making strong assumption on the model distributions. (2) **Difficulty in efficiently enhancing mutual independence among latent variables relevant and irrelevant to the properties**. This problem requires to ensure that each property is only correlated to its corresponding latent variable(s) and independent of all the others. Directly enforcing such mutual independence inherently between all pairs of latent variables incurs exponential number of pairs among properties and latent variables for such enforcement. Hence an efficient way is imperative. (3) **Difficulty in capturing and controlling correlated properties**. It is feasible that several independent latent variables can capture multiple independent properties via one-on-one mapping. But when the properties are correlated, they cannot be "one-on-one" mapped to corresponding independent latent variables anymore. However, correlated properties are commonly found in formatting a real world data. For example, when describing molecules, the properties *cLogP* and *cLogS* are dependent.

To solve the above challenges, we propose a new model, Property-controllable VAE (PCVAE), where a new Bayesian model is proposed to inductively bias the latent representation using explicit data properties via novel group-wise and property-wise disentanglement terms. Each data property is seamlessly linked to the corresponding latent variable by innovatively enforcing an invertible mutual dependence between them, as shown in Figure 1(d). Hence, when generating data, the corresponding latent variables are manipulated to simultaneously control multiple desired properties without influencing the others. We have also further extended our model to handle inter-correlated properties. Our key contributions are summarized as follows:

- A new Bayesian model that inductively biases the latent representation using explicit real data properties is proposed. A variational inference strategy and inference model have been customized to ensure effective Bayesian inference.

- Group-wise and property-wise disentanglement terms are proposed to enhance the mutual independence among property relevant and irrelevant latent variables .

- The invertible mutual dependence between property-latent variable pair is achieved by enforcing an invertibility constraint over a residual-based decoder.

- The quantitative and qualitative evaluation performed for this study revealed our PCVAE outperforms existing methods by up to 28% in capturing and 65% in manipulating the desired properties.

2 RELATED WORKS

Disentanglement Representation Learning. An important relevant area of research is disentangled representation learning (Alemi et al., 2017; Chen et al., 2018; Higgins et al., 2017; Kim & Mnih, 2018), which structures the latent space by minimizing the mutual information between all pairs of latent variables. The goal here is to learn representations that separate out the underlying explanatory factors responsible for variations in the data as these have been shown to be relatively resilient with respect to the complex variants involved (Bengio et al., 2013), and thus can be used to enhance generalizability as well as improve robustness against adversarial attack. However, as noted by Locatello et al. (2019a), the unsupervised learning of disentangled representations is impossible to capture the desired properties without supervision and inductive biases.

Learning latent representations via supervision. This ensures that the latent variables capture the desired properties though supervision, generally by directly defining properties as latent variables in the model (Locatello et al., 2019b). Unfortunately, apart from providing an explicit variable for the labelled property, this yields no other easily interpretable structures, for example discovering latent variables that are correlated to the properties, as the model proposed in the current study does. This is also an issue with other methods of structuring latent space that have been explored, such as batching data according to labels (Kulkarni et al., 2015) or using a discriminator network in a non-generative model (Lample et al., 2017). Some researchers have addressed this problem by linking latent variables with observed labels through adversarial learning (Creswell et al., 2017; Edwards & Storkey, 2015; Ganin et al., 2016; Mathieu et al., 2016). The most relevant work for our purposes is

CSVAE (Klys et al., 2018), where a subset of latent variables are correlated with binary properties via an adversarial learning. All the above works are limited when it comes to handling multiple continuous-valued properties due to their strict assumptions on the distribution of properties.

Data manipulation and generation. Here, trained machine earning models are utilized to manipulate and generate data in a controllable way with the desired properties, which is especially useful for applications in the image domain. Several works have specifically considered transferring attributes in images, which is the same goal as that in the CASVE. These earlier works (Zhou et al., 2017; Xiao et al., 2017; 2018) all transfer attributes from a source image onto a target image. These models can only perform categorical attribute transformation between images (e.g., "splice the beard style of image A onto image B"), but only through interpolation between existing images. Once trained, our proposed model can generate an objects with any value of a certain property (either observed or unobserved during training) that can be encoded in the subset of latent variables.

3 PROPERTY CONTROLLABLE VAE

3.1 PROBLEM FORMULATION

Suppose we are given a dataset $\mathcal{D}$ where each data instance is (x, y) with $x \in \mathbb{R}^n$ and $y = \{y_k \in \mathbb{R}\}_{k=1}^K$ to represent K properties of interest of x. For example, if x is a molecule, then we may have properties of interest, such as *cLogP* and *cLogS*. We assume that the data (x, y) are generated by some random process from continuous latent random variables (z, w). Each variable in w controls one of the properties of interest in y, while the variables in z control all the other aspects of x.

Our goal is to learn such a generative model involving (x, y) and (z, w), where the subset of variables (i.e., z) are disentangled from subset w, and the variables inside w are disentangled from each other. Once this model has been learned, then we can expect different elements of variables in w to control different properties of interest, which is a highly desirable goal for many data generation downstream tasks. For example, we may want to decrease the value of a specific property (e.g., protein energy) by changing the value of the corresponding element in w. It is also possible to directly set a desired property value (e.g., the mass of a molecule) and then generate the corresponding x with this target value (i.e., a molecule with the target mass value).

3.2 OVERALL OBJECTIVE

In this section, we first introduce the Bayesian variational inference of PCVAE. Then we introduce the proposed group-wise and property-wise disentanglement terms as part of the overall objective. Following this, an invertibility constraint is introduced to enforce mutual dependence between each property-latent variable pair. At last, PCVAE is extended to capture and control multiple correlated properties.

3.2.1 BAYESIAN VARIATIONAL INFERENCE OF PCVAE

The goal in Section 3.1 requires us to not only model the dependence between x and (w, z) for latent representation learning and data generation, but also model the dependence between y and w for property manipulation. We propose to achieve this by maximizing a form of variational lower bound on the joint log likely-hood $p(x, y)$ of our model. Given an approximate posterior $q(z, w|x, y)$, we can use the Jensen's equality to obtain the variational lower bound of $p(x, y)$ as:

$$\log p(x, y) = \log \mathbb{E}_{q(z,w|x,y)}[p(x, y, w, z)/q(z, w|x, y)]$$
$$\geq \mathbb{E}_{q(z,w|x,y)}[\log p(x, y, w, z)/q(z, w|x, y)]. \quad (1)$$

By assuming that z is independent from w and y, and $y|w$ is independent from x and z, to explicitly represent the dependence between x and (w, z) as well as the dependence between y and w, we can parameterize the joint log-likelihood as $\log P_{\theta,\gamma}(x, y, w, z)$ with θ and γ, and decompose it as:

$$\log p_{\theta,\gamma}(x, y, w, z) = \log p_\theta(x|z, w) + \log p(z, w) + \log p_\gamma(y|w). \quad (2)$$

Given the condition that a parameterized $q_\phi(z, w|x, y) = q_\phi(z, w|x) = q_\phi(z|x)q_\phi(w|x)$ (since the information on y is included in x), by taking Eq. 2 into the above variational lower bound term in Eq. 1, we obtain the negative part as an upper bound on $-\log p_{\theta,\gamma}(x, y)$ (as shown in the right sub-figure of Figure 1(d)):

$$\mathcal{L}_1 = -\mathbb{E}_{q_\phi(z,w|x)}[\log p_\theta(x|z, w)] - \mathbb{E}_{q_\phi(w|x)}[\log p_\gamma(y|w)] + D_{KL}(q_\phi(z, w|x)||p(z, w)) \quad (3)$$

This gives us the proposed Bayesian variational inference of PCVAE. As there are K properties of interest in y which are assigned and disentangled by the latent variables in w, the second term in Eq. 3 can be detailed as $\sum_k^K \mathbb{E}_{q_\phi(w|x)}[\log p_\gamma(y_k|w_k)]$.

3.2.2 GROUP-WISE AND PROPERTY-WISE DISENTANGLEMENT

Considering that the above derivation is conditional on two requirements: (1) z is independent from w and y and (2) the variables in w are independent from each other, while in practice minimizing the above objective $\mathcal{L}_1$ will not imply that our model will satisfy these conditions. We therefore propose to further penalize the novel *Group-wise-* and *Property-wise Disentanglement* terms.

We first decompose the KL (Kullback-Leibler) divergence term in Eq. 3 as:

$$D_{KL}(q_\phi(z,w|x)||p(z,w)) = D_{KL}(q(z,w,x) \| q(z,w)p(x)) + \underbrace{D_{KL}(q(z,w) \| \prod_{i,j} q(z_i)q(w_j))}_{\text{total correlation term}}$$

$$+ \sum_i D_{KL}(q(z_i) \| p(z_i)) + \sum_j D_{KL}(q(w_j) \| p(w_j)) \tag{4}$$

The second term in the right of the above equation is referred to as the total correlation (TC), as defined by Chen et al. (2018), which is one of many generalizations of mutual information to more than two random variables. The penalty on this TC term forces the model to find statistically independent factors in the data distribution. A heavier penalty on this term induces a more disentangled representation among all variables in both z and w, but as stated in our problem formulation, we only require that (1) variables in w are disentangled to capture different properties, and (2) although z is disentangled from w, the latent variables inside z do not need to be disentangled from each other. Roughly disentangling all pairs of latent variables without emphasis could lead to poor convergence and incur exponential number of pairs among properties and latent variables for such enforcement. Thus, we further decompose and analyze the TC term as:

$$D_{KL}(q(z,w) \| \prod_{i,j} q(z_i)q(w_j)) = \underbrace{D_{KL}(q(z,w) \| q(z)q(w))}_{\text{group-wise disentanglement}} + \underbrace{D_{KL}(q(w) \| \prod_i q(w_i))}_{\text{property-wise disentanglement}}$$

$$+ D_{KL}(q(z) \| \prod_i q(z_i)). \tag{5}$$

The first term in the right part of above decomposition enforces the independence between the two subsets of latent variables z and w, which we term *group-wise disentanglement*. The second term enforces the independences of variables inside w, ensuring that each latent variable can only capture the information of the single property assigned to it. We term this *property-wise disentanglement*. Imposing a heavy penalty on these two terms can satisfy the two requirements mentioned above. We can now obtain the second part for the objective of PCVAE by introducing the coefficient ρ as:

$$\mathcal{L}_2 = D_{KL}(q(z,w)||q(z)q(w)) + \rho D_{KL}(q(w)||\prod_i q(w_i)) \tag{6}$$

3.2.3 INVERTIBLE CONSTRAINT FOR PROPERTY CONTROL

As stated in the problem formulation, an important goal for our new model is to generate a data point x that retains the original property value of a given property y_k with great precision. More importantly, there should be no strict assumptions of parameters for $p(y_k)$ and $q(w_k|y_k)$. The most straightforward way to do this is to model both the mutual mapping between y_k and its relevant latent variable w_k, which, however, could incur double errors in this two-way mapping. To address it, we innovatively propose instead an invertible mapping that mathematically ensures the exact recovery of w_k given y_k based on the following deduction.

In the above objective, we only explicitly model the conditional distribution of $p_\gamma(y_k|w_k)$, hence, to achieve the precisely control of property via z and w, which is necessary to generate x with a certain property $y_k = m$, we need to maximize the probability that $y_k = m$ as follows:

$$x \sim p_\theta(x|z,w), \quad z, w \leftarrow \arg\max_{z\sim p(z), w\sim p(w)} p_\gamma(y_k = m|z,w), \tag{7}$$

which is equal to:

$$x \sim p_\theta(x|z,w),\ z \sim p(z),\ w_{j,j\neq k} \sim p(w_j), \quad w_k \leftarrow \arg\max_{w_k\sim p(w_k)} p_\gamma(y_k = m|w_k) \tag{8}$$

where w_k can be determined as follows ($\mathcal{N}$ in the followings denotes Gaussian distribution):

$$w_k \leftarrow \arg\max_{w_k\sim p(w_k)} p_\gamma(y_k = m|w_k)$$

$$= w_k \leftarrow \arg\max_{w_k\sim p(w_k)} \log \mathcal{N}(y_k = m|f_k(w_k;\gamma), \sigma_k)$$

$$= w_k \leftarrow \arg\max_{w_k\sim p(w_k)} -(m - f_k(w_k;\gamma))^2 = w_k \leftarrow f_k^{-1}(m)$$

Therefore, by learning an invertible function $f_k(w_k; \gamma)$ from w_k to y_k to model $p_\gamma(y_k|w_k)$, we can easily achieve the desired precise control of the property. To learn an invertible function $f_k(w_k; \gamma)$, we propose to leverage an invertible neural network. Inspired by the invertible ResNet (Behrmann et al., 2019), we decompose the function $f_k(w_k; \gamma)$ as $f_k(w_k; \gamma) = \bar{f}_k(w_k; \gamma) + w_k$. As proved by Behrmann et al. (2019), the sufficient condition that $f_k(w_k; \gamma)$ is invertible is that $Lip(\bar{f}_k) < 1$, where $Lip(\bar{f}_k)$ is the Lipschitz-constant of $\bar{f}_k(w_k; \gamma)$.

Thus, the overall objective of the proposed PCVAE is finally formalized as: $\min_{\theta, \phi, \gamma} \mathcal{L}_1 + \alpha \mathcal{L}_2$ with subject to $Lip(\bar{f}_k) < 1$ for all $k \in K$, where α is the coefficient parameter.

Remark (Monotonic relationship of property-latent variable pair)**.** *Given the condition that $f_k(w_k; \gamma)$ is invertible and continuous ($Lip(\bar{f}_k)$ is less than 1), $f_k(w_k; \gamma)$ is thus a monotonic function. This is very important to increase (or decrease) the value of property y_k by increasing (or decreasing) w_k, especially when the desired value of property is not available.*

3.2.4 GENERALIZATION OF HANDLING CORRELATED PROPERTIES

As stated in the third challenge in Section 1, there are usually several groups of properties involved in formatting data x and each group has several properties. These different groups are independent, but the properties within the same group are correlated. Thus, we can further generalize the above objective framework to handle the correlated properties inside the same group.

The notation for y_k is extended to $y_k = \{y_{j,k} \in \mathbb{R}\}_{j=1}^{M_k}$, signifying that there are M_k correlated properties inside the k-th property group. The properties inside the same property set y_k are correlated, while the different property sets (e.g. y_p and y_k) are independent. Similarly, the notation for w_k is extended as a group of latent variables to control the corresponding property set. For the properties inside the same group, we assume all depend on the same group of latent variables w_k as

$$p(y_{j,k}|w_k) = \mathcal{N}(y_{j,k}|f_k(w_k; \gamma)[j], \sigma_{j,k})), \tag{9}$$

where $f_k(w_k; \gamma)[j]$ denotes the j-th element of the output of $f_k(w_k; \gamma)$. Thus, the second term in Eq. 3 can be generalized as $\sum_k^K \sum_j^{M_k} \mathbb{E}_{q_\phi(w|x)}[\log p_\gamma(y_{j,k}|w_k)]$.

3.3 NEURAL NETWORK ARCHITECTURE OF PCVAE

To implement the first part of objective (i.e., $\mathcal{L}_1$), we use MLPs (Multi-perceptions), CNNs (Convolution Neural Networks) or GNNs (Graph Neural Networks) to represent the distributions over relevant random variables. If the data x are images, CNNs are used as the encoder and decoder to model $q_\phi(z, w|x)$ and $p_\theta(x|z, w)$, respectively, while if x are graphs, we can instead utilize GNNs. To implement the second part $\mathcal{L}_2$, it is necessary to calculate the group-wise and property-wise disentanglement terms. Thus, we utilize the Naïve Monte Carlo approximation based on a mini-batch of samples to underestimate $q(z)$, $q(w)$ and $q(w_k)$, as described by Chen et al. (2018).

To implement the invertible constraint and model the distribution of $p_\gamma(y_k|w_k)$, we utilize MLPs to model the function $\bar{f}_k(\cdot)$. Since the function $\bar{f}_k(\cdot)$ modeled by MLPs is a composition of contractive nonlinearities (e.g., ReLU, ELU, tanh) and linear mappings, based on the definition of Lipschitz-constant we have $Lip(\bar{f}_k) < 1$ if $\| W_l \|_2 < 1$ for $l \in L$, where W_l refer to the weights of the l-th layer in $\bar{f}_k$, $\| \cdot \|_2$ denotes the spectral norm, and L refers to the number of layer in the MLPs. To realize the above constraint on weights of neural networks, we propose to use the spectral normalization for each layer of MLPs, as introduced by Behrmann et al. (2019).

3.4 PRECISELY PROPERTY CONTROLLABLE GENERATION

Our proposed model can be applied to an important downstream task, namely precisely property controllable generation. Given the value of a required property y_k, the goal of property controllable generation is to generate a data x which holds the same value as this desired property. To achieve this, three steps are conducted: (1) infer the value of w_k based on the well-trained neural network $\bar{f}_k(\cdot)$ and the given property y_k via fixed-point iteration by following $w_k^{i+1} := y_k - \bar{f}_k(w_k^i; \gamma)$, where w_k^i is the updated latent variable at the i-th iteration step and $w_k^0 = y_k$; (2) randomly sample the values of z and the remaining variables in w from their prior distributions (i.e., Gaussian distribution) to obtain all the latent variables; and (3) generate a data x using the decoder based on the latent variables that are inferred from the previous two steps.

4 EXPERIMENT

This section reports the results of the qualitative and quantitative evaluation carried out to test the performance of the proposed model on two datasets in two domains, namely images and molecules. All experiments were conducted on a 64-bit machine with an NVIDIA GPU (GTX 1080 Ti, 11016 MHz, 11 GB GDDR5). The encoder and decoder components, their architectures and hyper-parameters for training can be found in Appendix A.

4.1 EXPERIMENT SETUP

4.1.1 DATASETS

The **dSprites** dataset (Matthey et al., 2017) consists of 2D shapes procedurally generated from ground truth independent semantic factors. The factors that are explored as properties of data in this experiment are *scale*, and the x and y positions (mentioned as *x_pos* and *y_pos*) of a sprite. All possible combinations of these semantic factors are used for generating a total of $730k$ images, where $580k/146k$ is the training/testing set split. The **QM9** dataset (Ramakrishnan et al., 2014) consists of $134k$ stable small organic molecules composed of up to 9 heavy atoms (Carbon (C), Oxygen (O), Nitrogen (N) and Fluorine (F)), where $120k/20k$ is the training/testing set split.

4.1.2 COMPARISON METHODS

In order to validate the superiority of our proposed model in capturing and manipulating the property during generation, we compare the performance of PCVAE to those achieved by three comparison models that are most relevant to our problem: (1) *semi-VAE* (Locatello et al., 2019b) is a semi-supervised model that enforces the value of each latent variable to be equal to the value of each property. Here we utilize all the labels for supervision for fairness; (2) *CSVAE* (Klys et al., 2018) is a VAE-based model that utilizes mutual information minimization to learn latent dimensions associated with only binary properties. Here we adjust this model to handle continuous property by assuming a Gaussian distribution; and (3) *PCVAE_tc* is a baseline model that holds the same inference model and property controlling strategy as PCVAE, of which the proposed group-wise and property-wise disentanglement terms are replaced with the TC term proposed in β-*TCVAE* (Chen et al., 2018). It is used to validate the effectiveness of the proposed group-wise and property-wise disentanglement.

4.2 EVALUATION FOR DISENTANGLED LATENT VARIABLES

In this section, we explore (1) whether each variable w_k successfully captures the information of the property that is assigned to it through supervision, and (2) whether the subset z of latent variables is independent from the properties.

Quantitative evaluation. We calculate the normalized mutual information between each encoded latent variable w_k and the property y_k that assigned to it, as well as the average mutual information between latent z and each y_k. Figure 2 shows the mutual information heat map by each model on *dSprites* dataset (results on QM9 datasets can be found in Appendix B). The element in the row of z_{avg} denotes to the average of all the mutual information between z and each property. In addition, we utilize the metric *avgMI*[1] proposed by Locatello et al. (2019b) to show an overall quantitative comparison between different methods, as shown in Table 1. The proposed PCVAE achieves the least avgMI of 0.166, which demonstrate its strength in enforcing the relationship between w_k and y_k. These results also validate the effectiveness and necessity of the proposed group-wise and property-wise disentanglement term, as PCVAE outperforms the baseline model PCVAE_tc on avgMI by around 28%. Though CSVAE shows an good performance in disentangling z and w, its latent variables in w turn in a poor performance for capturing the properties. Similar conclusions can also be drawn from the results on the QM9 dataset, where PCVAE outperforms the comparison models by about 16% in capturing two independent properties *cLogP* and *Molweights*.

Qualitative evaluation. We also qualitatively evaluate the dependence of each latent variable and its relevant property by visualizing the variation of the properties when traversing the priors of

---

[1]$avgMI = \parallel I(w, y) - E(K)) \parallel_F^2$, where k is the number of properties and $I(w, y)$ is the mutual information matrix between latent variables w and properties y. $E(K)$ is the identity matrix with size K.

Figure 2: Heat-maps of the mutual information between latent variables and three properties by each model for the dSprites dataset. Data value in each cell denotes the normalized mutual information.

Table 1: The avgMI achieved by each model on the dSprites and QM9 datasets.

Methods	avgMI (dSpirites)	avgMI (QM9)
Semi-VAE	0.266	1.004
CSVAE	0.602	1.000
PCVAE_tc	0.213	0.902
PCVAE	**0.166**	**0.8369**

Table 2: MSE between the expected and actual property of the generated molecules (PCVAE (cor) denotes the extensive model for correlated properties).

Model	cLogP	Molweights	cLogS
Semi-VAE	1.40	122.34	N/A
CSVAE	4.69	180.92	N/A
PCVAE_tc	5.02	131.15	N/A
PCVAE	1.29	87.62	N/A
PCVAE (cor)	1.33	53.49	1.15

each latent variable, as shown in Figure 3. In Figure 3, as the values of w_1, w_2 and w_3 change between $(-0.5, 0.5)$, the continuous variations of the assigned properties of *scale*, *x_position* and *y_position* of the generated images are clearly visible (as highlighted in red rectangle). The variables in $z = \{z_1, z_2, z_3\}$ have almost no influence on these properties, which validates the effectiveness of the group-wise disentanglement term. More evaluation results on QM9 dataset can be found in Appendix B.

Figure 3: The generated images by PCVAE when traversing three latent variables in subset z (upper 3 rows) and three latent variables in subset w (bottom 3 rows) for the dSprites dataset.

4.3 EVALUATION FOR PROPERTY CONTROLLABLE GENERATION

In this section, we validate the performance of the property controllable generation. Specifically, given a predefined value of property y_k, the aim is to explore whether the proposed model could generate a data point x with a property y'_k that is the same as y_k.

Qualitative evaluation. For dSprites dataset, since we have no ground-truth method with which to calculate the property y'_k of the generated images, we directly visualize the images that are generated given different values of property y_k. In Figure 4, each column contains four images generated given the same value of y_k (here y_k refers to the x_position property) but given the different values for the other two properties. The objects of the generated images in the same column clearly share the same *x_position*. More visualizations for the other properties can be found in Appendix B.

Quantitative evaluation. For the QM9 dataset, since the properties can not be visualized directly from the molecule, we quantitatively measure the property controllable performance in terms of the **MSE** (mean squared error) between the actual property y'_k of generated molecule and the desired property y_k, as shown in Table 2. The proposed PCVAE outperforms the other comparison mod-

Figure 4: The generated images when traversing the desired value of property *X-position*. Each column of images are generated given the same value of the desired property.

els in successfully controlling *cLogP* and *Molweights* in molecule generation with a smaller **MSE** than that of the comparison methods by around 65.1% and 40.5% on average, respectively. This demonstrate the superiority of PCVAE in precisely controlling the continuous-valued properties due to the effective invertible property prediction network. In addition, the obvious advantage of PC-VAE over PCVAE_tc demonstrate the effectiveness and necessity of the proposed group-wise and property-wise disentanglement term in precisely property controllable generation.

4.4 EVALUATION FOR HANDLING CORRELATED PROPERTIES

In this section, we access the ability of the proposed model to capture and control the correlated properties. The performance is tested on the QM9 molecule dataset for two tasks: property prediction and property controllable generation. Three properties are selected: *Molweights*, *cLogP* and *cLogS*. *Molweights* is naturally independent from *cLogP* and *cLogS*, while *cLogP* and *cLogS* are inner-correlated.

First, we evaluate whether the subset of latent variables w can power the ability of property prediction, which is a very important task for new compound design in drug discovery. Given a molecule, the trained encoder is used to get the relevant latent variable w_k to predict the property y_k. Table 3 compares the performance of property prediction task on PCVAE and comparison models for uncorrelated properties, as well as the extended model (denoted as PC-VAE(cor)) for correlated properties. As shown in Table 3, regarding the prediction of independent properties , PCVAE outperforms the comparison models with the smallest MSE of 33.33 in terms of *Molweights*. Regarding the prediction of correlated properties prediction, PCVAE(cor) is the only model that successfully captures the information of correlated properties (*cLogP* and *cLogS*) without influencing the prediction of *Molweights*.

Table 3: Evaluation of the property prediction task in term of MSE between the predicted and real properties.

Latent Variable	*Molweights*	*cLogP*	*cLogS*
semi-VAE	975.18	1.44	N/A
CSVAE	63.78	1.21	N/A
PCVAE_tc	34.37	**0.86**	N/A
PCVAE	**33.33**	1.21	N/A
PCVAE (cor)	**33.04**	**0.96**	**0.53**

Next, we further explore the performance of the PCVAE(cor) to control the generation of the correlated properties. As shown in Table 2, PCVAE(cor) achieves the smallest MSE on all the properties. It demonstrate that adding the supervision of its correlated property *cLogS* does not influence the control of the property *cLogP*. This also demonstrates the effectiveness of the invertible function for handling multi-input and multi-output data.

5 CONCLUSION

In this paper, we have proposed the PCVAE and its extended model, which learns a latent space that separates information correlated with the properties into a predefined subset of latent variables. To accomplish this, we first propose a novel Bayesian variational inference of PCVAE to jointly learn the distribution of data and properties followed by a novel group-wise and property-wise disentanglement term to deal with the complex dependency of subsets of latent variables. Then, we propose to enforce an invertible mutual dependence to allow the precise property controllable generation. At last, we demonstrate through quantitative and qualitative evaluations from three aspects that our proposed model achieves better performance than existing and baseline models. In future work, we plan to extend PCVAE to a semi-supervised setting, where some of the property labels are missing.

REFERENCES

Alexander A Alemi, Ian Fischer, Joshua V Dillon, and Kevin Murphy. Deep variational information bottleneck. In *International Conference on Machine Learning*, 2017.

Jens Behrmann, Will Grathwohl, Ricky TQ Chen, David Duvenaud, and Jörn-Henrik Jacobsen. Invertible residual networks. In *International Conference on Machine Learning*, pp. 573–582, 2019.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

Samuel Bowman, Luke Vilnis, Oriol Vinyals, Andrew Dai, Rafal Jozefowicz, and Samy Bengio. Generating sentences from a continuous space. In *Proceedings of The 20th SIGNLL Conference on Computational Natural Language Learning*, pp. 10–21, 2016.

Ricky TQ Chen, Xuechen Li, Roger B Grosse, and David K Duvenaud. Isolating sources of disentanglement in variational autoencoders. In *Advances in Neural Information Processing Systems*, pp. 2610–2620, 2018.

Antonia Creswell, Anil A Bharath, and Biswa Sengupta. Conditional autoencoders with adversarial information factorization. *space*, 19:24, 2017.

Harrison Edwards and Amos Storkey. Censoring representations with an adversary. *arXiv preprint arXiv:1511.05897*, 2015.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *The Journal of Machine Learning Research*, 17(1):2096–2030, 2016.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, 2017.

Artur Kadurin, Sergey Nikolenko, Kuzma Khrabrov, Alex Aliper, and Alex Zhavoronkov. drugan: an advanced generative adversarial autoencoder model for de novo generation of new molecules with desired molecular properties in silico. *Molecular pharmaceutics*, 14(9):3098–3104, 2017.

Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *International Conference on Machine Learning*, pp. 2649–2658, 2018.

Durk P Kingma, Shakir Mohamed, Danilo Jimenez Rezende, and Max Welling. Semi-supervised learning with deep generative models. In *Advances in neural information processing systems*, pp. 3581–3589, 2014.

Jack Klys, Jake Snell, and Richard Zemel. Learning latent subspaces in variational autoencoders. In *Advances in Neural Information Processing Systems*, pp. 6444–6454, 2018.

Tejas D Kulkarni, William F Whitney, Pushmeet Kohli, and Josh Tenenbaum. Deep convolutional inverse graphics network. In *Advances in neural information processing systems*, pp. 2539–2547, 2015.

Abhishek Kumar, Prasanna Sattigeri, and Avinash Balakrishnan. Variational inference of disentangled latent concepts from unlabeled observations. *International Conference on Learning Representations*, 2018.

Guillaume Lample, Neil Zeghidour, Nicolas Usunier, Antoine Bordes, Ludovic Denoyer, and Marc'Aurelio Ranzato. Fader networks: Manipulating images by sliding attributes. In *Advances in neural information processing systems*, pp. 5967–5976, 2017.

Qi Liu, Miltiadis Allamanis, Marc Brockschmidt, and Alexander L. Gaunt. Constrained graph variational autoencoders for molecule design. *The Thirty-second Conference on Neural Information Processing Systems*, 2018.

Francesco Locatello, Stefan Bauer, Mario Lucic, Gunnar Raetsch, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *international conference on machine learning*, pp. 4114–4124, 2019a.

Francesco Locatello, Michael Tschannen, Stefan Bauer, Gunnar Rätsch, Bernhard Schölkopf, and Olivier Bachem. Disentangling factors of variations using few labels. In *International Conference on Learning Representations*, 2019b.

Michael F Mathieu, Junbo Jake Zhao, Junbo Zhao, Aditya Ramesh, Pablo Sprechmann, and Yann LeCun. Disentangling factors of variation in deep representation using adversarial training. In *Advances in neural information processing systems*, pp. 5040–5048, 2016.

Loic Matthey, Irina Higgins, Demis Hassabis, and Alexander Lerchner. dsprites: Disentanglement testing sprites dataset. *URL https://github. com/deepmind/dsprites-dataset/.[Accessed on: 2018-05-08]*, 2017.

Yunchen Pu, Zhe Gan, Ricardo Henao, Xin Yuan, Chunyuan Li, Andrew Stevens, and Lawrence Carin. Variational autoencoder for deep learning of images, labels and captions. In *Advances in neural information processing systems*, pp. 2352–2360, 2016.

Raghunathan Ramakrishnan, Pavlo O Dral, Matthias Rupp, and O Anatole Von Lilienfeld. Quantum chemistry structures and properties of 134 kilo molecules. *Scientific data*, 1(1):1–7, 2014.

Taihong Xiao, Jiapeng Hong, and Jinwen Ma. Dna-gan: Learning disentangled representations from multi-attribute images. *Workshop of International conference on machine learning*, 2017.

Taihong Xiao, Jiapeng Hong, and Jinwen Ma. Elegant: Exchanging latent encodings with gan for transferring multiple face attributes. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 168–184, 2018.

Shuchang Zhou, Taihong Xiao, Yi Yang, Dieqiao Feng, Qinyao He, and Weiran He. Gene-gan: Learning object transfiguration and attribute subspace from unpaired data. *arXiv preprint arXiv:1705.04932*, 2017.

A   ARCHITECTURE AND HYPER-PARAMETERS

A.1   ARCHITECTURE AND HYPER-PARAMETERS FOR DSPRITS DATASET

Based on the description of the implementation of the proposed objective, there are three components, namely, *encoder_1* to model $p_\theta(z, w|x)$, *decoder_1* to model $p_\phi(x|z, w)$ and *decoder_2* to model $p_\gamma(w|y)$. When evaluate the dSprites data, the number of latent dimensions in z is 3 and the number of latent dimensions in w is also 3. The detailed architectures are shown in Table 4. The hyper-paramter used for training is detailed in Table 6.

Table 4: Encoders and decoders architectures of PCVAE for dSprites dataset (Each layers is expressed in the format as $< kernel\_size >< layer\_type >< Num\_channel >< Activation\_function >< stride\_size >$. *FC* refers to the fully connected layers).

Encoder_1	Decoder_1	Decoder_2
Input: $X \in \mathbb{R}^{64 \times 64}$	Input$[z, w] \in \mathbb{R}^6$	Input: $w_k \in \mathbb{R}$
4×4 Conv.32 ReLU.stride 2	FC.256 ReLU	FC.50 ReLU
4×4 Conv.32 ReLU.stride 2	FC.256 ReLU	Spectral_Norm Layer
4×4 Conv.32 ReLU.stride 2	FC.512 ReLU	FC.1
4×4 Conv.32 ReLU.stride 2	4×4 ConvTranspose.32 ReLU.stride 2	N/A
FC.256 ReLU	4×4 ConvTranspose.32 ReLU.stride 2	N/A
FC.256 ReLU	4×4 ConvTranspose.32 ReLU.stride 2	N/A
FC.12	4×4 ConvTranspose.64 ReLU.stride 2	N/A

A.2   ARCHITECTURE AND HYPER-PARAMETERS FOR MOLECULE QM9 DATASET

The architecture used for evaluation on the QM9 dataset are totally borrowed from the work proposed by Liu et al. (2018). A molecule is represented as a graph $G(X, A)$, where each atom is a node and X refers to the features for all nodes; each bond is an edge, where A denotes to the adjacent matrix of the graph. Considering it is not the concentration of this paper, we briefly introduce the model and provide it architecture parameters in Table 5. We recommend the reader to the work (Liu et al., 2018) for more details.

Table 5: Encoders and decoders architectures of PCVAE for QM9 dataset (Each layers is expressed in the format as $< kernel\_size >< layer\_type >< Num\_channel >< Activation\_function >< stride\_size >$. *FC* refers to the fully connected layers).

Encoder_1	Decoder_1	Decoder_2
Input: $G(X, A), X \in \mathbb{R}^9$	Input$[z, w] \in \mathbb{R}^{100}, h\_type \in \mathbb{R}^{101}$	Input: $w_k \in \mathbb{R}$
FC.100 ReLU	FC.100 ReLU	FC.20 ReLU
GGNN.100 ReLU	GGNN.100 ReLU	Spectral_Norm Layer
GGNN.100 ReLU	GGNN.100 ReLU	FC.1
FC.100	FC.9 (node) FC.3 (edge)	N/A

Molecule Encoder and Decoder. A *encoder_1* is constructed to model $p_\phi(z, w|x)$ based on a gated graph neural network (GGNN). As a result, by sampling from the modelled distribution, (z, w) are obtained variables containing the graph representation vectors. The molecule *decoder_1* models the distribution $p_\theta(x|z, w)$ to generate the molecule graph G. The molecule *decoder_2* models the distribution $p_\theta(y|w)$ to predict the properties y. The process proceeds in an auto-regressive style. In each step a focus node is chosen to be visited, and then the edges are generated related to this focus node. The nodes are ordered by using the breadth-first traversal. The molecule decoder mainly contains three steps, namely *node initialization*, *node update* and *edge selection and labelling*.

Node Initialization. We first define N as an upper bound on the number of nodes in the final generated graph. An initial state $h_i^{(t=0)}$ is assigned with each node v_i in a set of initially unconnected nodes. Specifically, $h_i^{(t=0)}$ is the concatenation as $[(z, w), \tau_i]$, where τ_i is an one-hot vector indicating the atom type. τ_i is derived from (z, w) by sampling from the softmax output of a learned mapping $\tau_i \sim f(Z_i)$. From these node-level states, we can calculate global representations $H(t)$, which is the average representation of nodes in the connected component at generation step t. In

addition to N working nodes, a special "stop node" is also initialized to a learned representation h_{end} for managing algorithm termination detailed as below.

Edge Selection and Labeling   At each step t, a focus node v_i is picked from the queue of nodes. Then an edges $e_{i,j}$ is selected from node v_i to node v_j with label $E_{i,j}$. Specifically, for each non-focus node v_j, we construct a feature vector $\eta_{i,j}^{(t)} = [h_i^{(t)}, h_j^{(t)}, d_{i,j}, H(t), H(0)]$, where $d_{i,j}$ is the graph distance (i.e. path) between two nodes v_i, v_j. We use these representations to produce a distribution over candidate edges as $p(e_{i,j}, E_{i,j}|\eta_{i,j}^{(t)}) = p(E_{i,j}|\eta_{i,j}^{(t)}, e_{i,j}) \cdot p(e_{i,j}|\eta_{i,j}^{(t)})$. The parameters of the distribution are calculated as softmax outputs from neural networks. New edges are sampled one by one from the above learned distributions. Any nodes that are connected to the graph for the first time during this edge selection are added to the node queue.

Node Update.   Whenever we obtain a new graph $G^{(t+1)}$ at step t, the previous node states $h_i^{(t)}$ is discarded and a new node representations $h_i^{(t+1)}$ for each node is calculated by taking their (possibly changed) neighborhood into account. To this end, a standard gated graph neural network (GGNN) is utilized through S steps, which is defined as a recurrent operation over messages $r_i^{(s)}$.

Termination.   In the edge generation process of each node, the edges to a node v_i is kept added until an edge to the stop node is selected. Then we move the focus from the node v_i, and regard v_i as a "closed" node. The next focus node is then selected from the focus queue. In this way, a single connected component is grown in a breadth-first manner. The node and edge generations continue until the queue of nodes is empty.

Table 6: hyper-paramter used for training on dSprites and QM9 datasets

Dataset	Learning_rate	Batch_size	α	ρ	Num_iteration	c (spectral_norm)
dSprites	5e-4	64	3	1	20	0.97
QM9	5e-4	32	1	6	100	1

B   ADDITIONAL EXPERIMENT RESULTS

B.1   EVALUATION ON DISENTANGLED LATENT VARIABLES

Evaluation results on dSprites.   We provide the qualitative evaluation on the comparison experiments when traversing the values of latent variables in Fig. 5. As shown here, the latent variables w learned by the baseline model PCVAE_tc could successfully capture the three properties, which validate the effectiveness of the proposed overall inference model. The latent variables w_2 and w_3 learned by CSVAE can capture the *x_pos* and *y_pos* properties, while w_1 fails in capture the *scale* property. Semi-VAE can capture the three properties but the quality of the generated images is very bad and biased.

Evaluation results on QM9 dataset.   We calculate the mutual information between each encoded latent variable w_k and the property y_k that assigned to it, as well as the average mutual information between latent z and each y_k, as shown in Figure 6 for the results on molecule QM9 dataset. For this difficult task in the molecule domain which contains the implicit properties, the proposed PCVAE still shows significant advantage in capturing the *Mol_weight* and *cLogP* properties. We also qualitative evaluate the relationship of each latent variable and its relevant properties. We visualize the variation of the properties on QM9 datasets, when traversing on the priors of each latent variable, as shown in Figure 7. The variable w_1 and w_2 could successfully capture the properties *Molweight* and *cLogP*.

B.2   EVALUATION FOR PRECISE PROPERTY CONTROL

Evaluation on dSprites dataset.   For dsprits dataset, since we have no ground-truth method to calculatethe properties y_k' of the image, we directly visualize the images that are generated given different properties y_k on three comparison models. As shown in Figure 8, each column shows four images generated given the same value of y_k, but given the different values of other properties. It

Figure 5: The generated images by comparison models when traversing on three latent variables in subset of latent z (upper3 rows) and three latent variables in subset of latent w (bottom 3 rows) for the Dsprits dataset

Figure 6: Comparison on Mutual Information between different latent variables on different properties on molecule QM9 dataset.

Figure 7: The properties of generated molecules when traversing on the corresponding latent variables in sub-space w by ControlVAE_tc (left) and ControlVAE (right).

could be easily observed that the objects of the generated images in the same column have the same value of y_k'. We provide the visualization of y_pos in Fig.8.

Figure 8: The generated images when traversing on the given desired property of Y-position. Each column of images share the same value of the desired property.