A Deep Learning Dataloader with Shared Data Preparation

Jian Xie[1]   **Jingwei Xu**[1*]   **Guochang Wang**[1]   **Yuan Yao**[1]   **Zenan Li**[1]
Chun Cao[1]   **Hanghang Tong**[2]
[1]Nanjing University   [2]University of Illinois Urbana-Champaign
{xiejian, wgchang, lizn}@smail.nju.edu.cn
{jingweix, y.yao, caochun}@nju.edu.cn
htong@illinois.edu

Abstract

Parallelly executing multiple training jobs on overlapped datasets is a common practice in developing deep learning models. By default, each of the parallel jobs prepares (i.e., loads and preprocesses) the data independently, causing redundant consumption of I/O and CPU. Although a centralized cache component can reduce the redundancies by reusing the data preparation work, each job's random data shuffling results in a low sampling locality causing heavy cache thrashing. Prior work tries to improve the sampling locality by enforcing all the training jobs loading the same dataset in the same order and pace. However, such a solution is only efficient under strong constraints: all jobs are trained on the same dataset with the same starting moment and training speed. In this paper, we propose a new data loading method for efficiently training parallel DNNs with much flexible constraints. Our method is still highly efficient when different training jobs use different but overlapped datasets and have different starting moments and training speeds. To achieve this, we propose a dependent sampling algorithm (DSA) and a domain-specific cache policy. Moreover, a novel tree data structure is designed to efficiently implement DSA. Based on the proposed techniques, we implemented a prototype, named JOADER, which can share data preparation work as long as the datasets are overlapped for different training jobs. We evaluate the proposed JOADER , showing a greater versatility and superiority of training speed improvement (up to 200% on ResNet18) without affecting the accuracy.

1   Introduction

The rapid development of deep learning frameworks and tools [2, 21] has enabled and facilitated researchers and practitioners in a multitude of disciplines (e.g., physics [27], chemistry [17], biology [11], and Earth science [22] in addition to computer science) to start developing their own DNN models solving various problems at hand. In such cases, they usually need to simultaneously run multiple training jobs on the same dataset or overlapped datasets[2], due to the purpose of model selection [14], hyper-parameter tuning [5], network architecture searching [24], etc.

Although widely used, the training of DNNs is usually time-consuming and tricky, which may affect the development efficiency, especially for general users from fields other than artificial intelligence. In literature, various approaches have been proposed to reduce the DNN training time such as data preparation optimization [3], communication overhead reduction [9, 8, 28], GPU memory optimization [7, 15, 25], and compiler-based operator optimization [6, 12, 16].

---

[*]Corresponding author.
[2]This could happen when we train models on different datasets sharing a particular portion of data, e.g., running the full experiment on ImageNet and further tuning parameters on TinyImageNet [10]).

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

Different from the above existing work, our focus is on the data preparation aspect, or more specifically, the data loading aspect, in the context of parallel DNN training. On the one hand, Mohan et al. [18] have observed that data preparation, which consists of data loading and the subsequent data preprocessing, occupies a significant portion of parallel DNN training time. This is due to the fact that multiple training jobs on the same data copy essentially create redundant data preparation efforts. Ideally, to reduce the load of hardware and boost the training efficiency, the prepared data should be cached in memory and serve for multiple jobs. However, the cache may thrash with a high probability as each job adopts a fully random shuffling strategy that independently shuffles the dataset in each epoch. On the other hand, it is until recently have some studies investigated the shuffling process itself [19, 18, 20]. These studies investigate to what extent the fully random shuffling is required and have observed that various shuffling strategies breaking the full randomness still yield competitive results. We name such randomness as *correlated randomness* as opposed to the full randomness. For example, prior work [18, 19] proposed to solve the cache thrashing issue by enforcing that all jobs iterate over the dataset in the same order and pace, and observed no accuracy loss. However, such a solution maximizes its performance under some strong constraints, i.e., all training jobs have to start simultaneously, use the same dataset, and have similar training speeds.

This paper proposes a new data loading method for training multiple parallel jobs. Specifically, we aim to relax the constraints of prior work in three aspects: 1) all jobs can start and end freely, 2) different datasets can be used as long as they are partially overlapped, and 3) jobs' training speeds may vary widely. For the above purposes, we first propose the *dependent sampling algorithm* (DSA) to schedule the sampling for each job while ensuring their correlated randomness. DSA is inspired by the correlated sampling theory [4] and it mainly involves three steps: 1) divide the dataset into two parts of intersection set and difference set, 2) correlate the selections between intersection and difference, and 3) share some operations for the intersection set to improve locality Furthermore, we design a domain-specific cache policy *RefCnt* that is tailored for parallel DNN training. It is aware of the fact that all jobs iterate over the dataset once in an epoch, and thus it can evict data that is least likely to be used in the near future. Finally, we design a novel data structure *dependent sampling tree* to efficiently implement the DSA by elaborately organizing the intersection sets and difference sets. Based on the above technologies, we implement a prototype system named JOADER and integrate it into PyTorch for evaluation. The evaluation results show that JOADER can boost training efficiency in more flexible cases. For example, it achieves up to 200% training speedup when models of different sizes are parallelly trained without affecting the accuracy.

The main contributions of this paper inlcude:

- A new dataloader for parallel DNN training on overlapped datasets.
- A sampling algorithm to increase the sampling locality with guaranteed randomness. The algorithm reaches the global optima when there are two training jobs.
- A domain-specific cache policy and a novel tree-based data structure for efficient implementation.
- Experimental evaluations demonstrating the performance improvements.

The rest of this paper is organized as follows. Section 2 introduces the background information. Section 3 describes the dependent sampling algorithm and our cache policy, followed by the description of the dependent sampling tree in Section 4. Section 5 presents the evaluation of the implemented dataloader JOADER. The paper is concluded in section 6.

2   Background

2.1   Problem Statement

In each epoch, a DNN training job sends data requests to the storage device and passes through the dataset in random order. For the brevity of the presentation, we assume that each data request involves only one data point/element, and we name the data access order over all the data elements as the *access path* for each epoch. Consider an example in Figure 1, where we assume two training jobs are running, and the two sampled data elements ('e1' and 'e2') requested by the two jobs are packaged and prepared together in one *round*.

Cache can hold the prepared data to serve the future duplicated requests. To fully utilize the cache when multiple DNN models are being trained simultaneously in a server, one could generate a cache-friendly access path by encouraging all jobs to request the same data within a short period, i.e.,

Figure 1: The access path of two training jobs. The target is to maximize the probability of sampling the same element in each round for all the jobs.

improving the sampling locality in each round. Meanwhile, we still need to ensure the correlated randomness for each job. To this end, we formulate the problem as follows:

Problem 1 *Assume there are n training jobs on overlapped datasets, where the i-th job J_i trains a model on dataset D_i with cardinality $|D_i|$. In each round, $p(e_j^i) = \frac{1}{|D_i|}$ indicates the probability of data element e_j being picked via sampling uniformly at random by J_i. For a given round, the goal is to maximize $p(e^1 = e^2 = ... = e^n)$, while maintaining $p(e^i) = \frac{1}{|D_i|}$.*

2.2 Related Work

Dataloader for multiple training jobs. Cerebro [19] is proposed to avoid redundant data preparation work for the task of model selection. It partitions the dataset across the servers into clusters and hopes the models iterate over data from one server to another instead of shuffling data. Although it can help avoid redundant data preparation work across servers, the work is still repeated on a single server. CoorDL [18] provides a more general solution for hyper-parameter optimization. In one turn, it distributes one batch to each job and caches the batch into the buffer for future usage. The batches are evicted until all jobs have consumed them in an epoch. However, CoorDL still has some limitations: 1) all jobs must be set up with the same batch size; 2) when the jobs have different training speeds, the faster jobs must wait for the slower ones; 3) CoorDL cannot handle situations where the jobs arrive at different moments or are trained on different datasets.

Domain-specific caching. Crafting a cache for a specific domain is not a new idea [23]. For example, Quiver [13] uses local solid-state drive (SSD) caches to eliminate the impact of slow reads from the remote storage. However, it is too expensive to prepare enough memory against cache thrashing for DNN training, especially considering the fact we need to cache not only the previous reading but also the results of data preprocessing. In this paper, we propose a well-designed sampling algorithm to improve the sampling locality with a small cache.

Correlated sampling. As a theoretical problem, correlated sampling [4] aims to minimize the probability of two sampling results being equal, given that the two players are sampling uniformly at random from two subsets of the same set. Some sampling strategies [26] give the optimal solution for two players. In this paper, we practically solve a related problem by designing an algorithm and a novel data structure for efficient implementation while enjoying their theoretical results.

3 Dependent Sampling Algorithm

3.1 Algorithm Design

To solve Problem 1, we propose a dependent sampling algorithm (DSA) to maximize the sampling locality while ensuring correlated randomness. In the following, we first present the algorithm in two-job case and then extend it to the n-job case.

Two-job Case. The proposed *dependent sampling algorithm* (DSA) involves three steps: 1) intersection calculating, 2) dependent selecting, and 3) shared sampling. For a better illustration, we assume two jobs J_1 and J_2 are being trained on two overlapped datasets D_1 (the yellow circle) and D_2 (the green circle), respectively, as shown in Figure 2.

First, we divide the datasets into three subsets: *intersection* set $I = D_1 \cap D_2$ and two *difference* sets $D_{d1} = D_1 \setminus I, D_{d2} = D_2 \setminus I$. For the default *independent sampling algorithm* (ISA), which is

(a) *Intersection calculating*: 1) calculate the intersection and difference; 2) let job select subset first and then sample in this subset randomly.

(b) *Dependent selecting*: Job2 makes decisions conditioned on the decisions of Job1, under the constraints that the probabilities of Job2 selecting difference set and intersection are uniformly distributed according to the total probability law.

(c) *Shared sampling*: if two jobs both select the intersection, then they share the sampling results.

Figure 2: Dependent sampling algorithm in the two-job case.

currently used by PyTorch, it then processes the data sampling uniformly at random in the dataset for each job independently. As shown in Figure 2a, the ISA algorithm can be divided into two steps: *selecting* and *sampling* procedures. In the selecting procedure, each job selects between its difference and intersection sets for sampling. In the sampling procedure, each job randomly picks an element e from the subset chosen in the previous step. This two-step process maintains the uniform distribution of sampling for each job.

Then, the proposed DSA takes a careful modification in the sampling procedure. As shown in Figure 2c, if the two jobs both select the intersection set, one shares the sampling result to another. We call this modification *shared sampling*. Based on shared sampling, the probability that two jobs selecting the same element is equal to that both jobs selecting the intersection set.

To further improve locality, we need to improve the probability of both two jobs selecting the intersection, which can be achieved according to the conditional probability, as shown in Figure 2b. The independent events in the selecting procedure can be transformed into the dependent ones, making the probability of the second job conditional. That is, J_2 makes decisions conditioned on the decision of J_1.

To maximize the sampling locality, we formulate the conditional probabilities of dependent selecting in case of $|D_1| < |D_2|$. For J_1, the dependent selecting procedure is the same as that in ISA: selecting I with the probability of $\frac{|I|}{|D_1|}$, and D_{d1} with the probability of $\frac{|D_{d1}|}{|D_1|}$. The selecting procedure of J_2 makes the decision according to J_1. If J_1 selects D_{d1}, then J_2 must select another difference set D_{d2}. If J_1 select I, then J_2 selects I with the probability of $\frac{|D_1|}{|D_2|}$ and D_{d2} with probability $\frac{|D_2|-|D_1|}{|D_2|}$. Figure 2b shows the above selecting procedure. For the case of $|D_2| < |D_1|$, we just need to exchange the order of J_1 and J_2 to apply the above rules.

According to above conditional probabilities, the probability of $p(e_j^1 = e_i^2)$ is $\frac{|I|}{\max(|D_2|,|D_1|)}$, which is also the theoretical upper bound as discussed in Theorem 1. The proof of this theorem can be found in Proof 1.

Theorem 1 *Assume there are 2 jobs J_1, J_2 sampling uniformly at random from two datasets D_1, D_2 respectively, and the elements they sampled are e_j^1, e_i^2. The probability of these two elements being equal cannot be larger than $\frac{|I|}{\max(|D_2|,|D_1|)}$ where $I = D_1 \cap D_2$.*

N-job Case. DSA of n-jobs is similar to two-jobs at the beginning. The difference happens when some jobs select difference sets. We need to go through the above procedure recursively for these jobs rather than sampling in the current difference set directly, as shown in Figure 3. The reason for recursive execution is that some data may only be shared by part of the jobs. In the extreme case, if all datasets are mutually disjoint, then the intersection in the first recursion is empty and the DSA is useless. Therefore, we need to further check whether there are shared data for part of the jobs.

Figure 3: An illustration for the n-job case of DSA. We assume three jobs $\{J_1, J_2, J_3\}$ with datasets $\{D_1, D_2, D_3\}$, and there are three possible sampling cases: 1) all jobs select intersection, 2) some jobs select intersection and some select difference, and 3) all jobs select difference. Note that if there is one job selecting difference, all following jobs must select difference.

The conditional probability for n-jobs that are sorted by the cardinalities of their datasets is formulated as follows. 1) The first job J_1 selects the intersection with the probability of $\frac{|I|}{|D_1|}$ while selecting the difference with the probability of $\frac{|D_{d1}|}{|D_1|}$. 2) If the job J_{i-1} selects the difference set, then job J_i must select the difference set. If job J_{i-1} selects the intersection set, then job J_i selects the intersection with the probability of $\frac{|D_{i-1}|}{|D_i|}$ while selecting the difference set with the probability of $\frac{|D_i|-|D_{i-1}|}{|D_i|}$. For the above algorithm, we can observe that if one job selects the difference, then all subsequent jobs will choose the difference, which is an important feature for the data structure in Section 4.

The pseudo code of DSA are shown in Appendix B for completeness. Here, we provide the theoretical result as follows, whose proofs can be found in Appendix D.2.

Theorem 2 *Assume there are multiples jobs with the i-th job J_i trained on dataset D_i. The probability of any element e being picked for J_i via DSA is $p(e) = \frac{1}{|D_i|}$.*

3.2 RefCnt Cache Policy

If we allow jobs to vary greatly in speed, then some data may be evicted before they are consumed by all jobs. Therefore, we need a cache policy that can take out the data that is least likely to be used (i.e., the data that least jobs will request) in the near future. Classical cache policies (e.g., LRU and LFU) are not suitable for deep learning scenarios, where each training job reads each data only once in an epoch. So the total number of request to each data equals to the number of jobs using the data for training. To this end, if we could record the count of data request, the number of request to this data in near future could be derived. The fewer jobs that access the data, the higher the eviction priority of that data.

Based on the above understanding, we design the caching policy *RefCnt*. We maintain a reference count for each data element. If a job will request the element in the future, we increase its reference count; if a job reads the data, we decrease its reference count. When the cache is full, the data with the lowest reference count will be evicted.

4 Dependent Sampling Tree

The time complexity of DSA is $O(nm)$, where n is the number of jobs and m is the maximum cardinality of the datasets. The worst case happens if all jobs select the difference set in each recursion,

which means we need n recursions for n jobs. Each recursion has the time complexity of $O(m)$.[3] To reduce the time complexity of sampling, we can maintain the intersections for DSA to avoid the intersection calculation in each recursion, which can make each recursion cost constant time. In the worst case of DSA, the complexity of DSA is reduced from $O(nm)$ to $O(n)$.

We propose the dependent sampling tree for organizing the intersections. Although the number of intersections is $2^n - 1$ for n sets, only $n - 1$ intersections are valuable. In DSA, we only need to calculate the intersection of datasets for those jobs that select the difference, as shown in Figure 3. When the jobs are sorted by the cardinality of their datasets, the job selecting the difference will make all following jobs select the difference sets. Therefore, the possible combinations for jobs that select the difference must be the suffixes of the sorted jobs array. For example, if there are three sorted jobs $[J_1, J_2, J_3]$, the groups of jobs choosing the difference set can only be one of the following three sets, including $[J_1, J_2, J_3]$, $[J_2, J_3]$, and $[J_3]$. Thus, the sets to be calculated are $\{D_1 \cap D_2 \cap D_3, D_2 \cap D_3\}$.

4.1 Tree Definition

For n datasets $\{D_1, D_2, ..., D_n\}$ in ascending order w.r.t. $|D_1| < |D_2| < ... < |D_n|$, we need to calculate $n - 1$ intersections $\{D_1 \cap ... \cap D_n, D_2 \cap ... \cap D_n, ..., D_{n-1} \cap D_n\}$. We build a dependent sampling tree, where each intersection is an internal vertex, and each difference set is a leaf. Meanwhile, all vertices in a path from the root to a leaf represent a complete dataset. The definition of dependent sampling tree is as follows

Definition 1 *Dependent sampling tree is a binary tree that stores a collection of datasets $\{D_1, D_2, ..., D_n\}$, with $|D_1| < |D_2| < ... < |D_n|$. In the tree, the root is the intersection of all datasets $I = D_1 \cap D_2... \cap D_n$. The right child is the difference of the smallest dataset $D_1 \setminus I$. The left child is a new dependent sampling tree of $\{D_2 \setminus I, D_3 \setminus I, ..., D_n \setminus I\}$. When there is only one dataset, the tree has one vertex that contains the dataset.*

If there are n datasets, the height of the dependent sampling tree is $n - 1$. Figure 4a shows an example with three sets $\{D_1, D_2, D_3\}$ with $|D_1| < |D_2| < |D_3|$. In this tree, vertex A contains $D_A = D_1 \cap D_2 \cap D_3$, and vertex B contains $D_B = (D_2 \setminus D_A) \cap (D_3 \setminus D_A)$. For the leaf vertices C, E, and F, they maintain the other differences.

4.2 Tree Operations

When executing the DSA algorithm, dependent sampling tree should maintain the datasets into intersection and difference sets dynamically. Furthermore, dependent sampling tree should also support the situations when a job finishes its execution or a new job starts. In this part, we discuss the operations provided by dependent sampling tree, which are *sampling*, *deletion*, and *insertion*.

Sampling. The intersections of the flow in Figure 3 can be represented by one or multiple vertexes of the rightest path in the dependent sampling tree. Thus, the process of DSA is to traverse the path from the root to the most-right leaf in the tree. When traversing to an internal vertex, the jobs will decide whether to select this vertex according the conditional probability. For those jobs that do not select this vertex, they will make decisions in the right child tree.

Sometimes the intersection can be composed of multiple vertexes. For example, if only the job of D_3 selects difference at A in Figure 4a, then it can sample both in B and F. In these cases, the algorithm needs to first select a vertex that belongs to the intersection and then sample.

Dataset Deletion. When a job finishes training or is killed, we should delete its dataset from the tree. The *deletion* involves two steps: 1) deleting the corresponding leaf vertex, and 2) merging its parent vertex with its sibling vertex. For example, if we want to delete D_2 in Figure 4a, we need to delete the leaf vertex E and merge vertex B with F, as shown in Figure 4b. The time complexity is $O(1)$ since deleting and merging both cost constant time.

---

[3]1) The intersection calculation needs to traverse the dataset so its complexity is linear to the cardinality of the dataset. 2) In the worst case, only the first job needs to make the decision, and others follow it. Therefore, dependent selecting needs constant time. 3) Sampling only needs to pick a random number between 0 and the size of the dataset, which needs constant time.

(a) Dependent sampling tree of three datasets $\{D_1, D_2, D_3\}$

(b) Delete a dataset D_2 from the dependent sampling tree

(c) Insert a smaller dataset D ($|D| \leq |D_1|$) in dependent sampling tree

(d) Insert a larger dataset D ($|D| > |D_1|$) in dependent sampling tree

Figure 4: Illustration for the proposed dependent sampling tree.

Dataset Insertion. The *insertion* operation depends on the cardinality of the new dataset D. When D is smaller than the smallest set in the sampling tree, the procedure involves three steps: 1) calculating the intersection of it and the root of the tree, 2) setting the new intersection as the new root of the dependent sampling tree, and 3) setting the difference set of the old root as the right child and the difference of D as the left child for the new root. For example, Figure 4c shows the new tree after inserting a smaller dataset D. The new root X is the intersection of D and the set in vertex A. The old tree becomes the right sub-tree, and the difference of the dataset D becomes the left leaf.

When the new dataset D is larger than the smallest dataset in the sampling tree, we need to insert it recursively: 1) calculating the intersection of D and root A and set it as new root X, 2) adding the difference of A to its children, 3) deleting the old root A and adding their children to the new root, 4) recursively executing step 1 on X's right child with the difference set of D until the difference set is the smallest in the current sub-tree. An example of this procedure is shown in Figure 4d. In the worst case, the time complexity of *insertion* is $O(n|D|)$ if the new dataset D is the largest [4].

5   Evaluation

In this section, we evaluate JOADER on ImageNet with the family of ResNet models. We denote the default dataloader strategy in PyTorch as the 'Baseline' method, and further compare JOADER with the state-of-the-art method CoorDL [18]. Due to the space limit, we mainly show two experiments in the paper and more experimental results can be found in the appendix. First, we profile the server when there are multiple training jobs to show the bottlenecks and compare JOADER with CoorDL and Baseline in synchronous case. Second, we evaluate JOADER in asynchronous cases: 1) multiple models trained at different speeds, 2) multiple jobs arrived at different moments, and 3) multiple datasets only partially overlapped. For the results in the appendix, we summarize them as follows: 1) ablation studies show that both DSA and RefCnt improve the training efficiency , 2) the I/O speed is not the bottleneck for data loading , and 3) we train ResNet18 with PyTorch and JOADER separately to show JOADER does not affect the accuracy.

The evaluated models are the basic models with their default settings in torchvision [1], and trained on top of the PyTorch 1.6.0 DL framework. The experiments were conducted on a GPU server with two Intel Xeon Gold 5118 CPUs @ 2.30GHz (24 physical cores and 48 threads), 500GB RAM, and 6 TITAN RTX GPUs. The server ran Ubuntu 18.04 with GNU/Linux kernel 4.15.0. The disk is Symbios Logic MegaRAID SAS-3 3316 of 1GB/s read speed.

5.1   Performance in Synchronous Cases

In this experiment, we start training multiple ResNet18 models at the same time but with different hyper-parameters. We start from training 1 model to training 6 models on ImageNet, and profile the server for different dataloaders. The experiments show that the CPU utilization tends to be the bottleneck, as shown in Figure 5.

The CoorDL and JOADER both can reduce the CPU utilization greatly by sharing the data preparation. Additionally, it shows that JOADER can achieve close performance to CoorDL when all training jobs start at the same time and have a similar speed. Note that CoorDL is designed for such synchronous cases while JOADER can also handle asynchronous cases as we will later show. The time cost of each

---

[4]In practice, the dataset is a bitmap set of data indices in the dataset, e.g., a unique integer id that identifies data. Therefore, the insert operation is very fast, which only takes a little time compared with training time.

Figure 5: The CPU utilization when training multiple ResNet18 models simultaneously. CPU quickly becomes the bottleneck for the Baseline dataloader of PyTorch, while both CoorDL and JOADER can greatly reduce CPU utilization.

Figure 6: The CPU utilization and lifetime when training 5 models with different speeds. JOADER can reduce the CPU utilization and keep each job's own speed. In contrast, fast job must wait for the slow job for CoorDL (e.g., ResNet18 costs the same time with ResNet152).

(a) The CPU utilization and lifetime when four jobs start at different moments. JOADER is faster and causes less CPU load because it can reuse the data preparation work from previous jobs.

(b) The CPU utilization when datasets are partially overlapped. JOADER can reduce 10% CPU utilization when half of datasets are in the intersection set for 2 jobs.

Figure 7: Training jobs arrive at different moments and have different datasets

epoch is shown in Table 1. With 6 training jobs, JOADER saves 44.8% training time with over 40% less CPU utilization, compared the default Baseline in PyTorch.

Table 1: The time cost of different dataloaders when training multiple ResNet18 models in an epoch.

Number of jobs	1	2	3	4	5	6
CoorDL (min)	32.82	31.73	32.73	34.76	35.28	37.98
JOADER (min)	32.70	32.49	33.72	36.32	37.44	37.55
Baseline (min)	31.74	35.01	40.04	52.11	57.67	67.85

5.2 Performance in Asynchronous Cases

Next, we consider three asynchronous cases when multiple models differ in training speeds, arriving moments, and datasets.

Multiple models with different training speeds. We first simultaneously train five models (ResNet18, ResNet34, ResNet50, ResNet101, and ResNet152) with different training speeds, and show the lifetime and CPU utilization results in Figure 6. With the Baseline dataloader provided by PyTorch, each job preprocesses the data individually so that the CPU load is extremely heavy.

CoorDL enforces multiple jobs requesting the data in lockstep to share the data preparation work, and it achieves less CPU load and higher training speed than Baseline. However, the faster jobs (smaller models) must wait for the slower jobs, making CPU idle during the training period. JOADER can both reduce the CPU load by sharing the preprocessing work and keep these jobs' own training speeds. For example, ResNet18 runs $4\times$ faster using JOADER compared with CoorDL. Furthermore, this experiment suggests that our system has less profitable for larger models because GPU tends to be the bottleneck for those models.

Multiple models arriving at different moments. Next, we consider the situation that multiple DNN training jobs start at different moments. Since CoorDL must wait for all the jobs to be ready for training, we only compare JOADER with Baseline in this experiment. Figure 7a shows the CPU utilization when four ResNet18 training jobs arrive at different moments. JOADER takes up less CPU load than the Baseline. This is due to the fact Baseline repeats the data preparation work for new jobs, whereas JOADER reuses the prepared data from previous jobs. As a result, JOADER saves 17.1% training time and 8.7% CPU utilization.

Multiple models with partially overlapping datasets. Finally, we show the CPU utilization when the two datasets only partially overlap in Figure 7b. The datasets are re-sampled from ImageNet. We use the ratio between intersection size and dataset size to measure the overlapping degree. The larger the intersection, the more data to share. We still compare with the Baseline method only since CoorDL requires all jobs having the same access path over datasets. From the figure, we can observe that the CPU utilization of the same dataset is only 60% of that of different datasets. Additionally, the CPU utilization always decrease as the intersection size increases, showing that JOADER is valid with some overlapping elements. The reason is that the DSA algorithm can get the same sampling results with the max probability and the cache policy evicts the useless data with higher priority.

6   Conclusion

Accelerating DNN training is a fundamental challenge in deep learning. This paper presents an approach to boosting training efficiency by caching data prep work and reusing them to parallel training jobs. To prevent cache thrashing, we propose DSA to improve sampling locality with ensured randomness. We also propose a novel tree-based data structure to efficiently implement the proposed algorithm. Furthermore, a domain-specific cache policy is proposed for evicting data that is least used in the near future. At last, we evaluate the proposed approach and the results show significant improvement in asynchronous cases while achieving close performance in synchronous cases to CoorDL which is specially designed for such cases.

7   Discussion

Limitations. Although JOADER proved its effectiveness in classic scenarios, it inevitably works under certain constraints. For the Dependent Sampling Algorithm, superior locality as it brings, it breaks the strict independence across workloads, which means for correlated workloads, e.g., parallel tasks aimed for variance reduction by by ensembles, Joader won't achieve an as good result as workloads without strict independence constraints.

Bottleneck. For efficiency of the Dependent Sampling Tree implementation, the bottleneck can come from CPU or disk I/O. Based on our experiment in Appendix A, disk I/O cost during training process would be masked by CPU cost if the disk I/O speed is over 350MB/s. Otherwise if the disk I/O read speed is under 350MB/s, the bottleneck would come from I/O. We tested our implementation under a SSD with disk I/O read speed at 1GB/s, which is a pretty common spec, any disk with better read speed should achieve better results.

Cost of Dependent Sampling Tree. JOADER introduce the Dependent Sampling Tree compared with primeval dataloader, which can bring more operations for datasets, such as calculating intersection. To reduce them, the bitmap index are used to represented the dataset. To evaluate the time cost of dataset operations, we have conducted an additional experiment by randomly inserting 128 datasets

into our system. The size of each dataset is between 1,000,000 and 2,000,000 elements (note that ImageNet contains 1,400,000 images). The average cost of inserting each dataset is 0.57 seconds.

Other machine learning tasks. JOADER can be applied to all machine learning tasks which need to iteratively traverse the dataset in random order. However, the benefit depends on the cost of reading and processing. In computer vision, image is usually large, and image decoding takes much calculation. Thus, JOADER can get better benefits. In contrast, if the data is small, e.g., each sample in the NLP dataset only tasks several bytes, and the cost of processing is little. In this case, our system cannot speed up training too much.

Acknowledgments and Disclosure of Funding

We thank the anonymous reviewers for their helpful comments. This work was supported in part by the Key-Area Research & Development Program of Guangdong Province (No. 2020B010164003), the National Natural Science Foundation of China (No. 62025202, 62172199), and the Collaborative Innovation Center of Novel Software Technology and Industrialization. Hanghang Tong is partially supported by NSF (1947135).

References

[1] The package consists of popular datasets, model architectures, and common image transformations for computer vision. `https://pytorch.org/vision/stable/index.html`, 2021.

[2] Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, et al. Tensorflow: A system for large-scale machine learning. In *12th {USENIX} symposium on operating systems design and implementation ({OSDI} 16)*, pages 265–283, 2016.

[3] Jonghyun Bae, Jongsung Lee, Yunho Jin, Sam Son, Shine Kim, Hakbeom Jang, Tae Jun Ham, and Jae W Lee. {FlashNeuron}:{SSD-Enabled} {Large-Batch} training of very deep neural networks. In *19th USENIX Conference on File and Storage Technologies (FAST 21)*, pages 387–401, 2021.

[4] Mohammad Bavarian, Badih Ghazi, Elad Haramaty, Pritish Kamath, Ronald L Rivest, and Madhu Sudan. Optimality of correlated sampling strategies. *Theory of Computing*, 16(1), 2020.

[5] James Bergstra and Yoshua Bengio. Random search for hyper-parameter optimization. *Journal of machine learning research*, 13(2), 2012.

[6] Tianqi Chen, Thierry Moreau, Ziheng Jiang, Lianmin Zheng, Eddie Yan, Haichen Shen, Meghan Cowan, Leyuan Wang, Yuwei Hu, Luis Ceze, et al. {TVM}: An automated end-to-end optimizing compiler for deep learning. In *13th {USENIX} Symposium on Operating Systems Design and Implementation ({OSDI} 18)*, pages 578–594, 2018.

[7] Tianqi Chen, Bing Xu, Chiyuan Zhang, and Carlos Guestrin. Training deep nets with sublinear memory cost. *arXiv preprint arXiv:1604.06174*, 2016.

[8] Jiawei Fei, Chen-Yu Ho, Atal N Sahu, Marco Canini, and Amedeo Sapio. Efficient sparse collective communication and its application to accelerate distributed deep learning. In *Proceedings of the 2021 ACM SIGCOMM 2021 Conference*, pages 676–691, 2021.

[9] Sayed Hadi Hashemi, Sangeetha Abdu Jyothi, and Roy H Campbell. Tictac: Accelerating distributed deep learning with communication scheduling. *SysML 2019*, 2019.

[10] Guoxi Xu Jiayu Wu, Qixiang Zhang. Tiny imagenet challenge.

[11] John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.

[12] Taebum Kim, Eunji Jeong, Geon-Woo Kim, Yunmo Koo, Sehoon Kim, Gyeong-In Yu, and Byung-Gon Chun. Terra: Imperative-symbolic co-execution of imperative deep learning programs. *Advances in Neural Information Processing Systems*, 34, 2021.

[13] Abhishek Vijaya Kumar and Muthian Sivathanu. Quiver: An informed storage cache for deep learning. In *18th {USENIX} Conference on File and Storage Technologies ({FAST} 20)*, pages 283–296, 2020.

[14] Arun Kumar, Robert McCann, Jeffrey Naughton, and Jignesh M Patel. Model selection management systems: The next frontier of advanced analytics. *ACM SIGMOD Record*, 44(4):17–22, 2016.

[15] Gangmuk Lim, Jeongseob Ahn, Wencong Xiao, Youngjin Kwon, and Myeongjae Jeon. Zico: Efficient {GPU} memory sharing for concurrent {DNN} training. In *2021 USENIX Annual Technical Conference (USENIX ATC 21)*, pages 161–175, 2021.

[16] Zhongyi Lin, Evangelos Georganas, and John D Owens. Towards flexible and compiler-friendly layer fusion for cnns on multicore cpus. In *European Conference on Parallel Processing*, pages 232–248. Springer, 2021.

[17] Adam C Mater and Michelle L Coote. Deep learning in chemistry. *Journal of chemical information and modeling*, 59(6):2545–2559, 2019.

[18] Jayashree Mohan, Amar Phanishayee, Ashish Raniwala, and Vijay Chidambaram. Analyzing and mitigating data stalls in dnn training. *Proceedings of the VLDB Endowment*, 14(5):771–784, 2021.

[19] Supun Nakandala, Yuhao Zhang, and Arun Kumar. Cerebro: A data system for optimized deep learning model selection. *Proceedings of the VLDB Endowment*, 13(12):2159–2173, 2020.

[20] Thao Truong Nguyen, François Trahay, Jens Domke, Aleksandr Drozd, Emil Vatai, Jianwei Liao, Mohamed Wahib, and Balazs Gerofi. Why globally re-shuffle? revisiting data shuffling in large scale deep learning. In *IEEE International Parallel & Distributed Processing Symposium*, 2022.

[21] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

[22] Markus Reichstein, Gustau Camps-Valls, Bjorn Stevens, Martin Jung, Joachim Denzler, Nuno Carvalhais, et al. Deep learning and process understanding for data-driven earth system science. *Nature*, 566(7743):195–204, 2019.

[23] Michael Stonebraker. Operating system support for database management. *Communications of the ACM*, 24(7):412–418, 1981.

[24] Haotian Tang, Zhijian Liu, Shengyu Zhao, Yujun Lin, Ji Lin, Hanrui Wang, and Song Han. Searching efficient 3d architectures with sparse point-voxel convolution. In *European Conference on Computer Vision*, pages 685–702. Springer, 2020.

[25] Yuke Wang, Boyuan Feng, Gushu Li, Shuangchen Li, Lei Deng, Yuan Xie, and Yufei Ding. {GNNAdvisor}: An adaptive and efficient runtime system for {GNN} acceleration on {GPUs}. In *15th USENIX Symposium on Operating Systems Design and Implementation (OSDI 21)*, pages 515–531, 2021.

[26] Yun-Fu Wu. Correlated sampling techniques used in monte carlo simulation for risk assessment. *International Journal of Pressure Vessels and Piping*, 85(9):662–669, 2008. Special Issue: Advances in Structural Integrity of Nuclear Components in Asian Power Plants.

[27] Lenka Zdeborová. Understanding deep learning is also a job for physicists. *Nature Physics*, 16(6):602–604, 2020.

[28] Zhenwei Zhang, Qiang Qi, Ruitao Shang, Li Chen, and Fei Xu. Prophet: Speeding up distributed dnn training with predictable communication scheduling. In *50th International Conference on Parallel Processing*, pages 1–11, 2021.

Figure 8: When training multiple ResNet18 models simultaneously, the I/O speed is shown above.

Figure 9: When training 5 models with different speeds at the same time, the I/O speeds are shown above.

(a) When four jobs start at different moments, the I/O speeds are shown above.

(b) I/O speed are shown above when intersection sizes are different.

Figure 10: Training jobs arrive at different time and have different datasets

A Evaluation

In this section, we first present the I/O speed in the synchronous cases and asynchronous cases to show JOADER can reduce the redundant I/O work. Then, we evaluate the algorithm DSA and RefCnt separately for the ablation test. Finally, we show the loss and accuracy trace of ResNet18 in 40 epochs to demonstrate JOADER does not affect convergence speed. We denote the default dataloader strategy in PyTorch as the 'Baseline' method, and further compare JOADER with the state-of-the-art method CoorDL.

A.1 I/O speed

In this part, we show the I/O speed in the synchronous and asynchronous cases. Note that I/O is not the bottleneck in our server (Maximum I/O speed of the server is about 1GB/s). Figure 8 shows the I/O from training one job to training six jobs. The I/O speed of Baseline tends to increase while that of CoorDL and JOADER tends to decrease, because CoorDL and JOADER can reuse the data in memory. When we train 5 jobs (ResNet18, ResNet34, ResNet50, ResNet101, ResNet152) with different speed, the I/O speed is shown in Figure 9. Although the I/O speed of CoorDL is far less than JOADER, the fast job must wait for a slow job causing inefficiency. JOADER can make jobs run at their own speeds. Figure 10a show the I/O speed for four jobs that start at different moments. Due to the redundant I/O work, the baseline has a more considerable I/O speed. For JOADER, the more data is shared, the smaller the I/O speed, as shown in Figure 10b.

(a) Misses count of DSA and ISA for different intersections with a cache of size from 1 to 10000. DSA can always get the minimum misses.

(b) Misses count of DSA and ISA for different dataset sizes with a cache of size from 1 to 10000. DSA can reduce lots of misses.

Figure 11: Misses count of DSA and ISA in various scenes for 2 jobs

(a) Misses count for 4 jobs in an utterly random scene. RefCnt can reduce 10% misses for the same cache size.

(b) Misses count for 4 jobs with datasets of different sizes. RefCnt can reduce 10% misses for the same cache size.

Figure 12: The number of misses with different cache policies applied with dependent sampling algorithm.

A.2 Algorithm evaluation

In this section, we first compare ISA, the default sampling algorithm in PyTorch, with DSA to show the performance in two cases: 1) datasets overlap partially, and 2) datasets vary in size. Then we further compare the RefCnt with the generic cache policy in the above cases. We evaluate these algorithms in different cache sizes and the evaluation metric is the count of *cache misses*, indicating the number of elements not read from the cache. For n datasets $D_1, D_2, ..., D_n$, the maximum count of cache misses is $|D_1| + |D_2| + ... + |D_n|$ that all the data is read from the storage, while the minimum is $|D_1 \cup D_2 \cup ... \cup D_n|$ that all the repeated data is hit in cache.

We construct the following cases for evaluation[5] in Table 2:

Dependent sampling algorithm. In this part, we show DSA can significantly reduce the cache misses in various of scenes. To simulate various scenes, we generate multiple datasets with different sizes and different intersections. We use DSA to access them in shuffling order from the storage with the cache of different sizes (e.g., from one-slot to holding all datasets) to evaluate the number of misses, compared with the experimental results with ISA (shuffling independently).

We start the the evaluation in two jobs training on $dataset_1$ and $dataset_2$, respectively. We set up eight different configurations for the two datasets, which can be divided into two types: the different sizes of intersections and different sizes of the datasets, as shown in Table 2.

---

[5]1) $D = [0, 1e4]$ means dataset D constains all number from 0 to 10000. 2) $D = sample([0, 13333], 10000)$ means sample a subset D with 10000 of size from $[0, 13333]$ uniformly at random

Table 2: Configuration of the number of jobs and datasets

Algorithm	Case	Num	way of construct dataset
Sampling Algorithm	overlapping partially	2	$D_1 = [0, 1e4]; D_2 = [0, 1e4]$
		2	$D_1 = [0, 1e4]; D_2 = [7500, 17500]$
		2	$D_1 = [0, 1e4]; D_2 = [5000, 15000]$
		2	$D_1 = [0, 1e4]; D_2 = [2500, 12500]$
		4	$D_1, D_2, D_3, D_4 = sample([0, 13333], 10000)$
	varying in size	2	$D_1 = [0, 1e4]; D_2 = [0, 1e4]$
		2	$D_1 = [0, 1e4]; D_2 = [0, 7500]$
		2	$D_1 = [0, 1e4]; D_2 = [0, 5000]$
		2	$D_1 = [0, 1e4]; D_2 = [0, 2500]$
		4	$D_1 = [0, 1e4]; D_2 = [0, 7500], D_3 = [0, 5000], D_4 = [0, 2500]$
Cache Policy	overlapping partially	4	$D_1, D_2, D_3, D_4 = sample([0, 13333], 10000)$
	varying in size	4	$D_1 = [0, 1e4]; D_2 = [0, 7500], D_3 = [0, 5000], D_4 = [0, 2500]$

For different intersection sizes, Figure 11a plots the relations between cache size and the count of cache misses. For ISA, the misses count is 2x higher than the size of dataset in the case of one-slot cache, shows that all elements are missed and it decreases linearly as the cache size increase. Unless the cache can hold all the data of intersection, the misses count could be minimized. However, DSA can always get the minimum cache misses regardless of the cache size. The reason is that in the selecting procedure, all jobs must select the same subset when the datasets' sizes are equal, due to the conditional probability of 1. Thus, their sampling results would be the same, meaning that all jobs will access the same element simultaneously when the datasets with the same size.

Figure 11b plots the evaluation results on for the datasets with different sizes. For one-slot cache, DSA can reduce 50% cache misses compared with ISA when the dataset sizes differ by 25%. The cache held 30% dataset could get the best performance for DSA while ISA needs to cache 75% dataset to reach optimal. DSA needs to cache 25% data because the size difference brings some uncertainty in the selecting procedure.

Then, we evaluate the DSA algorithm on four DNN training jobs to show the outstanding performance of the DSA algorithm on multiple datasets. Multiple datasets bring more complexity to the intersection as there can be $2^n - 1$ intersection sets for n sets. To simulate an utterly random scene, we random sample 10,000 elements from 13,333 elements four times, making four different datasets for evaluation. Compared ISA in the random scene, DSA can reduce 50% misses with a one-slot cache (20000 misses out of 40000 misses), as shown in Figure 13a.

DSA also provides good performance for multiple jobs training on datasets with different sizes. Compared to ISA in Figure 13b, one-slot cache can reduce 30% cache misses (16000 misses out of 22000 misses) with DSA when four jobs are training on four datasets, with a 25% different size.

RefCnt cache policy. In this part, we compare cache policy RefCnt with the generic cache policies LRU, FIFO, and random replacement (RR) to show 10% misses reduction with the same cache size. We evaluate these policies in above two situations of four jobs: utterly random scene and different dataset sizes. Figure 12 shows the results, which can be summarized as two improvements: 1) RefCnt cache policy can reduce 10% misses in the same cache size compared with general cache policies, and 2) RefCnt cache policy can get the best performance with only caching the 60% dataset while the generic cache policies require holding the whole dataset.

A.3 Correctness experiments

To demonstrate JOADER does not affect convergence speed w.r.t. accuracy and loss, we train ResNet18 on ImageNet-1K with JOADER and PyTorch[6]. Figure 13 shows that the loss descent trajectory and accuracy trajectory are almost the same.

---

[6]To activate DSA, we run 2 jobs at different moments

(a) Accuracy trace   (b) Loss trace

Figure 13: Trace of training ResNet18 in 40 epochs

B Dependent Sampling Algorithm

In this section, we show the pseudo-code of the DSA, which involves two functions: selecting and sampling. The selecting algorithm is shown in Algorithm 1, and the sampling algorithm is shown in Algorithm 2.

Algorithm 1: Selecting Procedure

Data: n jobs $J_1, ..., J_n$ and n datasets $D_1, ..., D_n$
Result: The subset that each job selects

1 $JOB \leftarrow [J_1, ..., J_n]$; // Array of all jobs
2 $DS \leftarrow [D_1, ..., D_n]$; // Array of all datasets sorted by their cardinality
3 $S \leftarrow \emptyset$; // Set of data that are not selected
4 **while** $JOB \neq \emptyset$ **do**
5 $I \leftarrow \bigcap D_i - S, \forall D_i \in DS$;
6 $c \leftarrow |I|$;
7 **for** D, J ***in*** DS, JOB **do**
    // $\frac{c}{|D|-|S|}$ is the conditional probability $\frac{|D_{i-1}|}{|D_i|}$
8   **if** ***rand***$(0, 1) \leq \frac{c}{|D|-|S|}$ **then**
9   J selects I;
10     $DS \leftarrow DS - D$;
11     $JOB \leftarrow JOB - J$;
12     $c \leftarrow |D|$;
13   **else**
14   break;
15 **if** *There is no job selecting I* **then**
16    $JOB[0]$ selects $D[0] - I$;
17    $DS \leftarrow DS - D[0]$;
18    $JOB \leftarrow JOB - JOB[0]$;
19 $S \leftarrow S \cup I$;

C Sampling in Dependent Sampling Tree

The *sampling* operation involves two steps: 1) *Deciding:* choose a vertex for each job, and 2) *Sampling:* select an element in the corresponding vertex for each job randomly.

In *deciding*, we start the procedure from the root of the tree. In the beginning, all jobs are marked as *undecided*. In each vertex, all undecided jobs need to decide whether to select the current vertex, i.e.,

Algorithm 2: Sampling Procedure

Data: n jobs $J_1, ..., J_n$ and k subsets $S_1, ..., S_k$
Result: The sampling results of each job

1 $JOB \leftarrow [\{J_i, ..., J_j\}, ...]$; `// The job set where job selects the correspond subset`
2 $SUBSET \leftarrow [S_1, ..., S_k]$; `// The subset that the correspond job set selects`
3 **for** i **in** $0..k$ **do**
4 $\quad$ $subset \leftarrow SUBSET[i]$;
5 $\quad$ $job\_set \leftarrow JOB[i]$;
6 $\quad$ Sample e uniformly at random in $subset$;
7 $\quad$ **for** job **in** job_set **do**
8 $\quad\quad$ job picks e;

---

the intersection I in the DSA algorithm. If the job chooses the current vertex, we will remove them from the undecided job set. Then, the remaining undecided jobs are put down to the child and make decisions recursively until the undecided job set is empty, like Algorithm 1.

However, in *deciding*, there may be an intersection that contains multiple vertices of the sampling tree. As shown in Figure 4c, if job J_2 with D_2 and job J_3 with D_3 do not choose the root X in the first recursion, then they should make decision in the intersection $(D_2 - D_X) \cap (D_3 - D_X)$, which contains the datasets in vertices A and B. In this case, we should combine these vertices into a big set first and start the deciding procedure once. If someone chooses the big set, it should choose a vertex from the big set randomly again.

After the deciding procedure, each job is assigned to a vertex randomly. Then, we need to select an element in the corresponding vertex randomly. Based on the *united sampling* discussed in Section 3, those jobs that are assigned to the same vertex should share the same sampling result.

Each data item in the dataset should be read exactly once for a job in an epoch. Intuitively, the data item should be deleted from the vertex to avoid being read by the job repeatedly. This process raises the issue that other jobs may need the deleted element that some have read. For example, suppose in the Figure 4a, job J_1 fetches the element e_1 from vertex A while job J_2 and job J_3 fetch the element from other vertices. Thus, for J_1, we should remove e_1 from vertex A, but J_2 and J_3 still need the element e_1.

The compensation procedure is introduced in sampling to solve this issue, which adds the deleted element to the child vertex of the job that still needs it. To decide which vertex needs compensation, we construct a job set for each vertex that contains all the jobs that will sample in this vertex. For example, the job set of vertex A is $\{J_1, J_2, J_3\}$ and the set of vertex B is $\{J_2, J_3\}$ in Figure 4a. And after deleting some elements, we should construct a compensation set containing all the jobs that still need the deleted elements. If the compensation set includes the job set, the deleted elements are added to the corresponding vertex.

Partially Sampling. When some jobs are much faster than other jobs, we only need the sampling results for these fast jobs. The sampling procedures are the same as the above. However, the tree cannot be ordered after sampling because these datasets decrease fast and can be less than the above datasets in the tree soon. Therefore, we need to reorder the tree, just like the intersection procedure.

D Proof of Algorithm

In this section, we present the derivation and the proof for the proposed algorithm. Proposition 1 shows the first principle for randomness. Table 3 presents some notations for the following proof.

Proposition 1 *For any job J_i, the probability of choosing any element from dataset D_i is $\frac{1}{|D_i|}$.*

Table 3: Notation in sampling algorithm

J_i	The i-th job
D_i	Dataset that J_i trains upon
I	Intersection of all datasets
D_{di}	$D_i - I_i$
$|D|$	Cardinality of set D
J_i^I	Event that J_i chooses the intersection
J_i^D	Event that J_i do not choose the intersection
e_j^i	Element e_j picked by J_i in one round
S	Set of elements that are not selected

D.1 Derivation in Two-job Case

There are 2 jobs J_1 and J_2 which training upon datasets D_1 and D_2, while the intersection is $I = D_1 \cap D_1$ and two difference sets are $D_{d1} = D_1 - I, D_{d2} = D_2 - I$. Their cardinalities are $|D_1|, |D_2|, |I|, |D_{d1}|,$ and $|D_{d2}|$. The event that J_1 selects the intersection is J_1^I, while the event that J_1 selects the difference set is J_1^D.

Due to the randomness, the constraints that we need to maintain are

$$\begin{cases} p(J_1^I) = \dfrac{|I|}{|D_1|}, p(J_1^D) = \dfrac{|D_{d1}|}{|D_1|} \\ p(J_2^I) = \dfrac{|I|}{|D_2|}, p(J_2^D) = \dfrac{|D_{d2}|}{|D_2|}. \end{cases} \tag{1}$$

Since J_2 makes the decision conditioned on J_1, we can the formulate the equations according to the law of total probability in below

$$\begin{cases} p(J_2^I) = p(J_2^I|J_1^I) * p(J_1^I) + p(J_2^I|J_1^D) * p(J_1^D) \\ p(J_2^D) = p(J_2^D|J_1^I) * p(J_1^I) + p(J_2^D|J_1^D) * p(J_1^D). \end{cases} \tag{2}$$

After *shared sampling*, our target is to maximize the probability of J_1 and J_2 both choose the intersection, which is positive correlated with $p(J_2^I|J_1^I)$. The $p(J_2^I|J_1^I)$ is

$$\begin{aligned} p(J_2^I|J_1^I) &= \frac{p(J_2^I) - p(J_2^I|J_1^D) * p(J_1^D)}{p(J_1^I)} \\ &\leq min(1, \frac{p(J_2^I)}{p(J_1^I)}) \\ &\leq min(1, \frac{|D_1|}{|D_2|}). \end{aligned} \tag{3}$$

Therefore, we can get the conditional probability in two cases

$$p(J_2^I|J_1^I) = \begin{cases} 1, & \text{if } |D_1| > |D_2| \\ \frac{|D_1|}{|D_2|}, & \text{if } |D_1| \leq |D_2|. \end{cases} \tag{4}$$

When $|D_1| \leq |D_2|$, the other conditional probabilities of J_2 conditioned on J_1 can be derived as follows

$$\begin{cases} p(J_2^I|J_1^D) = 0 \\ p(J_2^D|J_1^D) = 1 \\ p(J_2^D|J_1^I) = 1 - \dfrac{|D_1|}{|D_2|}. \end{cases} \tag{5}$$

In *dependent selecting* procedure, the probability of both choosing intersection set is $p(J_1^I)*p(J_2^I|J_1^I)$. With *data partition*, we can get

$$p(e_j^1 = e_i^2) = p(J_1^I) * p(J_2^I|J_1^I) \leq \frac{|I|}{\max(|D_2|, |D_1|)}, \tag{6}$$

while e_j^1, e_i^2 is the sampling results of J_1, J_2 in one round.

We then prove the the proposed dependent algorithm gives the optimal solution for the scenario of two-jobs.

Proof 1 *Assume that the distribution of the event exists, and the probability of $p(e_j^1 = e_i^2)$ is unknown. When e_j^1 and e_i^2 are equal, they must belong to the intersection set D_i. Therefore, $p(e_j^1 = e_i^2)$ is equal to $p(e_j^1 = e_i^2, e_j^1 \in D_i, e_i^2 \in D_i)$. Due to the definition of joint probability, we can get*

$$p(e_j^1 = e_i^2) \leq p(e_j^1 \in D_i), \quad and \quad p(e_j^1 = e_i^2) \leq p(e_i^2 \in D_i).$$

Due to the constraint of randomness, e_j^1 and e_i^2 are both sampled under the uniform distribution, so $p(e_j^1 \in D_i) = \frac{|D_i|}{|D_1|}$ and $p(e_i^2 \in D_i) = \frac{|D_i|}{|D_2|}$. Then $p(e_j^1 = e_i^2) \leq \frac{|D_i|}{|D_1|}$ and $p(e_j^1 = e_i^2) \leq \frac{|D_i|}{|D_2|}$ both hold. Thus, for any distribution of the event, it holds that

$$p(e_j^1 = e_i^2) \leq \frac{|D_i|}{\max(|D_2|, |D_1|)}.$$

D.2 Derivation in N-job Case

Assume there are n jobs $\{J_1, ..., J_n\}$ and n datasets $\{D_1, ..., D_n\}$, while the intersection $I = \bigcap_{i=1}^{n} D_i$. For the k-th job where $k > 1$, the probability of the job J_k chooses the intersection is

$$p(J_k^I) = p(J_k^I | J_1^I, J_2^I, ..., J_{k-1}^I) * p(J_1^I, J_2^I, ..., J_{k-1}^I) + x, \tag{7}$$

where x is the sum of probabilities of J_k chooses intersection in other conditions. With the similar process in Proof 1, we can get the result for k-jobs, where the maximum probability of they all choose intersection is also $p(J_1^I ... J_k^I) \leq \frac{|I|}{max(D_1, ..., D_k)}$. Then, we can get

$$p(J_k^I | J_1^I, J_2^I, ..., J_{k-1}^I) \leq min(\frac{p(J_k^I)}{p(J_1^I, J_2^I, ..., J_{k-1}^I)}, 1)$$

$$\leq min(\frac{\frac{|I|}{|D_k|}}{\frac{|I|}{max(D_1, ..., D_{k-1})}}, 1) \tag{8}$$

$$\leq min(\frac{max(D_1, ..., D_{k-1})}{|D_k|}, 1).$$

Assume that the datasets are sorted in ascending order w.r.t. their cardinalities, then the formula can be written as for the maximum probability

$$p(J_k^I | J_1^I, J_2^I, ..., J_{k-1}^I) = \frac{|D_{k-1}|}{|D_k|}. \tag{9}$$

The probability of n jobs all choose intersection I is

$$p(J_1^I, J_2^I, ..., J_n^I) = \frac{|I|}{|D_1|} * \frac{|D_1|}{|D_2|} * ... * \frac{|D_{n-1}|}{|D_n|} \leq \frac{|I|}{|D_n|}, \tag{10}$$

which is the theoretical maximum according to a similar Proof 1.

D.3 Proof of Randomness

We prove the Proposition 1 for Algorithm 1. Although multiple jobs share the sampling results in the sampling procedure, the random sampling is not changed. Therefore, to prove Proposition 1, we only need to prove the subsets are randomly selected for each job. The Lemma is stated as follow

Lemma 1 *In each loop of selecting procedure, the intersection I is selected with the probability of $\frac{|I|}{|D_i|}$ for every job J_i.*

In the line 8-12 of Algorithm 1, the job J_i chooses the intersection only if the previous job has chosen the intersection I, that the probability is

$$p(J_i^I) = p(J_i^I | J_{i-1}^I, ...) * p(J_{i-1}^I, ...)$$
$$= \frac{|I|}{|D_i| - |S|}.$$
(11)

Therefore, the Lemma 1 is satisfied only if the probability of entering this loop is $\frac{|D_i| - |S|}{|D_i|}$, that is

Lemma 2 *For each loop, the set of elements that are not selected is S, and the probability of entering this loop is $\frac{|D_i| - |S|}{|D_i|}$ for job J_i.*

Proof 2 *We prove the Lemma 2 by induction on loop index k.*

Base case. *Show Lemma 2 holds for the first loop.*
The first loop ($k = 1$) must be entered, while S is an empty set and $\frac{|D_i| - |S|}{|D_i|} = 1$. Thus Lemma 2 is satisfied.

Induction step. *Show that for any $k \geq 1$, if the k-th recursion holds Lemma 2, then $(k + 1)$-th loop also holds.*
The probability of entering the k-th loop is $\frac{|D_i| - |S|}{|D_i|}$, and if job J_i does not select the intersection in the k-th loop, then it entering the $(k + 1)$-th loop. The probability of J_i does not select intersection is

$$\begin{aligned}
p(J_i^D) &= p(J_k^D) + p(J_{k+1}^D) + ... + p(J_i^D) \\
&= p(J_k^D) + p(J_{k+1}^D | J_k^I) * p(J_k^I) + ... + p(J_i^D | J_{i-1}^I) * p(J_{i-1}^I) \\
&= p(J_k^D) + (1 - p(J_{k+1}^I | J_k^I)) * p(J_k^I) + ... + (1 - p(J_i^I | J_{i-1}^I) * p(J_{i-1}^I) \\
&= p(J_k^D) + p(J_k^I) - p(J_{k+1}^I) + p(J_{k+1}^I) - ... - p(J_i^I) \\
&= 1 - p(J_i^I) \\
&= 1 - \frac{|I|}{|D_k| - |S|} * \frac{|D_k| - |S|}{|D_{k+1} - |S|} * \frac{|D_{i-1}| - |S|}{|D_i| - |S|} \\
&= \frac{|D_i| - |S| - |I|}{|D_i| - |S|}
\end{aligned}$$
(12)

where J_k is the first job in job List JOB, then we can get the probability of entering the next loop is $\frac{|D_i| - |S| - |I|}{|D_i|}$ while new S is $S \cup I$, which also satisfies the Lemma 2.

Conclusion. *Since both the base case and the inductive step have been proved as true, the Lemma 2 holds for every loop by mathematical induction.*