Rethinking Reasoning Quality in Large Language Models through Enhanced Chain-of-Thought via RL

Abstract

Reinforcement learning (RL) has recently become the dominant paradigm for strengthening the reasoning abilities of large language models (LLMs). Yet the rule-based reward functions commonly used on mathematical or programming benchmarks assess only answer format and correctness, providing no signal as to whether the induced Chain-of-Thought (CoT) actually improves the answer. Furthermore, such task-specific training offers limited control over logical depth and therefore may fail to reveal a model's genuine reasoning capacity. We propose **D**ynamic **R**easoning **E**fficiency **R**eward (**DRER**) — a plug-and-play RL reward framework that reshapes both reward and advantage signals. (i) A *Reasoning Quality Reward* assigns fine-grained credit to those reasoning chains that demonstrably raise the likelihood of the correct answer, directly incentivising the trajectories with beneficial CoT tokens. (ii) A *Dynamic Length Advantage* decays the advantage of responses whose length deviates from a validation-derived threshold, stabilising training. To facilitate rigorous assessment, we also release *LogicTree*, a dynamically constructed deductive reasoning dataset that functions both as RL training data and as a comprehensive benchmark. Experiments show that DRER achieves significant improvements in reasoning accuracy and CoT quality over baseline methods across diverse training settings, while also reducing token usage during inference. Moreover, it demonstrates strong generalization on both reasoning and mathematical benchmarks, such as GPQA and AIME24. These results indicate that DRER, as a plug-and-play fine-grained RL reward framework, reliably strengthens reasoning behavior and provides a practical pathway toward enhancing the reasoning capabilities of large language models. All code and data are available in our anonymous repository https://anonymous.4open.science/r/DRER-D34E.

1 Introduction

Recent reasoning models (DeepMind, 2024; Qwen, 2024; Team et al., 2025), including R1-like reproductions (Team et al., 2025; Mei et al., 2025; Yu et al., 2025; Shao et al., 2024; Hu, 2025; Kool et al., 2019; Ahmadian et al., 2024), have adopted reinforcement learning (RL) to enhance chain-of-thought reasoning. By systematically exploring verifiable reasoning paths that lead to correct answers, these methods incrementally boost performance and deliver remarkable gains. Current RL-driven CoT approaches typically train on mathematics and programming benchmarks (OpenAI, 2024; Guo et al., 2025; Cobbe et al., 2021; Chen et al., 2021), whose inherently stepwise solution procedures serve as natural proxies for logical inference (Wang et al., 2024a; Li et al., 2024), and they rely on rule-based reward (OpenAI, 2024; Guo et al., 2025) functions that assess only final answer correctness and formatting. This reliance stems from the straightforward evaluability of math and code tasks, where simple answer extraction or format checks suffice to assign reward signals and compute policy advantages.

However, this approach still faces two critical challenges. First, by relying solely on final-answer correctness as the reward signal, the model cannot distinguish which reasoning steps statistically boost the likelihood of the correct answers (Paul et al., 2024), nor quantify each token's substantive contribution to the conclusion; instead, it may lean on "decorative" chains that diverge from genuine deductive paths (Zhang et al., 2024), thereby undermining the accurate evaluation and effective training of its reasoning ability.

Second, the corpora used to reinforce "reasoning ability" are almost entirely drawn from execution-verifiable domains (Sprague et al., 2024b)—such as mathematical problem sets and code synthesis tasks—while unified training data targeting pure

formal logical inference remains severely lacking (Morishita et al., 2024). Such constrained training regimens risk conceptual overextension (Paul et al., 2024), whereby success on specific tasks is misconstrued as evidence of broadly applicable logical reasoning skills, potentially leading to an overestimation of the model's true inferential competence.

To address the limitations of outcome-only reward modeling in reasoning tasks, we propose *Dynamic Reasoning Efficiency Reward* (DRER), a plug-and-play reinforcement learning framework that reshapes both reward and advantage signals. DRER introduces two key mechanisms: (1) a *Reasoning-Quality Reward*, which assigns fine-grained credit to reasoning chains that statistically improve the likelihood of the correct answer, thereby reinforcing the utility of CoT tokens; and (2) a *Dynamic-Length Advantage*, which attenuates the policy advantage of responses whose lengths deviate from a validation-derived threshold, improving training stability. The overall framework is illustrated in Figure 1. In addition, we release *LogicTree*, a domain-agnostic deductive reasoning dataset carefully constructed to provide focused training supervision and to serve as a clean evaluation benchmark for identifying pathological reasoning behaviours.

Our experiments demonstrate that DRER significantly improves chain-of-thought (CoT) reasoning quality across different baseline algorithms and training corpora by providing fine-grained reward signals. When trained on the General Reasoning dataset, DRER consistently yields substantial improvements over both GRPO (Shao et al., 2024) and DAPO (Yu et al., 2025) base algorithms, achieving superior reasoning accuracy and CoT quality across a wide range of benchmarks. When trained on the LogicTree dataset, the combination of DRER and DAPO increases the accuracy of Qwen2.5-7B-Instruct-1M from 13.2% to 60.0%, while reducing token consumption by approximately 75% and achieving higher reasoning consistency. Taken together, these results show that DRER, as a plug-and-play fine-grained reward framework, reliably enhances the reasoning capabilities of LLMs in diverse training settings and offers significant advantages over existing baseline methods.

The main contributions of this paper are summarized as follows:

- We propose **DRER** (**D**ynamic **R**easoning **E**fficiency **R**eward), a novel reinforcement learning reward framework that adaptively reshapes both reward and advantage signals to improve CoT reasoning.
- We release *LogicTree*, a domain-agnostic benchmark for formal deductive reasoning that serves dual purposes: functioning as both a focused training set and a clean evaluation benchmark, while providing valuable insights into LLMs' reasoning behaviours.
- We systematically validate our approach through extensive experiments, confirming the effectiveness of our methodology in improving both reasoning quality and efficiency.

2 Preliminary

Group Relative Policy Optimization (GRPO) GRPO(Shao et al., 2024) removes the value function used in PPO(Schulman et al., 2017a) and estimates the advantages within a group of G responses sampled by the behavior policy $\pi_{\theta_{\text{old}}}$ for each pair of questions-answers (q, a). GRPO maximizes a PPO-style clipped objective with an explicit KL penalty:

$$
\mathcal{J}_{\text{GRPO}}(\theta) = \mathbb{E}_{(q,a)\sim\mathcal{D},\{o_i\}\sim\pi_{\theta_{\text{old}}}}\left[\frac{1}{G}\sum_{i=1}^{G}\frac{1}{|o_i|}\right.
$$

$$
\sum_{t=1}^{|o_i|}\Big(\min\big(r_{i,t}\hat{A}_{i,t},\ \text{clip}(r_{i,t}, 1-\epsilon, 1+\epsilon)\hat{A}_{i,t}\big) \quad (1)
$$

$$
\left.- \beta\,\mathrm{D}_{\text{KL}}(\pi_\theta \parallel \pi_{\text{ref}})\Big)\right],
$$

where

$$
r_{i,t}(\theta) = \frac{\pi_\theta(o_{i,t} \mid q, o_{i,<t})}{\pi_{\theta_{\text{old}}}(o_{i,t} \mid q, o_{i,<t})},
$$
$$
\hat{A}_{i,t} = \frac{R_i - \text{mean}(\{R_i\}_{i=1}^{G})}{\text{std}(\{R_i\}_{i=1}^{G})}. \quad (2)
$$

GRPO first averages token-level losses within each response and then across the group, a sample-level aggregation that can implicitly favor longer responses and thus influence training dynamics (Liu et al., 2025).

Decouple Clip and Dynamic Sampling Policy Optimization (DAPO) DAPO (Yu et al., 2025) retains GRPO's group-based sampling and advantage normalization but introduces two modifications: (i) asymmetric clipping bounds ($\varepsilon_{\text{low}} \neq$

Figure 1: Overview of the Dynamic Reasoning Efficiency Reward (DRER) framework. $Length_{95}$ and $Length_5$ represent the 95th and 5th percentile lengths, respectively, computed from the validation set, and are used to normalize reasoning trajectory lengths according to task type or difficulty.

ε_{high}) that permit broader exploration while keeping updates conservative, and (ii) a dynamic sampling constraint requiring the group to contain both correct and incorrect responses, thereby ensuring meaningful advantage shaping. Both $r_{i,t}$ and $\hat{A}_{i,t}$ are computed as in Eq. 2.

Reward Modeling Reward modeling in RL for LLMs falls into two categories: learned reward models (RMs) and rule-based rewards. Learned RMs—including process reward models (PRMs) such as MATH-SHEPHERD (Wang et al., 2024b) and OmegaPRM (Luo et al., 2024a)—can evaluate intermediate reasoning steps but incur high annotation costs and potential data bias. Rule-based rewards (Lyu et al., 2025; Xie et al., 2025; Li et al., 2025; Guo et al., 2025), which check answer correctness and format validity, are far cheaper and more transparent, making them the dominant choice for large-scale RL training. Their critical shortcoming, however, is that they evaluate only the final outcome: the quality of intermediate reasoning steps goes entirely unsupervised, allowing models to produce correct answers via spurious or incoherent chains of thought (Zhang et al., 2025).

3 Method

3.1 DRER

To close this gap, we introduce Dynamic Reasoning Efficiency Reward (DRER), a plug-and-play framework that supplements outcome-level rewards with fine-grained signals about *how* the model reasons. DRER shapes both the reward and the advantage: it credits reasoning chains that demonstrably raise the likelihood of the correct answer while attenuating the influence of responses whose lengths deviate from a validation-derived norm.

Given an input question x, the large-language model (LLM) π_θ produces an output sequence y autoregressively:

$$\pi_\theta(y \mid x) = \prod_{t=1}^{T} P_{\pi_\theta}(y_t \mid x, y_{<t}), \quad (3)$$

where the sequence $y = [c, a]$ denotes the model's output sequence, where the first contiguous segment $c = (c_1, \ldots, c_{T_c})$ comprises the CoT tokens and the second segment $a = (a_1, \ldots, a_{T_a})$ contains the answer tokens. The overall sequence length satisfies $T = T_c + T_a$.

We believe that if the generated CoT tokens c are positive and coherent with the correct answer, it should *increase* the model's confidence in predicting ground-truth answer token:

$$\ell_{CoT} = \frac{1}{T_a} \sum_{t=1}^{T_a} \log \pi_\theta(a_t^\star \mid x_{CoT}, c, a_{<t}^\star),$$

$$\qquad\qquad\qquad\qquad\qquad (4)$$

$$\ell_{NoCoT} = \frac{1}{T_a} \sum_{t=1}^{T_a} \log \pi_\theta(a_t^\star \mid x_{NoCoT}, a_{<t}^\star),$$

CoT reasoning tokens that positively contribute to the model's ability to infer the correct answer should satisfy

$$\ell_{CoT} > \ell_{NoCoT}. \quad (5)$$

where x_{CoT} and x_{NoCoT} denote the CoT and no CoT input question respectively; $c = (c_1, \ldots, c_{T_c})$ is the generated CoT of length T_c; $a^\star = (a_1^\star, \ldots, a_{T_a}^\star)$ is the ground-truth answer consisting of T_a tokens, and $a_{<t}^\star$ stands for its prefix up to position $t-1$; Finally, π_θ is the autoregressive language model policy parameterised by θ.

To validate this hypothesis, we conduct experiments using Qwen2.5-7B-Instruct-1M on benchmarks. We first evaluate model-generated CoT trajectories using GPT-5.1 under a unified step-wise rubric, and examine how CoT quality scores correlate with the delta of log-probabilities. We then perform a CoT-disturbance test by comparing original

CoT traces with shuffled and cross-question variants to assess delta of log-probabilities relevance to reasoning structure and semantic relevance. Finally, we analyze the impact of CoT on answer correctness by comparing likelihood shifts between CoT and no-CoT and examining fix and break rates across datasets. Full experimental details and results are provided in section 4.6.

Reasoning Quality Reward To make the confidence-boosting property in (5) learnable, we define for each training instance $\mathbf{x}$ the log-likelihood margin

$$\Delta(\mathbf{x}) = \ell_{\text{CoT}} - \ell_{\text{NoCoT}}, \tag{6}$$

where ℓ_{CoT} and ℓ_{NoCoT} are given in (4). A positive $\Delta(\mathbf{x})$ indicates that the generated CoT reasoning tokens enhance the model's confidence in the correct answer, whereas a negative value reveals detrimental or spurious reasoning.

To obtain a numerically stable reward, we pass the margin through a smooth, bounded squashing function

$$R_q = \tanh\big(\Delta(\mathbf{x})\big), \tag{7}$$

yielding the *reasoning-quality reward*. The hyperbolic tangent preserves the sign of the margin, caps extreme values.

We incorporate R_q into the overall reinforcement-learning objective by maximising the expected composite return

$$R = R_{\text{task}} + \lambda_q R_q, \tag{8}$$

where R_{task} denotes the task-level reward (e.g., answer and format correctness) and $\lambda_q > 0$ is a weighting coefficient that balances task success and reasoning quality. This formulation directly rewards reasoning chains that demonstrably increase the likelihood of the correct answer while penalising uninformative or misleading chains, thereby systematically improving the model's logical reliability and interpretability.

Dynamic Length Advantage After every validation round we record the lengths $\{L_i\}$ of responses that are both correct and structurally valid within each difficulty bucket[1]. The empirical 5% and 95% quantiles define a dynamic lower and upper length bound, $L_{\min}^{(d)}$ and $L_{\max}^{(d)}$, respectively, for bucket d. For a training sample i with effective response

length ℓ_i, we introduce a multiplicative attenuation coefficient

$$g_i = \exp\!\Big(-\frac{\max\{0,\, L_{\min}^{(d)} - \ell_i\,,\, \ell_i - L_{\max}^{(d)}\}}{\tau}\Big), \tag{9}$$

where $\tau > 0$, $L_{\min}^{(d)}$ denotes the 5th-percentile response length observed in the previous validation step for bucket d, while $L_{\max}^{(d)}$ corresponds to the 95th percentile in the same distribution. The variable ℓ_i represents the effective response length of the current sample i, and $\tau \in [5, 10]$ is a temperature hyperparameter that controls the decay rate of the attenuation function.

The attenuation is then applied to the advantage computed by GROUP COMPUTATION, $\hat{A}_i = g_i A_i$, so that responses that are excessively short ($\ell_i < L_{\min}^{(d)}$) or verbose ($\ell_i > L_{\max}^{(d)}$) are exponentially down-weighted. This mechanism penalises pathological length behaviours while preserving the signal of well-sized, high-quality chains of thought. The complete algorithm procedure of DRER is detailed in Appendix 1.

3.2 LogicTree

Most 'reasoning' benchmarks still fail to isolate formal deduction. Difficulty is inflated by injecting domain facts or arithmetic tricks, so logical skill is confounded with knowledge retrieval and calculation (Lin et al., 2025; Sprague et al., 2024b). Logical depth and structure remain almost uncontrollable: items rarely reveal how accuracy decays as inference chains lengthen, and no systematic consistency checks can be run across paraphrased versions of the same proof pattern (Saparov et al., 2023; Sprague et al., 2024a). Finally, intermediate steps are almost never evaluated; model capability is judged solely by the final answer (Paul et al., 2024).

Therefore, we present the LogicTree dataset, based on nested deductive reasoning rules that poses significant challenges to state-of-the-art LRMs. Solving these problems requires models to not only recognize and correctly apply reasoning logic across diverse contexts but also to strategically plan hierarchical inference steps. Specifically, our dataset exhibits following key features:

Programmatic Construction, The reasoning depth, breadth, and number of sub-questions are fully controllable as shown in Figure 2 and Appendix A.2. Beyond evaluating models' judgment on root conclusions, intermediate reason-

---

[1] A bucket may correspond to a task type, question template, or any other granularity used in specific tasks.

Figure 2: The framework of LOGICTREE automatic construction pipeline. We first sample atomic logic structures and sentences from seven deduction logic rules and four sentential logics, then fill it with natural statements in filtered AscentKB (Nguyen et al., 2021), and eventually construct the nested argument tree. Those intermediate will be hidden and transformed into questions.

ing steps are extracted and expanded into sub-questions. Compared to prior deductive reasoning benchmarks, this enables granular assessment of models' hierarchical reasoning accuracy.

Diverse Logical Forms, In contrast to grid puzzles or other logic games, LogicTree incorporates seven deductive reasoning rules and four sentential logic patterns, with each problem featuring distinct rule combinations. This significantly elevates the logical complexity.

Probing LLMs' Foundational Reasoning, We undertake multifaceted efforts to examine models' core logical capabilities. First, the dataset is decoupled from domain-specific knowledge to ensure models focus solely on pure logical reasoning. Second, we propose a logical consistency metric to evaluate models' ability to comprehend identical underlying logic across varying contextual representations.

Evaluation The LogicTree dataset is programmatically generated with full control over logical depth, sub-problem quantity, and reasoning variations, which enables multifaceted analysis of models' logic mechanism from novel perspectives.

We introduce three evaluation metrics: (1) Accuracy: Standard correctness rate, only credited when every sub-question is correctly answered; (2) Consistency Ratio: Reasoning stability across logically equivalent queries, measured as consistent correctness over several isomorphic questions; (3) $F\beta$-Score: Balances Answer Rate (proportion of valid *True*/*False* responses) and Precision (accuracy among valid responses) with parameter β.

Note that, unlike traditional NLI datasets with three-class classification (Cheng et al., 2025; Liu and Zhang, 2024) (*True*, *False*, or *Uncertain*), we restrict labels to *True*/*False* to mitigate semantic ambiguity that often artificially inflates accuracy by encouraging defaulting to *Uncertain*. LLMs may respond with *Unknown* during inference, reducing statistical noise from random guessing.

4 Experiment

4.1 Experimental Settings

In the experiment section, we conduct 400-step post-training of the Qwen2.5-7B-Instruct-1M model using two baseline algorithms, DAPO and GRPO, with two distinct training datasets: Logic-Tree Data, focused on deductive logic, and General Reasoning Data, which blends mathematical and multi-domain reasoning data. This diversified training setup fully demonstrates the generality of the DRER framework. Specific experimental settings can be found in Appendix D.1. The main experiments evaluate the model on multiple public benchmarks and the LogicTree benchmark, confirming the enhancement of logical reasoning capability. Additionally, we perform detailed attribution and ablation studies to elucidate the mechanism and validate the effectiveness of each module within DRER.

4.2 Main Results

Training Across 400 training steps, accuracy on LogicTree rises monotonically from 7% to nearly 60% (Figure 5), while reasoning traces become more concise. Table 18 shows that DRER improves both final accuracy and convergence in the two settings. Figure 3 and Figure 11 further indicate that DRER reaches stronger or comparable performance earlier than the DAPO/GRPO baselines, suggesting better training efficiency.

Deductive Rule	Logical Form	Amount
Modus Ponens	$(p \rightarrow q) \wedge p \implies q$	6 760
Modus Tollens	$(p \rightarrow q) \wedge \neg q \implies \neg p$	6 750
Hypothetical Syllogism	$(p \rightarrow q) \wedge (q \rightarrow r) \implies (p \rightarrow r)$	4 230
Disjunctive Syllogism	$(p \vee q) \wedge \neg p \implies q$	6 865
Reductio *ad Absurdum*	$(p \rightarrow q) \wedge (p \rightarrow \neg q) \implies \neg p$	6 780
Constructive Dilemma	$(p \rightarrow q) \wedge (r \rightarrow s) \wedge (p \vee r) \implies (q \vee s)$	1 900
Disjunction Elimination	$(p \vee q) \wedge (p \rightarrow s) \wedge (q \rightarrow s) \implies s$	6 625

Table 1: Deductive reasoning rules statistics on LogicTree 9.6k problems spanning depth 1-8.

Figure 3: Accuracy on the LogicTree during post-training with DAPO (left) and GRPO (right), with and without DRER.

Evaluation We additionally evaluated robustness with 5 random seeds on representative settings (GRPO/DAPO with and without DRER) over AIME24, GPQA, and LogicTree (Table 20). Mean performance remains stable with small standard deviations, and the relative ranking is consistent with the main results.

Table 2 reports results of the trained 7B model under different training configurations. Overall, DRER consistently outperforms baseline methods. With LogicTree-only training, gains appear on logic benchmarks (LogiQA2.0 and ZebraLogic) and transfer to math benchmarks (AIME24 and TheoremQA). With General Reasoning training, improvements remain stable on both math and multi-domain benchmarks, including MMLU-Pro and GPQA.

As detailed in Table 3, even advanced models such as GPT-o3-mini, DeepSeek-R1, and Claude3.7 remain below 20% at reasoning depths 7–8 on LogicTree. Qwen3-235B reaches 25% at depth 7 and 53% on average, still indicating clear difficulty on complex deductive reasoning. In contrast, our trained 7B model attains the best average accuracy and still achieves 31% at maximum depth.

We also observe distinct *Unknown* response tendencies across models. GPT-o4-mini is more conservative than GPT-4o (more *Unknown*), which leads to similar overall accuracy; however, it achieves higher Precision and *Fβ-Score* on valid

responses (Appendix 9).

4.3 Ablation Study

To quantify the contribution of each design choice in DRER, we conduct an ablation study.

Effect of Reasoning Quality Reward. As shown in Table 4, removing RQR reduces accuracy on both AIME24 (↓3.6) and GPQA (↓5.5). Appendix Figure 4 shows that the reasoning-quality reward rises and then stabilises, supporting that RQR consistently guides the policy toward CoT trajectories that genuinely help the final answer.

Effect of Dynamic Length Advantage. A small number of extreme-length responses in early training can destabilise the learned length distribution. DLA mitigates this by attenuating the advantage of these outliers. As shown in Table 4 and Figure 5, removing DLA lowers AIME24 by 2.1 points and GPQA by 3.3 points, while also increasing response-length fluctuations.

4.4 Does model really learn the logical paradigm?

A key question is whether models truly learn logic or merely memorize puzzles. Prior work (Cheng et al., 2025) shows self-contradiction on logically equivalent propositions; LogicTree tests this directly using problems with identical logical structures but different linguistic instantiations. Our Consistency Ratio quantifies this capability.

As shown in Table 19, most models handle simple deductive reasoning, but at depths 7–8 even state-of-the-art models such as GPT-o3-mini, Qwen3-235B, deepseek-r1, and Claude3.7 approach zero consistency, indicating limited capability for stable long-chain and combinatorial reasoning.

Model	AIME 24	MATH-500	TheoremQA	MMLU-Pro	GPQA	LogiQA2.0	ZebraLogic	LogicTree
Qwen2.5-7B	12.8	55.8	21.1	38.8	27.9	45.7	30.9	13.2
Training on LogicTree Data								
GRPO	13.1	54.7	18.2	38.4	27.1	47.1	33.5	45.1
GRPO+DRER	13.4	**56.2**	**18.9**	38.1	29.0	**52.6**	**36.2**	54.2
DAPO	13.9	55.9	17.6	**40.1**	33.5	46.5	32.3	52.4
DAPO+DRER	**16.5**	56.0	17.5	39.3	**35.2**	51.2	33.4	**60.0**
Traning on General Reasoning Data								
GRPO	14.8	56.4	24.2	39.1	29.9	45.3	31.8	11.0
GRPO+DRER	17.2	59.2	**25.1**	**39.7**	35.4	46.7	31.6	**14.1**
DAPO	14.5	56.6	23.9	38.5	32.3	45.6	31.1	13.0
DAPO+DRER	**18.3**	**61.8**	22.8	39.0	**38.6**	**47.5**	**32.4**	12.1

Table 2: Performance on Mathematical and Reasoning benchmarks. Qwen2.5-7B model referrs to `Qwen/Qwen2.5-7B-Instruct-1M`. AIME24 and LogicTree results are reported as Avg@32 and Avg. score, respectively; all other datasets use standard accuracy.

Model / Depth	1	2	3	4	5	6	7	8	Avg.
Qwen3-235B-A22B	**0.96**	**0.83**	0.66	**0.71**	0.46	0.32	0.25	0.07	0.53
Deepseek-R1	0.85	0.76	0.61	0.47	0.36	0.18	0.19	0.07	0.44
Claude-3.7-Sonnet	0.76	0.67	0.21	0.10	0.07	0.02	0.02	0.00	0.23
GPT-o4-mini	0.74	0.64	0.25	0.20	0.10	0.06	0.05	0.02	0.26
GRPO	0.81	0.71	0.58	0.42	0.45	0.20	0.20	0.11	0.45
GRPO+DRER	0.87	0.75	0.69	0.54	0.61	0.35	0.27	0.22	0.54
DAPO	0.88	0.73	0.66	0.47	0.60	0.36	0.23	0.20	0.52
Ours (DAPO+DRER)	0.90	**0.83**	**0.76**	0.59	**0.67**	**0.45**	**0.31**	**0.31**	**0.60**$^{\uparrow 0.47}$

Table 3: Comparison of Accuracy on LogicTree. For the complete results referring to Table 18.

We further examine whether models explicitly invoke specific deductive rules in their responses. Figure 10 provides word-frequency statistics across reasoning depths and representative examples. Explicit paradigm mentions decrease as logical complexity increases, and competence is uneven across paradigms—for example, DeepSeek-R1 frequently references *Modus Tollens* but rarely invokes *Disjunction Elimination*. Our framework shows better rule identification under higher complexity.

4.5 Why Does RQR Accurately Measure Reasoning Quality?

Information-theoretic interpretation. In information theory, the mutual information between two random variables Z and Y is defined as

$$I(Z;Y) = \mathbb{E}_{z,y}\left[\log \frac{p(z,y)}{p(z)\,p(y)}\right]$$

$$= \mathbb{E}_{z,y}\left[\log p(y \mid z) - \log p(y)\right]. \tag{10}$$

Then, the mutual information between the chain-of-thought z and the correct answer y^* conditioned on the input x can be expressed as:

$$I(z; y^* \mid x) = \mathbb{E}_{z,y^*|x}\Big[\log p(y^* \mid x, z)$$
$$- \log p(y^* \mid x)\Big]. \tag{11}$$

As shown in Eq.6 and Eq.7, RQR can be viewed as a sample-based estimator of the conditional mutual information $I(z; y^* \mid x)$ between CoT and the correct answer, i.e., the *information gain* contributed by CoT tokens to prediction. Additional validation is provided in Appendix E.

GPT-5.1–Based CoT Quality Scoring To assess whether RQR meaningfully estimates reasoning quality, we run controlled evaluations using GPT-5.1 as an external CoT judge. We compare trajectories from the base model, DAPO-only model, and DAPO+DRER model, and analyze how GPT-5.1 scores correlate with RQR. The full protocol and rubric are provided in Appendix E.1.

Results show a clear monotonic relationship: trajectories with higher GPT-5.1 quality scores consistently receive higher RQR values, indicating

Method	AIME 24	GPQA
DRER	**18.3**	**38.6**
w/o RQR	14.7$_{\downarrow 3.6}$	33.1$_{\downarrow 5.5}$
w/o DLA	16.2$_{\downarrow 2.1}$	35.3$_{\downarrow 3.3}$

Table 4: Ablation experiment result on DRER. Compare the performance w/o Reasoning Quality Reward(RQR) or Dynamic Length Advantage(DLA). Avg@32 score is reported on AIME24.

Table 5: Training dynamics of model response length w/o Dynamic Length Advantage(DLA).

that RQR tracks genuine reasoning improvement. DRER also shifts outputs toward higher-quality CoT, with clearly higher GPT-5.1 scores than both base and DAPO-only models. These findings suggest that RQR both reflects reasoning quality and functions as an effective training signal.

4.6 Does model's reasoning behaviour become more effective?

To isolate the effect of explanatory CoT on answer confidence, we test Qwen2.5-7B-Instruct-1M on 500 GSM8K and 500 LogicTree problems, generating both direct-answer (No-CoT) and step-by-step CoT outputs for each prompt. We define a CoT as **effective** when the model is *incorrect* under No-CoT but *correct* with CoT, and compute the log-probability gain of the ground-truth answer tokens $a_t^\star$ as $\ell_{\text{CoT}} - \ell_{\text{NoCoT}}$.

Samples are grouped by answer transition: **(WR)** wrong No-CoT / right CoT, **(RR)** right No-CoT / right CoT, **(WW)** wrong in both, and **(RW)** right No-CoT / wrong CoT. Statistics are reported in Tables 14 and 15.

We further split results by the sign of $\Delta\ell$ (Tables 16 and 17). Positive $\Delta\ell$ is associated with a higher fix rate (more WR transitions), while negative $\Delta\ell$ shows a higher break rate and lower fix rate.

Figure 12 and Figure 13 show prediction distributions for a difficulty-3 problem over 100 samples. Compared with the DAPO 400-step baseline, the DRER-trained policy yields a sharper peak around the ground-truth answer, indicating better concentration of probability mass on correct solutions.

Finally, Figure 6 and Figure 7 show that DRER maintains shorter and more stable responses, saving tokens per problem relative to baseline while improving accuracy. This supports DRER's ability to improve reasoning quality and reduce inference cost simultaneously.

5 Conclusion and Future Work

We propose DRER, a plug-and-play RL reward framework that reshapes both reward and advantage signals to explicitly link each reasoning step to the model's confidence in the correct answer, and LogicTree, a programmatically constructed deductive reasoning benchmark with controllable logical depth.

Extensive experiments show that DRER, through its fine-grained reward signals, enhances CoT reasoning quality, strengthens logical capability, and accelerates training convergence across diverse settings, while also reducing token usage during inference. Moreover, models trained on LogicTree generalise to mathematical benchmarks such as GPQA and AIME24, highlighting LogicTree as a reliable diagnostic environment for reasoning mechanisms in LLMs.

We release all code and the complete Logic-Tree corpus to ensure transparency and reproducibility. Together, DRER and LogicTree provide a lightweight, theoretically grounded basis for reasoning-aligned RL, enabling more interpretable LLMs in logic-critical domains.

6 Limitations

The main contributions of this work are twofold: we propose DRER, a plug-and-play reward framework that improves reinforcement learning for reasoning by jointly modeling CoT quality and length efficiency, and we introduce LogicTree, a benchmark with controllable reasoning depth for systematic training and evaluation of logical reasoning. Despite strong empirical results, our study has two limitations. First, the current LogicTree benchmark is primarily focused on deductive reasoning, and does not yet cover a broader range of reasoning

paradigms; future work will extend it to broader paradigms such as analogical and inductive reasoning for more comprehensive evaluation. Second, due to computational and resource constraints, our experiments are mainly conducted on mainstream models and do not yet cover more models from the open-source community. We plan to broaden model coverage and training settings in future work to further validate the generality and robustness of the proposed framework.

References

Arash Ahmadian, Chris Cremer, Matthias Gallé, Marzieh Fadaee, Julia Kreutzer, Olivier Pietquin, Ahmet Üstün, and Sara Hooker. 2024. Back to basics: Revisiting reinforce style optimization for learning from human feedback in llms. *Preprint*, arXiv:2402.14740.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, and 1 others. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Michael K Chen, Xikun Zhang, and Dacheng Tao. 2025. Justlogic: A comprehensive benchmark for evaluating deductive reasoning in large language models. *arXiv preprint arXiv:2501.14851*.

Fengxiang Cheng, Haoxuan Li, Fenrong Liu, Robert van Rooij, Kun Zhang, and Zhouchen Lin. 2025. Empowering llms with logical reasoning: A comprehensive survey. *arXiv preprint arXiv:2502.15652*.

Pengyu Cheng, Yong Dai, Tianhao Hu, Han Xu, Zhisong Zhang, Lei Han, Nan Du, and Xiaolong Li. 2024. Self-playing adversarial language game enhances llm reasoning. *Advances in Neural Information Processing Systems*, 37:126515–126543.

Peter Clark, Oyvind Tafjord, and Kyle Richardson. 2020. Transformers as soft reasoners over language. *arXiv preprint arXiv:2002.05867*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, and 1 others. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Google DeepMind. 2024. Gemini 2.0 flash thinking.

Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. 2021. Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies. *Transactions of the Association for Computational Linguistics*, 9:346–361.

Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Nan Duan, and Weizhu Chen. 2023. Critic: Large language models can self-correct with tool-interactive critiquing. *arXiv preprint arXiv:2305.11738*.

Jiayi Gui, Yiming Liu, Jiale Cheng, Xiaotao Gu, Xiao Liu, Hongning Wang, Yuxiao Dong, Jie Tang, and Minlie Huang. 2024. Logicgame: Benchmarking rule-based reasoning abilities of large language models. *arXiv preprint arXiv:2408.15778*.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Simeng Han, Hailey Schoelkopf, Yilun Zhao, Zhenting Qi, Martin Riddell, Wenfei Zhou, James Coady, David Peng, Yujie Qiao, Luke Benson, and 1 others. 2022. Folio: Natural language reasoning with first-order logic. *arXiv preprint arXiv:2209.00840*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the math dataset. In *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, volume 1.

Jian Hu. 2025. Reinforce++: A simple and efficient approach for aligning large language models. *arXiv preprint arXiv:2501.03262*.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. 2023. Large language models cannot self-correct reasoning yet. *arXiv preprint arXiv:2310.01798*.

Berkcan Kapusuzoglu, Supriyo Chakraborty, Chia-Hsuan Lee, and Sambit Sahu. 2025. Critique-guided distillation: Improving supervised fine-tuning via better distillation. *arXiv preprint arXiv:2505.11628*.

Mehran Kazemi, Quan Yuan, Deepti Bhatia, Najoung Kim, Xin Xu, Vaiva Imbrasaite, and Deepak Ramachandran. 2023. Boardgameqa: A dataset for natural language reasoning with contradictory information. *Advances in Neural Information Processing Systems*, 36:39052–39074.

Wouter Kool, Herke van Hoof, and Max Welling. 2019. Buy 4 REINFORCE samples, get a baseline for free! In *Deep Reinforcement Learning Meets Structured Prediction, ICLR 2019 Workshop, New Orleans, Louisiana, United States, May 6, 2019*. OpenReview.net.

Chengshu Li, Jacky Liang, Andy Zeng, Xinyun Chen, Karol Hausman, Dorsa Sadigh, Sergey Levine, Li Fei-Fei, Fei Xia, and Brian Ichter. 2024. Chain of code: Reasoning with a language model-augmented code emulator. In *International Conference on Machine Learning*, pages 28259–28277. PMLR.

Xuefeng Li, Haoyang Zou, and Pengfei Liu. 2025. Limr: Less is more for rl scaling. *Preprint*, arXiv:2502.11886.

Bill Yuchen Lin, Ronan Le Bras, Kyle Richardson, Ashish Sabharwal, Radha Poovendran, Peter Clark, and Yejin Choi. 2025. Zebralogic: On the scaling limits of llms for logical reasoning. *arXiv preprint arXiv:2502.01100*.

Hanmeng Liu, Jian Liu, Leyang Cui, Zhiyang Teng, Nan Duan, Ming Zhou, and Yue Zhang. 2023. Logiqa 2.0—an improved dataset for logical reasoning in natural language understanding. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 31:2947–2962.

Hanmeng Liu and Yue Zhang. 2024. A survey on logical reasoning of large pre-trained language models. In *Proceedings of the 23rd Chinese National Conference on Computational Linguistics (Volume 2: Frontier Forum)*, pages 48–62, Taiyuan, China. Chinese Information Processing Society of China.

Jian Liu, Leyang Cui, Hanmeng Liu, Dandan Huang, Yile Wang, and Yue Zhang. 2020. Logiqa: A challenge dataset for machine reading comprehension with logical reasoning. *arXiv preprint arXiv:2007.08124*.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. 2025. Understanding r1-zero-like training: A critical perspective. *Preprint*, arXiv:2503.20783.

Liangchen Luo, Yinxiao Liu, Rosanne Liu, Samrat Phatale, Meiqi Guo, Harsh Lara, Yunxuan Li, Lei Shu, Yun Zhu, Lei Meng, Jiao Sun, and Abhinav Rastogi. 2024a. Improve mathematical reasoning in language models by automated process supervision. *Preprint*, arXiv:2406.06592.

Liangchen Luo, Yinxiao Liu, Rosanne Liu, Samrat Phatale, Meiqi Guo, Harsh Lara, Yunxuan Li, Lei Shu, Yun Zhu, Lei Meng, and 1 others. 2024b. Improve mathematical reasoning in language models by automated process supervision. *arXiv preprint arXiv:2406.06592*.

Chengqi Lyu, Songyang Gao, Yuzhe Gu, Wenwei Zhang, Jianfei Gao, Kuikun Liu, Ziyi Wang, Shuaibin Li, Qian Zhao, Haian Huang, Weihan Cao, Jiangning Liu, Hongwei Liu, Junnan Liu, Songyang Zhang, Dahua Lin, and Kai Chen. 2025. Exploring the limit of outcome reward for learning mathematical reasoning. *Preprint*, arXiv:2502.06781.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, and 1 others. 2023. Self-refine: Iterative refinement with self-feedback. *Advances in Neural Information Processing Systems*, 36:46534–46594.

Zhiyu Mei, Wei Fu, Kaiwei Li, Guangju Wang, Huanchen Zhang, and Yi Wu. 2025. Real: Efficient

rlhf training of large language models with parameter reallocation. In *Proceedings of the Eighth Conference on Machine Learning and Systems, MLSys 2025, Santa Clara, CA, USA, May 12-15, 2025*. mlsys.org.

Terufumi Morishita, Gaku Morio, Atsuki Yamaguchi, and Yasuhiro Sogawa. 2024. Enhancing reasoning capabilities of llms via principled synthetic logic corpus. *Advances in Neural Information Processing Systems*, 37:73572–73604.

Tuan-Phong Nguyen, Simon Razniewski, and Gerhard Weikum. 2021. Advanced semantics for commonsense knowledge extraction. In *Proceedings of the Web Conference 2021*, pages 2636–2647.

OpenAI. 2024. Learning to reason with llms.

Debjit Paul, Robert West, Antoine Bosselut, and Boi Faltings. 2024. Making reasoning matter: Measuring and improving faithfulness of chain-of-thought reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 15012–15032.

Qwen. 2024. Qwq-32b: Embracing the power of reinforcement learning.

Chi Ruan, Dongfu Jiang, Yubo Wang, and Wenhu Chen. 2025. Critique-coder: Enhancing coder models by critique reinforcement learning. *arXiv preprint arXiv:2509.22824*.

Abulhair Saparov and He He. 2022. Language models are greedy reasoners: A systematic formal analysis of chain-of-thought. *arXiv preprint arXiv:2210.01240*.

Abulhair Saparov, Richard Yuanzhe Pang, Vishakh Padmakumar, Nitish Joshi, Mehran Kazemi, Najoung Kim, and He He. 2023. Testing the general deductive reasoning capacity of large language models using ood examples. *Advances in Neural Information Processing Systems*, 36:3083–3105.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017a. Proximal policy optimization algorithms. *Preprint*, arXiv:1707.06347.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017b. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Mingchuan Zhang, YK Li, Yu Wu, and Daya Guo. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36:8634–8652.

Zayne Sprague, Xi Ye, Kaj Bostrom, Swarat Chaudhuri, and Greg Durrett. 2024a. Musr: Testing the limits of chain-of-thought with multistep soft reasoning. *ICLR*.

Zayne Sprague, Fangcong Yin, Juan Diego Rodriguez, Dongwei Jiang, Manya Wadhwa, Prasann Singhal, Xinyu Zhao, Xi Ye, Kyle Mahowald, and Greg Durrett. 2024b. To cot or not to cot? chain-of-thought helps mainly on math and symbolic reasoning. *arXiv preprint arXiv:2409.12183*.

Kimi Team, Angang Du, Bofei Gao, Bowei Xing, Changjiu Jiang, Cheng Chen, Cheng Li, Chenjun Xiao, Chenzhuang Du, Chonghua Liao, and 1 others. 2025. Kimi k1. 5: Scaling reinforcement learning with llms. *arXiv preprint arXiv:2501.12599*.

Nemika Tyagi, Mihir Parmar, Mohith Kulkarni, Aswin Rrv, Nisarg Patel, Mutsumi Nakamura, Arindam Mitra, and Chitta Baral. 2024. Step-by-step reasoning to solve grid puzzles: Where do llms falter? *arXiv preprint arXiv:2407.14790*.

Karthik Valmeekam, Matthew Marquez, and Subbarao Kambhampati. 2023. Can large language models really improve by self-critiquing their own plans? *arXiv preprint arXiv:2310.08118*.

Ke Wang, Junting Pan, Weikang Shi, Zimu Lu, Houxing Ren, Aojun Zhou, Mingjie Zhan, and Hongsheng Li. 2024a. Measuring multimodal mathematical reasoning with math-vision dataset. *Advances in Neural Information Processing Systems*, 37:95095–95169.

Peiyi Wang, Lei Li, Zhihong Shao, R. X. Xu, Damai Dai, Yifei Li, Deli Chen, Y. Wu, and Zhifang Sui. 2024b. Math-shepherd: Verify and reinforce llms step-by-step without human annotations. *Preprint*, arXiv:2312.08935.

Peiyi Wang, Lei Li, Zhihong Shao, Runxin Xu, Damai Dai, Yifei Li, Deli Chen, Yu Wu, and Zhifang Sui. 2024c. Math-shepherd: Verify and reinforce llms step-by-step without human annotations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9426–9439.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, and 1 others. 2024d. Mmlu-pro: A more robust and challenging multi-task language understanding benchmark. In *The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.

Yubo Wang, Ping Nie, Kai Zou, Lijun Wu, and Wenhu Chen. 2025a. Unleashing the reasoning potential of pre-trained llms by critique fine-tuning on one problem. *arXiv preprint arXiv:2506.03295*.

Yubo Wang, Xiang Yue, and Wenhu Chen. 2025b. Critique fine-tuning: Learning to critique is more effective than learning to imitate. *arXiv preprint arXiv:2501.17703*.

Xumeng Wen, Zihan Liu, Shun Zheng, Shengyu Ye, Zhirong Wu, Yang Wang, Zhijian Xu, Xiao Liang, Junjie Li, Ziming Miao, and 1 others. 2025. Reinforcement learning with verifiable rewards implicitly incentivizes correct reasoning in base llms. *arXiv preprint arXiv:2506.14245*.

Chulin Xie, Yangsibo Huang, Chiyuan Zhang, Da Yu, Xinyun Chen, Bill Yuchen Lin, Bo Li, Badih Ghazi, and Ravi Kumar. 2024. On memorization of large language models in logical reasoning. In *The 4th Workshop on Mathematical Reasoning and AI at NeurIPS'24*.

Tian Xie, Zitian Gao, Qingnan Ren, Haoming Luo, Yuqian Hong, Bryan Dai, Joey Zhou, Kai Qiu, Zhirong Wu, and Chong Luo. 2025. Logic-rl: Unleashing llm reasoning with rule-based reinforcement learning. *Preprint*, arXiv:2502.14768.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W Cohen, Ruslan Salakhutdinov, and Christopher D Manning. 2018. Hotpotqa: A dataset for diverse, explainable multi-hop question answering. *arXiv preprint arXiv:1809.09600*.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, Haibin Lin, Zhiqi Lin, Bole Ma, Guangming Sheng, Yuxuan Tong, Chi Zhang, Mofan Zhang, Wang Zhang, Hang Zhu, and 16 others. 2025. Dapo: An open-source llm reinforcement learning system at scale. *Preprint*, arXiv:2503.14476.

Dan Zhang, Sining Zhoubian, Yisong Yue, Yuxiao Dong, and Jie Tang. 2024. Rest-mcts*: Llm self-training via process reward guided tree search. *arXiv preprint arXiv:2406.03816*.

Yi-Fan Zhang, Xingyu Lu, Xiao Hu, Chaoyou Fu, Bin Wen, Tianke Zhang, Changyi Liu, Kaiyu Jiang, Kaibing Chen, Kaiyu Tang, Haojie Ding, Jiankang Chen, Fan Yang, Zhang Zhang, Tingting Gao, and Liang Wang. 2025. R1-reward: Training multimodal reward model through stable reinforcement learning. *Preprint*, arXiv:2505.02835.

Qin Zhu, Fei Huang, Runyu Peng, Keming Lu, Bowen Yu, Qinyuan Cheng, Xipeng Qiu, Xuanjing Huang, and Junyang Lin. 2025. Autologi: Automated generation of logic puzzles for evaluating reasoning abilities of large language models. *arXiv preprint arXiv:2502.16906*.

A Technical Appendices and Supplementary Material

A.1 Seven Deductive Paradigms in LOGICTREE

LogicTree centres on seven classic deductive paradigms that constitute the atomic reasoning units of every sample. Each paradigm is implemented as a dedicated Python class (see `logic.py`)

Table 6: An example of a logictree puzzle.

whose constructor generates the required premises and the logically entailed conclusion. The table below summarises their formal schemata together with bilingual surface examples.

A.2 LogicTree: Template and Construction

We construct LogicTree through three automated steps:

1. **Logical Node Sampling.** Atomic premises and target conclusions are sampled from seven classical deductive rules (e.g., Modus Ponens, Modus Tollens) and four sentential logics, generating symbolic propositions.

2. **Natural-Language Instantiation.** Each symbolic proposition is mapped to natural declarative statements retrieved from the filtered AscentKB corpus (Nguyen et al., 2021), excluding ambiguous expressions or compound sentences to enhance lexical diversity while maintaining clarity.

3. **Nested-Tree Assembly.** The instantiated nodes are recursively composed into reasoning trees with configurable depth and width. Intermediate conclusions are masked from given premises, then transformed into sub-questions to create multi-step problem instances. This design ensures the inference process depends solely on logical form rather than sentence semantics, effectively decoupling reasoning from world knowledge.

A.3 Primitive and Compound Propositions

LogicTree expresses every deductive instance in terms of one *primitive statement* and four *compound connectives*. The primitive `Statement` captures an atomic fact—e.g. "Alice studies."— while the four connectives build larger formulas: *negation*, *conjunction*, *implication*, and *inclusive disjunction*. Each connective is implemented as a dedicated class whose method `.nl()` randomly selects a surface template from `expressions.json`. Table 11 summarises the five constructs, their formal notation, and representative English renderings.

Lexicalization. When generating a sample, the pipeline first creates `Statement` objects for the chosen entities, then composes them with the connectives above. For example, calling `Negation(S).nl()` yields a randomly chosen negated template such as *"The claim that S is false."*; calling `Conditional(P,Q).nl()` may return *"Provided that P, we know that Q."*. This template sampling, combined with optional adverb or negator insertion, gives LogicTree a high level of lexical diversity while preserving formal truth values.

B Related Work

In this section, we review prior work related to our problem setting, including logical reasoning datasets (Section B.1) and reasoning-improvement methods (Section B.2).

Algorithm 1 DRER: **D**ynamic **R**easoning **E**fficiency **R**eward.

Require: Prompts $P = \{q_b\}_{b=1}^B$, ground-truth answers $Y^\star = \{a_b^\star\}_{b=1}^B$,
  1: policy π_θ, rule reward $R_{\text{rule}}(\cdot)$, reasoning weight λ_q,
  2: bucket IDs $\{d_b\}_{b=1}^B$, bounds $\big(L_{\min}^{(d)}, L_{\max}^{(d)}\big)$, temperature τ
Ensure: Advantages $A \in \mathbb{R}^{B \times L}$
    (1) Build trajectories
  3: $C \leftarrow \pi_\theta(P, \text{mode} = cot)$ $\triangleright$ CoT trajectories
  4: **for** $b = 1$ **to** B **do**
  5:     $t_n[b] \leftarrow \text{NoCoTPrompt}(q_b) \,\|\, \text{FormatAnswer}(a_b^\star)$
  6:     Replace answer span in $C[b]$ with $a_b^\star \to t_c[b]$; record span $\mathcal{A}_b$
  7: **end for**
    (2) Reasoning-quality reward
  8: **for** $b = 1$ **to** B **do**
  9:     $\ell_c = \frac{1}{|\mathcal{A}_b|}\sum_{t \in \mathcal{A}_b} \log p_\theta(a_{b,t}^\star \mid t_c[b])$
 10:     $\ell_n = \frac{1}{|\mathcal{A}_b|}\sum_{t \in \mathcal{A}_b} \log p_\theta(a_{b,t}^\star \mid t_n[b])$
 11:     $R_q[b] \leftarrow \tanh(\ell_c - \ell_n)$
 12:     $R_{\text{seq}}[b] \leftarrow R_{\text{rule}}(C[b]) + \lambda_q R_q[b]$
 13:     Expand $R_{\text{seq}}[b]$ to token reward $r_{b,\cdot}$ on $C[b]$
 14: **end for**
    (3) Group-wise normalisation
 15: **for all** prompt group g **do**
 16:     $\mu_g \leftarrow \text{mean}(r_{m,\cdot})$, $\sigma_g \leftarrow \text{std}(r_{m,\cdot})$ $(m \in g)$
 17:     **for** $m \in g$ **do** $\triangleright$ raw advantage $\tilde{A}$
 18:        $\tilde{A}_{m,\cdot} \leftarrow \dfrac{r_{m,\cdot} - \mu_g}{\sigma_g + \varepsilon}$
 19:     **end for**
 20: **end for**
    (4) Dynamic-length attenuation
 21: **for** $b = 1$ **to** B **do**
 22:     $\ell_b \leftarrow \text{Length}(C[b])$, $d \leftarrow d_b$
 23:     $g_b \leftarrow \exp\!\Big(-\dfrac{\max\{0, \ L_{\min}^{(d)} - \ell_b, \ \ell_b - L_{\max}^{(d)}\}}{\tau}\Big)$
 24:     $A_{b,\cdot} \leftarrow g_b \cdot \tilde{A}_{b,\cdot}$
 25: **end for**
 26: **return** A

B.1 Related Datasets

Logical reasoning datasets can broadly be categorized into three types. The first type focuses on deductive reasoning. The second type is based on grid-based logic puzzles. The third category comprises datasets based on multi-hop or strategic question answering. These datasets assess language models' logical capabilities from various perspectives, including formal logic, multi-step planning, structural induction, and strategy analysis. In addition, there are general-purpose reasoning datasets that are also frequently used to evaluate LLMs' logical reasoning abilities.

B.1.1 Deductive Reasoning

ConTRoL, consisting of 8,325 pairs of expert-designed datasets, is a challenging segment-level NLI dataset to evaluate model's contextual reasoning capacity from police recruitment tests. Rule-Taker (Clark et al., 2020) is a benchmark dataset designed to test whether language models can logically reason about natural language rules and facts by determining whether the conclusions follow, do not follow, or are uncertain. LogiQA (Liu et al., 2020) is a benchmark of 8,678 civil service exam questions designed to evaluate models' reading comprehension and deductive reasoning across five logical types by requiring conclusion drawing from

textual premises. LogiQA2.0 (Liu et al., 2023) is the enhanced version of LogiQA (Liu et al., 2020), featuring improved translations, expert-verified annotations, and new NLI tasks, designed to evaluate logical reasoning and reading comprehension in MRC and NLI formats. FOLIO (Han et al., 2022) is a manually annotated dataset containing 1,430 logically complex natural language reasoning examples with first-order logic (FOL) annotations, designed to evaluate and benchmark the deductive reasoning and NL-FOL translation capabilities of Large Language models. PrOntoQA (Saparov and He, 2022) is a benchmark proposed in 2022 to evaluate LLMs' reasoning by generating question-answer pairs from first-order logic, revealing their struggles with multi-step proof planning despite valid individual steps. Compared with PrOntoQA (Saparov and He, 2022), PrOntoQA-OOD (Saparov et al., 2023) is designed to evaluate the general deductive reasoning abilities of LLMs by testing their ability to generalize to more complex, compositional proofs, particularly those that are out-of-distribution (OOD). JustLogic (Chen et al., 2025) a generated deductive reasoning benchmark designed to evaluate LLMs, featuring high complexity, being independent of prior knowledge, and conducting in-depth error analysis in terms of reasoning depth and argumentative form.

However, the existing logical reasoning datasets still have some limitations. Most datasets have fixed or limited reasoning depth and breadth, which limits their ability to conduct a comprehensive evaluation of complex multi-step reasoning models. Many datasets entwine semantic information with logic, which may lead the model to rely on semantic cues rather than pure logical reasoning.

Furthermore, the majority focus only on final answer correctness, lacking assessment of the intermediate reasoning process and overall explanation quality.

In contrast, the LogicTree dataset we proposed has significant advantages: it is programmed and dynamically constructed, allowing for flexible control over the depth, breadth, and difficulty of inference; It separates semantics from logic to precisely evaluate pure deductive reasoning; It introduces a new logical consistency metric across multiple logical equivalence problems to measure the model's grasp of the underlying logical structure.

B.1.2 Grid-Based Logic Puzzles

BoardgameQA(Kazemi et al., 2023) is a dataset designed to evaluate the reasoning ability of language models when dealing with contradictory information. GridPuzzle(Tyagi et al., 2024) is a dataset of grid-based logic puzzles designed to evaluate LLMs' structured, multi-step reasoning abilities through both final answers and detailed reasoning chains. The Knights and Knaves(Xie et al., 2025) dataset is a reasoning dataset designed to test logical deduction, where characters are either knights (truth-tellers) or knaves (liars), featuring controlled difficulty levels, procedural generation, and verifiability.

Existing datasets, such as GridPuzzle (Tyagi et al., 2024), Knights and Knaves (KK) (Xie et al., 2024) provide valuable reasoning benchmarks, but they all have limitations. For example, KK (Xie et al., 2024) entangles logical reasoning with semantic cues, taking the risk of rapid learning through keyword associations. Some logic puzzles focus on the final answer without verifying the intermediate steps, allowing the model to guess without sufficient reasoning.

On the contrary, LogicTree evaluates the final and intermediate steps and executes the complete reasoning chain. It also introduces a logical consistency rate among variants of the same logical form and uses semantic-logical unentanglement to ensure that the model relies on reasoning rather than superficial clues.

B.1.3 Multi-hop or Strategic Question Answering

HotpotQA (Yang et al., 2018) is a multi-hop question-answering dataset that requires reasoning across multiple documents and provides supporting facts to enhance the interpretability of the QA system. StrategyQA (Geva et al., 2021) is a benchmark dataset designed to evaluate implicit multi-step reasoning in LLMs across 15 domains and 13 strategies. SPAG (Cheng et al., 2024) is self-laying based adversarial language game dataset designed to enhance and evaluate the reasoning ability through a game involving indirect communication and strategic reasoning about hidden target words. LOGICGAME (Gui et al., 2024) is a benchmark designed to evaluate LLMs' ability to understand, execute, and plan based on predefined rules through diverse, verifiable game scenarios requiring multi-step logical reasoning. AutoLogi (Zhu et al., 2025) is a benchmark for open-ended logic puzzles with

controllable difficulty and program-based verification, designed to evaluate the reasoning ability of LLMs.

Compared with datasets such as HotpotQA (Yang et al., 2018), StrategyQA (Geva et al., 2021), they emphasize various forms of multi-step or strategic reasoning across natural language problems, but there are still obvious limitations: The reasoning strategies in existing datasets are often broad and empirical rather than based on formal logical deduction frameworks (for example, StrategyQA (Geva et al., 2021) relies on heuristic and empirical categories). Many datasets focus on language pattern matching or cross-document evidence aggregation rather than verifying the true formal reasoning process (for example, HotpotQA (Yang et al., 2018)). LogicTree, on the other hand, strictly adheres to classical mathematical logic, adopting clear and well-defined deduction rules, and does not rely on common sense knowledge, providing a pure logical reasoning environment.

B.1.4 General-Purpose Datasets

MMLU-Pro(Wang et al., 2024d) is an advanced benchmark of 12,000 expert-reviewed, 10-option questions across 14 disciplines, designed to better evaluate LLM performance with greater difficulty and reduced noise than the original MMLU (Hendrycks et al., 2021). However, it primarily evaluates broad knowledge and reasoning abilities rather than focusing on strong formal logical reasoning. Thus, it is not specifically designed to test models' capabilities in complex multi-step logical deduction.

B.2 Related Reasoning Methods

Recent research has explored improving LLM reasoning through critique-based or reward-model-based mechanisms. Below we summarize the most relevant directions and clarify how our approach differs.

B.2.1 Critique-Based Reasoning Approaches

Early self-improvement methods such as Self-Refine, Reflexion, and CRITIC require models to generate critique text to revise their own answers (Madaan et al., 2023; Shinn et al., 2023; Gou et al., 2023). Subsequent analyses report that such iterative critique loops can be unstable or rely on superficial linguistic artifacts rather than genuine logical reasoning (Huang et al., 2023; Valmeekam et al., 2023).

Other work focuses on supervised critique generation, such as Critique Fine-Tuning (CFT), which trains models to imitate human- or teacher-provided critique trajectories (Wang et al., 2025a,b). Similarly, Critique-Guided Distillation uses an external critic to score outputs and distills these scores into the model (Kapusuzoglu et al., 2025).

These methods rely on explicit critique traces or external critic models and supervise critique *content*. In contrast, DRER evaluates whether the reasoning chain itself improves the likelihood of the correct answer, without requiring critique generation or additional supervision.

B.2.2 Positioning DRER Relative to CFT and CRL

Critique Reinforcement Learning (CRL) incorporates critiques into RL by rewarding models for predicting correct True/False judgments about candidate solutions (Ruan et al., 2025). CRL therefore optimizes judgment correctness, whereas DRER optimizes the causal contribution of reasoning steps via CoT–NoCoT likelihood margins.

CFT-based methods supervise the generation or imitation of critique traces (Wang et al., 2025a,b), while self-reflection methods rely on iterative critique production (Madaan et al., 2023; Shinn et al., 2023). DRER differs in that it introduces a counterfactual, gold-grounded reward that directly measures the usefulness of reasoning steps, without learning to critique or to judge solutions.

B.2.3 Process-Level Reinforcement Learning for Reasoning

Another line of work improves reasoning through reinforcement learning that directly optimizes model behavior on reasoning tasks without relying on critique generation. Early RLHF-style approaches focus on outcome rewards (Schulman et al., 2017b) but do not supervise intermediate steps.

More recently, process-level RL methods such as GRPO and DAPO (Shao et al., 2024; Yu et al., 2025) use step-dependent rewards or decomposition strategies to encourage more stable reasoning trajectories. RLVR-style methods further incorporate structured or rule-based verification to provide process supervision (Wen et al., 2025). These approaches demonstrate that reinforcing intermediate reasoning behaviors can improve both accuracy and consistency.

DRER shares the goal of process-level supervision but differs fundamentally in how reasoning quality is evaluated: instead of using rule-based scoring or explicit correctness checks, DRER introduces a counterfactual, likelihood-based reward that measures whether the CoT reasoning trajectory increases model support for the correct answer. This avoids the need for handcrafted rules or verifiers while still providing a process-level training signal.

B.2.4 Reward-Model-Based Reasoning

Another family of methods trains reward models to evaluate reasoning steps or final answers (Wang et al., 2024c; Luo et al., 2024b). These systems can improve reasoning quality but require substantial labeled comparisons or step-by-step critiques. In contrast, DRER does not require a separate reward model; instead, it uses a counterfactual log-likelihood difference derived directly from the model's own outputs, providing a lighter-weight and verifiable training signal.

B.2.5 Overall Methodological Positioning

Critique-based approaches supervise critique production or correctness, while reward-modeling approaches train external evaluators of reasoning quality. Process-oriented RL methods, such as RLVR-style training, supervise only the final answer.

DRER occupies a distinct space: it introduces a counterfactual, gold-grounded reward that measures whether the reasoning chain genuinely increases support for the correct answer. Thus, DRER complements rather than overlaps with critique-based or reward-modeling paradigms.

C Prompt Templates

Tables 8 and 9 list the exact prompts used in our experiments: a *Chain-of-Thought (CoT)* version that elicits step-by-step reasoning, and a *No-CoT* variant that asks for the final answer only. Curly-braced placeholders are replaced at runtime (`{paragraph}`, `{current_question}`, `{num_q}`). The two prompts share identical task instructions, so performance differences isolate the effect of showing or hiding the reasoning chain.

D Training details

D.1 Training setting

Table 12 records important training parameters. Experiments are conducted on $4 \times$H20 (80G) GPUs with CUDA 12.0, PyTorch 2.6.0, transformers 4.47.1. The Main Experiment phase (DAPO+DRER) trains for 400 training steps and takes approximately 50 hours. Training is carried out with a learning rate of 3×10^{-7}, a maximum response length of 4096 tokens, the batch size is 16 and 16 responses per prompt. For GRPO, the KL divergence coefficient is set to 0.001. In the DRER framework, we set $\lambda_q = 1$ and $\tau = 8$.

As shown in Equation 8, there are two parts of reward in DRER framework. Our Reasoning Quality Reward R_q is range from $[-\lambda, \lambda]$ to measure whether those CoT tokens help to choose the correct answer. The general task reward R_{task} depends on the specific training data, usually to verify the model's answer and format correctness. In our experiment, hyperparameter λ is set to 1, the total task reward is computed as:

$$R_{\text{task}} = S_{\text{format}} + S_{\text{answer}}$$

where the format score (S_{format}) evaluates whether the model's response adheres to the required output structure:

$$S_{\text{format}} = \begin{cases} 1, & \text{if format is correct} \\ -1, & \text{if format is incorrect} \end{cases}$$

And the answer score (S_{answer}) evaluates the correctness of the response content against the ground truth.

$$S_{\text{answer}} = \begin{cases} 2, & \text{answer fully correct} \\ -1.5, & \text{answer partial mismatch} \\ -2, & \text{not parseable or missing} \end{cases}$$

D.2 Training Dynamics

E Supplementary Experiments

E.1 Experiment A: GPT-5.1–Based CoT Quality Scoring

To further validate whether our Reward for Quality Reasoning (RQR) corresponds to genuine reasoning quality, we conduct an additional external evaluation using GPT-5.1.

We randomly sample 4000 chain-of-thought (CoT) trajectories from the evaluation set, including outputs from the base model, the DAPO-only model, and the DAPO+DRER model. GPT-5.1 is instructed to evaluate each trajectory in a step-wise manner. For every reasoning step, GPT-5.1 assigns

Figure 4: Reasoning quality reward on the LogicTree during post-training with DRER.

Figure 5: Training dynamic of the DAPO baseline with the DRER framework over 400 steps.

binary judgments along three dimensions: *correctness*, *coherence*, and *necessity*. The detailed evaluation rubric and prompt are provided in Table 25, and a representative annotated example is shown in Table 24. For each trajectory, we aggregate the step-wise labels into a single CoT quality score, bucket the examples by this CoT Score, and compute the mean RQR within each bucket to examine how RQR correlates with externally assessed reasoning quality.

For a CoT consisting of T steps, we define:

$$\text{Correctness} = \frac{1}{T} \sum_{t=1}^{T} \text{correctness}_t,$$

$$\text{Necessity} = \frac{1}{T} \sum_{t=1}^{T} \text{necessity}_t. \tag{12}$$

To penalize chains whose logical flow breaks early, let

$$k = \min\{t \mid \text{coherence}_t = 0\}$$

be the index of the first coherence error. Coherence is defined as follows, where $\alpha = 0.7$.:

$$\text{Coherence} = \begin{cases} 1, & \text{if coherence}_t = 1 \; \forall t \\ \alpha^{(T-k)}, & \text{otherwise} \end{cases}$$

We combine the three dimensions into a single CoT quality score: CoT Score $= 0.5 \cdot$ Correctness $+ 0.3 \cdot$ Coherence $+ 0.2 \cdot$ Necessity.

We bucket all examples by CoT Score and compute the mean RQR within each bucket.

The results reveal a clear and consistent trend: CoT trajectories with higher GPT-5.1 quality scores obtain substantially higher RQR values, whereas trajectories receiving low scores consistently yield

Figure 6: Comparison of response lengths over training steps between DAPO and DAPO+DRER. The integration of DRER leads to a reduction in response length, indicating enhanced efficiency with concise output.

Figure 7: Comparison of response lengths over training steps between GRPO and GRPO+DRER. The integration of DRER leads to a reduction in response length, indicating enhanced efficiency with concise output.

lower RQR. After DRER training, both the distribution of GPT-5.1 CoT scores and the corresponding RQR values shift markedly toward higher-quality regions.

These observations indicate that RQR assigns larger rewards to more logically coherent and effective reasoning chains, demonstrating that the learned reward signal aligns with genuine reasoning quality rather than surface-level patterns.

Across both the DAPO-only and DAPO+DRER models, we observe that:

- Higher CoT Score consistently corresponds to higher RQR;

- DRER training increases RQR across all buckets, with the largest improvements in the high-quality CoT region.

Overall, these findings confirm that RQR is well aligned with GPT-5.1's step-wise evaluation of reasoning, capturing meaningful aspects of logical correctness and procedural validity.

E.2 Experiment B: CoT Disturbance Test

To assess whether the Reward for Quality Reasoning (RQR) is sensitive to the structural and semantic validity of reasoning trajectories, we conduct a controlled CoT–perturbation study on 4,000 randomly sampled questions from our evaluation set.

For each question, we construct three variants of the chain-of-thought (CoT):

- **Original CoT**: the unmodified reasoning tra-

Figure 8: Comparison of CoT score distributions and corresponding mean RQR values across three training settings: Base model, DAPO-only, and DAPO+DRER. Bars represent the frequency of samples within each CoT score bucket, while the line plots show the mean RQR computed over the same buckets. DRER produces a clear shift toward higher-quality CoT trajectories and consistently higher RQR across all buckets.

jectory generated by the model.

- **Shuffled CoT**: a sentence-level random permutation of the same trajectory, disrupting logical order while preserving content.

- **Cross-question CoT**: a CoT drawn from a different evaluation question, approximately length-matched but semantically unrelated.

For each variant, we compute the RQR defined in Eq. (7). Table 13 reports the mean RQR, standard deviation, and proportion of positive RQR values.

Summary of Results. These results indicate that RQR exhibits clear sensitivity to both the semantic relevance and structural coherence of the reasoning chain, rather than displaying a simple preference for the presence of CoT tokens. The significant differences across perturbation types suggest that RQR captures the degree to which intermediate reasoning steps either support or hinder the correct answer probability, reflecting their contribution in the problem-solving process.

E.3 Experiment C: Analysis of the effects of CoT

E.4 Experiment D: LogicTree Evaluation

This section lists full evaluation on LogicTree as logic benchmark.

Table 18 exhibits the full evaluation data of Accuracy on LogicTree benchmark across various reasoning depths.

Table 19 presents the complete evaluation data of Consistency Ratio on LogicTree benchmark.

E.5 Experiment E: Multi-Seed Robustness

Figure 9 plots the complete evaluation data of $F\beta$-Score, which provides a balanced metric to compare the comprehensive performance across those LLMs.

Figure 10 shows the distribution of these deductive logical keywords in LLM responses.

To examine whether models explicitly invoke deductive reasoning rules during inference, we analyzed the word frequencies of seven canonical paradigm names (e.g., *Modus Ponens*, *Modus Tollens*, *Disjunction Elimination*) in model responses across all reasoning depths.

The results indicate a clear drop in explicit paradigm mentions as logical complexity grows, suggesting that models increasingly rely on implicit or heuristic reasoning at higher depths rather than systematically applying named rules. Moreover, there are notable disparities across paradigms. For example, DeepSeek-R1 responses most frequently reference *Modus Tollens*, while *Disjunction Elimination* appears substantially less often. This disparity may stem from either the inherent complexity of the latter rule or inadequate exposure during pre-training. Our framework (DAPO+DRER) shows improved rule identification capacity with increasing response length and logical complexity, indicating that the fine-grained reward signal encourages more explicit and structured reasoning behaviour.

Figure 11 compares the reasoning token efficiency between DeepSeek-R1 and our model.

Figure 12 compares the output distribution between models trained with DAPO and

Figure 9: $F\beta$-Score, Answer Rate and Precision metrics Comparison across various models.

DAPO+DRER respectively. The DAPO+DRER model demonstrates significantly higher confidence in correct answers, as shown by a strong concentration of predictions on the fully correct label set ([true, true, true]). In contrast, the baseline DAPO model produces more scattered outputs, indicating lower certainty. This highlights the effectiveness of DRER in combination with CoT reasoning for improving answer consistency and correctness.

Figure 13 compares the output distribution between base model and variant trained with DAPO+DRER. The DAPO+DRER model produces highly concentrated predictions on the fully correct label ([true, true, true]), indicating strong confidence and consistency. In contrast, Qwen2.5-7B-Instruct-1M predictions are widely dispersed across incorrect and partially correct categories, reflecting lower answer certainty. This highlights the effectiveness of DRER combined with CoT in guiding the model toward accurate and confident output.

Table 21 reports the average evaluation results on 15 graduate students who had received systematic training in mathematical logic or introductory logic courses. The results show that for problems of simple to moderate difficulty (reasoning depth 1–5), human participants consistently identified the implicit logical rules and produced correct answers. For deeper reasoning levels (6–8), although the problems remain theoretically solvable, the context length can exceed 1k tokens, making manual step-by-step deduction extremely tedious and error-prone. For this reason, depth-6–8 questions were excluded from human testing.

Table 22 shows the exact model names and snapshots evaluated in our experiments.

F   Limitations

Despite the empirical gains achieved by DRER and LogicTree, several limitations remain:

- **Logic coverage.** LogicTree is limited to the deductive reasoning paradigm, while more diverse forms such as analogical reasoning, inductive reasoning, or traceable reasoning have not yet been evaluated.
- **Model scale and cost.** All experiments use Qwen-2.5-7B-Instruct-1M as backbone. The memory and latency overhead of token-level rewards on 70 B-scale or MoE models is unknown and may be prohibitive.
- **Evaluation bias.** Training and evaluation rely on an automatic logic verifier and confidence scores; no human preference or chain-quality annotation is included, which may overlook subjective aspects of reasoning quality.
- **Synthetic corpus and social bias.** LogicTree sentences are synthetically generated; potential social biases or misuse risks in real-world deployments have not been systematically analysed.

In future work we plan to extend DRER to higher-order logic, explore low-cost reward approximations, and incorporate human evaluation and bias auditing to mitigate these limitations.

G Broader Impact

Our work aims to align large language models with formal logical principles, potentially improving the reliability and interpretability of machine reasoning. By releasing the LOGICTREE dataset and DRER code under a permissive licence, we enable researchers and practitioners to build verifiable agents for education, scientific discovery, and safety- critical auditing, where transparent deductive chains are preferable to opaque heuristics.

G.1 Positive societal outcomes.

A reasoning-aligned model can serve as a didactic tutor in introductory logic courses, assist engineers in detecting faulty assumptions in software specifications, and support legal or medical professionals by highlighting which premises lead to a conclusion rather than merely producing an answer. The synthetic nature of LOGICTREE limits exposure to personal data and reduces the risk of privacy leaks.

G.2 Potential risks.

More persuasive and logically consistent outputs could be weaponised for misinformation or overly authoritative automation. Over-reliance on synthetic benchmarks might also hide biases that appear in real-world discourse. Furthermore, token-level reward signals expose fine-grained model behaviour, which could be exploited to reverse-engineer proprietary system prompts.

G.3 Mitigations.

We distribute our resources with an explicit no-malicious-use clause, encourage downstream users to apply bias and misinformation audits, and recommend human oversight for high-stakes deployment. Future work will extend DRER to real-world corpora and incorporate human preference feedback, allowing broader yet safer adoption of reasoning-aligned reinforcement learning.

H Case Study: Chain-of-Thought Quality

To complement the quantitative evaluation, we present a case study based on the example shown in Table 23, which compares reasoning traces produced by different models on the same LogicTree instance. This case study highlights how DRER improves both the clarity and efficiency of chain-of-thought (CoT) reasoning.

H.1 dapo+drer (ours)

Driven by DRER's *token-level reward* and *dynamic-length mask*, the trace is both concise and transparent: six orderly steps map directly onto the formal pipeline *identify rule → resolve disjunction → propagate truth*. Expressions such as "apply transitivity" signal an explicit shift toward symbolic reasoning, the behaviour DRER is designed to promote. At roughly ∼70 tokens—far shorter than the 100+ tokens typical of vanilla DAPO—the chain remains fully verifiable, demonstrating DRER's combined gains in *effectiveness* and *efficiency*.

H.2 o4mini

Although it yields the correct answer, steps 2–4 compress several entailments into a single sentence and omit rule names, reducing transparency. With a length of about ∼40 tokens, it illustrates the "shallow-but-correct" pattern observed in §4.2.

H.3 Qwen2.5-7B-Instruct

This trace shows the greatest *length drift*: more than 110 tokens, many of them descriptive filler unrelated to logic, matching the "decorative-token inflation" failure mode in our diagnostics. Despite some correct premise restatement, the model ultimately outputs Unknown, confirming that verbosity does not equal confidence.

H.4 DeepSeek-R1

Provides only a meta-level remark ("break down each conditional") before jumping to the answer, leaving the derivation invisible; such hidden reasoning yields the lowest Consistency Ratio in our evaluation across paraphrastic variants.

H.5 Summary.

dapo+drer offers the clearest, rule-grounded, and length-controlled chain of thought; **o4mini** is concise but omits warrants and lacks length regularisation; **Qwen2.5-7B-Instruct** is verbose yet uncertain; and **DeepSeek-R1** lacks an explicit chain. The contrast underscores DRER's targeted improvements in symbolic clarity, response economy, and process–outcome alignment.

I LLM Usage

Large Language Models (LLMs) were used to aid in the writing and polishing of the manuscript.

Specifically, we used an LLM to assist in refining the language, improving readability, and ensuring clarity in various sections of the paper. The model helped with tasks such as sentence rephrasing, grammar checking, and enhancing the overall flow of the text.

It is important to note that the LLM was not involved in the ideation, research methodology, or experimental design. All research concepts, ideas, and analyses were developed and conducted by the authors. The contributions of the LLM were solely focused on improving the linguistic quality of the paper, with no involvement in the scientific content or data analysis.

The authors take full responsibility for the content of the manuscript, including any text generated or polished by the LLM. We have ensured that the LLM-generated text adheres to ethical guidelines and does not contribute to plagiarism or scientific misconduct.

Paragraph:
When the notion that 'if the statement that states the worms also eat the food scraps and worm bin bedding is false, then the statement 'emergent wetland vegetation is rooted in soil that is under the water for most of the time' can be considered false' is untrue is true, it follows that hydrangeas need minimal care in well-drained, fertile soil, and are shade lovers.One may reasonably assume that if the notion that 'if the statement that states the worms also eat the food scraps and worm bin bedding is false, then the statement 'emergent wetland vegetation is rooted in soil that is under the water for most of the time' can be considered false' is untrue, then those that suggest hydrangeas need minimal care in well-drained, fertile soil, and are shade lovers are wrong.Assuming sometimes, cancer cells left behind after treatment eventually form new tumors, we know that if either eggs from common ducks require about 28 days to hatch or the island was originally inhabited by Ligures Ilvates, who gave it the ancient name Ilva, then if the statement that states the worms also eat the food scraps and worm bin bedding is false, then emergent wetland vegetation is rooted in soil that is under the water for most of the time.The statement that states sometimes, cancer cells left behind after treatment eventually form new tumors is right.Whenever the claim that either eggs from common ducks require about 28 days to hatch or the island was originally inhabited by Ligures Ilvates, who gave it the ancient name Ilva is false is true, the following statement is also true: the bowl acts as a carb hole.Whenever the claim that either eggs from common ducks require about 28 days to hatch or the island was originally inhabited by Ligures Ilvates, who gave it the ancient name Ilva is false is true, the following statement is also true: the statement 'the bowl acts as a carb hole' can be considered false.

Question:
The statement 'the worms also eat the food scraps and worm bin bedding' can be considered true. It is a common misconception that if the statement that states the worms also eat the food scraps and worm bin bedding is false, then emergent wetland vegetation is rooted in soil that is under the water for most of the time.

Model Response:
1. Analyze the logical structure of the given statements.
2. Identify the conditions and implications in each statement.
3. Determine the truth value of the given statements and how they relate to each other.
4. Check the consistency of the statements with the provided premises.
5. Deduce the implications of the given statements on the conclusion.
6. Evaluate the final conclusion based on the logical consistency and the given premises.
</think>
<answer>[True, False]</answer>

Solution:
True
False

Table 7: Model Response of logictree.

COT prompt

System Input:
<|im_start|>system
You are a helpful assistant. The assistant first thinks step by step about the reasoning process in the mind and then provides the user with the answer.
The reasoning process and answer are enclosed within <think> ... </think> and <answer> ... </answer> tags, respectively, i.e.
<think> Write the reasoning process for the given paragraph here </think>
<answer> Fill in the final answer list for {num_q} question(s) here: True, False or Unknown. Like this: [True, False...] </answer>
You must choose one of the following answers:
– TRUE: if the premises entail the statement
– FALSE: if the premises contradict the statement
– UNKNOWN: if you cannot determine the truth value of the statement from the premises
You will be given a paragraph of logical premises and a statement. Perform logical reasoning **strictly based on the premises** using propositional logic.
Assume all premises are true. Do not rely on prior world knowledge.
<|im_end|>

User Input:
<|im_start|>user
Paragraph: {paragraph}
{current_question}
<|im_end|> <|im_start|>assistant <think>

Variable meanings:
{num_q}: Number of questions in the current prompt.
{paragraph}: The paragraph containing the logical premises.
{current_question}: The specific statement whose truth value is to be evaluated.

Table 8: Full Chain-of-Thought (CoT) Prompt Template Used for DRER Training and Evaluation.

Table 9: Full No-CoT Prompt Template used for DRER training and evaluation.

Paradigm	Formal Schema	Surface Realisation
Modus Ponens	$(p \to q) \land p \Rightarrow q$	If Alice studies, she will pass. Alice studies. Therefore, she will pass.
Modus Tollens	$(p \to q) \land \neg q \Rightarrow \neg p$	If it rains, the road is wet. The road is not wet. Thus, it did not rain.
Hypothetical Syllogism	$(p \to q) \land (q \to r) \Rightarrow (p \to r)$	If A wins, B celebrates. If B celebrates, C is happy. Hence, if A wins then C is happy.
Disjunctive Syllogism	$(p \lor q) \land \neg p \Rightarrow q$	Either today is Monday or Tuesday. Today is not Monday. Therefore, today is Tuesday.
Reductio ad Absurdum	$(p \to q) \land (p \to \neg q) \Rightarrow \neg p$	Assume the number is both even and odd. This leads to a contradiction. Thus, the number is not both even and odd.
Constructive Dilemma	$(p \to q) \land (r \to s) \land (p \lor r) \Rightarrow (q \lor s)$	If it rains, we stay in; if it is sunny, we picnic. Either it rains or it is sunny. Hence, we either stay in or picnic.
Disjunction Elimination	$(p \lor q) \land (p \to s) \land (q \to s) \Rightarrow s$	Either I study or I work. If I study, I will learn. If I work, I will learn. Thus, I will learn.

Table 10: Seven deductive paradigms that serve as the atomic reasoning units in LOGICTREE.

Construct	Logical Form	Example Surface Realisation (EN)
Statement (atomic)	p	*Alice studies.*
Negation	$\neg p$	*It is **not** true that Alice studies.*
Conjunction	$P \wedge q$	*Alice studies **and** Bob plays chess.*
Implication (Conditional)	$P \rightarrow q$	***If** it rains, **then** the road becomes wet.*
Inclusive Disjunction	$P \vee q$	***Either** today is Monday **or** Tuesday.*

Table 11: Primitive and compound proposition types used in LOGICTREE.

Algorithm	Train Batch Size	Rollout N	KL Coef	Max Response Len
GRPO	16	16	0.001	4096
DAPO	16	16	–	4096

Table 12: Important Training Parameters.

CoT Variant	Mean RQR ↑	Std RQR	% RQR > 0 ↑
Original CoT	0.29	0.42	73%
Shuffled CoT	0.08	0.31	41%
Cross-question CoT	-0.34	0.33	7%

Table 13: Experiment B: RQR under different CoT perturbations on 2,000 randomly sampled evaluation questions. The ordering Original $>$ Shuffled $>$ Cross demonstrates that RQR aligns with reasoning quality and task relevance.

Original ↓ / With CoT →	Wrong (W)	Correct (R)
Wrong (W)	-4.32	2.46
Correct (R)	-5.00	-0.47

Table 14: Average $\ell_{\text{CoT}} - \ell_{\text{NoCoT}}$ by answer transition in GSM8K.

Original ↓ / With CoT →	Wrong (W)	Correct (R)
Wrong (W)	-1.13	1.81
Correct (R)	-3.79	-4.76

Table 15: Average $\ell_{\text{CoT}} - \ell_{\text{NoCoT}}$ by answer transition in LogicTree.

Group by $\Delta\ell$ sign	#Instances	Mean $\Delta\ell$	$p(\text{W}\rightarrow\text{R})$	$p(\text{R}\rightarrow\text{W})$
$\Delta\ell > 0$ (CoT favored)	140	+2.20	0.74	0.02
$\Delta\ell < 0$ (NoCoT favored)	360	-2.60	0.02	0.24

Table 16: Answer-transition proportions conditioned on the sign of $\Delta\ell = \ell_{\text{CoT}} - \ell_{\text{NoCoT}}$ on GSM8K (N=500). $p(\text{W}\rightarrow\text{R})$ is the fix rate; $p(\text{R}\rightarrow\text{W})$ is the break rate.

Group by $\Delta\ell$ sign	#Instances	Mean $\Delta\ell$	$p(\text{W}\rightarrow\text{R})$	$p(\text{R}\rightarrow\text{W})$
$\Delta\ell > 0$ (CoT favored)	120	+1.70	0.67	0.04
$\Delta\ell < 0$ (NoCoT favored)	380	-3.90	0.05	0.23

Table 17: Answer-transition proportions conditioned on the sign of $\Delta\ell = \ell_{\text{CoT}} - \ell_{\text{NoCoT}}$ on LogicTree (N=500). $p(\text{W}\rightarrow\text{R})$ is the fix rate; $p(\text{R}\rightarrow\text{W})$ is the break rate.

Model	1	2	3	4	5	6	7	8	Avg.
Qwen3-235B-A22B	**0.96**	**0.83**	0.66	**0.71**	0.46	0.32	0.25	0.07	0.53
Deepseek-R1	0.85	0.76	0.61	0.47	0.36	0.18	0.19	0.07	0.44
Claude-3.7-Sonnet	0.76	0.67	0.21	0.10	0.07	0.02	0.02	0.00	0.23
Qwen3-8B	0.86	0.83	0.49	0.44	0.32	0.11	0.14	0.08	0.41
GPT-o4-mini	0.74	0.64	0.25	0.20	0.10	0.06	0.05	0.02	0.26
GPT-o3-mini	0.66	0.56	0.07	0.07	0.03	0.02	0.01	0.00	0.18
Qwen3-4B	0.74	0.74	0.39	0.29	0.29	0.06	0.09	0.04	0.33
Gemini-2.5-Flash-Preview	0.86	0.64	0.41	0.31	0.24	0.11	0.06	0.00	0.33
GPT-4o	0.63	0.60	0.28	0.13	0.13	0.00	0.00	0.00	0.22
Phi-4-14B	0.72	0.67	0.31	0.27	0.19	0.04	0.01	0.01	0.28
Gemma-3-27B	0.65	0.41	0.15	0.04	0.00	0.00	0.00	0.00	0.16
Deepseek-v3	0.39	0.24	0.05	0.06	0.00	0.00	0.00	0.00	0.09
GPT-4o-mini	0.44	0.24	0.27	0.11	0.12	0.02	0.02	0.01	0.15
Qwen2.5-7B-Instruct-1M	0.36	0.29	0.15	0.12	0.08	0.01	0.01	0.00	0.13
GRPO	0.81	0.71	0.58	0.42	0.45	0.20	0.20	0.11	0.45
GRPO+DRER	0.87	0.75	0.69	0.54	0.61	0.35	0.27	0.22	0.54
DAPO	0.88	0.73	0.66	0.47	0.60	0.36	0.23	0.20	0.52
DAPO+DRER (Ours)	0.90	**0.83**	**0.76**	0.59	**0.67**	**0.45**	**0.31**	**0.31**	**0.60**$^{\uparrow 0.47}$

Table 18: Comparison of LRM's(above) and LLM's(below) accuracy on LogicTree across various logical depth.

Model	1	2	3	4	5	6	7	8	Avg.
Qwen3-235B-A22B	**0.90**	0.65	0.30	**0.50**	0.15	0.00	0.05	0.00	0.32
Deepseek-R1	0.70	0.55	0.20	0.15	0.10	0.00	0.05	0.00	0.22
Claude-3.7-Sonnet	0.65	0.35	0.00	0.00	0.00	0.00	0.00	0.00	0.12
Qwen3-8B	0.65	**0.70**	0.05	0.05	0.05	0.00	0.00	0.00	0.19
GPT-o4-mini	0.50	0.35	0.00	0.05	0.00	0.00	0.00	0.00	0.11
GPT-o3-mini	0.45	0.30	0.00	0.00	0.00	0.00	0.00	0.00	0.09
Qwen3-4B	0.40	0.30	0.05	0.05	0.00	0.00	0.00	0.00	0.10
Gemini-2.5-Flash-Preview	0.75	0.50	0.15	0.05	0.00	0.00	0.00	0.00	0.18
GPT-4o	0.40	0.35	0.00	0.05	0.00	0.00	0.00	0.00	0.10
Phi-4-14	0.35	0.35	0.05	0.05	0.00	0.00	0.00	0.00	0.10
Gemma-3-27B	0.25	0.20	0.00	0.00	0.00	0.00	0.00	0.00	0.06
Deepseek-v3	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02
GPT-4o-mini	0.10	0.10	0.00	0.00	0.00	0.00	0.00	0.00	0.03
Qwen2.5-7B-Instruct-1M	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01
GRPO	0.55	0.50	0.40	0.25	0.45	0.20	**0.15**	0.00	0.29
GRPO+DRER	0.65	0.50	0.25	0.25	0.25	0.10	0.00	0.00	0.25
DAPO	0.65	0.45	0.45	0.20	**0.50**	0.10	0.05	**0.10**	0.31
DAPO+DRER (Ours)	0.70	**0.70**	**0.60**	0.35	**0.50**	**0.35**	0.00	**0.10**	**0.41**$^{\uparrow 0.4}$

Table 19: Comparison of Consistency Ratio on LogicTree across various logical depth.

Training Data	Method	AIME24	GPQA	LogicTree
LogicTree	GRPO	13.1 ± 0.25	27.1 ± 0.36	45.1 ± 1.21
LogicTree	GRPO+DRER	13.4 ± 0.16	29.0 ± 0.49	54.2 ± 0.64
LogicTree	DAPO	13.9 ± 0.36	33.5 ± 0.49	52.4 ± 1.00
LogicTree	DAPO+DRER	16.5 ± 0.25	35.2 ± 0.36	60.0 ± 0.81
General Reasoning	GRPO	14.8 ± 0.49	29.9 ± 0.64	11.0 ± 0.25
General Reasoning	GRPO+DRER	17.2 ± 0.36	35.4 ± 0.49	14.1 ± 0.36
General Reasoning	DAPO	14.5 ± 0.64	32.3 ± 0.81	13.0 ± 0.49
General Reasoning	DAPO+DRER	18.3 ± 0.49	38.6 ± 0.64	12.1 ± 0.36

Table 20: Multi-seed results over 5 random seeds on representative method/data settings, reported as mean $\pm$ std.

Figure 10: Word frequencies of seven deductive reasoning terms explicitly mentioned in LLMs response DRER.

Model	1	2	3	4	5	6	7	8	Avg.
Qwen3-235B-A22B	0.96	0.83	0.66	0.71	0.46	0.32	0.25	0.07	0.53
Deepseek-R1	0.85	0.76	0.61	0.47	0.36	0.18	0.19	0.07	0.44
Claude-3.7-Sonnet	0.76	0.67	0.21	0.10	0.07	0.02	0.02	0.00	0.23
GPT-o4-mini	0.74	0.64	0.25	0.20	0.10	0.06	0.05	0.02	0.26
DAPO+DRER (Ours)	0.90	0.83	0.76	0.59	0.67	0.45	0.31	0.31	0.60
Human	1.00	1.00	0.98	0.93	0.85	-	-	-	-

Table 21: Comparison of LLM and Human accuracy on LogicTree across various logical depth.

Figure 11: Comparison of DeepSeek-R1's and our model's accuracy and average response token on LogicTree.

Figure 12: Prediction distribution comparison between DAPO and DAPO+DRER under Chain-of-Thought (CoT) prompting.

Figure 13: Prediction distribution comparison between our model (DAPO+DRER) and Qwen2.5-7B-Instruct-1M under Chain-of-Thought (CoT) prompting.

Model	Organization	Size	Notes	Source
DeepSeek-R1	DeepSeek	671B	MoE	`deepseek-ai/DeepSeek-R1`
DeepSeek-V3	DeepSeek	671B	MoE	`deepseek-ai/DeepSeek-V3`
Claude 3.7 Sonnet	Anthropic	–		`claude-3-7-sonnet-20250219`
Gemini 2.0 Flash Thinking Preview	Google	–		`gemini-2.5-flash-preview-04-17`
Gemma-3-27B	Google	27B		`google/gemma-3-27b-it`
Qwen3-235B-A22B	Alibaba	235B	MoE	`qwen3-235b-a22b`
Qwen3-30B-A3B	Alibaba	30B	MoE	`qwen3-30b-a3b`
Qwe3-8B	Alibaba	–		`qwen3-8b`
Qwen3-4B	Alibaba	–		`qwen3-4b`
Qwen2.5-7B-Instruct-1M	Alibaba	–	MoE	`qwen2.5-7b-instruct-1m`
Phi-4-14B	Microsoft	14B		`microsoft/phi-4`
GPT-o4-mini	OpenAI	–		`o4-mini-2025-04-16`
GPT-o3	OpenAI	–		`o3-mini-2025-01-31`
GPT-4o-mini	OpenAI	–		`gpt-4o-mini-2024-07-18`
GPT-4o	OpenAI	–		`gpt-4o-2024-11-20`

Table 22: Details of the organization and model source (model version for proprietary models, and Huggingface model name for open-source models) for the LLMs evaluated in LogicTree.

Four-model CoT Comparison

Question

It is a common misconception that if *ribbons relate post : How to sew trims*, then *titanium dioxide and zinc oxide also functioned in this fashion.*

dapo+drer

Chain-of-Thought

1. Analyze the logical structure of the premises.
2. Identify conditional statements and their parts.
3. Resolve the disjunction via the invertebrate–coral premise.
4. Propagate truth to the olive-oil statement.
5. Apply transitivity to obtain *ribbons* $\rightarrow$ TiO$_2$/ZnO.
6. Compare with the question's claim.

Answer: **False**

Qwen2.5-7B-Instruct-1M

Chain-of-Thought

1. Let's analyze step by step.
2. Coral reefs need light and thus occur only in shallow waters.
3. Olive oil is heat-stable.
4. If ribbons $\rightarrow$ TiO$_2$/ZnO.
5. "Anus on top" is false $\Rightarrow$ coral-reef statement true.
6. No evidence of misconception.
7. Hence information is insufficient.

Answer: **Unknown**

o4mini

Chain-of-Thought

1. "Anus on top" is false.
2. Therefore coral-reef-light is true.
3. Thus olive-oil statement is true.
4. Hence conditional *ribbons* $\rightarrow$ TiO$_2$/ZnO is true.
5. The question claims this conditional is a misconception.
6. Contradiction $\Rightarrow$ question is false.

Answer: **False**

deepseekr1

Chain-of-Thought

1. I need to analyze consistency; I will break down each conditional and test with the premises.

Answer: **False**

Table 23: Four-model CoT Comparison (Prompt-style)

CoT on AIME (DAPO)

Question

Let $x, y,$ and z be positive real numbers that satisfy the following system of equations:

$$\log_2\left(\frac{x}{yz}\right) = \frac{1}{2}, \quad \log_2\left(\frac{y}{xz}\right) = \frac{1}{3}, \quad \log_2\left(\frac{z}{xy}\right) = \frac{1}{4}.$$

Then the value of $\left|\log_2\left(x^4 y^3 z^2\right)\right|$ is $\frac{m}{n}$, where m and n are relatively prime positive integers. Find $m + n$.

DAPO

Given the system of equations:

$$\log_2\left(\frac{x}{yz}\right) = \frac{1}{2}, \qquad \log_2\left(\frac{y}{xz}\right) = \frac{1}{3}, \qquad \log_2\left(\frac{z}{xy}\right) = \frac{1}{4},$$

we rewrite each in exponential form:

$$\frac{x}{yz} = 2^{1/2}, \quad \frac{y}{xz} = 2^{1/3}, \quad \frac{z}{xy} = 2^{1/4}.$$

Multiplying all three equations:

$$\left(\frac{x}{yz}\right)\left(\frac{y}{xz}\right)\left(\frac{z}{xy}\right) = 2^{1/2+1/3+1/4},$$

and the left-hand side simplifies to

$$\frac{xyz}{x^2 y^2 z^2} = \frac{1}{xyz},$$

so

$$\frac{1}{xyz} = 2^{13/12} \quad \Rightarrow \quad xyz = 2^{-13/12}.$$

Let $\log_2 x = a$, $\log_2 y = b$, $\log_2 z = c$. Then

$$a + b + c = \log_2(xyz) = -\frac{13}{12}.$$

Using the original equations:

$$a - (b + c) = \frac{1}{2}, \qquad b - (a + c) = \frac{1}{3}, \qquad c - (a + b) = \frac{1}{4}.$$

However, the incorrect solution attempted to compute:

$$4a + 3b + 2c = 4\left(\frac{1}{2}\right) + 3\left(\frac{1}{3}\right) + 2\left(\frac{1}{4}\right) \qquad \text{Unsupported Equation}$$

$$= 2 + 1 + \frac{1}{2} = \frac{7}{2},$$

which assumes

$$a = \frac{1}{2}, \quad b = \frac{1}{3}, \quad c = \frac{1}{4}$$

Table 24: CoT Comparison (DAPO and DAPO+DRER)

Thus the final claim:
$$\left|\log_2(x^4y^3z^2)\right| = \frac{7}{2}$$
$$m + n = 9$$

Answer: **9** (×)

DAPO+DRER

To solve the given system of equations involving logarithms, we start by letting $a = \log_2 x$, $b = \log_2 y$, and $c = \log_2 z$.

The system becomes:
$$a - b - c = \frac{1}{2}, \qquad b - a - c = \frac{1}{3}, \qquad c - a - b = \frac{1}{4}.$$

Solving:
$$(a - b - c) + (b - a - c) = \frac{1}{2} + \frac{1}{3} \implies -2c = \frac{5}{6} \implies c = -\frac{5}{12}.$$

Substitute into the third equation:
$$-\frac{5}{12} - a - b = \frac{1}{4} \implies a + b = -\frac{2}{3}.$$

Substitute into the first equation:
$$a - b + \frac{5}{12} = \frac{1}{2} \implies a - b = \frac{1}{12}.$$

Solving the two-equation system:
$$a = -\frac{7}{24}, \qquad b = -\frac{3}{8}.$$

Thus:
$$c = -\frac{5}{12}.$$

Compute:
$$\log_2(x^4y^3z^2) = 4a + 3b + 2c = -\frac{25}{8}.$$

Since $\frac{m}{n} = \frac{25}{8}$, we have $m + n = 25 + 8 = 33$.

Answer: **33** (✓)

Table 24: CoT Comparison (DAPO and DAPO+DRER) (continued)

> **GPT-5.1 Prompt**
>
> You are an expert judge for mathematical and logical reasoning steps. You will be given:
>
> - A problem statement (`QUESTION`).
> - A full sequence of reasoning steps.
> - The current reasoning step to evaluate (`CURRENT_STEP`), which is step {t}.
>
> 1. **correctness**: whether the content inside this step is mathematically or logically correct.
> 2. **coherence**: whether this step is consistent with the `QUESTION` and `ALL_STEPS`, and a reasonable next move.
>
> 3. **necessity**: whether this step contributes essential progress toward solving the problem.
>
> **Strict Scoring Rubric**
> **[correctness]**
> Score 1 if: no error; does not contradict the question or prior steps.
> Score 0 if: algebraic/logical mistake, rule misapplied, or contradicts prior steps.
> **[coherence]**
> Score 1 if: naturally follows from question and all steps; new notation properly introduced.
> Score 0 if: unjustified assumption, reverses earlier conclusions, or disconnected from
>
> flow.
> **[necessity]**
> Score 1 if: introduces nontrivial information used later; removal would make solution less complete.
> Score 0 if: merely restates prior info, is meta-commentary, or explores an unused direction.
> **Output Format (Mandatory).**
> You must output exactly one JSON dictionary:
> {"correctness": 0/1, "coherence": 0/1, "necessity": 0/1, "analysis": "2-4 sentences explaining your scores."}
>
> Rules: output must be valid JSON; only these four fields; no lists, markdown, backticks, or extra commentary.
> **Final Instruction.** Evaluate the current step:
> QUESTION: {QUESTION}
> ALL_STEPS: {ALL_STEPS}
> CURRENT_STEP (step {t}): {CURRENT_STEP}

Table 25: GPT-5.1 prompt for scoring CoT trajectories