# Learning Language-Conditioned Robot Behavior from Offline Data and Crowd-Sourced Annotation

**Abstract:** We study the problem of learning a range of vision-based manipulation tasks from a large offline dataset of robot interaction. In order to accomplish this, humans need easy and effective ways of specifying tasks to the robot. Goal images are one popular form of task specification, as they are already grounded in the robot's observation space. However, goal images also have a number of drawbacks: they are inconvenient for humans to provide, they can over-specify the desired behavior leading to a sparse reward signal, or under-specify task information in the case of non-goal reaching tasks. Natural language provides a convenient and flexible alternative for task specification, but comes with the challenge of grounding language in the robot's observation space. To scalably learn this grounding we propose to leverage *offline pre-collected robotic datasets* (including highly sub-optimal or random data) with *crowd-sourced natural language labels*. With this data, we learn a simple classifier which predicts if a change in state completes a language instruction. This provides a language-conditioned reward function that can then be used for offline multi-task RL. In our experiments, we find that on language-conditioned manipulation tasks our approach outperforms both goal-image specifications and language conditioned imitation techniques by more than 25%, and is able to perform visuomotor tasks from natural language, such as "open the right drawer" and "move the stapler", on a Franka Emika Panda robot.

**Keywords:** Natural Language, Offline RL, Visuomotor Manipulation

## 1 Introduction

We are motivated by the goal of generalist robots which can be commanded to complete a diverse range of manipulation tasks. Doing so requires humans to be able to effectively specify tasks for the robot to solve. One popular approach to task specification is through goal-states, which by definition are grounded in the robot's observation space, making them a natural choice for self-supervised techniques [1, 2, 3, 4]. However, goal-state specification comes with a number of drawbacks, including (a) human effort required in generating a goal state to provide the robot, (b) task over-specification resulting in a sparse reward signal (e.g. a goal image for the task of pushing a *single* object also specifies positions of all other objects and the robot itself), and (c) task under-specification (e.g. putting an object out of sight in a box or non-goal reaching tasks like rotating a faucet indefinitely). Natural language presents a promising alternative form of specification, providing an easy way for humans to communicate tasks. Moreover, natural language can flexibly represent non-goal reaching tasks and tasks with varying degrees of specificity, such as grasping

Figure 1: We learn language-conditioned visuomotor policies using sub-optimal offline data, crowd-sourced annotation, and pre-trained language models, enabling us to complete language-specified tasks on a real robot while being robust to complex rephrasings of the task description.

*any* marker from a desk with several markers, while a single goal image could only capture one instance of success. To this end, we study the problem of learning *language-conditioned visuomotor manipulation skills from offline datasets of robotic interaction.*

Despite the abundant benefits of being able to command robots with natural language, such agents have remained out of reach. A major challenge in acquiring such agents is that the language instructions need to be grounded in the agent's high-dimensional observation space. Learning this grounding is difficult, and requires diverse interaction data paired with language annotations. Recent works have made progress towards learning such grounding by annotating data collected by humans [5, 6, 7]; however, collecting many human teleoperated trajectories on real robots can be costly and time consuming, and is thus difficult to scale to a broad set of language conditioned behaviors.

Our key insight is that a practical and scalable way to ground language is to combine offline datasets of robotic interaction with post-hoc crowd-sourced natural language labels. Unlike prior work, we do not assume this data comes from an human expert or is optimal, allowing us to leverage sub-optimal data that was autonomously collected by the robot, much of which may not solve any particular task, but can more easily be collected at scale. Given such pre-collected data, we can then use crowd-sourcing to scalably label trajectories with natural language labels describing the behaviors in the data. To learn from this sub-optimal data with noisy annotations, we learn a simple classifier which takes as input a natural language instruction and an initial and final image, and predicts whether or not the transition completes the instruction. Moreover, we employ pretrained language models and data augmentation to enable the classifier to generalize to natural language with limited amounts of grounded language data. This learned classifier can then be used as a language-conditioned reward function for offline RL to learn language conditioned behaviors.

Concretely, in this work we propose to learn language conditioned skills from vision using sub-optimal offline data and crowd-sourced annotations (See Figure 1). We present a simple technique to learn language-conditioned rewards from this data, which we call **L**anguage-conditioned **O**ffline **R**eward **L**earning (LORL), and combine it with visual model-predictive control to complete language conditioned tasks (See Figure 2). In our experiments in simulation, we observe that even with data collected by a random policy our proposed method solves language-conditioned object manipulation tasks 25% more effectively than language conditioned imitation learning techniques, as well as 40% more effectively than goal-image conditioned comparisons which over-specify the task. Additionally, we observe that by virtue of leveraging pretrained language models our learned reward is capable of generalizing from scripted language instructions to unseen natural language zero-shot, suggesting that knowledge in pretrained language models can enable more efficient learning of grounded language. Finally, we leverage an existing real robot dataset of sub-optimal data, label the dataset using crowd-sourcing, and use it to complete five challenging visuomotor tasks specified by natural language, such as "open the right drawer" or "move the stapler" on a real Franka Emika Panda robot.

## 2  Related Work

There is a rich literature of work which studies interactive agents, and grounding their behaviors in natural language [8, 9, 10, 11]. Many prior works have studied this problem in the context of *instruction following* [9, 10, 12], where an agent aims to complete a task specified by a natural language instruction. While these approaches have been largely studied in simulated spatial games [12, 13, 14, 15] or in object-directed visual navigation in simulated robots [16, 17, 18, 19, 20, 21, 15] some of which include high-level object interaction [22], in this work we focus on the domain of learning control for *vision-based robotic manipulation*.

Early works have approached instruction following with strategies like semantic parsing mapped to motion primitives or pre-defined actions to execute tasks in virtual domains [23, 24, 25, 26] and on simulated robots [27, 28]. Unlike these approaches, we directly learn robotic control from images and natural language instructions, and don't assume any predefined motion primitives. More recently, end-to-end deep learning has been used to condition agents on language instructions [29, 16, 30, 19, 6, 7, 31], which are then trained under an imitation or reinforcement learning objective. In the reinforcement learning setting, works have adopted a range of strategies, from language-conditioned reinforcement learning while leveraging environment rewards [13, 32, 33, 34, 35, 36] to using language as a reward bonus to densify the environment reward and aid in exploration [37, 38, 39, 40, 41]. In contrast, we do not assume any environment provided reward signal, and rather aim to *learn* effective language-conditioned rewards from annotated data of interaction.

Figure 2: **Language-conditioned Offline Reward Learning (LORL)**. We propose a technique to learn language-conditioned behavior from offline datasets of robot interaction (**left**). To do so, we crowd-source natural language annotations describing the behavior in the offline data, and use it to learn a language-conditioned reward function (**middle**). We then combine this reward and a learned visual dynamics model through model predictive control to complete language specified tasks form vision on a real robot (**right**).

Numerous prior works have also studied learning language conditioned rewards online from demonstrations or examples of successful completion of tasks and language annotations [5, 14, 40]. These works then use the learned reward to optimize policies through online RL, often using the agents own online experience to train the reward [14, 42]. While these works also learn language-conditioned rewards, and in some cases also use discriminative techniques to learn the reward [14, 40], our work aims to learn language conditioned behaviors from entirely offline datasets (which may be highly sub-optimal), posing additional challenges around distribution shift and choosing negative examples. As a result of using offline data, we are able to learn language conditioned behaviors on real robots.

Other works have studied using offline data in the form of demonstrations or human teleoperated trajectories to learn language conditioned robotic agents [6, 7]. These works treat the offline data as near optimal, and leverage imitation learning techniques to learn language-conditioned policies. Unlike these works, we don't assume optimality of the collected data, allowing us to learn from arbitrary offline datasets, including datasets of random behavior, which can be considerably easier to collect at scale on a real robot than human teleoperation data [43, 44]. Moreover, we observe in Section 5.1 that our proposed approach outperforms imitation learning techniques in our domain.

Many prior works have studied how robots can learn to complete a wide range of tasks from vision. While many approaches have been taken to task-specification, including task IDs [45, 46], robot and human demonstrations [47, 48, 49], and meta-learning from rewards [50], a common approach is goal-conditioned learning [51, 52, 2, 1], where an agent learns to reach particular goal states or distributions [53]. Many approaches have been applied to this domain, ranging from goal-conditioned model-free learning [2, 54, 46, 55] with goal relabeling [52], model-based planning with a learned visual dynamics model [56, 57], to methods which combine the both [58]. Unlike these works, the focus of this work is multi-task visuomotor learning from natural language specifications. Furthermore, we find in Section 5.1 that using our language-conditioned reward we can more effectively complete tasks than leveraging a goal image specification, while requiring less human effort to specify the task.

## 3   Preliminaries

In this work we consider an interactive agent which aims to complete $K$ tasks $\{\mathcal{T}_k\}_1^K \subset \mathcal{T}$ where $\mathcal{T}$ denotes the space of all tasks. For each task $\mathcal{T}_i \in \mathcal{T}$ the agent operates in a Markov decision process MDP $\mathcal{M} = (\mathcal{S}, \mathcal{A}, p, \mathcal{R}_i, T)$ where $\mathcal{S}$ is the state space (in our case RGB images), $\mathcal{A}$ is the robot's action space, $p(s_{t+1}|s_t, a_t)$ is the robot environment's stochastic dynamics, $\mathcal{R}_i : \mathcal{S} \times \mathcal{S} \to \{0, 1\}$ indicates the binary reward at state $s$ for completing task $\mathcal{T}_i$ from initial state $s_0$, and $T$ is the episode horizon. Lastly, let $\mathcal{L}$ denote the set of all natural language, and let $\mathcal{L}_i \subset \mathcal{L}$ denote the set of language instructions which describe task $i$. Note that there can exist many instructions $l \in \mathcal{L}_i$ which describe a task $\mathcal{T}_i$ (e.g. "pick up the blue marker" and "grasp and lift the blue marker"), and any particular

instruction $l \in \mathcal{L}$ can describe multiple tasks (e.g. "pick up the marker" can describe the task of picking up the blue marker or the green marker).

In this work we assume that the true reward function $\mathcal{R}_i$ for each task $\mathcal{T}_i$ is unobserved, and must be inferred from natural language. Concretely, we assume access to an offline dataset $\mathcal{D}$ of $N$ trajectories, where each trajectory $\tau_n$ is a tuple containing a sequence of states and actions, and a single natural language instruction $\tau_n = ([(s_0, a_0), (s_1, a_1), ..., (s_T)], l_n)$. We assume that $l_n \in \mathcal{L}_i$ for at least one task $\mathcal{T}_i \in \mathcal{T}$ for which $\mathcal{R}_i(s_0, s_T) = 1$. Note $\mathcal{T}_i$ does not need to be in $\{\mathcal{T}_k\}_1^K$, meaning the offline data/annotations can consist of tasks unrelated to the robot's target tasks (e.g. "doing nothing"). Our goal then is to learn a parametrized reward model $\mathcal{R}_\theta : \mathcal{S} \times \mathcal{S} \times \mathcal{L} \to [0, 1]$ which conditioned on a language instruction $l$, initial state $s_0$, and state $s$ infers the true reward function $\mathcal{R}_i(s_0, s)$ for *some* task $\mathcal{T}_i$ for which $l \in \mathcal{L}_i$. Given $\mathcal{R}_\theta$, we aim to instantiate a stochastic language-conditioned policy $\pi : \mathcal{S} \times \mathcal{S} \times L \to \mathcal{A}$, which conditioned on a natural language instruction $l$ produces actions to maximize the expected sum of rewards $\sum_{t=0}^{T} \mathcal{R}_i(s_0, s_t)$ for the inferred task $\mathcal{T}_i$.

# 4 Language-conditioned Offline Reward Learning (LORL)

Now we describe how we go about learning our parametrized language-conditioned reward $\mathcal{R}_\theta$ from $\mathcal{D}$, as well as how we instantiate our language-conditioned policy $\pi$ to maximize the learned reward, also shown in Figure 2. Our key idea is that while we cannot make assumptions about the optimality of the behavior in $\mathcal{D}$, we can use the the initial and final states of each trajectory and provided language annotations to ground what changes in state correspond to successful completion of language instructions. Then to learn control we can leverage all of the data in $\mathcal{D}$ to learn a global task-agnostic model of the dynamics of the robots environment, which can be combined with the learned reward via model-predictive control (MPC) to complete language conditioned tasks.

## 4.1 Learning the Reward Function

Given the provided dataset $\mathcal{D} = [\tau_1, ..., \tau_N]$ of $N$ trajectories $\tau_n = ([(s_0, a_0), (s_1, a_1), ..., (s_T)], l_n)$, how might we go about learning our reward function $\mathcal{R}_\theta$? Critically, the behavior policy which collected this data could be sub-optimal. Therefore, we cannot assume the optimality of any particular action taken. However, because the human provided annotations describe the task being completed in the video, the assumption we can make about the data is that going from the start to the end of the trajectory constitutes completion of $l_n$. Therefore, we implement our reward function as a binary classifier $\mathcal{R}_\theta(s_0, s, l)$ which looks at the initial state $s_0$, current state $s$, and language instruction $l$ and predicts if going from the initial state to the current state satisfies the language instruction.

Training the reward function in this manner has numerous favorable properties. First, unlike explicitly predicting a single instance of a successful goal state for a language instruction or vice-versa, a classifier can easily capture the many-to-many mapping that exists between language instructions and tasks. Doing so allows it to capture the full space of successful behavior even in cases where there exists many possible language instructions $l$ which can describe completing a task $\mathcal{T}_i$ and many possible pairs of initial and final states $(s_0, s_T)$ which can constitute successfully completing any given instruction $l$. Second, by virtue of being *context-dependent* on the initial state, the reward function can be used for persistent behaviors like continuously rotating a faucet, which cannot be represented by a goal image. Lastly, unlike other works which use classifiers for single-task reward learning [59, 60, 44] on robots, a language-conditioned reward classifier can flexibly represent many tasks with an easy to provide form of task-specification. Concretely, we sample positive examples $(s_0, s_T, l_t) \in \tau_n \sim \mathcal{D}$ from the annotated dataset which constitute successfully completing an instruction and generate negative examples which don't complete instructions $(s_0', s_T', l') \sim \mathcal{N}$ also from $\mathcal{D}$ (described in detail in the next sections). We then minimize the binary cross entropy loss:

$$\mathcal{J}(\theta) = \mathbb{E}_{(s_0, s_T, l) \sim \mathcal{D}}[\log(\mathcal{R}_\theta(s_0, s_T, l))] + \mathbb{E}_{(s_0', s_T', l') \sim \mathcal{N}}[\log(1 - \mathcal{R}_\theta(s_0', s_T', l'))]. \quad (1)$$

**Positive Selection.** Selecting positive examples for the classifier is straightforward, as we know the initial and final state in an episode labeled with instruction $l$ satisfy that command. However, it is also highly likely that there are other states near the beginning and end of the episode for which the instruction is satisfied. Therefore we employ a noisy labeling scheme where we label any $(s_i, s_j, l)$ for which $i \leq \alpha T$ and $j \geq (1 - \alpha)T$ as a positive. Higher values of $\alpha$ may occasionally include false positives, but also significantly increase the set of positives which can be used for training.

**Negative Selection.** First, we choose initial and final states from episodes with *different* language instructions as negatives. Specifically, for language command $l$, we select negatives $s_0', s_T'$ by

Instruction: "Open the cabinet on the desk"

**Figure 3: Training LORL.** We train LORL on balanced batches of positive examples where the initial/final image transition satisfies the language command (**left**), negative examples where the initial/final states satisfy a *different* instruction (**middle**), and negative examples where the initial and final image are reversed (**right**).

selecting any $(s_0, s_T, l') \sim \mathcal{D}$ where $l' \neq l$. Note that since there may be instructions $l' \neq l$ which describe the same task, this may occasionally yield false negatives, however like prior work [59, 44] we find that we can learn an effective reward despite noisy negatives. Second, to encourage the reward to capture temporal progress (as opposed to focusing on spurious visual features), we also include the example $(s_T, s_0, l)$ as a negative in training $\mathcal{R}_\theta$. Ultimately, we train on balanced batches of positive examples and both types of negative examples (See Figure 3).

**Data Augmentation.** Reward functions trained using classifiers have been shown to be prone to over-fitting creating a sparse or incorrect reward signal [44]. This issue is further exacerbated by the fact that we only have limited positive examples per episode. To combat this, we use visual data augmentation in the form of affine transformations and color jitter as well as uniform noise in the embedding space of language instructions to prevent classifier over-fitting.

**Leveraging Pre-Trained Language Models.** Finally, learning the meaning of raw natural language while simultaneously grounding the robot's actions using only crowd-sourced data of a few thousand robot episodes with language annotations poses a significant challenge. Therefore we leverage a fixed pre-trained distilbert sentence encoder [61], to encode the natural language commands into a fixed length vector in $\mathbb{R}^{768}$ before they go into the classifier. We find in Section 5.2 that by using the pre-trained model we can generalize to unseen natural language commands from synthetic data.

### 4.2 Learning Language Conditioned Policies with Visual Model Predictive Control

Once trained, the learned reward function $\mathcal{R}_\theta$ in principle could be used with any form of offline reinforcement learning to learn language-conditioned policies. In this work, we aim to learn visuo-motor control on real robots from large datasets of sub-optimal or even random offline data. Model-based RL techniques have been particularly effective in this endeavor [56, 49], and in our case all offline data can be used to train a single task-agnostic visual dynamics model. We then use this model with planning to maximize the learned language-conditioned reward $\mathcal{R}_\theta$. Specifically, we learn a forward visual dynamics model $s_{t+1} \sim p_\theta(s_t, a_t)$ which is trained on the entire offline dataset $\mathcal{D}$, and does not use language annotations. We leverage off-the-shelf action-conditioned video prediction frameworks for learning this model [62, 63], which we describe in detail in the supplement.

Given the learned dynamics model $p_\theta$ and the learned reward function $\mathcal{R}_\theta$, we then use model predictive control to instantiate a policy to complete language-conditioned tasks. Specifically, given a language instruction $l$ and initial state $s_0$, we sample $M$ different actions sequences of length $H$, which we feed through $p_\theta$ to get a predicted future state $\hat{s}_{t+H}^m$. For each prediction we compute the reward as $\mathcal{R}_\theta(s_0, \hat{s}_{t+H}^m, l)$. Action sequences are optimized to maximize reward using the cross-entropy method (CEM) [64], until the best action sequence is applied in the environment (Figure 4).

## 5 Experiments

In our experiments we aim to study three main questions. **(1)** How does our proposed method for learning language conditioned policies from offline data compare to both language-conditioned and goal-image conditioned prior methods? **(2)** By virtue of using pre-trained language models, to what extent can our method generalize to unseen natural language commands? **(3)** Can our method be used to solve visuomotor tasks on a real robot using crowd-sourced annotations? We study experiments (1) and (2) in simulation, and experiment (3) on a Franka Emika Panda robot positioned in front of a desk. For qualitative results and videos, please see https://sites.google.com/view/robot-lorl.

Figure 4: **Executing Language-conditioned Policies with LORL.** To execute language-conditioned behavior, we perform model predictive control with a learned visual dynamics model and LORL. Specifically, from the initial state we predict many future states for different action sequences (**left/middle**). We then rank those sequences according to the LORL reward for the user specified natural language instruction (**middle**). After multiple iterations, the best action sequence is stepped in the environment executing the task (**right**).

## Simulated Domain

We study our first two experimental questions in a simulated domain developed on top of the Meta-World [45] environment, where a simulated sawyer robot interacts on a tabletop with a drawer, a faucet, and two mugs (see Figure 5 (left)). In this domain, we collect an offline dataset of 50,000 episodes by running a random policy in the environment, and label episodes procedurally using the true environment state yielding 2311 unique instructions (see Figure 5 (right)). After training on this data, we evaluate on 6 tasks which involve (1) closing the drawer, (2) opening the drawer, (3) turning the faucet

Figure 5: **Simulated Domain/Data.** We leverage a simulated domain developed on top of Meta-World [45] which contains a Saywer robot interacting with a drawer, faucet, and two mugs (**left**). We collect data using a random policy, and annotate episodes with language instructions using the environment state (**right**).

left and (4) right, and (5) pushing the black mug to the right, and (6) pushing the white mug down.

### 5.1 Does LORL enable effective language-conditioned behavior compared to prior work?

In this experiment we aim to evaluate how LORL compares to prior techniques for learning language and goal image conditioned behavior on the 6 target tasks described previously.

**Comparisons.** We compare LORL (**Ours**) to language-conditioned behavior-cloning (**LCBC**), which imitates the behavior in the offline dataset conditioned on the language instruction label, which is reflective of prior works that use imitation learning to learn language-conditioned behavior [6, 7]. We also compare to language-conditioned RL (**LCRL**), which labels the final state in each episode as having reward 1 for the annotated language instruction and 0 elsewhere, and trains a language conditioned-policy using offline Q learning, which reflects a fully offline version of the low-level policy used in [32]. Furthermore, we compare to using a goal-image as the task specification (**Pixel**) instead of language, and provide the agent with a ground truth goal-image of the object in its desired position, with which we use L2 pixel distance as a planning cost, reflective of prior work in visual MPC [56, 65]. Finally, we include an (**Oracle**) which uses the ground truth dynamics model and ground truth reward indicating the upper bound on the performance of the CEM planner, as well as the performance of a (**Random**) policy. All comparisons use the same architecture and data where possible; see the supplement for further details.

**Results.** Figure 6 shows the success rates over 3 seeds of 100 trials, ordered by legend. We observe first that our proposed approach outperforms the next best method, language-conditioned behavior cloning, by more than 25%. By learning a language-conditioned reward and planning over it, the robot executes the tasks more effectively than what it observed in the data. On the other hand, because the data is sub-optimal, language-conditioned imitation learning is only able to learn coarse directions associated with each task, and as a result fails on tasks that require more fine-grained motion like "turn faucet left". Second, we observe that language-conditioned RL with a binary reward struggles to learn at all, indicating the difficulty in jointly learning language-grounding and control. Finally,

Figure 6: **Comparison to Prior Work.** On 6 simulated language-conditioned tasks, we find that LORL (Ours) outperforms language-conditioned imitation learning (LCBC) and Q-learning (LCRL) as well as goal-image task specification (Pixel) by more than 25%. Success rates and standard error computed over 3 seeds of 100 trials.

266 we find that naively using goal-images also fails, performing comparably with a random policy. We
267 observe that the agent tries to match the arm position in the goal instead of the interacting with the
268 objects, highlighting the limitation of goal-images in their tendency to *over-specify* the task.

### 5.2 Can LORL generalize zero-shot to unseen natural language commands?

270 In our second experiment, we study our
271 methods ability to generalize to unseen in-
272 structions by nature of using pre-trained
273 language models. Specifically, for the
274 six target tasks, we test our method with
275 a *rephrased instruction*, which was com-
276 pletely unseen during training. We evalu-
277 ate task performance on the **Original** com-
278 mands, on the commands with an **Unseen**
279 **Verb** (e.g. "turn faucet left" → "rotate
280 faucet left"), on the command with an **Un-**
281 **seen Noun** (e.g. "move black mug right"
282 → "move dark cup right"), and **Unseen**
283 **Verb+Noun** (e.g. "close drawer" → "shut

| Success Rate | Ours | Ours (-PM) |
|---|---|---|
| Original | **56 ± 1%** | 40 ± 1% |
| Unseen Verb | **51 ± 3%** | 33 ± 2% |
| Unseen Noun | **51 ± 1%** | 39 ± 4% |
| Unseen Verb + Noun | **47 ± 2%** | 17 ± 3% |
| Unseen Natural Language | **46 ± 2%** | 21 ± 1% |

Table 1: **Effect of Pre-trained Language Models.** We compare the models ability to generalize to unseen instructions and natural language when learning with a fixed, pre-trained language model (Ours), compared to training the same architecture from scratch only on the grounded language data (Ours (-PM)). We see significant performance improvement in both seen and unseen commands by using the pre-trained model.

284 cabinet"). Finally, we also test on **Unseen Natural Language** commands collected from 9 human
285 volunteers who were asked to rephrase the command in a creative way, for example "turn faucet
286 left"→ "Spin nozzle left". The full set of unseen instructions for each task is in the supplement.

287 In Figure 7, we see that on average when changing the verb *or* noun, we only see a drop in success
288 rate of 5%, and when changing both or using human provided natural language, we see at most a 10%
289 drop in success rate. Furthermore, in Table 1 we compare performance with and without using the
290 pre-trained language model, and observe that without the pre-trained language model performance
291 is worse on seen instructions and drops significantly more on unseen instructions (up to 23% vs
292 10%), suggesting that the pre-trained language model is essential to learning and generalization. This
293 suggests that by using the knowledge in large un-grounded language models we can learn language
294 groundings when grounded language data is limited, opening up the potential to use small datasets or
295 *entirely programmatic language* to learn groundings which generalize to natural language.

Figure 7: **Generalization to Unseen Commands**. We observe that by leveraging pre-trained language models, LORL is able to generalize to unseen instructions with unseen verbs, nouns, and human generated instructions with a minimal (≤ 10%) drop in performance. Success rates computed over 3 seeds of 100 trials.

### 5.3 Can LORL be used to learn language-conditioned visuomotor skills on a real robot?

Finally, we study the efficacy of our method in learning language-conditioned behavior on a real robot using sub-optimal offline data and crowd-sourced annotation. We consider a Franka Emika Panda robot mounted over an IKEA desk with two drawers and a cabinet, which can hold a range of objects (Figure 8). The robot's observation space consists of 4 camera viewpoints, each providing $64 \times 64$ RGB images. The robot's action space is delta end-effector control.

**Data and Annotation.** We use an offline 3000 episode (150000 frame) dataset without any modification from concurrent work [66], which trains policies for different behaviors on the IKEA desk using online RL. As a result, our dataset consists of diverse behaviors, but is also sub-optimal in that it comes from the replay buffer of a learning policy which will often not complete any task or will complete tasks in highly sub-optimal ways.

To annotate the data, we leverage crowd-sourcing, specifically Amazon Mechanical Turk. We ask human annotators to describe the behavior, if any, that the robot is doing, and to phrase it as a command. We collect 6000 annotations, two per episode, containing a total of 1699 unique instructions, examples of which can be seen in Figure 8. We filter out episodes for which annotators wrote "do nothing" or indicated they could not understand what the robot was doing. See supplement for details about the environment, data, tasks, distribution of annotations, and annotator interface.

Figure 8: **Robot Domain/Data.** Our real robot domain consists of a Franka Emika Panda mounted over an IKEA desk (**left**). We crowd-source annotations describing the tasks being completed in an offline dataset from this environment (**right**).

**Results.** We find in Table 2 that, by training LORL on this annotated dataset and using it for visual MPC with a learned dynamics model in this domain, the robot can complete 5 challenging language specified tasks with a 66% success rate on average across tasks. Additionally, we find that removing negative training examples with the initial state and final state swapped (**LORL (-Neg)**) reduces performance by 30%, suggesting that such negatives are essential for the reward to effectively capture task progress.

Finally, we test LORL's robustness to more complex vocabulary and instruction length, by replacing the commands for opening the left drawer and moving the stapler with "Open the small black and white drawer on the left fully" and "Push the small gray stapler around on top of the black desk" respectively. We find that LORL is still able to succeed **7/10** and **5/10** times respectively, providing evidence that it is robust to instruction phrasing, consistent with the results in Section 5.2.

| Task (10 Trials Each) | LORL | LORL (-Neg) |
|---|---|---|
| "Open the left drawer" | **90%** | 30% |
| "Open the right drawer" | **40%** | 0% |
| "Move the stapler" | **50%** | 0% |
| 'Reach the marker" | **70%** | **70%** |
| "Reach the cabinet" | **80%** | **80%** |
| Average over tasks | **66%** | 36% |

Table 2: **Real Robot Results.** Using LORL we are able to complete 5 challenging visuomotor tasks on a robot specified by language with a 66% success rate.

## 6 Limitations and Future Work

We have presented LORL, a technique for learning language conditioned behavior from offline data and crowd sourced annotation that is effective for visuomotor control on real robots and is capable of generalizing to unseen language instructions. However, a number of limitations still remain. First, while in this work we have focused on learning short-horizon skills from language, composing these skills to solve long-horizon language-specified tasks is important for making robots useful in the real world. The primary bottleneck to extending LORL to longer horizons is the planner and visual dynamics models used for VMPC. Combining LORL with a model-free offline RL technique could mitigate these challenges and enable longer horizon tasks. Second, while we have presented language specification as an alternative to goal images, goal images maintain the benefit of being self-supervised and in some cases can be effective task specification. Unifying both forms of specification for robots would be a valuable future direction. Finally, further investigation into how best to select negative examples (rather than randomly) could enable learning a more accurate reward.

# References

[1] C. Finn and S. Levine. Deep visual foresight for planning robot motion. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2017.

[2] A. V. Nair, V. Pong, M. Dalal, S. Bahl, S. Lin, and S. Levine. Visual reinforcement learning with imagined goals. In *Advances in Neural Information Processing Systems*, 2018.

[3] C. Colas, P. Fournier, O. Sigaud, and P.-Y. Oudeyer. Curious: Intrinsically motivated multi-task, multi-goal reinforcement learning. *ArXiv*, abs/1810.06284, 2018.

[4] B. Ichter, P. Sermanet, and C. Lynch. Broadly-exploring, local-policy trees for long-horizon task planning. *ArXiv*, abs/2010.06491, 2020.

[5] J. Fu, A. Balan, S. Levine, and S. Guadarrama. From language to goals: Inverse reinforcement learning for vision-based instruction following. *ArXiv*, abs/1902.07742, 2019.

[6] C. Lynch and P. Sermanet. Grounding language in play. *ArXiv*, abs/2005.07648, 2020.

[7] S. Stepputtis, J. Campbell, M. Phielipp, S. Lee, C. Baral, and H. B. Amor. Language-conditioned imitation learning for robot manipulation tasks. *ArXiv*, abs/2010.12083, 2020.

[8] T. Winograd. Understanding natural language. *Cognitive Psychology*, 3(1):1–191, 1972. ISSN 0010-0285. doi:https://doi.org/10.1016/0010-0285(72)90002-3. URL https://www.sciencedirect.com/science/article/pii/0010028572900023.

[9] M. MacMahon, B. Stankiewicz, and B. Kuipers. Walk the talk: Connecting language, knowledge, and action in route instructions. 01 2006.

[10] T. Kollar, S. Tellex, D. Roy, and N. Roy. Toward understanding natural language directions. In *HRI 2010*, 2010.

[11] J. Luketina, N. Nardelli, G. Farquhar, J. N. Foerster, J. Andreas, E. Grefenstette, S. Whiteson, and T. Rocktäschel. A survey of reinforcement learning informed by natural language. In *IJCAI*, 2019.

[12] S. I. Wang, P. Liang, and C. D. Manning. Learning language games through interaction. *ArXiv*, abs/1606.02447, 2016.

[13] M. Jänner, K. Narasimhan, and R. Barzilay. Representation learning for grounded spatial reasoning. *Transactions of the Association for Computational Linguistics*, 6:49–61, 2018.

[14] D. Bahdanau, F. Hill, J. Leike, E. Hughes, S. Hosseini, P. Kohli, and E. Grefenstette. Learning to understand goal specifications by modelling reward. In *ICLR*, 2019.

[15] K. Chen, J. Chen, J. Chuang, M. V'azquez, and S. Savarese. Topological planning with transformers for vision-and-language navigation. *ArXiv*, abs/2012.05292, 2020.

[16] K. Hermann, F. Hill, S. Green, F. Wang, R. Faulkner, H. Soyer, D. Szepesvari, W. Czarnecki, M. Jaderberg, D. Teplyashin, M. Wainwright, C. Apps, D. Hassabis, and P. Blunsom. Grounded language learning in a simulated 3d world. *ArXiv*, abs/1706.06551, 2017.

[17] A. Chang, A. Dai, T. Funkhouser, M. Halber, M. Niessner, M. Savva, S. Song, A. Zeng, and Y. Zhang. Matterport3d: Learning from RGB-D data in indoor environments. *International Conference on 3D Vision (3DV)*, 2017.

[18] P. Anderson, Q. Wu, D. Teney, J. Bruce, M. Johnson, N. Sünderhauf, I. Reid, S. Gould, and A. van den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

[19] D. S. Chaplot, K. M. Sathyendra, R. K. Pasumarthi, D. Rajagopal, and R. Salakhutdinov. Gated-attention architectures for task-oriented language grounding. In *AAAI*, 2018.

[20] H. Chen, A. Suhr, D. K. Misra, N. Snavely, and Y. Artzi. Touchdown: Natural language navigation and spatial reasoning in visual street environments. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 12530–12539, 2019.

[21] J. Krantz, E. Wijmans, A. Majumdar, D. Batra, and S. Lee. Beyond the nav-graph: Vision-and-language navigation in continuous environments. 2020.

[22] M. Shridhar, J. Thomason, D. Gordon, Y. Bisk, W. Han, R. Mottaghi, L. Zettlemoyer, and D. Fox. ALFRED: A Benchmark for Interpreting Grounded Instructions for Everyday Tasks. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020. URL https://arxiv.org/abs/1912.01734.

[23] G. Kuhlmann, P. Stone, R. J. Mooney, and Shavlik. Guiding a reinforcement learner with natural language advice: Initial results in robocup soccer. In *AAAI 2004*, 2004.

[24] D. L. Chen and R. J. Mooney. Learning to interpret natural language navigation instructions from observations. pages 859–865, August 2011. URL http://nn.cs.utexas.edu/?chen:aaai11.

[25] Y. Artzi and L. Zettlemoyer. Weakly supervised learning of semantic parsers for mapping instructions to actions. *Transactions of the Association for Computational Linguistics*, 1:49–62, 2013. doi:10.1162/tacl_a_00209. URL https://www.aclweb.org/anthology/Q13-1005.

[26] J. Andreas and D. Klein. Alignment-based compositional semantics for instruction following. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 1165–1174, Lisbon, Portugal, Sept. 2015. Association for Computational Linguistics. doi:10.18653/v1/D15-1138. URL https://www.aclweb.org/anthology/D15-1138.

[27] T. Kollar, S. Tellex, D. Roy, and N. Roy. Grounding verbs of motion in natural language commands to robots. *Springer Tracts in Advanced Robotics*, 79, 01 2010. doi:10.1007/978-3-642-28572-1_3.

[28] S. Tellex, T. Kollar, S. Dickerson, M. Walter, A. Banerjee, S. Teller, and N. Roy. Understanding natural language commands for robotic navigation and mobile manipulation. volume 2, 01 2011.

[29] H. Mei, M. Bansal, and M. R. Walter. Listen, attend, and walk: Neural mapping of navigational instructions to action sequences. In *AAAI*, 2016.

[30] D. K. Misra, J. Langford, and Y. Artzi. Mapping instructions and visual observations to actions with reinforcement learning. In *EMNLP*, 2017.

[31] A. Akakzia, C. Colas, P.-Y. Oudeyer, M. Chetouani, and O. Sigaud. Grounding Language to Autonomously-Acquired Skills via Goal Generation. In *ICLR 2021 - Ninth International Conference on Learning Representation*, Vienna / Virtual, Austria, May 2021. URL https://hal.inria.fr/hal-03121146.

[32] Y. Jiang, S. Gu, K. Murphy, and C. Finn. Language as an abstraction for hierarchical deep reinforcement learning. In *NeurIPS*, 2019.

[33] H. Chan, Y. Wu, J. Kiros, S. Fidler, and J. Ba. Actrce: Augmenting experience via teacher's advice for multi-goal reinforcement learning. *ArXiv*, abs/1902.04546, 2019.

[34] J. D. Co-Reyes, A. Gupta, S. Sanjeev, N. Altieri, J. DeNero, P. Abbeel, and S. Levine. Guiding policies with language via meta-learning. *ArXiv*, abs/1811.07882, 2019.

[35] M. Chevalier-Boisvert, D. Bahdanau, S. Lahlou, L. Willems, C. Saharia, T. Nguyen, and Y. Bengio. Babyai: A platform to study the sample efficiency of grounded language learning. In *ICLR*, 2019.

[36] J. D. Kanu, E. Dessalene, X. Lin, C. Fermuller, and Y. Aloimonos. Following instructions by imagining and reaching visual goals. *ArXiv*, abs/2001.09373, 2020.

[37] R. Kaplan, C. Sauer, and A. Sosa. Beating atari with natural language guided reinforcement learning. *ArXiv*, abs/1704.05539, 2017.

[38] P. Goyal, S. Niekum, and R. Mooney. Using natural language for reward shaping in reinforcement learning. *ArXiv*, abs/1903.02020, 2019.

[39] X. E. Wang, Q. Huang, A. Çelikyilmaz, J. Gao, D. Shen, Y. Wang, W. Y. Wang, and L. Zhang. Reinforced cross-modal matching and self-supervised imitation learning for vision-language navigation. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6622–6631, 2019.

[40] S. P. Mirchandani, S. Karamcheti, and D. Sadigh. Ella: Exploration through learned language abstraction. *ArXiv*, abs/2103.05825, 2021.

[41] P. Goyal, S. Niekum, and R. Mooney. Pixl2r: Guiding reinforcement learning using natural language by mapping pixels to rewards. *ArXiv*, abs/2007.15543, 2020.

[42] G. Cideron, M. Seurin, F. Strub, and O. Pietquin. Self-educated language agent with hindsight experience replay for instruction following. *ArXiv*, abs/1910.09451, 2019.

[43] S. Dasari, F. Ebert, S. Tian, S. Nair, B. Bucher, K. Schmeckpeper, S. Singh, S. Levine, and C. Finn. Robonet: Large-scale multi-robot learning. In *Conference on Robot Learning*, 2019.

[44] A. S. Chen, H. Nam, S. Nair, and C. Finn. Batch exploration with examples for scalable robotic reinforcement learning. *IEEE Robotics and Automation Letters*, 2021.

[45] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on Robot Learning*, 2020.

[46] D. Kalashnikov, J. Varley, Y. Chebotar, B. Swanson, R. Jonschkowski, C. Finn, S. Levine, and K. Hausman. Mt-opt: Continuous multi-task robotic reinforcement learning at scale. *ArXiv*, abs/2104.08212, 2021.

[47] C. Finn, T. Yu, T. Zhang, P. Abbeel, and S. Levine. One-shot visual imitation learning via meta-learning. In *CoRL*, 2017.

[48] T. Yu, C. Finn, S. Dasari, A. Xie, T. Zhang, P. Abbeel, and S. Levine. One-shot imitation from observing humans via domain-adaptive meta-learning. In *Proceedings of Robotics: Science and Systems*, Pittsburgh, Pennsylvania, June 2018.

[49] A. S. Chen, S. Nair, and C. Finn. Learning generalizable robotic reward functions from "in-the-wild" human videos. *ArXiv*, abs/2103.16817, 2021.

[50] T. Zhao, A. Nagabandi, K. Rakelly, C. Finn, and S. Levine. Meld: Meta-reinforcement learning from images via latent state models. *ArXiv*, abs/2010.13957, 2020.

[51] L. P. Kaelbling. Learning to achieve goals. In *IN PROC. OF IJCAI-93*, pages 1094–1098. Morgan Kaufmann, 1993.

[52] M. Andrychowicz, D. Crow, A. Ray, J. Schneider, R. H. Fong, P. Welinder, B. McGrew, J. Tobin, P. Abbeel, and W. Zaremba. Hindsight experience replay. *ArXiv*, abs/1707.01495, 2017.

[53] S. Nasiriany, V. H. Pong, A. Nair, A. Khazatsky, G. Berseth, and S. Levine. Disco rl: Distribution-conditioned reinforcement learning for general-purpose policies. *ArXiv*, abs/2104.11707, 2021.

[54] B. Eysenbach, R. Salakhutdinov, and S. Levine. Search on the replay buffer: Bridging planning and reinforcement learning. In *NeurIPS*, 2019.

[55] Y. Chebotar, K. Hausman, Y. Lu, T. Xiao, D. Kalashnikov, J. Varley, A. Irpan, B. Eysenbach, R. C. Julian, C. Finn, and S. Levine. Actionable models: Unsupervised offline reinforcement learning of robotic skills. *ArXiv*, abs/2104.07749, 2021.

[56] F. Ebert, C. Finn, S. Dasari, A. Xie, A. Lee, and S. Levine. Visual foresight: Model-based deep reinforcement learning for vision-based robotic control. *arXiv:1812.00568*, 2018.

[57] Y.-C. Lin, M. Bauzá, and P. Isola. Experience-embedded visual foresight. *ArXiv*, abs/1911.05071, 2019.

[58] S. Tian, S. Nair, F. Ebert, S. Dasari, B. Eysenbach, C. Finn, and S. Levine. Model-based visual planning with self-supervised functional distances. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=UcoXdfrORC.

[59] J. Fu, A. Singh, D. Ghosh, L. Yang, and S. Levine. Variational inverse control with events: A general framework for data-driven reward definition. In *Advances in Neural Information Processing Systems*, 2018.

[60] A. Singh, L. Yang, C. Finn, and S. Levine. End-to-end robotic reinforcement learning without reward engineering. In *Proceedings of Robotics: Science and Systems*, FreiburgimBreisgau, Germany, June 2019.

[61] V. Sanh, L. Debut, J. Chaumond, and T. Wolf. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *ArXiv*, abs/1910.01108, 2019.

[62] M. Babaeizadeh, C. Finn, D. Erhan, R. H. Campbell, and S. Levine. Stochastic variational video prediction. *arXiv:1710.11252*, 2017.

[63] B.-H. Wu, S. Nair, R. Martín-Martín, L. Fei-Fei, and C. Finn. Greedy hierarchical variational autoencoders for large-scale video prediction. *ArXiv*, abs/2103.04174, 2021.

[64] R. Y. Rubinstein and D. P. Kroese. *The cross-entropy method: a unified approach to combinatorial optimization, Monte-Carlo simulation and machine learning*. Springer Science & Business Media, 2013.

[65] S. Nair and C. Finn. Hierarchical foresight: Self-supervised learning of long-horizon tasks via visual subgoal generation. *ArXiv*, abs/1909.05829, 2020.

[66] Anonymous. Example-driven model-based reinforcement learning for solving long-horizon visuomotor tasks.