Proactive Robot Assistance via Spatio-Temporal Object Modeling

Abstract: Proactive robot assistance enables a robot to anticipate and provide for a user's needs without being explicitly asked. We formulate proactive assistance as the problem of the robot anticipating temporal patterns of object movements associated with everyday user routines, and proactively assisting the user by placing objects to adapt the environment to their needs. We introduce a generative graph neural network to learn a unified spatio-temporal predictive model of object dynamics from temporal sequences of object arrangements. We additionally contribute the Household Object Movements from Everyday Routines (HOMER) dataset, which tracks household objects associated with human activities of daily living across 50+ days for five simulated personas. Our model outperforms the leading baseline in modeling object dynamics, with a 42% increase in F-1 score on predicting which objects will move in a certain predictive window, and 64% increase in accuracy on predicting the correct object destination.

Keywords: Proactive Assistance, Robot Learning, Graph Neural Network, Spatio-Temporal Object Tracking

Figure 1: The robot observes and learns patterns of object movements resulting from everyday activities, which it then uses to predict and execute proactive object relocations, such that the objects are in locations where the user will need them in the near future.

1 Introduction

Service robots that operate in everyday human environments and assist users with everyday tasks promise to be valuable in domestic [1] as well as workplace [2] settings, and can cater to the needs of a wide range of users, including children [3], older adults [4], and people with disabilities [5]. Critically, prior studies have shown that in longitudinal assistive scenarios, users show a strong preference for *proactive robot assistance*, such that the robot is able to anticipate and provide for the user's needs without being explicitly asked [6, 7, 8]. Prior work has focused on two proactive assistance scenarios: assistance with fixed pre-determined tasks (e.g., manufacturing assembly [9, 10], object arrangement [11]) and open world assistance in a home or office setting [7, 12, 13].

In this work, we focus on the problem of proactive robot assistance in open world environments. In such scenarios, assistance often takes the form of object placement. Examples include the robot

Submitted to the 6th Conference on Robot Learning (CoRL 2022). Do not distribute.

fetching objects for the user in anticipation of their need (e.g., taking out the breakfast cereal and bowl in the morning), as well as restoring objects after use (e.g., cleaning up after a meal), all without being asked. Prior work has addressed proactive assistance by relying on detailed models of human activity, requiring the robot to perform human activity recognition or human action prediction in order to determine which action to perform next [12, 14, 15]. However, building activity recognition models that comprehensively cover *all* human activities remains a challenging problem due to the diversity of human behavior. Furthermore, it may be impractical or impossible for the robot to keep the person in view and monitor activities continuously throughout the day.

Our work contributes a novel approach for proactive open world robot assistance that does not require recognition of the underlying user activity. Our key insight is that *objects* provide perspective into the user's activities and needs, without explicit activity recognition. Since proactive assistance primarily takes the form of object relocation, tracking the movement of objects in the environment has the benefit of providing actionable object-level information that can be utilized to provide anticipatory assistance. Therefore, as illustrated in Figure 1, our work aims to understand patterns in temporal daily routines of users, anticipate user needs, and plan assistive actions.

Specifically, the contributions of our work are as follows. First, we contribute the Household Object Movements from Everyday Routines (HOMER) dataset, which tracks household objects associated with human activities across 50+ days for five simulated personas. Second, we provide a formal definition for proactive assistance as an object dynamics modeling problem. Third, we contribute a novel generative graph neural network model that performs spatio-temporal object tracking and facilitates proactive robot assistance by modeling future movement of objects in an environment. We validate our approach against prior works that perform object tracking based on object-object relation frequencies [16] and previously observed periodic routines [17]. Our approach outperforms both baselines even with as little as 5 days of training data, and results in a 42% increase in F-1 score on predicting which objects will move in a certain predictive window, and 64% increase in accuracy on predicting the correct object destination over the leading baseline. Additionally, we demonstrate the use of our system on a physical robot proactively assisting a user with their morning routine.

2   Prior Work

In this section, we discuss prior work relating to the problem of object tracking, the representation of object arrangements, and the computational models relating to our tracking formulation.

Object tracking methods have been developed towards various applications, such as manipulation in home robots [18], collision avoidance [19], augmented reality [20], and robot localization [21]. Computer vision has been used to extract object trajectories from video [22], and RFID tags have been used to detect object motion resulting from human actions [23] or the identity of objects being used [24]. Most closely related to our work are methods aimed at aiding object search, which traditionally leverage probabilistic models. [25] combines prior knowledge, observations, and known constraints to represent beliefs over object locations. To include statistical domain knowledge in a similar probabilistic framework, [16] leverages correlational information from datasets to generate semantic priors on the likelihood of inter-object relations. FreMEn [17] and temporal persistence modeling [26] leverage past experience in the environment to model a temporal function of existence of objects of interest in a location. We seek to combine spatial inter-object relations and observed object location histories into a unified spatio-temporal model of object dynamics.

Object tracking for proactive assistance requires us to construct object models that span both space and time. To model space, we utilize *scene graphs*, which are represented by a set of $< object, relationship, subject >$ triplets, and we model their progression in time through a sequence of scene graphs at discrete time intervals. Spatio-temporal graphs are typically used for inference through methods such as probabilistic models [27] or graphical LSTMs [28], but learning a predictive model of the temporal dynamics of graphical object arrangements requires a generative model that can represent the future scene graph given the current scene graph.

Generative Graph Neural Network models are capable of learning dynamics over a graphical space from data, and use encoder-decoder frameworks [29, 30, 31], or step-wise modification [32, 33,

Figure 2: Generative graph neural network to predict a future scene, given the current scene and time. The input graph edges are embedded into latent space and then passed through attention-based aggregation to obtain information from neighboring edges and temporal context to predict the output edge existence.

34]. We find the latter more suitable for our application, because of sparse changes in scenes over consecutive time steps. Due to lack of domain specific heuristics that some modification-based networks [32, 34] require, we derive inspiration from a general graph translation method, Node-Edge Co-evolving Deep Graph Translator (NEC-DGT) [33] to learn our predictive model only based on data. Graph Neural Networks have been adapted to model temporal dynamics [35], by exploiting relationships between graphs proximal in time [36], or related by known temporal periodicities in data [37]. However, our model also needs to derive information from the absolute value of time (e.g. the user usually has breakfast *around 8am*, in addition to *after brushing their teeth*). Hence, we use a time representation inspired from prior work [38] as a global context for our network.

3 Problem Formulation

At any given time t, we model the state of the environment, X_t, as consisting of a set of object-location pairs (o_i, l_i) representing the placement of object $o_i \in \mathcal{O}$ at location $l_i \in \mathcal{L}$. The state of the environment can be modified by an embodied agent (human or robot) by performing a *relocation* action $r(o, l_1, l_2)$ to move object $o \in \mathcal{O}$ from location l_1 to location l_2. We assume all objects in $\mathcal{O}$ to be relocatable, and allow objects to also serve as locations for placement of other objects (e.g., food items placed on a *plate*), such that $\mathcal{O} \cap \mathcal{L} \neq \emptyset$. We assume instances of the same class (e.g., one of multiple *cereal* instances) to be uniquely identifiable.

Based on the above formulation, we model the object relocation problem as consisting of two parts. First, given a set of previous observations of the environment $X_{0:M}$ over some time span M, learn the model $\Phi(X_t, t) \rightarrow \hat{X}_{t+\delta}$ that takes the time t and the state of the environment X_t and predicts the future state $\hat{X}_{t+\delta}$ some fixed δ timesteps in the future. Second, define the function $\Psi(X_t, \hat{X}_{t+\delta}) \rightarrow \mathcal{R}$ which returns the set of relocations $\mathcal{R}$ required to transition the environment from X_t to $\hat{X}_{t+\delta}$.

4 Spatio-Temporal Object Dynamics Model

We aim to learn the spatio-temporal dynamics of object locations over graphical representations to conserve spatial relationship information. We represent the environment state, X_t, at a given time t as a directed graph, $G_t = \{V, E\}$, and learn a model $\Phi(G_t, t) \rightarrow p(G_{t+\delta})$ to predict a fully-connected probabilistic graph from data. G_t has an in-tree or anti-arborescence structure with nodes $V = \{v_i\}$ representing each object/location instance in the environment, and one edge $\{e_{i,j}\} \in E$ originating from every node, except the root node, connecting it with its parent location node. The output probabilistic graph $p(G_{t+\delta})$ represents a distribution over possible in-trees, and we can infer the posterior, $\hat{G}_{t+\delta} = \arg\max_{G_{t+\delta}} p(G_{t+\delta})$, by picking the most likely out-edge for every node.

To learn the dynamics Φ from graph sequences, we create a graph translation model[1]. The inputs to our model are one-hot encodings identifying each object instance as node embeddings, the edge existence/adjacency matrix of the input graph, and an encoding of the output graph timestamp. Our time encoding is similar to that utilized by Time2Vec [38], which uses sinusoidal functions parametrized by time periods τ to generate a feature representation of time that can be used to model periodicity in event predictions. Instead of learning the time periods in an end-to-end manner to optimize for the prediction task, as done in Time2Vec, we use n_τ pre-specified periods to induce meaningful priors on temporal periodicities, and use both sines and cosines for our periodic functions.

---

[1]We share our implementation of the model at `https://github.com/anonymous-004/SpatioTemporalObjectTracking`

(a) Source samples of what time each activity is done

(b) Extract habits for every activity by clustering the samples

(c) Compose complete distributions using a habit for every activity

(d) Source action scripts for each activity

(e) Comparison of activity distributions and schedule samples of two personas shows common activities such as showering and breakfast, as well as activities unique to each persona, for instance Persona A does cleaning and watches TV in the evening, and Persona B leaves the house after lunch and does laundry in the morning.

Figure 3: Process for generating the HOMER behavioral dataset.

Our model generates latent edge features from the input edge existence and the associated node embeddings using a Multi Layer Perceptron (MLP), and passes them through aggregation layers to predict output edge existence probabilities as outlined in Figure 2. The first aggregation step operates on the input graph topology. For every edge $e_{i,j}$, we aggregate the neighboring edge features belonging to the four categories of sharing the origin $e_{i,k}$, sharing the destination $e_{l,j}$, originating from destination $e_{j,m}$, and ending at origin $e_{n,i}$ by summation and concatenate the four resulting vectors along with the feature of edge $e_{i,j}$ and time context to produce the output feature for edge $e_{i,j}$. In this manner, the first aggregation layer generates edge features containing information about itself, its neighbors, and time, which are passed through an MLP to generate attention weights for each edge. In the second round, aggregation is done in a similar fashion, but on a fully connected graph topology, with edge features being weighed by the attention weights before being summed, and the resulting features are passed through an MLP to predict output edge existence likelihoods.

Our model is inspired by the the edge evolution framework in NEC-DGT [33], which operates directly on a fully connected graph topology. We found such unweighted message passing over all edges to be sub-optimal for scaling to the large number of objects in a house, potentially due to over-squashing, so we employed the above attention mechanism. By predicting attention weights based on the sparse input graph topology, we allow the signal from those edges to be stronger. To avoid limiting the model's receptive field to existing neighbors, we allow all edges to contribute in the second step of aggregation, expecting the learned weights to emphasize important neighbors. Empirical results shown in Sec.7.3 confirm that such a mechanism is indeed beneficial.

5   Behavioral Simulation Dataset

To train and validate spatio-temporal object tracking for proactive open world robot assistance, we require a dataset capturing the locations of household objects as they move over the course of routine

day-to-day human activities. Specifically, we require data that is longitudinal (spanning weeks or months) and captures naturally occurring variations in human behavior. Prior work has extensively documented routine activities in the home, particularly through datasets for activity recognition [39, 40, 41, 42]. However, existing datasets that contain object location data span only a few hours of data [43, 44, 45], and longitudinal datasets lack object location data [40, 46, 47].

We introduce the Household Object Movements from Everyday Routines (HOMER) dataset composed of routine behaviors spanning several weeks generated for five *personas* representing the habits of different individuals. The dataset is based on an apartment setting, where each apartment consists of four rooms and contains 66-77 objects. We used the VirtualHome simulator [48] to model human behavior, as it supports human agents, object interaction, and 33 high-level semantic commands, such as *find*, *walk*, *grab*, without requiring low-level motion control. Figure 3 presents an overview of the dataset generation process. First, we obtained a list of activities of daily living relevant to in-home routines from the activity recognition literature [49]. The complete set of activities is shown in Figure 3e. We then sourced our dataset using a two-step strategy, first sourcing high level activity schedules, and separately the low level action sequences to perform each activity.

Activity Schedules: To obtain realistic activity schedules, we collected data from 21 workers[2] on Amazon Mechanical Turk about which hours on a typical day from 6am to 12am they are likely to be doing each activity, Figure 3a. To build a probabilistic model that realistically captures variations in human behavior, we divided the samples for every activity into four clusters, such that the aggregate distributions for each cluster represent a common underlying *habit* of the constituent individuals pertaining to that activity (e.g., skipping breakfast vs eating breakfast), Figure 3b. To define a persona, we select a habit to represent the temporal distribution of how they do each activity, ensuring their mutual distinctness by maximizing their KL-divergence through genetic optimization, Figure 3c (see supplementary materials for more details).

Action Sequences: In parallel to the above, we used the VirtualHome simulator to collect execution scripts emulating each activity of daily living. We recruited 23 participants to compose step-by-step action sequences for each activity, defining the avatar's movement and interactions with various objects, as well as the minimum and maximum time duration needed to do each action, as shown in Figure 3d. The outcome was a set of action sequences, along with time duration ranges needed to perform each action, for all activities.

Schedule Sampling: Finally, we combined the activity schedules and action sequences and generated the HOMER dataset capturing how objects move throughout the environment over time. We characterized each of our five fictitious persona by a temporal activity distribution and an action script per activity, and used Monte Carlo sampling to generate samples of their daily routines[3], which are visualized in Figure 3e. When executed on the simulator, these routines provide a sequence of object arrangements, from which we derive states X_t to train and evaluate our model.

6 Evaluation

We test our predictive model on sequential scenes from each of our five persona datasets. We use τ_i of 1 day, 12 hours, 6 hours, 3 hours, 1 hour, 30 mins, and 10 mins to induce meaningful priors on periodicity of human activities, and construct each of the our MLPs with a single hidden layer consisting of 20 neurons and ReLU activation. We use Adam optimizer with a learning rate of 10^{-3}. We train our model separately on each persona dataset, and use a withheld set of 10 days for evaluation. Starting with a known graph G_t at time t, we use our network to predict the probabilistic graph one step (10 mins) into the future $p(G_{t+1})$. We feed the probabilistic output back into the model, run it iteratively to predict further into the future, and finally derive the desired posterior estimate $\hat{G}_{t+\delta}$. All reported results are averaged across the five personas.

---

[2]4F/17M, nearly equal participation from age groups of 25-35, 35-45, and over 45. Four of original 25 workers were omitted due to nonsensical answers, leaving 21 workers.

[3]The complete dataset is shared here. The code to generate data is at `https://github.com/anonymous-004/tasksim`; implementation details are in `https://github.com/anonymous-004/tasksim/blob/main/routines/README.md`.

6.1 Baselines

We compare our predictive model against two prior works on open world object tracking:

Static Semantic, adapted from [16], calculates static priors over object locations using observed object-location relation frequencies. The model propagates the given state by adding noise and updates it using the prior. To adapt the noise model to our topological formulation, we use a tunable probability of change and spread belief uniformly over all potential placement locations, as opposed to nearby areas in metric space.

FreMEn, adapted from [17], uses past experience to model the prior probability of existence of object-location relationships as periodic functions in time. We maintain beliefs over topological relations instead of the metric occupancy grid used in [17]. The final belief is a combination of the given state and periodic temporal priors, with a tunable time-decaying weight as suggested in [17].

6.2 Metrics

Given the current state X_t, represented by the graph G_t, our objective is to predict the state graph δ timesteps in the future, $\hat{G}_{t+\delta}$. Specifically, for proactive assistance the robot must predict object relocations resulting from human actions, $r(o_i, l_1, l_2)$, signifying the movement of object o_i from its original location l_1 to destination l_2. The set of such relocations, $\hat{\mathcal{R}}_{t:t+1}$, predicted to happen one step into the future $t + 1$ can be written as

$$\hat{\mathcal{R}}_{t:t+1} = \{r(o_i, l_1, l_2) | e_{i,l_1} \in \hat{G}_t, e_{i,l_2} \in \hat{G}_{t+1}, l_1 \neq l_2\}$$

To assist δ-steps into the future, the robot needs to predict relocations $\hat{\mathcal{R}}_{t:t+\delta}$ obtained from sequential predictions from time t to $t + \delta$ and reconciling multiple relocations:

$$\hat{\mathcal{R}}_{t:t+\delta} = \hat{\mathcal{R}}_{t:t+\delta-1} \cup \{r(o_i, l_1, l_2) | r(o_i, l_1, l_2) \in \hat{\mathcal{R}}_{t+\delta-1:t+\delta}, r(o_i, l_1, l_3) \notin \hat{\mathcal{R}}_{t:t+\delta-1}\}$$

We can extract the set of objects that are relocated as a part of relocation set $\mathcal{R}$ as

$$\mathcal{O}(\mathcal{R}) = \{o_i | r(o_i, l_1, l_2) \in \mathcal{R}\}$$

We evaluate model selected relocations against the ground truth relocations ($\mathcal{R}_{t:t+\delta}$). The exact order and precise timing of the robot's relocations is not critical as long as they occur before the human-generated event (e.g, the bowl or cereal could be taken out first). Hence, we measure the predictive performance of relocations over the entire proactivity δ, using the following metrics to capture how well the model predicts the objects that are relocated in that window and their destinations.

- **Precision**: The fraction of objects predicted to relocate ($\mathcal{O}(\hat{\mathcal{R}}_{t:t+\delta})$) that are correct

$$P_t = \frac{|\mathcal{O}(\hat{\mathcal{R}}_{t:t+\delta}) \cap \mathcal{O}(\mathcal{R}_{t:t+\delta})|}{|\mathcal{O}(\hat{\mathcal{R}}_{t:t+\delta})|}$$

- **Recall**: The fraction of objects that actually relocated ($\mathcal{O}(\mathcal{R}_{t:t+p})$) that were correctly predicted

$$R_t = \frac{|\mathcal{O}(\hat{\mathcal{R}}_{t:t+\delta}) \cap \mathcal{O}(\mathcal{R}_{t:t+\delta})|}{|\mathcal{O}(\mathcal{R}_{t:t+\delta})|}$$

- **Destination Accuracy**: The fraction of actual relocations ($\mathcal{R}_{t:t+\delta}$) that were correctly predicted, including both the object and its destination

$$D_t = \frac{|\hat{\mathcal{R}}_{t:t+\delta} \cap \mathcal{R}_{t:t+\delta}|}{|\mathcal{R}_{t:t+\delta}|}$$

7 Results

Below, we compare the performance of our model against the baselines, investigate the effect of fewer training samples, show the importance of our attention mechanism and time encoding, and finally validate our model on a real robot.

7.1 Performance comparison

We use metrics of precision, recall and destination accuracy, as well as F-1 scores calculated using precision and recall, to evaluate the performance of our model, trained on 50 days of training data for a proactivity window δ of 10 minutes to 120 minutes with increments of 10 minutes. Table 1 and Figure 4 present the results. Our method achieves an average 42% higher F-1 score and 89% higher precision over the leading baseline, FreMEn, and only slightly lower recall relative to baselines as shown in Figure 4a.

(a) Precision-Recall   (b) Num. relocations predicted   (c) Destination Accuracy

Figure 4: Our method achieves higher precision and F1-score despite slightly lower recall (4a) for proactivity δ of 10 minutes (darker markers) to 120 minutes (lighter markers), at intervals of 10. The baselines achieve a higher recall by predicting a large number of relocations (4b), at the cost of lower destination accuracy (4c).

Figures 4b and 4c shed light on the differences in algorithmic performance. We observe that FreMEn (squares) makes too many relocation predictions compared to ground-truth relocations (dashed), resulting in a low destination accuracy for object placement. This is due to the fact that FreMEn rearrangements are based on a prior that is conditioned entirely on *time*, without considering current environment state X_t. As a result, natural deviations in user behavior (e.g., early breakfast) will cause the model to place objects in their typical locations (e.g., cereal back in the cabinet) even while still in use. The Static Semantic (circles) baseline demonstrates similar weaknesses because its prior is agnostic to both X_t and time. In a real world scenario, both baseline methods would cause the robot to constantly rearrange objects in the house, sometimes correctly predicting an object that would have moved, but at the expense of moving too many unrelated and unnecessary items.

By contrast, our model models both state and time, and is able to model typical state progressions. Experimental results show that our method (triangles) does not over-predict relocations, resulting in a 9% lower recall and 64% higher destination accuracy than the leading baseline, FreMEn. With a wider proactivity δ the methods predict more changes correctly because of greater error tolerance in predicting the exact time of relocations, but beyond a certain δ, this benefit is countered by the difficulty of predicting far out into the future, causing a saturation or even a degradation of performance, as seen in the recall (Figure 4a) and destination accuracy (Figure 4c) metrics.

Method	F-1 score	Precision	Recall	Dest. Acc.
Static Semantic	0.2595	0.2327	**0.4941**	0.1355
FreMEn	0.3642	0.3289	0.4687	0.1957
Ours	**0.5184**	**0.6223**	0.4492	**0.3220**

Table 1: Comparison of average metrics for our method against the baselines.

7.2 Training Data Efficiency

We evaluate data efficiency by training each model using varying amounts of training data, from 5 to 50 days of observations. As shown in Figure 5, our method improves performance as more data becomes available and outperforms both baselines even with as little as 5 days of training data.

7.3 Model Analysis

We perform an analysis to measure the impact of our attention mechanism and time representation. The purpose of our attention mechanism is to avoid over-squashing caused by message passing over a fully connected graph topology with a large branching factor. Empirical results shown in Table 2 prove its benefit as our

Method	F-1
Ours	**0.5184**
Without Attention	0.4023
Without Time Enc.	0.4195

Table 2: Model Analysis

Figure 5: Mean and standard deviation of F-1 Score and Destination Accuracy for 5-50 days of training data.

model outperforms a version without such a mechanism. Our model also exhibits superior performance over using a linear representation of time as a single number in minutes.

7.4 Robot Validation

Finally, we present a proof-of-concept demo of our system on a Fetch robot assisting with a breakfast routine, as shown in Figure 6 and detailed in our accompanying video. The shown scenario demonstrates anticipatory assistance through taking out of cereal, milk and bowl prior to the user's breakfast. Additionally, the robot anticipates the need to clean up, resulting in the restorative actions of placing the cereal box and milk back, and leaving the bowl in the sink. One benefit of our object-based proactive assistance model is that it is robust to variations in the user's routine. As shown when the user skips breakfast, even though the robot prepared the breakfast items, it will also replace them once breakfast time has elapsed.

|(a)|(b)|(c)|(d)|

Figure 6: The robot observes user behavior and learns patterns therein (a). The robot uses the learned model for proactive assistance (b), reducing effort to the user (c) both before the breakfast activity, and after (d).

8 Discussion, Limitations and Future Work

In this paper, we introduce an object-centric perspective to providing proactive robot assistance, present a novel dataset for longitudinal object tracking, and contribute a novel generative graph neural network formulation for predicting future environmental scenes. Our results show that our model significantly outperforms two prior techniques for modeling environmental dynamics, even if given as little as 5 days of training data. We additionally demonstrate that the model can be used on a real robot to accurately predict future objects movements and plan anticipatory and restorative actions that benefit the user, without the need for activity recognition and subsequent analysis of used objects in each activity. Such assistance does not require explicit user commands, reducing the burden on the user.

Limitations and Future Work: As discussed earlier, leveraging only object data removes reliance on potentially incomplete or inaccurate activity recognition models, which can be a strength in complex real-world deployment scenarios. However, the lack of activity modeling is also a limitation because the robot is unaware of the user's current actions. For example, if the user is taking an unusually long time to eat breakfast, the robot may clean up too early. Future work should combine the capabilities of both object-based and activity-based systems. An additional limitation is that our method does not currently account for object state. Future work should expand the representation to condition object placement on state information (e.g., place clean bowls in cabinet and dirty bowls in the sink). Finally, human behavior is rarely deterministic and user preferences may be hard to predict (e.g., cereal or yogurt for breakfast). Future work should integrate user interaction to enable the robot to confirm with the user before performing actions with high uncertainty.

References

[1] G. Wilson, C. Pereyda, N. Raghunath, G. de la Cruz, S. Goel, S. Nesaei, B. Minor, M. Schmitter-Edgecombe, M. E. Taylor, and D. J. Cook. Robot-enabled support of daily activities in smart home environments. *Cognitive Systems Research*, 54:258–272, 2019. ISSN 1389-0417. doi:https://doi.org/10.1016/j.cogsys.2018.10.032.

[2] R. Stock, M. Merkle, D. Eidens, M. Hannig, P. Heineck, M. A. Nguyen, and J. Völker. When robots enter our workplace: understanding employee trust in assistive robots. *ICIS 2019 Proceedings*, 2019.

[3] R. J. López-Sastre, M. Baptista-Ríos, F. J. Acevedo-Rodríguez, S. Pacheco-da Costa, S. Maldonado-Bascón, and S. Lafuente-Arroyo. A low-cost assistive robot for children with neurodevelopmental disorders to aid in daily living activities. *International Journal of Environmental Research and Public Health*, 18(8), 2021. ISSN 1660-4601. doi: 10.3390/ijerph18083974.

[4] G. Mois and J. M. Beer. The role of healthcare robotics in providing support to older adults: a socio-ecological perspective. *Current Geriatrics Reports*, 9(2):82–89, 2020.

[5] S. W. Brose, D. J. Weber, B. A. Salatin, G. G. Grindle, H. Wang, J. J. Vazquez, and R. A. Cooper. The role of assistive robotics in the lives of persons with disability. *American Journal of Physical Medicine & Rehabilitation*, 89(6):509–521, 2010.

[6] H.-M. Gross, S. Mueller, C. Schroeter, M. Volkhardt, A. Scheidig, K. Debes, K. Richter, and N. Doering. Robot companion for domestic health assistance: Implementation, test and case study under everyday conditions in private apartments. In *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 5992–5999, 2015. doi: 10.1109/IROS.2015.7354230.

[7] G. Peleka, A. Kargakos, E. Skartados, I. Kostavelis, D. Giakoumis, I. Sarantopoulos, Z. Doulgeri, M. Foukarakis, M. Antona, S. Hirche, E. Ruffaldi, B. Stanczyk, A. Zompas, J. Hernandez-Farigola, N. Roberto, K. Rejdak, and D. Tzovaras. Ramcip - a service robot for mci patients at home. In *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 1–9, 2018. doi:10.1109/IROS.2018.8594214.

[8] J. Baraglia, M. Cakmak, Y. Nagai, R. P. Rao, and M. Asada. Efficient human-robot collaboration: when should a robot take initiative? *The International Journal of Robotics Research*, 36 (5-7):563–579, 2017.

[9] B. Hayes and B. Scassellati. Effective robot teammate behaviors for supporting sequential manipulation tasks. In *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 6374–6380. IEEE, 2015.

[10] V. V. Unhelkar, P. A. Lasota, Q. Tyroller, R.-D. Buhai, L. Marceau, B. Deml, and J. A. Shah. Human-aware robotic assistant for collaborative assembly: Integrating human motion prediction with planning in time. *IEEE Robotics and Automation Letters*, 3(3):2394–2401, 2018. doi:10.1109/LRA.2018.2812906.

[11] J. Baraglia, M. Cakmak, Y. Nagai, R. Rao, and M. Asada. Initiative in robot assistance during collaborative task execution. In *2016 11th ACM/IEEE international conference on human-robot interaction (HRI)*, pages 67–74. IEEE, 2016.

[12] H. Harman and P. Simoens. Action graphs for proactive robot assistance in smart environments. *Journal of Ambient Intelligence and Smart Environments*, 12(2):79–99, 2020.

[13] M. Ali, S. Alili, M. Warnier, and R. Alami. An architecture supporting proactive robot companion behavior. In *AISB 2009 Convention*, 2009.

[14] X. Puig, T. Shu, S. Li, Z. Wang, Y.-H. Liao, J. B. Tenenbaum, S. Fidler, and A. Torralba. Watch-and-help: A challenge for social perception and human-AI collaboration. In *International Conference on Learning Representations*, 2021.

[15] N. Oh, J. Park, J. Ho Kwak, and S. Jo. A robot capable of proactive assistance through handovers for sequential tasks. In *2021 18th International Conference on Ubiquitous Robots (UR)*, pages 296–301, 2021. doi:10.1109/UR52253.2021.9494681.

[16] Z. Zeng, A. Röfer, and O. C. Jenkins. Semantic linking maps for active visual object search. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 1984–1990. IEEE, 2020.

[17] T. Krajník, M. Kulich, L. Mudrová, R. Ambrus, and T. Duckett. Where's waldo at time t ? using spatio-temporal models for mobile robot search. In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pages 2140–2146, 2015. doi:10.1109/ICRA.2015.7139481.

[18] B. A. Erol, A. Majumdar, J. Lwowski, P. Benavidez, P. Rad, and M. Jamshidi. Improved deep neural network object tracking system for applications in home robotics. In *Computational Intelligence for Pattern Recognition*, pages 369–395. Springer, 2018.

[19] A. Mukhtar, L. Xia, and T. B. Tang. Vehicle detection techniques for collision avoidance systems: A review. *IEEE transactions on intelligent transportation systems*, 16(5):2318–2338, 2015.

[20] H. Uchiyama and E. Marchand. Object detection and pose tracking for augmented reality: Recent approaches. In *18th Korea-Japan Joint Workshop on Frontiers of Computer Vision (FCV)*, 2012.

[21] C.-C. Wang, C. Thorpe, S. Thrun, M. Hebert, and H. Durrant-Whyte. Simultaneous localization, mapping and moving object tracking. *The International Journal of Robotics Research*, 26 (9):889–916, 2007.

[22] A. Yilmaz, O. Javed, and M. Shah. Object tracking: A survey. *ACM Comput. Surv.*, 38(4): 13–es, dec 2006. ISSN 0360-0300. doi:10.1145/1177352.1177355.

[23] Y. H. Lee and I. Marsic. Object motion detection based on passive uhf rfid tags using a hidden markov model-based classifier. *Sensing and Bio-Sensing Research*, 21:65–74, 2018. ISSN 2214-1804. doi:https://doi.org/10.1016/j.sbsr.2018.10.005.

[24] J. Wu, A. Osuntogun, T. Choudhury, M. Philipose, and J. M. Rehg. A scalable approach to activity recognition based on object use. In *2007 IEEE 11th international conference on computer vision*, pages 1–8. IEEE, 2007.

[25] M. Lorbach, S. Höfer, and O. Brock. Prior-assisted propagation of spatial information for object search. In *2014 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 2904–2909. IEEE, 2014.

[26] R. Toris and S. Chernova. Temporal persistence modeling for object search. In *2017 IEEE international conference on robotics and automation (ICRA)*, pages 3215–3222. IEEE, 2017.

[27] B. Douillard, D. Fox, and F. Ramos. A spatio-temporal probabilistic model for multi-sensor object recognition. In *2007 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 2402–2408. IEEE, 2007.

[28] A. Jain, A. R. Zamir, S. Savarese, and A. Saxena. Structural-rnn: Deep learning on spatio-temporal graphs. In *Proceedings of the ieee conference on computer vision and pattern recognition*, pages 5308–5317, 2016.

[29] W. Jin, R. Barzilay, and T. Jaakkola. Junction tree variational autoencoder for molecular graph generation. In *International conference on machine learning*, pages 2323–2332. PMLR, 2018.

[30] W. Jin, K. Yang, R. Barzilay, and T. Jaakkola. Learning multimodal graph-to-graph translation for molecule optimization. In *International Conference on Learning Representations*, 2019.

[31] D. Zhou, L. Zheng, J. Xu, and J. He. Misc-gan: A multi-scale generative model for graphs. *Frontiers in big Data*, 2:3, 2019.

[32] M. Sacha, M. Błaz, P. Byrski, P. Dabrowski-Tumanski, M. Chrominski, R. Loska, P. Włodarczyk-Pruszynski, and S. Jastrzebski. Molecule edit graph attention network: modeling chemical reactions as sequences of graph edits. *Journal of Chemical Information and Modeling*, 61(7):3273–3284, 2021.

[33] X. Guo, L. Zhao, C. Nowzari, S. Rafatirad, H. Homayoun, and S. M. P. Dinakarrao. Deep multi-attributed graph translation with node-edge co-evolution. In *2019 IEEE International Conference on Data Mining (ICDM)*, pages 250–259. IEEE, 2019.

[34] Z. Zhou, S. Kearnes, L. Li, R. N. Zare, and P. Riley. Optimization of molecules via deep reinforcement learning. *Scientific reports*, 9(1):1–10, 2019.

[35] S. M. Kazemi, R. Goel, K. Jain, I. Kobyzev, A. Sethi, P. Forsyth, and P. Poupart. Representation learning for dynamic graphs: A survey. *J. Mach. Learn. Res.*, 21(70):1–73, 2020.

[36] S. Yan, Y. Xiong, and D. Lin. Spatial temporal graph convolutional networks for skeleton-based action recognition. In *Thirty-second AAAI conference on artificial intelligence*, 2018.

[37] H. Peng, H. Wang, B. Du, M. Z. A. Bhuiyan, H. Ma, J. Liu, L. Wang, Z. Yang, L. Du, S. Wang, et al. Spatial temporal incidence dynamic graph neural networks for traffic flow forecasting. *Information Sciences*, 521:277–290, 2020.

[38] V. Peñaloza. Time2vec embedding on a seq2seq bi-directional lstm network for pedestrian trajectory prediction. *Res. Comput. Sci.*, 149(11):249–260, 2020.

[39] R. Singh, A. Sonawane, and R. Srivastava. Recent evolution of modern datasets for human activity recognition: A deep survey. *Multimedia Systems*, 26(2):83–106, 2020.

[40] D. J. Cook, A. S. Crandall, B. L. Thomas, and N. C. Krishnan. Casas: A smart home in a box. *Computer*, 46(7):62–69, 2012.

[41] S. Das, R. Dai, M. Koperski, L. Minciullo, L. Garattoni, F. Bremond, and G. Francesca. Toyota smarthome: Real-world activities of daily living. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 833–842, 2019.

[42] D. F. Fouhey, W. Kuo, A. A. Efros, and J. Malik. From lifestyle vlogs to everyday interactions. In *CVPR*, 2018.

[43] S. Stein and S. J. McKenna. Combining embedded accelerometers with computer vision for recognizing food preparation activities. In *Proceedings of the 2013 ACM international joint conference on Pervasive and ubiquitous computing*, pages 729–738, 2013.

[44] R. Goyal, S. Ebrahimi Kahou, V. Michalski, J. Materzynska, S. Westphal, H. Kim, V. Haenel, I. Fruend, P. Yianilos, M. Mueller-Freitag, et al. The" something something" video database for learning and evaluating visual common sense. In *Proceedings of the IEEE international conference on computer vision*, pages 5842–5850, 2017.

[45] G. A. Sigurdsson, A. Gupta, C. Schmid, A. Farhadi, and K. Alahari. Charades-ego: A large-scale dataset of paired third and first person videos. *arXiv preprint arXiv:1804.09626*, 2018.

[46] J. Cumin, G. Lefebvre, F. Ramparany, and J. L. Crowley. A dataset of routine daily activities in an instrumented home. In *International Conference on Ubiquitous Computing and Ambient Intelligence*, pages 413–425. Springer, 2017.

[47] U. Köckemann, M. Alirezaie, J. Renoux, N. Tsiftes, M. U. Ahmed, D. Morberg, M. Lindén, and A. Loutfi. Open-source data collection and data sets for activity recognition in smart homes. *Sensors*, 20(3):879, 2020.

[48] X. Puig, K. Ra, M. Boben, J. Li, T. Wang, S. Fidler, and A. Torralba. Virtualhome: Simulating household activities via programs. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 8494–8502, 2018.

[49] S. Ramasamy Ramamurthy and N. Roy. Recent trends in machine learning for human activity recognition—a survey. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery*, 8(4):e1254, 2018.