# Anomaly Detection in Multi-Agent Trajectories for Automated Driving

**Abstract:**
Human drivers can easily assess normal driving behaviour based on their accumulated experience over time. Also, they can react fast in cases of abnormal driving situations to avoid accidents. Similar to humans, automated vehicles are supposed to perform anomaly detection. In this work, we propose the spatio-temporal graph auto-encoder for learning normal driving behaviours. Our innovation is the ability to jointly learn multiple trajectories of a dynamic number of agents. To perform anomaly detection, we first estimate a density function of the learned trajectory feature representation; and then detect anomalies in low-density regions. Due to the lack of multi-agent trajectory datasets for anomaly detection in automated driving, we introduce our dataset using a driving simulator for normal and abnormal manoeuvres. Our evaluations show that our approach learns the relation between different agents and delivers promising results compared to the related works. The code, simulation and the dataset will be publicly available.

**Keywords:** Anomaly Detection, Multi-Agent Trajectory, Graph Neural Networks, Automated Driving

## 1 Introduction

Human drivers obtain experience of what is normal driving behaviour by observing traffic participants over time. Based on the driving experience of normal situations, they develop a sensitivity to all kinds of abnormal driving situations, e.g. recognising a ghost driver, and thus react early enough to these driving anomalies. The ghost driver often breaks the rules for driving because of fatigue or missing attention, resulting in entering the opposite lane. Similar to humans, autonomous vehicles are supposed to perform anomaly detection automatically as part of the automated driving modules [1, 2, 3]. Learning, thus, normal driving behaviour, e.g. using agent trajectories, is necessary for detecting anomalies.

Anomaly detection is a long-developed approach in computer vision to spot abnormal human behaviour [4, 5] or vehicle motion in traffic [6]. In robotics, it detects hardware failures of self-flying delivery drones [7] or helps a wheeled robot to navigate around unseen obstacles [8]. Although these approaches can be transferred to automated driving, they only consider a single agent in a static environment. That is barely the case for automated vehicles, where several agents influence each other through interaction. In this work, we present an approach to detect anomalies in multi-agent trajectories for automated vehicles.

We propose a spatio-temporal graph auto-encoder (STGAE) for trajectory embedding. Similar to the standard auto-encoder, it learns a latent representation of multi-agent trajectories. The main innovation of STGAE is the ability to simultaneously learn multiple trajectories for a dynamic number of agents. In a second step, we perform kernel density estimation (KDE) on the latent representation of the STGAE. We empirically observe that KDE captures well the distribution of the normal trajectory data. During the test phase, we detect anomalies in low-density regions of the estimated density. To evaluate our approach, we introduce a new dataset due to the lack of existing datasets for multi-agent trajectory anomaly detection for automated driving. The current automotive datasets [9, 10] contain

many hours of recordings, but lack anomalies due to the rareness of abnormal driving situations, whereas anomaly detection datasets [11, 12] have the required anomaly labels but are not relevant to automotive and automated driving problems. Finally, scenario staging is often applied in behaviour modelling [13], but its prohibitive for driving anomalies since it will put the actors into life danger. For these reasons, we develop a multi-agent simulation and create a dataset with normal and abnormal manoeuvres. Then, we evaluate our method for single- and multi-agent configurations, including comparisons with deep sequential auto-encoder and linear models. Moreover, we rely on the standard metrics for anomaly detection to show that our approach delivers promising results compared to the other methods.

To the best of our knowledge, we are the first to leverage spatio-temporal graph neural networks in the context of anomaly detection of multi-agent dynamical systems. Due to the lack of available datasets, we introduce a simulated dataset for multi-agent anomaly detection (MAAD). We will publish our code, simulation and the dataset to enable research in this area.

## 2 Related Work

**Multi-Agent Trajectory Modelling.** Trajectory prediction is essential for automated driving [14, 15]. Modelling the interaction with the environment and between the participants improves the prediction quality [13, 16]. The idea of information exchange across agents is studied in multiple works [17, 18, 19]. For example, Alahi *et al.* introduce a social-pooling layer into LSTMs to incorporate interaction features between agents [20]. Recently, graph neural networks (GNN) outperform traditional sequential models on trajectory prediction benchmarks [21, 22]. GNNs explicitly model agents as nodes and their connection as edges to represent the social interaction graph. According to this, the social spatio-temporal graph convolution neural network (ST-GCNN) presented in [5] extracts spatial and temporal dependencies between agents. In this work, we use a similar architecture to design our spatio-temporal graph auto-encoder for learning a representation of the normal data.

**Anomaly Detection.** On image and video data, anomaly detection is a long-standing topic. Handcrafted and motion features were traditionally employed for anomaly detection based on probabilistic PCA [23] or one-class SVM [24]. At the moment, deep neural networks dominate the anomaly detection approaches [25, 26]. The usual approach is training an auto-encoder with normal data and then measure the deviation of the test samples from the learned representation. For instance, Morais *et al.* [5] proposed a sequential auto-encoder to encode skeleton-based human motion and consider the reconstruction error as a measure for the detection of irregular motion patterns. Also, the variational auto-encoder (VAE) in [27] can learn the normal data distribution from a set of raw sensor signals. In this work, we formulate the idea of learning the normal data distribution with the spatio-temporal graph auto-encoder. Unlike the prior work, we estimate a density function with the latent representation instead of relying on the reconstruction error.

**Anomaly Detection in Trajectory Prediction and Control.** Anomaly detection has been extensively studied in robotics, e.g. model predictive control [28], collaborative robots [29], autonomous drones [7], robot navigation in crowds [30] and uncertain environments [31, 8]. Nevertheless, the prior work only address the problem of single agent anomaly detection. We tackle the problem of detecting anomalies in multi-agent trajectories.

## 3 Anomaly Detection in Multi-Agent Trajectories

We study the problem of anomaly detection in multi-agent trajectories. The input to our approach is a scene with $N$ agents represented as a time series with frames $f_t = \{f_0, f_1, ..., f_T\}$ and length $T$, where $N$ is finite but can vary over scenarios. Each frame contains the $N$ agent states $\mathbf{s}_t^i = \{\mathbf{s}_t^1, ..., \mathbf{s}_t^N\}$. Our goal is to correctly predict the class $c_t = \{0, 1\}$, i.e. normal or abnormal, of an unseen frame during testing, while only showing normal scenes during training.

We follow a two-stage approach to detect the anomalies. First, we train a spatio-temporal graph convolution network auto-encoder to represent normal trajectories in a feature space, section 3.1. Second, we use the latent representation to fit a probabilistic density to the normal trajectories using kernel density estimation, section 3.2. Section 3.3 describes how we detect anomalies given the estimated density.

## 3.1 Spatio-Temporal Graph Auto-Encoder

We define a spatio-temporal graph auto-encoder (STGAE) as composition of a multi-agent trajectory encoder $g(\cdot)$ and a trajectory decoder $f(\cdot)$. The encoder maps a set of agent trajectories on a latent subspace. The decoder transforms the latent features back in the input space.

**Trajectory Encoding.** We first introduce the trajectory encoder. Given a set of $N$ agent trajectories of length $T$, we define a spatio-temporal graph $\mathcal{G} = \{\mathcal{G}_t \mid \forall t \in \{1,\ldots,T\}\}$ as a set of directed spatial graphs $\mathcal{G}_t = (\mathcal{V}_t, \mathcal{E}_t)$. The spatial graphs model the multiple agents as nodes $\mathcal{V}_t$ and their connectivity as edges $\mathcal{E}_t$ to compute pairwise influences. The set of graph nodes $\mathcal{V}_t = \{v_t^i \mid \forall i \in \{1,\ldots,N\}\}$ contain information of the agent states in terms of relative locations $v_t^i = (x_t^i, y_t^i)$. In a setting of multiple moving agents sharing the same environment, interaction influences individual agent behaviour. Therefore we define a set of edges $\mathcal{E}_t = \{e_t^{ij} \mid \forall i,j \in \{1,\ldots,N\}\}$ weather nodes $v_t^i$ and $v_t^j$ are connected, $e_t^{ij} = 1$, or disconnected, $e_t^{ij} = 0$. In this way we define the unweighted adjacency matrix $A_t'$ for all pairs of nodes. However, in many cases a binary adjacency matrix is not sufficient. In order to model different degrees of influence we make use of a weighted adjacency matrix as presented in [32]. We model the influence with a kernel function for each $e_t^{ij}$ to compute the weighting factor $a_t^{ij}$. The kernel function measures the similarity between two agents in the same time step as

$$a_t^{ij} = \begin{cases} 1/\|v_t^i - v_t^j\|_2 & , \|v_t^i - v_t^j\|_2 \neq 0 \\ 0 & , \text{Otherwise.} \end{cases} \tag{1}$$

Note, we use the relative agent positions in the kernel function. For the rare cases when both agents share the exact same relative position, we assume disconnection following [32]. With the resulting weighted adjacency matrix defined as $A_t = \{a_t^{ij} \mid \forall i,j \in \{1,\ldots,N\}\}$. Notice, the adjacency matrix has the same size for all time steps but varies in terms of influence weighting between time steps.

To aggregate features in both dimensions space and time, we use so-called spatio-temporal graph convolution neural networks (ST-GCNN). As introduced in [33], graph convolutions are applied on each frame individually first. Like convolutions share features across a pixel neighbourhood in images, graph convolutions share features across the neighbourhood $\mathcal{N}(v_t^i)$ of node $v_t^i$. In other words, to compute the spatial features of a given node we multiply all neighbours with the corresponding weight vector $\mathbf{w}$ and summarise over the entire neighbourhood. For the selection of the neighbours we define a sampling function $p(.)$ such that the features in layer $l$ can be written as

$$v_t^{i(l+1)} = \sum_{v_t^{j(l)} \in \mathcal{N}(v_t^{i(l)})} p(v_t^{i(l)}, v_t^{j(l)}) \cdot \mathbf{w}(v_t^{i(l)}, v_t^{j(l)})). \tag{2}$$

Before we give a definition of the spatial features in matrix form, we follow standard procedures and compute the normalised graph Laplacian [34]

$$\hat{A}_t = D_t^{-\frac{1}{2}} \tilde{A}_t D_t^{-\frac{1}{2}} \tag{3}$$

with the graph Laplacian $\tilde{A}_t = A_t + I$, where $I$ denotes the identity matrix, and the node degree matrix $D_t$ with diagonal entries defined as $D_t^{ii} = \sum_j \tilde{A}_t^{ij}$. We assume a fully connected graph and the weights estimated by the kernel function. We stack all $\hat{A}_t$ and the node features $\mathcal{V}_t^{(l)}$ of graph layer $l$ to $\hat{A} \in \mathbb{R}^{T \times N \times N}$ and $\mathcal{V}^{(l)} \in \mathbb{R}^{T \times N \times F}$ with feature dimension $F$, respectively. We define the spatial features as

$$f(\mathcal{V}^{(l)}, \hat{A}) = \sigma(\hat{A}\mathcal{V}^{(l)}\mathbf{W}^{(l)}), \tag{4}$$

with weight matrix $\mathbf{W}^{(l)}$ and activation function $\sigma(\cdot)$. This represents the features of the individual spatial graphs in the sequence. In dynamical systems, spatial features are not expressive enough

since they ignore important temporal relationships. To include the time dimension we connect the same node over consecutive frames using temporal convolutions as introduced in [35]. As a result of the encoder we receive the encoded features $Z \in \mathbb{R}^{T \times N \times \tilde{F}}$ with the feature dimension $\tilde{F}$.

**Trajectory Decoding.** Given the encoded representations we define a decoder to reconstruct the set of input sequences. The decoder directly applies multiple temporal convolutions on the temporal dimension of the latent features $Z$ [35]. To include agent interactions, the convolutions aggregate features across agents. We denote the decoder output as $\hat{\mathcal{V}}$.

**Training.** The goal is to train a STGAE to reconstruct the observed relative positions of each agent. Both, encoder and decoder are trained simultaneously in an end-to-end manner. Consider the training set $\mathcal{U}$ containing the normal scenarios and the test set $\mathcal{W}$ with both normal and abnormal scenarios. During training, the model learns to understand the patterns of the normal scenarios. We identified the auto-encoder learns more general features using a bi-variate loss instead of a simple mean squared error loss. This means, we predict a standard deviation $\sigma_t^i$ and a correlation factor $\rho_t^i$ in addition to the mean $\mu_t^i$. We assume that $(x_t^i, y_t^i)$ follows a bi-variate Gaussian distribution with $\mathbf{p}_t^i \sim \mathcal{N}(\mu_t^i, \sigma_t^i, \rho_t^i)$ and the reconstruction $\hat{v}_t^i$ follows an estimated bi-variate distribution $\mathcal{N}(\hat{\mu}_t^i, \hat{\sigma}_t^i, \hat{\rho}_t^i)$. We train the model to minimise the negative log-likelihood, defined as

$$L_r(\mathbf{W}) = -\sum_{t=1}^{T} \log(\mathbb{P}((\mathbf{p}_t^i | \hat{\mu}_t^i, \hat{\sigma}_t^i, \hat{\rho}_t^i)). \tag{5}$$

As it is the case for other sequential models [5], our STGAE requires inputs of a fixed temporal length. Therefore we clip each sequence into smaller fixed-size segments. Consider one scene of length $T'$, a segment $S_k = \{f_t \mid \forall t = \{b_k...e_k\}\}$ contains the frames $f_t$ beginning at $b_k$ to the end $e_k$ of the segment. We clip the segments using the sliding window strategy defined in [5], with stride $s$ and segment length $T = e_k - b_k$.

## 3.2 Kernel Density Estimation for Normal Trajectories

For the detection of anomalies we use a density-based approach. The idea is based on the assumption, that the normal samples underlie a common probability distribution and anomalies occur in regions with lower density. We use kernel density estimation (KDE) to approximate the distribution of the normal trajectories. The KDE is directly applied on the latent feature representation of the STGAE.

Given the trained STGAE, we encode all segments $S$ from the training set. Considering a segment $S_k$ the encoder outputs $Z_k \in \mathbb{R}^{T \times N \times \tilde{F}}$, which is composed of $T \times N$ feature vectors $z \in \mathbb{R}^{\tilde{F}}$. The set of training samples is thus represented as $S \times T \times N$ feature vectors, we summarise as $\mathbf{Z}$. The KDE assumes all samples to be i.i.d. random variables drawn from an unknown distribution $p$ [36]. We approximate the real density at point $z$ by $\hat{p}$ defined as

$$\hat{p}(z) = \frac{1}{|\mathbf{Z}|h} \sum_{i=1}^{|\mathbf{Z}|} K\left(\frac{z - z_i}{h}\right) \quad \text{with the Gaussian Kernel [37]} \quad K(x) \propto exp\left(-\frac{\|x\|^2}{2h^2}\right). \tag{6}$$

The kernel function weighs the observations differently based on the similarity to its neighbours. The parameter responsible for the weights of the points is the bandwidth $h$, which serves as a smoothing parameter. Note, we consider each frame as individual input, each feature vector $z$ includes both spatial interaction as well as temporal dependencies. To sum-up, equation 6 computes a probability density for every given frame.

## 3.3 Abnormal Trajectory Detection

**Inference.** To compute a density for an unseen frame we draw a segment from the test set and compute its latent representation using the STGAE encoder. Given the latent representations we can estimate the probability density for each individual frame using the kernel density estimator from equation 6. Note, the feature decoder is not required during testing.

Figure 1: Example sequences from the proposed MAAD dataset. We show the observed trajectory of each agent. The first frame shows a save overtaking manoeuvre form the normal set. The other three frames contain abnormal actions: the blue vehicle is pushing the red vehicle aside, an aggressive reeving action of the red vehicle and a ghost driver who even collides with the upcoming traffic.

**Anomaly Score.** To compute the anomaly score, we follow a similar pipeline as introduced in [5]. Consider all segments in the test set extracted via the sliding-window strategy. Using our two-stage approach, we predict a probability density for each frame $f_t$ in the segments. Given the stride $s$ and length $T$ of the sliding window strategy, where $s < T$, a specific frame $f_t$ is included in multiple segments $S_t$. This results in multiple feature encodings $z_{t,u}^i$ for agent $i$ in frame $t$ in segment $u$. To score one agent in a frame, we predict the probability density for each encoding and take the mean as:

$$\alpha(z_t^i) = \frac{\sum_{u \in S_t} p(z_{t,u}^i)}{|S_t|}. \tag{7}$$

This results in one anomaly score for each agent in a specific frame. To identify if a frame is normal or abnormal we compute the frame anomaly score by applying the max-pooling operation

$$\alpha(f_t) = max(\alpha(z_t^i))_{i \in 1,...,N}. \tag{8}$$

The max-pooling operation avoids missing anomalies compared to the mean, which is not justifiable in automated driving.

## 4 Experimental Results

In the following we present the first dataset for anomaly detection in multi-agent trajectories and evaluate our method in comparison to seven baselines.

### 4.1 Dataset Development

To evaluate our algorithm we develop a novel dataset for anomaly detection in multi-agent trajectories using the OpenAI Gym *MultiCarRacing-v0* environment [38]. Since it was originally released as a multi-agent racing environment for learning visual control policies [39], we adapt it for anomaly simulation. We design a scenario of a two-lane highway shared by two vehicles, which naturally leads to interaction, e.g. speed adjustments, lane changes or overtaking actions. The vehicles are controlled by human players to record multiple expert trajectories. For a new sequence we choose random initialisation of the agent starting positions to increase trajectory diversity.

In this way, we create a dataset with 113 normal scenes and 33 abnormal scenes. Beforehand, 11 different types of anomalies are defined in terms of breaking driving rules or careless behaviour[1]. Each abnormal scenario is recorded three times to incorporate variations between different recordings (See Figure 1). After recording, the sequences are annotated with frame-wise labels by human experts using the ELAN annotation software [40]. We use 80 randomly selected normal sequences for training and the remaining 66 sequences for testing. The sequences are sub-sampled to 10 Hz and we use a segment length of $T = 15$ time steps, which corresponds to 1.5 seconds. To the best of our knowledge, this is the first dataset of its kind addressing multi-agent anomaly detection in automated driving.

---

[1]We define the 11 anomaly sub-classes as *leave road*, *left spreading*, *aggressive overtaking*, *pushing aside*, *aggressive reeving*, *right spreading*, *skidding*, *staggering*, *tailating*, *thwarting* and *wrong-way-driving*.

## 4.2 Baselines

Our baselines include *multi-agent* models as variants of our method, which explicitly model interaction, as well as *single-agent* models, ignoring interaction. The baselines can be further categorised as *one-class* and *reconstruction* methods.

**Single-Agent.** To examine the effect of interaction, we define four interaction-free models, two parameter-free and two neural network approaches. As simple parameter-free reconstruction method, we employ the constant velocity model (*CVM*) from [41]. Secondly, we approximate the trajectory with interpolation between the first and the last time step of the observed trajectory, we denote the model as linear temporal interpolation (*LTI*). The linear models succeed in the metrics, if the velocity profile of abnormal trajectories highly deviates from the normal trajectories. As a single-agent neural network, first we adapt the *Seq2Seq* model from [42]. It is composed of an encoder LSTM and a decoder LSTM. The encoder computes a feature vector representing one trajectory. After the last input is processed, the decoder tries to reconstruct the input trajectory from the feature vector. Next, we implement an interaction-free variant of STGAE by setting $A_t = I$. This reduces the model to a spatio-temporal auto-encoder, why we call it *STAE*.

**Multi-Agent.** Based on the proposed STGAE we evaluate three multi-agent baselines. For the first two variants, we use STGAE as reconstruction method. We train one STGAE with a bivariate loss (*STGAE-biv*) and a second with classical MSE loss (*STGAE-mse*) on the trajectory reconstruction task. Similar to our approach, the third variant is a one-class classification method. We replace the KDE of our method with a one-class SVM (OC-SVM), which is an adaption of the traditional SVM to one-class classification. It takes the encoder features as input and finds a hyperplane separating the data points from the origin while ensuring that the hyperplane has maximum distance from the origin [43]. The baseline is denoted as *STGAE+OC-SVM*.

## 4.3 Evaluation Metrics

We quantitatively evaluate our approach and compare it with the baselines by following the standard evaluation protocols used in the anomaly detection literature [44, 45, 46]: AUROC, AUPR-Error, AUPR-Success and FPR at 95% TPR. The AUROC metric integrates over the area under the Receiver Operating Characteristic curve (ROC) and results in a threshold-independent evaluation. Note that a classifier with 50 % AUROC is equal to a random classifier, while 100 % is the upper limit and denotes the best possible classifier. We use the Area Under the Precision-Recall (AUPR) curve as our second metric. Other than AUROC, it is able to adjust for class imbalances, which is always the case in anomaly detection, i.e. the amount of abnormal samples is small compared to normal samples [45]. Here, we show both AUPR metrics, the AUPR-normal, where we treat the normal class as positive, and the AUPR-abnormal, where we treat the abnormal class as positive. Additionally we show the false positive rate at 95% true positive rate (FPR-95%-TPR). For the one-class methods we directly apply the metrics on the output score, while for the reconstruction methods we take the mean squared error (MSE) between the given and the reconstructed trajectory as anomaly score following [5].

## 4.4 Implementation Details

The CVM approximates the agent trajectories assuming the same velocity for all time steps. The velocity is estimated given the first two time steps of a sequence. For LTI the reconstruction error is defined as the distance between the ground-truth trajectory and equidistantly sampled locations on a straight line between the beginning and the end of the trajectory. Both, the encoder and decoder of the Seq2Seq model, are implemented with 3 stacked LSTM layers and 15 hidden features. We train the network for 1500 epochs using Adam optimiser with learning rate 0.01.

Our STGAE method is implemented as ST-GCNN encoder [32] and TCN decoder [35]. The encoder is composed of one spatial graph convolution layer and one TCN layer, both with five latent features, followed by the decoder consisting of five TCN layers for reconstruction. We train for 250 epochs using Stochastic Gradient Descent and learning rate 0.01, and decay the learning rate to 0.002 after 150 epochs. For evaluating STGAE-biv we sample 20 reconstructed trajectories from the bivariate Gaussian distribution. STGAE with MSE loss does not use sampling.

Table 1: Comparison of the proposed method with the baselines on the proposed MAAD dataset using four metrics: AURC, AUPR-Normal, AUPR-Abnormal and FPR-95%-TPR. We differentiate between single- and multi-agent and further categorise into reconstruction and one-class classification methods. Highest scores are written in **bold**.

| | Method | One-class vs. Reconstruction | AUROC ↑ | AUPR-Normal ↑ | AUPR-Abnormal ↑ | FPR-95%-TPR ↓ |
|---|---|---|---|---|---|---|
| Single-Agent | CVM [41] | reconstruction | 83.11 | 95.99 | 54.47 | 74.62 |
| | LTI | reconstruction | 75.47 | 92.37 | 48.89 | 95.03 |
| | Seq2Seq [42] | reconstruction | 58.06 | 89.88 | 19.88 | 84.12 |
| | STAE-biv $|A_t = I$ | reconstruction | 70.01 | 92.90 | 30.98 | 81.65 |
| Multi-Agent | STGAE-mse | reconstruction | 87.70 | 97.55 | **55.90** | 48.34 |
| | STGAE-biv | reconstruction | 72.67 | 92.83 | 37.61 | 89.76 |
| | STGAE-biv+OC-SVM | one-class | 87.38 | 97.73 | 50.63 | **38.95** |
| | Ours | one-class | **88.34** | **97.88** | 55.57 | 40.90 |

Figure 2: The ROC curves of the single-agent models (dashed lines) and the multi-agent models (solid lines).

Figure 3: AUROC metric over the segment length. Our method is more stable for various segment lengths.

254 Both one-class classification methods (OC-SVM and KDE) are implemented using a Gaussian ker-
255 nel and the best hyperparameters are selected via grid search. Note, that OC-SVM has a minor
256 supervised advantage, since validation of the model takes place on a holdout test set, i.e. 20% ran-
257 domly selected from the test data. Hyperparameter tuning of $\gamma$ and $\nu$ for OC-SVM is performed via
258 grid search with $\gamma \in \{2^{-10}, 2^{-9}, ..., 2^{-1}\}$ and $\nu \in \{0.01, 0.1\}$. The bandwidth of KDE is selected
259 from $h \in \{2^{-4.5}, 2^{-4}, ..., 2^{5}\}$ via 5-fold cross-validation with the log-likelihood score as in [47].

## 4.5 Results

261 We present our results and compare them to the baselines. Afterwards, we evaluate on the different
262 anomaly types and finally the performance stability over input sequence length.

263 **Comparison with the Baselines.** The comparison of our method with the baselines is presented
264 in Table 1. Additionally, we show the ROC curves of all approaches in Figure 2. Our STGAE-
265 biv+KDE outperforms both the linear and the deep methods in two out of four metrics, namely
266 AUROC and AUPR-Normal, and is on par with STGAE-mse for AUPR-Abnormal. The second
267 one-class classification approach STGAE-biv+OC-SVM reaches similar performance and is the best
268 for FPR-95%-TPR, but cannot reach the high-score in the remaining metrics. Considering the ROC
269 curves, both one-class methods have a similar course with slight advantages for our method using
270 KDE for anomaly detection.

271 Overall, besides STGAE-biv, the multi-agent models show higher accuracy compared to methods
272 considering each agent individually. This indicates, that some manoeuvres are only anomalous in
273 the context of other traffic participants and could be considered as normal if the agent is alone on the
274 street. This observation is also the reason for the performance drop for STGAE-biv, if the adjacency
275 matrix $A_t$ is reduced to the identity matrix, i.e. no feature aggregation over neighbours. The linear
276 models perform competitively, which gives rise to the difference between normal and abnormal
277 lying in the degree of linearity of the trajectories. We empirically observe that Seq2Seq can not
278 differentiate between normal and abnormal trajectories for most experiments because it fails to learn

Table 2: AUROC on different types of anomalies. The multi-agent models reach high-scores in interaction manoeuvres, while single-agent methods win for non-interaction anomalies. Highest scores are written in **bold**.

| Abnormal class | CVM | LTI | Seq2Seq | STAE-biv $A_t = I$ | STGAE -mse | STGAE -biv | STGAE-biv +SVM | Ours |
|---|---|---|---|---|---|---|---|---|
| leave road | 88.66 | 32.30 | 91.06 | 92.95 | 99.24 | 94.32 | **99.57** | 98.22 |
| left spreading | 90.88 | **96.90** | 47.06 | 55.06 | 91.92 | 52.76 | 94.16 | 96.56 |
| aggressive overtaking | 91.78 | 78.30 | 59.09 | 50.30 | 92.52 | 59.92 | 91.80 | **93.24** |
| pushing aside | 91.54 | 79.98 | 75.55 | 82.02 | **98.73** | 72.51 | 89.84 | 90.44 |
| aggressive reeving | **96.67** | 61.15 | 79.00 | 81.97 | 96.33 | 86.37 | 92.31 | 94.57 |
| right spreading | 87.66 | 89.83 | 45.22 | 61.75 | **96.33** | 53.57 | 95.55 | 96.24 |
| skidding | 96.90 | 94.69 | 90.00 | 98.84 | 98.31 | 70.24 | 98.80 | **99.65** |
| staggering | 86.87 | 85.30 | 57.83 | 72.64 | 90.58 | 66.53 | 94.91 | **96.01** |
| tailgating | 77.18 | 70.20 | 35.88 | 74.11 | **88.71** | 86.42 | 83.55 | 84.87 |
| thwarting | **98.08** | 90.75 | 88.34 | 92.56 | 92.68 | 96.58 | 81.95 | 81.59 |
| wrong-way driving | 63.16 | 64.63 | 68.86 | 53.90 | 61.46 | 57.88 | 73.11 | **73.15** |
| overall | 83.11 | 75.47 | 58.06 | 70.01 | 87.70 | 72.67 | 87.38 | **88.34** |

the sequential dependencies during training. Overall, our approach can detect most of the anomalies compared to the baselines.

**Detection Score on Anomaly Types.** Table 2 shows the evaluation of the eleven anomaly types. To compute the ROC curve for an anomaly type, we consider this anomaly as positive and ignore all frames labelled with another anomaly category. Our method outperforms the others in four of the eleven classes and is competitive for the remaining ones. In particular, we significantly outperform the single-agent baselines on the *aggressive overtaking* category. We argue that it requires interaction modelling to distinguish the aggressive from a normal manoeuvre. Overall, the *wrong-way-driving* category leaves space for improvement. Including absolute coordinates in addition to velocity could help to learn more meaningful interaction features. Some abnormal trajectories can be detected without caring about interaction. This is when the linear models show their benefits, see *left spreading* or *thwarting* for LTI and CVM, respectively. The *left spreading* action is highly non-linear, such that the LTI model fails to approximate correctly what results in high anomaly scores. Similar, *thwarting* results through strong braking, which is not following the constant velocity assumption of CVM. Again, STGAE-mse is the best reconstruction method and outperforms on three sub-classes, however with the downside of a computational expensive trajectory decoder.

**Ablation Study on Observed Sequence Length.** Figure 3 shows the influence of different segment length $T \in \{4, 8, 10, 15, 20, 25, 40\}$ on the recognition performance. For the comparison we retrain STGAE-biv and the subsequent KDE on different segment length and compare with the linear models. Although we see a correlation between STGAE-biv and our method, our results remain stable for a large interval. As reported before, we reach the best performance for $T = 15$. In general, the performance of linear models decreases for higher input length, which means that linear models are good trajectory approximators only for short sequences. Over all methods, the performance drops for larger sequence length. Both, CVM and LTI, could reach better performances with peaks at 0.8 seconds, however our method remains the best overall with 88.34 % AUROC.

## 5 Conclusion

We presented the spatio-temporal graph auto-encoder for trajectory representation learning. Our main contribution is the ability to simultaneously learn multiple trajectories for a dynamic number of agents. Our model learns normal driving behaviour for performing afterwards anomaly detection. To this end, we performed kernel density estimation on the latent representation of the model. During the testing, we detect anomalies in low-density regions of the estimated density. Due to the lack of datasets for multi-agent trajectory anomaly detection for automated driving, we presented a synthetic multi-agent dataset with normal and abnormal manoeuvres. In our evaluations, we compared our approach with several baselines to show superior performance.

## References

[1] N. Engel, S. Hoermann, M. Horn, V. Belagiannis, and K. Dietmayer. Deeplocalization: Landmark-based self-localization with deep neural networks. In *2019 IEEE Intelligent Transportation Systems Conference (ITSC)*, pages 926–933. IEEE, 2019.

[2] J. Strohbeck, V. Belagiannis, J. Müller, M. Schreiber, M. Herrmann, D. Wolf, and M. Buchholz. Multiple trajectory prediction with deep temporal and spatial convolutional neural networks. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 1992–1998. IEEE, 2020.

[3] J. Wiederer, A. Bouazizi, U. Kressel, and V. Belagiannis. Traffic control gesture recognition for autonomous vehicles. In *2020 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 10676–10683, 2020. doi:10.1109/IROS45743.2020.9341214.

[4] Y. Lu, F. Yu, M. K. K. Reddy, and Y. Wang. Few-shot scene-adaptive anomaly detection. In *European Conference on Computer Vision*, pages 125–141. Springer, 2020.

[5] R. Morais, V. Le, T. Tran, B. Saha, M. Mansour, and S. Venkatesh. Learning regularity in skeleton trajectories for anomaly detection in videos. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11996–12004, 2019.

[6] J. Chen, G. Ding, Y. Yang, W. Han, K. Xu, T. Gao, Z. Zhang, W. Ouyang, H. Cai, and Z. Chen. Dual-modality vehicle anomaly detection via bilateral trajectory tracing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4016–4025, 2021.

[7] V. Sindhwani, H. Sidahmed, K. Choromanski, and B. Jones. Unsupervised anomaly detection for self-flying delivery drones. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 186–192. IEEE, 2020.

[8] R. McAllister, G. Kahn, J. Clune, and S. Levine. Robustness to out-of-distribution inputs via task-aware generative uncertainty. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 2083–2089. IEEE, 2019.

[9] H. Caesar, V. Bankiti, A. H. Lang, S. Vora, V. E. Liong, Q. Xu, A. Krishnan, Y. Pan, G. Baldan, and O. Beijbom. nuscenes: A multimodal dataset for autonomous driving. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 11621–11631, 2020.

[10] M. Braun, S. Krebs, F. Flohr, and D. M. Gavrila. Eurocity persons: A novel benchmark for person detection in traffic scenes. *IEEE transactions on pattern analysis and machine intelligence*, 41(8):1844–1861, 2019.

[11] W. Liu, D. L. W. Luo, and S. Gao. Future frame prediction for anomaly detection – a new baseline. In *2018 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

[12] C. Lu, J. Shi, and J. Jia. Abnormal event detection at 150 fps in matlab. In *Proceedings of the IEEE international conference on computer vision*, pages 2720–2727, 2013.

[13] J. F. P. Kooij, N. Schneider, F. Flohr, and D. M. Gavrila. Context-based pedestrian path prediction. In *European Conference on Computer Vision*, pages 618–633. Springer, 2014.

[14] A. Elnagar. Prediction of moving objects in dynamic environments using kalman filters. In *Proceedings 2001 IEEE International Symposium on Computational Intelligence in Robotics and Automation (Cat. No.01EX515)*, pages 414–419, 2001. doi:10.1109/CIRA.2001.1013236.

[15] S. Zernetsch, S. Kohnen, M. Goldhammer, K. Doll, and B. Sick. Trajectory prediction of cyclists using a physical model and an artificial neural network. In *2016 IEEE Intelligent Vehicles Symposium (IV)*, pages 833–838, 2016. doi:10.1109/IVS.2016.7535484.

[16] K. M. Kitani, B. D. Ziebart, J. A. Bagnell, and M. Hebert. Activity forecasting. In *European Conference on Computer Vision*, pages 201–214. Springer, 2012.

[17] A. Gupta, J. Johnson, L. Fei-Fei, S. Savarese, and A. Alahi. Social gan: Socially acceptable trajectories with generative adversarial networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2255–2264, 2018.

[18] A. Sadeghian, V. Kosaraju, A. Sadeghian, N. Hirose, H. Rezatofighi, and S. Savarese. Sophie: An attentive gan for predicting paths compliant to social and physical constraints. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1349–1358, 2019.

[19] N. Lee, W. Choi, P. Vernaza, C. B. Choy, P. H. Torr, and M. Chandraker. Desire: Distant future prediction in dynamic scenes with interacting agents. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 336–345, 2017.

[20] A. Alahi, K. Goel, V. Ramanathan, A. Robicquet, L. Fei-Fei, and S. Savarese. Social lstm: Human trajectory prediction in crowded spaces. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 961–971, 2016.

[21] Y. C. Tang and R. Salakhutdinov. Multiple futures prediction. *arXiv preprint arXiv:1911.00997*, 2019.

[22] B. Ivanovic and M. Pavone. The trajectron: Probabilistic multi-agent trajectory modeling with dynamic spatiotemporal graphs. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2375–2384, 2019.

[23] J. Kim and K. Grauman. Observe locally, infer globally: a space-time mrf for detecting abnormal activities with incremental updates. In *2009 IEEE conference on computer vision and pattern recognition*, pages 2921–2928. IEEE, 2009.

[24] D. H. Hu, X.-X. Zhang, J. Yin, V. W. Zheng, and Q. Yang. Abnormal activity recognition based on hdp-hmm models. In *IJCAI*, pages 1715–1720, 2009.

[25] D. Xu, Y. Yan, E. Ricci, and N. Sebe. Detecting anomalous events in videos by learning deep representations of appearance and motion. *Computer Vision and Image Understanding*, 156: 117–127, 2017.

[26] S. Kim, Y. Choi, and M. Lee. Deep learning with support vector data description. *Neurocomputing*, 165:111–117, 2015.

[27] D. Park, Y. Hoshi, and C. C. Kemp. A multimodal anomaly detector for robot-assisted feeding using an lstm-based variational autoencoder. *IEEE Robotics and Automation Letters*, 3(3): 1544–1551, 2018.

[28] K. Lee, G. N. An, V. Zakharov, and E. A. Theodorou. Perceptual attention-based predictive control. In L. P. Kaelbling, D. Kragic, and K. Sugiura, editors, *Proceedings of the Conference on Robot Learning*, volume 100 of *Proceedings of Machine Learning Research*, pages 220–232. PMLR, 30 Oct–01 Nov 2020. URL http://proceedings.mlr.press/v100/lee20b.html.

[29] B. Hayes and J. A. Shah. Interpretable models for fast activity recognition and anomaly explanation during collaborative robotics tasks. In *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6586–6593. IEEE, 2017.

[30] A. Bera, S. Kim, and D. Manocha. Realtime anomaly detection using trajectory-level crowd behavior learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pages 50–57, 2016.

[31] T. Ji, S. T. Vuppala, G. Chowdhary, and K. Driggs-Campbell. Multi-modal anomaly detection for unstructured and uncertain environments. *arXiv preprint arXiv:2012.08637*, 2020.

[32] A. Mohamed, K. Qian, M. Elhoseiny, and C. Claudel. Social-stgcnn: A social spatio-temporal graph convolutional neural network for human trajectory prediction. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14424–14432, 2020.

[33] S. Yan, Y. Xiong, and D. Lin. Spatial temporal graph convolutional networks for skeleton-based action recognition. In *Proceedings of the AAAI conference on artificial intelligence*, volume 32, 2018.

[34] T. N. Kipf and M. Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

[35] C. Lea, M. D. Flynn, R. Vidal, A. Reiter, and G. D. Hager. Temporal convolutional networks for action segmentation and detection. In *proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 156–165, 2017.

[36] E. Parzen. On estimation of a probability density function and mode. *The annals of mathematical statistics*, 33(3):1065–1076, 1962.

[37] M. Nicolau, J. McDermott, et al. One-class classification for anomaly detection with kernel density estimation and genetic programming. In *European Conference on Genetic Programming*, pages 3–18. Springer, 2016.

[38] G. Brockman, V. Cheung, L. Pettersson, J. Schneider, J. Schulman, J. Tang, and W. Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

[39] W. Schwarting, T. Seyde, I. Gilitschenski, L. Liebenwein, R. Sander, S. Karaman, and D. Rus. Deep latent competition: Learning to race using visual control policies in latent space. *arXiv preprint arXiv:2102.09812*, 2021.

[40] H. Sloetjes and P. Wittenburg. Annotation by category-elan and iso dcr. In *6th international Conference on Language Resources and Evaluation (LREC 2008)*, 2008.

[41] C. Schöller, V. Aravantinos, F. Lay, and A. Knoll. What the constant velocity model can teach us about pedestrian motion prediction. *IEEE Robotics and Automation Letters*, 5(2):1696–1703, 2020.

[42] S. H. Park, B. Kim, C. M. Kang, C. C. Chung, and J. W. Choi. Sequence-to-sequence prediction of vehicle trajectory via lstm encoder-decoder architecture, 2018.

[43] B. Schölkopf, R. C. Williamson, A. J. Smola, J. Shawe-Taylor, J. C. Platt, et al. Support vector method for novelty detection. In *NIPS*, volume 12, pages 582–588. Citeseer, 1999.

[44] C. Corbière, N. THOME, A. Bar-Hen, M. Cord, and P. Pérez. Addressing failure prediction by learning model confidence. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/757f843a169cc678064d9530d12a1881-Paper.pdf.

[45] D. Hendrycks and K. Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. *CoRR*, abs/1610.02136, 2016. URL http://arxiv.org/abs/1610.02136.

[46] M. Z. Zaheer, J.-h. Lee, M. Astrid, and S.-I. Lee. Old is gold: Redefining the adversarially learned one-class classifier training paradigm. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14183–14193, 2020.

[47] L. Ruff, R. Vandermeulen, N. Goernitz, L. Deecke, S. A. Siddiqui, A. Binder, E. Müller, and M. Kloft. Deep one-class classification. In *International conference on machine learning*, pages 4393–4402. PMLR, 2018.