Diverse Weight Averaging for Out-of-Distribution Generalization

Abstract

Standard neural networks struggle to generalize under distribution shifts. For out-of-distribution generalization in computer vision, the best current approach averages the weights along a training run. In this paper, we propose Diverse Weight Averaging (DiWA) that makes a simple change to this strategy: DiWA averages the weights obtained from several independent training runs rather than from a single run. Perhaps surprisingly, averaging these weights performs well under soft constraints despite the network's nonlinearities. The main motivation behind DiWA is to increase the functional diversity across averaged models. Indeed, models obtained from different runs are more diverse than those collected along a single run thanks to differences in hyperparameters and training procedures. We motivate the need for diversity by a new bias-variance-covariance-locality decomposition of the expected error, exploiting similarities between DiWA and standard functional ensembling. Moreover, this decomposition highlights that DiWA succeeds when the variance term dominates, which we show happens when the marginal distribution changes at test time. Experimentally, DiWA consistently improves the state of the art on the competitive DomainBed benchmark without inference overhead.

1 Introduction

Learning robust models that generalize well is critical for many real-world applications [1, 2]. Yet, the classical Empirical Risk Minimization (ERM) lacks robustness to distribution shifts [3, 4, 5]. To improve out-of-distribution (OOD) generalization in classification, several recent works proposed to train models simultaneously on multiple related but different domains [6]. Though theoretically appealing, domain-invariant approaches [7] either underperform [8, 9] or only slightly improve [10, 11] ERM on the reference DomainBed benchmark [12]. The state-of-the-art strategy on DomainBed is currently to average the weights obtained along a training trajectory [13]. [14] argues that this weight averaging (WA) succeeds in OOD because it finds solutions with flatter loss landscapes.

In this paper, we show the limitations of this flatness-based analysis and provide a new explanation for the success of WA in OOD. It is based on WA's similarity with ensembling [15], a well-known strategy to improve robustness [16, 17], that averages the predictions from various models. Based on [18], we present a bias-variance-covariance-locality decomposition of WA's expected error. It contains four terms: *first* the bias that we show increases under shift in label posterior distributions (i.e., correlation shift [19]); *second*, the variance that we show increases under shift in input marginal distributions (i.e., diversity shift [19]); *third*, the covariance that decreases when models are diverse; *finally*, a locality condition on the weights of averaged models.

Based on this analysis, we aim at obtaining diverse models whose weights are averageable with our Diverse Weight Averaging (DiWA) approach. In practice, DiWA averages in weights the models obtained from independent training runs that share the same initialization. The motivation is that

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

those models are more diverse than those obtained along a single run [20, 21]. Yet, averaging the weights of independently trained networks with batch normalization [22] and ReLU layers [23] may be counter-intuitive. Such averaging is efficient especially when models can be connected linearly in the weight space via a low loss path. Interestingly, this linear mode connectivity property [24] was empirically validated when the runs start from a shared pretrained initialization [25]. This insight is at the heart of DiWA but also of other recent works [26, 27, 28], as further discussed in the related work (Section 6).

In summary, our main contributions are the following:

- We propose a new theoretical analysis of WA for OOD based on a bias-variance-covariance-locality decomposition of its expected error (Section 2). By relating correlation shift to its bias and diversity shift to its variance, we show that WA succeeds under diversity shift.

- We empirically tackle the covariance term by increasing the diversity across models averaged in weights. In our DiWA approach, we decorrelate their training procedures: in practice, these models are obtained from independent runs (Section 3). We then empirically validate that diversity improves OOD performance (Section 4) and show that DiWA is state of the art on all real-world datasets from the DomainBed benchmark [12] (Section 5).

2 Theoretical insights

Under the setting described in Section 2.1, we introduce WA in Section 2.2 and decompose its expected OOD error in Section 2.3. Then, we separately consider the four terms of this bias-variance-covariance-locality decomposition in Section 2.4. This theoretical analysis will allow us to better understand when WA succeeds, and most importantly, how to improve it empirically in Section 3.

2.1 Notations and problem definition

Notations. We denote $\mathcal{X}$ the input space of images, $\mathcal{Y}$ the label space and $\ell : \mathcal{Y}^2 \to \mathbb{R}_+$ a loss function. S is the training (source) domain with distribution p_S, and T is the test (target) domain with distribution p_T. For simplicity, we will indistinctly use the notations p_S and p_T to refer to the joint, posterior and marginal distributions of (X, Y). We note $f_S, f_T : \mathcal{X} \to \mathcal{Y}$ the source and target labeling functions. We assume that there is no noise in the data: then f_S is defined on $\mathcal{X}_S \triangleq \{x \in \mathcal{X}/p_S(x) > 0\}$ by $\forall (x, y) \sim p_S, f_S(x) = y$ and similarly f_T is defined on $\mathcal{X}_T \triangleq \{x \in \mathcal{X}/p_T(x) > 0\}$ by $\forall (x, y) \sim p_T, f_T(x) = y$.

Problem. We consider a neural network (NN) $f(\cdot, \theta) : \mathcal{X} \to \mathcal{Y}$ made of a fixed architecture f with weights θ. We seek θ minimizing the target generalization error:

$$\mathcal{E}_T(\theta) = \mathbb{E}_{(x,y) \sim p_T}[\ell(f(x, \theta), y)]. \tag{1}$$

$f(\cdot, \theta)$ should approximate f_T on $\mathcal{X}_T$. However, this is complex in the OOD setup because we only have data from domain S in training, related yet different from T. The differences between S and T are due to distribution shifts (i.e., the fact that $p_S(X, Y) \neq p_T(X, Y)$) which are decomposed per [19] into **diversity shift** (a.k.a. covariate shift), when marginal distributions differ (i.e., $p_S(X) \neq p_T(X)$), and **correlation shift** (a.k.a. concept shift), when posterior distributions differ (i.e., $p_S(Y|X) \neq p_T(Y|X)$ and $f_S \neq f_T$). The weights are typically learned on a training dataset d_S from S (composed of n_S i.i.d. samples from $p_S(X, Y)$) with a configuration c, which contains all other sources of randomness in learning (e.g., initialization, hyperparameters, training stochasticity, epochs, etc.). We call $l_S = \{d_S, c\}$ a learning procedure on domain S, and explicitly write $\theta(l_S)$ to refer to the weights obtained after stochastic minimization of $1/n_S \sum_{(x,y) \in d_S} \ell(f(x, \theta), y)$ w.r.t. θ under l_S.

2.2 Weight averaging for OOD and limitations of current analysis

Weight averaging. We study the benefits of combining M individual member weights $\{\theta_m\}_{m=1}^M \triangleq \{\theta(l_S^{(m)})\}_{m=1}^M$ obtained from M (potentially correlated) identically distributed (i.d.) learning procedures $L_S^M \triangleq \{l_S^{(m)}\}_{m=1}^M$. Under conditions discussed in Section 3.2, these M weights can be averaged despite nonlinearities in the architecture f. Weight averaging (WA) [13], defined as:

$$f_{\text{WA}} \triangleq f(\cdot, \theta_{\text{WA}}), \text{ where } \theta_{\text{WA}} \triangleq \theta_{\text{WA}}(L_S^M) \triangleq 1/M \sum_{m=1}^M \theta_m, \tag{2}$$

83 is the state of the art [14, 29] on DomainBed [12] when the weights $\{\theta_m\}_{m=1}^M$ are sampled along a
84 single training trajectory (a description we refine in Remark 1 from Appendix C.2).

Limitations of the flatness-based analysis. To explain this success, Cha *et al.* [14] argue that flat
86 minima generalize better; indeed, WA flattens the loss landscape. Yet, as shown in Appendix B, this
87 analysis does not fully explain WA's spectacular results on DomainBed. First, flatness does not act on
88 distribution shifts thus the OOD error is uncontrolled with their upper bound (see Appendix B.1).
89 Second, this analysis does not clarify why WA outperforms in OOD Sharpness-Aware Minimizer
90 (SAM) [30], which directly optimizes flatness (see Appendix B.2). Finally, it does not justify
91 why combining WA and SAM succeeds in IID [31] yet fails in OOD (see Appendix B.3). These
92 observations motivate a new analysis of WA; we propose one below that better explains these results.

2.3 Bias-variance-covariance-locality decomposition

94 We now introduce our bias-variance-covariance-locality decomposition which extends the bias-
95 variance decomposition [32] to WA. In the rest of this theoretical section, ℓ is the Mean Squared Error
96 for simplicity: yet, our results may be extended to other losses as in [33]. In this case, the expected
97 error of a model with weights $\theta(l_S)$ w.r.t. the learning procedure l_S was decomposed in [32] into:

$$\mathbb{E}_{l_S}\mathcal{E}_T(\theta(l_S)) = \mathbb{E}_{(x,y)\sim p_T}[\text{bias}^2(x,y) + \text{var}(x)], \tag{BV}$$

98 where $\text{bias}(x,y), \text{var}(x)$ are the bias and variance of the considered model w.r.t. a sample (x,y),
99 defined later in Equation (BVCL). To decompose WA's error, we leverage the similarity (al-
100 ready highlighted in [13]) between WA and functional ensembling (ENS) [15, 34], a more tra-
101 ditional way to combine a collection of weights. More precisely, ENS averages the predictions,
102 $f_{\text{ENS}} \triangleq f_{\text{ENS}}(\cdot, \{\theta_m\}_{m=1}^M) \triangleq 1/M \sum_{m=1}^M f(\cdot, \theta_m)$. Lemma 1 establishes that f_{WA} is a first-order
103 approximation of f_{ENS} when $\{\theta_m\}_{m=1}^M$ are close in the weight space.

Lemma 1 (WA and ENS. Proof in Appendix C.1. Adapted from [13, 28].)**.** *Given* $\{\theta_m\}_{m=1}^M$ *with*
105 *learning procedures* $L_S^M \triangleq \{l_S^{(m)}\}_{m=1}^M$. *Denoting* $\Delta_{L_S^M} = \max_{m=1}^M \|\theta_m - \theta_{WA}\|_2$, $\forall(x,y) \in \mathcal{X} \times \mathcal{Y}$:

$$f_{WA}(x) = f_{ENS}(x) + O(\Delta_{L_S^M}^2) \text{ and } \ell(f_{WA}(x),y) = \ell(f_{ENS}(x),y) + O(\Delta_{L_S^M}^2).$$

106 This similarity is useful since Equation (BV) was extended into a bias-variance-covariance decompo-
107 sition for ENS in [18, 35]. We can then derive the following decomposition of WA's expected test
108 error. To take into account the M averaged weights, the expectation is over the joint distribution
109 describing the M identically distributed (i.d.) learning procedures $L_S^M \triangleq \{l_S^{(m)}\}_{m=1}^M$.

Proposition 1 (Bias-variance-covariance-locality decomposition of the expected generalization error
111 of WA in OOD. Proof in Appendix C.2.)**.** *Denoting* $\bar{f}_S(x) = \mathbb{E}_{l_S}[f(x,\theta(l_S))]$, *under identically*
112 *distributed learning procedures* $L_S^M \triangleq \{l_S^{(m)}\}_{m=1}^M$, *the expected generalization error on domain* T
113 *of* $\theta_{WA}(L_S^M) \triangleq \frac{1}{M}\sum_{m=1}^M \theta_m$ *over the joint distribution of* L_S^M *is:*

$$\mathbb{E}_{L_S^M}\mathcal{E}_T(\theta_{WA}(L_S^M)) = \mathbb{E}_{(x,y)\sim p_T}\Big[\text{bias}^2(x,y) + \frac{1}{M}\text{var}(x) + \frac{M-1}{M}\text{cov}(x)\Big] + O(\bar{\Delta}^2),$$

$$\text{where } \text{bias}(x,y) = y - \bar{f}_S(x),$$

$$\text{and } \text{var}(x) = \mathbb{E}_{l_S}\Big[\big(f(x,\theta(l_S)) - \bar{f}_S(x)\big)^2\Big], \tag{BVCL}$$

$$\text{and } \text{cov}(x) = \mathbb{E}_{l_S,l'_S}\Big[\big(f(x,\theta(l_S)) - \bar{f}_S(x)\big)\big(f(x,\theta(l'_S))) - \bar{f}_S(x)\big)\Big],$$

$$\text{and } \bar{\Delta}^2 = \mathbb{E}_{L_S^M}\Delta_{L_S^M}^2 \text{ with } \Delta_{L_S^M} = \overset{M}{\underset{m=1}{\max}}\|\theta_m - \theta_{WA}\|_2.$$

114 cov *is the prediction covariance between two member models whose weights are averaged. The*
115 *locality term* $\bar{\Delta}^2$ *is the expected squared maximum distance between weights and their average.*

116 Equation (BVCL) decomposes the OOD error of WA into four terms. The bias is the same as that of
117 each of its i.d. members. WA's variance is split into the variance of each of its i.d. members divided
118 by M and a covariance term. The last locality term constrains the weights to ensure the validity of
119 our approximation. In conclusion, combining M models divides the variance by M but introduces
120 the covariance and locality terms which should be controlled along bias to guarantee low OOD error.

2.4 Analysis of the bias-variance-covariance-locality decomposition

We now analyze the four terms in Equation (BVCL). We show that bias dominates under correlation shift (Section 2.4.1) and variance dominates under diversity shift (Section 2.4.2). Then, we discuss a trade-off between covariance, reduced with diverse models (Section 2.4.3), and the locality term, reduced when weights are similar (Section 2.4.4). This analysis shows that *WA is effective against diversity shift when M is large and when its members are diverse but close in the weight space*.

2.4.1 Bias and correlation shift (and support mismatch)

We relate OOD bias to correlation shift [19] under Assumption 1, where $\bar{f}_S(x) \triangleq \mathbb{E}_{l_S}[f(x, \theta(l_S))]$. As discussed in Appendix C.3.2, Assumption 1 is reasonable for a large NN trained on a large dataset representative of the source domain S. It is relaxed in Proposition 4 from Appendix C.3.

Assumption 1 (Small IID bias). $\exists \epsilon > 0$ *small s.t.* $\forall x \in \mathcal{X}_S, |f_S(x) - \bar{f}_S(x)| \leq \epsilon$.

Proposition 2 (OOD bias and correlation shift. Proof in Appendix C.3). *With a bounded difference between the labeling functions $f_T - f_S$ on $\mathcal{X}_T \cap \mathcal{X}_S$, under Assumption 1, the bias on domain T is:*

$$\mathbb{E}_{(x,y)\sim p_T}[\text{bias}^2(x,y)] = \textit{Correlation shift} + \textit{Support mismatch} + O(\epsilon),$$

$$\textit{where Correlation shift} = \int_{\mathcal{X}_T \cap \mathcal{X}_S} (f_T(x) - f_S(x))^2 p_T(x) dx, \tag{3}$$

$$\textit{and Support mismatch} = \int_{\mathcal{X}_T \setminus \mathcal{X}_S} \left(f_T(x) - \bar{f}_S(x)\right)^2 p_T(x) dx.$$

We analyze the first term by noting that $f_T(x) \triangleq \mathbb{E}_{p_T}[Y|X = x]$ and $f_S(x) \triangleq \mathbb{E}_{p_S}[Y|X = x]$, $\forall x \in \mathcal{X}_T \cap \mathcal{X}_S$. This expression confirms that our correlation shift term measures shifts in posterior distributions between source and target, as in [19]. It increases in presence of spurious correlations: e.g., on ColoredMNIST [8] where the color/label correlation is reversed at test time. The second term is caused by support mismatch between source and target. It was analyzed in [36] and shown irreducible in their "No free lunch for learning representations for DG". Yet, this term can be tackled if we transpose the analysis in the feature space rather than the input space. This motivates encoding the source and target domains into a shared latent space, e.g., by pretraining the encoder on a task with minimal domain-specific information as in [36].

This analysis explains why WA fails under correlation shift, as shown on ColoredMNIST in Appendix G. Indeed, combining different models does *not* reduce the bias, which remains the same as the bias of its members. Section 2.4.2 explains that WA is however efficient against diversity shift.

2.4.2 Variance and diversity shift

Variance is known to be large in OOD [5] and to cause a phenomenon named underspecification, when models behave differently in OOD despite similar test IID accuracy. We now relate OOD variance to diversity shift [19] in a simplified setting. We fix the source dataset d_S (with input support X_{d_S}), the target dataset d_T (with input support X_{d_T}) and the network's initialization. We get a closed-form expression for the variance of f over all other sources of randomness under Assumptions 2 and 3.

Assumption 2 (Kernel regime). *f is in the kernel regime [37, 38].*

This states that f behaves as a Gaussian process (GP); it is reasonable if f is a wide network [37, 39]. The corresponding kernel K is the neural tangent kernel (NTK) [37] depending only on the initialization. GPs are useful because their variances have a closed-form expression (Appendix C.4.1). To simplify the expression of variance, we now make Assumption 3.

Assumption 3 (Constant norm and low intra-sample similarity on d_S). *$\exists (\lambda_S, \epsilon)$ with $0 \leq \epsilon \ll \lambda_S$ such that $\forall x_S \in X_{d_S}, K(x_S, x_S) = \lambda_S$ and $\forall x'_S \neq x_S \in X_{d_S}, |K(x_S, x'_S)| \leq \epsilon$.*

This states that training samples have the same norm (following standard practice [39, 40, 41, 42]) and weakly interact [43, 44]. This assumption is further discussed and relaxed in Appendix C.4.2. We are now in a position to relate variance and diversity shift when $\epsilon \to 0$.

162 **Proposition 3** (OOD variance and diversity shift. Proof in Appendix C.4). *Given f trained on source*
163 *dataset d_S (of size n_S) with NTK K, under Assumptions 2 and 3, the variance on dataset d_T is:*

$$\mathbb{E}_{x_T \in X_{d_T}}[\text{var}(x_T)] = \frac{n_S}{2\lambda_S} MMD^2(X_{d_S}, X_{d_T}) + \lambda_T - \frac{n_S}{2\lambda_S}\beta_T + O(\epsilon), \tag{4}$$

164 *where MMD is the empirical Maximum Mean Discrepancy in the RKHS of $K^2(x, y)$ =*
165 $(K(x, y))^2$; $\lambda_T \triangleq \mathbb{E}_{x_T \in X_{d_T}} K(x_T, x_T)$ *and* $\beta_T \triangleq \mathbb{E}_{(x_T, x'_T) \in X^2_{d_T}, x_T \neq x'_T} K^2(x_T, x'_T)$ *are the em-*
166 *pirical mean similarities respectively measured between identical (w.r.t. K) and different (w.r.t. K^2)*
167 *samples averaged over X_{d_T}.*

168 The MMD empirically estimates shifts in input marginals, i.e., between $p_S(X)$ and $p_T(X)$. Our
169 expression of variance is thus similar to the diversity shift formula in [19]: our MMD distance
170 replaces the L_1 divergence previously used in [19]. The other terms, λ_T and β_T, both involve internal
171 dependencies on the target dataset d_T: they are constants w.r.t. X_{d_T} and do not depend on distribution
172 shifts. At fixed d_T and under our assumptions, Equation (4) shows that variance on d_T decreases
173 when X_{d_S} and X_{d_T} are closer (for the MMD distance defined by the kernel K^2) and increases when
174 they deviate. Intuitively, the further X_{d_T} is from X_{d_S}, the less the model's predictions on X_{d_T} are
175 constrained after fitting d_S.

176 This analysis shows that WA reduces the impact of diversity shift as combining M models divides the
177 variance per M. This is a strong property achieved *without requiring data from the target domain*.

2.4.3 Covariance and diversity

179 The covariance term increases when the predictions of $\{f(\cdot, \theta_m)\}_{m=1}^M$ are correlated. In the worst
180 case where all predictions are identical, covariance equals variance and WA is no longer beneficial.
181 On the other hand, the lower the covariance, the greater the gain of WA over its members; this is
182 derived by comparing Equations (BV) and (BVCL), as detailed in Appendix C.5. It motivates tackling
183 covariance by encouraging members to make different predictions, thus to be functionally diverse.
184 Diversity is a widely analyzed concept in the ensemble literature, for which numerous measures
185 have been introduced [45, 46, 47]. Deep ensembles [15] usually seek zero covariance by members'
186 independence [48]: we follow this objective in Section 3 by decorrelating the learning procedures.

2.4.4 Locality and linear mode connectivity

188 To ensure that WA approximates ENS, the last locality term $O(\bar{\Delta}^2)$ constrains the weights to be close.
189 Yet, the covariance term analyzed in Section 2.4.3 is antagonistic, as it motivates functionally diverse
190 models. Overall, to reduce WA's error in OOD, we thus seek a good trade-off between diversity and
191 locality. In practice, we consider that the main goal of this locality term is to ensure that the weights
192 are averageable despite the nonlinearities in the NN such that WA's error does not explode. This is
193 why in Section 3, we empirically relax this locality constraint and simply require that the weights are
194 linearly connectable in the loss landscape, as in the linear mode connectivity [24]. We empirically
195 verify later in Figure 1 that the approximation $f_{\text{WA}} \approx f_{\text{ENS}}$ remains valid even in this case.

3 DiWA: Diverse Weight Averaging

3.1 Motivation: weight averaging from different runs for more diversity

198 **Limitations of previous WA approaches**   Our analysis in Sections 2.4.1 and 2.4.2 showed that
199 the bias and the variance terms are mostly fixed by the distribution shifts at hand. In contrast, the
200 covariance term can be reduced by enforcing diversity across models (Section 2.4.3) obtained from
201 learning procedures $\{l_S^{(m)}\}_{m=1}^M$. Yet, previous methods [14, 29] only average weights obtained
202 along a single run. This corresponds to highly correlated procedures sharing the same initialization,
203 hyperparameters, batch ordering, data augmentations and noise, that only differ by the number of
204 training steps. The models are thus mostly similar: this does not leverage the full potential of WA.

205 **DiWA**   Our Diverse Weight Averaging approach seeks to reduce the OOD expected error in Equa-
206 tion (BVCL) by decreasing covariance across models: DiWA decorrelates the learning procedures
207 $\{l_S^{(m)}\}_{m=1}^M$. In this paper, our weights are obtained from $M \gg 1$ different runs, with diverse

---

Algorithm 1 DiWA Pseudo-code

Require: θ_0 pretrained encoder and initialized classifier; $\{h_m\}_{m=1}^H$ hyperparameter configurations.

Training: $\forall m = 1$ to H, $\theta_m \triangleq \text{FineTune}(\theta_0, h_m)$

Weight selection:

  Uniform: $\mathcal{M} = \{1, \cdots, H\}$.

  Restricted: Rank $\{\theta_m\}_{m=1}^H$ by decreasing $\text{ValAcc}(\theta_m)$.

  $\mathcal{M} \leftarrow \emptyset$

  for $m = 1$ to H **do**

    If $\text{ValAcc}(\theta_{\mathcal{M} \cup \{m\}}) \geq \text{ValAcc}(\theta_{\mathcal{M}})$

    $\mathcal{M} \leftarrow \mathcal{M} \cup \{m\}$

Inference: with $f(\cdot, \theta_{\mathcal{M}})$, where $\theta_{\mathcal{M}} = \sum_{m \in \mathcal{M}} \theta_m / |\mathcal{M}|$.

---

learning procedures: these have different hyperparameters (learning rate, weight decay and dropout probability), batch orders, data augmentations (e.g., random crops, horizontal flipping, color jitter, grayscaling), stochastic noise and number of training steps. Thus, the corresponding models are more diverse on domain T per [21] and reduce the impact of variance when M is large. However, this may break the locality requirement analyzed in Section 2.4.4 if the weights are too distant. Empirically, we show that DiWA works under two conditions: shared initialization and mild hyperparameter ranges.

3.2 Approach: shared initialization, mild hyperparameter search and weight selection

Shared initialization. The shared initialization condition follows [25]: when models are fine-tuned from a shared pretrained model, their weights can be connected along a linear path where error remains low [24]. Following standard practice on DomainBed [12], our encoder is pretrained on ImageNet [49]; this pretraining is key as it controls the bias (by defining the feature support mismatch, see Section 2.4.1) and variance (by defining the kernel K, see Appendix C.4.4). Regarding the classifier initialization, we test two methods. The first is the random initialization, which may distort the features [50]. The second is Linear Probing (LP) [50]: it first learns the classifier (while freezing the encoder) to serve as a shared initialization. Then, LP finetunes the encoder and the classifier together in the M subsequent runs; the locality term is smaller as weights remain closer (see [50]).

Mild hyperparameter search. As shown in Figure 5, extreme hyperparameter ranges lead to weights whose average may perform poorly. Indeed, weights obtained from extremely different hyperparameters may not be linearly connectable; they may belong to different regions of the loss landscape. In our experiments, we thus use the mild search space defined in Table 5, first introduced in SWAD [14]. These hyperparameter ranges induce diverse models that are averageable in weights.

Weight selection. The last step of our approach (summarized in Algorithm 1) is to choose which weights to average among those available. We explore two simple weight selection protocols, as in [28]. The first *uniform* equally averages all weights; it is practical but may underperform when some runs are detrimental. The second *restricted* (*greedy* in [28]) solves this drawback by restricting the number of selected weights: weights are ranked in decreasing order of validation accuracy and sequentially added only if they improve DiWA's validation accuracy.

In the following sections, we experimentally validate our theory. First, Section 4 confirms our findings on the OfficeHome dataset [51] where diversity shift dominates [19] (see Appendix E.2 for a similar analysis on PACS [52]). Then, Section 5 shows that DiWA is state of the art on DomainBed [12].

4 Empirical validation of our theoretical insights

We consider several collections of weights $\{\theta_m\}_{m=1}^M$ ($2 \leq M < 10$) trained on the "Clipart", "Product" and "Photo" domains from OfficeHome [51] with a shared random initialization and mild hyperparameter ranges. These weights are first indifferently sampled from a single run (every 50 batches) or from different runs. They are evaluated on "Art", the fourth domain from OfficeHome.

WA vs. ENS. Figure 1 validates Lemma 1 and that $f_{\text{WA}} \approx f_{\text{ENS}}$. More precisely, f_{WA} slightly but consistently improves f_{ENS}: we discuss this in Appendix D. Moreover, a larger M improves the

Figure 1: Each dot displays the accuracy (↑) of weight averaging (WA) vs. accuracy (↑) of prediction averaging (ENS) for M models.

Figure 2: Each dot displays the accuracy (↑) gain of WA over its members vs. the prediction diversity [46] (↑) for M models.

results; in accordance with Equation (BVCL), this motivates averaging as many weights as possible. In contrast, large M is computationally impractical for ENS at test time, requiring M forwards.

Diversity and accuracy. We validate in Figure 2 that f_{WA} benefits from diversity. Here, we measure diversity with the ratio-error [46], i.e., the ratio $N_{\text{diff}}/N_{\text{simul}}$ between the number of different errors N_{diff} and of simultaneous errors N_{simul} in test for a pair in $\{f(\cdot, \theta_m)\}_{m=1}^M$. A higher average over the $\binom{M}{2}$ pairs means that members are less likely to err on the same inputs. Specifically, the gain of $\text{Acc}(\theta_{\text{WA}})$ over the mean individual accuracy $\frac{1}{M}\sum_{m=1}^M \text{Acc}(\theta_m)$ increases with diversity. Moreover, this phenomenon intensifies for larger M: the linear regression's slope (i.e., the accuracy gain per unit of diversity) increases with M. This is consistent with the $(M-1)/M$ factor of $\text{cov}(x)$ in Equation (BVCL), as further highlighted in Appendix E.1.2. Finally, in Appendix E.1.1, we show that the conclusion also holds with CKAC [47], another established diversity measure.

Increasing diversity thus accuracy via different runs. Now we investigate the difference between sampling the weights from a single run or from different runs. Figure 3 *first* shows that diversity increases when weights come from different runs. *Second*, in Figure 4, this is reflected on the accuracies in OOD. Here, we rank by validation accuracy the 60 weights obtained (1) from 60 different runs and (2) along 1 well-performing run. We then consider the WA of the top M weights as M increases from 1 to 60. Both have initially the same performance and improve with M; yet, WA of weights from different runs gradually outperforms the single-run WA. *Finally*, Figure 5 shows that this holds only for mild hyperparameter ranges and with a shared initialization. Otherwise, when hyperparameter distributions are extreme (as defined in Table 5) or when classifiers are not similarly initialized, DiWA may perform worse than its members due to a violation of the locality condition. These experiments confirm that *diversity is key as long as the weights remain averageable*.

Figure 3: Frequencies of prediction diversities (↑) [46] across 2 weights obtained along a single run or from different runs.

Figure 4: WA accuracy (↑) as M increases, when the M weights are obtained along a single run or from different runs.

Figure 5: Each dot displays the accuracy (↑) gain of WA over its members vs. prediction diversity (↑) for $2 \leq M < 10$ models.

5 Experimental results on the DomainBed benchmark

5.1 Benchmark and experimental details

Datasets. In this section, we present our evaluation on DomainBed [12]. By imposing the code, the training procedures and the ResNet50 [53] architecture, DomainBed is arguably the fairest benchmark for OOD. It includes 5 multi-domain real-world datasets: PACS [52], VLCS [54], OfficeHome [51], TerraIncognita [55] and DomainNet [56]. [19] showed that *diversity shift dominates in these datasets*. Each domain is successively considered as the target T while other domains are merged into the source S. The validation dataset is sampled from S, i.e., we follow DomainBed's training-domain model selection. The experimental setup is further described in Appendix F.1. Our code will be available anonymously at https://anonymous.4open.science/r/DiWA-anonymous-9884/.

Baselines. ERM is the standard Empirical Risk Minimization. Coral [10] is the best approach based on domain invariance. SWAD (Stochastic Weight Averaging Densely) [14] and MA (Moving Average) [29] average weights along one training trajectory but differ in their weight selection strategy. SWAD [14] is the current state of the art (SoTA) thanks to it "overfit-aware" strategy, yet at the cost of three additional hyperparameters (a patient parameter, an overfitting patient parameter and a tolerance rate) tuned per dataset. In contrast, MA [29] is easy to implement as it simply combines all checkpoints uniformly starting from batch 100 until the end of training. For the sake of fairness, we only report methods with no inference overhead; we discuss approaches like EoA [29] in Appendix D.

Our runs. ERM and DiWA share the same training protocol in DomainBed: yet, instead of keeping only one run from the grid-search, DiWA leverages M runs. In practice, we sample 20 configurations from the hyperparameter distributions detailed in Table 5 and report the mean and standard deviation across 3 data splits. For each run, we select the weights of the epoch with the highest validation accuracy. ERM and MA select the model with highest validation accuracy across the 20 runs, following standard practice on DomainBed. DiWA-restricted selects $1 \leq M \leq 20$ weights with Algorithm 1 while DiWA-uniform averages all $M = 20$ weights. DiWA† averages uniformly the $M = 3 \times 20 = 60$ weights from all 3 data splits. DiWA† benefits from larger M (without additional inference cost) and from data diversity (see Appendix E.1.3). However, we cannot report standard deviations for DiWA† for computational reasons. Moreover, DiWA† cannot leverage the restricted weight selection, as the validation is not shared across all 60 weights that have different data splits.

5.2 Full results on DomainBed

We report our results in Table 1, detailed per domain in Appendix F.2. With a randomly initialized classifier, DiWA†-uniform is the best on PACS, VLCS and OfficeHome: DiWA-uniform is the second best on PACS and OfficeHome. On TerraIncognita and DomainNet, DiWA is penalized by some bad runs, filtered in DiWA-restricted which improves results on these datasets. Classifier initialization with linear probing (LP) [50] improves all methods on OfficeHome, TerraIncognita and DomainNet. On these datasets, DiWA† increases previous SoTAs by 2.2, 1.6 and 1.2 points respectively. After averaging, DiWA† with LP improves SWAD by 1.1 points and *establishes a new SoTA of* 68.0%.

Table 1: **Accuracy** ($\%$, $\uparrow$) **on DomainBed with ResNet50** (best in **bold** and second best underlined).

	Algorithm	Weight selection	Init	PACS	VLCS	OfficeHome	TerraInc	DomainNet	Avg
	ERM	N/A		85.5 ± 0.2	77.5 ± 0.4	66.5 ± 0.3	46.1 ± 1.8	40.9 ± 0.1	63.3
	Coral [10]	N/A	Random	86.2 ± 0.3	78.8 ± 0.6	68.7 ± 0.3	47.6 ± 1.0	41.5 ± 0.1	64.6
	SWAD [14]	Overfit-aware		88.1 ± 0.1	79.1 ± 0.1	70.6 ± 0.2	50.0 ± 0.3	46.5 ± 0.1	66.9
	MA [29]	Uniform		87.5 ± 0.2	78.2 ± 0.2	70.6 ± 0.1	50.3 ± 0.5	46.0 ± 0.1	66.5
Our runs	ERM	N/A		85.5 ± 0.5	77.6 ± 0.2	67.4 ± 0.6	48.3 ± 0.8	44.1 ± 0.1	64.6
	MA [29]	Uniform		87.9 ± 0.1	78.4 ± 0.1	70.3 ± 0.1	49.9 ± 0.2	46.4 ± 0.1	66.6
	DiWA	Restricted: $M \leq 20$	Random	87.9 ± 0.2	79.2 ± 0.1	70.5 ± 0.1	50.5 ± 0.5	46.7 ± 0.1	67.0
	DiWA	Uniform: $M = 20$		88.8 ± 0.4	79.1 ± 0.2	71.0 ± 0.1	48.9 ± 0.5	46.1 ± 0.1	66.8
	DiWA†	Uniform: $M = 60$		**89.0**	**79.4**	71.6	49.0	46.3	67.1
	ERM	N/A		85.9 ± 0.6	78.1 ± 0.5	69.4 ± 0.2	50.4 ± 1.8	44.3 ± 0.2	65.6
	MA [29]	Uniform		87.8 ± 0.3	78.5 ± 0.4	71.5 ± 0.3	51.4 ± 0.6	46.6 ± 0.0	67.1
	DiWA	Restricted: $M \leq 20$	LP [50]	88.0 ± 0.3	78.5 ± 0.1	71.5 ± 0.2	51.6 ± 0.9	**47.7 ± 0.1**	67.5
	DiWA	Uniform: $M = 20$		88.7 ± 0.2	78.4 ± 0.2	72.1 ± 0.2	51.4 ± 0.6	47.4 ± 0.2	67.6
	DiWA†	Uniform: $M = 60$		**89.0**	78.6	**72.8**	**51.9**	**47.7**	**68.0**

DiWA with different objectives. So far we used ERM that does not leverage the domain information. Table 2 shows that DiWA-uniform benefits from averaging weights trained with Interdomain Mixup [57] and Coral [10]: accuracy gradually improves as we add more objectives. Indeed, as highlighted in Appendix E.1.3, DiWA benefits from the increased diversity brought by the various objectives. This also suggests a new kind of linear connectivity across models despite being trained with different objectives; the complete analysis of this is left for future research.

Table 2: **Accuracy** $(\%, \uparrow)$ **on OfficeHome** domain "Art" with various objectives.

Algorithm	No WA	MA	DiWA	DiWA†
ERM	62.9 ± 1.3	$\underline{65.0} \pm 0.2$	67.3 ± 0.2	67.7
Mixup	$\underline{63.1} \pm 0.7$	$\mathbf{66.2} \pm 0.3$	67.8 ± 0.6	68.4
Coral	$\mathbf{64.4} \pm 0.4$	64.4 ± 0.4	67.7 ± 0.2	68.2
ERM/Mixup	N/A	N/A	67.9 ± 0.7	$\underline{68.9}$
ERM/Coral	N/A	N/A	$\underline{68.1} \pm 0.3$	68.7
ERM/Mixup/Coral	N/A	N/A	$\mathbf{68.4} \pm 0.4$	**69.1**

5.3 Limitations of DiWA

Despite this success, DiWA has some limitations. *First*, DiWA cannot benefit from additional diversity that would break the linear connectivity between weights — as discussed in Appendix D. *Second*, DiWA (like all WA approaches) can tackle diversity shift but not correlation shift: this property is explained for the first time in Section 2.4 and illustrated in Appendix G on ColoredMNIST.

6 Related work

Generalization and ensemble. To generalize under distribution shifts, invariant approaches [8, 9, 11, 10, 58, 59] try to detect the causal mechanism rather than memorize correlations: yet, they do not outperform ERM on various benchmarks [12, 19, 60]. In contrast, ensembling of deep networks [15, 61, 62] consistently increases robustness [16] and was successfully applied to domain generalization [29, 63, 64, 65, 66, 67]. As highlighted in [18] (whose analysis underlies our Equation (BVCL)), ensembling works due to the diversity among its members. This diversity comes primarily from the randomness of the learning procedure [15] and can be increased with different hyperparameters [68], data [69, 70, 71], augmentations [72, 73] or with regularizations [48, 66, 67, 74, 75].

Weight averaging. Recent works combine models in weights rather than in predictions. They [13, 76, 77, 78, 79] perform WA on checkpoints collected along a single run: compared to ensembling [15], this was shown suboptimal in IID [17] but successful in OOD [14, 29]. Cyclical learning rates [13], introduced to visit multiple minimas, perform worse on OOD than constant learning rates [14]. Following the linear mode connectivity [24, 80] and the fact that many independent models can be connected [81], a second group of works (including DiWA) average weights with fewer constraints [26, 27, 28, 82, 83, 84]. The recent "Model soups" by Wortsman *et al.* [28] developed a WA algorithm similar to Algorithm 1. However the task, the theoretical analysis and most importantly the objectives of these two works are fundamentally different. Regarding the task, we focused on OOD generalization and the multi-domain DomainBed benchmark. Theoretically, we explain why WA succeeds in OOD under diversity shift. The bias/correlation shift, variance/diversity shift and diversity-based findings are novel; they are confirmed empirically. Regarding the motivations, DiWA aims at combining weights from diverse models: our work may be analyzed as a general framework to average in weights models which can be obtained in various ways, as traditionally done in ensembling. In contrast, [28] challenges the standard model selection after a grid search. Thus, DiWA and [28] are theoretically complementary and applied successfully in different contexts.

7 Conclusion

In this paper, we propose a new explanation for the success of WA in OOD by leveraging its ensembling nature. Our analysis is based on a new bias-variance-covariance-locality decomposition for WA, where we theoretically relate bias to correlation shift and variance to diversity shift. It also shows that diversity is key to improve generalization. This motivates our DiWA approach that averages in weights models trained independently. DiWA improves the state of the art on DomainBed, the reference benchmark for OOD generalization. Critically, DiWA has no additional inference cost — removing a key limitation of standard ensembling. Our work may encourage the community to further create diverse learning procedures and objectives — whose models may be averaged in weights.

References

[1] John R. Zech, Marcus A. Badgeley, Manway Liu, Anthony B. Costa, Joseph J. Titano, and Eric Karl Oermann. Variable generalization performance of a deep learning model to detect pneumonia in chest radiographs: A cross-sectional study. *PLOS Medicine*, 2018. (pp. 1 and 16)

[2] Alex J DeGrave, Joseph D Janizek, and Su-In Lee. Ai for radiographic covid-19 detection selects shortcuts over signal. *Nature Machine Intelligence*, 2021. (pp. 1 and 16)

[3] Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. In *ICLR*, 2019. (p. 1)

[4] Harshay Shah, Kaustav Tamuly, Aditi Raghunathan, Prateek Jain, and Praneeth Netrapalli. The pitfalls of simplicity bias in neural networks. In *NeurIPS*, 2020. (p. 1)

[5] Alexander D'Amour, Katherine Heller, Dan Moldovan, Ben Adlam, Babak Alipanahi, Alex Beutel, Christina Chen, Jonathan Deaton, Jacob Eisenstein, Matthew D Hoffman, et al. Underspecification presents challenges for credibility in modern machine learning. *JMLR*, 2020. (pp. 1 and 4)

[6] Krikamol Muandet, David Balduzzi, and Bernhard Schölkopf. Domain generalization via invariant feature representation. In *ICML*, 2013. (p. 1)

[7] Jonas Peters, Peter Bühlmann, and Nicolai Meinshausen. Causal inference by using invariant prediction: identification and confidence intervals. *JSTOR*, 2016. (p. 1)

[8] Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint*, 2019. (pp. 1, 4, 9, and 33)

[9] David Krueger, Ethan Caballero, Joern-Henrik Jacobsen, Amy Zhang, Jonathan Binas, Dinghuai Zhang, Remi Le Priol, and Aaron Courville. Out-of-distribution generalization via risk extrapolation (rex). In *ICML*, 2021. (pp. 1 and 9)

[10] Baochen Sun, Jiashi Feng, and Kate Saenko. Return of frustratingly easy domain adaptation. In *AAAI*, 2016. (pp. 1, 8, 9, 28, 30, 31, 32, and 33)

[11] Alexandre Rame, Corentin Dancette, and Matthieu Cord. Fishr: Invariant gradient variances for out-of-distribution generalization. In *ICML*, 2022. (pp. 1, 9, and 33)

[12] Ishaan Gulrajani and David Lopez-Paz. In search of lost domain generalization. In *ICLR*, 2021. (pp. 1, 2, 3, 6, 8, 9, 15, 16, 17, 26, 30, and 33)

[13] Pavel Izmailov, Dmitrii Podoprikhin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. Averaging weights leads to wider optima and better generalization. In *UAI*, 2018. (pp. 1, 2, 3, 9, and 18)

[14] Junbum Cha, Sanghyuk Chun, Kyungjae Lee, Han-Cheol Cho, Seunghyun Park, Yunsung Lee, and Sungrae Park. Swad: Domain generalization by seeking flat minima. In *NeurIPS*, 2021. (pp. 1, 3, 5, 6, 8, 9, 17, 18, 19, 22, 30, 31, and 32)

[15] Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *NeurIPS*, 2017. (pp. 1, 3, 5, 9, 18, 26, and 27)

[16] Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In *NeurIPS*, 2019. (pp. 1 and 9)

[17] Arsenii Ashukha, Alexander Lyzhov, Dmitry Molchanov, and Dmitry Vetrov. Pitfalls of in-domain uncertainty estimation and ensembling in deep learning. In *ICLR*, 2020. (pp. 1 and 9)

[18] Naonori Ueda and Ryohei Nakano. Generalization error of ensemble estimators. In *ICNN*, 1996. (pp. 1, 3, 9, and 19)

[19] Nanyang Ye, Kaican Li, Lanqing Hong, Haoyue Bai, Yiting Chen, Fengwei Zhou, and Zhenguo Li. Ood-bench: Benchmarking and understanding out-of-distribution generalization datasets and algorithms. *arXiv preprint*, 2021. (pp. 1, 2, 4, 5, 6, 8, 9, 21, 30, and 33)

[20] Stanislav Fort, Huiyi Hu, and Balaji Lakshminarayanan. Deep ensembles: A loss landscape perspective. *arXiv preprint*, 2019. (p. 2)

[21] Raphael Gontijo-Lopes, Yann Dauphin, and Ekin Dogus Cubuk. No one representation to rule them all: Overlapping features of training methods. In *ICLR*, 2022. (pp. 2, 6, and 28)

[22] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015. (p. 2)

[23] Abien Fred Agarap. Deep learning using rectified linear units (relu). *arXiv preprint*, 2018. (p. 2)

[24] Jonathan Frankle, Gintare Karolina Dziugaite, Daniel M. Roy, and Michael Carbin. Linear mode connectivity and the lottery ticket hypothesis. In *ICML*, 2020. (pp. 2, 5, 6, and 9)

[25] Behnam Neyshabur, Hanie Sedghi, and Chiyuan Zhang. What is being transferred in transfer learning? In *NeurIPS*, 2020. (pp. 2, 6, and 27)

[26] Mitchell Wortsman, Gabriel Ilharco, Jong Wook Kim, Mike Li, Hanna Hajishirzi, Ali Farhadi, Hongseok Namkoong, and Ludwig Schmidt. Robust fine-tuning of zero-shot models. In *CVPR*, 2022. (pp. 2, 9, and 27)

[27] Michael Matena and Colin Raffel. Merging models with fisher-weighted averaging. *arXiv preprint*, 2021. (pp. 2 and 9)

[28] Mitchell Wortsman, Gabriel Ilharco, Samir Yitzhak Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S. Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, and Ludwig Schmidt. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. *arXiv preprint*, 2022. (pp. 2, 3, 6, 9, 18, and 26)

[29] Devansh Arpit, Huan Wang, Yingbo Zhou, and Caiming Xiong. Ensemble of averages: Improving model selection and boosting performance in domain generalization. *arXiv preprint*, 2021. (pp. 3, 5, 8, 9, 18, 19, 22, 27, 30, 31, 32, and 33)

[30] Pierre Foret, Ariel Kleiner, Hossein Mobahi, and Behnam Neyshabur. Sharpness-aware minimization for efficiently improving generalization. In *ICLR*, 2021. (pp. 3 and 18)

[31] Jean Kaddour, Linqing Liu, Ricardo Silva, and Matt J. Kusner. Questions for flat-minima optimization of modern neural networks. *arXiv preprint*, 2022. (pp. 3 and 18)

[32] Ron Kohavi, David H Wolpert, et al. Bias plus variance decomposition for zero-one loss functions. In *ICML*, 1996. (pp. 3, 20, and 26)

[33] Pedro Domingos. A unified bias-variance decomposition. In *ICML*, 2000. (p. 3)

[34] Thomas G Dietterich. Ensemble methods in machine learning. In *MCS*, 2000. (p. 3)

[35] Gavin Brown, Jeremy Wyatt, and Ping Sun. Between two extremes: Examining decompositions of the ensemble objective function. In *MCS*, 2005. (pp. 3 and 19)

[36] Yangjun Ruan, Yann Dubois, and Chris J. Maddison. Optimal representations for covariate shift. In *ICLR*, 2022. (pp. 4, 21, and 26)

[37] Arthur Jacot, Franck Gabriel, and Clement Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In *NeurIPS*, 2018. (pp. 4, 24, and 26)

[38] Amit Daniely. Sgd learns the conjugate kernel class of the network. In *NeurIPS*, 2017. (p. 4)

[39] Jaehoon Lee, Yasaman Bahri, Roman Novak, Samuel S Schoenholz, Jeffrey Pennington, and Jascha Sohl-Dickstein. Deep neural networks as gaussian processes. In *ICLR*, 2017. (pp. 4 and 24)

[40] Julien Ah-Pine. Normalized kernels as similarity indices. In *PAKDD*, 2010. (pp. 4 and 24)

[41] Benyamin Ghojogh, Ali Ghodsi, Fakhri Karray, and Mark Crowley. Reproducing kernel hilbert space, mercer's theorem, eigenfunctions, nystrom method, and use of kernels in machine learning: Tutorial and survey. *arXiv preprint*, 2021. (pp. 4 and 24)

[42] Jason Rennie. How to normalize a kernel matrix. *MIT Computer Science - Artificial Intelligence Lab Tech Rep*, 2005. (pp. 4 and 24)

[43] Hangfeng He and Weijie Su. The local elasticity of neural networks. In *ICLR*, 2020. (pp. 4 and 24)

[44] Mariia Seleznova and Gitta Kutyniok. Neural tangent kernel beyond the infinite-width limit: Effects of depth and initialization. *arXiv preprint*, 2022. (pp. 4 and 24)

[45] Ludmila I Kuncheva and Christopher J Whitaker. Measures of diversity in classifier ensembles and their relationship with the ensemble accuracy. *Machine learning*, 2003. (p. 5)

[46] Matti Aksela. Comparison of classifier selection methods for improving committee perfor-mance. In *MCS*, 2003. (pp. 5, 7, 18, 27, and 29)

[47] Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey E. Hinton. Similarity of neural network representations revisited. In *ICML*, 2019. (pp. 5, 7, 27, and 29)

[48] Alexandre Rame and Matthieu Cord. Dice: Diversity in deep ensembles via conditional redundancy adversarial estimation. In *ICLR*, 2021. (pp. 5, 9, and 27)

[49] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NeurIPS*, 2012. (pp. 6 and 26)

[50] Ananya Kumar, Aditi Raghunathan, Robbie Matthew Jones, Tengyu Ma, and Percy Liang. Fine-tuning can distort pretrained features and underperform out-of-distribution. In *ICLR*, 2022. (pp. 6, 8, 26, 30, 31, and 32)

[51] Hemanth Venkateswara, Jose Eusebio, Shayok Chakraborty, and Sethuraman Panchanathan. Deep hashing network for unsupervised domain adaptation. In *CVPR*, 2017. (pp. 6, 8, and 30)

[52] Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M Hospedales. Deeper, broader and artier domain generalization. In *ICCV*, 2017. (pp. 6, 8, and 30)

[53] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016. (pp. 8 and 30)

[54] Chen Fang, Ye Xu, and Daniel N Rockmore. Unbiased metric learning: On the utilization of multiple datasets and web images for softening bias. In *ICCV*, 2013. (pp. 8 and 30)

[55] Sara Beery, Grant Van Horn, and Pietro Perona. Recognition in terra incognita. In *ECCV*, 2018. (pp. 8 and 30)

[56] Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *ICCV*, 2019. (pp. 8, 30, and 33)

[57] Shen Yan, Huan Song, Nanxiang Li, Lincan Zou, and Liu Ren. Improve unsupervised domain adaptation with mixup training. *arXiv preprint*, 2020. (pp. 9, 28, and 30)

[58] Shiori Sagawa, Pang Wei Koh, Tatsunori B. Hashimoto, and Percy Liang. Distributionally robust neural networks. In *ICLR*, 2020. (pp. 9 and 16)

[59] Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *JMLR*, 2016. (p. 9)

[60] Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanas Phillips, Irena Gao, Tony Lee, Etienne David, Ian Stavness, Wei Guo, Berton Earnshaw, Imran Haque, Sara M Beery, Jure Leskovec, Anshul Kundaje, Emma Pierson, Sergey Levine, Chelsea Finn, and Percy Liang. Wilds: A benchmark of in-the-wild distribution shifts. In *ICML*, 2021. (p. 9)

[61] Lars Kai Hansen and Peter Salamon. Neural network ensembles. *IEEE transactions on pattern analysis and machine intelligence*, 1990. (p. 9)

[62] Anders Krogh and Jesper Vedelsby. Neural network ensembles, cross validation, and active learning. In *NeurIPS*, 1995. (p. 9)

[63] Kowshik Thopalli, Sameeksha Katoch, Jayaraman J. Thiagarajan, Pavan K. Turaga, and Andreas Spanias. Multi-domain ensembles for domain generalization. In *NeurIPS Workshop*, 2021. (p. 9)

[64] Yusuf Mesbah, Youssef Youssry Ibrahim, and Adil Mehood Khan. Domain generalization using ensemble learning. In *ISWA*, 2022. (p. 9)

[65] Ziyue Li, Kan Ren, Xinyang Jiang, Bo Li, Haipeng Zhang, and Dongsheng Li. Domain generalization using pretrained models without fine-tuning. *arXiv preprint*, 2022. (p. 9)

[66] Yoonho Lee, Huaxiu Yao, and Chelsea Finn. Diversify and disambiguate: Learning from underspecified data. *arXiv preprint*, 2022. (p. 9)

[67] Matteo Pagliardini, Martin Jaggi, François Fleuret, and Sai Praneeth Karimireddy. Agree to disagree: Diversity through disagreement for better transferability. *arXiv preprint*, 2022. (p. 9)

[68] Florian Wenzel, Jasper Snoek, Dustin Tran, and Rodolphe Jenatton. Hyperparameter ensembles for robustness and uncertainty quantification. In *NeurIPS*, 2020. (p. 9)

[69] Leo Breiman. Bagging predictors. *Machine learning*, 1996. (pp. 9 and 28)

[70] Jeremy Nixon, Balaji Lakshminarayanan, and Dustin Tran. Why are bootstrapped deep ensembles not better? In *NeurIPS Workshop*, 2020. (p. 9)

[71] Teresa Yeo, Oguzhan Fatih Kar, and Amir Roshan Zamir. Robustness via cross-domain ensembles. In *ICCV*, 2021. (p. 9)

[72] Yeming Wen, Ghassen Jerfel, Rafael Muller, Michael W Dusenberry, Jasper Snoek, Balaji Lakshminarayanan, and Dustin Tran. Combining ensembles and data augmentation can harm your calibration. In *ICLR*, 2021. (p. 9)

[73] Alexandre Rame, Remy Sun, and Matthieu Cord. Mixmo: Mixing multiple inputs for multiple outputs via deep subnetworks. In *ICCV*, 2021. (pp. 9 and 27)

[74] Tianyu Pang, Kun Xu, Chao Du, Ning Chen, and Jun Zhu. Improving adversarial robustness via promoting ensemble diversity. In *ICML*, 2019. (p. 9)

[75] Damien Teney, Ehsan Abbasnejad, Simon Lucey, and Anton van den Hengel. Evading the simplicity bias: Training a diverse set of models discovers solutions with superior ood generalization. *arXiv preprint*, 2021. (p. 9)

[76] Felix Draxler, Kambis Veschgini, Manfred Salmhofer, and Fred Hamprecht. Essentially no barriers in neural network energy landscape. In *ICML*, 2018. (p. 9)

[77] Hao Guo, Jiyong Jin, and Bin Liu. Stochastic weight averaging revisited. *arXiv preprint*, 2022. (p. 9)

[78] Wesley J Maddox, Pavel Izmailov, Timur Garipov, Dmitry P Vetrov, and Andrew Gordon Wilson. A simple baseline for bayesian uncertainty in deep learning. In *NeurIPS*, 2019. (p. 9)

[79] Michael Zhang, James Lucas, Jimmy Ba, and Geoffrey E Hinton. Lookahead optimizer: k steps forward, 1 step back. *NeurIPS*, 32, 2019. (p. 9)

[80] Vaishnavh Nagarajan and J Zico Kolter. Uniform convergence may be unable to explain generalization in deep learning. *NeurIPS*, 2019. (p. 9)

[81] Gregory Benton, Wesley Maddox, Sanae Lotfi, and Andrew Gordon Gordon Wilson. Loss surface simplexes for mode connecting volumes and fast ensembling. In *ICML*, 2021. (p. 9)

[82] Vipul Gupta, Santiago Akle Serrano, and Dennis DeCoste. Stochastic weight averaging in parallel: Large-batch training that generalizes well. In *ICLR*, 2020. (p. 9)

[83] Leshem Choshen, Elad Venezian, Noam Slonim, and Yoav Katz. Fusing finetuned models for better pretraining. *arXiv preprint*, 2022. (p. 9)

[84] Mitchell Wortsman, Maxwell Horton, Carlos Guestrin, Ali Farhadi, and Mohammad Rastegari. Learning neural network subspaces. *ICML*, 2021. (p. 9)

[85] Su Lin Blodgett, Lisa Green, and Brendan O'Connor. Demographic dialectal variation in social media: A case study of african-american english. In *EMNLP*, 2016. (p. 16)

[86] Solon Barocas and Andrew D Selbst. Big data's disparate impact. *Calif. L. Rev.*, 2016. (p. 16)

[87] Laurent Dinh, Razvan Pascanu, Samy Bengio, and Yoshua Bengio. Sharp minima can generalize for deep nets. In *ICML*, 2017. (p. 17)

[88] Henning Petzka, Michael Kamp, Linara Adilova, Cristian Sminchisescu, and Mario Boley. Relative flatness and generalization. In *NeurIPS*, 2021. (p. 17)

[89] Zhewei Yao, Amir Gholami, Kurt Keutzer, and Michael W Mahoney. Pyhessian: Neural networks through the lens of the hessian. In *Big Data*, 2020. (p. 17)

[90] Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint*, 2022. (p. 18)

[91] Carl Edward Rasmussen. Gaussian processes in machine learning. In *Summer school on machine learning*, 2003. (p. 23)

[92] Fernando Pérez-Cruz, Steven Van Vaerenbergh, Juan José Murillo-Fuentes, Miguel Lázaro-Gredilla, and Ignacio Santamaria. Gaussian processes for nonlinear signal processing: An overview of recent advances. *EEE Signal Process. Mag.*, 2013. (p. 23)

[93] Greg Yang and Hadi Salman. A fine-grained spectral perspective on neural networks. *arXiv preprint*, 2019. (p. 24)

[94] Damien Brain and Geoffrey I Webb. On the effect of data set size on bias and variance in classification learning. In *AKAW*, 1999. (p. 24)

[95] Arthur Gretton, Karsten M. Borgwardt, Malte J. Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *Journal of Machine Learning Research*, 13(25):723–773, 2012. (p. 25)

[96] Jan R Magnus and Heinz Neudecker. *Matrix differential calculus with applications in statistics and econometrics*. John Wiley & Sons, 2019. (p. 25)

[97] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *ICML*, 2021. (p. 26)

[98] Saurabh Singh, Derek Hoiem, and David Forsyth. Swapout: Learning an ensemble of deep architectures. In *NeurIPS*, 2016. (p. 27)

[99] Bradley Efron. Bootstrap methods: another look at the jackknife. In *Breakthroughs in statistics*. 1992. (p. 28)

[100] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015. (p. 30)

[101] Yann LeCun, Corinna Cortes, and Chris Burges. Mnist handwritten digit database, 2010. (p. 33)